






Test Graphs of Conducted Output Power Spectral Density for band 5.725-5.85 GHz


















































Report No.: AGC00408240808FR04

Page 64 of 109

10. Conducted Band Edge and Out-of-Band Emissions

10.1 Provisions Applicable

	Applicable to	Limit			
Restricted bands	789033 D02 General UNII Test	Field strength at 3m (dBuV/m)			
recentated barrae	Procedures New Rules v02r01	PK: 74	AV: 54		
Out of the restricted bands	Applicable to	EIRP Limit (dBm/MHz)	Equivalent field Strength at 3m (dBuV/m)		
	FCC 15.407(b)(1)				
	15.407(b)(2)	PK: -27	PK: 68.2		
	15.407(b)(3)				
	15.407(b)(4)	See Note 2			


Note 1: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

E =
$$\frac{1000000 \quad \sqrt{30 P}}{3}$$
 µV/m, where P is the eirp (Watts).

Note 2: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.


10.2 Measurement Procedure


- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Set the Span = wide enough to capture the peak level of the in-band emission and all spurious emissions from the lowest frequency generated in the EUT up through the 10th harmonic.
- 3. RBW = 1MHz; VBW= 3MHz; Sweep = auto; Detector function = Peak. (Test frequency below 1GHz)
- 4. RBW = 1 MHz; VBW= 3 MHz; Sweep = auto; Detector function = Peak. (Test frequency Above 1GHz)
- 5. Set SPA Trace 1 Max hold, then View.
- 6. Antenna gain and path loss have been compensated to the Correction factor.
- 7. Mark the maximum useless stray point and compare it with the limit value to record the result.





10.3 Measurement Setup (Block Diagram of Configuration)










10.4 Measurement Results

Test Graphs of Spurious Emissions outside of the 5.15-5.25 GHz band




















Test Graph 802.11a ANT1 5240 6Mbps Frequency Band 2


#VBW 3.0 MHz


Span 4.100 GHz Sweep 8.000 ms (30000 pts)


Center 3.050 GHz #Res BW 1.0 MHz












Freq Offset 0 Hz

Scale Type

Span 4.100 GHz Sweep 8.000 ms (30000 pts)






Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Test Graph 802.11n40 ANT1 5190 MCS0 Frequency Band 2

#VBW 3.0 MHz


Center 3.050 GHz #Res BW 1.0 MHz




















Test Graph 802.11n40 ANT1 5230 MCS0 Frequency Band 2












<u>Auto</u>

Span 4.100 GHz Sweep 8.000 ms (30000 pts) Man

Freq Offset 0 Hz

Scale Type






Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Test_Graph_802.11ac80_ANT1_5210_MCS0_Frequency Band 2

#VBW 3.0 MHz


Center 3.050 GHz #Res BW 1.0 MHz















Test Graphs of Spurious Emissions outside of the 5.725-5.85 GHz band




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Test_Graph_802.11a_ANT1_5745_6Mbps_Frequency Band2




















Test Graph 802.11a ANT1 5825 6Mbps Frequency Band2



















Test Graph 802.11n40 ANT1 5755 MCS0 Frequency Band2

















Test Graph 802.11n40 ANT1 5795 MCS0 Frequency Band2

#VBW 3.0 MHz

Span 4.650 GHz Sweep 8.000 ms (30000 pts)

Log

Center 3.325 GHz #Res BW 1.0 MHz



Stop Freq 27.000000000 GHz

CF Step 2.107500000 GHz

Freq Offset 0 Hz

Scale Type


Man

<u>Auto</u>

Log

Span 21.08 GHz Sweep 54.00 ms (30000 pts)






Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Test Graph 802.11n40 ANT1 5795 MCS0 Frequency Band4

#VBW 3.0 MHz

Center 16.46 GHz #Res BW 1.0 MHz








Test_Graph_802.11ac80_ANT1_5775_MCS0_Frequency Band2

#VBW 3.0 MHz


Span 4.650 GHz Sweep 8.000 ms (30000 pts)

Log

Center 3.325 GHz #Res BW 1.0 MHz











11. Radiated Spurious Emission

11.1 Measurement Limit

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

NOTE:

- 1. The lower limit shall apply at the transition frequencies.
- 2. Emission level (dBuV/m) = 20 log Emission level (uV/m).

3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

	Applicable to	Limit			
Restricted	789033 D02 General UNII Test	Field strength at 3m (dBuV/m)			
bands	Procedures New Rules v02r01	PK: 74	AV: 54		
	Applicable to	EIRP Limit (dBm/MHz)	Equivalent field Strength at 3m (dBuV/m)		
Out of the	FCC 15.407(b)(1)				
restricted bands	15.407(b)(2)	PK: -27	PK: 68.2		
	15.407(b)(3)				
	15.407(b)(4)		See Note 2		

Note 1: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

E =
$$\frac{1000000 - \sqrt{30 P}}{3}$$
 µV/m, where P is the eirp (Watts).

Note 2: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.



Report No.: AGC00408240808FR04

Page 87 of 109

11.2 Measurement Procedure

- The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.



Report No.: AGC00408240808FR04

Page 88 of 109

The following table is the setting of spectrum analyzer and receiver.

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04.Section G) Unwanted emissions measurement.

♦ Procedure for Unwanted Emissions Measurements Below 1000MHz:

- RBW = 120 kHz
- VBW = 300 kHz
- Detector = Peak
- Trace mode = max hold

♦ Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz:


- RBW = 1 MHz
- VBW ≥ 3 MHz
- Detector = Peak
- Sweep time = auto
- Trace mode = max hold

Procedures for Average Unwanted Emissions Measurements Above 1000MHz:

- RBW = 1 MHz
- VBW = 10 Hz, when duty cycle is no less than 98 percent.
- VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

Procedures for Average Unwanted Emissions Measurements Above 1000MHz:


- RBW = 1 MHz
- VBW = 3 MHz Detector = power averaging (rms), set span/(# of points in sweep) ≥ RBW/2.
- Averaging type = power averaging (RMS)
- The correction factor shall be offset is 10 $\log (1/x)$, where x is the duty cycle.






11.3 Measurement Setup (Block Diagram of Configuration)


Radiated Emission Test Setup 9kHz-30MHz



Radiated Emission Test Setup 30MHz-1000MHz



Radiated Emission Test Setup Above 1000MHz



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



11.4 Measurement Result

Radiated Emission Below 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.

Radiated Emission Test Results at 30MHz-1GHz

EUT Nar	me Smart PAD Tablet			Model Name		AGM_PAD_T2		
Tempera	nture	23.2°C	23.2°C			umidity	57.8%	
Pressur	e	960hPa			Test Voltag	е	DC 3.85\	by battery
Test Mo	de	802.11n(20	MHz)_518	30MHz	Antenna		Horizontal	
	130			FCC Part 150)		1	
	120							
	110							
	90							
	80							
[m//\r	70							
Level[dBµV/m]	60							
Leg-	50							* 6
	30	* ²	3			4	State Market Space and State Space and Space a	Mary Mary Comme
	20	V 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	~~~~		munder warment	hayen you want bear		
	10							
	-10							
	30M		100M	Frequency[Hz	rl			1G
	— QP Limit * QP Detector	Horizontal PK		ricquericy[iiz	-1			
NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	33.88	33.86	12.12	40.00	6.14	100	10	Horizontal
2	51.34	34.02	15.58	40.00	5.98	100	60	Horizontal
3	98.87	29.13	16.73	43.50	14.37	100	50	Horizontal
	463.59	32.85	23.86	46.00	13.15	100	20	Horizontal
4	040.07	34.92	25.14	46.00	11.08	100	30	Horizontal
<u>4</u> 5	612.97	U U —						

Result: Pass



EUT Name		Smart PAI	Smart PAD Tablet		Model Nan	ne	AGM_PAD_T2	
Temperature		23.2°C		Relative Humidity		57.8%		
Pressure		960hPa			Test Voltag	де	DC 3.85V by battery	
Test Mode		802.11n(2	0MHz)_51	80MHz	Antenna		Vertical	
13	0			FCC Part 15C				
12 11 10 9 8 8 [[W//Vigp]] 9 6 6 5 5 4 3 2 1	000000000000000000000000000000000000000	— Vertical PK	100M	Frequency[Hz		and the second	5	1G
NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	32.91	30.87	12.41	40.00	9.13	100	80	Vertical
2	62.01	34.86	17.23	40.00	5.14	100	50	Vertical
3	98.87	34.53	16.73	43.50	8.97	100	0	Vertical

43.50

46.00

46.00

9.94

10.65

5.67

100

100

100

300

60

40

Vertical

Vertical

Vertical

Result: Pass

4

5

6

157.07

617.82

857.41

Note:

1. Factor=Antenna Factor + Cable loss, Margin= Limit-Measurement.

33.56

35.35

40.33

2. All test modes had been pre-tested, Refer to Chapter 5 of the report for details.

17.62

25.68

29.93



Report No.: AGC00408240808FR04

Page 92 of 109

Radiated Emissions Test Results Above 1GHz

EUT Name	Smart PAD Tablet	Model Name	AGM_PAD_T2
Temperature	23.2°C Relative Humidity		57.8%
Pressure	essure 960hPa Test Vol		DC 3.85V by battery
Test Mode	802.11n20_5180MHz	Antenna	Horizontal/Vertical

Radiated Emission Above 1GHz-Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value - Type	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре	
10360.000	48.14	9.14	57.28	68.20	-10.92	peak	
15540.000	50.21	10.22	60.43	74.00	-13.57	peak	
15540.000	32.05	10.22	42.27	54.00	-11.73	AVG	
Remark:							

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Radiated Emission Above 1GHz-Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value - Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре
10360.000	48.63	9.14	57.77	68.20	-10.43	peak
15540.000	48.36	10.22	58.58	74.00	-15.42	peak
15540.000	31.07	10.22	41.29	54.00	-12.71	AVG
	_		_		_	

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

Result: Pass



Page 93 of 109

Radiated Emissions Test Results Above 1GHz

EUT Name	Smart PAD Tablet	Model Name	AGM_PAD_T2	
Temperature	23.2°C	Relative Humidity	57.8%	
Pressure	960hPa	Test Voltage	DC 3.85V by battery	
Test Mode	802.11n20_5200MHz	Antenna	Horizontal/Vertical	

Radiated Emission Above 1GHz-Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре
10400.000	48.12	9.14	57.26	68.20	-10.94	peak
15600.000	48.21	10.22	58.43	74.00	-15.57	peak
15600.000	30.19	10.22	40.41	54.00	-13.59	AVG
Domork:						
Remark:						
Factor = Antenna Fac	tor + Cable Loss	- Pre-amplifie	r.			

Radiated Emission Above 1GHz-Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре
10400.000	48.31	9.14	57.45	68.20	-10.75	peak
15600.000	47.89	10.22	58.11	74.00	-15.89	peak
15600.000	31.57	10.22	41.79	54.00	-12.21	AVG
Remark:						

Result: Pass

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Factor = Antenna Factor + Cable Loss - Pre-amplifier.



Page 94 of 109

Radiated Emissions Test Results Above 1GHz

EUT Name	Smart PAD Tablet	Model Name	AGM_PAD_T2	
Temperature	23.2°C	Relative Humidity	57.8%	
Pressure	960hPa	Test Voltage	DC 3.85V by battery	
Test Mode	802.11n20_5240MHz	Antenna	Horizontal/Vertical	

Radiated Emission Above 1GHz-Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре
10480.000	47.52	9.27	56.79	68.20	-11.41	peak
15720.000	49.36	10.38	59.74	74.00	-14.26	peak
15720.000	31.17	10.38	41.55	54.00	-12.45	AVG
D I						
Remark:						
Factor = Antenna Fac	tor + Cable Loss	- Pre-amplifie	r.			

Radiated Emission Above 1GHz-Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type			
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре			
10480.000	47.69	9.27	56.96	68.20	-11.24	peak			
15720.000	48.31	10.38	58.69	74.00	-15.31	peak			
15720.000	31.11	10.38	41.49	54.00	-12.51	AVG			
Remark:	Remark:								

Result: Pass

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Factor = Antenna Factor + Cable Loss - Pre-amplifier.



Page 95 of 109

Radiated Emissions Test Results Above 1GHz

EUT Name	Smart PAD Tablet	Model Name	AGM_PAD_T2	
Temperature	23.2°C	Relative Humidity	57.8%	
Pressure	960hPa	Test Voltage	DC 3.85V by battery	
Test Mode	802.11n20_5745MHz	Antenna	Horizontal/Vertical	

Radiated Emission Above 1GHz-Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value - Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре
11490.000	49.63	9.42	59.05	74.00	-14.95	peak
11490.000	32.11	9.42	41.53	54.00	-12.47	AVG
17235.000	42.69	10.51	53.20	68.20	-15.00	peak
Remark:	1	1	1			1
Factor = Antenna Fac	tor + Cable Loss	– Pre-amplifie	r.			

Radiated Emission Above 1GHz-Vertical

Meter Reading	Factor	Emission Level	Limits	Margin	Value
(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Type
49.89	9.42	59.31	74.00	-14.69	peak
31.17	9.42	40.59	54.00	-13.41	AVG
41.01	10.51	51.52	68.20	-16.68	peak
	Reading (dBµV) 49.89 31.17	Reading Factor (dBµV) (dB) 49.89 9.42 31.17 9.42	Reading Factor Level (dBμV) (dB) (dBμV/m) 49.89 9.42 59.31 31.17 9.42 40.59	Reading Factor Level Limits (dBμV) (dB) (dBμV/m) (dBμV/m) 49.89 9.42 59.31 74.00 31.17 9.42 40.59 54.00	Reading Factor Level Limits Margin (dBμV) (dB) (dBμV/m) (dBμV/m) (dB) 49.89 9.42 59.31 74.00 -14.69 31.17 9.42 40.59 54.00 -13.41

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

Result: Pass



Page 96 of 109

Radiated Emissions Test Results Above 1GHz

EUT Name	Smart PAD Tablet	Model Name	AGM_PAD_T2	
Temperature	23.2°C	Relative Humidity	57.8%	
Pressure	960hPa	Test Voltage	DC 3.85V by battery	
Test Mode	802.11n20_5785MHz	Antenna	Horizontal/Vertical	

Radiated Emission Above 1GHz-Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	
11570.000	48.63	9.42	58.05	74.00	-15.95	peak
11570.000	32.01	9.42	41.43	54.00	-12.57	AVG
17355.000	41.33	10.51	51.84	68.20	-16.36	peak
Remark:						

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

Radiated Emission Above 1GHz-Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Type
11570.000	49.36	9.42	58.78	74.00	-15.22	peak
11570.000	31.52	9.42	40.94	54.00	-13.06	AVG
17355.000	41.39	10.51	51.90	68.20	-16.30	peak
Remark:						

Result: Pass



Page 97 of 109

Radiated Emissions Test Results Above 1GHz

EUT Name	Smart PAD Tablet	Model Name	AGM_PAD_T2
Temperature	23.2°C	Relative Humidity	57.8%
Pressure	960hPa	Test Voltage	DC 3.85V by battery
Test Mode	802.11n20_5825MHz	Antenna	Horizontal/Vertical

Radiated Emission Above 1GHz-Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре
11650.000	49.31	9.62	58.93	74.00	-15.07	peak
11650.000	33.14	9.62	42.76	54.00	-11.24	AVG
17475.000	41.25	10.75	52.00	68.20	-16.20	peak
Remark:						
Factor = Antenna Factor	or + Cable Loss	- Pre-amplifie	r.			

ractor = Antenna ractor + Cable Loss -

Radiated Emission Above 1GHz-Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Type
11650.000	49.52	9.62	59.14	74.00	-14.86	peak
11650.000	32.21	9.62	41.83	54.00	-12.17	AVG
17475.000	40.36	10.75	51.11	68.20	-17.09	peak
Remark:						

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

Result: Pass


Note:

- The amplitude of other spurious emissions from 1GHz to 40 GHz which are attenuated more than 20 dB below the permissible value need not be reported.
- 2. Factor = Antenna Factor + Cable loss Amplifier gain, Margin=Measure Result-Limit.
- The "Factor" value can be calculated automatically by software of measurement system. 3.
- All test modes had been pre-tested. Refer to Chapter 5 of the report for details.




EUT Name	Smart PAD Tablet	Model Name	AGM_PAD_T2
Temperature	23.2°C	Relative Humidity	57.8%
Pressure	960hPa	Test Voltage	DC 3.85V by battery
Test Mode	802.11n20_5180MHz	Antenna	Horizontal

Test Graph for Peak Measurement




Test Graph for Average Measurement



Result: Pass

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. $Further\ enquiry\ of\ validity\ or\ verification\ of\ the\ test\ report\ should\ be\ addressed\ to\ AGC\ by\ agc 01@agccert.com.$


Web: http://www.agccert.com/






EUT Name	Smart PAD Tablet	Model Name	AGM_PAD_T2
Temperature	23.2°C	Relative Humidity	57.8%
Pressure	960hPa	Test Voltage	DC 3.85V by battery
Test Mode	802.11n20_5180MHz	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement




Result: Pass




EUT Name	Smart PAD Tablet	Model Name	AGM_PAD_T2
Temperature	23.2°C	Relative Humidity	57.8%
Pressure	960hPa	Test Voltage	DC 3.85V by battery
Test Mode	802.11n40_5190MHz	Antenna	Horizontal


Test Graph for Peak Measurement



Test Graph for Average Measurement



Result: Pass





EUT Name	Smart PAD Tablet	Model Name	AGM_PAD_T2
Temperature	23.2°C	Relative Humidity	57.8%
Pressure	960hPa	Test Voltage	DC 3.85V by battery
Test Mode	802.11n40_5190MHz	Antenna	Vertical


Test Graph for Peak Measurement



Test Graph for Average Measurement



Result: Pass





EUT Name	Smart PAD Tablet	Model Name	AGM_PAD_T2
Temperature	23.2°C	Relative Humidity	57.8%
Pressure	960hPa	Test Voltage	DC 3.85V by battery
Test Mode	802.11ac80_5210MHz	Antenna	Horizontal


Test Graph for Peak Measurement



Test Graph for Average Measurement



Result: Pass





EUT Name	Smart PAD Tablet	Model Name	AGM_PAD_T2
Temperature	23.2°C	Relative Humidity	57.8%
Pressure	960hPa	Test Voltage	DC 3.85V by battery
Test Mode	802.11ac80_5210MHz	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement



Result: Pass



Page 104 of 109

Note:

- 1. The factor had been edited in the "Input Correction" of the Spectrum Analyzer.
- 2. All test modes had been pre-tested, Refer to Chapter 5 of the report for details.



12. AC Power Line Conducted Emission Test


12.1 Measurement limit

Fraguenav	Maximum RF	Line Voltage
Frequency	Q.P (dBµV)	Average (dBμV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50MHz.

12.2 Block Diagram of Line Conducted Emission Test





Page 106 of 109

12.3 Preliminary Procedure of Line Conducted Emission Test

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received charging voltage by adapter which received 120V/60Hzpower by a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 Ohm load; the second scan had Line 1 connected to a 50 Ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

12.4 Final Procedure of Line Conducted Emission Test

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- The test data of the worst case was reported on the Summary Data page.

Detector Line

L1

L1

L1

L1

L1

L1



12.5 Test Result of Line Conducted Emission Test

√lode	802.11n(20M	Hz)5180MF	łz	L	SN Line		Hot Sic	de
Level	[dBµV]						•	
80								
70								
60		 - -	<u></u>	<u>-ii</u>		1 1 1 1	i	i
50		· 	<u> </u>			+ + + +		
40			i-i					
30 🤝	- my	manufaller way	whyderwal-waterwale				<u>-</u>	
20 =		~	4 - Ft	A STATE OF THE PERSON NAMED IN	OCHAR COL	+ -	in this section is	لنسابا
10		+			-			
0		+	1-+ ! !	- ! !			 !	!
-10 L 150	0k 300k 400	k 600k 800k	1M 2	2M 3M	4M 5M 6N	8M 10M	20	M 30M
MEAS	S agc_fin UREMENT		: "agc_	fin"				
MEAS 2024/	UREMENT 9/12 23:		: "agc_ Transd	fin" Limit	Marg	in De	tector	Line
MEAS 2024/	UREMENT	56	_		_	in De	tector	Line
MEAS 2024/ Fr	UREMENT 9/12 23: equency MHz .334000	56 Level dBμV 22.50	Transd dB	Limit dBµV	36	dB .9 QF	,	L1
MEAS 2024/ Fr 0	UREMENT 9/12 23: equency MHz .334000 .590000	56 Level dBµV 22.50 19.10	Transd dB	Limit dBµV 59	36 36	dB .9 QF .9 QF)	L1 L1
MEAS 2024/ Fr 0 0 1	UREMENT 9/12 23: equency MHz .334000 .590000 .026000	56 Level dBμV 22.50 19.10 20.50	Transd dB 6.1 6.2 6.2	Limit dBµV 59 56	36 36 35	dB .9 QF .9 QF .5 QF)	L1 L1 L1
MEAS 2024/ Fr 0 0 1 10	UREMENT 9/12 23: equency MHz .334000 .590000 .026000 .818000	Level dBμV 22.50 19.10 20.50 18.00	Transd dB 6.1 6.2 6.2 6.7	Limit dBµV 59 56 60	36 36 35 42	dB .9 QF .9 QF .5 QF		L1 L1 L1
MEAS 2024/ Fr 0 0 1 10 10	UREMENT 9/12 23: equency MHz .334000 .590000 .026000 .818000 .978000	Level dBμV 22.50 19.10 20.50 18.00 18.10	Transd dB 6.1 6.2 6.2 6.7 6.7	Limit dBµV 59 56 60	36 36 35 42 41	dB .9 QF .9 QF .5 QF .0 QF .9 QF		L1 L1 L1 L1
MEAS 2024/ Fr 0 0 1 10 10	UREMENT 9/12 23: equency MHz .334000 .590000 .026000 .818000	Level dBμV 22.50 19.10 20.50 18.00	Transd dB 6.1 6.2 6.2 6.7	Limit dBµV 59 56 60	36 36 35 42 41	dB .9 QF .9 QF .5 QF .0 QF .9 QF		L1 L1 L1
MEAS 2024/ Fr 0 0 1 10 10	UREMENT 9/12 23: equency MHz .334000 .590000 .026000 .818000 .978000	Level dBμV 22.50 19.10 20.50 18.00 18.10	Transd dB 6.1 6.2 6.2 6.7 6.7	Limit dBµV 59 56 60	36 36 35 42 41	dB .9 QF .9 QF .5 QF .0 QF .9 QF		L1 L1 L1 L1

Result: Pass

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Frequency Level Transd Limit Margin

dB

6.1

6.2

6.7

6.7

6.7

6.2

dBµV

49

46

46

50

50

50

dB

ΑV

ΑV

ΑV

ΑV

ΑV

ΑV

32.4

29.6

30.2

36.5

41.7

43.0

dBuV

16.50

16.40

15.80

13.50

8.30

7.00

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

MHz

0.354000

0.502000

1.266000

10.822000

10.982000

11.242000

30M



		А	C Po	owe	r Line Cond	lucted	Emis	sio	n Te	est				
Test Mode	802.11n(2	802.11n(20MHz)5180MHz				LISN	l Lir	ne			N	eutral	Side	
80 70 60 50	[dBµV]			 -			 	 			 - T - - T -			
40 30 20 10			1	- - - - - -	and applicately applying to		 	 	 		 	 		

MEASUREMENT RESULT: "agc fin"

2024/9/12 23:53

+ + +MES agc_fin

ZUZ4/9/1Z Z3:	55					
Frequency MHz	Level dBµV		Limit dBµV	Margin dB	Detector	Line
0.170000	23.70	6.1	65	41.3	QP	N
0.750000	19.90	6.2	56	36.1	QP	N
1.386000	19.90	6.2	56	36.1	QP	N
2.162000	15.40	6.2	56	40.6	QP	N
10.238000	14.20	6.7	60	45.8	QP	N
10.634000	17.10	6.7	60	42.9	QP	N

2M

Frequency [Hz]

3M

4M 5M 6M

8M 10M

MEASUREMENT RESULT: "agc fin2"

2024/9/12 23:53

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.358000	16.50	6.1	49	32.3	AV	N
0.526000	16.00	6.2	46	30.0	AV	N
1.334000	15.80	6.2	46	30.2	AV	N
2.158000	10.80	6.2	46	35.2	AV	N
10.222000	4.40	6.7	50	45.6	AV	N
10.602000	6.60	6.7	50	43.4	AV	N

Result: Pass



Page 109 of 109

Appendix I: Photographs of Test Setup

Refer to the Report No.: AG00408240808AP03

Appendix II: Photographs of EUT

Refer to the Report No.: AG00408240808AP04

----End of Report----



Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.