

## RF EXPOSURE EVALUATION

### EUT Specification

<b>EUT</b>	BabyShark Children's Robot Vacuum
<b>Model Number</b>	BSRV200
<b>FCC ID</b>	2AVRVBSRV200RX
<b>Antenna gain (Max)</b>	2.41dBi
<b>Operation Frequency</b>	GFSK: 2401-2463MHz
<b>Input Rating</b>	Battery 7.4V, DC 5V from adapter
<b>Max. output power</b>	10.11dBm(0.010257W)

### Test Requirement:

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

$$11.1 \text{ Friis transmission formula: } P_d = (P_{out} * G) / (4 * \pi * R^2)$$

Where

Pd= Power density in mW/cm<sup>2</sup>

Pout=output power to antenna in mW

G= Numeric gain of the antenna relative to isotropic antenna

Pi=3.1416

R= distance between observation point and center of the radiator in cm=20cm

Pd the limit of MPE,  $1\text{mW/cm}^2$ . If we know the maximum gain of the nd total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.


### 11.2 Measurement Result

Antenna gain: 2.41 dBi

2.4GHz :

Mode	Channe l Freq. (MHz)	Measu red power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenn a Gain (Num eric)	Evaluation result (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
GFSK	2401	10.11	10±1	11	1.637	0.004100	1
GFSK	2432	8.04	8±1	9	1.637	0.002587	1
GFSK	2463	8.86	9±1	10	1.637	0.003257	1

Signature:



Tiger Xu

Date: 2022-10-17