

FCC REPORT

Applicant: SHEN ZHEN TOMSTAR TECHNOLOGY CO., LTD

Address of Applicant: Room 2110-2116, Huafeng International Commercial Building, Xixiang, BaoAn district, Shenzhen, China

Equipment Under Test (EUT)

Product Name: SMART BAND

Model No.: TS01, TS06, TS09, SW30, SW56

FCC ID: 2APD3TS01

Applicable standards: FCC CFR Title 47 Part 15 Subpart B

Date of sample receipt: 24 Jun., 2019

Date of Test: 25 Jun., to 01 Jul., 2019

Date of report issued: 02 Jul., 2019

Test Result: PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	02 Jul., 2019	Original

Tested by:



Test Engineer

Date:

02 Jul., 2019

Reviewed by:



Project Engineer

Date:

02 Jul., 2019

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY.....	4
5 GENERAL INFORMATION.....	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF E.U.T.	5
5.3 TEST MODE.....	5
5.4 MEASUREMENT UNCERTAINTY.....	5
5.5 DESCRIPTION OF SUPPORT UNITS	5
5.6 RELATED SUBMITTAL(S) / GRANT (s).....	5
5.7 DESCRIPTION OF CABLE USED	6
5.8 LABORATORY FACILITY.....	6
5.9 LABORATORY LOCATION	6
5.10 TEST INSTRUMENTS LIST.....	7
6 TEST RESULTS AND MEASUREMENT DATA.....	8
6.1 CONDUCTED EMISSION.....	8
6.2 RADIATED EMISSION.....	11
7 TEST SETUP PHOTO	17
8 EUT CONSTRUCTIONAL DETAILS	18

4 Test Summary

Test Item	Section in CFR 47	Result
Conducted Emission	Part 15.107	Pass
Radiated Emission	Part 15.109	Pass

Remark:
Pass: The EUT complies with the essential requirements in the standard.
N/A: The EUT not applicable of the test item.

5 General Information

5.1 Client Information

Applicant:	SHEN ZHEN TOMSTAR TECHNOLOGY CO., LTD
Address:	Room 2110-2116, Huafeng International Commercial Building, Xixiang, BaoAn district, Shenzhen, China
Manufacturer:	Tomstar Industrial Limited
Address:	Room 2110-2116, Huafeng International Commercial Building, Xixiang, BaoAn district, Shenzhen, China

5.2 General Description of E.U.T.

Product Name:	SMART BAND
Model No.:	TS01, TS06, TS09, SW30, SW56
Power supply:	Rechargeable Li-ion Battery DC3.7V, 180mAh
Remark:	Item No.: TS01, TS06, TS09, SW30, SW56 were identical inside, the electrical circuit design, layout, components used and internal wiring, with only difference being model name.
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

5.3 Test Mode

Operating mode	Detail description
Charging mode	Keep the EUT in Charging(by PC) mode(Worst case)
Working mode	Keep the EUT in Working mode

The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

5.4 Measurement Uncertainty

Parameters	Expanded Uncertainty
Conducted Emission (9kHz ~ 30MHz)	±1.60 dB (k=2)
Radiated Emission (9kHz ~ 30MHz)	±3.12 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	±4.54 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	±5.84 dB (k=2)
Radiated Emission (18GHz ~ 40GHz)	±3.36 dB (k=2)

5.5 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC ID/DoC
DELL	PC	OPTIPLEX745	N/A	DoC

5.6 Related Submittal(s) / Grant (s)

This is an original grant, no related submittals and grants.

5.7 Description of Cable Used

Cable Type	Description	Length	From	To
Detached USB Cable	Unshielded	0.60m	EUT	Adapter

5.8 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Designation No.: CN1211**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

● **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

● **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

5.9 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.

Address: No. B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,

Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755-23118282, Fax: +86-755-23116366

Email: info@ccis-cb.com, Website: http://www.ccis-cb.com

5.10 Test Instruments list

Radiated Emission:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	SAEMC	9m*6m*6m	966	07-22-2017	07-21-2020
Loop Antenna	SCHWARZBECK	FMZB1519B	00044	03-18-2019	03-17-2020
BiConiLog Antenna	SCHWARZBECK	VULB9163	497	03-18-2019	03-17-2020
Horn Antenna	SCHWARZBECK	BBHA9120D	916	03-18-2019	03-17-2020
Horn Antenna	SCHWARZBECK	BBHA9120D	1805	06-22-2017	06-21-2020
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170582	11-21-2018	11-20-2019
EMI Test Software	AUDIX	E3	Version: 6.110919b		
Pre-amplifier	HP	8447D	2944A09358	03-18-2019	03-17-2020
Pre-amplifier	CD	PAP-1G18	11804	03-18-2019	03-17-2020
Spectrum analyzer	Rohde & Schwarz	FSP30	101454	03-18-2019	03-17-2020
Spectrum analyzer	Rohde & Schwarz	FSP40	100363	11-21-2018	11-20-2019
EMI Test Receiver	Rohde & Schwarz	ESRP7	101070	03-18-2019	03-17-2020
Cable	ZDECL	Z108-NJ-NJ-81	1608458	03-18-2019	03-17-2020
Cable	MICRO-COAX	MFR64639	K10742-5	03-18-2019	03-17-2020
Cable	SUHNER	SUCOFLEX100	58193/4PE	03-18-2019	03-17-2020

Conducted Emission:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
EMI Test Receiver	Rohde & Schwarz	ESCI	101189	03-18-2019	03-17-2020
Pulse Limiter	SCHWARZBECK	OSRAM 2306	9731	03-18-2019	03-17-2020
LISN	CHASE	MN2050D	1447	03-18-2019	03-17-2020
LISN	Rohde & Schwarz	ESH3-Z5	8438621/010	07-21-2018	07-20-2019
Cable	HP	10503A	N/A	03-18-2019	03-17-2020
EMI Test Software	AUDIX	E3	Version: 6.110919b		


6 Test results and Measurement Data

6.1 Conducted Emission

Test Requirement:	FCC Part 15 B Section 15.107																		
Test Method:	ANSI C63.4:2014																		
Test Frequency Range:	150kHz to 30MHz																		
Class / Severity:	Class B																		
Receiver setup:	RBW=9kHz, VBW=30kHz																		
Limit:	<table border="1"> <thead> <tr> <th>Frequency range (MHz)</th> <th colspan="2">Limit (dBμV)</th> </tr> <tr> <th></th> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>0.5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>			Frequency range (MHz)	Limit (dB μ V)			Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	0.5-30	60	50	*
Frequency range (MHz)	Limit (dB μ V)																		
	Quasi-peak	Average																	
0.15-0.5	66 to 56*	56 to 46*																	
0.5-5	56	46																	
0.5-30	60	50																	
Test setup:	<p><i>Remark:</i> E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>																		
Test procedure	<ol style="list-style-type: none"> The E.U.T and simulators are connected to the main power through a line impedance stabilization network(L.I.S.N.). They provide a 50ohm/50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2014 on conducted measurement. 																		
Test environment:	Temp.:	22.5 °C	Humid.:	55%	Press.:	101kPa													
Test Instruments:	Refer to section 5.9 for details																		
Test mode:	Refer to section 5.3 for details																		
Test results:	Pass																		

Measurement data:

Product name:	SMART BAND	Product model:	TS01
Test by:	Yaro	Test mode:	Charging mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5°C Huni: 55%



Level (dBuV)

FCC PART15 B QP

FCC PART15 B AV

Trace: 9


Frequency (MHz)

Freq	Read	LISN	Cable	Limit	Over	Remark
	Level	Factor	Loss			
MHz	dBuV	dB	dB	dBuV	dB	
1	0.162	42.16	-0.44	10.77	52.49	65.34 -12.85 QP
2	0.389	32.33	-0.37	10.72	42.68	58.08 -15.40 QP
3	0.393	29.65	-0.37	10.72	40.00	47.99 -7.99 Average
4	0.585	35.24	-0.39	10.76	45.61	56.00 -10.39 QP
5	0.654	27.98	-0.38	10.77	38.37	46.00 -7.63 Average
6	0.788	31.51	-0.38	10.81	41.94	56.00 -14.06 QP
7	0.788	27.45	-0.38	10.81	37.88	46.00 -8.12 Average
8	1.049	28.52	-0.38	10.88	39.02	46.00 -6.98 Average
9	1.568	32.25	-0.40	10.93	42.78	56.00 -13.22 QP
10	1.568	27.84	-0.40	10.93	38.37	46.00 -7.63 Average
11	1.959	26.03	-0.41	10.96	36.58	46.00 -9.42 Average
12	2.608	32.55	-0.43	10.93	43.05	56.00 -12.95 QP

Notes:

- An initial pre-scan was performed on the line and neutral lines with peak detector.
- Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- Final Level = Receiver Read level + LISN Factor + Cable Loss.

Product name:	SMART BAND	Product model:	TS01
Test by:	Yaro	Test mode:	Charging mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Neutral
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5°C Huni: 55%



Freq MHz	Read Level dBuV	LISN Factor	Cable Loss dB	Level dBuV	Limit Line dBuV	Over Limit dB	Over Limit Remark
	MHz	dB	dB		dB	dB	
1	0.152	43.83	-0.68	10.78	53.93	65.87	-11.94 QP
2	0.170	33.32	-0.68	10.77	43.41	54.94	-11.53 Average
3	0.206	40.93	-0.69	10.76	51.00	63.36	-12.36 QP
4	0.393	27.43	-0.64	10.72	37.51	47.99	-10.48 Average
5	0.589	35.98	-0.65	10.76	46.09	56.00	-9.91 QP
6	0.654	35.58	-0.64	10.77	45.71	56.00	-10.29 QP
7	0.654	28.17	-0.64	10.77	38.30	46.00	-7.70 Average
8	1.049	27.65	-0.63	10.88	37.90	46.00	-8.10 Average
9	1.303	28.83	-0.65	10.90	39.08	46.00	-6.92 Average
10	1.568	33.96	-0.66	10.93	44.23	56.00	-11.77 QP
11	1.568	28.98	-0.66	10.93	39.25	46.00	-6.75 Average
12	1.959	33.21	-0.67	10.96	43.50	56.00	-12.50 QP

Notes:

- An initial pre-scan was performed on the line and neutral lines with peak detector.
- Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- Final Level =Receiver Read level + LISN Factor + Cable Loss.


6.2 Radiated Emission

Test Requirement:	FCC Part 15 B Section 15.109					
Test Method:	ANSI C63.4:2014					
Test Frequency Range:	30MHz to 25000MHz					
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)					
Receiver setup:	Frequency	Detector	RBW	VBW		
	30MHz-1GHz	Quasi-peak	120kHz	300kHz		
	Above 1GHz	Peak	1MHz	3MHz		
Limit:	RMS	1MHz	3MHz	Average Value		
	Frequency	Limit (dBuV/m @3m)		Remark		
	30MHz-88MHz	40.0		Quasi-peak Value		
88MHz-216MHz		43.5		Quasi-peak Value		
216MHz-960MHz		46.0		Quasi-peak Value		
960MHz-1GHz		54.0		Quasi-peak Value		
Above 1GHz		54.0		Average Value		
		74.0		Peak Value		
Test setup:	Below 1GHz					
	Above 1GHz					

Test Procedure:	1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.					
Test environment:	Temp.:	24 °C	Humid.:	57%	Press.:	1 01kPa
Test Instruments:	Refer to section 5.9 for details					
Test mode:	Refer to section 5.3 for details					
Test results:	Passed					
Remark:	All of the observed value above 6GHz were the noise floor , only report worse case 30MHz-6GHz					

Measurement Data:**Below 1GHz:**

Product Name:	SMART BAND	Product Model:	TS01
Test By:	Yaro	Test mode:	Charging mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	110.569	41.10	11.60	2.05	29.45	25.30	43.50	-18.20 QP
2	158.668	41.69	9.24	2.57	29.14	24.36	43.50	-19.14 QP
3	221.392	36.39	11.55	2.84	28.70	22.08	46.00	-23.92 QP
4	303.544	36.60	13.68	2.95	28.46	24.77	46.00	-21.23 QP
5	463.970	33.52	16.98	3.32	28.89	24.93	46.00	-21.07 QP
6	845.088	30.31	22.52	4.21	28.02	29.02	46.00	-16.98 QP

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	SMART BAND	Product Model:	TS01
Test By:	Yaro	Test mode:	Charging mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq MHz	Read Level dBuV	Antenna Factor dB/m	Cable Loss Factor dB	Preamp Level dB	Limit Line dBuV/m	Over Line dBuV/m	Over Limit dB	Remark
1 34.037	38.26	11.09	0.98	29.96	20.37	40.00	-19.63	QP
2 160.909	38.54	9.32	2.60	29.12	21.34	43.50	-22.16	QP
3 168.414	42.75	9.59	2.64	29.06	25.92	43.50	-17.58	QP
4 270.375	34.58	13.10	2.86	28.50	22.04	46.00	-23.96	QP
5 435.590	33.26	16.16	3.16	28.85	23.73	46.00	-22.27	QP
6 677.580	32.50	20.09	4.04	28.72	27.91	46.00	-18.09	QP

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Above 1GHz:

Product Name:	SMART BAND	Product Model:	TS01
Test By:	Yaro	Test mode:	Charging mode
Test Frequency:	1 GHz ~ 6 GHz	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq MHz	Read Level dBuV	Antenna Factor dB/m	Cable Loss dB	Preamp Factor dB	Level dBuV/m	Limit Line dBuV/m	Over Line dB	Remark
1 4697.350	46.84	30.81	6.85	41.99	42.51	74.00	-31.49	Peak
2 4697.350	38.62	30.81	6.85	41.99	34.29	54.00	-19.71	Average
3 5147.218	46.95	31.76	7.05	41.93	43.83	74.00	-30.17	Peak
4 5147.218	38.24	31.76	7.05	41.93	35.12	54.00	-18.88	Average
5 5750.997	48.09	32.65	7.74	41.96	46.52	74.00	-27.48	Peak
6 5750.997	39.63	32.65	7.74	41.96	38.06	54.00	-15.94	Average

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	SMART BAND	Product Model:	TS01
Test By:	Yaro	Test mode:	Charging mode
Test Frequency:	1 GHz ~ 6 GHz	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz	Environment:	Temp: 24°C Huni: 57%



Freq MHz	Read	Antenna Level	Cable Loss	Preamp Factor	Limit Level	Line dBuV/m	Over Line dBuV/m	Over Line dB	Over Line Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 4179.719	48.26	30.34	6.37	41.81	43.16	74.00	-30.84	Peak	
2 4179.719	40.23	30.34	6.37	41.81	35.13	54.00	-18.87	Average	
3 5289.370	48.36	32.11	7.10	41.91	45.66	74.00	-28.34	Peak	
4 5289.370	40.35	32.11	7.10	41.91	37.65	54.00	-16.35	Average	
5 6326.346	47.53	34.09	8.17	41.95	47.84	74.00	-26.16	Peak	
6 6326.346	39.57	34.09	8.17	41.95	39.88	54.00	-14.12	Average	

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.