



CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel: +86-755-27521059 Fax: +86-755-27521011 <http://www.sz-ctc.org.cn>

TEST REPORT

Report No.: **CTC20220169E05**

FCC ID.....: **2AT7J-G3**

Applicant.....: **Shenzhen Free Dynamic Development Co., LTD.**

Address.....: Room 1201, South Block, Yuanxing science and technology building, Nanshan District, Shenzhen, China

Manufacturer.....: Shenzhen Free Dynamic Development Co., Ltd.

Address.....: Room 1201, South Block, Yuanxing science and technology building, Nanshan District, Shenzhen, China

Product Name.....: **Robot Vacuum Cleaner**

Trade Mark.....: /

Model/Type reference.....: G3

Listed Model(s): G5,G7

Standard.....: **FCC CFR Title 47 Part 15 Subpart C Section 15.247**

Date of receipt of test sample...: Feb. 8, 2022

Date of testing.....: Feb. 22, 2022 to Mar. 12, 2022

Date of issue.....: May. 23, 2022

Result.....: **PASS**

Compiled by:

(Printed name+signature)

Lucy Lan

Supervised by:

(Printed name+signature)

Miller Ma

Approved by:

(Printed name+signature)

Totti Zhao

Testing Laboratory Name.....: **CTC Laboratories, Inc.**

Address.....: 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

This test report may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CTC. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CTC within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit. The test report merely correspond to the test sample.



Table of Contents

Page

| | |
|---|-----------|
| 1. TEST SUMMARY | 3 |
| 1.1. TEST STANDARDS..... | 3 |
| 1.2. REPORT VERSION | 3 |
| 1.3. TEST DESCRIPTION..... | 3 |
| 1.4. TEST FACILITY | 4 |
| 1.5. MEASUREMENT UNCERTAINTY | 4 |
| 1.6. ENVIRONMENTAL CONDITIONS..... | 5 |
| 2. GENERAL INFORMATION | 6 |
| 2.1. CLIENT INFORMATION | 6 |
| 2.2. GENERAL DESCRIPTION OF EUT | 6 |
| 2.3. ACCESSORY EQUIPMENT INFORMATION | 7 |
| 2.4. OPERATION STATE | 8 |
| 2.5. MEASUREMENT INSTRUMENTS LIST | 9 |
| 3. TEST ITEM AND RESULTS | 10 |
| 3.1. CONDUCTED EMISSION..... | 10 |
| 3.2. RADIATED EMISSION | 13 |
| 3.3. BAND EDGE EMISSIONS (RADIATED) | 36 |
| 3.4. BAND EDGE AND SPURIOUS EMISSIONS (CONDUCTED) | 49 |
| 3.5. BANDWIDTH..... | 62 |
| 3.6. PEAK OUTPUT POWER | 70 |
| 3.7. POWER SPECTRAL DENSITY | 72 |
| 3.8. ANTENNA REQUIREMENT..... | 77 |



1. TEST SUMMARY

1.1. Test Standards

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Operation within the bands of 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz.

[RSS 247 Issue 2](#): Standard Specifications for Frequency Hopping Systems (FHSs) and Digital Transmission Systems (DTSs) Operating in the Bands 902-928MHz, 2400-2483.5MHz and 5725-5850MHz.

[ANSI C63.10-2013](#): American National Standard for Testing Unlicensed Wireless Devices.

1.2. Report Version

| Revised No. | Date of issue | Description |
|-------------|---------------|-------------|
| 01 | May. 23, 2022 | Original |
| | | |
| | | |

1.3. Test Description

| FCC Part 15 Subpart C (15.247) / RSS 247 Issue 2 | | | | |
|--|------------------|-----------------------------|--------|---------------|
| Test Item | Standard Section | | Result | Test Engineer |
| | FCC | IC | | |
| Antenna Requirement | 15.203 | / | Pass | Lucy Lan |
| Conducted Emission | 15.207 | RSS-Gen 8.8 | Pass | Lucy Lan |
| Band Edge Emissions | 15.247(d) | RSS 247 5.5 | Pass | Lucy Lan |
| 6dB Bandwidth | 15.247(a)(2) | RSS 247 5.2 (a) | Pass | Lucy Lan |
| Conducted Max Output Power | 15.247(b)(3) | RSS 247 5.4 (d) | Pass | Lucy Lan |
| Power Spectral Density | 15.247(e) | RSS 247 5.2 (b) | Pass | Lucy Lan |
| Transmitter Radiated Spurious | 15.209&15.247(d) | RSS 247 5.5& RSS-Gen 8.9 | Pass | Lucy Lan |

Note: The measurement uncertainty is not included in the test result.



1.4. Test Facility

CTC Laboratories, Inc.

Add: 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

A2LA-Lab Cert. No.: 4340.01

CTC Laboratories, Inc. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

Industry Canada (Registration No.: 9783A, CAB Identifier: CN0029)

CTC Laboratories, Inc. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration NO.: 9783A on Jan, 2016.

FCC (Registration No.: 951311, Designation Number CN1208)

CTC Laboratories, Inc. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 951311, Aug 26, 2017.

1.5. Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the CTC Laboratories, Inc. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Below is the best measurement capability for CTC Laboratories, Inc.



| Test Items | Measurement Uncertainty | Notes |
|---|-------------------------|-------|
| Transmitter power conducted | 0.42 dB | (1) |
| Transmitter power Radiated | 2.14 dB | (1) |
| Conducted spurious emissions 9kHz~40GHz | 1.60 dB | (1) |
| Radiated spurious emissions 9kHz~40GHz | 2.20 dB | (1) |
| Conducted Emissions 9kHz~30MHz | 3.20 dB | (1) |
| Radiated Emissions 30~1000MHz | 4.70 dB | (1) |
| Radiated Emissions 1~18GHz | 5.00 dB | (1) |
| Radiated Emissions 18~40GHz | 5.54 dB | (1) |
| Occupied Bandwidth | ----- | (1) |

Note (1): This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

1.6. Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

| | |
|-----------------------|-----------|
| Temperature: | 21°C~27°C |
| Relative Humidity: | 40%~60% |
| Atmospheric Pressure: | 101kPa |



2. GENERAL INFORMATION

2.1. Client Information

| | |
|---------------|---|
| Applicant: | Shenzhen Free Dynamic Development Co., Ltd. |
| Address: | Room 1201, South Block, Yuanxing science and technology building, Nanshan District, Shenzhen, China |
| Manufacturer: | Shenzhen Free Dynamic Development Co., Ltd. |
| Address: | Room 1201, South Block, Yuanxing science and technology building, Nanshan District, Shenzhen, China |

2.2. General Description of EUT

| | |
|--------------------------------------|---|
| Product Name: | Robot Vacuum Cleaner |
| Trade Mark: | / |
| Model/Type reference: | G3 |
| Listed Model(s): | G5,G7 |
| Model Differences: | All product models are different in shell color and customer number; Its internal structure, circuit principle, PCB wiring of the product and all the key components related to safety and electromagnetic compatibility performance are identical. |
| Power supply: | DC 19V/1A from Charging Station DC 14.4V from Battery DC 19V/1.2A from Self Empty Station |
| Charging Station Model : | G3 Input: 100-240V~ 50/60Hz 1A Output: 19V/1A |
| Self Empty Station Model: | S1 Input: 220-240V~ 50/60Hz 1A Output: 19V/1.2A |
| Hardware version: | / |
| Software version: | / |
| 2.4G WIFI 802.11b/ g/ n(HT20) | |
| Modulation: | 802.11b: DSSS(CCK, DQPSK, DBPSK) 802.11g/n: OFDM(BPSK, QPSK, 16QAM, 64QAM) |
| Operation frequency: | 802.11b/g/n(HT20): 2412MHz~2462MHz |
| Channel number: | 802.11b/g/n(HT20): 11 channels |
| Channel separation: | 5MHz |
| Antenna 1 and 2 type: | FPC |
| Antenna 1 and 2 gain: | 0dBi |



2.3. Accessory Equipment Information

| Equipment Information | | | |
|---------------------------|---------------|--------------|--------------|
| Name | Model | S/N | Manufacturer |
| Notebook | E14 | / | Lenovo |
| Cable Information | | | |
| Name | Shielded Type | Ferrite Core | Length |
| USB Cable | Unshielded | NO | 100cm |
| Test Software Information | | | |
| Name | Version | / | / |
| WifiSRRC | 2.1 | / | / |

2.4. Operation State

Operation Frequency List: The EUT has been tested under typical operating condition. The Applicant provides communication tools software to control the EUT for staying in continuous transmitting and receiving mode for testing.

Operation Frequency List:

| Channel | Frequency (MHz) |
|---------|-----------------|
| 01 | 2412 |
| 02 | 2417 |
| 03 | 2422 |
| 04 | 2427 |
| 05 | 2432 |
| 06 | 2437 |
| 07 | 2442 |
| 08 | 2447 |
| 09 | 2452 |
| 10 | 2457 |
| 11 | 2462 |

Data Rated

Preliminary tests were performed in different data rate, and found which the below bit rate is worst case mode, so only show data which it is a worst case mode.

| Mode | Data rate (worst mode) |
|---------------|------------------------|
| 802.11b | 1Mbps |
| 802.11g | 6Mbps |
| 802.11n(HT20) | HT-MCS0 |

Test mode

| |
|--|
| For RF test items: |
| The engineering test program was provided and enabled to make EUT continuous transmit. |
| For AC power line conducted emissions: |
| The EUT was set to connect with the WLAN AP under large package sizes transmission. |
| For Radiated spurious emissions test item: |
| The engineering test program was provided and enabled to make EUT continuous transmit. The EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data Recorded in the report. |



2.5. Measurement Instruments List

| Tonscend JS0806-2 Test system | | | | | |
|-------------------------------|-------------------------------------|-----------------|-----------|------------|------------------|
| Item | Test Equipment | Manufacturer | Model No. | Serial No. | Calibrated until |
| 1 | Spectrum Analyzer | Rohde & Schwarz | FSU26 | 100105 | Dec.23, 2022 |
| 2 | Spectrum Analyzer | Rohde & Schwarz | FUV40-N | 101331 | Mar. 15, 2022 |
| 3 | MXG Vector Signal Generator | Agilent | N5182A | MY47420864 | Dec.23, 2022 |
| 4 | Signal Generator | Agilent | E8257D | MY46521908 | Dec.23, 2022 |
| 5 | Power Sensor | Agilent | U2021XA | MY5365004 | Mar. 15, 2022 |
| 6 | Power Sensor | Agilent | U2021XA | MY5365006 | Mar. 15, 2022 |
| 7 | Simultaneous Sampling DAQ | Agilent | U2531A | TW54493510 | Mar. 15, 2022 |
| 8 | Climate Chamber | TABAI | PR-4G | A8708055 | Dec.23, 2022 |
| 9 | Wideband Radio Communication Tester | Rohde & Schwarz | CMW500 | 116410 | Dec.23, 2022 |
| 10 | Climate Chamber | ESPEC | MT3065 | / | Dec.23, 2022 |
| 11 | 300328 v2.2.2 test system | TONSCEND | v2.6 | / | / |

| Radiated emission(3m chamber 2) | | | | | |
|---------------------------------|--------------------------|--------------|------------|------------|------------------|
| Item | Test Equipment | Manufacturer | Model No. | Serial No. | Calibrated Until |
| 1 | Trilog-Broadband Antenna | Schwarzbeck | VULB 9168 | 9168-1013 | Jan. 12, 2023 |
| 2 | Horn Antenna | Schwarzbeck | BBHA 9120D | 9120D-647 | Dec. 23, 2022 |
| 3 | Spectrum Analyzer | R&S | FSU26 | 100105 | Dec. 23, 2022 |
| 4 | Spectrum Analyzer | R&S | FSV40-N | 101331 | Mar. 15, 2022 |
| 5 | Pre-Amplifier | SONOMA | 310 | 186194 | Dec. 23, 2022 |
| 6 | Low Noise Pre-Amplifier | EMCI | EMC051835 | 980075 | Dec. 23, 2022 |
| 7 | Test Receiver | R&S | ESC17 | 100967 | Dec. 23, 2022 |

| Radiated emission(3m chamber 3) | | | | | |
|---------------------------------|------------------------------|--------------|------------|------------|------------------|
| Item | Test Equipment | Manufacturer | Model No. | Serial No. | Calibrated Until |
| 1 | Trilog-Broadband Antenna | Schwarzbeck | VULB 9168 | 9168-759 | Nov. 09, 2022 |
| 2 | Horn Antenna | Schwarzbeck | BBHA 9120D | 9120D-647 | Dec. 23, 2022 |
| 3 | Test Receiver | Keysight | N9038A | MY56400071 | Dec. 23, 2022 |
| 4 | Broadband Premplifier | SCHWARZBECK | BBV9743B | 259 | Dec. 23, 2022 |
| 5 | Mirowave Broadband Amplifier | SCHWARZBECK | BBV9718C | 111 | Dec. 23, 2022 |

Note: The cable loss has calculated in test result which connection between each test instruments.

3. TEST ITEM AND RESULTS

3.1. Conducted Emission


Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.207/ RSS - Gen 8.8:

| Frequency range (MHz) | Limit (dBuV) | |
|-----------------------|--------------|-----------|
| | Quasi-peak | Average |
| 0.15-0.5 | 66 to 56* | 56 to 46* |
| 0.5-5 | 56 | 46 |
| 5-30 | 60 | 50 |

* Decreases with the logarithm of the frequency.

Test Configuration




Test Procedure

1. The EUT was setup according to ANSI C63.10:2013 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
4. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
5. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
6. Conducted Emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
7. During the above scans, the emissions were maximized by cable manipulation.


**Test Mode:**

Please refer to the clause 2.4.

Test Results



| | |
|---------------|---------------|
| Test Voltage: | AC 120V/60 Hz |
| Terminal: | Neutral |



Final Measurement Detector 1

| Frequency (MHz) | QuasiPeak (dBu V) | Meas. Time (ms) | Bandwidth (kHz) | Filter | Line | Corr. (dB) | Margin (dB) | Limit (dBu V) | Comment |
|-----------------|-------------------|-----------------|-----------------|--------|------|------------|-------------|---------------|---------|
| 0.205620 | 45.2 | 1000.00 | 9.000 | On | N | 10.0 | 18.2 | 63.4 | |
| 0.346870 | 39.9 | 1000.00 | 9.000 | On | N | 10.0 | 19.1 | 59.0 | |
| 0.487010 | 37.1 | 1000.00 | 9.000 | On | N | 10.0 | 19.1 | 56.2 | |

Final Measurement Detector 2

| Frequency (MHz) | Average (dBu V) | Meas. Time (ms) | Bandwidth (kHz) | Filter | Line | Corr. (dB) | Margin (dB) | Limit (dBu V) | Comment |
|-----------------|-----------------|-----------------|-----------------|--------|------|------------|-------------|---------------|---------|
| 0.270820 | 29.8 | 1000.00 | 9.000 | On | N | 10.0 | 21.3 | 51.1 | |
| 0.344120 | 25.7 | 1000.00 | 9.000 | On | N | 10.0 | 23.4 | 49.1 | |
| 0.496830 | 21.6 | 1000.00 | 9.000 | On | N | 10.0 | 24.5 | 46.1 | |

Emission Level= Read Level+ Correct Factor



3.2. Radiated Emission

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.209/ RSS – Gen 8.9:


| Frequency (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-----------------|-----------------------------------|-------------------------------|
| 0.009~0.490 | 2400/F(KHz) | 300 |
| 0.490~1.705 | 24000/F(KHz) | 30 |
| 1.705~30.0 | 30 | 30 |
| 30~88 | 100 | 3 |
| 88~216 | 150 | 3 |
| 216~960 | 200 | 3 |
| 960~1000 | 500 | 3 |

| Frequency (MHz) | dB(uV/m) (at 3 meters) | |
|-----------------|------------------------|---------|
| | Peak | Average |
| Above 1000 | 74 | 54 |


Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission Level (dBuV/m)=20log Emission Level (uV/m).


Test Configuration



Below 30MHz Test Setup



30-1000MHz Test Setup



Above 1GHz Test Setup

Test Procedure

1. The EUT was setup and tested according to ANSI C63.10:2013
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Below 1 GHz:
RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - (3) From 1 GHz to 10th harmonic:
RBW=1MHz, VBW=3MHz Peak detector for Peak value.
RBW=1MHz, VBW=3MHz RMS detector for Average value.

Test Mode

Please refer to the clause 2.4.

Test Result

9 KHz~30 MHz

From 9 KHz to 30 MHz: Conclusion: PASS


Note:

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Pre-scan all antenna, only show the test data for worse case antenna on the test report.



30MHz-1GHz

| | |
|------------|-----------------------------|
| Ant. Pol. | Horizontal |
| Test Mode: | ANT1 802.11b Mode 2412MHz |
| Remark: | Only worse case is reported |




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1 | 118.2700 | 39.39 | -17.80 | 21.59 | 43.50 | -21.91 | QP |
| 2 | 141.8733 | 50.53 | -19.92 | 30.61 | 43.50 | -12.89 | QP |
| 3 * | 175.1767 | 54.81 | -18.33 | 36.48 | 43.50 | -7.02 | QP |
| 4 | 397.9533 | 41.87 | -11.12 | 30.75 | 46.00 | -15.25 | QP |
| 5 | 792.0967 | 36.35 | -4.24 | 32.11 | 46.00 | -13.89 | QP |
| 6 | 995.1500 | 38.33 | -1.71 | 36.62 | 54.00 | -17.38 | QP |

Remarks:

- Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
- Margin value = Level -Limit value



| | |
|------------|-----------------------------|
| Ant. Pol. | Vertical |
| Test Mode: | ANT1 802.11b Mode 2412MHz |
| Remark: | Only worse case is reported |



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1 | 118.5933 | 45.44 | -17.85 | 27.59 | 43.50 | -15.91 | QP |
| 2 | 141.2267 | 54.54 | -19.95 | 34.59 | 43.50 | -8.91 | QP |
| 3 * | 174.8533 | 53.33 | -18.34 | 34.99 | 43.50 | -8.51 | QP |
| 4 | 224.6467 | 45.89 | -15.36 | 30.53 | 46.00 | -15.47 | QP |
| 5 | 397.9533 | 42.68 | -11.12 | 31.56 | 46.00 | -14.44 | QP |
| 6 | 792.0967 | 37.54 | -4.24 | 33.30 | 46.00 | -12.70 | QP |

Remarks:


1. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor

2. Margin value = Level - Limit value



Adobe 1GHz

| | |
|------------|--|
| Ant. Pol. | Horizontal |
| Test Mode: | TX B Mode 2412MHz |
| Remark: | No report for the emission which more than 20 dB below the prescribed limit. |



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1 * | 4823.954 | 54.43 | -3.44 | 50.99 | 54.00 | -3.01 | AVG |
| 2 | 4823.990 | 57.36 | -3.44 | 53.92 | 74.00 | -20.08 | peak |

Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor
2. Margin value = Level - Limit value



| | |
|------------|--|
| Ant. Pol. | Vertical |
| Test Mode: | TX B Mode 2412MHz |
| Remark: | No report for the emission which more than 20 dB below the prescribed limit. |

120.0 dBuV/m

</



| | |
|------------|--|
| Ant. Pol. | Horizontal |
| Test Mode: | TX B Mode 2437MHz |
| Remark: | No report for the emission which more than 20 dB below the prescribed limit. |


120.0 dBuV/m



| | |
|------------|--|
| Ant. Pol. | Vertical |
| Test Mode: | TX B Mode 2437MHz |
| Remark: | No report for the emission which more than 20 dB below the prescribed limit. |

120.0 dBuV/m

1000.000






| | |
|------------|--|
| Ant. Pol. | Vertical |
| Test Mode: | TX B Mode 2462MHz |
| Remark: | No report for the emission which more than 20 dB below the prescribed limit. |


120.0 dBuV/m

1000.000





| | |
|------------|--|
| Ant. Pol. | Vertical |
| Test Mode: | TX G Mode 2412MHz |
| Remark: | No report for the emission which more than 20 dB below the prescribed limit. |





| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1 * | 4823.528 | 41.19 | -3.44 | 37.75 | 54.00 | -16.25 | AVG |
| 2 | 4824.007 | 55.01 | -3.44 | 51.57 | 74.00 | -22.43 | peak |

Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor

2. Margin value = Level - Limit value








| | |
|------------|--|
| Ant. Pol. | Horizontal |
| Test Mode: | TX G Mode 2462MHz |
| Remark: | No report for the emission which more than 20 dB below the prescribed limit. |


120.0 dBuV/m

<





| | |
|------------|--|
| Ant. Pol. | Horizontal |
| Test Mode: | TX N20 Mode 2412MHz |
| Remark: | No report for the emission which more than 20 dB below the prescribed limit. |




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1 | 4823.424 | 57.77 | -3.44 | 54.33 | 74.00 | -19.67 | peak |
| 2 * | 4823.508 | 43.71 | -3.44 | 40.27 | 54.00 | -13.73 | AVG |

Remarks:


1. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor

2. Margin value = Level - Limit value





| | |
|------------|--|
| Ant. Pol. | Horizontal |
| Test Mode: | TX N20 Mode 2437MHz |
| Remark: | No report for the emission which more than 20 dB below the prescribed limit. |





| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1 | 4873.977 | 56.43 | -3.31 | 53.12 | 74.00 | -20.88 | peak |
| 2 * | 4874.016 | 41.97 | -3.31 | 38.66 | 54.00 | -15.34 | AVG |

Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor

2. Margin value = Level - Limit value







| | |
|------------|--|
| Ant. Pol. | Vertical |
| Test Mode: | TX N20 Mode 2462MHz |
| Remark: | No report for the emission which more than 20 dB below the prescribed limit. |

120.0 dBuV/m

1000.000 (MHz) 26000.00

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1 * | 4924.166 | 38.60 | -3.20 | 35.40 | 54.00 | -18.60 | AVG |
| 2 | 4924.179 | 53.10 | -3.20 | 49.90 | 74.00 | -24.10 | peak |

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

3.3. Band Edge Emissions (Radiated)


Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d)/ RSS 247 5.5:

| Restricted Frequency Band (MHz) | (dBuV/m)(at 3m) | |
|---------------------------------|-----------------|---------|
| | Peak | Average |
| 2310 ~2390 | 74 | 54 |
| 2483.5 ~2500 | 74 | 54 |

Conducted band edge limit: The highest point of the operating frequency waveform down 20dB

Test Configuration



Test Procedure

1. The EUT was setup and tested according to ANSI C63.10:2013 requirements.
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.
5. The receiver set as follow:
RBW=1MHz, VBW=3MHz Peak detector for Peak value.
RBW=1MHz, VBW see note 1 with Peak Detector for Average Value.

Note 1: For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements.

2: Duty Cycle> 98%, VBW=10Hz.


Test Mode


Please refer to the clause 2.4.


Test Results





(1) Radiation Test



































3.4. Band edge and Spurious Emissions (Conducted)

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

Test Configuration



Test Procedure

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
RBW = 100 kHz, VBW ≥ RBW, scan up through 10th harmonic.
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

Test Mode

Please refer to the clause 2.4.


Test Results

(1) Band edge Conducted Test

| TestMode | Antenna | ChName | Channel | RefLevel[dBm] | Result[dBm] | Limit[dBm] | Verdict |
|-----------|---------|--------|---------|---------------|-------------|------------|---------|
| 11B | Ant1 | Low | 2412 | 6.03 | -44.06 | <=-13.97 | PASS |
| | | High | 2462 | 10.12 | -52.21 | <=-9.89 | PASS |
| 11G | Ant1 | Low | 2412 | 4.45 | -29 | <=-15.55 | PASS |
| | | High | 2462 | 4.28 | -45.72 | <=-15.73 | PASS |
| 11N20SISO | Ant1 | Low | 2412 | 4.01 | -29.53 | <=-15.99 | PASS |
| | | High | 2462 | 3.99 | -41 | <=-16.02 | PASS |



Test plot as follows:



CTC Laboratories, Inc.


1-2/F, Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011

Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn



11N20SISO_Ant1_Low_2412



11N20SISO_Ant1_High_2462



CTC Laboratories, Inc.

1-2/F, Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011

Http://www.sz-ctc.org.cn


For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn

**(2) Conducted Spurious Emissions Test**

| TestMode | Antenna | Channel | FreqRange [Mhz] | RefLevel [dBm] | Result [dBm] | Limit [dBm] | Verdict |
|-----------|---------|---------|-----------------|----------------|--------------|-------------|---------|
| 11B | Ant1 | 2412 | Reference | 6.32 | 6.32 | --- | PASS |
| | | | 30~1000 | 6.32 | -61.25 | <=-13.68 | PASS |
| | | | 1000~26500 | 6.32 | -40.75 | <=-13.68 | PASS |
| | | 2437 | Reference | 6.04 | 6.04 | --- | PASS |
| | | | 30~1000 | 6.04 | -61.1 | <=-13.96 | PASS |
| | | | 1000~26500 | 6.04 | -42.2 | <=-13.96 | PASS |
| | | 2462 | Reference | 8.77 | 8.77 | --- | PASS |
| | | | 30~1000 | 8.77 | -60.51 | <=-11.23 | PASS |
| | | | 1000~26500 | 8.77 | -39.71 | <=-11.23 | PASS |
| 11G | Ant1 | 2412 | Reference | 4.17 | 4.17 | --- | PASS |
| | | | 30~1000 | 4.17 | -59.8 | <=-15.83 | PASS |
| | | | 1000~26500 | 4.17 | -47.9 | <=-15.83 | PASS |
| | | 2437 | Reference | 4.66 | 4.66 | --- | PASS |
| | | | 30~1000 | 4.66 | -60.27 | <=-15.34 | PASS |
| | | | 1000~26500 | 4.66 | -49.35 | <=-15.34 | PASS |
| | | 2462 | Reference | 3.34 | 3.34 | --- | PASS |
| | | | 30~1000 | 3.34 | -60.87 | <=-16.66 | PASS |
| | | | 1000~26500 | 3.34 | -48.74 | <=-16.66 | PASS |
| 11N20SISO | Ant1 | 2412 | Reference | 4.03 | 4.03 | --- | PASS |
| | | | 30~1000 | 4.03 | -60.57 | <=-15.97 | PASS |
| | | | 1000~26500 | 4.03 | -48.72 | <=-15.97 | PASS |
| | | 2437 | Reference | 4.34 | 4.34 | --- | PASS |
| | | | 30~1000 | 4.34 | -59.98 | <=-15.66 | PASS |
| | | | 1000~26500 | 4.34 | -49.53 | <=-15.66 | PASS |
| | | 2462 | Reference | 3.65 | 3.65 | --- | PASS |
| | | | 30~1000 | 3.65 | -60.75 | <=-16.35 | PASS |
| | | | 1000~26500 | 3.65 | -48.5 | <=-16.35 | PASS |



Test plot as follows:



CTC Laboratories, Inc.



1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011

Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn



CTC Laboratories, Inc.



1-2/F, Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011

Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn



CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059


Fax: (86)755-27521011

Http://www.sz-ctc.org.cn


For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn



11G_Ant1_2412_30~1000



11G_Ant1_2412_1000~26500



11G_Ant1_2437_0~Reference

CTC Laboratories, Inc.




1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011

Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn



CTC Laboratories, Inc.


1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011


Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn






11N20SISO_Ant1_2412_30~1000



11N20SISO_Ant1_2412_1000~26500



11N20SISO_Ant1_2437_0~Reference

CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059


Fax: (86)755-27521011

Http://www.sz-ctc.org.cn


For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn



11N20SISO_Ant1_2437_30~1000



11N20SISO_Ant1_2437_1000~26500



11N20SISO_Ant1_2462_0~Reference

CTC Laboratories, Inc.


1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011

Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn



CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011

Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn