






HID Global Corporation HDP5000e Model X002700 Antenna Specifications

Gain Declaration for LF and HF Inductive Loop Antennas


| Frequency | 125kHz, 13.56MHz |
|-----------|------------------|
| Gain | 1.0 dBi |

Radiation Patterns: Horizontal



Radiation Patterns: Vertical

Vertical Plane Radiation Pattern





FREE +1 800 237 7769 MAIN +1 512 776 9000



Antenna Specifications

OMNIKEY 5122 (optional)

Frequency: 13.56MHz

Gain: 1dBi

Dimensions: 58mm x 70mm



OMNIKEY 5127SI (optional)

Frequency: 13.56MHz

Gain: 1dBi

Dimensions: 54mm x 39mm





FREE +1 800 237 7769 MAIN +1 512 776 9000



OMNIKEY 5127SI (optional)

Frequency:125kHz

Gain: 1dBi

Dimensions: 54mm x 65mm




Ribbon RFID (included in Printer)

Frequency: 13.56MHz

Gain: 1dBi

Dimensions: 38mm








Film RFID (included in Printer)

Frequency: 13.56MHz

Gain: 1dBi

Dimensions: 38mm



Contact Name: Steven Peterson

Signature:

Manager Product Regulatory and Compliance, Global Product Compliance Tel 952-258-3411

steven.peterson@hidglobal.com