


FCC Co-Location Test Report

FCC ID : I88WX3310-B0
Equipment : Dual-Band Wireless AX Gigabit Access Point / Extender
Model No. : WX3310-B0
Brand Name : ZYXEL
Applicant : Zyxel Communications Corporation
Address : No.2 Industry East RD. IX, Hsinchu Science Park,
Hsinchu 30075, Taiwan, R.O.C
Standard : 47 CFR FCC Part 15.247
47 CFR FCC Part 15.407
Received Date : Feb. 03, 2020
Tested Date : Apr. 28 ~ May 21, 2020

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:


Along Chen / Assistant Manager

Approved by:



Gary Chang / Manager



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	The Equipment List	6
1.3	Test Standards	7
1.4	Deviation from Test Standard and Measurement Procedure.....	7
1.5	Measurement Uncertainty	7
2	TEST CONFIGURATION	8
2.1	Testing Condition	8
2.2	The Worst Test Modes and Channel Details	8
3	TRANSMITTER TEST RESULTS.....	9
3.1	Unwanted Emissions into Restricted Frequency Bands	9
4	TEST LABORATORY INFORMATION	16

Release Record

Report No.	Version	Description	Issued Date
FR020306CO	Rev. 01	Initial issue	Jun. 02, 2020

Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.247(d) 15.407(b) 15.209	Radiated Emissions	[dBuV/m at 3m]:41.64MHz 34.96 (Margin -5.04dB) - QP	Pass

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

WLAN	
Operating Frequency	2412 MHz ~ 2462 MHz 5180 MHz ~ 5240 MHz 5260 MHz ~ 5320 MHz 5500 MHz ~ 5720 MHz 5745 MHz ~ 5825 MHz
Modulation Type	802.11b: DSSS (DBPSK / DQPSK / CCK) 802.11a/g/n/ac/ax: BPSK / QPSK / 16QAM / 64QAM / 256QAM / 1024 QAM

1.1.2 Antenna Details

Ant. No.	Model	Type	Connector	Operating Frequencies (MHz) / Antenna Gain (dBi)				
				2400~2483.5	5150~5250	5250~5350	5470~5725	5725~5850
1	Ant1 (RFPCA242309IMLB901)	PIFA	ipex	0	0.5	1	1.5	1.75
2	Ant2 (RFPCA242311IMLB901)	PIFA	ipex	0	0.5	1	1.5	1.75
3	Ant3 (RFPCA221116IM5B901)	Dipole	ipex	--	0.5	1	1.5	1.75
4	Ant4 (RFPCA232007IMLB901)	Dipole	ipex	--	0.5	1	1.5	1.75

1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	12Vdc from AC adapter
-------------------	-----------------------

1.1.4 Accessories

Accessories		
No.	Equipment	Description
1	AC adapter	Brand: MNC Model: MAUS-1201501801 I/P: 100-240Vac, 50/60Hz, 0.5A O/P: 12Vdc, 1.5A Power Line: DC 1.5m non-shielded without core
2	RJ45 cable	1.5m non-shielded without core

1.2 The Equipment List

Test Item	Radiated Emission				
Test Site	966 chamber1 / (03CH01-WS)				
Tested Date	Apr. 28 ~ Apr. 30, 2020				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101498	Dec. 17, 2019	Dec. 16, 2020
Receiver	R&S	ESR3	101658	Dec. 12, 2019	Dec. 11, 2020
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Jul. 12, 2019	Jul. 11, 2020
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Dec. 12, 2019	Dec. 11, 2020
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 15, 2019	Nov. 14, 2020
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 13, 2019	Nov. 12, 2020
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Oct. 07, 2019	Oct. 06, 2020
Preamplifier	EMC	EMC02325	980225	Jul. 09, 2019	Jul. 08, 2020
Preamplifier	Agilent	83017A	MY39501308	Oct. 08, 2019	Oct. 07, 2020
Preamplifier	EMC	EMC184045B	980192	Aug. 01, 2019	Jul. 31, 2020
RF Cable	EMC	EMC104-SM-SM-80 00	181106	Oct. 07, 2019	Oct. 06, 2020
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Oct. 07, 2019	Oct. 06, 2020
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Oct. 07, 2019	Oct. 06, 2020
LF cable 1M	EMC	EMCCFD400-NM-N M-1000	160502	Oct. 07, 2019	Oct. 06, 2020
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Oct. 07, 2019	Oct. 06, 2020
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-002	Oct. 07, 2019	Oct. 06, 2020
Measurement Software	AUDIX	e3	6.120210g	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Test Date	May 21, 2020				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101063	Apr. 30, 2020	Apr. 29, 2021
Power Meter	Anritsu	ML2495A	1241002	Oct. 23, 2019	Oct. 22, 2020
Power Sensor	Anritsu	MA2411B	1207366	Oct. 23, 2019	Oct. 22, 2020
AC POWER SOURCE	APC	AFC-500W	F312060012	Dec. 02, 2019	Dec. 01, 2020
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

1.3 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247

47 CFR FCC Part 15.407

ANSI C63.10-2013

FCC KDB 558074 D01 15.247 Meas Guidance v05r02

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01

FCC KDB 412172 D01 Determining ERP and EIRP v01r01

1.4 Deviation from Test Standard and Measurement Procedure

None

1.5 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Measurement Uncertainty	
Parameters	Uncertainty
Radiated emission $\leq$ 1GHz	± 3.41 dB
Radiated emission $>$ 1GHz	± 4.59 dB

2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
Radiated Emissions	03CH01-WS	23-24°C / 65%	Akun Chung
Conducted Emissions	TH01-WS	22°C / 63%	Alex Huang

- FCC Designation No.: TW0009
- FCC site registration No.: 207696
- ISSED#: 10807A
- CAB identifier: TW2732

2.2 The Worst Test Modes and Channel Details

Test item	Modulation Mode	Test Channel	Data Rate	Test Configuration
Radiated Emissions ≤1GHz	2.4GHz 11g + 5GHz 11a	CH06 + CH149	6 Mbps +6 Mbps	---
Radiated Emissions >1GHz				---
Conducted Emissions				---
Note: The selected channel is the maximum power channel of WiFi mode				

3 Transmitter Test Results

3.1 Unwanted Emissions into Restricted Frequency Bands

3.1.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Qusai-Peak value is measured for frequency below 1GHz except for 9~90 kHz, 110~490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.1.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m.
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

3.1.3 Test Setup


Radiated Emissions below 1 GHz



Radiated Emissions above 1 GHz




Transmitter Conducted Unwanted Emissions (30MHz~40GHz)



3.1.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	2.4GHz 11g + 5GHz 11a			Test Channel			CH06 + CH149																																																																								
Polarization	Horizontal																																																																														
Level (dBuV/m) <table><thead><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr></thead><tbody><tr><td>1</td><td>38.73</td><td>28.31</td><td>40.00</td><td>-11.69</td><td>37.07</td><td>-8.76</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>2</td><td>67.83</td><td>24.78</td><td>40.00</td><td>-15.22</td><td>34.74</td><td>-9.96</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>124.09</td><td>35.60</td><td>43.50</td><td>-7.90</td><td>45.87</td><td>-10.27</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>4</td><td>171.62</td><td>29.89</td><td>43.50</td><td>-13.61</td><td>38.88</td><td>-8.99</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>240.49</td><td>25.78</td><td>46.00</td><td>-20.22</td><td>35.95</td><td>-10.17</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>6</td><td>304.51</td><td>28.44</td><td>46.00</td><td>-17.56</td><td>36.33</td><td>-7.89</td><td>Peak</td><td>---</td><td>---</td></tr></tbody></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	38.73	28.31	40.00	-11.69	37.07	-8.76	Peak	---	---	2	67.83	24.78	40.00	-15.22	34.74	-9.96	Peak	---	---	3	124.09	35.60	43.50	-7.90	45.87	-10.27	Peak	---	---	4	171.62	29.89	43.50	-13.61	38.88	-8.99	Peak	---	---	5	240.49	25.78	46.00	-20.22	35.95	-10.17	Peak	---	---	6	304.51	28.44	46.00	-17.56	36.33	-7.89	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																						
1	38.73	28.31	40.00	-11.69	37.07	-8.76	Peak	---	---																																																																						
2	67.83	24.78	40.00	-15.22	34.74	-9.96	Peak	---	---																																																																						
3	124.09	35.60	43.50	-7.90	45.87	-10.27	Peak	---	---																																																																						
4	171.62	29.89	43.50	-13.61	38.88	-8.99	Peak	---	---																																																																						
5	240.49	25.78	46.00	-20.22	35.95	-10.17	Peak	---	---																																																																						
6	304.51	28.44	46.00	-17.56	36.33	-7.89	Peak	---	---																																																																						
Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m). Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.																																																																															

Modulation	2.4GHz 11g + 5GHz 11a	Test Channel	CH06 + CH149
Polarization	Vertical		



The spectrum plot displays the emission level in dBUV/m across a frequency range from 30 MHz to 1000 MHz. The y-axis ranges from 0 to 90 dBUV/m. A red line represents the FCC CLASS-B limit, which is 40 dBUV/m from 30 to 100 MHz, 43.5 dBUV/m from 100 to 300 MHz, 46 dBUV/m from 300 to 1000 MHz, and 75 dBUV/m above 1000 MHz. A blue line shows the measured emission level, with six specific peaks labeled 1 through 6. The peaks are at 41.64 MHz, 74.62 MHz, 122.15 MHz, 173.56 MHz, 279.29 MHz, and 442.25 MHz. The emission level is generally below the limit, with a margin of at least 4.23 dB at the highest peak.


	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	41.64	34.96	40.00	-5.04	43.36	-8.40	QP	103	185
2	74.62	33.78	40.00	-6.22	45.34	-11.56	Peak	---	---
3	122.15	35.35	43.50	-8.15	45.73	-10.38	Peak	---	---
4	173.56	30.31	43.50	-13.19	39.51	-9.20	Peak	---	---
5	279.29	27.18	46.00	-18.82	35.85	-8.67	Peak	---	---
6	442.25	31.10	46.00	-14.90	35.33	-4.23	Peak	---	---


Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.



3.1.5 Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation	2.4GHz 11g + 5GHz 11a			Test Channel	CH06 + CH149																																																						
Polarization	Horizontal																																																										
 <table> <tr> <th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr> <tr> <td>1</td><td>3308.00</td><td>42.07</td><td>54.00</td><td>-11.93</td><td>43.20</td><td>-1.13</td><td>Average</td><td>202</td><td>255</td></tr> <tr> <td>2</td><td>3308.00</td><td>53.08</td><td>74.00</td><td>-20.92</td><td>54.21</td><td>-1.13</td><td>Peak</td><td>202</td><td>255</td></tr> <tr> <td>3</td><td>8182.00</td><td>47.56</td><td>54.00</td><td>-6.44</td><td>37.70</td><td>9.86</td><td>Average</td><td>200</td><td>30</td></tr> <tr> <td>4</td><td>8182.00</td><td>58.06</td><td>74.00</td><td>-15.94</td><td>48.20</td><td>9.86</td><td>Peak</td><td>200</td><td>30</td></tr> </table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	3308.00	42.07	54.00	-11.93	43.20	-1.13	Average	202	255	2	3308.00	53.08	74.00	-20.92	54.21	-1.13	Peak	202	255	3	8182.00	47.56	54.00	-6.44	37.70	9.86	Average	200	30	4	8182.00	58.06	74.00	-15.94	48.20	9.86	Peak	200	30
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																		
1	3308.00	42.07	54.00	-11.93	43.20	-1.13	Average	202	255																																																		
2	3308.00	53.08	74.00	-20.92	54.21	-1.13	Peak	202	255																																																		
3	8182.00	47.56	54.00	-6.44	37.70	9.86	Average	200	30																																																		
4	8182.00	58.06	74.00	-15.94	48.20	9.86	Peak	200	30																																																		
Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).																																																											

Modulation	2.4GHz 11g + 5GHz 11a				Test Channel	CH06 + CH149																																																					
Polarization	Vertical																																																										
 <table> <tr> <th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr> <tr> <td>1</td><td>3308.00</td><td>41.62</td><td>54.00</td><td>-12.38</td><td>42.75</td><td>-1.13</td><td>Average</td><td>159</td><td>160</td></tr> <tr> <td>2</td><td>3308.00</td><td>53.54</td><td>74.00</td><td>-20.46</td><td>54.67</td><td>-1.13</td><td>Peak</td><td>159</td><td>160</td></tr> <tr> <td>3</td><td>8182.00</td><td>45.62</td><td>54.00</td><td>-8.38</td><td>35.76</td><td>9.86</td><td>Average</td><td>180</td><td>10</td></tr> <tr> <td>4</td><td>8182.00</td><td>56.90</td><td>74.00</td><td>-17.10</td><td>47.04</td><td>9.86</td><td>Peak</td><td>180</td><td>10</td></tr> </table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	3308.00	41.62	54.00	-12.38	42.75	-1.13	Average	159	160	2	3308.00	53.54	74.00	-20.46	54.67	-1.13	Peak	159	160	3	8182.00	45.62	54.00	-8.38	35.76	9.86	Average	180	10	4	8182.00	56.90	74.00	-17.10	47.04	9.86	Peak	180	10
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																		
1	3308.00	41.62	54.00	-12.38	42.75	-1.13	Average	159	160																																																		
2	3308.00	53.54	74.00	-20.46	54.67	-1.13	Peak	159	160																																																		
3	8182.00	45.62	54.00	-8.38	35.76	9.86	Average	180	10																																																		
4	8182.00	56.90	74.00	-17.10	47.04	9.86	Peak	180	10																																																		
Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).																																																											

3.1.6 Conducted Emissions (30MHz~40GHz)

Conducted Emission Plots



4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin
Kou District, New Taipei City,
Taiwan, R.O.C.

Kwei Shan

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd St.,
Kwei Shan District, Tao Yuan City
333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd
St., Kwei Shan District, Tao Yuan
City 333, Taiwan, R.O.C..

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==