

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: 2BLHD-QF100

EUT Specification

EUT	Sound Box
Frequency band (Operating)	<input checked="" type="checkbox"/> WIFI: 2.412GHz-2.462GHz <input checked="" type="checkbox"/> LTE Band 2: TX 1850MHz -1910MHz, RX 1930MHz -1990MHz <input checked="" type="checkbox"/> LTE Band 4: TX 1710MHz -1755MHz, RX 2110MHz -2155MHz <input checked="" type="checkbox"/> LTE Band 5: TX 824MHz -849MHz, RX 869MHz -894MHz <input checked="" type="checkbox"/> LTE Band 7: TX 2500MHz -2570MHz, RX 2620MHz -2690MHz
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation)
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure ($S = 5\text{mW}/\text{cm}^2$) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure ($S=1\text{mW}/\text{cm}^2$)
Antenna diversity	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
Max. output power	2.4G WIFI 802.11b: 16.88 dBm 802.11g: 15.43 dBm 802.11n HT20: 14.32 dBm LTE Band 2: 24.00 dBm LTE Band 4: 22.93 dBm LTE Band 5: 21.75 dBm LTE Band 7: 19.92 dBm
Antenna gain (Max)	2.4G WIFI: -0.58 dBi LTE Band 2: 2.46 dBi LTE Band 4: -0.92 dBi LTE Band 5: 0.09 dBi LTE Band 7: 2.37 dBi
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $P_d=(P_{out}*G)/(4*\pi*R^2)$

Where

P_d = Power density in mW/cm², P_{out} =output power to antenna in mW.

G= gain of antenna in linear scale, π =3.1416

R= distance between observation point and center of the radiator in cm=20cm

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

For multiple RF sources: Multiple RF sources are exempt if:

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation

$$\sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Evaluated_k: the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

Exposure Limit_k: either the general population/uncontrolled maximum permissible exposure (MPE) or specific Absorption rate (SAR) limit for each fixed, mobile, or portable RF source k.

Measurement Result

4G:

Mode	Max Measured Power (dBm)	Tune up tolerance (dBm)	Max tune up conducted power(dBm)	Output Peak power (mW)	Ant. Gain (dBi)	Ant. Gain (numeric)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
LTE Band 2	24.00	24 ± 1	25	316.228	2.46	1.762	0.11085	1
LTE Band 4	22.93	22 ± 1	23	199.526	-0.92	0.809	0.03212	1
LTE Band 5	21.75	21 ± 1	22	158.489	0.09	1.021	0.03219	0.55
LTE Band 7	19.92	19 ± 1	20	100.000	2.37	1.726	0.03433	1

2.4G WIFI:

Mode	Max Measured Power (dBm)	Tune up tolerance (dBm)	Max tune up conducted power(dBm)	Output Peak power (mW)	Ant. Gain (dBi)	Ant. Gain (numeric)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
802.11b	16.88	16 ± 1	17	50.119	-0.58	0.875	0.00872	1
802.11g	15.43	15 ± 1	16	39.811	-0.58	0.875	0.00693	1
802.11n HT20	14.32	14 ± 1	15	31.623	-0.58	0.875	0.00550	1

Maximum Simultaneous transmission MPE Ratio for 4G & 2.4G WIFI

Maximum MPE ratio (4G)	Maximum MPE ratio (2.4G WIFI)	Σ MPE ratios	Limit	Results
0.11085	0.00872	0.11957	1.000	Pass

Signature:



Shawn Wen

Date: 2025-4-1