



Test Report

Product	Bluetooth Low Energy Transceiver
Name and address of the applicant	LEGO System A/S Aastvej 1, 7190 Billund, Denmark
Name and address of the manufacturer	LEGO System A/S Aastvej 1, 7190 Billund, Denmark
Model	LEAF No.1
Rating	3Vdc (Primary Batteries)
Trademark	LEGO
Serial number	See page 3
Additional information	This tested device can be operated with BLE.
Tested according to	FCC Part 15.247 Frequency Hopping Transmitters / Digital Transmission Systems Industry Canada RSS-247, Issue 2 Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices
Order number	386635
Tested in period	2019.12.05 – 2019.12.10
Issue date	2020.01.10
Name and address of the testing laboratory	 Instituttveien 6 Kjeller, Norway CAB Number: FCC: NO0001 ISED: NO0470 TEL: +47 22 96 03 30 FAX: +47 22 96 05 50   An accredited technical test executed under the Norwegian accreditation scheme
 Prepared by [G.Suhanthakumar]  Approved by [Frode Sveinsen]	
This report shall not be reproduced except in full without the written approval of Nemko. Opinions and interpretations expressed within this report are not part of the current accreditation. This report was originally distributed electronically with digital signatures. For more information contact Nemko.	

CONTENTS

1	INFORMATION	3
1.1	Test Item.....	3
1.2	Normal test condition.....	4
1.3	Test Engineer(s)	4
1.4	Description of modification for Modification Filing	4
1.5	Family List Rational	4
1.6	Antenna Requirement.....	4
1.7	Worst-Case Configuration and Mode	4
1.8	Comments	4
2	TEST REPORT SUMMARY	5
2.1	General.....	5
2.2	Test Summary	6
3	TEST RESULTS.....	7
3.1	Number of Frequencies	7
3.2	Power Line Conducted Emissions.....	8
3.3	99% Occupied Bandwidth	9
3.4	DTS Bandwidth (6 dB BW)	13
3.5	Peak Power Output	16
3.6	Conducted Emissions at Antenna Connector	22
3.7	Restricted Bands of operation	26
3.8	Spurious Emissions (Radiated)	27
3.9	Power Spectral Density (PSD).....	42
4	Measurement Uncertainty.....	46
5	LIST OF TEST EQUIPMENT	47
6	BLOCK DIAGRAM.....	48
6.1	Power Line Conducted Emission.....	48
6.2	Test Site Radiated Emission	48

1 INFORMATION

1.1 Test Item

Name	LEGO
FCC ID	NPI49242
ISED ID	3072A-49242
Model/version	LEAF No.1
Serial number	Radiated sample : "A" Conducted sample: "B"
Hardware identity and/or version	PCBA revision J
Software identity and/or version	1.0.00
Frequency Range	2402 – 2480 MHz
Tunable Bands	None
Number of Channels	40
Operating Modes	TX and RX
Measured BW (99%)	2.1 MHz
Emission clasification	F1D
Transmitter spurious, dBµV/m@3m	50.63 (2.4835GHz), PK
Type of Modulation	GFSK
User Frequency Adjustment	None
Conducted Output Power, Max	0.00041 W (-3.82dBm)
Type of Power Supply	3.0Vdc (2x 1.5Vdc AAA batteries)
Antenna Connector	Only integral antenna
Number of Antennas	1
Diversity or Smart Antennas	None
Desktop Charger	N/A

Description of Test Item

The device tested is a construction toy which controls arms, legs and remotely control via BLE with remote device such as iOS, Android or similar.

1.2 Normal test condition

Temperature: 20 - 24 °C
Relative humidity: 20 - 50 %
Normal test voltage: 3.0Vdc

The values are the limit registered during the test period.

1.3 Test Engineer(s)

G.Suhanthakumar

1.4 Description of modification for Modification Filing

Not applicable.

1.5 Family List Rational

Not Applicable.

1.6 Antenna Requirement

Is the antenna detachable?

☐ Yes ☒ No

If detachable, is the antenna connector non-standard?

☐ Yes ☐ No

Type of antenna connector: N/A

Ref. FCC §15.203

1.7 Worst-Case Configuration and Mode

Radiated Emissions were performed with the EUT set to transmit at the channel with the highest output power as worst-case scenario.

1.8 Comments

All measurements were done with the EUT powered by a fully charged battery.

No ports to populate.

2 TEST REPORT SUMMARY

2.1 General

All measurements are traceable to national standards.

The tests were conducted for demonstrating compliance with FCC CFR 47 Part 15, paragraph 15.247 and ISED Canada RSS-247 Issue 2 and RSS-GEN Issue 5.

Tests were performed in accordance with ANSI C63.4-2014 and ANSI C63.10-2013.

Radiated tests were made in a semi-anechoic chamber at measuring distances of 1m, 3m and 10m.

A description of the test facility is on file with FCC and ISED.

☒ New Submission

☒ Production Unit

☐ Class II Permissive Change

☐ Pre-production Unit

DTS Equipment Code

☐ Family Listing



THIS TEST REPORT APPLIES ONLY TO THE ITEM(S) AND CONFIGURATIONS TESTED.

Deviations from, additions to, or exclusions from the test specifications are described in "Summary of Test Data".

Nemko Group authorizes the above named entity to reproduce this report provided it is reproduced in its entirety and for use by the entity's employees only. Any reproduction of parts of this report requires approval in writing from Nemko Group.

Any use that a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Group accepts no responsibility for damages suffered by any third party caused by decisions made or actions based on this report.

2.2 Test Summary

Name of test	FCC Part 15 reference	RSS-247 Issue 2, RSS-GEN Issue 5 reference	Result
Supply Voltage Variations	15.31(e)	6.11 (RSS-GEN)	N/A ¹
Number of frequencies	15.31(m)	6.8 (RSS-GEN)	Complies
Antenna Requirement	15.203	6.8 (RSS-GEN)	Complies ²
Power Line Conducted Emission	15.107(a) 15.207(a)	7.2 / 8.8 (RSS-GEN)	N/A ¹
99% Occupied Bandwidth	N/A	6.7 (RSS-GEN)	Complies
DTS Bandwidth	15.247(a)(2)	5.2 (1) (RSS-247)	Complies
Peak Power Output	15.247(b)	5.4 (RSS-247)	Complies
Power Spectral Density	15.247(e)	5.2 (2) (RSS-247)	Complies
Spurious Emissions (Antenna Conducted)	15.247(c)(d)	5.5 (RSS-247)	Complies
Spurious Emissions (Radiated)	15.247(c)(d) 15.109(a) 15.209(a)	5.5 (RSS-247) 7.3 (RSS-GEN) 8.9 (RSS-GEN)	Complies

¹ The tested equipment only operates with battery.

² Integral antenna.

-Only for information

3 TEST RESULTS

3.1 Number of Frequencies

FCC Part 15.31 (m)

RSS-Gen 6.8

Authorized Band:	2400 - 2483.5 MHz
Frequency band width:	83.5MHz
Low Channel:	2402MHz
Mid channel:	2440MHz
High Channel:	2480MHz

3.2 Power Line Conducted Emissions

FCC Part 15.207

ISED RSS-GEN Issue 5, Clause 7.2 / 8.8

Measurement procedure: ANSI C63.4-2014 using 50 μ H/50 ohms LISN

Test Results: N/A

Measurement Data:

3.3 99% Occupied Bandwidth

RSS-Gen, 6.7

ISED Canada RSS-247 Issue 2, Clause 5.1

ISED Canada RSS-GEN Issue 5, Clause 6.7

Measurement procedure: ANSI C63.10-2013 Clause 6.9.2 / 7.8.3

Test Results: Complies

Measurement Data:

Channel Frequency (MHz)	Measured 99% BW (MHz)
2402	2.1
2440	2.1
2480	2.1


See attached plots.

Requirements:

Frequency hopping systems in the 2400 - 2483.5 MHz band shall use at least 15 non-overlapping channels. No requirements for bandwidth for this frequency band.


No requirements for Digital Transmission Systems.

No requirement for 99% BW, reported for information only.




Date: 7.DEC.2019 14:12:45

99% Bandwidth , ch2402MHz



Date: 7.DEC.2019 14:16:50

99% Bandwidth , ch2440MHz



Date: 7.DEC.2019 14:26:57

99% Bandwidth , ch2480MHz

3.4 DTS Bandwidth (6 dB BW)

FCC Part 15.247 (a)(2)

ISED Canada RSS-247 Issue 2, Clause 5.2 (a)

Measurement procedure: ANSI C63.10-2013 Clause 11.8

Test Results: Complies


Measurement Data:

Channel Frequency (MHz)	Measured DTS BW (MHz)
2402	1.43
2440	1.34
2480	1.42

Requirements:


For Digital Transmission Systems in the 2400-2483.5 MHz band the minimum 6 dB bandwidth shall be at least 500 KHz.

No requirements for Frequency Hopping Systems.




Date: 7.DEC.2019 14:11:31

DTS Bandwidth, ch2402MHz



Date: 7.DEC.2019 14:18:00

DTS Bandwidth, ch2440MHz



Date: 7.DEC.2019 14:25:49

6 dB Bandwidth, ch2480MHz

3.5 Peak Power Output

FCC part 15.247 (b)

ISED Canada RSS-247 Issue 2, Clause 5.4

Measurement procedure: ANSI C63.10-2013 Clause 11.9.1.2

Test Results: Complies

Measurement Data:

	2402 MHz	2440 MHz	2480 MHz
Conducted Power (dBm)	-3.82	-4.03	-4.29
Conducted Power (mWatts)	0.41	0.40	0.37
Field Strength (dBμV/m), VP	89.34	88.26	87.88
EIRP, Calculated (mWatts)	0.26	0.20	0.18
Antenna gain (dBi)	-2.1	-2.9	-3.1

Antenna gain = $10 \cdot \log(\text{EIRP} / \text{Conducted power})$ dBi

EIRP is calculated from measured field strength by the formulas in KDB 412172 D01 Determining ERP and EIRP v01.

See attached plots.

Requirements:


The maximum peak output power shall not exceed the following limits:

For frequency hopping systems employing at least 75 hopping channels: 1 Watt

For all other frequency hopping systems in the 2400 - 2483.5 MHz band: 0.125 Watts


For Digital Transmission Systems in the 2400 - 2483.5 MHz band: 1 Watt

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power from the intentional radiator shall be reduced below the stated value above by the amount in dB that the directional gain of the antenna exceeds 6 dBi.




Date: 7.DEC.2019 14:09:16

Conducted Power , Ch2402MHz




Date: 7.DEC.2019 14:18:39

Conducted Power , Ch2440MHz




Date: 7.DEC.2019 14:24:53

Conducted Power, Ch2480MHz




Date: 7.DEC.2019 12:45:41

Radiated Field strength, HP, ch2402MHz




Date: 7.DEC.2019 13:26:32

Radiated Field strength, HP, ch2440MHz




Date: 7.DEC.2019 13:06:40

Radiated Field strength, HP, ch2480MHz




Date: 7.DEC.2019 12:38:34

Radiated Field strength, VP, ch2402MHz



Date: 7.DEC.2019 13:28:18

Radiated Field strength, VP, ch2440MHz



Date: 7.DEC.2019 13:10:17

Radiated Field strength, VP, ch2480MHz

3.6 Conducted Emissions at Antenna Connector

Para. No.: 15.247 (d)

ISED Canada RSS-247 Issue 2, Clause 5.5

Measurement procedure: ANSI C63.10-2013 Clause 11.11

Test Results: Complies

Carrier Frequency	Highest Value (dBc)	Margin (dB)	Verdict
2402 MHz	40.3	>30	Pass
2440 MHz	42.8	>30	Pass
2480 MHz	47.9	>30	Pass

Measured with Peak Detector


RF conducted power to 25 GHz: see attached plots.

Limit

Peak measurement	RMS averaging
20 dBc or more in 100 kHz bandwidth	30 dBc or more in 100 kHz bandwidth


Detector type shall be the same as used for measuring Output Power.

Attenuation below the general limits specified in part 15.209(a) is not required.




Date: 7.DEC.2019 14:30:29

Conducted spurious emissions, 10MHz - 10GHz, ch2402MHz




Date: 7.DEC.2019 14:31:13

Conducted spurious emissions, 10GHz - 25GHz, ch2402MHz




Date: 7.DEC.2019 14:20:21

Conducted spurious emissions, 10MHz - 10GHz, ch2440MHz




Date: 7.DEC.2019 14:21:28

Conducted spurious emissions, 10GHz - 25GHz, ch2440MHz



Date: 7.DEC.2019 14:23:16

Conducted spurious emissions, 10MHz - 10GHz, ch2480MHz



Date: 7.DEC.2019 14:22:13

Conducted spurious emissions, 10GHz - 25GHz, ch2480MHz

3.7 Restricted Bands of operation

Restricted Bands of operation for FCC and ISSED are defined in FCC Part 15.205 and ISSED RSS-GEN, Issue 4 clause 8.10.

Generally, no fundamentals are allowed in the restricted bands and all emissions must comply with the limits in FCC 15.209 or RSS-GEN, Issue 5, clause 8.9.

FCC (MHz)	ISED (MHz)	FCC (GHz)	ISED (GHz)
0.090-0.110		0.96-1.24 1.3-1.427	0.96-1.427
0.495-0.505		1.435-1.6265	
2.1735-2.1905		1.6455-1.6465	
	3.020-3.026	1.660-1.710	
4.125-4.128		1.7188-1.7222	
4.17725-4.17775		2.2-2.3	
4.20725-4.20775		2.31-2.39	
	5.677-5.683	2.4835-2.5	
6.215-6.218		2.69-2.9	2.655-2.9
6.26775-6.26825		3.26-3.267	
6.31175-6.31225		3.332-3.339	
8.291-8.294		3.3458-3.358	
8.362-8.366		3.6-4.4	3.5-4.4
8.37625-8.38675		4.5-5.15	
8.41425-8.41475		5.35-5.46	
12.29-12.293		7.25-7.75	
12.51975-12.52025		8.025-8.5	
12.57675-12.57725		9.0-9.2	
13.36-13.41		9.3-9.5	
16.42-16.423		10.6-12.7	
16.69475-16.69525		13.25-13.4	
16.80425-16.80475		14.47-14.5	
25.5-25.67		15.35-16.2	
37.5-38.25		17.7-21.4	
73-74.6		22.01-23.12	
74.8-75.2		23.6-24.0	
108-121.94 123-138	108-138	31.2-31.8	
149.9-150.05		36.43-36.5	
156.52475-156.52525		Above 38.6	
156.7-156.9			
162.0125-167.17			
167.72-173.2			
240-285			
322-335.4			
399.9-410			
608-614			

Frequencies in **Bold** text are specific for FCC or ISSED, all other frequencies are common.

3.8 Spurious Emissions (Radiated)

FCC Part 15.209 (a)

ISED Canada RSS-GEN Issue 5, Clause 7.3 / 8.9

Measurement procedure: ANSI C63.10-2013 Clause 11.12

Test Results: Complies

Measurement Data:

Band-Edge

	Measured field strength (dBμV/m)		Limit	Margin	
	2390 MHz	2483.5 MHz	dBμV/m	dB	
Peak Detector	40.17	50.63	74	33.83	23.37
Average Detector	/	/	54	/	/
Average with DC correction	/	/	54	/	/

Worst case given in the table

See attached plots.

Duty Cycle Correction Factor Calculation:

For 0 byte payload:

Duty Cycle = On Time / (Period * Number of Channels) = $98 \mu\text{s} / (625 \mu\text{s} * 40) = 0.00392$ (0.39%)

Duty Cycle Correction factor = $-20 \times \log(\text{Duty Cycle}) = -48\text{dB}$


For 37 byte payload:

Duty Cycle = On Time / (Period * Number of Channels) = $394.4 \mu\text{s} / (628 \mu\text{s} * 40) = 0.0016$ (0.16%)


Duty Cycle Correction factor = $-20 \times \log(\text{Duty Cycle}) = -56\text{dB}$

Maximum allowed Duty Cycle Correction: 20 dB


Maximum Duty Cycle Correction Factor according to Para 15.35 (b): 20 dB



Duty cycle with 0 byte payload




Duty cycle with 37 byte payload




Date: 7.DEC.2019 12:50:16

Lower Band Edge, PK , ch2402MHz with 100% modulated signal




Date: 7.DEC.2019 13:11:16

Upper Band Edge, PK , ch2480MHz with 100% modulated signal




Date: 7.DEC.2019 13:14:37

Lower Band Edge, PK , ch2402MHz with 0 byte payload




Date: 7.DEC.2019 13:18:15

Upper Band Edge, PK , ch2480MHz with 0 byte payload



Date: 7.DEC.2019 13:21:23

Lower Band Edge, PK , ch2402MHz with 37 byte payload



Date: 7.DEC.2019 13:23:37

Upper Band Edge, PK , ch2480MHz with 37 byte payload

Radiated emission 30 – 1000 MHz.

FCC Part 15.209 (a)

ISED Canada RSS-GEN Issue 5, Clause 7.3/8.9

Measurement procedure: ANSI C63.10-2013 Clause 11.12

Test Results: Complies

Detector: Quasi-Peak

Measuring distance 3 m

Tested in TX mode

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
61.551400	12.22	40.00	27.78	1000.0	120.000	151.0	V	45.0


See attached plots

Requirements/Limit

FCC	Part 15.209 @ frequencies defined in §15.205	
ISED	RSS-GEN Issue 5, Clause 8.9 @ frequencies defined in clause 8.10	
	Radiated emission limit @3 meters	
Frequency (MHz)	Quasi Peak (μV/m)	Quasi Peak (dBμV/m)
30 – 88	100	40.0
88 – 216	150	43.5
216 – 960	200	46.0
Above 960	500	54.0

The limit above 1000 MHz is specified for Average Detector, when the measurement is performed with a Peak Detector a Duty-Cycle Correction Factor has to be calculated to find the corresponding Average Detector value.

Full Spectrum



Radiated Emissions, 1-25 GHz

FCC Part 15.209 (a), ISCED Canada RSS-GEN Issue 5, Clause 7.3/8.9

Measurement procedure: ANSI C63.10-2013 Clause 11.12

Measuring distance: 3m (1 – 8 GHz), 1m (8 – 25 GHz)

Peak Detector: (Restricted band frequencies)

Frequency	RF channel	Dist. corr. factor	Field strength, Peak Detector, 3m	Limit	Margin
GHz	L,M,H	dB	dB μ V/m	dB μ V/m	dB
4.804	M	0	45.32	74	28.68
4.88	H	0	/	74	/
4.96	L	0	/	74	/
7.32	M	0	/	74	/
7.44	H	0	/	74	/
Other freqs	L,M,H	0	None detected	74	>20

Average Detector: (Restricted band frequencies)

Frequency	RF channel	Dist. corr. factor	Field strength, Average Detector, 3m	Duty cycle corr. factor	Limit	Margin
GHz	L,M,H	dB	dB μ V/m	dB	dB μ V/m	dB
4.804	M	0	/	/	54	/
4.88	H	0	/	/	54	/
4.96	L	0	/	/	54	/
7.32	M	0	/	/	54	/
7.44	H	0	/	/	54	/
Other freqs	L,M,H	/	None detected	20	54	>20

*distance correction is included on the plot.

Maxium is obtained in HP

For 37 byte payload:

Duty Cycle = On Time / (Period * Number of Channels) = 394.4 μ s / (628 μ s * 40) = 0.0016 (0.16%)


Duty Cycle Correction factor = -20 x log (Duty Cycle) = -56dB

Maximum allowed Duty Cycle Correction: 20 dB

Antenna factor, amplifier gain and cable loss are included in spectrum analyzer "Transducer factor"., See plots.


Requirements/Limit

FCC	Part 15.209 @ frequencies defined in §15.205	
ISED	RSS-GEN Issue 5, Clause 8.9 @ frequencies defined in clause 8.10	
	Radiated emission limit @3 meters	
Frequency (MHz)	AV (dB μ V/m)	Peak (dB μ V/m)
Above 1 GHz	54.0	74.0




Date: 7.DEC.2019 12:53:44

Radiated spurious emissions, VP, 1 - 3GHz, ch2402MHz, PK scan




Date: 7.DEC.2019 12:55:16

Radiated spurious emissions, HP, 1 - 3GHz, ch2402MHz, PK scan




Date: 7.DEC.2019 12:58:19

Radiated spurious emissions, VP, 1 - 3GHz, ch2440MHz, PK scan




Date: 7.DEC.2019 12:56:46

Radiated spurious emissions, HP, 1 - 3GHz, ch2440MHz, PK scan




Date: 7.DEC.2019 13:00:19

Radiated spurious emissions, VP, 1 - 3GHz, ch2480MHz, PK scan




Date: 7.DEC.2019 13:01:38

Radiated spurious emissions, HP, 1 - 3GHz, ch2480MHz, PK scan




Date: 7.DEC.2019 13:35:01

Radiated spurious emissions, VP, 3 - 18GHz, ch2402MHz, PK scan




Date: 7.DEC.2019 13:36:28


Radiated spurious emissions, HP, 3 - 18GHz, ch2402MHz, PK scan



Radiated spurious emissions, VP, 3 - 18GHz, ch2440MHz, PK scan




Radiated spurious emissions, HP, 3 - 18GHz, ch2440MHz, PK scan




Date: 7.DEC.2019 13:43:01

Radiated spurious emissions, VP, 3 - 18GHz, ch2480MHz, PK scan




Date: 7.DEC.2019 13:45:08

Radiated spurious emissions, HP, 3 - 18GHz, ch2480MHz, PK scan



Date: 7.DEC.2019 13:54:57

Pre-scan, Radiated spurious emissions, VP, 18 - 25GHz @ 1m distance



Date: 7.DEC.2019 13:54:42

Pre-scan, Radiated spurious emissions, HP, 18 - 25GHz @ 1m distance

3.9 Power Spectral Density (PSD)

FCC part 15.247(e)

ISED Canada RSS-247 Issue 2, Clause 5.2 (2)

Measurement procedure: ANSI C63.10-2013 Clause 11.10

Test Results: Complies

Measured and Calculated Data:


The measurement procedures PKPSD described in ANSI C63.10-2013 was used.

	2402 MHz	2440 MHz	2480 MHz
Measured value (dBm)	-16.11	-16.83	-17.27

Requirements:


The Power Spectral Density of a Digital Transmission System shall be no greater than +8 dBm in any 3 kHz band

No requirements for Frequency Hopping Systems.




Date: 7.DEC.2019 14:14:22

Conducted PSD, ch2402MHz



Date: 7.DEC.2019 14:16:13

Conducted PSD, ch2440MHz



Date: 7.DEC.2019 14:28:15

Conducted PSD, ch2480MHz

4 Measurement Uncertainty

Measurement Uncertainty Values		
Test Item		Uncertainty
Output Power		±0.5 dB
Power Spectral Density		±0.5 dB
Out of Band Emissions, Conducted	< 3.6 GHz	±0.6 dB
	> 3.6 GHz	±0.9 dB
Spurious Emissions, Radiated	< 1 GHz	±2.5 dB
	> 1 GHz	±2.2 dB
Emission Bandwidth		±4 %
Power Line Conducted Emissions		+2.9 / -4.1 dB
Spectrum Mask Measurements	Frequency	±5 %
	Amplitude	±1.0 dB
Frequency Error		±0.6 ppm
Temperature Uncertainty		±1 °C

All uncertainty values are expanded standard uncertainty to give a confidence level of 95%, based on coverage factor k=2

5 LIST OF TEST EQUIPMENT

To facilitate inclusion on each page of the test equipment used for related tests, each item of test equipment and ancillaries are identified (numbered) by the Test Laboratory.

No.	Instrument/ ancillary	Type of instrument/ ancillary	Manufacturer	Ref. no.	Cal. Date	Cal. Due
1.	ESU40	EMI Receiver	Rohde & Schwarz	LR1639	2019.01	2020.01
2.	FSW43	Spectrum analyser	Rohde & Schwarz	LR1690	2019.01	2020.01
3.	HFH2-Z2	Active Loop antenna	Rohde & Schwarz	LR1660	2019.06	2021.06
4.	3115	Antenna horn	EMCO	LR 1330	2016.10	2020.10
5.	PM 320K	Antenna Horn	Sivers	LR 1717	N/A	
6.	DBF-520-20	Antenna Horn	Systron-Donner corp	LR 102	N/A	
7.	638	Antenna Horn	NARDA	LR 1480	N/A	
8.	637	Antenna Horn	NARDA	LR 099	N/A	
9.	ARJB1	Bi-log Hybrid Antenna	Sunol	LR 1734	2018.05	2020.05
10	4768-10	Attenuator	Narda	LR 1356	Cal b4 use	
11	6HC3000/18000	Highpass Filter	Trilithic	LR 1614	Cal b4 use	
12	8449B	Pre-amplifier	Hewlett Packard	LR 1322	2019.07	2020.07
13	310N	Pre-amplifier	Sonoma	LR 1686	2019.07	2020.07
14	Model 45	Multimeter	Fluke	LT 5218	2018.11	2020.11

The software listed below has been used for one or more tests.


No.	Manufacturer	Name	Version	Comment
1	Rohde & Schwarz	GPBShot	2.7	Screenshots from R&S Spectrum Analyzers
2	Rohde & Schwarz	RScommander	1.9.2 64bit	Versatile Software Tool for R&S Instruments
3	Rohde & Schwarz	EMC 32	10.50.40	Radiated Emission test software

Revision history


Version	Date	Comment	Sign
01	2020.01.10	First Version	gns

6 BLOCK DIAGRAM

6.1 Power Line Conducted Emission



6.2 Test Site Radiated Emission



This test setup is used for all radiated emissions tests. For frequencies below 30 MHz the measuring distance is 10m, for all other frequencies it is 3m or 1m. Emissions above 1 GHz are measured with a Spectrum Analyzer and Horn Antenna. For measurements above 18 GHz the test receiver is moved inside the anechoic chamber and located next to the antenna to minimize the cable loss. All measurements at 1GHz and above were performed with turntable height 1.5m and with the ground plane covered by absorbers. A pre-amplifier is used for all measurements above 30 MHz, and High-Pass or Band-Pass filter is used for all harmonics.