



TEST REPORT

Product Name Model Number FCC ID Wireless Broadband Router
WUC128
PBLWUC128

Applicant Address

: Advance Multimedia Internet Technology Inc.

ess : <u>No. 32,</u>

: <u>No. 32, Hwan-Gong Rd, Yung Kang City,</u> <u>Tainan Hsien, Taiwan</u>

Received Date : February 21, 2005

Tested Date : February 23 ~ April 26, 2005

Issued by Compliance Certification Services Inc. Tainan Lab.

No. 8, Jiu Ceng Ling, Jiaokeng Village,Sinhua Township, Tainan Hsien 712, Taiwan R.O.C. TEL : (06)580-2201 FAX : (06)580-2202

Notes :

- 1. This report will be invalid if duplicated or photocopied in part.
- 2. This report refers only to the specimen(s) submitted to testing, and be invalid as seperately used.
- 3. This report is invalid without examination stamp and signature of this institute.
- 4. The tested specimen(s) will be preserved for thirty days from the data issued.
- 5. The report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.





Test Report Certification

Product Name	: Wireless Broadband Router
Model Number	: <u>WUC128</u>
FCC ID	: <u>PBLWUC128</u>
Applicant	: Advance Multimedia Internet Technology Inc.

Measurement Standard :

FCC 47 C.F.R. Part 15, Subpart B and Subpart C (2004) ANSI C63.4 (2003)

Tested By Date : May 05, 2005 Section Manager (Jeter Wu **Approved By :** Date : May 05, 2005 (Alex Chiu Manager)

WE HEREBY CERTIFY THAT: The measurements shown in the attachment were made in accordance with the procedures indicated, and the energy emitted by the equipment was found to be within the limits applicable. We assume full responsibility for the accuracy and completeness of these measurements and vouch for the qualifications of all persons taking them.



 FCC ID
 : PBLWUC128

 Report No.
 : 50221404-RP1

 Page
 3 of 55

TABLE OF CONTENTS

TITLE	PAGE NO
1. GENERAL INFORMATION	
1.1 General Statement	5
1.2 General Description of EUT & Power	5
1.3 Description of Peripherals	6
1.4 EUT & Peripherals Setup Diagram	6
1.5 EUT Operating Procedure	6
1.6 Description of Laboratory	7
1.7 Summary of Test Results	7
2. CONDUCTED POWERLINE TEST	
2.1 Test Equipments	
2.2 Test Setup	
2.3 Conducted Power Line Emission Limit	9
2.4 Test Procedure	9
2.5 Uncertainty of Conducted Emission	9
2.6 Conducted RF Voltage Measurement	
2.7 Photos of Conduction Test	
3. RADIATED EMISSION TEST	
3.1 Test Equipments	
3.2 Test Setup	
3.3 Radiation Limit	
3.4 Test Procedures	
3.5 Uncertainty of Radiated Emission	
3.6 Radiated RF Noise Measurement	
3.7 Photos of Open Site	
4. 6dB BANDWIDTH MEASUREMENT	
4.1 Test Equipments	
4.2 Test Setup	
4.3 Limits of 6dB Bandwidth Measurement	
4.4 Test Procedure	
4.5 Uncertainty of Conducted Emission	
4.6 Test Results	
4.7 Photo of 6db Bandwidth Measurement	
5. MAXIMUM PEAK OUTPUT POWER	
5.1 Test Equipments	
5.2 Test Setup	



5.3 Limits of Maximum Peak Output Power	
5.4 Test Procedure	41
5.5 Uncertainty of Conducted Emission	
5.6 Test Results	
5.7 Photo of Maximum Peak Output Power Measurement	
6. POWER SPECTRAL DENSITY MEASUREMENT	45
6.1 Test Equipments	
6.2 Test Setup	
6.3 Limits of Power Spectral Density Measurement	
6.4 Test Procedure	
6.5 Uncertainty of Conducted Emission	
6.6 Test Results	
6.7 Photo of Power Spectral Density Measurement	
7. BAND EDGE MEASUREMENT	49
7.1 Test Equipments	
7.2 Test Setup	
7.3 Limits of Band Edge Emissions Measurement	
7.4 Test Procedure	
7.5 Uncertainty of Conducted Emission	
7.6 Test Results	
7.7 Photo of Band edge Measurement	
8. ANTENNA REQUIREMENT	53
8.1 Standard Applicable	
8.2 Antenna Connected Construction	
9. RF EXPOSURE EVALUATION	54
9.1 Friis Formula	
9.2 EUT Operating Condition	
9.3 Test Result of RF Exposure Evaluation	
9.3.1 Antenna Gain9.3.2 Output Power into Antenna & RF Exposure Evaluation Distance	55 55



1. GENERAL INFORMATION

1.1 General Statement

MEASUREMENT DEVIATION: Comply with standard in full

TRACEABILITY : This test result is traceable to National or International std.

1.2 General Description of EUT & Power

Product Name Wireless Broadband Router		
Model Number	WUC128	
Frequency Range	2412 ~ 2462 MHz	
Frequency Channel	2412MHz + 5×n (MHz), n = 0, 1, 2,10	
Channel Number	11 Channels	
Channel Spacing	5MHz	
Air Data Rate	54Mbps (802.11g Mode), 11Mbps(802.11b Mode)	
	802.11b : DSSS(CCK, DQPSK, DBPSK)	
Type of Modulation	802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK)	
Frequency Selection	by software / firmware	
Transmitter Classification	Mobile device	
	2.4GHz (Direct Sequence Spread Spectrum and Orthogonal	
EUT Description	Frequency Division Multiplex) Data Transceiver for WLAN	
	application	
Antenna Type	Dipole Antenna Gain : 1.8dBi	
Power Source	5VDC (From Adapter)	

Power Adapter :

No.	Manufacturer	Model No.	Input Power	Output Power
1		TC10A 050	100-240~1.0A	51/ 2.04
1	FAIKWAI	IC10A-050	MAX 50-60Hz	3V, 2.0A



No.		Product	Manufacturer	Model No.	FCC ID	Signal cable
1	>	PC	HP	d330uT	DOC	N/A
2	>	Note Book	HP	CNC 6000	CNTPP2090	N/A
3		LCD Monitor	HP	1502	DOC	VGA cable,shd,1.5m
4		LCD Monitor	SAMPO	SL7003	DOC/R4AA03	VGA cable,shd,1.5m
5	>	LCD Monitor	BenQ	QTT3	DOC	VGA cable,shd,1.8m
6	>	Keyboard(PS2)	HP	KB-0133	DOC	Keyboard cable,shd,1.9m
7	>	Mouse(PS2)	HP	M-S69	JNZ211443	Mouse cable,shd,1.8m
8		Modem	LEMEL	MD-56K	DOC	RS232 cable,shd,1.1m
9		Printer	HP	DeskJet 660C	DOC	Printer cable,shd,1.8m
10		HUB	LEMEL	LM-S5M4C	DOC	N/A
11		CCD Camera	Logitech	QuickCam	DOC	USB cable,shd,1.8m
12		CCD Camera	OEM	CD7844	DOC	USB cable,shd,2.0m
13		SpeakSystem	KINKO	KY-550	R34100	Audio cable,1.6m*2
14		USB Flash Disk	Transcend	JetFlash	D33193	USB cable,shd,0.3m
15		HeadPhone	3D	MIC -06	DOC	Audio cable,1.8m

1.3 Description of Peripherals

1.4 EUT & Peripherals Setup Diagram



The indicated numbers (1)(2)....,please refer to item 1.3

1.5 EUT Operating Procedure

- 1. Set up all computers like the setup diagram.
- 2. According to test item , set TX & RX mode from CH1 to CH11.



1.6 Description of Laboratory

SITE DESCRIPTION :

FCC certificate NO.	: 228014
BSMI certificate NO.	: SL2-IN-E-0039
NVLAP Lab code	: 200627-0
CNLA certificate NO.	: CNLA-ZL03116
VCCI certificate NO.	: R-1989, C-2142

NAME OF SITE : Compliance Certification Services Inc. (Tainan Lab.)

SITE LOCATION : No. 8, Jiu Ceng Ling, Jiaokeng Village, Sinhua Township,

Tainan Hsien 712, Taiwan R.O.C.

1.7 Summary of Test Results

	The	EUT	has	been	tested	according t	o the	following	specifications:
--	-----	-----	-----	------	--------	-------------	-------	-----------	-----------------

APP	Subpart B and Subpart C		
Standard Section	Test Item and Limit	Result	REMARK
15.107	AC Power Conducted Emission	DASS	Meet the requirement of limit
15.207	Limit : Sec 15.107	1 499	Meet the requirement of mint
15.247(a)(2)	Spectrum Bandwidth of a Orthogonal Frequency Division Multiplex System Limit : 6dB bandwidth > 500KHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit
15.109 15.205 15.209	Transmitter Radiated Emissions Limit : Table 15.209	PASS	Meet the requirement of limit
15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit
15.247(d)	Out of Band Emission and Restricted Band Radiation Limit:20dB less than peak value of fundamental frequency Restricted band Limit: Table 15.209	PASS	Meet the requirement of limit



2. CONDUCTED POWERLINE TEST

2.1 Test Equipments

The following test equipments are used during the conducted power line tests :

Manufacturer or Type	Model No.	Serial No.	Date of Calibration	Calibratio n Period	Remark
			SEP. 29, 2004		
		8121-446	For Insertion	1 YEAR	FINAL
SCHWARZBECK	NNLK		loss		
L.I.S.N.	8121		DEC. 09, 2004		
		8121-308	For Insertion	1 YEAR	FINAL
			loss		
R&S TEST RECEIVER	ESCS 30	100348	JUN. 16, 2005	1 YEAR	FINAL
R & S PULSE LIMIT	ESH3-Z2	100110	DEC. 27, 2004	1 YEAR	FINAL
TYPE N COAXIAL CABLE			DEC. 26, 2004	1 YEAR	FINAL

2.2 Test Setup





2.3 Conducted Power Line Emission Limit

For unintentional device, according to § 15.107(a) Line Conducted Emission Limits is as following :

Fraguancy	Maximum RF Line Voltage (dBµV)					
(MH ₇)	CLA	SS A	CLASS B			
(141112)	Q.P.	Ave.	Q.P.	Ave.		
0.15 - 0.50	79	66	66-56	56-46		
0.50 - 5.00	73	60	56	46		
5.00 - 30.0	73	60	60	50		

For intentional device, according to § 15.207(a) Line Conducted Emission Limit is same as above table.

2.4 Test Procedure

The test procedure is performed in a $12ft \times 12ft \times 8ft(L \times W \times H)$ shielded room. The EUT along with its peripherals were placed on a $1.0m(W) \times 1.5m(L)$ and 0.8m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane. The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chasis ground was bounded to the horizontal ground plane of shielded room. All peripherals were connected to the second LISN and the chasis ground also bounded to the horizontal ground plane of shielded room. The EUT and the LISN was bundled. The power cables of peripherals were unbundled. All connecting cables of EUT and peripherals were moved to find the maximum emission.

2.5 Uncertainty of Conducted Emission

The uncertainty of conducted emission is ± 2.1 dB.



2.6 Conducted RF Voltage Measurement

The frequency spectrum from 0.15 MHz to 30 MHz was investigated. All emissions not reported are much lower than the prescribed limits.

Company	Advance Multimedia Internet Technology Inc.	Test Date	2005/02/23
Product Name	Wireless Broadband Router	Test By	Jerry Chang
Model Name	WUC128	TEMP & Humidity	26 , 60%



REMARKS :

1. Correction Factor = Insertion loss + cable loss

2. Margin value = Emission level – Limit value



The frequency spectrum from 0.15 MHz to 30 MHz was investigated. All emissions not reported are much lower than the prescribed limits.

Company	Advance Multimedia Internet Technology Inc.	Test Date	2005/02/23
Product Name	Wireless Broadband Router	Test By	Jerry Chang
Model Name	WUC128	TEMP & Humidity	26 , 60%





REMARKS :

1. Correction Factor = Insertion loss + cable loss

2. Margin value = Emission level – Limit value



3. RADIATED EMISSION TEST

3.1 Test Equipments

The following test equipments are utilized in making the measurements contained in this report.

Manufacturer or Type	Model No.	Serial No.	Date of Calibration	Calibration Period	Remark
O.A.T.S		No.6	SEP. 12, 2004	1 YEAR	FINAL
R&S EMI RECEIVER	ESVS10	833206/012	FEB. 24, 2005	1 YEAR	FINAL
R&S Spectrum Analyzer	FSEM	829054/017	MAR. 18, 2005	1 YEAR	FINAL
CHASE BI-LOG ANTENNA	CBL6112B	2341	FEB. 18, 2005	1 YEAR	FINAL
Horn Antenna	AH-118	071032	AUG. 02,2004	1 YEAR	FINAL
SMA 18G Cable	SUCOFLEX104(1M)	001	MAR. 22, 2005	1 YEAR	FINAL
HP Pre-Amplifer	8447F	2944A03817	MAR. 09, 2005	1 YEAR	FINAL
HP Signal Generator	8673C	2938A00663	FEB. 02,2005	1 YEAR	FINAL
RF SWITCH	ERS-180A		JAN. 31,2005	1 YEAR	FINAL
POWER METER	8541C	1835448	APR. 17, 2005	1 YEAR	FINAL

3.2 Test Setup

The diagram below shows the test setup that is utilized to make the measurements for emission below 1GHz.



Antenna Elevation Variable



The diagram below shows the test setup that is utilized to make the measurements for emission above 1GHz.



Antenna Elevation Variable

3.3 Radiation Limit

For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values :

Frequency	Distance	Radiated	Radiated	
(MHz)	(Meters)	(dBµV/m)	(µV/m)	
30-88	3	40.0	100	
88-216	3	43.5	150	
216-960	3	46.0	200	
Above 960	3	54.0	500	

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency bard in which the EUT is operating, the radiofrequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of desired power.



3.4 Test Procedures

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. During performing radiated emission below 1GHz, the EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1GHz, the EUT was set 1 meters away from the interference-receiving antenna.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarization of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 KHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
- 2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

3.5 Uncertainty of Radiated Emission

The uncertainty of radiated emission is ± 3.2 dB.

NOTE :



3.6 Radiated RF Noise Measurement

The frequency spectrum from 30 MHz to 1000 MHz was investigated. All emissions not reported are much lower than the prescribed limits. All readings are quasi-peak values.

Company	Advance Multimedia Internet Technology Inc.	Test Date	2005/04/13
Product Name	Wireless Broadband Router	Test By	Jerry Chang
Model Name	WUC128	TEMP & Humidity	27 , 58%

HORIZONTAL

Freq-	Antenna	Cable	Meter Reading	Limits	Emission Level	Antenna	Turntable	Monain
Uency	Factor	Loss	at 3 m(dB µ V)		at 3 m(dB µ V/m)	Height(cm)	Turntable	wargin
			Here's surfal	(dD u V/m)		II	A 1.	
(MHz)	(dB/m)	(dB)	Horizontal		Horizontal	Horizontal	Angle	п
30.00	20.02	0.60	*	39.00	*	*	*	*
125.00	12.35	1.05	26.50	43.50	39.90	240	199	-3.60
200.00	9.98	1.24	24.50	43.50	35.72	117	114	-7.78
375.00	14.20	2.13	15.80	46.00	32.14	117	114	-13.86
500.00	17.63	2.60	19.30	46.00	39.53	117	114	-6.47
625.00	18.99	3.09	20.00	46.00	42.08	119	127	-3.92
750.00	20.42	3.50	12.70	46.00	36.62	119	127	-9.38
875.00	21.80	3.73	6.50	46.00	32.02	119	127	-13.98

VERTICAL

Freq-	Antenna	Cable	Meter Reading	Limits	Emission Level	Antenna	Turntable	Monein
Uency	Factor	Loss	at 3 m(dB µ V)		at 3 m(dB µ V/m)	Height(cm)	Turntable	Margin
			Horizontal	(dD 11 V/m)	Honizontol	Howingental	Amala	N7
(MHz)	(dB/m)	(dB)	Horizontai		Horizontai	Horizontai	Aligie	v
30.00	20.02	0.60	*	39.00	*	*	*	*
125.00	12.35	1.05	28.90	43.50	42.30	105	114	-1.20
200.00	9.98	1.24	29.00	43.50	40.22	138	360	-3.28
300.00	13.73	1.60	11.10	46.00	26.43	100	203	-19.57
375.00	14.20	2.13	14.50	46.00	30.84	100	70	-15.17
400.00	14.36	2.31	13.50	46.00	30.17	119	127	-15.83
500.00	17.63	2.60	14.70	46.00	34.93	119	127	-11.07
625.00	18.99	3.09	14.20	46.00	36.28	119	127	-9.72

REMAR:

1. * Undetectable

2. Emission level ($dB\mu V/m$) = Antenna Factor (dB/m) + Cable loss (dB)

+ Meter Reading ($dB\mu V$).

3. According to technical experiences, all spurious emission at channel 1,6,11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in finial test.

4. The test data marked in gray background means the EUT emission data islocated in the margin uncertainty range of emission limits.



Company	Advance Multimedia Internet Technology Inc.	Test Date	2005/02/18
Product Name	Wireless Broadband Router	Test By	Jerry Chang
Model Name	WUC128	TEMP & Humidity	27 , 58%

CH1 RX				Measurement Distance at 3m Horizontal polarity							
Freq. (MHz)	Reading (dBµV)	AF (dB/m)	Cable (dB)	Pre-amp (dB)	Dist (dB)	Filter (dB)	$\begin{array}{c} Level \\ (dB\mu V/m) \end{array}$	Limit (dBµV/m)	Margin (dB)	Mark (P/Q/A)	Height (Meter)
1200.06	41.69	25.20	4.23	31.22	0.00	0.00	39.91	74	-34.09	Р	1.0
1200.06	33.26	25.20	4.23	31.22	0.00	0.00	31.48	54	-22.52	А	1.0
2038.04	48.91	29.08	5.56	31.91	0.00	0.00	51.64	74	-22.36	Р	1.0
2038.04	45.94	29.08	5.56	31.91	0.00	0.00	48.67	54	-5.33	А	1.0
4075.96	42.10	30.46	7.68	32.95	0.00	0.00	47.28	74	-26.72	Р	1.0
4075.96	30.06	30.46	7.68	32.95	0.00	0.00	35.24	54	-18.76	A	1.0

1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain.

2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz,VBW=10Hz

3. The result basic equation calculation as follow :

Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

4. The test limit is 3M limit.

5. The frequency was searched to 18GHz.



Company	Advance Multimedia Internet Technology Inc.	Test Date	2005/02/18
Product Name	Wireless Broadband Router	Test By	Jerry Chang
Model Name	WUC128	TEMP & Humidity	27 , 58%

CH1 RX				Measurement Distance at 3m Vertical polarity							
Freq. (MHz)	Reading (dBµV)	AF (dB/m)	Cable (dB)	Pre-amp (dB)	Dist (dB)	Filter (dB)	$\begin{array}{c} Level \\ (dB\mu V/m) \end{array}$	Limit (dBµV/m)	Margin (dB)	Mark (P/Q/A)	Height (Meter)
1200.01	42.87	25.20	4.23	31.22	0.00	0.00	41.09	74	-32.91	Р	1.0
1200.01	35.41	25.20	4.23	31.22	0.00	0.00	33.63	54	-20.37	А	1.0
2038.03	52.73	29.08	5.56	31.91	0.00	0.00	55.46	74	-18.54	Р	1.0
2038.03	50.13	29.08	5.56	31.91	0.00	0.00	52.86	54	-1.14	А	1.0
4075.73	41.94	30.45	7.68	32.95	0.00	0.00	47.12	74	-26.88	Р	1.0
4075.73	32.80	30.45	7.68	32.95	0.00	0.00	37.98	54	-16.02	A	1.0

1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain.

2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz

3. The result basic equation calculation as follow :

Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

4. The test limit is 3M limit.

5. The frequency was searched to 18GHz.



Company	Advance Multimedia Internet Technology Inc.	Test Date	2005/02/18
Product Name	Wireless Broadband Router	Test By	Jerry Chang
Model Name	WUC128	TEMP & Humidity	27 , 58%

CH6 RX				Measurement Distance at 3m Horizontal polarity							
Freq. (MHz)	Reading (dBµV)	AF (dB/m)	Cable (dB)	Pre-amp (dB)	Dist (dB)	Filter (dB)	$\begin{array}{c} Level \\ (dB\mu V/m) \end{array}$	Limit (dBµV/m)	Margin (dB)	Mark (P/Q/A)	Height (Meter)
1199.76	42.57	25.20	4.23	31.22	0.00	0.00	40.79	74	-33.21	Р	1.0
1199.76	33.26	25.20	4.23	31.22	0.00	0.00	31.48	54	-22.52	А	1.0
2062.96	48.93	29.13	5.59	31.90	0.00	0.00	51.74	74	-22.26	Р	1.0
2062.96	45.41	29.13	5.59	31.90	0.00	0.00	48.22	54	-5.78	А	1.0
4159.26	42.57	30.96	7.74	32.90	0.00	0.00	48.36	74	-25.64	Р	1.0
4159.26	30.38	30.96	7.74	32.90	0.00	0.00	36.17	54	-17.83	A	1.0

1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain.

2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz,VBW=10Hz

3. The result basic equation calculation as follow :

Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

4. The test limit is 3M limit.

5. The frequency was searched to 18GHz.



Company	Advance Multimedia Internet Technology Inc.	Test Date	2005/02/18
Product Name	Wireless Broadband Router	Test By	Jerry Chang
Model Name	WUC128	TEMP & Humidity	27 , 58%

	CH6	RX		Measurement Distance at 3m Vertical polarity							
Freq. (MHz)	Reading (dBµV)	AF (dB/m)	Cable (dB)	Pre-amp (dB)	Dist (dB)	Filter (dB)	$\begin{array}{c} Level \\ (dB\mu V/m) \end{array}$	Limit (dBµV/m)	Margin (dB)	Mark (P/Q/A)	Height (Meter)
1199.98	43.51	25.20	4.23	31.22	0.00	0.00	41.73	74	-32.27	Р	1.0
1199.98	35.75	25.20	4.23	31.22	0.00	0.00	33.97	54	-20.03	А	1.0
2063.01	51.86	29.13	5.59	31.90	0.00	0.00	54.67	74	-19.33	Р	1.0
2063.01	50.01	29.13	5.59	31.90	0.00	0.00	52.82	54	-1.18	А	1.0
4126.03	43.23	30.76	7.72	32.92	0.00	0.00	48.78	74	-25.22	Р	1.0
4126.03	32.80	30.76	7.72	32.92	0.00	0.00	38.35	54	-15.65	A	1.0

1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain.

2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz,VBW=10Hz

3. The result basic equation calculation as follow :

Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

4. The test limit is 3M limit.

5. The frequency was searched to 18GHz.



Company	Advance Multimedia Internet Technology Inc.	Test Date	2005/02/18
Product Name	Wireless Broadband Router	Test By	Jerry Chang
Model Name	WUC128	TEMP & Humidity	27 , 58%

	CH11	RX		Measurement Distance at 3m Horizontal polarity							
Freq. (MHz)	Reading (dBµV)	AF (dB/m)	Cable (dB)	Pre-amp (dB)	Dist (dB)	Filter (dB)	$\begin{array}{c} Level \\ (dB\mu V/m) \end{array}$	Limit (dBµV/m)	Margin (dB)	Mark (P/Q/A)	Height (Meter)
1199.96	42.95	25.20	4.23	31.22	0.00	0.00	41.17	74	-32.83	Р	1.0
1199.96	34.10	25.20	4.23	31.22	0.00	0.00	32.32	54	-21.68	А	1.0
2088.06	48.48	29.18	5.62	31.90	0.00	0.00	51.37	74	-22.63	Р	1.0
2088.06	45.01	29.18	5.62	31.90	0.00	0.00	47.90	54	-6.10	А	1.0
4176.01	42.95	31.06	7.75	32.89	0.00	0.00	48.86	74	-25.14	Р	1.0
4176.01	31.26	31.06	7.75	32.89	0.00	0.00	37.17	54	-16.83	A	1.0

1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain.

2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz

3. The result basic equation calculation as follow :

Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

4. The test limit is 3M limit.

5. The frequency was searched to 18GHz.



Company	Advance Multimedia Internet Technology Inc.	Test Date	2005/02/18
Product Name	Wireless Broadband Router	Test By	Jerry Chang
Model Name	WUC128	TEMP & Humidity	27 , 58%

	CH11	RX			Measurement Distance at 3m Vertical polarity							
Freq. (MHz)	Reading (dBµV)	AF (dB/m)	Cable (dB)	Pre-amp (dB)	Dist (dB)	Filter (dB)	$\begin{array}{c} Level \\ (dB\mu V/m) \end{array}$	Limit (dBµV/m)	Margin (dB)	Mark (P/Q/A)	Height (Meter)	
1199.96	43.09	25.20	4.23	31.22	0.00	0.00	41.31	74	-32.69	Р	1.0	
1199.96	34.69	25.20	4.23	31.22	0.00	0.00	32.91	54	-21.09	А	1.0	
2087.96	54.65	29.18	5.62	31.90	0.00	0.00	57.54	74	-16.46	Р	1.0	
2087.96	49.87	29.18	5.62	31.90	0.00	0.00	52.76	54	-1.24	А	1.0	
4176.13	41.69	31.06	7.75	32.89	0.00	0.00	47.61	74	-26.39	Р	1.0	
4176.13	32.32	31.06	7.75	32.89	0.00	0.00	38.24	54	-15.76	A	1.0	

1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain.

2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz

3. The result basic equation calculation as follow :

Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

4. The test limit is 3M limit.

5. The frequency was searched to 18GHz.



Company	Advance Multimedia Internet Technology Inc.	Test Date	2005/02/18
Product Name	Wireless Broadband Router	Test By	Jerry Chang
Model Name	WUC128	TEMP & Humidity	27 , 58%

		CH1 '	ΓХ		Ν	/leasu	ıremei	nt Distance	at 3m H	Iorizonta	ıl polarity	1
	Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
	(MHz)	(dBµV)	(dB/m)	(dB)	(dB)	dB	dB	$(dB\mu V/m)$	(dBµV/m)	(dB)	(P/Q/A)	(Meter)
*	2389.90	25.58	30.00	5.98	0.00	0.00	0.00	61.56	74.00	-12.44	Р	1.00
*	2389.90	14.30	30.00	5.98	0.00	0.00	0.00	50.28	54.00	-3.72	А	1.00
	2399.90	27.57	29.80	5.99	0.00	0.00	0.00	63.36	81.77	-18.41	Р	1.00
	2399.90	18.13	29.80	5.99	0.00	0.00	0.00	53.92	78.43	-24.51	А	1.00
	2413.05	65.94	29.83	6.01	0.00	0.00	0.00	101.77	Fundamental		Р	1.00
	2413.05	62.60	29.83	6.01	0.00	0.00	0.00	98.43	Freque	ncy	А	1.00
	2037.91	49.47	29.08	5.56	31.91	0.00	0.00	52.20	81.77	-29.58	Р	1.00
	2037.91	47.01	29.08	5.56	31.91	0.00	0.00	49.74	78.43	-28.70	А	1.00
*	4823.92	43.93	33.65	8.29	32.80	0.00	2.00	55.08	74.00	-18.92	Р	1.00
*	4823.92	35.24	33.65	8.29	32.80	0.00	2.00	46.39	54.00	-7.61	А	1.00
	7236.00	38.94	36.47	9.99	32.85	0.00	2.00	54.55	81.77	-27.23	Р	1.00
	7236.00	27.88	36.47	9.99	32.85	0.00	2.00	43.49	78.43	-34.95	А	1.00

Note :

1. The measurement was searched to 10th harmonic, Remark "---" means that the emissions level is too low to be measured.

2. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)

3. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz

4. Remark "*" means the Restricted band.

5. The result basic equation calculation is as follow:

Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

6. The other emission levels were very low against the limit

7. The test limit distance is 3M limit.



Company	Advance Multimedia Internet Technology Inc.	Test Date	2005/04/06
Product Name	Wireless Broadband Router	Test By	Jerry Chang
Model Name	WIC228	TEMP & Humidity	27 , 58%

		CH1 '	ΓХ			Meas	surem	ent Distance	e at 3m	Vertical	polarity	
	Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
	(MHz)	(dBµV)	(dB/m)	(dB)	(dB)	dB	dB	$(dB\mu V/m)$	$(dB\mu V/m)$	(dB)	(P/Q/A)	(Meter)
*	2389.90	28.15	29.78	5.98	0.00	0.00	0.00	63.91	74.00	-10.09	Р	1.00
*	2389.90	16.08	29.78	5.98	0.00	0.00	0.00	51.84	54.00	-2.16	А	1.00
	2399.90	32.14	29.80	5.99	0.00	0.00	0.00	67.93	90.52	-22.59	Р	1.00
	2399.90	25.35	29.80	5.99	0.00	0.00	0.00	61.14	87.24	-26.10	А	1.00
	2413.05	74.69	29.83	6.01	0.00	0.00	0.00	110.52	Fundam	ental	Р	1.00
	2413.05	71.41	29.83	6.01	0.00	0.00	0.00	107.24	Freque	ncy	А	1.00
	2038.10	55.29	29.08	5.56	31.91	0.00	0.00	58.02	90.52	-32.51	Р	1.00
	2038.10	54.12	29.08	5.56	31.91	0.00	0.00	56.85	87.24	-30.40	А	1.00
*	4823.93	43.71	33.65	8.29	32.80	0.00	2.00	54.86	74.00	-19.14	Р	1.00
*	4823.93	36.24	33.65	8.29	32.80	0.00	2.00	47.39	54.00	-6.61	А	1.00
	7236.00	40.12	36.47	9.99	32.85	0.00	2.00	55.73	90.52	-34.80	Р	1.00
	7236.00	27.88	36.47	9.99	32.85	0.00	2.00	43.49	87.24	-43.76	А	1.00

Note :

1. The measurement was searched to 10th harmonic, Remark "---" means that the emissions level is too low to be measured.

2. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)

3. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz

4. Remark "*" means the Restricted band.

5. The result basic equation calculation is as follow:

Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

6. The other emission levels were very low against the limit

7. The test limit distance is 3M limit.



Company	Advance Multimedia Internet Technology Inc.	Test Date	2005/04/06
Product Name	Wireless Broadband Router	Test By	Jerry Chang
Model Name	WUC128	TEMP & Humidity	27 , 58%

		CH6	TX		Ν	Measurement Distance at 3m Horizontal polarity						
	Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
	(MHz)	(dBµV)	(dB/m)	(dB)	(dB)	dB	dB	$(dB\mu V/m)$	(dBµV/m)	(dB)	(P/Q/A)	(Meter)
	2437.95	66.71	29.88	6.04	0.00	0.00	0.00	102.62	Fundame	ental	Р	1.00
	2437.95	63.45	29.88	6.04	0.00	0.00	0.00	99.36	Frequency		А	1.00
	2062.97	49.44	29.13	5.59	31.90	0.00	0.00	52.25	82.62	-30.37	Р	1.00
	2062.97	46.92	29.13	5.59	31.90	0.00	0.00	49.73	79.36	-29.63	А	1.00
*	4873.89	42.80	33.75	8.34	32.81	0.00	1.80	53.88	74.00	-20.12	Р	1.00
*	4873.89	33.26	33.75	8.34	32.81	0.00	1.80	44.34	54.00	-9.66	А	1.00
*	7311.00	40.42	36.62	10.04	32.95	0.00	2.00	56.13	74.00	-17.87	Р	1.00
*	7311.00	28.28	36.62	10.04	32.95	0.00	2.00	43.99	54.00	-10.01	А	1.00

Note :

1. The measurement was searched to 10th harmonic, Remark "---" means that the emissions level is too low to be measured.

2. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)

3. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz

4. Remark "*" means the Restricted band.

5. The result basic equation calculation is as follow:

Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

6. The other emission levels were very low against the limit

7. The test limit distance is 3M limit.



Company	Advance Multimedia Internet Technology Inc.	Test Date	2005/04/06
Product Name	Wireless Broadband Router	Test By	Jerry Chang
Model Name	WUC128	TEMP & Humidity	27 , 58%

		CH6	ΤХ			Meas	surem	ent Distance	e at 3m	Vertical	polarity	
	Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
	(MHz)	(dBµV)	(dB/m)	(dB)	(dB)	dB	dB	$(dB\mu V/m)$	(dBµV/m)	(dB)	(P/Q/A)	(Meter)
	2438.05	73.33	29.88	6.04	0.00	0.00	0.00	109.24	Fundame	ental	Р	1.00
	2438.05	70.25	29.88	6.04	0.00	0.00	0.00	106.16	Freque	ncy	А	1.00
	2062.97	54.56	29.13	5.59	31.90	0.00	0.00	57.37	89.24	-31.87	Р	1.00
	2062.97	52.68	29.13	5.59	31.90	0.00	0.00	55.49	86.16	-30.67	А	1.00
*	4873.89	44.60	33.75	8.34	32.81	0.00	1.80	55.68	74.00	-18.32	Р	1.00
*	4873.89	38.46	33.75	8.34	32.81	0.00	1.80	49.54	54.00	-4.46	А	1.00
*	7311.00	40.12	36.62	10.04	32.95	0.00	2.00	55.83	74.00	-18.17	Р	1.00
*	7311.00	28.67	36.62	10.04	32.95	0.00	2.00	44.38	54.00	-9.62	А	1.00

Note :

1. The measurement was searched to 10th harmonic, Remark "---" means that the emissions level is too low to be measured.

2. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)

3. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz

4. Remark "*" means the Restricted band.

5. The result basic equation calculation is as follow:

Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

6. The other emission levels were very low against the limit

7. The test limit distance is 3M limit.



Company	Advance Multimedia Internet Technology Inc.	Test Date	2005/04/06
Product Name	Wireless Broadband Router	Test By	Jerry Chang
Model Name	WUC128	TEMP & Humidity	27 , 58%

		CH117	ГХ		Ν	Aeası	ıremei	nt Distance	at 3m H	Iorizonta	ıl polarity	1
	Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
	(MHz)	(dBµV)	(dB/m)	(dB)	(dB)	dB	dB	$(dB\mu V/m)$	(dBµV/m)	(dB)	(P/Q/A)	(Meter)
	2460.54	65.94	29.92	6.06	0.00	0.00	0.00	101.92	Fundame	ental	Р	1.00
	2460.54	62.64	29.92	6.06	0.00	0.00	0.00	98.62	Freque	ncy	А	1.00
*	2483.50	25.01	29.97	6.09	0.00	0.00	0.00	61.07	74.00	-12.93	Р	1.00
*	2483.50	13.26	29.97	6.09	0.00	0.00	0.00	49.32	54.00	-4.68	А	1.00
*	2483.60	24.03	29.97	6.09	0.00	0.00	0.00	60.09	74.00	-13.91	Р	1.00
*	2483.60	13.03	29.97	6.09	0.00	0.00	0.00	49.09	54.00	-4.91	А	1.00
	2088.00	47.97	29.18	5.62	31.90	0.00	0.00	50.86	81.92	-31.06	Р	1.00
	2088.00	44.42	29.18	5.62	31.90	0.00	0.00	47.31	78.62	-31.31	А	1.00
*	4923.99	43.58	33.85	8.39	32.83	0.00	1.60	54.59	74.00	-19.41	Р	1.00
*	4923.99	34.88	33.85	8.39	32.83	0.00	1.60	45.89	54.00	-8.11	А	1.00
*	7386.00	39.50	36.77	10.09	33.05	0.00	2.00	55.31	74.00	-18.69	Р	1.00
*	7386.00	29.04	36.77	10.09	33.05	0.00	2.00	44.85	54.00	-9.15	А	1.00

Note :

1. The measurement was searched to 10th harmonic, Remark "---" means that the emissions level is too low to be measured.

2. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)

3. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz

4. Remark "*" means the Restricted band.

5. The result basic equation calculation is as follow:

Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

6. The other emission levels were very low against the limit

7. The test limit distance is 3M limit.



Company	Advance Multimedia Internet Technology Inc.	Test Date	2005/04/06
Product Name	Wireless Broadband Router	Test By	Jerry Chang
Model Name	WUC128	TEMP & Humidity	27 , 58%

		CH11	ΤХ			Meas	surem	ent Distance	e at 3m	Vertical	polarity	
	Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
	(MHz)	(dBµV)	(dB/m)	(dB)	(dB)	dB	dB	$(dB\mu V/m)$	(dBµV/m)	(dB)	(P/Q/A)	(Meter)
	2461.04	72.83	29.92	6.06	0.00	0.00	0.00	108.82	Fundame	ental	Р	1.00
	2461.04	69.77	29.92	6.06	0.00	0.00	0.00	105.76	Freque	ncy	А	1.00
*	2483.50	24.25	29.97	6.09	0.00	0.00	0.00	60.31	74.00	-13.69	Р	1.00
*	2483.50	13.90	29.97	6.09	0.00	0.00	0.00	49.96	54.00	-4.04	А	1.00
*	2488.00	24.34	29.98	6.10	0.00	0.00	0.00	60.41	74.00	-13.59	Р	1.00
*	2488.00	14.10	29.98	6.10	0.00	0.00	0.00	50.17	54.00	-3.83	А	1.00
	2088.02	52.28	29.18	5.62	31.90	0.00	0.00	55.17	88.82	-33.64	Р	1.00
	2088.02	50.68	29.18	5.62	31.90	0.00	0.00	53.57	85.76	-32.18	А	1.00
*	4923.96	43.37	33.85	8.39	32.83	0.00	1.60	54.38	74.00	-19.62	Р	1.00
*	4923.96	36.08	33.85	8.39	32.83	0.00	1.60	47.09	54.00	-6.91	А	1.00
*	7386.00	41.26	36.77	10.09	33.05	0.00	2.00	57.07	74.00	-16.93	Р	1.00
*	7386.00	29.39	36.77	10.09	33.05	0.00	2.00	45.20	54.00	-8.80	А	1.00

Note :

1. The measurement was searched to 10th harmonic, Remark "---" means that the emissions level is too low to be measured.

2. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)

3. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz

4. Remark "*" means the Restricted band.

5. The result basic equation calculation is as follow:

Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

6. The other emission levels were very low against the limit

7. The test limit distance is 3M limit.



Company	Advance Multimedia Internet Technology Inc.	Test Date	2005/02/16
Product Name	Wireless Broadband Router	Test By	Jerry Chang
Model Name	WUC128	TEMP & Humidity	26 , 60%

		CH1 '	ΤХ		Ν	Aeası	iremei	nt Distance	at 3m H	Iorizonta	ıl polarity	1
	Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
	(MHz)	(dBµV)	(dB/m)	(dB)	(dB)	dB	dB	$(dB\mu V/m)$	(dBµV/m)	(dB)	(P/Q/A)	(Meter)
*	2389.90	26.19	29.78	5.98	0.00	0.00	0.00	61.95	74.00	-12.05	Р	1.00
*	2389.90	14.30	29.78	5.98	0.00	0.00	0.00	50.06	54.00	-3.94	А	1.00
	2399.90	31.95	29.80	5.99	0.00	0.00	0.00	67.74	82.93	-15.19	Р	1.00
	2399.90	17.42	29.80	5.99	0.00	0.00	0.00	53.21	72.98	-19.77	А	1.00
	2413.75	67.10	29.83	6.01	0.00	0.00	0.00	102.93	Fundame	ental	Р	1.00
	2413.75	57.15	29.83	6.01	0.00	0.00	0.00	92.98	Freque	ncy	А	1.00
	2038.05	49.87	29.08	5.56	31.91	0.00	0.00	52.60	82.93	-30.34	Р	1.00
	2038.05	47.15	29.08	5.56	31.91	0.00	0.00	49.88	72.98	-23.11	А	1.00
*	4824.00	39.92	33.65	8.29	32.80	0.00	2.00	51.07	74.00	-22.93	Р	1.00
*	4824.00	28.28	33.65	8.29	32.80	0.00	2.00	39.43	54.00	-14.57	Α	1.00

Note :

1. The measurement was searched to 10th harmonic, Remark "---" means that the emissions level is too low to be measured.

2. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)

3. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz

4. Remark "*" means the Restricted band.

5. The result basic equation calculation is as follow:

Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

6. The other emission levels were very low against the limit

7. The test limit distance is 3M limit.



Company	Advance Multimedia Internet Technology Inc.	Test Date	2005/02/16
Product Name	Wireless Broadband Router	Test By	Jerry Chang
Model Name	WUC128	TEMP & Humidity	26 , 60%

		CH1 '	ΤХ			Meas	surem	ent Distance	e at 3m	Vertical	polarity	
	Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
	(MHz)	(dBµV)	(dB/m)	(dB)	(dB)	dB	dB	$(dB\mu V/m)$	$(dB\mu V/m)$	(dB)	(P/Q/A)	(Meter)
*	2389.90	28.25	29.78	5.98	0.00	0.00	0.00	64.01	74.00	-9.99	Р	1.00
*	2389.90	15.59	29.78	5.98	0.00	0.00	0.00	51.35	54.00	-2.65	А	1.00
	2399.90	38.18	29.80	5.99	0.00	0.00	0.00	73.97	90.65	-16.68	Р	1.00
	2399.90	23.37	29.80	5.99	0.00	0.00	0.00	59.16	81.20	-22.04	А	1.00
	2404.84	74.84	29.81	6.00	0.00	0.00	0.00	110.65	Fundame	ental	Р	1.00
	2404.84	65.39	29.81	6.00	0.00	0.00	0.00	101.20	Freque	ncy	А	1.00
	2038.05	55.23	29.08	5.56	31.91	0.00	0.00	57.96	90.65	-32.69	Р	1.00
	2038.05	54.02	29.08	5.56	31.91	0.00	0.00	56.75	81.20	-24.45	А	1.00
*	4824.00	40.71	33.65	8.29	32.80	0.00	2.00	51.86	74.00	-22.14	Р	1.00
*	4824.00	28.67	33.65	8.29	32.80	0.00	2.00	39.82	54.00	-14.18	А	1.00

Note :

1. The measurement was searched to 10th harmonic, Remark "---" means that the emissions level is too low to be measured.

2. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)

3. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz

4. Remark "*" means the Restricted band.

5. The result basic equation calculation is as follow:

Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

6. The other emission levels were very low against the limit

7. The test limit distance is 3M limit.



Company	Advance Multimedia Internet Technology Inc.	Test Date	2005/04/06
Product Name	Wireless Broadband Router	Test By	Jerry Chang
Model Name	WUC128	TEMP & Humidity	27 , 58%

		CH6	TX		Ν	Aeası	ıremei	nt Distance	at 3m H	Iorizonta	l polarity	1
	Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
	(MHz)	(dBµV)	(dB/m)	(dB)	(dB)	dB	dB	$(dB\mu V/m)$	(dBµV/m)	(dB)	(P/Q/A)	(Meter)
	2438.85	66.82	29.88	6.04	0.00	0.00	0.00	102.73	Fundam	ental	Р	1.00
	2438.85	57.76	29.88	6.04	0.00	0.00	0.00	93.67	Frequency		А	1.00
	2063.08	49.52	29.13	5.59	31.90	0.00	0.00	52.33	82.73	-30.40	Р	1.00
	2063.08	46.64	29.13	5.59	31.90	0.00	0.00	49.45	73.67	-24.22	А	1.00
*	4874.00	39.74	33.75	8.34	32.81	0.00	1.80	50.82	74.00	-23.18	Р	1.00
*	4874.00	28.28	33.75	8.34	32.81	0.00	1.80	39.36	54.00	-14.64	A	1.00

Note :

1. The measurement was searched to 10th harmonic, Remark "---" means that the emissions level is too low to be measured.

2. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)

3. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz

4. Remark "*" means the Restricted band.

5. The result basic equation calculation is as follow:

Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

6. The other emission levels were very low against the limit

7. The test limit distance is 3M limit.



Company	Advance Multimedia Internet Technology Inc.	Test Date	2005/02/16
Product Name	Wireless Broadband Router	Test By	Jerry Chang
Model Name	WUC128	TEMP & Humidity	26 , 60%

	CH6 TX				Measurement Distance at 3m Vertical polarity							
	Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
	(MHz)	(dBµV)	(dB/m)	(dB)	(dB)	dB	dB	(dBµV/m)	$(dB\mu V/m)$	(dB)	(P/Q/A)	(Meter)
	2431.33	73.45	29.86	6.03	0.00	0.00	0.00	109.34	Fundam	ental	Р	1.00
	2431.33	63.59	29.86	6.03	0.00	0.00	0.00	99.48	Frequency		А	1.00
	2063.06	54.72	29.13	5.59	31.90	0.00	0.00	57.53	89.34	-31.81	Р	1.00
	2063.06	53.14	29.13	5.59	31.90	0.00	0.00	55.95	79.48	-23.53	А	1.00
*	4874.00	39.28	33.75	8.34	32.81	0.00	1.80	50.36	74.00	-23.64	Р	1.00
*	4874.00	28.28	33.75	8.34	32.81	0.00	1.80	39.36	54.00	-14.64	А	1.00

Note :

1. The measurement was searched to 10th harmonic, Remark "---" means that the emissions level is too low to be measured.

2. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)

3. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz

4. Remark "*" means the Restricted band.

5. The result basic equation calculation is as follow:

Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

6. The other emission levels were very low against the limit

7. The test limit distance is 3M limit.



Company	Advance Multimedia Internet Technology Inc.	Test Date	2005/04/06
Product Name	Wireless Broadband Router	Test By	Jerry Chang
Model Name	WUC128	TEMP & Humidity	27 , 58%

	CH11 TX				Measurement Distance at 3m Horizontal polarity						1	
	Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
	(MHz)	(dBµV)	(dB/m)	(dB)	(dB)	dB	dB	$(dB\mu V/m)$	(dBµV/m)	(dB)	(P/Q/A)	(Meter)
	2454.93	66.39	29.91	6.06	0.00	0.00	0.00	102.36	Fundame	ental	Р	1.00
	2454.93	56.93	29.91	6.06	0.00	0.00	0.00	92.90	Freque	ncy	А	1.00
*	2483.50	25.42	29.97	6.09	0.00	0.00	0.00	61.48	74.00	-12.52	Р	1.00
*	2483.50	13.26	29.97	6.09	0.00	0.00	0.00	49.32	54.00	-4.68	А	1.00
*	2483.60	24.36	29.97	6.09	0.00	0.00	0.00	60.42	74.00	-13.58	Р	1.00
*	2483.60	13.48	29.97	6.09	0.00	0.00	0.00	49.54	54.00	-4.46	А	1.00
	2087.96	48.06	29.18	5.62	31.90	0.00	0.00	50.95	82.36	-31.40	Р	1.00
	2087.96	44.11	29.18	5.62	31.90	0.00	0.00	47.00	72.90	-25.89	А	1.00
*	4924.00	40.01	33.85	8.39	32.83	0.00	1.60	51.02	74.00	-22.98	Р	1.00
*	4924.00	28.28	33.85	8.39	32.83	0.00	1.60	39.29	54.00	-14.71	А	1.00

Note :

1. The measurement was searched to 10th harmonic, Remark "---" means that the emissions level is too low to be measured.

2. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)

3. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz

4. Remark "*" means the Restricted band.

5. The result basic equation calculation is as follow:

Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

6. The other emission levels were very low against the limit

7. The test limit distance is 3M limit.



Company	Advance Multimedia Internet Technology Inc.	Test Date	2005/04/06
Product Name	Wireless Broadband Router	Test By	Jerry Chang
Model Name	WUC128	TEMP & Humidity	27 , 58%

	CH11 TX					Measurement Distance at 3m Vertical polarity						
	Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
	(MHz)	(dBµV)	(dB/m)	(dB)	(dB)	dB	dB	$(dB\mu V/m)$	$(dB\mu V/m)$	(dB)	(P/Q/A)	(Meter)
	2463.75	72.58	29.93	6.07	0.00	0.00	0.00	108.57			Р	1.00
	2463.75	63.56	29.93	6.07	0.00	0.00	0.00	99.55			А	1.00
*	2483.50	25.07	29.97	6.09	0.00	0.00	0.00	61.13	74.00	-12.87	Р	1.00
*	2483.50	13.90	29.97	6.09	0.00	0.00	0.00	49.96	54.00	-4.04	А	1.00
*	2483.60	25.47	29.97	6.09	0.00	0.00	0.00	61.53	74.00	-12.47	Р	1.00
*	2483.60	13.69	29.97	6.09	0.00	0.00	0.00	49.75	54.00	-4.25	А	1.00
	2088.06	52.61	29.18	5.62	31.90	0.00	0.00	55.50	88.57	-33.07	Р	1.00
	2088.06	50.65	29.18	5.62	31.90	0.00	0.00	53.54	79.55	-26.01	А	1.00
*	4924.00	39.50	33.85	8.39	32.83	0.00	1.60	50.51	74.00	-23.49	Р	1.00
*	4924.00	28.67	33.85	8.39	32.83	0.00	1.60	39.68	54.00	-14.32	А	1.00

Note :

1. The measurement was searched to 10th harmonic, Remark "---" means that the emissions level is too low to be measured.

2. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)

3. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz

4. Remark "*" means the Restricted band.

5. The result basic equation calculation is as follow:

Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

6. The other emission levels were very low against the limit

7. The test limit distance is 3M limit.



4. 6dB BANDWIDTH MEASUREMENT

4.1 Test Equipments

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration	Calibration Period
ROHDE & SCHWARZ SPECTRUM ANALYZER	FSEM	830270/015	March 18, 2005	1 Year

Note:

- 1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.2 Test Setup



4.3 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is >500 KHz

4.4 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 KHz RBW and 1MHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

4.5 Uncertainty of Conducted Emission

The uncertainty of conducted emission is \pm 200 KHz.



4.6 Test Results

Company	Advance Multimedia Internet Technology Inc	Test Date	2005/04/12
Product Name	Wireless Broadband Router	Test By	Jerry Chang
Model Name	WUC128	TEMP & Humidity	30 , 55%

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	12.26	0.5	PASS
6	2437	12.26	0.5	PASS
11	2462	12.37	0.5	PASS

Note : For 802.11b Mode

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	16.56	0.5	PASS
6	2437	16.56	0.5	PASS
11	2462	16.56	0.5	PASS

Note : For 802.11g Mode







Note: For 802.11b Mode









5. MAXIMUM PEAK OUTPUT POWER

5.1 Test Equipments

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration	Calibratio n Period
ROHDE & SCHWARZ SPECTRUM ANALYZER	FSEM	830270/015	March 18, 2005	1 Year

Note:

- 1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

5.2 Test Setup



5.3 Limits of Maximum Peak Output Power

The Maximum Peak Output Power Measurement is 30dBm.

5.4 Test Procedure

- The spectrum shall be set as follows: Span: 1.5 times channel integration bandwidth. RBW: 1MHz VBW: 3MHz Detector: Peak Sweep: Single trace
- 2. Compute the combined power of all signal responses contained in the trace by covering all the data points.
- 3. For 99% occupied BW, place the markers at the frequency at which 0.5% of the power lies to the right of the right marker and 0.5% of the power lies to the left of the left marker.
- 4. The peak output power is the channel power integrated over 99% bandwidth.



5.5 Uncertainty of Conducted Emission

The uncertainty of conducted emission is \pm 1.82dB.

5.6 Test Results

Company	Advance Multimedia Internet Technology Inc	Test Date	2005/04/12
Product Name	Wireless Broadband Router	Test By	Jerry Chang
Model Name	WUC128	TEMP & Humidity	30 , 55%

Channel	Channel Frequency (MHz)	Peak Power Output (dBm)	Peak Power Limit (dBm)	Pass / Fail
1	2412	18.92	30	PASS
6	2437	18.60	30	PASS
11	2462	18.24	30	PASS

Note :

1. For 802.11b mode.

2. At finial test to get the worst-case emission at 1Mbps.

3. Cable loss = 0.57dB, Attenuator = 10dB.

4. The results are calculated as the following equation : Peak Power Output = Peak Power Reading + Cable loss

Channel	Channel Frequency (MHz)	Peak Power Output (dBm)	Peak Power Limit (dBm)	Pass / Fail
1	2412	17.76	30	PASS
6	2437	17.32	30	PASS
11	2462	16.97	30	PASS

Note :

1. For 802.11g mode.

2. At finial test to get the worst-case emission at 6Mbps.

3. Cable loss = 0.57dB, Attenuator = 10dB.

4. The results are calculated as the following equation :

Peak Power Output = Peak Power Reading + Cable loss

5.7 Photo of Maximum Peak Output Power Measurement



Note: For 802.11b Mode





Note: For normal 802.11g Mode



6. POWER SPECTRAL DENSITY MEASUREMENT

6.1 Test Equipments

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration	Calibratio n Period
ROHDE & SCHWARZ SPECTRUM ANALYZER	FSEM	830270/015	March 18, 2005	1 Year

Note :

- 1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

6.2 Test Setup



6.3 Limits of Power Spectral Density Measurement

The Maximum Power Spectral Density Measurement is 8dBm/3KHz.



6.4 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3KHz RBW and 30KHz VBW, set sweep time=span / 3KHz.

The power spectral density was measured and recorded.

The sweep time is allowed to be longer than span / 3KHz for a full response of the mixer in the spectrum analyzer.

6.5 Uncertainty of Conducted Emission

The uncertainty of conducted emission is \pm 1.82dB.

6.6 Test Results

Company	Advance Multimedia Internet Technology Inc Test Date		2005/04/12
Product Name	Wireless Broadband Router	Test By	Jerry Chang
Model Name	WUC128	TEMP & Humidity	30,55%

Channel	Channel Frequency (MHz)	Final RF Power Level in 3KHz BW (dBm)	Maxmum Limit (dBm)	Pass / Fail
1	2412	-14.93	8	PASS
6	2437	-15.38	8	PASS
11	2462	-15.38	8	PASS

Note : For 11Mbps (802.11b mode) at finial test to get the worst-case emission at 1Mbps.

Channel	Channel Frequency (MHz)	Final RF Power Level in 3KHz BW (dBm)	Maxmum Limit (dBm)	Pass / Fail
1	2412	-16.78	8	PASS
6	2437	-16.69	8	PASS
11	2462	-17.09	8	PASS

Note : For 54Mbps (802.11g mode) at finial test to get the worst-case emission at 6Mbps.





6.7 Photo of Power Spectral Density Measurement

Channel 11 Note: For 802.11b Mode







7. BAND EDGE MEASUREMENT

7.1 Test Equipments

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration	Calibratio n Period
ROHDE & SCHWARZ SPECTRUM ANALYZER	FSEM	830270/015	March 18, 2005	1 Year

Note :

- 1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

7.2 Test Setup



7.3 Limits of Band Edge Emissions Measurement

- 1. Below –20dB of the highest emission level in operating band.
- 2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

7.4 Test Procedure

Section 15.247(d): Spurious emissions. The following tests are required:

Set the span wide enough to capture the peak level of the emission operating on the channel closest to the band edge. Set the RBW and VBW and maxhold the trace. Allow the trace to stabilize. Enable the marker-delta function, then use the marker-delta value function to move the marker to the peak of the in-band emission submit the plot.

7.5 Uncertainty of Conducted Emission

The uncertainty of conducted emission is \pm 1.82dB.



7.6 Test Results

A. Conducted

Refer to 7.7 photo of out band Emission measurement

B. Radiated

Company	Advance Multimedia Internet Technology Inc Test Date		2005/04/12
Product Name	Wireless Broadband Router	Test By	Jerry Chang
Model Name	WUC128	TEMP & Humidity	30 , 55%

For 802.11b mode

Refer to the section 3.6, the measured radiated band edge emissions are listed below:

Band edge Frequency		Measured ra edge field (dBu	diated band strength V/m)	Radiated band edge field strength limit (dBuV/m)		Test result
(MI	Hz)	Horizontal	Vertical	Horizontal	Vertical	
2200.00	PK	63.36	67.93	81.77	90.52	DASS
2399.90	AV	53.92	61.14	78.43	87.24	rass
2482.50	PK	61.07	60.31	74.00	74.00	DACC
2483.50	AV	49.32	49.96	54.00	54.00	PASS

For 802.11g mode

Refer to the section 3.6, the measured radiated band edge emissions are listed below :

Band edge Frequency		Measured ra edge field (dBu	ndiated band l strength V/m)	Radiated band edge field strength limit (dBuV/m)		Test result
(MHz	:)	Horizontal	Vertical	Horizontal	Vertical	
2200.00	РК	67.74	73.97	82.93	90.65	DASS
2399.90	AV	53.21	59.16	72.98	81.20	rass
2482 50	РК	61.48	51.63	74.00	74.00	DASS
2483.50	AV	49.32	40.46	54.00	54.00	r add

Note :

1. Radiated band edge field strength is measured with FCC recommended mark-delta method.

2. Measured radiated band edge field strength Test Results = Radiated fundamental emission field strength - DELTA.

3. DELTA = Relative measurement between conducted measured peak level of fundamental emission and relevant band edge emission. Please refer to 7.7 photo of Band Edge Measurement.







Note: For 802.11b Mode





Note: For 802.11g Mode



8. ANTENNA REQUIREMENT

8.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

8.2 Antenna Connected Construction

The antenna used in this product is Dipole antenna. The maximum Gain of this antenna is 1.8dBi.



9. RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range	Electric Field	Magnetic Field	Power Density	Average Time
(MHz)	Strength (V/m)	Strength (A/m)	(mW/cm ²)	Average Thire
(A) Limits for Occupational / Control Exposures				
300-1,500			F/300	6
1,500-100,000			5	
(B) Limits for General Population / Uncontrol Exposures				
300-1,500	1,500 F/1500		6	
1,500-100,000	1		30	

9.1 Friis Formula

Friis transmission formula: $P_d = (P_{out}*G)/(4*p_i*r^2)$ Where

 $P_d = power density in mW/cm^2$

 $P_{out} = output power to antenna in mW$

G = gain of antenna in linear scale

 $P_i = 3.1416$

r = distance between observation point and center of the radiator in cm

 P_d is the limit of MPE, 1 mW/cm2. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance "r" where the MPE limit is reached.

9.2 EUT Operating Condition

A software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



9.3 Test Result of RF Exposure Evaluation

Test Item	: RF Exposure Evaluation Data
Test Mode	: Normal Operation

9.3.1 Antenna Gain

Antenna Gain : The maximum Gain measured in fully anechoic chamber is 1.514 linear scale.

9.3.2 Output Power into Antenna & RF Exposure Evaluation Distance

Channel	Channel Frequency (MHz)	Output Power to Antenna (dBm)	Power Density at 20cm (mW/cm ²)	LIMITS (mW/cm ²)
1	2412	18.92	0.023482	1
6	2437	18.60	0.021814	1
11	2462	18.24	0.020078	1

Note :

1. For 802.11b mode (1Mbps).

- 2. The power density Pd (4th column) at a distance of 20cm calculated from the friis transmission formula is far below the limit of 1 mW/cm². The EUT is classified as mobile product. So, RF exposure limit warning or SAR test are not required.
- 3. The EUT is classified as mobile module. RF exposure evaluation will be evaluated after the EUT is installed with the host.

Channel	Channel Frequency (MHz)	Output Power to Antenna (dBm)	Power Density at 20cm (mW/cm ²)	LIMITS (mW/cm ²)
1	2412	17.76	0.017978	1
6	2437	17.32	0.016245	1
11	2462	16.97	0.014988	1

Note :

- 2. The power density Pd (4th column) at a distance of 20cm calculated from the friis transmission formula is far below the limit of 1 mW/cm^2 . The EUT is classified as mobile product. So, RF exposure limit warning or SAR test are not required.
- 3. The EUT is classified as mobile module. RF exposure evaluation will be evaluated after the EUT is installed with the host.