



BEC INCORPORATED

SAR EXEMPTION REPORT

**TEST STANDARDS:
FCC Part 15 Subpart C Intentional Radiator**

**Lutron Model JPZ0148
LED Lighting Controller with BLE Radio**

FCC ID: JPZ0148

REPORT BEC-2259-05

**CUSTOMER:
Lutron Electronics Company Incorporated
7200 Suter Road
Coopersburg, PA 18036**

PREPARED BY: Thomas Koester
Thomas Koester, Test Engineer

REVIEWED and APPROVED BY: Steve Fanella
Steve Fanella, Quality Manager

The results described in this report relate only to the item(s) tested. This document shall not be reproduced except in full without prior written permission of BEC Incorporated





TABLE OF CONTENTS

Notice to Customer	3
Revision History	3
1.0 Administrative Information.....	4
1.1 General Information Table	4
2.0 Applicable Requirements, Methods, and Procedures	5
2.1 Applicable Requirements	5
2.2 Referenced Documents	5
2.3 Limits for Exemption	5
2.4 Separation Distance Rationale	5
3.0 Maximum Permissible Exposure.....	6
3.1 Maximum Permissible Exposure Calculation Referenced Sections Used	6
3.2 Maximum Permissible Exposure Calculation Results	8
Appendix A – Test Equipment.....	9



Notice to Customer

This report and any recommendations it contain represent the result of BEC's testing and assessment on behalf of your company. Testing has been conducted according to accepted engineering standards and practices. This report reflects testing and assessment of product samples provided by your company and may not reflect the characteristics of other samples, especially those produced at different times. Therefore, this report and its findings and recommendations, if implemented, should not be construed as an assurance or implied warranty for the continuing electromagnetic compatibility (EMC) of the product. **BEC shall not be liable for incidental or consequential damages, even if advised of the possibility thereof.**

BEC will not disseminate this report to other parties without your express permission. You may reproduce this report in its entirety including this notice and the entireties of any supplemental test reports on the same product (e.g. reports on additional testing following modification). However 'you may not reproduce portions of the report (except for the entirety of the summary section) or quote from it for any purpose without specific prior written permission from BEC'.

The BEC Decision Rule: Measurement Uncertainty is not applied to any testing measurements or test results provided to the customer by BEC Incorporated at this time.

Revision History

Revision #	Description of Changes	Date of Changes	Date Released
0	Test Report Initial Release	N/A	07/27/2023



1.0 Administrative Information

1.1 General Information Table

Project Number	BEC-2259
Manufacturer	Lutron Electronics
Model Number	JPZ0148
EUT Description	LED Lighting Controller with BLE Radio
Sample Type	Modified with SMA connector on transmitter output port (Antenna Conducted Test Sample)
Sample Number	2259-03
Serial Numbers	02F25720
FCC ID	JPZ0148
Frequency of Operation	2400 – 2480 MHz
Frequencies Tested	Low 1 Mbps (2402 MHz) Low 2 Mbps (2404 MHz), Middle (2440 MHz), High (2480 MHz)
Antenna Gain	+ 4.30 dBi, + 2.15 dBd
Tune Up Tolerance	+/- 1.0 dBm
Antenna Type	Planar Inverted-F PCB Trace Antenna (PIFA)
Modulation	GFSK
FCC Classification	Digital Transmission System (DTS)
Date Samples Received	06/05/2023
EUT Firmware Version	lorikeet_app_001.037.003
Applicable FCC Rules	47 CFR Part 2.1093
KDB Guidance Document	447498 D04 Interim General RF Exposure Guidance v01
Separation Distance	The separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm.
Device Type	Mobile Device



2.0 Applicable Requirements, Methods, and Procedures

2.1 Applicable Requirements

The results of the measurement of the radio disturbance characteristics of the EUT described herein may be applied and where appropriate, provide a presumption of compliance to one or more of the following requirements or to other requirements at the discretion of the customer, regulatory agencies, or other entities.

2.2 Referenced Documents

The following are documents referenced in the SAR Exemption Calculation for this device.

KDB Document KDB 447498 D04 Interim General RF Exposure Guidance v01

FCC eCFR 47 Chapter 1, Subchapter A, Part 1, Section § 1.1310(d)(2) MPE limits in § 1.1310(e)(1) - Table 1

2.3 Limits for Exemption

Table 1 – Synopsis of FCC RF Exposure Limits for Mobile and Portable Devices

Frequency f		FCC RF Exposure Limits
$f \leq 100$ kHz		All devices assessed case-by-case (guidelines for wireless power transfer devices are provided KDB Pub. 680106)
$100 \text{ kHz} < f \leq 300 \text{ kHz}$		SAR limits in § 1.1310 (b), (c), (d)
$300 \text{ kHz} < f \leq 6 \text{ GHz}$	Portable device	SAR limits in § 1.1310 (b), (c), (d)
	Mobile device	Per § 2.1093(d) SAR limits in § 1.1310 (b), (c), (d) OR Per § 1.1310(d)(2) MPE limits in § 1.1310(e)(1) - Table 1
$f > 6 \text{ GHz}$		For all devices, MPE limits in § 1.1310(e)(1) - Table 1

2.4 Separation Distance Rationale

The Lutron JPZ0148 is a LED lighting controller which is installed in an area away from the user and is controlled remotely by a different product. The manufacturer declares a minimum separation distance of 20 cm between user and device. This device is designed to be mounted on a wall at a height of traditional lighting control devices. The highest output power, based upon the measurements below, is used to compute the exemption limit for Routine Evaluation.



3.0 Maximum Permissible Exposure

3.1 Maximum Permissible Exposure Calculation Referenced Sections Used

§15.247 Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

- (i) Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. *See* §1.1307(b)(1) of this chapter.

§1.1307 Actions that may have a significant environmental effect, for which Environmental Assessments (EAs) must be prepared.

(b)(1) The appropriate exposure limits in §§1.1310 and 2.1093 of this chapter are generally applicable to all facilities, operations and transmitters regulated by the Commission.

§1.1310 Radiofrequency radiation exposure limits.

(2) At operating frequencies less than or equal to 6 GHz, the limits for maximum permissible exposure (MPE), derived from whole-body Specific Absorption Rate (SAR) limits and listed in Table 1 of paragraph (e) of this section, may be used instead of whole-body SAR limits as set forth in paragraph (a) through (c) of this section to evaluate the environmental impact of human exposure to RF radiation as specified in §1.1307(b), except for portable devices as defined in §2.1093 as these evaluations shall be performed according to the SAR provisions in §2.1093 of this chapter.

(4) Both the MPE limits listed in Table 1 of paragraph (e) of this section and the SAR limits as set forth in paragraph (a) through (c) of this section and in §2.1093 of this chapter are for continuous exposure, that is, for indefinite time periods. Exposure levels higher than the limits are permitted for shorter exposure times, as long as the average exposure over the specified averaging time in Table 1 is less than the limits. Detailed information on our policies regarding procedures for evaluating compliance with all of these exposure limits can be found in the FCC's *OET Bulletin 65*, "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields," and in supplements to *Bulletin 65*, all available at the FCC's Internet Web site: <http://www.fcc.gov/oet/rfsafety>



§2.1093 Radiofrequency radiation exposure evaluation: portable devices.

(b) For purposes of this section, a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

From: OET Bulletin 65 Edition 97-02, page 19.

$$S = \frac{PG}{4\pi R^2} \quad (3)$$

where: S = Power Density (in appropriate units, e.g., mW/cm²)
P = Power input to the antenna (in appropriate units, e.g., mW)
G = Power Gain of the antenna (numeric) in the direction of interest to an isotropic radiator
R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

or:
$$S = \frac{EIRP}{4\pi R^2} \quad (4)$$

where: EIRP = equivalent (or effective) isotropically radiated power



3.2 Maximum Permissible Exposure Calculation Results

Using Limits Per § 1.1310(d)(2) MPE limits in § 1.1310(e)(1) -Table 1

Calculation

1. $P(\text{dBm}) = \text{Maximum conducted output power (dBm)} + \text{Tune-up Tolerance (dB)}$
2. $P(\text{dBm})$ is converted to $P(\text{mW})$
3. $P(\text{mW}) = 1\text{mW} * 10^{(P(\text{dBm})/10)}$
4. $G (\text{numeric}) = 10^{(\text{Antenna Gain}/10)}$
5. Calculate S (Power Density) using Equation (3)

EUT Transmission Signal Type	Frequency	Max Power Input P(dBm)	Converted Power Input P(mW)	G = Power Gain (numeric)	S = Power Density @ 20 cm	1.1310 Radio Frequency Radiation Exposure Limits (Tx Frequency 1500 to 100000 MHz)	Margin
	MHz	dBm	mW	dBd	mW/cm ²	mW/cm ²	
DTS - BLE Modulated with GFSK at 2 Mbps Data Rate	2480.0	12.07	0.0161	2.692	0.0086	1.00	-0.9914

Antenna power shown in the above table reflect the highest measured levels among the low, middle and high frequencies for the DTS transmitter.

Results: The maximum calculated Power Density of the measurements for the DTS transmitter contained in the Lutron JPZ0148 is a LED lighting controller is 0.0086 mW/cm². This complies with the limit of 1.0 mW/cm² from Table 1(ii) of 47 CFR Part 1.1310(e)(1). Therefore, exposure evaluation is not required.



Appendix A – Test Equipment

Equipment	Manufacturer	Model #	Serial #	BEC #	Calibration Date	Calibration Cycle	Calibration Due Date
EMI Receiver (20 Hz – 26.5 GHz)	Rohde & Schwarz	ESIB 26	836119/006	1010	12/09/22	3 Years	12/09/25