

APPENDIX H: LTE AND NR LOWER BANDWIDTH RF CONDUCTED POWERS

Note: Some bands do not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 1 of 222

H.1 LTE Lower Bandwidth RF Conducted Powers

H.1.1 LTE Band 71

Table H-1
LTE Band 71 Ant A Measured P_{Max} for all DSI - 15 MHz Bandwidth

LTE Band 71 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133297 (680.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.40	0	0
	1	36	24.38		0
	1	74	24.20		0
	36	0	23.15	0-1	1
	36	18	23.11		1
	36	37	23.18		1
	75	0	23.09		1
16QAM	1	0	23.46	0-1	1
	1	36	23.44		1
	1	74	23.35		1
	36	0	22.18	0-2	2
	36	18	22.11		2
	36	37	22.21		2
	75	0	22.10		2
64QAM	1	0	22.31	0-2	2
	1	36	22.26		2
	1	74	22.03		2
	36	0	21.11	0-3	3
	36	18	21.10		3
	36	37	21.19		3
	75	0	21.18		3
256QAM	1	0	19.27	0-5	5
	1	36	19.31		5
	1	74	19.22		5
	36	0	19.02		5
	36	18	19.07		5
	36	37	19.11		5
	75	0	19.10		5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 2 of 222

Table H-2
LTE Band 71 Ant A Measured P_{Max} for all DSI - 10 MHz Bandwidth

LTE Band 71 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133172 (668.0 MHz)	133297 (680.5 MHz)	133422 (693.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.29	24.16	23.90	0	0
	1	25	23.94	24.26	24.19		0
	1	49	24.04	24.31	24.04		0
	25	0	23.08	23.16	23.23	0-1	1
	25	12	23.16	23.17	23.27		1
	25	25	23.12	23.19	23.18		1
16QAM	50	0	23.17	23.17	23.18	0-1	1
	1	0	23.35	23.41	23.48		1
	1	25	23.31	23.45	23.39		1
	1	49	23.30	23.33	23.11	0-2	1
	25	0	22.14	22.25	22.24		2
	25	12	22.30	22.12	22.32		2
64QAM	25	25	22.20	22.25	22.22	0-2	2
	50	0	22.15	22.14	22.23		2
	1	0	22.43	22.37	22.50	0-2	2
	1	25	22.46	22.41	22.43		2
	1	49	22.32	22.42	22.27		2
	256QAM	25	0	21.06	21.24	21.30	0-3
25		12	21.26	21.24	21.32	3	
25		25	21.16	21.23	21.26	3	
50		0	21.16	21.19	21.14	3	
256QAM	1	0	19.26	18.99	19.20	0-5	5
	1	25	19.28	19.22	19.47		5
	1	49	19.20	19.30	19.11		5
	25	0	19.07	18.96	19.17		5
	25	12	19.16	19.13	19.30		5
	25	25	19.11	19.15	19.27		5
	50	0	19.13	19.07	19.11		5

Table H-3
LTE Band 71 Ant A Measured P_{Max} for all DSI - 5 MHz Bandwidth

LTE Band 71 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133147 (665.5 MHz)	133297 (680.5 MHz)	133447 (695.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.26	24.16	24.11	0	0
	1	12	24.08	24.28	24.34		0
	1	24	23.97	24.19	23.96		0
	12	0	23.21	23.16	23.22	0-1	1
	12	6	23.29	23.19	23.20		1
	12	13	23.16	23.22	23.24		1
16QAM	25	0	23.15	23.10	23.15	0-1	1
	1	0	23.74	23.42	23.43		1
	1	12	23.82	23.69	23.40		1
	1	24	23.49	23.44	23.18	0-2	1
	12	0	22.24	22.20	22.18		2
	12	6	22.33	22.18	22.23		2
64QAM	12	13	22.20	22.18	22.24	0-2	2
	25	0	22.15	22.16	22.18		2
	1	0	22.48	22.33	22.48		0-2
	1	12	22.48	22.39	22.40	2	
	1	24	22.37	22.41	22.11	2	
	256QAM	12	0	21.20	21.16	21.19	0-3
12		6	21.25	21.21	21.22	3	
12		13	21.15	21.24	21.21	3	
25		0	21.17	21.12	21.20	0-5	3
1		0	19.20	19.17	19.13		5
1		12	19.29	19.47	19.42		5
1	24	19.03	19.19	19.15	5		
12	0	19.16	19.14	19.10	5		
12	6	19.16	19.12	19.13	5		
256QAM	12	13	19.12	19.18	19.09	0-5	5
	25	0	19.07	19.12	19.10		5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 3 of 222

Table H-4
LTE Band 71 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

LTE Band 71 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133297 (680.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.58	0	0
	1	36	24.70		0
	1	74	24.67		0
	36	0	23.46	0-1	1
	36	18	23.35		1
	36	37	23.40		1
	75	0	23.36		1
16QAM	1	0	23.74	0-1	1
	1	36	23.60		1
	1	74	23.42		1
	36	0	22.51	0-2	2
	36	18	22.48		2
	36	37	22.52		2
	75	0	22.49		2
64QAM	1	0	22.74	0-2	2
	1	36	22.60		2
	1	74	22.50		2
	36	0	21.44	0-3	3
	36	18	21.39		3
	36	37	21.50		3
	75	0	21.44		3
256QAM	1	0	19.47	0-5	5
	1	36	19.59		5
	1	74	19.42		5
	36	0	19.33		5
	36	18	19.30		5
	36	37	19.40		5
	75	0	19.38		5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 4 of 222

Table H-5

LTE Band 71 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

LTE Band 71 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133172 (668.0 MHz)	133297 (680.5 MHz)	133422 (693.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.54	24.46	24.36	0	0
	1	25	24.42	24.60	24.54		0
	1	49	24.35	24.39	24.45		0
	25	0	23.55	23.51	23.49	0-1	1
	25	12	23.56	23.52	23.64		1
	25	25	23.57	23.57	23.52		1
16QAM	50	0	23.47	23.46	23.50	0-1	1
	1	0	23.86	23.73	23.73		1
	1	25	23.56	23.84	23.56		1
	1	49	23.46	23.62	23.35	0-2	1
	25	0	22.52	22.49	22.52		2
	25	12	22.54	22.61	22.58		2
64QAM	25	25	22.60	22.59	22.56	0-2	2
	50	0	22.42	22.47	22.51		2
	1	0	22.67	22.49	22.57	0-2	2
	1	25	22.74	22.79	22.59		2
	1	49	22.41	22.71	23.05		2
	25	0	21.43	21.49	21.48	0-3	3
25	12	21.57	21.50	21.57	3		
25	25	21.51	21.52	21.45	3		
256QAM	50	0	21.54	21.46	21.49	0-5	3
	1	0	19.47	19.46	19.50		5
	1	25	19.46	19.60	19.99		5
	1	49	19.51	19.49	19.35		5
	25	0	19.37	19.46	19.46		5
	25	12	19.45	19.44	19.57		5
256QAM	25	25	19.55	19.45	19.49	0-5	5
	50	0	19.50	19.48	19.37		5

Table H-6

LTE Band 71 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 71 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133147 (665.5 MHz)	133297 (680.5 MHz)	133447 (695.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.62	24.58	24.43	0	0
	1	12	24.70	24.57	24.52		0
	1	24	24.43	24.44	24.32		0
	12	0	23.52	23.41	23.43	0-1	1
	12	6	23.50	23.51	23.47		1
	12	13	23.41	23.52	23.52		1
16QAM	25	0	23.44	23.42	23.43	0-1	1
	1	0	23.93	23.81	23.68		1
	1	12	23.80	23.92	23.72		1
	1	24	23.56	23.88	23.77	0-2	1
	12	0	22.62	22.50	22.48		2
	12	6	22.54	22.54	22.46		2
64QAM	12	13	22.47	22.57	22.44	0-2	2
	25	0	22.48	22.45	22.36		2
	1	0	22.62	22.73	22.53		0-2
	1	12	22.78	22.80	22.75	2	
	1	24	22.46	22.70	22.56	0-3	
	12	0	21.52	21.43	21.46		3
12	6	21.57	21.50	21.51	3		
256QAM	12	13	21.51	21.49	21.51	0-3	3
	25	0	21.41	21.42	21.43		3
	1	0	19.64	19.51	19.58		0-5
	1	12	19.43	19.52	19.49	5	
	1	24	19.33	19.50	19.45	5	
	12	0	19.45	19.39	19.40	5	
12	6	19.41	19.50	19.43	5		
12	13	19.32	19.49	19.40	5		
	25	0	19.37	19.37	19.41		5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 5 of 222

Table H-7
LTE Band 71 Ant E Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

LTE Band 71 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133297 (680.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	21.56	0	0
	1	36	21.71		0
	1	74	21.75		0
	36	0	21.65	0-1	0
	36	18	21.70		0
	36	37	21.57		0
	75	0	21.63		0
16QAM	1	0	21.82	0-1	0
	1	36	21.85		0
	1	74	21.58		0
	36	0	21.73	0-2	0
	36	18	21.67		0
	36	37	21.70		0
	75	0	21.75		0
64QAM	1	0	21.86	0-2	0
	1	36	21.85		0
	1	74	21.77		0
	36	0	21.46	0-3	0.5
	36	18	21.45		0.5
	36	37	21.49		0.5
	75	0	21.35		0.5
256QAM	1	0	19.41	0-5	2.5
	1	36	19.60		2.5
	1	74	19.45		2.5
	36	0	19.35		2.5
	36	18	19.25		2.5
	36	37	19.30		2.5
	75	0	19.35		2.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 6 of 222

Table H-8
LTE Band 71 Ant E Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

LTE Band 71 10 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			133172 (668.0 MHz)	133297 (680.5 MHz)	133422 (693.0 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	21.78	21.71	21.61	0	0	
	1	25	21.78	21.78	21.69		0	
	1	49	21.74	21.65	21.48		0	
	25	0	21.71	21.56	21.53	0-1	0	
	25	12	21.61	21.67	21.59		0	
	25	25	21.77	21.63	21.64		0	
16QAM	50	0	21.47	21.72	21.58	0-1	0	
	1	0	21.85	21.84	21.83		0	
	1	25	21.83	21.79	21.80		0	
	1	49	21.78	21.73	21.69	0-2	0	
	25	0	21.65	21.80	21.67		0	
	25	12	21.67	21.53	21.67		0	
64QAM	25	25	21.75	21.78	21.68	0-2	0	
	50	0	21.61	21.76	21.55		0	
	1	0	21.82	21.85	21.84		0-2	0
	1	25	21.84	21.80	21.82	0		
	1	49	21.80	21.78	21.78	0		
	25	0	21.50	21.45	21.30	0-3	0.5	
25	12	21.46	21.46	21.42	0.5			
25	25	21.51	21.50	21.35	0.5			
256QAM	50	0	21.40	21.47	21.30	0-3	0.5	
	1	0	19.45	19.34	19.52		0-5	2.5
	1	25	19.63	19.64	19.43			2.5
	1	49	19.54	19.50	19.59	2.5		
	25	0	19.34	19.50	19.32	2.5		
	25	12	19.43	19.39	19.36	2.5		
25	25	19.48	19.40	19.33	2.5			
	50	0	19.49	19.29	19.29	2.5		

Table H-9
LTE Band 71 Ant E Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 71 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133147 (665.5 MHz)	133297 (680.5 MHz)	133447 (695.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.66	21.64	21.50	0	0
	1	12	21.71	21.66	21.61		0
	1	24	21.57	21.61	21.40		0
	12	0	21.73	21.59	21.58	0-1	0
	12	6	21.66	21.73	21.56		0
	12	13	21.71	21.73	21.57		0
	25	0	21.67	21.69	21.58	0	
16QAM	1	0	21.70	21.75	21.68	0-1	0
	1	12	21.60	21.68	21.70		0
	1	24	21.58	21.60	21.66		0
	12	0	21.72	21.70	21.57	0-2	0
	12	6	21.82	21.77	21.51		0
	12	13	21.76	21.64	21.59		0
	25	0	21.71	21.71	21.52	0	
64QAM	1	0	21.80	21.71	21.73	0-2	0
	1	12	21.76	21.78	21.85		0
	1	24	21.77	21.76	21.58		0
	12	0	21.46	21.44	21.38	0-3	0.5
	12	6	21.60	21.43	21.32		0.5
	12	13	21.53	21.45	21.26		0.5
	25	0	21.37	21.31	21.25		0.5
256QAM	1	0	19.52	19.45	19.31	0-5	2.5
	1	12	19.54	19.62	19.33		2.5
	1	24	19.47	19.44	19.23		2.5
	12	0	19.48	19.50	19.18		2.5
	12	6	19.41	19.33	19.27		2.5
	12	13	19.43	19.40	19.28		2.5
	25	0	19.42	19.33	19.14		2.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 7 of 222

H.1.2 LTE Band 12

Table H-10
LTE Band 12 Ant A Measured P_{Max} for all DSI - 5 MHz Bandwidth

LTE Band 12 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.16	24.22	24.17	0	0
	1	12	24.18	24.21	24.17		0
	1	24	24.07	24.01	24.13		0
	12	0	23.07	23.12	23.15	0-1	1
	12	6	23.19	23.20	23.19		1
	12	13	23.03	23.17	23.20		1
16QAM	25	0	23.12	23.12	23.10	0-1	1
	1	0	23.26	23.38	23.61		1
	1	12	23.33	23.59	23.56		1
	1	24	23.33	23.26	23.45	0-2	1
	12	0	22.09	22.09	22.17		2
	12	6	22.24	22.25	22.27		2
64QAM	12	13	22.09	22.09	22.18	0-2	2
	25	0	22.08	22.19	22.11		2
	1	0	22.30	22.23	22.28	0-2	2
	1	12	22.32	22.43	22.65		2
	1	24	22.29	22.46	22.19		2
	256QAM	12	0	21.08	21.02	21.05	0-3
12		6	21.19	21.23	21.18	3	
12		13	21.12	21.19	21.16	3	
25		0	21.17	21.18	21.21	0-5	3
1		0	19.01	19.15	19.22		5
1		12	19.15	19.21	19.14		5
1	24	19.11	19.15	19.15	5		
12	0	19.06	19.12	19.03	5		
12	6	19.21	19.19	19.17	5		
256QAM	12	13	19.02	19.07	19.08	0-5	5
	25	0	19.03	19.10	19.01		5

Table H-11
LTE Band 12 Ant A Measured P_{Max} for all DSI - 3 MHz Bandwidth

LTE Band 12 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.27	24.05	24.08	0	0
	1	7	24.15	24.12	24.31		0
	1	14	24.05	24.07	24.01		0
	8	0	23.12	23.03	23.08	0-1	1
	8	4	23.12	23.20	23.16		1
	8	7	23.11	23.19	23.28		1
16QAM	15	0	23.14	23.16	23.10	0-1	1
	1	0	23.23	23.37	23.22		1
	1	7	23.34	23.61	23.53		1
	8	0	22.15	22.15	22.22	0-2	2
	8	4	22.15	22.31	22.28		2
	8	7	22.19	22.13	22.17		2
64QAM	15	0	22.16	22.22	22.23	0-2	2
	1	0	22.21	22.11	22.23		2
	1	7	22.36	22.28	22.41		2
	1	14	22.25	22.16	22.40	0-3	2
	8	0	21.19	21.10	21.20		3
	8	4	21.15	21.24	21.22		3
256QAM	8	7	21.19	21.24	21.22	0-5	3
	15	0	21.15	21.20	21.07		3
	1	0	19.09	18.99	19.00		5
	1	7	19.26	19.30	19.43		5
	1	14	19.06	19.06	19.05		5
	8	0	19.15	19.05	19.09		5
256QAM	8	4	19.09	19.16	19.20	0-5	5
	8	7	19.10	19.13	19.12		5
	15	0	19.11	19.12	19.06		5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 8 of 222

Table H-12
LTE Band 12 Ant A Measured P_{Max} for all DSI – 1.4 MHz Bandwidth

LTE Band 12 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.35	23.93	24.15	0	0
	1	2	24.02	24.05	23.99		0
	1	5	24.05	24.02	24.08		0
	3	0	24.04	24.03	24.13		0
	3	2	24.07	24.08	24.01		0
	3	3	23.94	24.09	24.08		0
	6	0	23.08	23.08	23.11		0-1
16QAM	1	0	23.33	23.35	23.35	0-1	1
	1	2	23.50	23.19	23.28		1
	1	5	23.17	23.33	23.34		1
	3	0	23.21	23.19	23.31		1
	3	2	23.08	23.23	23.20		1
	3	3	23.22	23.18	23.36		1
	6	0	22.11	22.30	22.26		0-2
64QAM	1	0	22.60	22.70	22.45	0-2	2
	1	2	22.41	22.20	22.51		2
	1	5	22.18	22.25	22.24		2
	3	0	22.40	22.09	22.22		2
	3	2	22.03	22.20	22.32		2
	3	3	22.23	22.37	22.15		2
	6	0	21.08	21.19	21.08		0-3
256QAM	1	0	19.13	19.02	19.20	0-5	5
	1	2	19.29	19.17	19.20		5
	1	5	19.17	19.13	19.17		5
	3	0	19.13	19.06	19.23		5
	3	2	19.22	19.16	19.14		5
	3	3	19.13	19.23	19.18		5
	6	0	19.09	19.13	19.18		5

Table H-13
LTE Band 12 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 12 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.40	24.42	24.49	0	0
	1	12	24.33	24.53	24.38		0
	1	24	24.36	24.32	24.48		0
	12	0	23.34	23.33	23.42	0-1	1
	12	6	23.48	23.55	23.45		1
	12	13	23.44	23.36	23.45		1
	25	0	23.39	23.40	23.41		1
16QAM	1	0	23.63	23.84	23.74	0-1	1
	1	12	23.68	23.65	23.89		1
	1	24	23.66	23.62	23.84		1
	12	0	22.37	22.50	22.45	0-2	2
	12	6	22.45	22.51	22.49		2
	12	13	22.38	22.41	22.44		2
	25	0	22.45	22.48	22.35		2
64QAM	1	0	22.62	22.51	22.63	0-2	2
	1	12	22.54	22.53	22.67		2
	1	24	22.51	22.60	22.53		2
	12	0	21.41	21.37	21.42	0-3	3
	12	6	21.46	21.46	21.45		3
	12	13	21.39	21.37	21.44		3
	25	0	21.40	21.41	21.34		3
256QAM	1	0	19.42	19.36	19.44	0-5	5
	1	12	19.54	19.59	19.53		5
	1	24	19.38	19.36	19.41		5
	12	0	19.31	19.31	19.36		5
	12	6	19.39	19.48	19.38		5
	12	13	19.36	19.35	19.46		5
	25	0	19.39	19.38	19.35		5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 9 of 222

Table H-14

LTE Band 12 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 3 MHz Bandwidth

LTE Band 12 3 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	24.38	24.37	24.31	0	0	
	1	7	24.31	24.38	24.56		0	
	1	14	24.48	24.32	24.28		0	
	8	0	23.39	23.39	23.41	0-1	1	
	8	4	23.53	23.49	23.58		1	
	8	7	23.47	23.42	23.46		1	
16QAM	15	0	23.48	23.43	23.39	0-1	1	
	1	0	23.59	23.69	23.56		0-1	1
	1	7	23.72	23.65	23.52			1
	1	14	23.61	23.76	23.65	0-2		1
	8	0	22.49	22.50	22.44		2	
	8	4	22.48	22.45	22.50		2	
64QAM	8	7	22.48	22.46	22.49	0-2	2	
	15	0	22.42	22.41	22.41		2	
	1	0	22.44	22.49	22.50		0-2	2
	1	7	22.64	22.70	22.83	2		
	1	14	22.54	22.51	22.52	0-3		2
	8	0	21.47	21.46	21.47		3	
8	4	21.45	21.49	21.59	3			
256QAM	8	7	21.43	21.52	21.43	0-3	3	
	15	0	21.45	21.43	21.42		3	
	1	0	19.31	19.29	19.17		0-5	5
	1	7	19.64	19.43	19.51	5		
	1	14	19.37	19.45	19.32	5		
	8	0	19.31	19.35	19.31	5		
8	4	19.39	19.40	19.46	5			
8	7	19.35	19.36	19.43	5			
	15	0	19.35	19.36	19.31		5	

Table H-15

LTE Band 12 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) – 1.4 MHz Bandwidth

LTE Band 12							
1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.35	24.35	24.43	0	0
	1	2	24.37	24.33	24.48		0
	1	5	24.35	24.38	24.40		0
	3	0	24.30	24.33	24.31		0
	3	2	24.33	24.31	24.32		0
	3	3	24.33	24.37	24.45		0
	6	0	23.33	23.44	23.37	0-1	1
16QAM	1	0	23.70	23.78	23.61	0-1	1
	1	2	23.51	23.77	23.88		1
	1	5	23.53	23.67	23.51		1
	3	0	23.57	23.52	23.54		1
	3	2	23.51	23.52	23.43		1
	3	3	23.75	23.60	23.44		1
	6	0	22.44	22.45	22.40	0-2	2
64QAM	1	0	22.65	22.57	22.41	0-2	2
	1	2	22.78	22.84	22.72		2
	1	5	22.38	22.32	22.63		2
	3	0	22.58	22.47	22.59		2
	3	2	22.51	22.47	22.48		2
	3	3	22.47	22.42	22.49		2
	6	0	21.43	21.36	21.47	0-3	3
256QAM	1	0	19.40	19.33	19.54	0-5	5
	1	2	19.52	19.56	19.43		5
	1	5	19.45	19.39	19.40		5
	3	0	19.45	19.32	19.37		5
	3	2	19.45	19.32	19.41		5
	3	3	19.41	19.65	19.51		5
	6	0	19.33	19.31	19.39	5	

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 10 of 222

Table H-16
LTE Band 12 Ant E Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 12 5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	21.48	21.44	21.48	0	0	
	1	12	21.45	21.59	21.64		0	
	1	24	21.50	21.49	21.52		0	
	12	0	21.49	21.50	21.49	0-1	0	
	12	6	21.60	21.64	21.65		0	
	12	13	21.60	21.61	21.61		0	
16QAM	25	0	21.54	21.49	21.56	0-1	0	
	1	0	21.80	21.62	21.70		0	
	1	12	21.59	21.79	21.68		0	
	1	24	21.75	21.77	21.70	0-2	0	
	12	0	21.56	21.44	21.48		0	
	12	6	21.61	21.58	21.70		0	
64QAM	12	13	21.74	21.74	21.63	0-2	0	
	25	0	21.51	21.59	21.52		0	
	1	0	21.70	21.68	21.81		0-2	0
	1	12	21.68	21.65	21.75	0		
	1	24	21.71	21.58	21.70	0		
	256QAM	12	0	21.56	21.52	21.26	0-3	0.5
12		6	21.62	21.52	21.40	0.5		
12		13	21.65	21.51	21.23	0.5		
25		0	21.22	21.25	21.25	0.5		
256QAM		1	0	19.37	19.36	19.31	0-5	2.5
		1	12	19.16	19.27	19.30		2.5
	1	24	19.36	19.22	19.16	2.5		
	12	0	19.15	19.22	19.17	2.5		
	12	6	19.16	19.19	19.32	2.5		
	12	13	19.27	19.30	19.21	2.5		
25	0	19.22	19.13	19.19	2.5			

Table H-17
LTE Band 12 Ant E Measured P_{Limit} for DSI = 1 (Head) - 3 MHz Bandwidth

LTE Band 12 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.42	21.37	21.38	0	0
	1	7	21.54	21.42	21.63		0
	1	14	21.38	21.44	21.44		0
	8	0	21.36	21.68	21.45	0-1	0
	8	4	21.50	21.50	21.56		0
	8	7	21.37	21.53	21.51		0
	15	0	21.58	21.49	21.46		0
16QAM	1	0	21.68	21.65	21.56	0-1	0
	1	7	21.70	21.68	21.68		0
	1	14	21.60	21.62	21.62		0
	8	0	21.64	21.51	21.55	0-2	0
	8	4	21.63	21.64	21.56		0
	8	7	21.56	21.45	21.61		0
	15	0	21.66	21.59	21.52		0
64QAM	1	0	21.53	21.56	21.50	0-2	0
	1	7	21.63	21.81	21.61		0
	1	14	21.46	21.72	21.61		0
	8	0	21.29	21.33	21.26	0-3	0.5
	8	4	21.37	21.35	21.33		0.5
	8	7	21.24	21.38	21.30		0.5
	15	0	21.35	21.29	21.20		0.5
256QAM	1	0	19.08	19.13	19.25	0-5	2.5
	1	7	19.46	19.44	19.24		2.5
	1	14	19.08	19.22	19.18		2.5
	8	0	19.36	19.26	19.15		2.5
	8	4	19.32	19.32	19.27		2.5
	8	7	19.17	19.20	19.31		2.5
	15	0	19.27	19.25	19.30		2.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 11 of 222

Table H-18
LTE Band 12 Ant E Measured P_{Limit} for DSI = 1 (Head) – 1.4 MHz Bandwidth

LTE Band 12 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.48	21.49	21.35	0	0
	1	2	21.43	21.43	21.38		0
	1	5	21.50	21.34	21.34		0
	3	0	21.38	21.49	21.50		0
	3	2	21.40	21.33	21.33		0
	3	3	21.40	21.55	21.34		0
	6	0	21.49	21.53	21.42	0-1	0
16QAM	1	0	21.59	21.48	21.84	0-1	0
	1	2	21.54	21.59	21.61		0
	1	5	21.63	21.64	21.67		0
	3	0	22.01	21.52	21.49		0
	3	2	21.72	21.54	21.54		0
	3	3	21.55	21.54	21.77		0
	6	0	21.52	21.59	21.55	0-2	0
64QAM	1	0	21.53	21.58	21.65	0-2	0
	1	2	21.61	21.82	21.66		0
	1	5	21.66	21.68	21.56		0
	3	0	21.64	22.11	21.61		0
	3	2	21.62	21.61	21.50		0
	3	3	21.85	21.88	21.57		0
	6	0	21.23	21.28	21.32	0-3	0.5
256QAM	1	0	19.42	19.26	19.14	0-5	2.5
	1	2	19.43	19.36	19.34		2.5
	1	5	19.12	19.44	19.29		2.5
	3	0	19.25	19.17	19.38		2.5
	3	2	19.24	19.17	19.14		2.5
	3	3	19.28	19.09	19.50		2.5
	6	0	19.21	19.14	19.14	2.5	

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 12 of 222

H.1.3 LTE Band 13

Table H-19
LTE Band 13 Ant A Measured P_{Max} for all DSI - 5 MHz Bandwidth

LTE Band 13 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.08	0	0
	1	12	24.12		0
	1	24	24.13		0
	12	0	23.00	0-1	1
	12	6	23.14		1
	12	13	23.03		1
	25	0	23.08		1
16QAM	1	0	23.39	0-1	1
	1	12	23.43		1
	1	24	23.38		1
	12	0	22.04	0-2	2
	12	6	22.10		2
	12	13	22.07		2
	25	0	21.98		2
64QAM	1	0	22.19	0-2	2
	1	12	22.25		2
	1	24	22.27		2
	12	0	20.98	0-3	3
	12	6	21.11		3
	12	13	21.03		3
	25	0	20.95		3
256QAM	1	0	18.95	0-5	5
	1	12	19.26		5
	1	24	19.10		5
	12	0	19.07		5
	12	6	19.13		5
	12	13	19.08		5
	25	0	19.01		5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 13 of 222

Table H-20
LTE Band 13 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 13 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.27	0	0
	1	12	24.23		0
	1	24	24.27		0
	12	0	23.25	0-1	1
	12	6	23.32		1
	12	13	23.25		1
	25	0	23.24		1
16QAM	1	0	23.67	0-1	1
	1	12	23.63		1
	1	24	23.44		1
	12	0	22.23	0-2	2
	12	6	22.26		2
	12	13	22.28		2
	25	0	22.17		2
64QAM	1	0	22.32	0-2	2
	1	12	22.63		2
	1	24	22.42		2
	12	0	21.27	0-3	3
	12	6	21.30		3
	12	13	21.21		3
	25	0	21.29		3
256QAM	1	0	19.27	0-5	5
	1	12	19.37		5
	1	24	19.26		5
	12	0	19.22		5
	12	6	19.25		5
	12	13	19.22		5
	25	0	19.13		5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 14 of 222

Table H-21
LTE Band 13 Ant E Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 13 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	21.33	0	0
	1	12	21.38		0
	1	24	21.44		0
	12	0	21.33	0-1	0
	12	6	21.48		0
	12	13	21.42		0
	25	0	21.39		0
16QAM	1	0	21.40	0-1	0
	1	12	21.43		0
	1	24	21.44		0
	12	0	21.39	0-2	0
	12	6	21.47		0
	12	13	21.40		0
	25	0	21.41		0
64QAM	1	0	21.37	0-2	0
	1	12	21.39		0
	1	24	21.33		0
	12	0	21.07	0-3	0.5
	12	6	21.16		0.5
	12	13	21.15		0.5
	25	0	21.09		0.5
256QAM	1	0	19.15	0-5	2.5
	1	12	19.25		2.5
	1	24	19.16		2.5
	12	0	19.13		2.5
	12	6	19.15		2.5
	12	13	19.10		2.5
	25	0	19.19		2.5

H.1.4 LTE Band 14

Table H-22
LTE Band 14 Ant A Measured P_{Max} for all DSI - 5 MHz Bandwidth

LTE Band 14 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23330 (793.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	23.90	0	0
	1	12	23.96		0
	1	24	23.88		0
	12	0	22.91	0-1	1
	12	6	22.91		1
	12	13	22.93		1
	25	0	22.87		1
16QAM	1	0	23.34	0-1	1
	1	12	23.37		1
	1	24	23.22		1
	12	0	21.92	0-2	2
	12	6	21.99		2
	12	13	21.95		2
	25	0	21.91		2
64QAM	1	0	22.08	0-2	2
	1	12	22.21		2
	1	24	22.14		2
	12	0	20.85	0-3	3
	12	6	20.95		3
	12	13	20.94		3
	25	0	20.89		3
256QAM	1	0	18.86	0-5	5
	1	12	19.03		5
	1	24	18.96		5
	12	0	18.85		5
	12	6	18.89		5
	12	13	18.87		5
	25	0	18.84		5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 16 of 222

Table H-23
LTE Band 14 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 14 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23330 (793.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.35	0	0
	1	12	24.42		0
	1	24	24.35		0
	12	0	23.37	0-1	1
	12	6	23.48		1
	12	13	23.42		1
	25	0	23.39		1
16QAM	1	0	23.58	0-1	1
	1	12	23.74		1
	1	24	23.70		1
	12	0	22.40	0-2	2
	12	6	22.53		2
	12	13	22.42		2
	25	0	22.39		2
64QAM	1	0	22.52	0-2	2
	1	12	22.63		2
	1	24	22.58		2
	12	0	21.33	0-3	3
	12	6	21.47		3
	12	13	21.39		3
	25	0	21.44		3
256QAM	1	0	19.37	0-5	5
	1	12	19.59		5
	1	24	19.31		5
	12	0	19.38		5
	12	6	19.34		5
	12	13	19.32		5
	25	0	19.36		5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 17 of 222

Table H-24
LTE Band 14 Ant E Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 14 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23330 (793.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	21.54	0	0
	1	12	21.66		0
	1	24	21.46		0
	12	0	21.61	0-1	0
	12	6	21.67		0
	12	13	21.61		0
	25	0	21.55		0
16QAM	1	0	21.69	0-1	0
	1	12	21.72		0
	1	24	21.70		0
	12	0	21.62	0-2	0
	12	6	21.73		0
	12	13	21.60		0
	25	0	21.64		0
64QAM	1	0	21.80	0-2	0
	1	12	21.80		0
	1	24	21.66		0
	12	0	21.38	0-3	0.5
	12	6	21.39		0.5
	12	13	21.33		0.5
	25	0	21.36		0.5
256QAM	1	0	19.27	0-5	2.5
	1	12	19.52		2.5
	1	24	19.29		2.5
	12	0	19.28		2.5
	12	6	19.31		2.5
	12	13	19.31		2.5
	25	0	19.34		2.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 18 of 222

H.1.5 LTE Band 26

Table H-25
LTE Band 26 Ant A Measured P_{Max} for all DSI - 10 MHz Bandwidth

LTE Band 26 (Cell) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26740 (819.0 MHz)	26865 (831.5 MHz)	26990 (844.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.47	23.97	24.35	0	0
	1	25	24.45	24.29	24.36		0
	1	49	24.28	24.40	24.33		0
	25	0	23.26	23.36	23.30	0-1	1
	25	12	23.32	23.29	23.39		1
	25	25	23.28	23.36	23.37		1
	50	0	23.27	23.26	23.24	1	
16QAM	1	0	23.32	23.44	23.40	0-1	1
	1	25	23.56	23.65	23.28		1
	1	49	23.46	23.73	23.34		1
	25	0	22.31	22.37	22.30	0-2	2
	25	12	22.30	22.29	22.27		2
	25	25	22.28	22.32	22.38		2
	50	0	22.33	22.29	22.29		2
64QAM	1	0	22.36	22.33	22.44	0-2	2
	1	25	22.41	22.70	22.31		2
	1	49	22.29	22.33	22.35		2
	25	0	21.27	21.29	21.29	0-3	3
	25	12	21.34	21.40	21.25		3
	25	25	21.35	21.39	21.36		3
	50	0	21.32	21.26	21.15		3
256QAM	1	0	19.23	19.18	19.44	0-5	5
	1	25	19.43	19.42	19.35		5
	1	49	19.28	19.35	19.37		5
	25	0	19.19	19.27	19.20		5
	25	12	19.26	19.32	19.22		5
	25	25	19.30	19.31	19.33		5
	50	0	19.30	19.25	19.22		5

Table H-26
LTE Band 26 Ant A Measured P_{Max} for all DSI - 5 MHz Bandwidth

LTE Band 26 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26715 (816.5 MHz)	26865 (831.5 MHz)	27015 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.25	24.49	24.34	0	0
	1	12	24.26	24.42	24.35		0
	1	24	24.24	24.21	24.19		0
	12	0	23.27	23.35	23.36	0-1	1
	12	6	23.35	23.39	23.32		1
	12	13	23.28	23.32	23.29		1
16QAM	25	0	23.32	23.28	23.26	0-1	1
	1	0	23.71	23.40	23.71		1
	1	12	23.48	23.51	23.51	0-1	1
	1	24	23.45	23.35	23.37		1
	12	0	22.29	22.43	22.31	0-2	2
	12	6	22.36	22.37	22.36		2
12	13	22.32	22.42	22.38	2		
64QAM	25	0	22.29	22.30	22.17	0-2	2
	1	0	22.34	22.51	22.49		2
	1	12	22.44	22.67	22.60	0-2	2
	1	24	22.41	22.37	22.32		2
	12	0	21.27	21.37	21.30	0-3	3
	12	6	21.34	21.36	21.33		3
12	13	21.28	21.43	21.29	3		
256QAM	25	0	21.31	21.31	21.31	0-5	3
	1	0	19.12	19.46	19.27		5
	1	12	19.38	19.43	19.52		5
	1	24	19.26	19.38	19.27		5
	12	0	19.18	19.28	19.28		5
	12	6	19.31	19.29	19.31		5
	12	13	19.26	19.31	19.30		5
	25	0	19.26	19.23	19.18		5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 19 of 222

Table H-27
LTE Band 26 Ant A Measured P_{Max} for all DSI - 3 MHz Bandwidth

LTE Band 26 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26705 (815.5 MHz)	26865 (831.5 MHz)	27025 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.25	24.36	24.29	0	0
	1	7	24.28	24.48	24.24		0
	1	14	24.14	24.29	24.30		0
	8	0	23.32	23.30	23.32	0-1	1
	8	4	23.31	23.28	23.31		1
	8	7	23.31	23.39	23.32		1
	15	0	23.26	23.33	23.22		1
16QAM	1	0	23.54	23.39	23.63	0-1	1
	1	7	23.50	23.57	23.68		1
	1	14	23.41	23.50	23.58		1
	8	0	22.39	22.31	22.29	0-2	2
	8	4	22.41	22.40	22.32		2
	8	7	22.37	22.43	22.37		2
	15	0	22.31	22.29	22.32		2
64QAM	1	0	22.40	22.74	22.52	0-2	2
	1	7	22.50	22.46	22.53		2
	1	14	22.34	22.39	22.28		2
	8	0	21.35	21.29	21.29	0-3	3
	8	4	21.37	21.40	21.34		3
	8	7	21.26	21.37	21.28		3
	15	0	21.32	21.36	21.21		3
256QAM	1	0	19.11	19.41	19.30	0-5	5
	1	7	19.35	19.32	19.38		5
	1	14	19.26	19.27	19.18		5
	8	0	19.24	19.26	19.25		5
	8	4	19.30	19.30	19.24		5
	8	7	19.23	19.30	19.26		5
	15	0	19.25	19.28	19.20		5

Table H-28
LTE Band 26 Ant A Measured P_{Max} for all DSI – 1.4 MHz Bandwidth

LTE Band 26 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26697 (814.7 MHz)	26865 (831.5 MHz)	27033 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.43	24.38	24.28	0	0
	1	2	24.26	24.29	24.32		0
	1	5	24.28	24.21	24.26		0
	3	0	24.25	24.24	24.24		0
	3	2	24.32	24.27	24.32		0
	3	3	24.35	24.36	24.35		0
	6	0	22.89	22.82	22.76	0-1	1
16QAM	1	0	23.48	23.52	23.35	0-1	1
	1	2	23.43	23.69	23.40		1
	1	5	23.33	23.68	23.54		1
	3	0	23.42	23.53	23.36		1
	3	2	23.53	23.38	23.39		1
	3	3	23.47	23.39	23.47		1
	6	0	22.45	22.26	22.31	0-2	2
64QAM	1	0	22.56	22.62	22.51	0-2	2
	1	2	22.47	22.58	22.56		2
	1	5	22.45	22.69	22.30		2
	3	0	22.39	22.22	22.48		2
	3	2	22.19	22.49	22.55		2
	3	3	22.34	22.54	22.42		2
	6	0	21.27	21.26	21.37	0-3	3
256QAM	1	0	19.41	19.36	19.30	0-5	5
	1	2	19.23	19.47	19.33		5
	1	5	19.32	19.28	19.24		5
	3	0	19.27	19.21	19.31		5
	3	2	19.37	19.24	19.27		5
	3	3	19.28	19.32	19.22		5
	6	0	19.15	19.14	19.21		5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 20 of 222

Table H-29

LTE Band 26 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

LTE Band 26 (Cell) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26740 (819.0 MHz)	26865 (831.5 MHz)	26990 (844.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.84	24.73	24.81	0	0
	1	25	24.97	24.93	24.84		0
	1	49	24.67	24.55	24.98		0
	25	0	23.69	23.69	23.71	0-1	1
	25	12	23.79	23.65	23.75		1
	25	25	23.76	23.65	23.75		1
	50	0	23.66	23.59	23.67		1
16QAM	1	0	23.85	23.80	23.71	0-1	1
	1	25	23.89	23.88	23.87		1
	1	49	23.88	23.82	23.89		1
	25	0	22.75	22.72	22.79	0-2	2
	25	12	22.70	22.71	22.70		2
	25	25	22.73	22.69	22.82		2
	50	0	22.59	22.60	22.74		2
64QAM	1	0	22.72	22.80	22.81	0-2	2
	1	25	22.91	22.73	22.90		2
	1	49	22.74	22.81	22.92		2
	25	0	21.59	21.63	21.73	0-3	3
	25	12	21.72	21.72	21.71		3
	25	25	21.74	21.67	21.75		3
	50	0	21.68	21.61	21.73		3
256QAM	1	0	19.68	19.73	19.74	0-5	5
	1	25	19.92	19.73	20.00		5
	1	49	19.80	19.65	19.84		5
	25	0	19.63	19.66	19.66		5
	25	12	19.67	19.65	19.64		5
	25	25	19.66	19.64	19.79		5
	50	0	19.62	19.61	19.74		5

Table H-30

LTE Band 26 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 26 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26715 (816.5 MHz)	26865 (831.5 MHz)	27015 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.68	24.58	24.65	0	0
	1	12	24.82	24.73	24.92		0
	1	24	24.68	24.64	24.60		0
	12	0	23.72	23.71	23.75	0-1	1
	12	6	23.74	23.66	23.75		1
	12	13	23.79	23.60	23.74		1
	25	0	23.63	23.55	23.71		1
16QAM	1	0	23.99	23.80	23.98	0-1	1
	1	12	23.96	23.95	24.00		1
	1	24	23.95	23.83	23.96		1
	12	0	22.80	22.71	22.75	0-2	2
	12	6	22.78	22.73	22.69		2
	12	13	22.74	22.70	22.77		2
	25	0	22.72	22.59	22.73		2
64QAM	1	0	22.90	22.80	22.99	0-2	2
	1	12	22.91	22.99	22.96		2
	1	24	22.96	22.81	22.93		2
	12	0	21.73	21.70	21.67	0-3	3
	12	6	21.76	21.66	21.78		3
	12	13	21.72	21.66	21.79		3
	25	0	21.63	21.64	21.61		3
256QAM	1	0	19.66	19.56	19.80	0-5	5
	1	12	19.68	19.80	19.84		5
	1	24	19.68	19.64	19.77		5
	12	0	19.64	19.66	19.66		5
	12	6	19.63	19.61	19.62		5
	12	13	19.74	19.64	19.77		5
	25	0	19.66	19.57	19.69		5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 21 of 222

Table H-31

LTE Band 26 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 3 MHz Bandwidth

LTE Band 26 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26705 (815.5 MHz)	26865 (831.5 MHz)	27025 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.75	24.61	24.76	0	0
	1	7	24.65	24.79	24.87		0
	1	14	24.62	24.77	24.52		0
	8	0	23.73	23.69	23.73	0-1	1
	8	4	23.74	23.64	23.71		1
	8	7	23.67	23.66	23.72		1
	15	0	23.74	23.61	23.73		1
16QAM	1	0	23.76	23.80	23.92	0-1	1
	1	7	23.86	23.96	23.85		1
	1	14	23.99	23.83	23.73		1
	8	0	22.72	22.62	22.73	0-2	2
	8	4	22.77	22.71	22.73		2
	8	7	22.69	22.70	22.74		2
	15	0	22.75	22.69	22.73		2
64QAM	1	0	22.93	22.80	22.89	0-2	2
	1	7	22.78	22.97	22.90		2
	1	14	22.81	22.83	22.82		2
	8	0	21.73	21.72	21.60	0-3	3
	8	4	21.78	21.67	21.74		3
	8	7	21.62	21.68	21.75		3
	15	0	21.62	21.65	21.70		3
256QAM	1	0	19.58	19.69	19.78	0-5	5
	1	7	19.68	19.82	19.83		5
	1	14	19.68	19.64	19.74		5
	8	0	19.61	19.60	19.75		5
	8	4	19.65	19.64	19.66		5
	8	7	19.62	19.63	19.74		5
	15	0	19.70	19.63	19.71		5

Table H-32

LTE Band 26 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) – 1.4 MHz Bandwidth

LTE Band 26 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26697 (814.7 MHz)	26865 (831.5 MHz)	27033 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.43	24.38	24.28	0	0
	1	2	24.26	24.29	24.32		0
	1	5	24.28	24.21	24.26		0
	3	0	24.25	24.24	24.24		0
	3	2	24.32	24.27	24.32		0
	3	3	24.35	24.36	24.35	0	
	6	0	22.83	22.82	22.76	0-1	1
16QAM	1	0	23.48	23.52	23.35	0-1	1
	1	2	23.43	23.69	23.40		1
	1	5	23.33	23.68	23.54		1
	3	0	23.42	23.53	23.36		1
	3	2	23.53	23.38	23.39		1
	3	3	23.47	23.39	23.47	1	
	6	0	22.45	22.26	22.31	0-2	2
64QAM	1	0	22.56	22.62	22.51	0-2	2
	1	2	22.47	22.58	22.56		2
	1	5	22.45	22.69	22.30		2
	3	0	22.39	22.22	22.48		2
	3	2	22.19	22.49	22.55		2
	3	3	22.34	22.54	22.42	2	
	6	0	21.27	21.26	21.37	0-3	3
256QAM	1	0	19.41	19.36	19.30	0-5	5
	1	2	19.23	19.47	19.33		5
	1	5	19.32	19.28	19.24		5
	3	0	19.27	19.21	19.31		5
	3	2	19.37	19.24	19.27		5
	3	3	19.28	19.32	19.22	5	
	6	0	19.15	19.14	19.21		5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 22 of 222

Table H-33
LTE Band 26 Ant E Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

LTE Band 26 (Cell) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26740 (819.0 MHz)	26865 (831.5 MHz)	26990 (844.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.36	21.28	21.30	0	0
	1	25	21.50	21.33	21.52		0
	1	49	21.38	21.27	21.38		0
	25	0	21.38	21.41	21.42	0-1	0
	25	12	21.36	21.38	21.39		0
	25	25	21.44	21.33	21.51		0
	50	0	21.39	21.31	21.42		0
16QAM	1	0	21.60	21.63	21.59	0-1	0
	1	25	21.62	21.54	21.62		0
	1	49	21.58	21.54	21.59		0
	25	0	21.45	21.39	21.34	0-2	0
	25	12	21.41	21.43	21.44		0
	25	25	21.33	21.41	21.49		0
	50	0	21.44	21.38	21.36		0
64QAM	1	0	21.57	21.60	21.51	0-2	0
	1	25	21.52	21.57	21.58		0
	1	49	21.50	21.44	21.55		0
	25	0	21.46	21.41	21.46	0-3	0
	25	12	21.41	21.41	21.51		0
	25	25	21.54	21.36	21.51		0
	50	0	21.39	21.36	21.38		0
256QAM	1	0	19.63	19.81	19.72	0-5	2
	1	25	19.83	19.81	19.77		2
	1	49	19.53	19.58	19.73		2
	25	0	19.61	19.56	19.61		2
	25	12	19.57	19.61	19.62		2
	25	25	19.59	19.63	19.73		2
	50	0	19.61	19.60	19.63		2

Table H-34
LTE Band 26 Ant E Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 26 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26715 (816.5 MHz)	26865 (831.5 MHz)	27015 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.35	21.27	21.30	0	0
	1	12	21.41	21.33	21.46		0
	1	24	21.24	21.26	21.32		0
	12	0	21.35	21.38	21.43	0-1	0
	12	6	21.36	21.42	21.44		0
	12	13	21.36	21.39	21.42		0
	25	0	21.39	21.28	21.44		0
16QAM	1	0	21.60	21.57	21.53	0-1	0
	1	12	21.51	21.55	21.57		0
	1	24	21.51	21.51	21.56		0
	12	0	21.47	21.45	21.41	0-2	0
	12	6	21.43	21.42	21.49		0
	12	13	21.41	21.42	21.53		0
	25	0	21.41	21.39	21.42		0
64QAM	1	0	21.63	21.60	21.61	0-2	0
	1	12	21.58	21.61	21.63		0
	1	24	21.51	21.51	21.58		0
	12	0	21.39	21.44	21.39	0-3	0
	12	6	21.44	21.44	21.52		0
	12	13	21.46	21.46	21.44		0
	25	0	21.36	21.44	21.45		0
256QAM	1	0	19.57	19.63	19.70	0-5	2
	1	12	19.78	19.79	19.80		2
	1	24	19.64	19.62	19.63		2
	12	0	19.55	19.59	19.64		2
	12	6	19.58	19.63	19.63		2
	12	13	19.63	19.64	19.67		2
	25	0	19.58	19.60	19.68		2

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 23 of 222

Table H-35
LTE Band 26 Ant E Measured P_{Limit} for DSI = 1 (Head) - 3 MHz Bandwidth

LTE Band 26 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26705 (815.5 MHz)	26865 (831.5 MHz)	27025 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.18	21.28	21.43	0	0
	1	7	21.30	21.36	21.47		0
	1	14	21.23	21.27	21.33		0
	8	0	21.40	21.36	21.45	0-1	0
	8	4	21.42	21.34	21.42		0
	8	7	21.32	21.37	21.56		0
16QAM	15	0	21.37	21.38	21.39	0-1	0
	1	0	21.46	21.37	21.56		0
	1	7	21.51	21.52	21.54		0
	1	14	21.51	21.54	21.57	0-2	0
	8	0	21.37	21.35	21.45		0
	8	4	21.39	21.50	21.38		0
64QAM	8	7	21.36	21.47	21.44	0-2	0
	15	0	21.38	21.38	21.45		0
	1	0	21.27	21.53	21.62		0-3
	1	7	21.55	21.65	21.64	0	
	1	14	21.57	21.54	21.44	0	
	8	0	21.38	21.28	21.49	0	
256QAM	8	4	21.32	21.32	21.43	0-3	0
	8	7	21.39	21.44	21.48		0
	15	0	21.44	21.40	21.44		0
	1	0	19.59	19.58	19.78	0-5	2
	1	7	19.54	19.77	19.72		2
	1	14	19.50	19.77	19.65		2
	8	0	19.67	19.56	19.69		2
	8	4	19.59	19.66	19.64		2
8	7	19.49	19.65	19.68	2		
15	0	19.53	19.55	19.48	2		

Table H-36
LTE Band 26 Ant E Measured P_{Limit} for DSI = 1 (Head) – 1.4 MHz Bandwidth

LTE Band 26 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26697 (814.7 MHz)	26865 (831.5 MHz)	27033 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.23	21.27	21.43	0	0
	1	2	21.32	21.39	21.36		0
	1	5	21.29	21.28	21.42		0
	3	0	21.26	21.29	21.41		0
	3	2	21.37	21.34	21.41		0
	3	3	21.37	21.39	21.41		0
16QAM	6	0	21.37	21.41	21.42	0-1	0
	1	0	21.60	21.65	21.65		0
	1	2	21.55	21.60	21.60	0-1	0
	1	5	21.51	21.01	21.35		0
	3	0	21.70	21.46	21.51		0
	3	2	21.36	21.46	21.49		0
64QAM	3	3	21.28	21.46	21.58	0-2	0
	6	0	21.25	21.44	21.52		0
	1	0	21.30	21.58	21.63	0-2	0
	1	2	21.40	21.57	21.50		0
	1	5	21.60	21.23	21.62		0
	3	0	21.53	21.35	21.60		0
256QAM	3	2	21.39	21.48	21.50	0-3	0
	3	3	21.57	21.43	21.58		0
	6	0	21.42	21.36	21.45	0-5	0
	1	0	19.73	19.45	19.69		2
	1	2	19.53	19.75	19.86		2
	1	5	19.60	19.76	19.76		2
	3	0	19.60	19.60	19.58		2
	3	2	19.42	19.66	19.76		2
3	3	19.38	19.64	19.81	2		
6	0	19.36	19.53	19.58	2		

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 24 of 222

H.1.6 LTE Band 66

Table H-37
LTE Band 66 (AWS) Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.96	18.92	18.71	0	0
	1	36	18.76	18.90	18.98		0
	1	74	18.85	18.88	19.03		0
	36	0	18.78	18.81	18.79	0-1	0
	36	18	18.69	18.85	18.82		0
	36	37	18.95	18.88	18.90		0
	75	0	18.84	18.82	18.77		0
16QAM	1	0	19.04	18.92	19.03	0-1	0
	1	36	19.09	19.30	19.06		0
	1	74	18.93	19.02	19.00		0
	36	0	18.90	18.83	18.87	0-2	0
	36	18	18.89	18.87	19.10		0
	36	37	18.94	19.10	18.94		0
	75	0	18.83	18.84	18.81		0
64QAM	1	0	18.99	18.99	19.10	0-2	0
	1	36	19.14	19.10	18.76		0
	1	74	18.83	19.13	19.06		0
	36	0	18.88	19.10	18.81	0-3	0
	36	18	18.99	18.92	19.30		0
	36	37	18.95	19.13	18.89		0
	75	0	18.85	18.74	18.97		0
256QAM	1	0	18.62	18.55	18.58	0-5	0.5
	1	36	18.55	18.70	18.49		0.5
	1	74	18.48	18.84	18.68		0.5
	36	0	18.38	18.55	18.39		0.5
	36	18	18.55	18.45	18.51		0.5
	36	37	18.60	18.59	18.61		0.5
	75	0	18.64	18.49	18.46		0.5

Table H-38
LTE Band 66 (AWS) Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.90	18.79	18.87	0	0
	1	25	18.78	18.91	18.80		0
	1	49	18.81	18.89	18.91		0
	25	0	18.82	18.89	18.86	0-1	0
	25	12	19.02	18.85	18.92		0
	25	25	18.94	18.94	18.88		0
	50	0	18.76	18.88	18.87		0
16QAM	1	0	19.02	19.22	19.00	0-1	0
	1	25	19.03	19.06	19.00		0
	1	49	18.98	19.06	19.06		0
	25	0	18.85	18.79	18.88	0-2	0
	25	12	18.91	18.92	18.84		0
	25	25	18.88	18.87	19.00		0
	50	0	18.93	18.82	18.82		0
64QAM	1	0	18.82	18.93	19.02	0-2	0
	1	25	19.06	19.01	19.05		0
	1	49	19.03	18.96	19.11		0
	25	0	18.76	18.83	18.78	0-3	0
	25	12	18.79	19.02	18.74		0
	25	25	18.80	18.99	18.78		0
	50	0	18.72	18.99	18.94		0
256QAM	1	0	18.55	18.54	18.60	0-5	0.5
	1	25	18.71	18.64	18.88		0.5
	1	49	18.41	18.65	18.64		0.5
	25	0	18.52	18.59	18.41		0.5
	25	12	18.56	18.64	18.57		0.5
	25	25	18.66	18.55	18.57		0.5
	50	0	18.45	18.34	18.55		0.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 25 of 222

Table H-39
LTE Band 66 (AWS) Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 5 MHz Bandwidth

LTE Band 66 (AWS)							
5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.83	18.80	19.07	0	0
	1	12	18.95	18.93	19.04		0
	1	24	18.91	18.80	18.83		0
	12	0	19.02	18.92	18.77	0-1	0
	12	6	18.99	19.02	18.86		0
	12	13	19.01	18.93	18.98		0
	25	0	18.96	18.79	18.74		0
16QAM	1	0	19.40	19.22	19.16	0-1	0
	1	12	19.20	19.35	19.01		0
	1	24	19.30	19.20	19.13		0
	12	0	19.07	18.83	18.82	0-2	0
	12	6	19.38	19.00	18.76		0
	12	13	18.89	18.94	18.60		0
	25	0	19.03	18.76	18.85		0
64QAM	1	0	18.99	18.82	18.81	0-2	0
	1	12	19.13	18.98	18.96		0
	1	24	19.38	19.07	18.90		0
	12	0	19.10	18.86	18.89	0-3	0
	12	6	19.09	18.97	18.94		0
	12	13	18.98	18.60	18.88		0
	25	0	18.90	18.77	18.86		0
256QAM	1	0	18.65	18.70	18.48	0-5	0.5
	1	12	18.85	18.49	18.65		0.5
	1	24	18.68	18.47	18.62		0.5
	12	0	18.62	18.49	18.56		0.5
	12	6	18.68	18.51	18.51		0.5
	12	13	18.65	18.62	18.58		0.5
	25	0	18.64	18.40	18.48		0.5

Table H-40
LTE Band 66 (AWS) Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.72	18.71	18.92	0	0
	1	7	18.91	18.97	18.85		0
	1	14	18.70	18.89	18.88		0
	8	0	18.77	18.90	18.85	0-1	0
	8	4	18.92	18.95	18.96		0
	8	7	19.17	19.02	18.93		0
	15	0	18.80	18.73	18.81		0
16QAM	1	0	18.94	19.10	19.16	0-1	0
	1	7	18.96	19.26	19.04		0
	1	14	19.00	19.11	18.97		0
	8	0	18.84	19.20	18.87	0-2	0
	8	4	18.97	18.98	19.16		0
	8	7	18.98	18.93	19.12		0
	15	0	18.91	18.80	18.88		0
64QAM	1	0	18.91	18.91	18.81	0-2	0
	1	7	19.08	19.04	19.12		0
	1	14	18.88	19.02	18.80		0
	8	0	18.79	18.87	18.77	0-3	0
	8	4	19.04	19.03	18.86		0
	8	7	18.95	18.88	18.95		0
	15	0	18.89	18.45	18.66		0
256QAM	1	0	18.57	18.44	18.35	0-5	0.5
	1	7	18.73	18.62	18.67		0.5
	1	14	18.43	18.84	18.54		0.5
	8	0	18.55	18.49	18.46		0.5
	8	4	18.59	18.72	18.54		0.5
	8	7	18.54	18.49	18.52		0.5
	15	0	18.55	18.52	18.48		0.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 26 of 222

Table H-41
LTE Band 66 (AWS) Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.84	18.96	18.78	0	0
	1	2	18.63	18.74	18.85		0
	1	5	18.74	18.79	18.75		0
	3	0	18.82	18.76	18.64		0
	3	2	18.79	18.77	18.64		0
	3	3	19.04	18.88	18.63		0
	6	0	18.82	18.80	18.77		0
16QAM	1	0	19.10	19.16	19.05	0-1	0
	1	2	19.29	19.05	18.90		0
	1	5	19.27	19.12	19.06		0
	3	0	19.04	18.89	18.88		0
	3	2	18.96	18.91	19.14		0
	3	3	19.01	19.19	19.04		0
	6	0	19.15	18.71	18.56		0
64QAM	1	0	19.19	19.16	19.00	0-2	0
	1	2	19.13	18.84	18.97		0
	1	5	19.22	19.08	19.08		0
	3	0	18.97	19.01	19.23		0
	3	2	18.92	19.23	18.89		0
	3	3	19.00	18.98	18.79		0
	6	0	19.00	18.96	18.99		0
256QAM	1	0	18.59	18.61	18.70	0-5	0.5
	1	2	18.65	18.58	18.36		0.5
	1	5	18.73	18.86	18.66		0.5
	3	0	18.62	18.65	18.50		0.5
	3	2	18.48	18.71	18.75		0.5
	3	3	18.54	18.76	18.49		0.5
	6	0	18.61	18.50	18.38		0.5

Table H-42
LTE Band 66 (AWS) Ant A Measured P_{Max} for DSI = 1 (Head) – 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.61	23.74	23.66	0	0
	1	36	23.86	23.42	23.33		0
	1	74	23.60	23.55	23.64		0
	36	0	22.46	22.48	22.48	0-1	1
	36	18	22.55	22.48	22.15		1
	36	37	23.00	22.57	22.58		1
	75	0	22.62	22.41	21.91	1	
16QAM	1	0	22.71	22.75	22.59	0-1	1
	1	36	22.79	22.64	22.71		1
	1	74	22.90	22.91	22.63		1
	36	0	21.60	21.39	21.55	0-2	2
	36	18	21.63	21.51	21.79		2
	36	37	21.63	21.59	21.56		2
	75	0	21.27	21.44	21.49	2	
64QAM	1	0	21.69	21.72	21.79	0-2	2
	1	36	21.79	21.73	21.78		2
	1	74	21.62	21.70	21.66		2
	36	0	20.57	20.38	20.48	0-3	3
	36	18	20.68	20.53	20.63		3
	36	37	20.61	20.57	20.61		3
	75	0	20.20	20.38	20.30	3	
256QAM	1	0	18.52	18.62	18.59	0-5	5
	1	36	18.51	18.58	18.78		5
	1	74	18.69	18.61	18.66		5
	36	0	18.53	18.52	18.55		5
	36	18	18.62	18.43	18.62		5
	36	37	18.55	18.63	18.61		5
	75	0	18.61	18.45	18.63		5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 27 of 222

Table H-43
LTE Band 66 (AWS) Ant A Measured P_{Max} for DSI = 1 (Head) – 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.71	23.51	23.64	0	0
	1	25	23.53	23.50	23.66		0
	1	49	23.66	23.69	23.76		0
	25	0	22.43	22.49	22.58	0-1	1
	25	12	22.93	22.60	22.43		1
	25	25	22.10	22.54	22.25		1
	50	0	22.67	22.39	22.11		1
16QAM	1	0	22.75	22.51	22.76	0-1	1
	1	25	22.78	22.99	22.66		1
	1	49	22.73	22.62	22.80		1
	25	0	21.32	21.42	21.56	0-2	2
	25	12	21.68	21.01	21.68		2
	25	25	21.24	21.69	21.67		2
	50	0	21.18	21.51	21.43		2
64QAM	1	0	21.62	21.67	21.96	0-2	2
	1	25	21.88	21.89	21.59		2
	1	49	21.72	21.55	21.92		2
	25	0	20.39	20.46	20.23	0-3	3
	25	12	20.76	20.46	20.61		3
	25	25	20.67	20.77	20.76		3
	50	0	20.66	20.49	20.57		3
256QAM	1	0	18.63	18.60	18.60	0-5	5
	1	25	18.75	18.79	18.68		5
	1	49	18.69	18.52	18.70		5
	25	0	18.60	18.58	18.47		5
	25	12	18.70	18.51	18.66		5
	25	25	18.72	18.69	18.65		5
	50	0	18.69	18.51	18.53		5

Table H-44
LTE Band 66 (AWS) Ant A Measured P_{Max} for DSI = 1 (Head) – 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.56	23.61	23.50	0	0
	1	12	23.72	23.39	23.57		0
	1	24	23.66	23.49	23.61		0
	12	0	22.64	22.52	22.50	0-1	1
	12	6	23.00	22.52	22.66		1
	12	13	22.59	22.54	22.57		1
	25	0	22.64	22.45	22.55		1
16QAM	1	0	22.70	22.76	22.94	0-1	1
	1	12	22.79	22.81	22.76		1
	1	24	22.94	22.80	22.69		1
	12	0	21.64	21.75	21.43	0-2	2
	12	6	21.72	21.57	21.68		2
	12	13	21.68	21.26	21.65		2
	25	0	21.63	21.95	21.45		2
64QAM	1	0	21.84	21.70	21.72	0-2	2
	1	12	21.86	21.60	21.86		2
	1	24	21.73	21.65	21.72		2
	12	0	20.88	20.44	20.51	0-3	3
	12	6	20.77	20.27	20.68		3
	12	13	20.68	20.67	20.58		3
	25	0	20.71	21.00	20.55		3
256QAM	1	0	18.58	18.56	18.60	0-5	5
	1	12	18.82	18.76	18.61		5
	1	24	18.70	18.65	18.81		5
	12	0	18.70	18.42	18.57		5
	12	6	18.76	18.54	18.70		5
	12	13	18.69	18.53	18.64		5
	25	0	18.67	18.43	18.56		5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 28 of 222

Table H-45
LTE Band 66 (AWS) Ant A Measured P_{Max} for DSI = 1 (Head) – 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.55	23.40	23.37	0	0
	1	7	23.75	23.67	23.55		0
	1	14	23.59	23.49	23.52		0
	8	0	22.63	22.38	22.59	0-1	1
	8	4	22.83	22.54	22.56		1
	8	7	22.60	22.50	22.35		1
	15	0	22.77	22.50	22.57		1
16QAM	1	0	22.64	22.60	22.73	0-1	1
	1	7	22.84	22.80	22.76		1
	1	14	22.87	22.77	22.63		1
	8	0	21.49	21.80	21.68	0-2	2
	8	4	22.10	21.56	21.57		2
	8	7	21.75	21.60	21.77		2
	15	0	22.00	21.19	21.50		2
64QAM	1	0	21.82	21.70	21.62	0-2	2
	1	7	21.97	21.71	21.82		2
	1	14	21.76	21.64	21.69		2
	8	0	20.41	20.91	20.55	0-3	3
	8	4	20.82	20.19	20.58		3
	8	7	20.99	20.48	20.93		3
	15	0	20.98	20.50	20.61		3
256QAM	1	0	18.57	18.65	18.50	0-5	5
	1	7	18.75	18.57	18.80		5
	1	14	18.54	18.65	18.53		5
	8	0	18.56	18.52	18.46		5
	8	4	18.74	18.63	18.66		5
	8	7	18.64	18.58	18.69		5
	15	0	18.54	18.49	18.54		5

Table H-46
LTE Band 66 (AWS) Ant A Measured P_{Max} for DSI = 1 (Head) – 1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.39	23.43	23.41	0	0
	1	2	23.36	23.48	23.36		0
	1	5	23.65	23.51	23.40		0
	3	0	23.41	23.38	23.53		0
	3	2	23.57	23.31	23.26		0
	3	3	23.69	23.33	23.18		0
	6	0	22.48	22.51	22.68	0-1	1
16QAM	1	0	22.77	22.63	22.66	0-1	1
	1	2	22.65	22.63	22.64		1
	1	5	22.75	22.71	22.75		1
	3	0	22.66	22.68	22.82		1
	3	2	22.72	22.47	22.62		1
	3	3	22.63	22.56	22.47		1
	6	0	21.59	21.51	21.88	0-2	2
64QAM	1	0	21.90	21.87	21.92	0-2	2
	1	2	21.65	21.66	21.64		2
	1	5	21.64	21.75	21.95		2
	3	0	21.69	21.60	21.85		2
	3	2	21.76	21.59	21.91		2
	3	3	21.79	21.35	21.71		2
	6	0	20.42	20.34	20.49	0-3	3
256QAM	1	0	18.82	18.60	18.81	0-5	5
	1	2	18.79	18.78	18.80		5
	1	5	18.61	18.50	18.75		5
	3	0	18.71	18.58	18.77		5
	3	2	18.63	18.51	18.60		5
	3	3	18.64	18.44	18.61		5
	6	0	18.48	18.53	18.55	5	

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 29 of 222

Table H-47
LTE Band 66 (AWS) Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.28	21.11	20.87	0	0
	1	36	21.42	21.05	20.91		0
	1	74	21.09	20.96	20.74		0
	36	0	21.02	21.03	20.83	0-1	0
	36	18	20.94	21.04	20.90		0
	36	37	21.03	21.01	20.94		0
	75	0	21.03	21.00	20.84		0
16QAM	1	0	21.43	21.14	20.88	0-1	0
	1	36	21.18	21.37	21.02		0
	1	74	21.06	21.13	21.07		0
	36	0	21.06	21.08	20.97	0-2	0
	36	18	21.07	21.03	20.90		0
	36	37	21.15	20.94	20.95		0
	75	0	21.05	21.08	20.91		0
64QAM	1	0	21.27	21.34	21.07	0-2	0
	1	36	21.08	21.45	21.00		0
	1	74	20.99	21.46	20.92		0
	36	0	20.86	20.87	20.65	0-3	0
	36	18	20.65	20.65	20.63		0
	36	37	20.78	20.80	20.68		0
	75	0	20.53	21.20	20.63		0
256QAM	1	0	19.01	18.88	18.84	0-5	2
	1	36	18.71	18.81	18.75		2
	1	74	18.87	18.70	18.68		2
	36	0	18.77	18.82	18.59		2
	36	18	18.71	18.77	18.67		2
	36	37	18.83	18.81	18.55		2
	75	0	18.79	18.77	18.73		2

Table H-48
LTE Band 66 (AWS) Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.03	21.05	20.76	0	0
	1	25	21.16	21.09	20.79		0
	1	49	21.09	21.01	20.73		0
	25	0	21.10	21.19	20.86	0-1	0
	25	12	21.04	21.05	20.95		0
	25	25	21.09	21.06	20.83		0
	50	0	21.07	21.04	20.90		0
16QAM	1	0	21.13	21.15	20.88	0-1	0
	1	25	21.14	21.47	20.96		0
	1	49	21.03	21.05	21.07		0
	25	0	21.12	21.18	20.85	0-2	0
	25	12	21.04	21.10	21.40		0
	25	25	21.06	21.13	20.74		0
	50	0	21.11	21.03	21.45		0
64QAM	1	0	20.85	21.28	20.94	0-2	0
	1	25	21.42	21.19	20.86		0
	1	49	21.06	21.08	20.96		0
	25	0	20.88	20.82	20.67	0-3	0
	25	12	20.79	20.88	20.66		0
	25	25	20.87	20.86	20.59		0
	50	0	20.82	21.04	20.64		0
256QAM	1	0	18.78	18.81	18.53	0-5	2
	1	25	18.90	18.84	18.66		2
	1	49	18.73	18.79	18.56		2
	25	0	18.80	18.92	18.67		2
	25	12	18.81	18.84	18.68		2
	25	25	18.84	18.83	18.59		2
	50	0	18.92	18.77	18.67		2

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 30 of 222

Table H-49
LTE Band 66 (AWS) Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.92	21.05	20.82	0	0
	1	12	21.16	21.18	21.03		0
	1	24	21.06	21.08	20.70		0
	12	0	21.08	21.10	20.92	0-1	0
	12	6	21.11	21.13	20.87		0
	12	13	21.14	21.20	20.82		0
	25	0	21.09	21.14	20.83		0
16QAM	1	0	21.28	21.15	20.97	0-1	0
	1	12	21.33	21.24	21.16		0
	1	24	21.38	21.12	21.28		0
	12	0	21.12	21.19	20.99	0-2	0
	12	6	21.12	21.18	20.94		0
	12	13	21.22	21.14	20.86		0
	25	0	21.13	21.18	20.93		0
64QAM	1	0	21.33	21.37	21.07	0-2	0
	1	12	21.16	21.19	21.14		0
	1	24	21.13	21.28	21.08		0
	12	0	21.00	20.91	20.65	0-3	0
	12	6	21.12	21.21	20.73		0
	12	13	21.04	21.10	20.57		0
	25	0	20.87	20.90	20.61		0
256QAM	1	0	18.86	18.82	18.71	0-5	2
	1	12	19.07	19.04	18.80		2
	1	24	18.83	18.95	19.17		2
	12	0	18.80	18.83	18.56		2
	12	6	18.90	18.92	18.62		2
	12	13	18.95	18.81	18.65		2
	25	0	18.78	18.89	18.60		2

Table H-50
LTE Band 66 (AWS) Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.03	20.99	20.68	0	0
	1	7	21.18	21.05	20.77		0
	1	14	20.98	21.04	20.71		0
	8	0	21.16	21.07	20.81	0-1	0
	8	4	21.15	21.17	20.84		0
	8	7	21.11	21.08	20.85		0
	15	0	21.07	21.07	20.82		0
16QAM	1	0	21.27	21.15	20.88	0-1	0
	1	7	21.45	21.39	21.08		0
	1	14	21.25	21.40	21.07		0
	8	0	21.40	21.19	20.87	0-2	0
	8	4	21.25	21.16	20.90		0
	8	7	21.22	21.17	20.89		0
	15	0	21.15	21.16	20.81		0
64QAM	1	0	21.48	21.20	21.00	0-2	0
	1	7	21.36	21.38	20.91		0
	1	14	21.22	21.23	20.88		0
	8	0	20.95	20.65	20.55	0-3	0
	8	4	20.90	20.88	20.73		0
	8	7	21.04	20.88	20.66		0
	15	0	20.90	20.88	20.60		0
256QAM	1	0	18.92	18.57	18.64	0-5	2
	1	7	19.07	19.03	18.68		2
	1	14	18.78	18.92	18.76		2
	8	0	18.88	18.89	18.61		2
	8	4	18.91	18.93	18.63		2
	8	7	18.91	18.90	18.42		2
	15	0	18.87	18.89	18.55		2

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 31 of 222

Table H-51
LTE Band 66 (AWS) Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.24	20.95	20.73	0	0
	1	2	21.07	21.08	20.83		0
	1	5	20.98	21.06	20.76		0
	3	0	21.01	20.91	20.86		0
	3	2	20.94	21.07	20.71		0
	3	3	21.00	21.02	20.63		0
	6	0	21.04	21.08	20.74		0
16QAM	1	0	21.35	21.34	21.05	0-1	0
	1	2	21.04	21.36	21.03		0
	1	5	21.24	21.16	21.15		0
	3	0	21.09	21.06	20.82		0
	3	2	21.17	21.04	21.03		0
	3	3	21.08	21.05	20.88		0
	6	0	21.21	21.19	20.84		0
64QAM	1	0	21.50	21.18	20.95	0-2	0
	1	2	20.96	21.36	20.95		0
	1	5	21.06	21.15	21.05		0
	3	0	21.44	21.21	20.89		0
	3	2	21.07	21.12	20.74		0
	3	3	20.96	21.23	20.83		0
	6	0	20.76	20.81	20.36		0
256QAM	1	0	19.23	19.29	19.10	0-5	2
	1	2	18.75	18.91	18.64		2
	1	5	18.93	18.65	18.71		2
	3	0	18.88	18.51	18.49		2
	3	2	18.82	18.88	18.87		2
	3	3	18.91	18.78	18.43		2
	6	0	18.72	18.69	18.41		2

Table H-52
LTE Band 66 (AWS) Ant F Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.37	18.81	18.87	0	0
	1	36	18.53	18.63	18.44		0
	1	74	18.59	18.48	18.42		0
	36	0	18.70	18.49	18.51	0-1	0
	36	18	18.66	18.52	18.51		0
	36	37	18.66	18.54	18.51		0
	75	0	18.71	18.64	18.49		0
16QAM	1	0	18.86	18.73	18.65	0-1	0
	1	36	18.55	18.88	19.04		0
	1	74	18.83	18.65	18.62		0
	36	0	18.61	18.62	18.37	0-2	0
	36	18	18.73	18.44	18.56		0
	36	37	18.54	18.53	18.43		0
	75	0	18.71	18.61	18.55		0
64QAM	1	0	18.51	18.66	18.57	0-2	0
	1	36	18.70	18.85	18.64		0
	1	74	18.93	18.64	18.75		0
	36	0	18.61	18.57	18.47	0-3	0
	36	18	18.71	18.66	18.50		0
	36	37	18.64	18.60	18.53		0
	75	0	18.64	18.70	18.58		0
256QAM	1	0	18.65	18.56	18.68	0-5	0
	1	36	18.81	18.84	18.54		0
	1	74	18.55	18.62	18.48		0
	36	0	18.70	18.34	18.55		0
	36	18	18.76	18.71	18.56		0
	36	37	18.62	18.64	19.03		0
	75	0	18.77	18.58	18.60		0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 32 of 222

Table H-53
LTE Band 66 (AWS) Ant F Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.43	18.52	18.44	0	0
	1	25	18.64	18.69	18.37		0
	1	49	18.45	18.54	18.34		0
	25	0	18.61	18.66	18.47	0-1	0
	25	12	18.71	18.66	18.43		0
	25	25	18.76	18.70	18.41		0
16QAM	50	0	18.60	18.69	18.57	0	
	1	0	18.82	18.75	18.76	0-1	0
	1	25	18.69	18.86	18.63		0
	1	49	18.81	19.05	18.62		0
	25	0	18.43	18.77	18.45	0-2	0
	25	12	18.72	18.65	18.53		0
64QAM	25	25	18.64	18.64	18.46		0-2
	50	0	18.67	18.57	18.47	0	
	1	0	18.71	18.75	18.45	0-2	
	1	25	18.78	18.70	18.50		0
	1	49	18.75	18.84	18.63		0-3
	25	0	18.66	18.64	18.57	0	
256QAM	25	12	18.73	18.67	18.41	0-3	
	25	25	18.59	18.73	18.58		0
	50	0	18.78	18.65	18.57		0-5
	1	0	18.55	18.80	18.55	0	
	1	25	18.78	18.78	18.42	0	
	1	49	18.74	18.83	18.50	0	
25	0	18.59	18.67	18.49	0		
256QAM	25	12	18.76	18.66	18.61	0	
	25	25	18.71	18.70	18.58	0	
	50	0	18.69	18.57	18.81	0	

Table H-54
LTE Band 66 (AWS) Ant F Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.51	18.63	18.45	0	0
	1	12	18.64	18.53	18.36		0
	1	24	18.56	18.50	18.50		0
	12	0	18.55	18.66	18.56	0-1	0
	12	6	18.75	18.76	18.53		0
	12	13	18.63	18.71	18.42		0
16QAM	25	0	18.61	18.61	18.58	0-1	0
	1	0	18.73	18.94	18.52		0
	1	12	18.82	18.89	18.61		0
	1	24	18.65	18.71	18.71	0-2	0
	12	0	18.73	18.56	18.49		0
	12	6	18.70	18.70	18.59		0
64QAM	12	13	18.74	18.68	18.56	0-2	0
	25	0	18.57	18.64	18.53		0
	1	0	18.94	18.87	18.40		0-2
	1	12	18.82	18.80	18.76	0	
	1	24	18.71	18.84	18.62	0-3	
	12	0	18.75	18.94	18.56		0
256QAM	12	6	18.78	18.67	18.52		0-3
	12	13	18.66	18.65	18.53	0	
	25	0	18.66	18.66	18.44	0	
	1	0	18.63	18.78	18.25	0-5	0
	1	12	18.78	18.94	18.70		0
	1	24	18.82	18.91	18.67		0
12	0	18.64	18.73	18.56	0		
12	6	18.80	18.63	18.60	0		
12	13	18.69	18.71	18.57	0		
	25	0	18.69	18.72	18.54	0	

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 33 of 222

Table H-55
LTE Band 66 (AWS) Ant F Measured P_{Limit} for DSI = 1 (Head) - 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.44	18.42	18.33	0	0
	1	7	18.73	18.58	18.45		0
	1	14	18.23	18.55	18.35		0
	8	0	18.55	18.61	18.48	0-1	0
	8	4	18.60	18.65	18.52		0
	8	7	18.65	18.64	18.44		0
	15	0	18.65	18.60	18.53		0
16QAM	1	0	18.74	18.71	18.44	0-1	0
	1	7	18.79	18.86	18.78		0
	1	14	18.80	18.81	18.45		0
	8	0	18.74	18.69	18.43	0-2	0
	8	4	18.72	18.72	18.61		0
	8	7	18.67	18.68	18.49		0
	15	0	18.65	18.70	18.48		0
64QAM	1	0	18.82	18.81	18.45	0-2	0
	1	7	18.93	19.00	18.72		0
	1	14	18.69	18.74	18.63		0
	8	0	18.73	18.72	18.55	0-3	0
	8	4	18.78	18.73	18.59		0
	8	7	18.75	18.75	18.59		0
	15	0	18.65	18.64	18.53		0
256QAM	1	0	18.73	18.61	18.58	0-5	0
	1	7	18.82	18.78	18.60		0
	1	14	18.66	18.66	18.47		0
	8	0	18.62	18.73	18.56		0
	8	4	18.79	18.81	18.60		0
	8	7	18.81	18.59	18.54		0
	15	0	18.73	18.70	18.42		0

Table H-56
LTE Band 66 (AWS) Ant F Measured P_{Limit} for DSI = 1 (Head) – 1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	18.48	18.59	18.52	0	0	
	1	2	18.62	18.51	18.48		0	
	1	5	18.61	18.64	18.40		0	
	3	0	18.48	18.51	18.34		0	
	3	2	18.45	18.42	18.40		0	
	3	3	18.48	18.46	18.32		0	
16QAM	6	0	18.62	18.52	18.41	0-1	0	
	1	0	18.75	18.69	18.58	0-1	0	
	1	2	18.67	18.62	18.83		0	
	1	5	18.79	18.50	18.40		0	
	3	0	18.65	18.66	18.42		0	
	3	2	18.80	18.58	18.50		0	
64QAM	3	3	18.72	18.65	18.63		0-2	0
	6	0	18.73	18.73	18.49	0		
	1	0	18.81	19.00	18.58	0-2		0
	1	2	18.69	18.73	18.73			0
	1	5	18.83	18.89	18.56			0
	3	0	18.77	18.97	18.46			0
256QAM	3	2	18.69	18.73	18.43		0-3	0
	3	3	18.87	18.58	18.64			0
	6	0	18.64	18.51	18.55	0		
	1	0	18.77	18.65	18.47	0-5		0
	1	2	18.74	19.01	18.56			0
	1	5	18.78	18.96	18.59			0
3	0	18.73	18.57	18.55	0			
3	2	18.53	18.61	18.54	0			
3	3	18.60	18.54	18.66	0			
6	0	18.62	18.64	18.57		0		

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 34 of 222

H.1.7 LTE Band 25

Table H-57
LTE Band 25 (PCS) Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.86	17.89	17.68	0	0
	1	36	17.80	17.78	17.62		0
	1	74	17.91	17.80	17.68		0
	36	0	17.89	17.89	17.68	0-1	0
	36	18	17.80	18.16	17.79		0
	36	37	17.77	17.90	17.82		0
16QAM	75	0	18.20	17.85	17.76	0-1	0
	1	0	18.02	18.02	17.91		0
	1	36	18.25	18.04	17.90		0
	1	74	17.83	18.15	18.00	0-2	0
	36	0	17.72	17.68	17.69		0
	36	18	17.49	17.88	17.89		0
64QAM	36	37	18.03	17.59	17.77	0-2	0
	75	0	17.79	17.92	17.87		0
	1	0	18.04	18.00	17.77		0
	1	36	18.07	18.02	17.85	0-2	0
	1	74	18.06	18.05	17.96		0
	36	0	17.66	17.92	17.51		0
256QAM	36	18	17.70	17.94	17.87	0-3	0
	36	37	17.52	17.91	17.84		0
	75	0	17.75	17.89	17.76		0
	1	0	18.05	18.10	17.80	0-5	0
	1	36	18.16	18.02	17.85		0
	1	74	18.20	17.94	17.87		0
36	0	17.94	17.80	17.78	0		
36	18	17.93	17.98	17.82	0		
36	37	18.02	17.99	17.76	0		
	75	0	17.91	17.81	17.80		0

Table H-58
LTE Band 25 (PCS) Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.97	17.93	17.63	0	0
	1	25	17.84	17.88	17.77		0
	1	49	17.77	17.93	17.61		0
	25	0	17.92	18.04	17.66	0-1	0
	25	12	17.88	17.75	17.76		0
	25	25	17.97	18.07	17.74		0
	50	0	17.83	17.77	17.69		0
16QAM	1	0	18.06	18.00	17.99	0-1	0
	1	25	18.26	17.99	17.90		0
	1	49	18.03	17.96	17.87		0
	25	0	17.78	17.94	17.76	0-2	0
	25	12	17.95	17.93	17.88		0
	25	25	18.03	17.92	17.84		0
	50	0	17.84	17.88	17.71		0
64QAM	1	0	17.92	18.00	17.89	0-2	0
	1	25	18.23	17.91	17.82		0
	1	49	18.00	18.10	17.94		0
	25	0	17.70	17.82	17.74	0-3	0
	25	12	17.86	17.95	17.66		0
	25	25	17.95	18.03	17.88		0
	50	0	17.64	17.38	17.50		0
256QAM	1	0	17.76	18.05	17.84	0-5	0
	1	25	18.12	18.15	17.89		0
	1	49	18.02	18.18	17.70		0
	25	0	17.87	17.83	17.73		0
	25	12	18.00	17.87	17.82		0
	25	25	17.98	17.88	17.87		0
	50	0	17.96	17.86	17.77		0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 35 of 222

Table H-59
LTE Band 25 (PCS) Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.74	17.97	17.76	0	0
	1	12	17.89	17.81	17.68		0
	1	24	17.96	17.88	17.71		0
	12	0	17.81	17.76	17.62	0-1	0
	12	6	17.84	17.89	17.96		0
	12	13	17.95	17.65	17.77		0
16QAM	25	0	17.57	17.69	17.32	0-1	0
	1	0	18.01	18.02	18.06		0
	1	12	17.99	18.04	17.90		0
	1	24	17.98	18.16	17.98	0-2	0
	12	0	17.95	17.88	17.74		0
	12	6	17.98	17.96	17.81		0
64QAM	12	13	18.30	18.00	17.90	0-2	0
	25	0	18.00	17.83	18.03		0
	1	0	18.19	17.96	17.80		0
	1	12	17.96	18.11	17.89	0-3	0
	1	24	17.94	18.16	17.97		0
	12	0	17.89	18.09	17.67		0
256QAM	12	6	18.02	18.06	17.79	0-5	0
	12	13	18.00	17.98	17.75		0
	25	0	17.97	17.20	17.70		0
	1	0	17.94	17.91	17.79	0-5	0
	1	12	18.25	17.91	17.84		0
	1	24	18.05	18.08	17.86		0
12	0	17.97	17.92	17.63	0		
12	6	17.89	18.07	17.91	0		
12	13	17.92	18.02	17.78	0		
	25	0	17.95	17.87	17.74		0

Table H-60
LTE Band 25 (PCS) Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.64	17.69	17.64	0	0
	1	7	17.80	17.97	17.79		0
	1	14	17.85	17.73	17.66		0
	8	0	17.82	17.94	17.68	0-1	0
	8	4	17.91	17.72	17.73		0
	8	7	17.92	17.73	17.73		0
	15	0	17.76	17.24	17.68		0
16QAM	1	0	18.03	18.03	18.00	0-1	0
	1	7	18.19	17.95	17.90		0
	1	14	18.08	18.09	17.92		0
	8	0	17.84	17.90	17.79	0-2	0
	8	4	18.09	18.05	17.80		0
	8	7	17.97	18.00	17.76		0
	15	0	17.82	18.01	17.51		0
64QAM	1	0	18.02	17.86	18.00	0-2	0
	1	7	18.13	18.21	17.93		0
	1	14	18.12	18.10	17.78		0
	8	0	17.78	18.04	17.80	0-3	0
	8	4	18.03	18.06	17.88		0
	8	7	18.06	17.96	17.85		0
	15	0	18.20	17.74	17.74		0
256QAM	1	0	17.71	17.87	17.72	0-5	0
	1	7	18.09	18.06	17.82		0
	1	14	17.90	17.88	17.72		0
	8	0	17.78	17.83	17.73		0
	8	4	18.05	18.02	17.85		0
	8	7	17.96	18.03	17.86		0
	15	0	17.91	17.78	17.83		0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 36 of 222

Table H-61
LTE Band 25 (PCS) Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	17.97	17.82	17.54	0	0	
	1	2	17.77	17.97	17.66		0	
	1	5	17.91	17.72	17.73		0	
	3	0	17.81	17.92	17.54		0	
	3	2	17.74	17.83	17.49		0	
	3	3	17.80	17.93	17.32		0	
16QAM	6	0	17.54	17.62	17.58	0-1	0	
	1	0	18.05	18.02	17.88		0	
	1	2	18.04	18.04	17.89	0-1	0	
	1	5	18.00	17.91	17.86		0	
	3	0	18.05	18.08	17.86		0	
	3	2	17.99	17.89	17.79		0	
64QAM	3	3	18.01	17.97	17.61	0-2	0	
	6	0	17.99	17.94	17.58		0	
	1	0	18.20	18.14	17.88		0-2	0
	1	2	18.08	18.10	17.94			0
	1	5	18.08	18.13	17.75			0
	3	0	17.97	17.94	17.89			0
3	2	18.12	17.92	17.72	0			
256QAM	3	3	18.10	18.02	17.89	0-3	0	
	6	0	17.83	17.98	17.50		0	
	1	0	17.82	18.08	17.59		0-5	0
	1	2	18.00	17.91	17.65			0
	1	5	18.07	17.97	17.79			0
	3	0	18.07	18.03	17.80			0
3	2	17.97	17.90	17.91	0			
256QAM	3	3	17.93	18.05	17.73	0-5		0
	6	0	17.91	17.94	17.69		0	

Table H-62
LTE Band 25 (PCS) Ant A Measured P_{Max} for DSI = 1 (Head) - 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.64	23.52	23.66	0	0
	1	36	23.59	23.40	23.39		0
	1	74	23.62	23.34	23.42		0
	36	0	22.52	22.23	22.55	0-1	1
	36	18	22.77	22.57	22.43		1
	36	37	22.48	22.60	22.43		1
16QAM	75	0	22.61	22.62	22.32	0-1	1
	1	0	22.74	22.44	22.65		1
	1	36	22.64	22.74	22.79		1
	1	74	22.68	22.78	22.76	0-2	1
	36	0	21.43	21.50	21.48		2
	36	18	21.67	21.56	21.15		2
64QAM	36	37	21.68	21.60	21.43	0-2	2
	75	0	21.63	21.29	21.44		2
	1	0	21.66	21.59	21.52		2
	1	36	21.88	21.66	21.73	0-3	2
	1	74	21.68	21.83	21.19		2
	36	0	20.51	20.56	20.46		3
256QAM	36	18	20.45	20.54	20.41	0-5	3
	36	37	20.69	20.61	20.60		3
	75	0	20.71	20.84	20.50		3
	1	0	18.66	18.54	18.31	0-5	5
	1	36	18.74	18.73	18.66		5
	1	74	18.72	18.64	18.38		5
36	0	18.61	18.47	18.48	5		
36	18	18.76	18.51	18.45	5		
36	37	18.62	18.62	18.48	5		
	75	0	18.71	18.61	18.36		5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 37 of 222

Table H-63
LTE Band 25 (PCS) Ant A Measured P_{Max} for DSI = 1 (Head) - 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.80	23.41	23.56	0	0
	1	25	23.68	23.50	23.42		0
	1	49	23.53	23.59	22.75		0
	25	0	22.64	22.51	22.39	0-1	1
	25	12	22.97	22.87	22.63		1
	25	25	22.54	22.63	22.44		1
	50	0	22.68	22.44	22.33		1
16QAM	1	0	22.82	22.57	22.72	0-1	1
	1	25	22.83	22.76	22.55		1
	1	49	22.60	22.91	22.19		1
	25	0	21.76	21.51	20.94	0-2	2
	25	12	21.55	21.61	21.48		2
	25	25	21.66	21.68	21.49		2
	50	0	21.69	21.02	21.49		2
64QAM	1	0	21.85	21.71	21.52	0-2	2
	1	25	21.68	21.80	21.73		2
	1	49	21.78	21.66	21.18		2
	25	0	20.74	20.50	20.41	0-3	3
	25	12	20.81	20.54	20.58		3
	25	25	20.71	20.73	20.53		3
	50	0	20.51	20.76	20.42		3
256QAM	1	0	18.88	18.62	18.50	0-5	5
	1	25	18.84	18.85	18.68		5
	1	49	18.63	18.71	18.24		5
	25	0	18.80	18.51	18.44		5
	25	12	18.74	18.59	18.42		5
	25	25	18.69	18.67	18.54		5
	50	0	18.77	18.53	18.51		5

Table H-64
LTE Band 25 (PCS) Ant A Measured P_{Max} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.74	23.51	23.43	0	0
	1	12	23.95	23.73	23.10		0
	1	24	23.80	23.61	22.81		0
	12	0	22.46	22.59	22.34	0-1	1
	12	6	22.50	22.64	22.42		1
	12	13	22.74	22.66	22.27		1
16QAM	25	0	22.70	22.39	22.39		1
	1	0	22.77	22.72	22.47	0-1	1
	1	12	22.86	22.93	22.35		1
	1	24	22.96	22.87	22.10		
	12	0	21.90	21.79	21.45	0-2	2
	12	6	22.05	21.68	21.48		2
12	13	21.83	21.77	20.81	2		
64QAM	25	0	21.82	21.31	21.44		2
	1	0	21.81	21.74	21.60	0-2	2
	1	12	22.02	21.84	21.46		2
	1	24	21.94	21.90	21.00		2
	12	0	20.72	20.59	20.28	0-3	3
	12	6	20.85	20.76	20.57		3
12	13	20.80	20.90	20.53	3		
256QAM	25	0	20.64	20.62	20.44		3
	1	0	18.81	18.65	18.51	0-5	5
	1	12	18.82	18.68	18.71		5
	1	24	18.86	18.78	18.10		5
	12	0	18.77	18.49	18.48		5
	12	6	18.77	18.72	18.49		5
12	13	18.80	18.64	18.52	5		
	25	0	18.72	18.58	18.50		5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 38 of 222

Table H-65
LTE Band 25 (PCS) Ant A Measured P_{Max} for DSI = 1 (Head) - 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.48	23.33	23.24	0	0
	1	7	23.80	23.61	22.97		0
	1	14	23.68	23.62	22.90		0
	8	0	22.60	22.44	22.23	0-1	1
	8	4	22.73	22.71	22.33		1
	8	7	22.60	22.29	22.45		1
16QAM	15	0	22.80	22.54	22.32	0-1	1
	1	0	22.78	22.52	22.44		1
	1	7	22.95	22.93	22.31		1
	1	14	22.78	22.58	22.10	0-2	1
	8	0	21.88	21.54	21.45		2
	8	4	21.83	21.73	21.57		2
64QAM	8	7	21.95	21.80	21.55	0-2	2
	15	0	21.70	21.54	21.48		2
	1	0	21.85	21.69	21.46		2
	1	7	21.93	21.70	21.18	0-3	2
	1	14	21.74	21.86	20.94		2
	8	0	20.52	20.31	20.37		3
256QAM	8	4	20.89	20.68	20.69	0-5	3
	8	7	20.82	20.67	20.51		3
	15	0	20.80	20.55	20.40		3
	1	0	18.63	18.58	18.41	0-5	5
	1	7	18.82	18.84	18.48		5
	1	14	18.84	18.73	17.95		5
256QAM	8	0	18.81	18.61	18.37	0-5	5
	8	4	18.82	18.77	18.54		5
	8	7	18.76	18.66	18.50		5
	15	0	18.74	18.58	18.41		5

Table H-66
LTE Band 25 (PCS) Ant A Measured P_{Max} for DSI = 1 (Head) – 1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.61	23.65	23.04	0	0
	1	2	23.62	23.60	22.98		0
	1	5	23.63	23.49	22.99		0
	3	0	23.54	23.76	23.25		0
	3	2	23.74	23.63	23.54		0
	3	3	23.54	23.61	23.54		0
	6	0	22.71	22.34	22.30		0-1
16QAM	1	0	22.91	22.75	22.18	0-1	1
	1	2	22.81	22.86	22.22		1
	1	5	22.88	22.59	22.19		1
	3	0	22.75	22.81	22.52		1
	3	2	22.53	22.59	22.38		1
	3	3	22.89	22.78	22.09		1
	6	0	21.80	21.73	21.02		0-2
64QAM	1	0	21.76	21.69	21.16	0-2	2
	1	2	21.54	21.70	21.22		2
	1	5	21.94	21.59	20.89		2
	3	0	21.78	21.26	21.34		2
	3	2	21.72	21.76	21.23		2
	3	3	21.76	21.80	21.36		2
	6	0	20.73	20.43	20.34		0-3
256QAM	1	0	18.80	18.55	18.14	0-5	5
	1	2	18.84	18.67	18.14		5
	1	5	18.82	18.76	18.14		5
	3	0	18.74	18.77	18.42		5
	3	2	18.87	18.72	18.36		5
	3	3	18.78	18.71	18.39		5
	6	0	18.71	18.67	18.47		5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 39 of 222

Table H-67
LTE Band 25 (PCS) Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.69	19.73	19.69	0	0
	1	36	19.69	19.74	19.70		0
	1	74	19.76	19.86	19.95		0
	36	0	19.73	19.76	19.80	0-1	0
	36	18	19.69	19.73	19.75		0
	36	37	19.83	19.83	19.79		0
	75	0	19.75	19.71	19.86		0
16QAM	1	0	19.85	20.14	19.86	0-1	0
	1	36	20.11	19.88	19.90		0
	1	74	19.95	19.83	19.88		0
	36	0	19.77	19.66	19.79	0-2	0
	36	18	19.81	19.80	19.81		0
	36	37	19.92	19.84	19.85		0
	75	0	19.82	19.71	19.82		0
64QAM	1	0	19.92	20.13	19.90	0-2	0
	1	36	20.00	19.96	19.93		0
	1	74	20.04	20.04	20.06		0
	36	0	19.85	19.82	19.75	0-3	0
	36	18	19.76	19.77	19.88		0
	36	37	19.93	19.84	19.84		0
	75	0	19.79	19.74	19.78		0
256QAM	1	0	18.56	18.60	18.59	0-5	1.5
	1	36	18.70	18.62	18.61		1.5
	1	74	18.67	18.68	18.58		1.5
	36	0	18.45	18.49	18.50		1.5
	36	18	18.53	18.49	18.55		1.5
	36	37	18.55	18.49	18.53		1.5
	75	0	18.47	18.42	18.57		1.5

Table H-68
LTE Band 25 (PCS) Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.61	19.69	19.74	0	0
	1	25	19.68	19.84	19.76		0
	1	49	19.74	19.76	19.80		0
	25	0	19.69	19.82	19.76	0-1	0
	25	12	19.87	19.87	19.76		0
	25	25	19.88	19.80	19.75		0
	50	0	19.75	19.78	19.70		0
16QAM	1	0	19.82	19.95	19.91	0-1	0
	1	25	20.17	20.00	19.90		0
	1	49	19.91	20.02	20.04		0
	25	0	19.98	19.84	19.76	0-2	0
	25	12	19.81	19.83	19.75		0
	25	25	19.85	19.90	19.75		0
	50	0	19.71	19.77	19.72		0
64QAM	1	0	20.07	20.15	19.98	0-2	0
	1	25	19.97	20.10	20.04		0
	1	49	20.03	20.02	20.01		0
	25	0	19.77	19.68	19.79	0-3	0
	25	12	19.87	19.87	19.84		0
	25	25	19.79	19.94	19.83		0
	50	0	19.81	19.89	19.66		0
256QAM	1	0	18.56	18.54	18.55	0-5	1.5
	1	25	18.65	18.62	18.61		1.5
	1	49	18.66	18.67	18.55		1.5
	25	0	18.50	18.51	18.43		1.5
	25	12	18.51	18.46	18.47		1.5
	25	25	18.58	18.58	18.57		1.5
	50	0	18.51	18.55	18.50		1.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 40 of 222

Table H-69
LTE Band 25 (PCS) Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.69	19.68	19.69	0	0
	1	12	19.82	19.75	19.81		0
	1	24	19.90	19.92	19.69		0
	12	0	19.75	19.74	19.75	0-1	0
	12	6	19.84	19.95	19.89		0
	12	13	19.95	19.93	19.83		0
	25	0	19.70	19.83	19.71		0
16QAM	1	0	19.84	19.95	19.86	0-1	0
	1	12	20.17	20.07	20.07		0
	1	24	20.08	19.96	19.94		0
	12	0	19.74	19.85	19.70	0-2	0
	12	6	19.90	19.92	19.87		0
	12	13	19.89	19.90	19.92		0
	25	0	19.79	19.84	19.74		0
64QAM	1	0	19.90	20.13	19.93	0-2	0
	1	12	20.16	20.13	20.02		0
	1	24	20.07	20.08	19.93		0
	12	0	19.80	19.85	19.77	0-3	0
	12	6	19.89	20.04	19.89		0
	12	13	20.01	19.92	19.86		0
	25	0	19.86	19.82	19.73		0
256QAM	1	0	18.60	18.55	18.57	0-5	1.5
	1	12	18.61	18.76	18.62		1.5
	1	24	18.67	18.67	18.66		1.5
	12	0	18.44	18.45	18.40		1.5
	12	6	18.58	18.62	18.57		1.5
	12	13	18.60	18.62	18.44		1.5
	25	0	18.49	18.48	18.45		1.5

Table H-70
LTE Band 25 (PCS) Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.70	19.66	19.67	0	0
	1	7	19.84	19.78	19.66		0
	1	14	19.85	19.71	19.68		0
	8	0	19.74	19.75	19.67	0-1	0
	8	4	19.96	19.94	19.70		0
	8	7	19.88	19.82	19.73		0
	15	0	19.73	19.73	19.66		0
16QAM	1	0	19.86	19.96	19.86	0-1	0
	1	7	20.17	20.00	19.97		0
	1	14	19.99	19.83	19.89		0
	8	0	19.75	19.81	19.70	0-2	0
	8	4	19.96	19.89	19.82		0
	8	7	19.97	19.89	19.82		0
	15	0	19.69	19.83	19.76		0
64QAM	1	0	19.98	20.13	20.00	0-2	0
	1	7	20.16	20.29	19.99		0
	1	14	20.02	19.92	19.80		0
	8	0	19.84	19.86	19.65	0-3	0
	8	4	19.92	20.02	19.80		0
	8	7	19.95	19.87	19.76		0
	15	0	19.83	19.79	19.74		0
256QAM	1	0	18.49	18.59	18.58	0-5	1.5
	1	7	18.67	18.71	18.73		1.5
	1	14	18.62	18.50	18.57		1.5
	8	0	18.40	18.48	18.43		1.5
	8	4	18.66	18.54	18.51		1.5
	8	7	18.59	18.53	18.49		1.5
	15	0	18.51	18.48	18.38		1.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 41 of 222

Table H-71
LTE Band 25 (PCS) Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.63	19.79	19.69	0	0
	1	2	20.13	19.68	19.64		0
	1	5	19.76	19.75	19.66		0
	3	0	19.71	19.63	19.64		0
	3	2	19.69	19.62	19.69		0
	3	3	19.64	19.75	19.62		0
	6	0	19.82	19.74	19.66		0
16QAM	1	0	19.94	19.94	19.86	0-1	0
	1	2	20.12	20.15	19.88		0
	1	5	19.87	19.86	19.85		0
	3	0	20.03	19.86	19.75		0
	3	2	19.75	19.80	19.67		0
	3	3	19.80	19.76	19.68		0
	6	0	19.92	19.92	19.81		0
64QAM	1	0	20.14	20.13	20.20	0-2	0
	1	2	20.19	19.95	19.93		0
	1	5	20.03	20.25	19.91		0
	3	0	19.90	19.93	19.90		0
	3	2	19.82	19.80	19.82		0
	3	3	19.99	20.03	19.81		0
	6	0	19.87	19.94	19.71		0
256QAM	1	0	18.75	18.77	18.52	0-3	1.5
	1	2	18.77	18.78	18.72		1.5
	1	5	18.69	18.84	18.55		1.5
	3	0	18.59	18.55	18.47		1.5
	3	2	18.55	18.55	18.50		1.5
	3	3	18.60	18.51	18.48		1.5
	6	0	18.55	18.51	18.48		1.5

Table H-72
LTE Band 25 (PCS) Ant F Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.42	18.89	18.38	0	0
	1	36	18.53	18.67	18.34		0
	1	74	18.50	18.46	18.26		0
	36	0	18.64	18.50	18.44	0-1	0
	36	18	18.70	18.53	18.50		0
	36	37	18.52	18.58	18.49		0
16QAM	75	0	18.59	18.46	18.46	0-1	0
	1	0	18.86	18.58	18.53		0
	1	36	18.67	18.70	18.61		0
	1	74	18.63	19.01	18.59	0-2	0
	36	0	18.64	18.58	18.45		0
	36	18	18.75	18.61	18.60		0
64QAM	36	37	18.62	18.67	18.56	0-2	0
	75	0	18.67	18.47	18.58		0
	1	0	18.81	18.55	18.64		0
	1	36	18.79	18.72	18.68	0-3	0
	1	74	18.72	18.85	18.56		0
	36	0	18.66	18.54	18.52		0
256QAM	36	18	18.76	18.66	18.64	0-5	0
	36	37	18.71	18.55	18.45		0
	75	0	18.60	18.58	18.52		0
	1	0	18.81	18.67	18.48	0-5	0
	1	36	18.83	18.83	18.65		0
	1	74	18.70	18.77	18.26		0
256QAM	36	0	18.57	18.62	18.50	0-5	0
	36	18	18.81	18.53	18.53		0
	36	37	18.68	18.56	18.47		0
	75	0	18.67	18.55	18.60		0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 42 of 222

Table H-73
LTE Band 25 (PCS) Ant F Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.50	18.62	18.34	0	0
	1	25	18.71	18.51	18.34		0
	1	49	18.56	18.38	18.47		0
	25	0	18.66	18.45	18.40	0-1	0
	25	12	18.63	18.61	18.45		0
	25	25	18.72	18.57	18.53		0
	50	0	18.69	18.57	18.39		0
16QAM	1	0	18.65	18.73	18.61	0-1	0
	1	25	19.04	18.74	18.47		0
	1	49	18.93	18.93	18.55		0
	25	0	18.63	18.58	18.49	0-2	0
	25	12	18.81	18.54	18.49		0
	25	25	18.71	18.63	18.48		0
	50	0	18.67	18.50	18.43		0
64QAM	1	0	18.78	18.71	18.50	0-2	0
	1	25	18.82	18.66	18.73		0
	1	49	18.79	18.48	18.68		0
	25	0	18.63	18.55	18.48	0-3	0
	25	12	18.74	18.54	18.46		0
	25	25	18.74	18.69	18.58		0
	50	0	18.78	18.52	18.56		0
256QAM	1	0	18.75	18.57	18.53	0-5	0
	1	25	18.87	18.71	18.57		0
	1	49	18.68	18.64	18.43		0
	25	0	18.79	18.56	18.35		0
	25	12	18.70	18.59	18.49		0
	25	25	18.78	18.58	18.50		0
	50	0	18.64	18.61	18.20		0

Table H-74
LTE Band 25 (PCS) Ant F Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.31	18.47	18.52	0	0
	1	12	18.50	18.55	18.47		0
	1	24	18.58	18.50	18.45		0
	12	0	18.42	18.49	18.40	0-1	0
	12	6	18.67	18.71	18.42		0
	12	13	18.66	18.64	18.43		0
	25	0	18.66	18.50	18.32	0	
16QAM	1	0	18.69	19.06	18.66	0-1	0
	1	12	18.94	18.66	18.60		0
	1	24	18.79	18.86	18.87		0
	12	0	18.50	18.63	18.43	0-2	0
	12	6	18.63	18.74	18.48		0
	12	13	18.74	18.64	18.63		0
	25	0	18.59	18.68	18.41	0	
64QAM	1	0	18.67	18.76	18.43	0-2	0
	1	12	18.92	18.76	18.72		0
	1	24	18.70	18.90	18.69		0
	12	0	18.49	18.63	18.35	0-3	0
	12	6	18.68	18.71	18.52		0
	12	13	18.64	18.73	18.51		0
	25	0	18.64	18.57	18.42		0
256QAM	1	0	18.63	18.40	18.54	0-5	0
	1	12	18.72	18.63	18.67		0
	1	24	18.69	18.77	18.57		0
	12	0	18.53	18.48	18.45		0
	12	6	18.64	18.66	18.54		0
	12	13	18.76	18.69	18.51		0
	25	0	18.65	18.55	18.45		0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 43 of 222

Table H-75
LTE Band 25 (PCS) Ant F Measured P_{Limit} for DSI = 1 (Head) - 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.39	18.44	18.21	0	0
	1	7	18.40	18.54	18.45		0
	1	14	18.47	18.46	18.45		0
	8	0	18.55	18.59	18.34	0-1	0
	8	4	18.53	18.60	18.45		0
	8	7	18.53	18.54	18.48		0
	15	0	18.63	18.55	18.34		0
16QAM	1	0	18.74	18.59	18.48	0-1	0
	1	7	18.72	18.85	18.55		0
	1	14	18.84	18.63	18.57		0
	8	0	18.64	18.69	18.33	0-2	0
	8	4	18.70	18.70	18.54		0
	8	7	18.59	18.67	18.40		0
	15	0	18.64	18.73	18.48		0
64QAM	1	0	18.68	18.58	18.52	0-2	0
	1	7	18.51	18.90	18.70		0
	1	14	18.69	18.72	18.56		0
	8	0	18.69	18.68	18.40	0-3	0
	8	4	18.68	18.74	18.58		0
	8	7	18.64	18.70	18.59		0
	15	0	18.65	18.57	18.43		0
256QAM	1	0	18.70	18.59	18.44	0-5	0
	1	7	18.82	18.80	18.66		0
	1	14	18.71	18.67	18.38		0
	8	0	18.69	18.61	18.35		0
	8	4	18.71	18.69	18.50		0
	8	7	18.65	18.79	18.48		0
	15	0	18.59	18.66	18.48		0

Table H-76
LTE Band 25 (PCS) Ant F Measured P_{Limit} for DSI = 1 (Head) – 1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.75	18.50	18.26	0	0
	1	2	18.40	18.52	18.31		0
	1	5	18.53	18.50	18.37		0
	3	0	18.41	18.54	18.21		0
	3	2	18.49	18.40	18.30		0
	3	3	18.48	18.43	18.37		0
	6	0	18.57	18.56	18.36		0-1
16QAM	1	0	18.86	18.79	18.80	0-1	0
	1	2	18.66	19.17	18.42		0
	1	5	18.81	18.79	18.62		0
	3	0	18.76	18.48	18.51		0
	3	2	18.50	18.61	18.59		0
	3	3	18.65	18.60	18.63		0
	6	0	18.79	18.56	18.45		0-2
64QAM	1	0	18.86	18.92	18.43	0-2	0
	1	2	18.72	18.67	18.71		0
	1	5	18.86	18.69	18.56		0
	3	0	18.78	18.52	18.72		0
	3	2	18.73	19.12	18.49		0
	3	3	18.81	18.86	18.65		0
	6	0	18.76	18.50	18.42		0-3
256QAM	1	0	18.93	18.58	18.80	0-5	0
	1	2	18.83	19.06	18.56		0
	1	5	18.68	18.67	18.59		0
	3	0	18.65	18.52	18.43		0
	3	2	18.81	18.71	18.47		0
	3	3	18.92	18.64	18.55		0
	6	0	18.57	18.65	18.44		0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 44 of 222

H.1.8 LTE Band 30

Table H-77
LTE Band 30 Ant A Measured P_{limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			27710 (2310.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	19.94	0	0
	1	12	19.87		0
	1	24	19.83		0
	12	0	19.84	0-1	0
	12	6	19.85		0
	12	13	19.74		0
	25	0	19.80		0
16QAM	1	0	20.16	0-1	0
	1	12	20.12		0
	1	24	20.05		0
	12	0	19.86	0-2	0
	12	6	19.84		0
	12	13	19.82		0
	25	0	19.80		0
64QAM	1	0	20.03	0-2	0
	1	12	20.17		0
	1	24	20.11		0
	12	0	19.45	0-3	0
	12	6	19.52		0
	12	13	19.39		0
	25	0	19.42		0
256QAM	1	0	17.51	0-5	2
	1	12	17.61		2
	1	24	17.46		2
	12	0	17.44		2
	12	6	17.49		2
	12	13	17.41		2
	25	0	17.41		2

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 45 of 222

Table H-78
LTE Band 30 Ant A Measured P_{Max} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			27710 (2310.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	22.54	0	0
	1	12	22.40		0
	1	24	22.27		0
	12	0	21.51	0-1	1
	12	6	21.57		1
	12	13	21.45		1
	25	0	21.44		1
16QAM	1	0	21.74	0-1	1
	1	12	21.63		1
	1	24	21.47		1
	12	0	20.53	0-2	2
	12	6	20.54		2
	12	13	20.45		2
	25	0	20.47		2
64QAM	1	0	20.74	0-2	2
	1	12	20.72		2
	1	24	20.68		2
	12	0	19.55	0-3	3
	12	6	19.54		3
	12	13	19.48		3
	25	0	19.48		3
256QAM	1	0	17.56	0-5	5
	1	12	17.73		5
	1	24	17.47		5
	12	0	17.45		5
	12	6	17.50		5
	12	13	17.42		5
	25	0	17.48		5

Table H-79
LTE Band 30 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			27710 (2310.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	19.56	0	0
	1	12	19.53		0
	1	24	19.45		0
	12	0	19.53	0-1	0
	12	6	19.54		0
	12	13	19.46		0
	25	0	19.52		0
16QAM	1	0	19.75	0-1	0
	1	12	19.73		0
	1	24	19.75		0
	12	0	19.57	0-2	0
	12	6	19.60		0
	12	13	19.49		0
	25	0	19.49		0
64QAM	1	0	19.78	0-2	0
	1	12	19.88		0
	1	24	19.76		0
	12	0	19.31	0-3	1
	12	6	19.36		1
	12	13	19.20		1
	25	0	19.25		1
256QAM	1	0	17.39	0-5	3
	1	12	17.37		3
	1	24	17.25		3
	12	0	17.28		3
	12	6	17.31		3
	12	13	17.23		3
	25	0	17.25		3

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 47 of 222

Table H-80
LTE Band 30 Ant F Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			27710 (2310.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	16.57	0	0
	1	12	16.53		0
	1	24	16.47		0
	12	0	16.51	0-1	0
	12	6	16.54		0
	12	13	16.46		0
	25	0	16.47		0
16QAM	1	0	16.83	0-1	0
	1	12	16.93		0
	1	24	16.81		0
	12	0	16.55	0-2	0
	12	6	16.58		0
	12	13	16.46		0
	25	0	16.47		0
64QAM	1	0	16.67	0-2	0
	1	12	16.80		0
	1	24	16.60		0
	12	0	16.54	0-3	0
	12	6	16.53		0
	12	13	16.47		0
	25	0	16.46		0
256QAM	1	0	16.66	0-5	0
	1	12	16.79		0
	1	24	16.59		0
	12	0	16.54		0
	12	6	16.60		0
	12	13	16.50		0
	25	0	16.48		0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 48 of 222

H.1.9 LTE Band 7

Table H-81

LTE Band 7 Ant B Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

LTE Band 7 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20825 (2507.5 MHz)	21100 (2535.0 MHz)	21375 (2562.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.59	20.31	20.22	0	0
	1	36	20.38	20.16	20.16		0
	1	74	20.40	19.93	20.08		0
	36	0	20.26	20.17	20.02	0-1	0
	36	18	20.36	20.15	19.99		0
	36	37	20.31	20.02	19.97		0
16QAM	75	0	20.21	20.01	19.87	0-1	0
	1	0	20.40	20.32	20.16		0
	1	36	20.42	20.16	20.18		0
	1	74	20.24	20.33	20.23	0-2	0
	36	0	20.38	20.27	20.10		0
	36	18	20.29	20.09	20.09		0
64QAM	36	37	20.41	20.25	20.20	0-2	0
	75	0	20.32	20.21	20.04		0
	1	0	20.62	20.30	20.35	0-2	0
	1	36	20.56	20.43	20.37		0
	1	74	20.52	20.09	20.39		0
	36	0	20.39	20.13	20.10	0-3	0
36	18	20.39	20.11	20.04	0		
36	37	20.40	20.17	20.17	0		
256QAM	75	0	20.35	20.14	20.16	0-5	0
	1	0	19.06	18.97	18.97		1.5
	1	36	19.04	18.78	18.84		1.5
	1	74	19.00	18.83	18.85		1.5
	36	0	18.94	18.71	18.68		1.5
	36	18	18.97	18.70	18.64		1.5
	36	37	18.92	18.72	18.76		1.5
75	0	18.96	18.72	18.65	1.5		

Table H-82

LTE Band 7 Ant B Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

LTE Band 7 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20800 (2505.0 MHz)	21100 (2535.0 MHz)	21400 (2565.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.52	20.19	20.21	0	0
	1	25	20.34	19.97	20.15		0
	1	49	20.21	19.96	20.15		0
	25	0	20.19	20.11	20.11	0-1	0
	25	12	20.20	20.13	20.06		0
	25	25	20.36	20.12	20.11		0
16QAM	50	0	20.18	20.03	20.20	0-1	0
	1	0	20.48	20.42	19.98		0
	1	25	20.56	20.30	20.31		0
	1	49	20.43	20.24	20.27	0-2	0
	25	0	20.41	20.16	20.07		0
	25	12	20.47	20.23	20.32		0
64QAM	25	25	20.17	19.93	20.14	0-2	0
	50	0	20.42	20.04	20.15		0
	1	0	20.57	20.33	20.43	0-2	0
	1	25	20.59	20.27	20.39		0
	1	49	20.45	20.34	20.42		0
	25	0	20.26	20.15	20.07	0-3	0
25	12	20.19	20.28	20.17	0		
25	25	20.27	20.14	20.32	0		
256QAM	50	0	20.25	20.13	20.01	0-5	0
	1	0	19.06	18.95	18.81		1.5
	1	25	19.10	18.95	19.01		1.5
	1	49	18.99	18.72	18.79		1.5
	25	0	19.01	18.80	18.75		1.5
	25	12	18.90	18.75	18.78		1.5
	25	25	18.76	18.71	18.75		1.5
	50	0	18.94	18.73	18.75		1.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 49 of 222

Table H-83
LTE Band 7 Ant B Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 7 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20775 (2502.5 MHz)	21100 (2535.0 MHz)	21425 (2567.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.34	20.38	20.12	0	0
	1	12	20.31	20.18	20.12		0
	1	24	20.33	20.20	20.11		0
	12	0	20.36	20.10	20.11	0-1	0
	12	6	20.31	20.17	20.06		0
	12	13	20.29	20.10	20.17		0
	25	0	20.23	20.20	20.03		0
16QAM	1	0	20.66	20.58	20.47	0-1	0
	1	12	20.70	20.48	20.43		0
	1	24	20.75	20.63	20.45		0
	12	0	20.37	20.14	20.09	0-2	0
	12	6	20.67	20.34	20.23		0
	12	13	20.37	20.13	20.22		0
	25	0	20.37	20.23	20.29		0
64QAM	1	0	20.48	20.42	20.40	0-2	0
	1	12	20.69	20.40	20.33		0
	1	24	20.65	20.42	20.31		0
	12	0	20.55	20.12	20.03	0-3	0
	12	6	20.57	20.33	20.55		0
	12	13	20.55	20.24	20.13		0
	25	0	20.35	20.21	20.32		0
256QAM	1	0	19.07	18.89	18.85	0-5	1.5
	1	12	19.35	18.97	19.00		1.5
	1	24	19.12	18.97	19.00		1.5
	12	0	18.96	18.70	18.68		1.5
	12	6	19.04	18.78	18.83		1.5
	12	13	19.00	18.76	18.80		1.5
	25	0	18.99	18.75	18.80		1.5

Table H-84
LTE Band 7 Ant B Measured P_{Max} for DSI = 1 (Head) - 15 MHz Bandwidth

LTE Band 7							
15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20825 (2507.5 MHz)	21100 (2535.0 MHz)	21375 (2562.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.98	23.95	23.82	0	0
	1	36	23.83	23.51	23.74		0
	1	74	24.05	23.54	23.65		0
	36	0	22.83	22.71	22.70	0-1	1
	36	18	22.89	22.92	22.79		1
	36	37	22.93	22.69	22.83		1
	75	0	22.90	22.72	22.58		1
16QAM	1	0	23.12	22.89	22.89	0-1	1
	1	36	23.07	22.77	22.86		1
	1	74	22.92	22.83	22.90		1
	36	0	21.98	21.84	21.79	0-2	2
	36	18	21.91	21.74	21.81		2
	36	37	21.81	21.68	21.97		2
	75	0	22.04	21.70	21.63		2
64QAM	1	0	22.18	21.95	21.77	0-2	2
	1	36	22.24	21.96	21.89		2
	1	74	22.07	21.93	22.01		2
	36	0	21.13	20.83	20.64	0-3	3
	36	18	20.91	20.69	20.74		3
	36	37	20.89	20.65	20.80		3
	75	0	20.91	20.86	20.82		3
256QAM	1	0	19.12	18.92	18.96	0-5	5
	1	36	19.05	18.86	18.94		5
	1	74	19.10	18.79	18.91		5
	36	0	18.91	18.73	18.72		5
	36	18	18.87	18.73	18.70		5
	36	37	18.94	18.72	18.76		5
	75	0	18.97	18.70	18.71		5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 50 of 222

Table H-85
LTE Band 7 Ant B Measured P_{Max} for DSI = 1 (Head) - 10 MHz Bandwidth

LTE Band 7 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20800 (2505.0 MHz)	21100 (2535.0 MHz)	21400 (2565.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.04	23.64	23.89	0	0
	1	25	23.84	23.64	23.83		0
	1	49	23.90	23.55	23.79		0
	25	0	22.96	22.71	22.73	0-1	1
	25	12	22.90	22.86	22.93		1
	25	25	22.76	22.76	22.81		1
16QAM	50	0	22.84	22.73	22.75	0-1	1
	1	0	23.13	22.79	22.67		1
	1	25	23.15	22.87	22.91		1
	1	49	23.05	22.98	22.96	0-2	1
	25	0	22.08	21.82	21.83		2
	25	12	21.98	21.85	21.94		2
64QAM	25	25	21.88	21.69	21.98	0-2	2
	50	0	21.91	21.69	21.80		2
	1	0	22.19	21.95	22.05	0-2	2
	1	25	22.21	21.94	22.16		2
	1	49	22.09	21.95	22.13		2
	25	0	21.02	20.88	20.77	0-3	3
25	12	20.98	20.82	20.89	3		
25	25	20.80	20.74	20.76	3		
256QAM	50	0	20.95	20.78	20.66	0-5	3
	1	0	19.08	18.86	18.82		5
	1	25	19.15	18.92	18.98		5
	1	49	18.87	18.75	18.91		5
	25	0	19.03	18.74	18.78		5
	25	12	18.93	18.75	18.85		5
25	25	18.88	18.71	18.79	5		
50	0	18.90	18.76	18.79	5		

Table H-86
LTE Band 7 Ant B Measured P_{Max} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 7 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20775 (2502.5 MHz)	21100 (2535.0 MHz)	21425 (2567.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.93	23.87	23.77	0	0
	1	12	23.89	23.82	23.72		0
	1	24	23.94	23.96	23.78		0
	12	0	22.97	22.81	22.67	0-1	1
	12	6	22.99	22.85	22.80		1
	12	13	22.91	22.76	22.92		1
16QAM	25	0	22.94	22.78	22.84	0-1	1
	1	0	23.29	23.09	23.03		1
	1	12	23.34	23.03	23.08		1
	1	24	23.27	23.11	23.02	0-2	1
	12	0	22.04	21.79	21.62		2
	12	6	22.13	21.85	21.80		2
64QAM	12	13	21.94	21.88	21.87	0-2	2
	25	0	21.99	21.68	21.83		2
	1	0	22.25	21.94	21.92		2
	1	12	22.19	22.00	22.18	0-3	2
	1	24	22.27	21.94	22.00		2
	12	0	21.05	20.73	20.67		3
256QAM	12	6	21.11	20.92	20.93	0-5	3
	12	13	20.88	20.71	20.92		3
	25	0	21.00	20.96	20.77		3
	1	0	19.14	18.86	18.81	0-5	5
	1	12	19.23	19.00	19.14		5
	1	24	19.13	18.86	19.06		5
12	0	18.97	18.74	18.72	5		
12	6	18.97	18.82	18.84	5		
12	13	18.98	18.74	18.79	5		

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 51 of 222

Table H-87

LTE Band 7 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

LTE Band 7 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20825 (2507.5 MHz)	21100 (2535.0 MHz)	21375 (2562.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.61	19.43	19.63	0	0
	1	36	19.59	19.48	19.60		0
	1	74	19.51	19.44	19.61		0
	36	0	19.59	19.53	19.61	0-1	0
	36	18	19.63	19.62	19.68		0
	36	37	19.64	19.60	19.66		0
	75	0	19.66	19.61	19.68		0
16QAM	1	0	19.82	19.56	19.89	0-1	0
	1	36	19.74	19.67	19.77		0
	1	74	19.72	19.67	19.75		0
	36	0	19.65	19.58	19.64	0-2	0
	36	18	19.72	19.67	19.74		0
	36	37	19.65	19.62	19.69		0
	75	0	19.70	19.62	19.74		0
64QAM	1	0	19.89	19.65	19.94	0-2	0
	1	36	19.90	19.85	19.96		0
	1	74	19.81	19.77	19.93		0
	36	0	19.62	19.58	19.68	0-3	0
	36	18	19.72	19.65	19.75		0
	36	37	19.69	19.61	19.70		0
	75	0	19.74	19.65	19.78		0
256QAM	1	0	19.00	18.95	19.02	0-5	1
	1	36	19.06	18.98	19.09		1
	1	74	18.97	18.93	19.01		1
	36	0	18.85	18.79	18.88		1
	36	18	18.95	18.90	18.96		1
	36	37	18.97	18.88	19.01		1
	75	0	18.94	18.88	18.92		1

Table H-88

LTE Band 7 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

LTE Band 7							
10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20800 (2505.0 MHz)	21100 (2535.0 MHz)	21400 (2565.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.68	19.55	19.75	0	0
	1	25	19.58	19.55	19.62		0
	1	49	19.54	19.59	19.64		0
	25	0	19.54	19.54	19.65	0-1	0
	25	12	19.70	19.65	19.64		0
	25	25	19.67	19.65	19.69		0
	50	0	19.69	19.65	19.64		0
16QAM	1	0	19.81	19.75	19.97	0-1	0
	1	25	19.79	19.87	19.91		0
	1	49	19.77	19.71	19.74		0
	25	0	19.65	19.62	19.73	0-2	0
	25	12	19.71	19.71	19.72		0
	25	25	19.69	19.68	19.76		0
	50	0	19.69	19.70	19.69		0
64QAM	1	0	19.93	19.93	19.96	0-2	0
	1	25	20.03	19.81	20.01		0
	1	49	19.95	19.90	19.96		0
	25	0	19.64	19.61	19.72	0-3	0
	25	12	19.77	19.72	19.70		0
	25	25	19.71	19.68	19.74		0
	50	0	19.70	19.73	19.72		0
256QAM	1	0	18.98	18.86	19.00	0-5	1
	1	25	19.14	19.04	19.08		1
	1	49	18.99	18.90	19.18		1
	25	0	18.89	18.85	18.95		1
	25	12	18.99	18.95	18.91		1
	25	25	18.94	18.87	18.96		1
	50	0	18.96	18.91	18.91		1

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 52 of 222

Table H-89
LTE Band 7 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 7 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20775 (2502.5 MHz)	21100 (2535.0 MHz)	21425 (2567.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.57	19.66	19.61	0	0
	1	12	19.61	19.72	19.67		0
	1	24	19.57	19.71	19.63		0
	12	0	19.65	19.56	19.63	0-1	0
	12	6	19.72	19.70	19.74		0
	12	13	19.70	19.67	19.73		0
	25	0	19.67	19.65	19.74		0
16QAM	1	0	19.89	20.01	19.99	0-1	0
	1	12	19.97	19.96	20.09		0
	1	24	19.97	20.06	20.11		0
	12	0	19.71	19.64	19.68	0-2	0
	12	6	19.78	19.77	19.86		0
	12	13	19.73	19.69	19.80		0
	25	0	19.71	19.67	19.77		0
64QAM	1	0	19.86	19.88	19.88	0-2	0
	1	12	19.88	20.03	19.95		0
	1	24	19.86	19.90	20.06		0
	12	0	19.74	19.66	19.69	0-3	0
	12	6	19.78	19.73	19.87		0
	12	13	19.72	19.72	19.80		0
	25	0	19.73	19.68	19.76		0
256QAM	1	0	19.08	18.95	19.02	0-5	1
	1	12	19.24	19.26	19.29		1
	1	24	19.14	19.08	19.21		1
	12	0	18.94	18.87	18.92		1
	12	6	18.99	18.96	19.02		1
	12	13	18.94	18.94	19.00		1
	25	0	18.94	18.90	19.00		1

Table H-90
LTE Band 7 Ant F Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

LTE Band 7 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20825 (2507.5 MHz)	21100 (2535.0 MHz)	21375 (2562.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	16.10	16.05	16.44	0	0
	1	36	16.19	16.62	16.13		0
	1	74	16.05	16.01	15.94		0
	36	0	16.14	16.13	15.96	0-1	0
	36	18	16.14	16.09	16.14		0
	36	37	16.16	16.17	16.15		0
	75	0	16.15	16.10	16.07		0
16QAM	1	0	16.31	16.39	16.31	0-1	0
	1	36	16.43	16.35	16.43		0
	1	74	16.44	16.33	16.26		0
	36	0	16.15	16.15	16.10	0-2	0
	36	18	16.20	16.18	16.21		0
	36	37	16.23	16.19	16.16		0
	75	0	16.16	16.24	16.17		0
64QAM	1	0	16.29	16.38	16.17	0-2	0
	1	36	16.33	16.21	16.64		0
	1	74	16.25	16.37	16.16		0
	36	0	16.19	16.13	16.15	0-3	0
	36	18	16.16	16.21	16.13		0
	36	37	16.13	16.21	16.11		0
	75	0	16.08	16.07	16.18		0
256QAM	1	0	16.18	16.34	16.33	0-5	0
	1	36	16.21	16.41	16.43		0
	1	74	16.12	16.18	16.11		0
	36	0	16.21	16.14	16.13		0
	36	18	16.08	16.26	16.20		0
	36	37	16.28	16.25	16.11		0
	75	0	16.15	16.20	16.20		0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 53 of 222

Table H-91
LTE Band 7 Ant F Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

LTE Band 7 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20800 (2505.0 MHz)	21100 (2535.0 MHz)	21400 (2565.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	16.14	16.13	16.15	0	0
	1	25	16.17	16.25	16.19		0
	1	49	16.11	16.05	16.10		0
	25	0	16.13	16.24	16.08	0-1	0
	25	12	16.15	16.14	16.17		0
	25	25	16.23	16.23	16.17		0
16QAM	50	0	16.11	16.13	16.16	0-1	0
	1	0	16.57	16.50	16.49		0
	1	25	16.38	16.27	16.38		0
	1	49	16.31	16.35	16.44	0-2	0
	25	0	16.26	16.29	16.18		0
	25	12	16.19	16.31	16.26		0
64QAM	25	25	16.22	16.33	16.32	0-2	0
	50	0	16.23	16.21	16.22		0
	1	0	16.33	16.22	16.33		0
	1	25	16.48	16.40	16.28	0-3	0
	1	49	16.19	16.29	16.21		0
	25	0	16.17	16.18	16.21		0
256QAM	25	12	16.23	16.22	16.26	0-5	0
	25	25	16.27	16.26	16.21		0
	50	0	16.26	16.27	16.16		0
	1	0	16.28	15.97	16.38	0-5	0
	1	25	16.35	16.44	16.22		0
	1	49	16.25	16.19	16.27		0
25	0	16.29	16.24	16.16	0		
25	12	16.20	16.02	16.26	0		
	25	25	16.24	16.21	16.12		0
	50	0	16.18	16.22	16.23		0

Table H-92
LTE Band 7 Ant F Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 7 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20775 (2502.5 MHz)	21100 (2535.0 MHz)	21425 (2567.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	16.09	16.24	16.15	0	0
	1	12	16.17	16.22	16.24		0
	1	24	16.23	16.16	15.99		0
	12	0	16.27	16.12	16.06	0-1	0
	12	6	16.27	16.30	16.20		0
	12	13	16.28	16.20	16.16		0
	25	0	16.22	16.06	16.21		0
16QAM	1	0	16.33	16.35	16.59	0-1	0
	1	12	16.69	16.37	16.30		0
	1	24	16.38	16.50	16.47		0
	12	0	16.32	16.16	16.17	0-2	0
	12	6	16.33	16.31	16.31		0
	12	13	16.34	16.24	16.35		0
	25	0	16.28	16.21	16.17		0
64QAM	1	0	16.13	16.32	16.18	0-2	0
	1	12	16.57	16.55	16.42		0
	1	24	16.38	16.12	16.29		0
	12	0	16.32	16.17	16.06	0-3	0
	12	6	16.34	16.27	16.19		0
	12	13	16.30	16.35	16.21		0
	25	0	16.23	16.16	16.18		0
256QAM	1	0	16.16	16.14	16.24	0-5	0
	1	12	16.53	16.38	16.35		0
	1	24	16.32	16.27	16.15		0
	12	0	16.22	16.16	16.12		0
	12	6	16.29	16.25	16.28		0
	12	13	16.17	16.35	16.19		0
	25	0	16.21	16.25	16.19		0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 54 of 222

H.1.10 LTE Band 41

Table H-93

LTE Band 41 Ant B Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

LTE Band 41 15 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	22.36	22.06	22.38	22.39	22.51	0	0
	1	36	22.29	22.19	22.33	22.34	22.39		0
	1	74	22.18	22.11	22.17	22.29	22.34		0
	36	0	22.45	22.37	22.66	22.75	22.52	0-1	0
	36	18	22.44	22.50	22.46	22.50	22.47		0
	36	37	22.17	22.59	22.34	22.54	22.43		0
	75	0	22.37	22.40	22.36	22.80	22.49		0
16QAM	1	0	22.29	22.18	22.62	22.63	22.54	0-1	0
	1	36	22.18	22.73	22.25	22.33	22.42		0
	1	74	22.14	22.46	22.25	22.55	22.26		0
	36	0	22.09	22.13	22.20	22.15	22.38	0-2	0
	36	18	22.32	22.22	22.29	22.01	22.64		0
	36	37	22.23	22.38	22.20	22.22	22.21		0
	75	0	22.35	22.21	22.03	22.31	22.48		0
64QAM	1	0	22.18	21.98	22.35	22.44	22.39	0-2	0
	1	36	22.37	22.12	22.38	22.38	22.06		0
	1	74	22.25	22.07	22.20	22.30	22.04		0
	36	0	21.15	21.30	21.11	21.15	21.37	0-3	1
	36	18	21.25	21.34	21.16	21.24	21.48		1
	36	37	21.56	21.26	20.95	21.35	21.38		1
	75	0	21.44	21.13	21.28	21.64	21.20		1
256QAM	1	0	19.13	19.03	19.29	19.32	19.46	0-5	3
	1	36	19.09	19.35	19.10	19.09	18.92		3
	1	74	19.15	19.40	19.01	19.16	19.06		3
	36	0	19.23	19.15	19.30	19.26	19.35		3
	36	18	19.24	19.28	19.24	19.33	19.30		3
	36	37	19.12	19.24	19.15	19.27	19.25		3
	75	0	19.18	19.24	19.22	19.29	19.31		3

Table H-94

LTE Band 41 Ant B Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

LTE Band 41 10 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	22.48	22.26	22.58	22.61	22.68	0	0
	1	25	22.40	22.27	22.44	22.52	22.62		0
	1	49	22.35	22.31	22.45	22.54	22.66		0
	25	0	22.47	22.72	22.82	22.57	22.78	0-1	0
	25	12	22.37	22.82	22.38	22.50	22.74		0
	25	25	22.48	22.75	22.68	22.58	22.66		0
	50	0	22.47	22.64	22.80	22.75	22.70		0
16QAM	1	0	22.58	22.41	22.70	22.79	22.71	0-1	0
	1	25	22.44	22.80	22.63	22.89	22.85		0
	1	49	22.36	22.76	22.40	22.47	22.64		0
	25	0	22.20	22.33	22.39	22.52	22.71	0-2	0
	25	12	22.19	22.26	22.39	22.59	22.48		0
	25	25	22.20	22.44	22.41	22.43	22.69		0
	50	0	22.25	22.49	22.57	22.49	22.43		0
64QAM	1	0	22.48	22.36	22.36	22.51	22.37	0-2	0
	1	25	22.30	22.38	22.60	22.52	22.12		0
	1	49	22.28	22.40	22.33	22.49	22.07		0
	25	0	21.57	21.28	21.51	21.46	21.36	0-3	1
	25	12	21.41	21.46	21.36	21.42	21.50		1
	25	25	21.23	21.56	21.60	21.44	21.75		1
	50	0	21.25	21.60	21.57	21.46	21.66		1
256QAM	1	0	19.21	19.32	19.40	19.45	19.37	0-5	3
	1	25	19.30	19.33	19.33	19.38	19.20		3
	1	49	19.15	19.16	19.19	19.34	18.99		3
	25	0	19.35	19.35	19.44	19.48	19.55		3
	25	12	19.38	19.47	19.44	19.52	19.55		3
	25	25	19.26	19.48	19.36	19.51	19.53		3
	50	0	19.35	19.43	19.49	19.53	19.56		3

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 55 of 222

Table H-95

LTE Band 41 Ant B Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	22.52	22.58	22.49	22.45	22.57	0	0
	1	12	22.52	22.57	22.46	22.60	22.59		0
	1	24	22.49	22.55	22.45	22.54	22.48		0
	12	0	22.70	22.69	22.47	22.71	22.74	0-1	0
	12	6	22.65	22.65	22.75	22.66	22.78		0
	12	13	22.49	22.51	22.43	22.44	22.64		0
	25	0	22.42	22.78	22.70	22.68	22.70	0	
16QAM	1	0	22.73	22.77	22.55	22.69	22.52	0-1	0
	1	12	22.61	22.79	22.39	22.72	22.63		0
	1	24	22.55	22.59	22.52	22.61	22.44		0
	12	0	22.23	22.32	22.33	22.42	22.51	0-2	0
	12	6	22.49	22.61	22.76	22.44	22.65		0
	12	13	22.25	22.52	22.39	22.43	22.36		0
	25	0	22.61	22.38	22.28	22.38	22.55	0	
64QAM	1	0	22.50	22.59	22.42	22.48	22.18	0-2	0
	1	12	22.51	22.53	22.39	22.51	22.00		0
	1	24	22.42	22.46	22.32	22.48	21.96		0
	12	0	21.41	21.60	21.41	21.34	21.35	0-3	1
	12	6	21.50	21.39	21.32	21.43	21.77		1
	12	13	21.42	21.63	21.58	21.55	21.61		1
	25	0	21.31	21.34	21.26	21.32	21.54	1	
256QAM	1	0	19.27	19.28	19.39	19.17	19.19	0-5	3
	1	12	19.29	19.47	19.38	19.44	19.19		3
	1	24	19.32	19.17	19.14	19.48	18.90		3
	12	0	19.49	19.35	19.39	19.49	19.51	0-5	3
	12	6	19.42	19.52	19.41	19.54	19.56		3
	12	13	19.34	19.41	19.46	19.51	19.45		3
	25	0	19.42	19.43	19.43	19.47	19.49	3	

Table H-96

LTE Band 41 Ant B Measured P_{Max} for DSI = 1 (Head) - 15 MHz Bandwidth

LTE Band 41 15 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	24.43	24.10	24.36	24.35	24.49	0	0
	1	36	24.44	24.20	24.33	24.35	24.42		0
	1	74	24.41	24.22	24.20	24.32	24.36		0
	36	0	23.62	23.35	23.35	23.40	23.71	0-1	1
	36	18	23.58	23.50	23.27	23.50	23.63		1
	36	37	23.47	23.41	23.31	23.50	23.43		1
	75	0	23.43	23.35	23.43	23.43	23.56		1
16QAM	1	0	23.69	23.53	23.52	23.46	23.47	0-1	1
	1	36	23.64	23.64	23.29	23.42	23.51		1
	1	74	23.45	23.35	23.10	23.46	23.35		1
	36	0	22.70	22.53	22.28	22.32	22.45	0-2	2
	36	18	22.61	22.52	22.43	22.34	22.59		2
	36	37	22.48	22.53	22.18	22.49	22.44		2
	75	0	22.53	22.49	22.46	22.48	22.53		2
64QAM	1	0	22.54	22.53	22.52	22.44	22.74	0-2	2
	1	36	22.61	22.36	22.44	22.61	22.67		2
	1	74	22.59	22.28	22.30	22.46	22.55		2
	36	0	21.62	21.45	21.29	21.40	21.50	0-3	3
	36	18	21.57	21.66	21.42	21.58	21.77		3
	36	37	21.61	21.44	21.33	21.54	21.62		3
	75	0	21.65	21.50	21.63	21.37	21.53		3
256QAM	1	0	19.58	19.27	19.44	19.33	19.53	0-5	5
	1	36	19.54	19.60	19.44	19.38	19.42		5
	1	74	19.42	19.37	19.16	19.42	19.28		5
	36	0	19.57	19.35	19.37	19.37	19.47	0-5	5
	36	18	19.53	19.49	19.36	19.37	19.53		5
	36	37	19.48	19.51	19.29	19.41	19.44		5
	75	0	19.48	19.48	19.37	19.41	19.46		5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 56 of 222

Table H-97
LTE Band 41 Ant B Measured P_{Max} for DSI = 1 (Head) - 10 MHz Bandwidth

LTE Band 41 10 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	24.37	24.18	24.35	24.37	24.61	0	0
	1	25	24.40	24.16	24.31	24.29	24.48		0
	1	49	24.44	24.16	24.24	24.34	24.48		0
	25	0	23.64	23.39	23.49	23.44	23.57	0-1	1
	25	12	23.58	23.54	23.67	23.52	23.64		1
	25	25	23.51	23.47	23.41	23.51	23.38		1
	50	0	23.43	23.51	23.56	23.47	23.46		1
16QAM	1	0	23.44	23.55	23.37	23.42	23.46	0-1	1
	1	25	23.33	23.84	23.36	23.60	23.40		1
	1	49	23.20	23.59	23.18	23.44	23.24		1
	25	0	22.42	22.41	22.45	22.43	22.54	0-2	2
	25	12	22.46	22.53	22.39	22.61	22.62		2
	25	25	22.37	22.46	22.39	22.53	22.57		2
	50	0	22.51	22.58	22.45	22.45	22.61		2
64QAM	1	0	22.56	22.37	22.52	22.48	22.63	0-2	2
	1	25	22.43	22.48	22.53	22.60	22.67		2
	1	49	22.38	22.44	22.40	22.52	22.60		2
	25	0	21.51	21.46	21.40	21.41	21.40	0-3	3
	25	12	21.35	21.79	21.45	21.43	21.46		3
	25	25	21.38	21.47	21.44	21.44	21.54		3
	50	0	21.55	21.49	21.37	21.53	21.77		3
256QAM	1	0	19.34	19.29	19.39	19.35	19.27	0-5	5
	1	25	19.34	19.49	19.34	19.52	19.45		5
	1	49	19.14	19.39	19.17	19.40	19.36		5
	25	0	19.44	19.39	19.41	19.42	19.50		5
	25	12	19.49	19.53	19.39	19.52	19.59		5
	25	25	19.38	19.54	19.31	19.49	19.55		5
	50	0	19.44	19.49	19.39	19.46	19.53		5

Table H-98
LTE Band 41 Ant B Measured P_{Max} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	24.52	24.45	24.23	24.34	24.45	0	0
	1	12	24.54	24.49	24.31	24.39	24.35		0
	1	24	24.52	24.46	24.19	24.32	24.36		0
	12	0	23.55	23.37	23.37	23.55	23.69	0-1	1
	12	6	23.60	23.59	23.38	23.55	23.53		1
	12	13	23.57	23.44	23.61	23.45	23.50		1
	25	0	23.67	23.63	23.39	23.47	23.45		1
16QAM	1	0	23.75	23.62	23.38	23.45	23.38	0-1	1
	1	12	23.49	23.50	23.32	23.46	23.28		1
	1	24	23.43	23.50	23.13	23.35	23.35		1
	12	0	22.71	22.43	22.34	22.49	22.58	0-2	2
	12	6	22.72	22.56	22.42	22.54	22.61		2
	12	13	22.62	22.56	22.34	22.52	22.53		2
	25	0	22.61	22.50	22.25	22.51	22.52		2
64QAM	1	0	22.52	22.63	22.41	22.68	22.58	0-2	2
	1	12	22.67	22.82	22.45	22.57	22.61		2
	1	24	22.56	22.62	22.34	22.45	22.46		2
	12	0	21.67	21.39	21.41	21.74	21.69	0-3	3
	12	6	21.66	21.54	21.44	21.49	21.57		3
	12	13	21.50	21.47	21.48	21.51	21.52		3
	25	0	21.51	21.62	21.47	21.42	21.72		3
256QAM	1	0	19.47	19.41	19.18	19.29	19.46	0-5	5
	1	12	19.54	19.58	19.31	19.34	19.52		5
	1	24	19.40	19.42	19.22	19.33	19.37		5
	12	0	19.55	19.40	19.40	19.49	19.51		5
	12	6	19.56	19.50	19.38	19.52	19.57		5
	12	13	19.49	19.47	19.34	19.48	19.50		5
	25	0	19.52	19.53	19.41	19.48	19.51		5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 57 of 222

Table H-99

LTE Band 41 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

LTE Band 41 15 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	21.45	21.47	21.51	21.48	21.52	0	0
	1	36	21.44	21.48	21.43	21.45	21.43		0
	1	74	21.32	21.46	21.33	21.42	21.29		0
	36	0	21.45	21.54	21.46	21.53	21.52	0-1	0
	36	18	21.49	21.61	21.55	21.54	21.56		0
	36	37	21.45	21.57	21.49	21.53	21.50		0
	75	0	21.50	21.57	21.50	21.48	21.54	0	
16QAM	1	0	21.47	21.40	21.45	21.59	21.56	0-1	0
	1	36	21.59	21.59	21.49	21.65	21.59		0
	1	74	21.39	21.37	21.41	21.39	21.37		0
	36	0	21.50	21.56	21.49	21.55	21.56	0-2	0
	36	18	21.54	21.61	21.54	21.56	21.56		0
	36	37	21.49	21.59	21.50	21.54	21.52		0
	75	0	21.55	21.59	21.53	21.48	21.55	0	
64QAM	1	0	21.59	21.44	21.66	21.57	21.65	0-2	0
	1	36	21.56	21.69	21.59	21.54	21.54		0
	1	74	21.40	21.68	21.31	21.48	21.42		0
	36	0	21.03	21.06	21.01	21.03	21.01	0-3	0.5
	36	18	21.04	21.14	21.06	21.01	21.11		0.5
	36	37	21.01	21.08	20.95	21.06	21.01		0.5
	75	0	21.05	21.08	21.04	21.01	21.04	0.5	
256QAM	1	0	19.02	18.93	19.02	18.99	19.04	0-5	2.5
	1	36	18.98	19.03	18.92	19.04	19.07		2.5
	1	74	18.76	18.94	18.81	19.03	18.94		2.5
	36	0	19.00	19.06	18.99	19.05	19.07		2.5
	36	18	19.06	19.11	19.04	19.02	19.08		2.5
	36	37	18.99	19.10	18.98	19.07	19.02		2.5
	75	0	19.01	19.06	19.04	19.00	19.06		2.5

Table H-100

LTE Band 41 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

LTE Band 41 10 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	21.47	21.53	21.51	21.55	21.54	0	0
	1	25	21.43	21.66	21.48	21.45	21.51		0
	1	49	21.37	21.44	21.40	21.50	21.43		0
	25	0	21.55	21.59	21.61	21.57	21.58	0	
	25	12	21.54	21.62	21.61	21.58	21.65	0-1	0
	25	25	21.51	21.61	21.54	21.60	21.56		0
16QAM	50	0	21.54	21.58	21.57	21.53	21.61	0	
	1	0	21.46	21.53	21.48	21.56	21.54	0-1	0
	1	25	21.51	21.55	21.60	21.64	21.58		0
	1	49	21.39	21.44	21.49	21.40	21.36		0
	25	0	21.59	21.58	21.65	21.57	21.59	0-2	0
	25	12	21.61	21.60	21.60	21.60	21.67		0
25	25	21.57	21.56	21.51	21.61	21.61	0		
64QAM	50	0	21.58	21.60	21.58	21.52	21.61	0	
	1	0	21.65	21.53	21.51	21.64	21.65	0-2	0
	1	25	21.51	21.64	21.58	21.70	21.63		0
	1	49	21.47	21.50	21.46	21.52	21.44		0
	25	0	21.10	21.07	21.10	21.06	21.08	0-3	0.5
	25	12	21.12	21.10	21.11	21.09	21.18		0.5
25	25	21.07	21.07	21.06	21.06	21.06	0.5		
256QAM	50	0	21.06	21.03	21.09	21.09	21.08	0.5	
	1	0	18.94	18.99	19.11	18.99	19.06	0-5	2.5
	1	25	19.01	19.06	19.03	19.15	19.00		2.5
	1	49	18.84	18.88	18.92	18.92	18.96		2.5
	25	0	19.11	19.09	19.12	19.07	19.01	2.5	
	25	12	19.10	19.11	19.11	19.07	19.16	2.5	
256QAM	25	25	19.03	19.10	19.08	19.12	19.08	2.5	
	50	0	19.08	19.09	19.08	19.09	19.11	2.5	

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 58 of 222

Table H-101

LTE Band 41 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth										
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)			
			Conducted Power [dBm]							
QPSK	1	0	21.46	21.50	21.41	21.40	21.42	0	0	
	1	12	21.55	21.54	21.49	21.52	21.48		0-1	0
	1	24	21.46	21.45	21.36	21.42	21.40			0
	12	0	21.55	21.59	21.55	21.52	21.53	0		
	12	6	21.57	21.58	21.57	21.54	21.61	0		
	12	13	21.55	21.58	21.50	21.56	21.55	0		
16QAM	25	0	21.58	21.59	21.54	21.50	21.55	0-1	0	
	1	0	21.47	21.36	21.48	21.50	21.52		0-2	0
	1	12	21.51	21.53	21.46	21.62	21.50			0
	1	24	21.51	21.45	21.34	21.50	21.40	0		
	12	0	21.57	21.55	21.55	21.55	21.49	0		
	12	6	21.59	21.55	21.56	21.54	21.59	0		
64QAM	12	13	21.55	21.54	21.53	21.58	21.59	0-2	0	
	25	0	21.58	21.58	21.53	21.54	21.57		0-3	0
	1	0	21.61	21.54	21.51	21.54	21.58			0
	1	12	21.66	21.68	21.58	21.63	21.62	0-3		0
	1	24	21.55	21.52	21.44	21.57	21.49		0	
	12	0	21.07	21.09	21.06	21.03	21.07		0.5	
256QAM	12	6	21.13	21.10	21.07	21.11	21.15	0-5	0.5	
	12	13	21.07	21.06	21.04	21.09	21.05		0-5	0.5
	25	0	21.02	21.07	21.02	21.01	21.07			0.5
	1	0	18.93	18.95	18.92	18.83	18.94	0-5		2.5
	1	12	19.04	19.00	19.05	19.08	19.11		2.5	
	1	24	18.85	18.97	18.81	18.91	18.83		2.5	
12	0	19.09	19.05	19.04	19.02	19.03	2.5			
12	6	19.12	19.07	19.08	19.03	19.11	2.5			
12	13	19.07	19.03	19.04	19.07	19.04	2.5			
256QAM	25	0	19.10	19.11	19.03	19.02	19.07	2.5		

Table H-102

LTE Band 41 Ant F Measured P_{Limit} for DSI = 1 (Head) – 15 MHz Bandwidth

LTE Band 41 15 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	18.32	18.16	18.43	18.12	18.17	0	0
	1	36	18.31	18.24	18.34	18.04	18.08		0
	1	74	18.21	18.18	18.24	17.93	18.01		0
	36	0	18.34	18.20	18.42	18.12	18.15	0-1	0
	36	18	18.38	18.31	18.45	18.09	18.16		0
	36	37	18.30	18.31	18.38	18.08	18.15		0
16QAM	75	0	18.42	18.32	18.42	18.00	18.10	0	
	1	0	18.28	18.23	18.37	18.11	18.16	0-1	0
	1	36	18.23	18.26	18.31	18.04	18.04		0
	1	74	18.08	18.20	18.09	17.93	18.04		0
	36	0	18.41	18.28	18.38	18.16	18.16	0-2	0
	36	18	18.40	18.31	18.41	18.08	18.15		0
36	37	18.32	18.34	18.41	18.09	18.18	0		
64QAM	75	0	18.38	18.27	18.42	18.03	18.11	0	
	1	0	18.48	18.28	18.46	18.21	18.31	0-2	0
	1	36	18.54	18.38	18.41	18.21	18.22		0
	1	74	18.35	18.30	18.32	18.13	18.14		0
	36	0	18.40	18.23	18.41	18.15	18.17	0-3	0
	36	18	18.41	18.32	18.43	18.10	18.18		0
36	37	18.41	18.31	18.34	18.07	18.18	0		
256QAM	75	0	18.41	18.31	18.42	17.98	18.13	0	
	1	0	18.42	18.23	18.43	18.22	18.33	0-5	0
	1	36	18.33	18.27	18.50	18.01	18.04		0
	1	74	18.18	18.30	18.31	18.11	18.00		0
	36	0	18.42	18.30	18.42	18.14	18.25	0	
	36	18	18.42	18.32	18.43	18.06	18.13	0	
	36	37	18.38	18.31	18.40	18.10	18.22	0	
	75	0	18.40	18.33	18.43	18.06	18.16	0	

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 59 of 222

Table H-103
LTE Band 41 Ant F Measured P_{Limit} for DSI = 1 (Head) – 10 MHz Bandwidth

LTE Band 41 10 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	18.41	18.28	18.41	18.21	18.23	0	0
	1	25	18.36	18.29	18.48	18.13	18.25		0
	1	49	18.33	18.21	18.34	18.06	18.14		0
	25	0	18.42	18.32	18.47	18.17	18.21	0-1	0
	25	12	18.48	18.34	18.54	18.11	18.25		0
	25	25	18.43	18.34	18.47	18.17	18.21		0
	50	0	18.46	18.34	18.48	18.15	18.20		0
16QAM	1	0	18.45	18.16	18.33	18.12	18.24	0-1	0
	1	25	18.26	18.22	18.33	18.02	18.21		0
	1	49	18.25	18.10	18.26	17.95	18.05		0
	25	0	18.44	18.31	18.44	18.14	18.21	0-2	0
	25	12	18.49	18.33	18.51	18.14	18.23		0
	25	25	18.41	18.30	18.44	18.13	18.25		0
	50	0	18.47	18.32	18.51	18.09	18.18		0
64QAM	1	0	18.56	18.35	18.59	18.34	18.37	0-2	0
	1	25	18.47	18.32	18.34	18.24	18.25		0
	1	49	18.40	18.31	18.40	18.05	18.25		0
	25	0	18.45	18.34	18.44	18.18	18.23	0-3	0
	25	12	18.47	18.38	18.49	18.09	18.23		0
	25	25	18.44	18.28	18.44	18.11	18.28		0
	50	0	18.47	18.31	18.48	18.12	18.15		0
256QAM	1	0	18.45	18.24	18.36	18.19	18.19	0-5	0
	1	25	18.44	18.37	18.56	18.10	18.23		0
	1	49	18.42	18.26	18.27	18.03	18.16		0
	25	0	18.44	18.33	18.46	18.16	18.25		0
	25	12	18.56	18.34	18.59	18.16	18.20		0
	25	25	18.45	18.34	18.46	18.20	18.29		0
	50	0	18.52	18.34	18.54	18.16	18.27		0

Table H-104
LTE Band 41 Ant F Measured P_{Limit} for DSI = 1 (Head) – 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	18.30	18.26	18.29	18.06	18.06	0	0
	1	12	18.45	18.32	18.40	18.13	18.15		0
	1	24	18.33	18.23	18.31	17.94	18.08		0
	12	0	18.50	18.37	18.47	18.14	18.17	0-1	0
	12	6	18.49	18.35	18.50	18.11	18.23		0
	12	13	18.42	18.34	18.46	18.15	18.23		0
	25	0	18.44	18.29	18.45	18.08	18.15		0
16QAM	1	0	18.43	18.25	18.29	17.97	17.98	0-1	0
	1	12	18.41	18.31	18.35	18.09	18.22		0
	1	24	18.29	18.03	18.25	18.01	18.10		0
	12	0	18.48	18.30	18.48	18.06	18.11	0-2	0
	12	6	18.48	18.30	18.48	18.05	18.13		0
	12	13	18.48	18.29	18.37	18.17	18.25		0
	25	0	18.43	18.34	18.43	18.05	18.15		0
64QAM	1	0	18.45	18.21	18.40	18.10	18.20	0-2	0
	1	12	18.53	18.52	18.61	18.16	18.21		0
	1	24	18.55	18.26	18.18	18.04	18.19		0
	12	0	18.48	18.36	18.46	18.11	18.20	0-3	0
	12	6	18.58	18.34	18.49	18.14	18.25		0
	12	13	18.48	18.27	18.41	18.13	18.22		0
	25	0	18.49	18.36	18.47	18.07	18.16		0
256QAM	1	0	18.28	18.28	18.41	17.92	18.02	0-5	0
	1	12	18.55	18.32	18.31	18.11	18.29		0
	1	24	18.32	18.28	18.43	18.11	18.08		0
	12	0	18.53	18.36	18.52	18.13	18.17		0
	12	6	18.51	18.38	18.52	18.15	18.25		0
	12	13	18.52	18.36	18.46	18.13	18.29		0
	25	0	18.52	18.38	18.53	18.14	18.22		0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 60 of 222

H.1.11 LTE Band 48

Table H-105

LTE Band 48 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

LTE Band 48 15 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55315 (3557.5 MHz)	55765 (3602.5 MHz)	56215 (3647.5 MHz)	56665 (3692.5 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	21.30	21.75	21.72	21.77	0	0
	1	36	21.44	21.65	22.00	22.11		0
	1	74	21.37	21.95	21.82	21.91		0
	36	0	20.53	20.82	20.76	20.83	0-1	0.5
	36	18	20.61	20.93	20.77	20.82		0.5
	36	37	20.70	20.88	20.91	20.97		0.5
	75	0	20.61	20.83	20.87	20.84	0.5	
16QAM	1	0	20.89	21.23	20.96	20.91	0-1	0.5
	1	36	20.73	21.33	21.24	21.05		0.5
	1	74	20.73	21.30	21.11	21.25		0.5
	36	0	19.48	19.73	19.78	19.80	0-2	1.5
	36	18	19.61	19.85	19.87	19.87		1.5
	36	37	19.66	19.91	19.92	19.95		1.5
	75	0	19.64	19.85	19.89	19.87	1.5	
64QAM	1	0	19.90	20.00	20.00	20.10	0-2	1.5
	1	36	19.91	20.05	20.20	20.18		1.5
	1	74	19.94	20.03	20.10	20.33		1.5
	36	0	18.49	18.78	18.79	18.85	0-3	2.5
	36	18	18.66	18.91	18.83	18.89		2.5
	36	37	18.67	18.86	18.93	18.92		2.5
	75	0	18.62	18.87	18.91	18.81		2.5
256QAM	1	0	16.48	16.68	16.92	16.95	0-5	4.5
	1	36	16.70	16.95	16.94	17.12		4.5
	1	74	16.92	16.73	17.06	17.21		4.5
	36	0	16.45	16.76	16.77	16.86		4.5
	36	18	16.59	16.82	16.79	16.89		4.5
	36	37	16.62	16.83	16.91	16.95		4.5
	75	0	16.62	16.85	16.90	16.90		4.5

Table H-106

LTE Band 48 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

LTE Band 48 10 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55290 (3555.0 MHz)	55757 (3601.7 MHz)	56223 (3648.3 MHz)	56690 (3695.0 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	21.63	21.63	21.89	21.99	0	0
	1	25	21.65	21.58	21.95	21.99		0
	1	49	21.66	21.66	21.94	22.05		0
	25	0	20.71	20.83	20.84	20.90	0-1	0.5
	25	12	20.69	20.88	20.89	20.89		0.5
	25	25	20.72	20.87	20.92	20.95		0.5
	50	0	20.62	20.89	20.91	20.85		0.5
16QAM	1	0	20.83	21.01	21.13	21.13	0-1	0.5
	1	25	20.80	21.07	21.14	21.23		0.5
	1	49	20.89	21.10	21.13	21.12		0.5
	25	0	19.75	19.91	19.80	19.89	0-2	1.5
	25	12	19.77	19.93	19.97	19.93		1.5
	25	25	19.73	19.93	19.95	20.00		1.5
	50	0	19.66	19.86	19.92	19.95		1.5
64QAM	1	0	19.90	20.07	20.11	20.17	0-2	1.5
	1	25	20.00	20.12	20.26	20.19		1.5
	1	49	19.82	20.08	20.11	20.23		1.5
	25	0	18.62	18.86	18.85	18.89	0-3	2.5
	25	12	18.65	18.92	18.97	18.93		2.5
	25	25	18.68	18.90	18.91	18.96		2.5
	50	0	18.63	18.91	18.97	18.93		2.5
256QAM	1	0	16.50	16.79	16.91	16.91	0-5	4.5
	1	25	17.06	17.01	17.13	17.08		4.5
	1	49	16.64	16.94	16.93	17.04		4.5
	25	0	16.64	16.84	16.81	16.96		4.5
	25	12	16.64	16.88	16.94	16.90		4.5
	25	25	16.67	16.85	16.93	17.01		4.5
	50	0	16.62	16.89	16.92	16.92		4.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 61 of 222

Table H-107

LTE Band 48 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 48 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			55265 (3552.5 MHz)	55748 (3600.8 MHz)	56232 (3649.2 MHz)	56715 (3697.5 MHz)			
			Conducted Power [dBm]						
QPSK	1	0	21.69	22.10	21.95	22.00	0	0	
	1	12	21.76	22.13	22.05	22.09		0	
	1	24	21.71	22.03	22.01	22.03		0	
	12	0	20.70	20.87	20.82	20.84	0-1	0.5	
	12	6	20.72	20.91	20.87	20.96		0.5	
	12	13	20.68	20.87	20.93	20.93		0.5	
16QAM	25	0	20.65	20.85	20.91	20.92	0-1	0.5	
	1	0	20.78	20.84	21.18	21.14		0.5	
	1	12	20.83	20.99	21.36	21.29		0.5	
	1	24	20.81	21.18	21.12	21.17	0-2	0.5	
	12	0	19.74	19.92	19.94	19.91		1.5	
	12	6	19.76	20.01	19.92	20.08		1.5	
64QAM	12	13	19.74	19.90	19.99	19.96	0-2	1.5	
	25	0	19.70	19.90	19.94	19.91		1.5	
	1	0	19.81	20.23	20.17	20.22		0-2	1.5
	1	12	20.10	20.16	20.21	20.31	1.5		
	1	24	19.83	20.21	20.21	20.02	1.5		
	12	0	18.74	18.91	18.87	18.88	0-3	2.5	
12	6	18.77	18.92	18.92	19.03	2.5			
12	13	18.67	18.89	18.93	18.99	2.5			
256QAM	25	0	18.73	18.87	18.94	18.93	0-3	2.5	
	1	0	16.70	16.89	16.91	16.95		0-5	4.5
	1	12	16.75	16.93	17.04	17.09			4.5
	1	24	16.64	16.92	17.00	17.05	4.5		
	12	0	16.70	16.82	16.84	16.89	4.5		
	12	6	16.77	16.95	16.93	17.02	4.5		
12	13	16.69	16.87	16.90	16.99	4.5			
25	0	16.69	16.85	16.89	16.97		4.5		

Table H-108

LTE Band 48 Ant F Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

LTE Band 48 15 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			55315 (3557.5 MHz)	55765 (3602.5 MHz)	56215 (3647.5 MHz)	56665 (3692.5 MHz)			
			Conducted Power [dBm]						
QPSK	1	0	17.26	17.37	17.65	17.74	0	0	
	1	36	17.33	17.71	17.72	17.77		0	
	1	74	17.20	17.58	17.78	17.79		0	
	36	0	17.52	17.77	17.83	17.86	0-1	0	
	36	18	17.65	17.88	17.84	17.91		0	
	36	37	17.70	17.89	17.94	17.99		0	
16QAM	75	0	17.63	17.86	17.91	17.87	0-1	0	
	1	0	17.67	17.78	17.71	17.70		0	
	1	36	17.60	18.07	17.83	18.01		0	
	1	74	17.84	17.91	17.92	17.99	0-2	0	
	36	0	17.56	17.79	17.82	17.89		0	
	36	18	17.67	17.91	17.85	17.91		0	
	36	37	17.70	17.93	17.98	18.02	0-2	0	
	75	0	17.70	17.92	17.97	17.96		0	
	64QAM	1	0	17.79	17.72	17.84		17.92	0-2
		1	36	18.09	18.02	17.84	18.01	0	
1		74	18.01	17.86	17.89	17.95	0		
36		0	17.56	17.83	17.83	17.95	0-3	0	
36		18	17.70	17.91	17.87	17.93		0	
36		37	17.71	17.92	17.95	18.06		0	
75		0	17.63	17.82	17.94	17.99	0-3	0	
256QAM		1	0	16.44	16.77	16.76		16.79	0-5
	1	36	16.79	16.67	16.81	16.91	1		
	1	74	16.65	17.01	17.02	16.98	1		
	36	0	16.52	16.79	16.84	16.92	1		
	36	18	16.71	16.90	16.81	16.97	1		
	36	37	16.68	16.91	16.97	17.08	1		
	75	0	16.72	16.91	16.91	16.96	1		

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 62 of 222

Table H-109
LTE Band 48 Ant F Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

LTE Band 48 10 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55290 (3555.0 MHz)	55757 (3601.7 MHz)	56223 (3648.3 MHz)	56690 (3695.0 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	17.26	17.68	17.77	17.85	0	0
	1	25	17.47	17.64	17.83	17.84		0
	1	49	17.35	17.68	17.83	17.91		0
	25	0	17.65	17.94	17.89	17.92	0-1	0
	25	12	17.71	17.92	17.95	17.94		0
	25	25	17.67	17.91	17.96	18.01		0
	50	0	17.66	17.92	17.98	17.93		0
16QAM	1	0	17.49	17.79	17.82	17.93	0-1	0
	1	25	17.67	18.09	17.96	17.93		0
	1	49	17.60	17.89	18.03	18.01		0
	25	0	17.70	17.95	17.94	17.93	0-2	0
	25	12	17.71	17.97	18.04	17.96		0
	25	25	17.71	17.92	18.03	18.06		0
	50	0	17.75	17.96	17.98	17.97		0
64QAM	1	0	17.66	18.03	18.01	18.02	0-2	0
	1	25	17.91	17.90	17.95	18.17		0
	1	49	17.88	18.19	18.08	18.13		0
	25	0	17.74	17.90	17.89	17.98	0-3	0
	25	12	17.70	17.96	18.00	18.00		0
	25	25	17.73	17.91	17.93	18.02		0
	50	0	17.76	17.94	17.97	17.96		0
256QAM	1	0	16.77	16.59	16.81	16.81	0-5	1
	1	25	16.74	16.84	16.99	16.93		1
	1	49	16.83	16.81	16.88	16.98		1
	25	0	16.72	16.89	16.88	16.96		1
	25	12	16.71	16.97	16.97	17.02		1
	25	25	16.73	16.93	16.96	17.03		1
	50	0	16.71	16.92	16.93	16.98		1

Table H-110
LTE Band 48 Ant F Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 48 5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55265 (3552.5 MHz)	55748 (3600.8 MHz)	56232 (3649.2 MHz)	56715 (3697.5 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	17.55	17.75	17.83	17.86	0	0
	1	12	17.52	17.82	17.90	17.93		0
	1	24	17.65	17.78	17.86	17.86		0
	12	0	17.68	17.87	17.90	17.93	0-1	0
	12	6	17.71	17.96	17.98	18.04		0
	12	13	17.64	17.91	17.98	17.99		0
	25	0	17.63	17.91	17.95	17.97		0
16QAM	1	0	17.71	17.74	17.94	17.87	0-1	0
	1	12	17.71	18.23	18.00	17.93		0
	1	24	17.64	18.09	17.92	17.95		0
	12	0	17.71	17.99	17.93	17.97	0-2	0
	12	6	17.76	17.99	17.98	18.08		0
	12	13	17.67	17.89	18.00	18.04		0
	25	0	17.69	17.96	18.00	18.01		0
64QAM	1	0	18.05	17.92	18.01	18.06	0-2	0
	1	12	18.15	18.00	18.02	18.05		0
	1	24	18.05	17.90	17.92	18.09		0
	12	0	17.70	17.96	17.89	17.98	0-3	0
	12	6	17.71	18.03	17.97	18.13		0
	12	13	17.72	17.96	18.07	18.11		0
	25	0	17.70	17.95	18.02	18.02		0
256QAM	1	0	16.89	17.11	16.87	16.80	0-5	1
	1	12	16.91	17.18	16.87	17.04		1
	1	24	16.86	17.24	16.77	16.97		1
	12	0	16.73	16.98	16.95	16.99		1
	12	6	16.71	17.07	16.97	17.08		1
	12	13	16.70	16.90	17.01	17.06		1
	25	0	16.70	16.91	16.96	17.07		1

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 63 of 222

H.2 NR Lower Bandwidth RF Conducted Powers

H.2.1 NR Band n71

Table H-111
NR Band n71 Ant A Measured P_{Max} for all DSI - 30 MHz Bandwidth

NR Band n71 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.46	0	0.0
	1	80	24.03		0.0
	1	158	23.96		0.0
	80	0	22.75	0-1	1.0
	80	40	24.13	0	0.0
	80	80	23.00	0-1	1.0
	160	0	23.04		1.0
DFT-s-OFDM 16QAM	1	1	23.00	0-1	1.0
CP-OFDM QPSK	1	1	22.06	0-1.5	1.5

Table H-112
NR Band n71 Ant A Measured P_{Max} for all DSI - 25 MHz Bandwidth

NR Band n71 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.87	0	0.0
	1	67	24.24		0.0
	1	131	24.21		0.0
	64	0	23.16	0-1	1.0
	64	35	24.27	0	0.0
	64	69	23.16	0-1	1.0
	128	0	23.19		1.0
DFT-s-OFDM 16QAM	1	1	22.81	0-1	1.0
CP-OFDM QPSK	1	1	22.46	0-1.5	1.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 64 of 222

Table H-113
NR Band n71 Ant A Measured P_{Max} for all DSI - 20 MHz Bandwidth

NR Band n71 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.78	0	0.0
	1	53	24.22		0.0
	1	104	24.13		0.0
	50	0	23.19	0-1	1.0
	50	28	24.00	0	0.0
	50	56	23.18	0-1	1.0
	100	0	23.29		1.0
DFT-s-OFDM 16QAM	1	1	22.67	0-1	1.0
CP-OFDM QPSK	1	1	22.36	0-1.5	1.5

Table H-114
NR Band n71 Ant A Measured P_{Max} for all DSI - 15 MHz Bandwidth

NR Band n71 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.81	0	0.0
	1	40	24.17		0.0
	1	77	24.18		0.0
	36	0	23.08	0-1	1.0
	36	22	24.30	0	0.0
	36	43	23.17	0-1	1.0
	75	0	23.24		1.0
DFT-s-OFDM 16QAM	1	1	22.69	0-1	1.0
CP-OFDM QPSK	1	1	22.37	0-1.5	1.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 65 of 222

Table H-115
NR Band n71 Ant A Measured P_{Max} for all DSI - 10 MHz Bandwidth

NR Band n71 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	133600 (668 MHz)	136100 (680.5 MHz)	138600 (693 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.80	24.10	24.03	0	0.0
	1	26	23.70	24.06	24.07		0.0
	1	50	23.57	24.03	23.72		0.0
	25	0	22.98	23.21	23.06	0-1	1.0
	25	14	23.74	24.31	24.14	0	0.0
	25	27	22.75	23.17	22.99	0-1	1.0
	50	0	22.92	23.23	23.08		1.0
DFT-s-OFDM 16QAM	1	1	22.77	22.94	22.87	0-1	1.0
CP-OFDM QPSK	1	1	22.39	22.17	22.65	0-1.5	1.5

Table H-116
NR Band n71 Ant A Measured P_{Max} for all DSI - 5 MHz Bandwidth

NR Band n71 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	133100 (665.5 MHz)	136100 (680.5 MHz)	139100 (695.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.77	24.18	24.22	0	0.0
	1	13	23.99	24.14	24.08		0.0
	1	23	23.81	24.23	23.71		0.0
	12	0	23.00	23.26	23.13	0-1	1.0
	12	7	23.98	24.24	24.14	0	0.0
	12	13	23.00	23.22	23.02	0-1	1.0
	25	0	23.16	23.25	23.12		1.0
DFT-s-OFDM 16QAM	1	1	22.78	23.08	23.04	0-1	1.0
CP-OFDM QPSK	1	1	22.43	22.67	22.71	0-1.5	1.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 66 of 222

Table H-117
NR Band n71 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n71 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.86	0	0.0
	1	80	24.27		0.0
	1	158	24.21		0.0
	80	0	23.02	0-1	1.0
	80	40	24.39	0	0.0
	80	80	23.28	0-1	1.0
	160	0	23.22		1.0
DFT-s-OFDM 16QAM	1	1	23.29	0-1	1.0
CP-OFDM QPSK	1	1	22.36	0-1.5	1.5

Table H-118
NR Band n71 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 25 MHz Bandwidth

NR Band n71 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	24.15	0	0.0
	1	67	24.35		0.0
	1	131	24.43		0.0
	64	0	23.36	0-1	1.0
	64	35	24.45	0	0.0
	64	69	23.32	0-1	1.0
	128	0	23.40		1.0
DFT-s-OFDM 16QAM	1	1	23.14	0-1	1.0
CP-OFDM QPSK	1	1	22.77	0-1.5	1.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 67 of 222

Table H-119
NR Band n71 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n71 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	24.08	0	0.0
	1	53	23.89		0.0
	1	104	23.87		0.0
	50	0	23.17	0-1	1.0
	50	28	23.99	0	0.0
	50	56	23.08	0-1	1.0
	100	0	23.20		1.0
DFT-s-OFDM 16QAM	1	1	22.95	0-1	1.0
CP-OFDM QPSK	1	1	22.72	0-1.5	1.5

Table H-120
NR Band n71 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n71 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	24.08	0	0.0
	1	40	23.89		0.0
	1	77	23.87		0.0
	36	0	23.17	0-1	1.0
	36	22	23.99	0	0.0
	36	43	23.08	0-1	1.0
	75	0	23.20		1.0
DFT-s-OFDM 16QAM	1	1	22.95	0-1	1.0
CP-OFDM QPSK	1	1	22.72	0-1.5	1.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 68 of 222

Table H-121
NR Band n71 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n71 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	133600 (668 MHz)	136100 (680.5 MHz)	138600 (693 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	24.08	24.42	24.25	0	0.0
	1	26	23.89	24.33	24.24		0.0
	1	50	23.87	24.37	24.19		0.0
	25	0	23.17	23.41	23.37	0-1	1.0
	25	14	23.99	24.39	24.40	0	0.0
	25	27	23.08	23.36	23.27	0-1	1.0
	50	0	23.20	23.41	23.40		1.0
DFT-s-OFDM 16QAM	1	1	22.95	23.18	23.01	0-1	1.0
CP-OFDM QPSK	1	1	22.72	23.02	22.98	0-1.5	1.5

Table H-122
NR Band n71 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n71 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	133100 (665.5 MHz)	136100 (680.5 MHz)	139100 (695.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	24.09	24.46	24.44	0	0.0
	1	13	24.22	24.48	24.40		0.0
	1	23	23.96	24.41	24.28		0.0
	12	0	23.31	23.40	23.36	0-1	1.0
	12	7	24.27	24.42	24.45	0	0.0
	12	13	23.29	23.42	23.37	0-1	1.0
	25	0	23.39	23.39	23.43		1.0
DFT-s-OFDM 16QAM	1	1	23.16	23.37	23.39	0-1	1.0
CP-OFDM QPSK	1	1	22.79	23.05	23.14	0-1.5	1.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 69 of 222

Table H-123
NR Band n71 Ant E Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n71 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	21.71	0	0.0
	1	80	21.86		0.0
	1	158	21.75		0.0
	80	0	21.66	0-1	0.0
	80	40	21.80	0	0.0
	80	80	21.61	0-1	0.0
	160	0	21.63		0.0
DFT-s-OFDM 16QAM	1	1	21.44	0-1	0.0
CP-OFDM QPSK	1	1	21.96	0-1.5	0.0

Table H-124
NR Band n71 Ant E Measured P_{Limit} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n71 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	21.77	0	0.0
	1	67	21.85		0.0
	1	131	21.79		0.0
	64	0	21.72	0-1	0.0
	64	35	21.79	0	0.0
	64	69	21.65	0-1	0.0
	128	0	21.64		0.0
DFT-s-OFDM 16QAM	1	1	21.50	0-1	0.0
CP-OFDM QPSK	1	1	21.90	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 70 of 222

Table H-125
NR Band n71 Ant E Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n71 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	21.59	0	0.0
	1	53	21.72		0.0
	1	104	21.75		0.0
	50	0	21.76	0-1	0.0
	50	28	21.75	0	0.0
	50	56	21.66	0-1	0.0
	100	0	21.86		0.0
DFT-s-OFDM 16QAM	1	1	21.45	0-1	0.0
CP-OFDM QPSK	1	1	21.74	0-1.5	0.0

Table H-126
NR Band n71 Ant E Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n71 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	21.66	0	0.0
	1	40	21.65		0.0
	1	77	21.52		0.0
	36	0	21.60	0-1	0.0
	36	22	21.71	0	0.0
	36	43	21.57	0-1	0.0
	75	0	21.69		0.0
DFT-s-OFDM 16QAM	1	1	21.51	0-1	0.0
CP-OFDM QPSK	1	1	21.84	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 71 of 222

Table H-127
NR Band n71 Ant E Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n71 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	133600 (668 MHz)	136100 (680.5 MHz)	138600 (693 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	21.67	21.67	21.68	0	0.0
	1	26	21.60	21.63	21.53		0.0
	1	50	21.55	21.69	21.44		0.0
	25	0	21.65	21.58	21.57	0-1	0.0
	25	14	21.70	21.70	21.69	0	0.0
	25	27	21.59	21.68	21.53	0-1	0.0
	50	0	21.69	21.63	21.64		0.0
DFT-s-OFDM 16QAM	1	1	21.45	21.51	21.47	0-1	0.0
CP-OFDM QPSK	1	1	21.75	21.65	21.70	0-1.5	0.0

Table H-128
NR Band n71 Ant E Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

NR Band n71 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	133100 (665.5 MHz)	136100 (680.5 MHz)	139100 (695.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	21.67	21.71	21.73	0	0.0
	1	13	21.70	21.84	21.69		0.0
	1	23	21.62	21.87	21.67		0.0
	12	0	21.76	21.78	21.76	0-1	0.0
	12	7	21.81	21.78	21.78	0	0.0
	12	13	21.68	21.78	21.71	0-1	0.0
	25	0	21.73	21.72	21.71		0.0
DFT-s-OFDM 16QAM	1	1	21.59	21.74	21.73	0-1	0.0
CP-OFDM QPSK	1	1	21.91	21.92	21.88	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 72 of 222

H.2.2 NR Band n12

Table H-129
NR Band n12 Ant A Measured P_{Max} for all DSI - 10 MHz Bandwidth

NR Band n12 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			141500 (707.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	24.10	0	0.0
	1	26	24.22		0.0
	1	50	24.12		0.0
	25	0	23.03	0-1	1.0
	25	14	24.08	0	0.0
	25	27	23.09	0-1	1.0
	50	0	23.11		1.0
DFT-s-OFDM 16QAM	1	1	22.93	0-1	1.0
CP-OFDM QPSK	1	1	22.74	0-1.5	1.5

Table H-130
NR Band n12 Ant A Measured P_{Max} for all DSI - 5 MHz Bandwidth

NR Band n12 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	140300 (701.5 MHz)	141500 (707.5 MHz)	142700 (713.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.98	24.08	24.03	0	0.0
	1	13	24.15	24.17	24.17		0.0
	1	23	24.08	24.13	24.07		0.0
	12	0	23.02	23.09	22.99	0-1	1.0
	12	7	23.98	24.16	24.11	0	0.0
	12	13	22.93	23.08	23.03	0-1	1.0
	25	0	23.02	23.12	23.12		1.0
DFT-s-OFDM 16QAM	1	1	22.88	22.92	22.97	0-1	1.0
CP-OFDM OPSK	1	1	22.73	22.80	22.56	0-1.5	1.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 73 of 222

Table H-131
NR Band n12 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n12 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			141500 (707.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	24.35	0	0.0
	1	26	24.26		0.0
	1	50	24.21		0.0
	25	0	23.33	0-1	1.0
	25	14	24.38	0	0.0
	25	27	23.29	0-1	1.0
	50	0	23.31		1.0
DFT-s-OFDM 16QAM	1	1	23.13	0-1	1.0
CP-OFDM QPSK	1	1	22.81	0-1.5	1.5

Table H-132
NR Band n12 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n12 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	140300 (701.5 MHz)	141500 (707.5 MHz)	142700 (713.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	24.27	24.27	24.25	0	0.0
	1	13	24.32	24.26	24.35		0.0
	1	23	24.22	24.19	24.16		0.0
	12	0	23.27	23.33	23.31	0-1	1.0
	12	7	24.30	24.32	24.35	0	0.0
	12	13	23.23	23.28	23.24	0-1	1.0
	25	0	23.22	23.28	23.28		1.0
DFT-s-OFDM 16QAM	1	1	23.13	23.21	23.16	0-1	1.0
CP-OFDM QPSK	1	1	22.83	22.92	23.00	0-1.5	1.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 74 of 222

Table H-133
NR Band n12 Ant E Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n12 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			141500 (707.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	21.71	0	0.0
	1	26	21.59		0.0
	1	50	21.56		0.0
	25	0	21.58	0-1	0.0
	25	14	21.54	0	0.0
	25	27	21.49	0-1	0.0
	50	0	21.54		0.0
DFT-s-OFDM 16QAM	1	1	21.38	0-1	0.0
CP-OFDM QPSK	1	1	21.74	0-1.5	0.0

Table H-134
NR Band n12 Ant E Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

NR Band n12 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	140300 (701.5 MHz)	141500 (707.5 MHz)	142700 (713.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	21.44	21.58	21.54	0	0.0
	1	13	21.61	21.59	21.57		0.0
	1	23	21.41	21.50	21.47		0.0
	12	0	21.50	21.57	21.52	0-1	0.0
	12	7	21.52	21.50	21.64	0	0.0
	12	13	21.76	21.44	21.47	0-1	0.0
	25	0	21.49	21.56	21.48		0.0
DFT-s-OFDM 16QAM	1	1	21.44	21.61	21.50	0-1	0.0
CP-OFDM QPSK	1	1	21.67	21.80	21.67	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 75 of 222

H.2.3 NR Band n14

Table H-135
NR Band n14 Ant A Measured P_{Max} for all DSI - 5 MHz Bandwidth

NR Band n14 5 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	158100 (790.5 MHz)	159100 (795.5 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	23.85	23.89	0	0.0
	1	13	24.09	23.67		0.0
	1	23	23.94	23.77		0.0
	12	0	22.98	22.78	0-1	1.0
	12	7	24.05	23.61	0	0.0
	12	13	22.97	22.59	0-1	1.0
	25	0	23.00	22.69		1.0
DFT-s-OFDM 16QAM	1	1	22.94	22.91	0-1	1.0
CP-OFDM QPSK	1	1	22.63	22.53	0-1.5	1.5

Table H-136
NR Band n14 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n14 5 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	158100 (790.5 MHz)	159100 (795.5 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	24.08	24.00	0	0.0
	1	13	24.15	24.10		0.0
	1	23	24.15	24.32		0.0
	12	0	23.07	23.00	0-1	1.0
	12	7	24.12	23.91	0	0.0
	12	13	23.18	22.91	0-1	1.0
	25	0	23.09	22.92		1.0
DFT-s-OFDM 16QAM	1	1	23.05	22.99	0-1	1.0
CP-OFDM OPSK	1	1	22.69	22.61	0-1.5	1.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 76 of 222

Table H-137
NR Band n14 Ant E Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

NR Band n14 5 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	158100 (790.5 MHz)	159100 (795.5 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	21.42	21.47	0	0.0
	1	13	21.47	21.62		0.0
	1	23	21.50	21.50		0.0
	12	0	21.42	21.53	0-1	0.0
	12	7	21.43	21.66	0	0.0
	12	13	21.42	21.53	0-1	0.0
	25	0	21.31	21.53		0.0
DFT-s-OFDM 16QAM	1	1	21.39	21.55	0-1	0.0
CP-OFDM QPSK	1	1	21.44	21.68	0-1.5	0.0

H.2.4 NR Band n26

Table H-138
NR Band n26 Ant A Measured P_{Max} for all DSI - 15 MHz Bandwidth

NR Band n26 15 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	164300 (821.5 MHz)	168300 (841.5 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	24.16	24.20	0	0.0
	1	40	24.16	24.11		0.0
	1	77	24.11	24.06		0.0
	36	0	23.17	23.10	0-1	1.0
	36	22	24.19	24.14	0	0.0
	36	43	23.09	23.03	0-1	1.0
	75	0	23.09	23.09		1.0
DFT-s-OFDM 16QAM	1	1	22.95	22.97	0-1	1.0
CP-OFDM QPSK	1	1	22.73	22.80	0-1.5	1.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 77 of 222

Table H-139
NR Band n26 Ant A Measured P_{Max} for all DSI - 10 MHz Bandwidth

NR Band n26 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	163800 (819 MHz)	166300 (831.5 MHz)	168800 (844 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	24.21	24.10	24.06	0	0.0
	1	26	24.22	24.10	23.99		0.0
	1	50	24.25	24.22	23.94		0.0
	25	0	23.14	23.11	23.06	0-1	1.0
	25	14	24.26	24.05	24.11	0	0.0
	25	27	22.93	23.18	23.00	0-1	1.0
	50	0	23.14	23.06	23.05		1.0
DFT-s-OFDM 16QAM	1	1	23.06	22.89	22.95	0-1	1.0
CP-OFDM QPSK	1	1	22.71	22.76	22.60	0-1.5	1.5

Table H-140
NR Band n26 Ant A Measured P_{Max} for all DSI - 5 MHz Bandwidth

NR Band n26 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	163300 (816.5 MHz)	166300 (831.5 MHz)	169300 (846.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	24.22	24.07	24.18	0	0.0
	1	13	24.33	24.25	24.28		0.0
	1	23	24.21	24.15	24.19		0.0
	12	0	23.19	23.08	23.08	0-1	1.0
	12	7	24.27	24.08	24.22	0	0.0
	12	13	23.23	23.11	23.17	0-1	1.0
	25	0	23.23	23.03	23.08		1.0
DFT-s-OFDM 16QAM	1	1	23.13	22.87	22.93	0-1	1.0
CP-OFDM QPSK	1	1	22.91	22.66	22.77	0-1.5	1.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 78 of 222

Table H-141
NR Band n26 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n26 15 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	164300 (821.5 MHz)	168300 (841.5 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	24.17	24.30	0	0.0
	1	40	24.25	24.19		0.0
	1	77	24.24	24.32		0.0
	36	0	23.15	23.24	0-1	1.0
	36	22	24.30	24.39	0	0.0
	36	43	23.19	23.16	0-1	1.0
	75	0	23.26	23.22		1.0
DFT-s-OFDM 16QAM	1	1	23.05	23.03	0-1	1.0
CP-OFDM QPSK	1	1	22.73	22.99	0-1.5	1.5

Table H-142
NR Band n26 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n26 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	163800 (819 MHz)	166300 (831.5 MHz)	168800 (844 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	24.26	24.23	24.29	0	0.0
	1	26	24.30	24.25	24.30		0.0
	1	50	24.48	24.28	24.42		0.0
	25	0	23.27	23.16	23.13	0-1	1.0
	25	14	24.29	24.33	24.30	0	0.0
	25	27	23.21	23.26	23.25	0-1	1.0
	50	0	23.25	23.27	23.22		1.0
DFT-s-OFDM 16QAM	1	1	23.15	23.00	23.11	0-1	1.0
CP-OFDM QPSK	1	1	22.71	22.74	22.79	0-1.5	1.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 79 of 222

Table H-143
NR Band n26 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n26 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	163300 (816.5 MHz)	166300 (831.5 MHz)	169300 (846.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	24.29	24.25	24.25	0	0.0
	1	13	24.38	24.33	24.37		0.0
	1	23	24.44	24.21	24.39		0.0
	12	0	23.17	23.18	23.23	0-1	1.0
	12	7	24.32	24.22	24.27	0	0.0
	12	13	23.24	23.17	23.25	0-1	1.0
	25	0	23.38	23.22	23.27		1.0
DFT-s-OFDM 16QAM	1	1	23.18	23.00	23.13	0-1	1.0
CP-OFDM QPSK	1	1	22.79	22.82	22.93	0-1.5	1.5

Table H-144
NR Band n26 Ant E Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n26 15 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	164300 (821.5 MHz)	168300 (841.5 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	21.05	21.15	0	0.0
	1	40	21.07	21.12		0.0
	1	77	21.12	21.07		0.0
	36	0	20.98	20.99	0-1	0.0
	36	22	21.23	21.11	0	0.0
	36	43	21.02	20.97	0-1	0.0
	75	0	21.02	21.01		0.0
DFT-s-OFDM 16QAM	1	1	21.06	20.99	0-1	0.0
CP-OFDM QPSK	1	1	21.14	21.20	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 80 of 222

Table H-145
NR Band n26 Ant E Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n26 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	163800 (819 MHz)	166300 (831.5 MHz)	168800 (844 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	21.11	21.09	21.17	0	0.0
	1	26	21.16	21.08	21.09		0.0
	1	50	21.16	21.09	21.08		0.0
	25	0	21.03	21.05	21.00	0-1	0.0
	25	14	21.21	21.22	21.20	0	0.0
	25	27	21.09	21.09	21.10	0-1	0.0
	50	0	21.06	21.12	21.04		0.0
DFT-s-OFDM 16QAM	1	1	21.12	20.97	20.89	0-1	0.0
CP-OFDM QPSK	1	1	21.32	21.16	21.06	0-1.5	0.0

Table H-146
NR Band n26 Ant E Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

NR Band n26 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	163300 (816.5 MHz)	166300 (831.5 MHz)	169300 (846.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	21.14	21.06	21.13	0	0.0
	1	13	21.16	21.25	21.23		0.0
	1	23	21.13	21.06	21.12		0.0
	12	0	21.18	21.09	21.12	0-1	0.0
	12	7	21.22	21.20	21.22	0	0.0
	12	13	21.05	21.08	21.11	0-1	0.0
	25	0	21.08	21.07	21.19		0.0
DFT-s-OFDM 16QAM	1	1	21.18	21.02	21.17	0-1	0.0
CP-OFDM QPSK	1	1	21.35	21.22	21.23	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 81 of 222

H.2.5 NR Band n70

Table H-147

NR Band n70 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n70 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			340500 (1702.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.99	0	0.0
	1	26	19.11		0.0
	1	50	19.07		0.0
	25	0	19.14	0-1	0.0
	25	14	19.05	0	0.0
	25	27	19.10	0-1	0.0
	50	0	19.09		0.0
DFT-s-OFDM 16QAM	1	1	19.08	0-1	0.0
CP-OFDM QPSK	1	1	19.28	0-1.5	0.0

Table H-148

NR Band n70 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n70 5 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	339500 (1697.5 MHz)	341500 (1707.5 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	19.42	19.17	0	0.0
	1	13	19.17	19.05		0.0
	1	23	19.24	19.15		0.0
	12	0	19.08	19.01	0-1	0.0
	12	7	19.14	19.05	0	0.0
	12	13	19.16	18.97	0-1	0.0
	25	0	19.18	19.02		0.0
DFT-s-OFDM 16QAM	1	1	19.20	18.98	0-1	0.0
CP-OFDM QPSK	1	1	19.41	19.22	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 82 of 222

Table H-149
NR Band n70 Ant A Measured P_{Max} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n70 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			340500 (1702.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.27	0	0.0
	1	26	23.42		0.0
	1	50	23.35		0.0
	25	0	22.42	0-1	1.0
	25	14	23.35	0	0.0
	25	27	22.47	0-1	1.0
	50	0	22.37		1.0
DFT-s-OFDM 16QAM	1	1	22.32	0-1	1.0
CP-OFDM QPSK	1	1	22.05	0-1.5	1.5

Table H-150
NR Band n70 Ant A Measured P_{Max} for DSI = 1 (Head) - 5 MHz Bandwidth

NR Band n70 5 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	339500 (1697.5 MHz)	341500 (1707.5 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	23.42	23.73	0	0.0
	1	13	23.70	23.72		0.0
	1	23	23.76	23.71		0.0
	12	0	22.49	22.84	0-1	1.0
	12	7	23.62	23.82	0	0.0
	12	13	22.68	22.84	0-1	1.0
	25	0	22.75	22.86		1.0
DFT-s-OFDM 16QAM	1	1	22.63	22.79	0-1	1.0
CP-OFDM OPSK	1	1	22.05	22.22	0-1.5	1.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 83 of 222

Table H-151
NR Band n70 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n70 10 MHz Bandwidth					
			Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	340500 (1702.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	20.88	0	0.0
	1	26	21.11		0.0
	1	50	21.28		0.0
	25	0	20.91	0-1	0.0
	25	14	21.13	0	0.0
	25	27	21.10	0-1	0.0
	50	0	21.01		0.0
DFT-s-OFDM 16QAM	1	1	20.67	0-1	0.0
CP-OFDM QPSK	1	1	21.06	0-1.5	0.0

Table H-152
NR Band n70 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n70 5 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	339500 (1697.5 MHz)	341500 (1707.5 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	20.91	21.21	0	0.0
	1	13	21.07	21.36		0.0
	1	23	20.91	21.37		0.0
	12	0	20.80	21.13	0-1	0.0
	12	7	20.96	21.31	0	0.0
	12	13	20.93	21.24	0-1	0.0
	25	0	20.86	21.27		0.0
DFT-s-OFDM 16QAM	1	1	20.85	21.02	0-1	0.0
CP-OFDM QPSK	1	1	21.07	21.44	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 84 of 222

Table H-153
NR Band n70 Ant F Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n70 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			340500 (1702.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.18	0	0.0
	1	26	18.23		0.0
	1	50	18.56		0.0
	25	0	18.16	0-1	0.0
	25	14	18.44	0	0.0
	25	27	18.31	0-1	0.0
	50	0	18.32		0.0
DFT-s-OFDM 16QAM	1	1	18.04	0-1	0.0
CP-OFDM QPSK	1	1	18.21	0-1.5	0.0

Table H-154
NR Band n70 Ant F Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

NR Band n70 5 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	339500 (1697.5 MHz)	341500 (1707.5 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.14	18.39	0	0.0
	1	13	18.28	18.73		0.0
	1	23	18.36	18.66		0.0
	12	0	18.12	18.47	0-1	0.0
	12	7	18.18	18.60	0	0.0
	12	13	18.30	18.56	0-1	0.0
	25	0	18.12	18.51		0.0
DFT-s-OFDM 16QAM	1	1	18.15	18.35	0-1	0.0
CP-OFDM QPSK	1	1	18.33	18.63	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 85 of 222

H.2.6 NR Band n66

Table H-155

NR Band n66 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 40 MHz Bandwidth

NR Band n66 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.74	0	0.0
	1	108	18.87		0.0
	1	214	18.89		0.0
	108	0	18.73	0-1	0.0
	108	54	18.91	0	0.0
	108	108	18.77	0-1	0.0
	216	0	18.81		0.0
DFT-s-OFDM 16QAM	1	1	18.67	0-1	0.0
CP-OFDM QPSK	1	1	18.84	0-1.5	0.0

Table H-156

NR Band n66 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 35 MHz Bandwidth

NR Band n66 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.82	0	0.0
	1	94	18.75		0.0
	1	186	18.71		0.0
	90	0	18.76	0-1	0.0
	90	49	18.64	0	0.0
	90	98	18.74	0-1	0.0
	180	0	18.69		0.0
DFT-s-OFDM 16QAM	1	1	18.64	0-1	0.0
CP-OFDM QPSK	1	1	18.94	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 86 of 222

Table H-157
NR Band n66 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n66 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.79	0	0.0
	1	80	18.76		0.0
	1	158	18.93		0.0
	80	0	18.83	0-1	0.0
	80	40	18.85	0	0.0
	80	80	18.82	0-1	0.0
	160	0	18.82		0.0
DFT-s-OFDM 16QAM	1	1	18.72	0-1	0.0
CP-OFDM QPSK	1	1	18.90	0-1.5	0.0

Table H-158
NR Band n66 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 25 MHz Bandwidth

NR Band n66 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.82	0	0.0
	1	67	18.86		0.0
	1	131	18.85		0.0
	64	0	18.82	0-1	0.0
	64	35	18.82	0	0.0
	64	69	18.84	0-1	0.0
	128	0	18.82		0.0
DFT-s-OFDM 16QAM	1	1	18.67	0-1	0.0
CP-OFDM QPSK	1	1	18.87	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 87 of 222

Table H-159

NR Band n66 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n66 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	344000 (1720 MHz)	349000 (1745 MHz)	354000 (1770 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.61	18.62	18.69	0	0.0
	1	53	18.59	18.68	18.67		0.0
	1	104	18.61	18.79	18.74		0.0
	50	0	18.68	18.75	18.75	0-1	0.0
	50	28	18.62	18.73	18.69	0	0.0
	50	56	18.69	18.74	18.80	0-1	0.0
	100	0	18.66	18.75	18.71		0.0
DFT-s-OFDM 16QAM	1	1	18.55	18.51	18.49	0-1	0.0
CP-OFDM QPSK	1	1	18.81	18.75	18.84	0-1.5	0.0

Table H-160

NR Band n66 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n66 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343500 (1717.5 MHz)	349000 (1745 MHz)	354500 (1772.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.79	18.68	18.79	0	0.0
	1	40	18.62	18.73	18.69		0.0
	1	77	18.70	18.80	18.75		0.0
	36	0	18.71	18.78	18.77	0-1	0.0
	36	22	18.68	18.76	18.72	0	0.0
	36	43	18.64	18.76	18.80	0-1	0.0
	75	0	18.69	18.72	18.70		0.0
DFT-s-OFDM 16QAM	1	1	18.71	18.61	18.55	0-1	0.0
CP-OFDM QPSK	1	1	18.93	18.95	18.92	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 88 of 222

Table H-161

NR Band n66 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n66 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343000 (1715 MHz)	349000 (1745 MHz)	355000 (1775 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.78	18.78	18.78	0	0.0
	1	26	18.83	18.84	18.91		0.0
	1	50	18.64	18.84	18.85		0.0
	25	0	18.79	18.82	18.82	0-1	0.0
	25	14	18.79	18.76	18.82	0	0.0
	25	27	18.78	18.78	18.94	0-1	0.0
	50	0	18.78	18.78	18.84		0.0
DFT-s-OFDM 16QAM	1	1	18.72	18.60	18.64	0-1	0.0
CP-OFDM QPSK	1	1	18.95	18.90	18.88	0-1.5	0.0

Table H-162

NR Band n66 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n66 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	342500 (1712.5 MHz)	349000 (1745 MHz)	355500 (1777.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.75	18.85	18.84	0	0.0
	1	13	18.73	18.81	18.86		0.0
	1	23	18.70	18.77	18.83		0.0
	12	0	18.66	18.73	18.78	0-1	0.0
	12	7	18.70	18.76	18.82	0	0.0
	12	13	18.66	18.73	18.74	0-1	0.0
	25	0	18.74	18.78	18.87		0.0
DFT-s-OFDM 16QAM	1	1	18.60	18.68	18.82	0-1	0.0
CP-OFDM QPSK	1	1	18.88	18.95	18.93	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 89 of 222

Table H-163
NR Band n66 Ant A Measured P_{Max} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n66 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.28	0	0.0
	1	108	23.34		0.0
	1	214	23.33		0.0
	108	0	22.27	0-1	1.0
	108	54	23.34	0	0.0
	108	108	22.42	0-1	1.0
	216	0	22.27		1.0
DFT-s-OFDM 16QAM	1	1	22.23	0-1	1.0
CP-OFDM QPSK	1	1	21.89	0-1.5	1.5

Table H-164
NR Band n66 Ant A Measured P_{Max} for DSI = 1 (Head) - 35 MHz Bandwidth

NR Band n66 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.46	0	0.0
	1	94	23.38		0.0
	1	186	23.48		0.0
	90	0	22.49	0-1	1.0
	90	49	23.39	0	0.0
	90	98	22.44	0-1	1.0
	180	0	22.39		1.0
DFT-s-OFDM 16QAM	1	1	22.50	0-1	1.0
CP-OFDM QPSK	1	1	21.95	0-1.5	1.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 90 of 222

Table H-165
NR Band n66 Ant A Measured P_{Max} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n66 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.53	0	0.0
	1	80	23.45		0.0
	1	158	23.48		0.0
	80	0	22.39	0-1	1.0
	80	40	23.49	0	0.0
	80	80	22.45	0-1	1.0
	160	0	22.45		1.0
DFT-s-OFDM 16QAM	1	1	22.49	0-1	1.0
CP-OFDM QPSK	1	1	21.94	0-1.5	1.5

Table H-166
NR Band n66 Ant A Measured P_{Max} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n66 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.45	0	0.0
	1	67	23.55		0.0
	1	131	23.48		0.0
	64	0	22.43	0-1	1.0
	64	35	23.45	0	0.0
	64	69	22.47	0-1	1.0
	128	0	22.37		1.0
DFT-s-OFDM 16QAM	1	1	22.51	0-1	1.0
CP-OFDM QPSK	1	1	22.08	0-1.5	1.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 91 of 222

Table H-167
NR Band n66 Ant A Measured P_{Max} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n66 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	344000 (1720 MHz)	349000 (1745 MHz)	354000 (1770 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.28	23.31	23.26	0	0.0
	1	53	23.04	23.29	23.33		0.0
	1	104	23.37	23.33	23.28		0.0
	50	0	22.32	22.34	22.31	0-1	1.0
	50	28	23.26	23.37	23.28	0	0.0
	50	56	22.24	22.36	22.27	0-1	1.0
	100	0	22.23	22.40	22.27		1.0
DFT-s-OFDM 16QAM	1	1	22.29	22.15	22.23	0-1	1.0
CP-OFDM QPSK	1	1	21.78	21.95	21.80	0-1.5	1.5

Table H-168
NR Band n66 Ant A Measured P_{Max} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n66 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343500 (1717.5 MHz)	349000 (1745 MHz)	354500 (1772.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.34	23.45	23.34	0	0.0
	1	40	22.79	23.34	23.22		0.0
	1	77	23.38	23.41	23.18		0.0
	36	0	22.35	22.36	22.35	0-1	1.0
	36	22	23.28	23.40	23.33	0	0.0
	36	43	22.25	22.39	22.34	0-1	1.0
	75	0	22.40	22.34	22.20		1.0
DFT-s-OFDM 16QAM	1	1	22.29	22.28	22.21	0-1	1.0
CP-OFDM QPSK	1	1	21.76	21.92	21.98	0-1.5	1.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 92 of 222

Table H-169
NR Band n66 Ant A Measured P_{Max} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n66 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343000 (1715 MHz)	349000 (1745 MHz)	355000 (1775 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.29	23.35	23.41	0	0.0
	1	26	22.90	23.37	23.41		0.0
	1	50	22.99	23.30	23.04		0.0
	25	0	22.38	22.32	22.36	0-1	1.0
	25	14	23.38	23.31	23.29	0	0.0
	25	27	22.40	22.43	22.42	0-1	1.0
	50	0	22.49	22.39	22.41		1.0
DFT-s-OFDM 16QAM	1	1	22.21	22.31	22.38	0-1	1.0
CP-OFDM QPSK	1	1	21.70	21.97	21.98	0-1.5	1.5

Table H-170
NR Band n66 Ant A Measured P_{Max} for DSI = 1 (Head) - 5 MHz Bandwidth

NR Band n66 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	342500 (1712.5 MHz)	349000 (1745 MHz)	355500 (1777.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.33	23.34	23.33	0	0.0
	1	13	22.97	23.37	23.09		0.0
	1	23	22.94	23.41	22.87		0.0
	12	0	22.21	22.35	22.26	0-1	1.0
	12	7	23.26	23.31	23.31	0	0.0
	12	13	22.30	22.30	22.33	0-1	1.0
	25	0	22.32	22.32	22.42		1.0
DFT-s-OFDM 16QAM	1	1	22.21	22.30	22.28	0-1	1.0
CP-OFDM QPSK	1	1	21.92	21.92	22.00	0-1.5	1.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 93 of 222

Table H-171
NR Band n66 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 40 MHz Bandwidth

NR Band n66 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	21.06	0	0.0
	1	108	20.82		0.0
	1	214	20.74		0.0
	108	0	20.87	0-1	0.0
	108	54	20.91	0	0.0
	108	108	20.73	0-1	0.0
	216	0	20.87		0.0
DFT-s-OFDM 16QAM	1	1	20.91	0-1	0.0
CP-OFDM QPSK	1	1	21.18	0-1.5	0.0

Table H-172
NR Band n66 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 35 MHz Bandwidth

NR Band n66 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.79	0	0.0
	1	94	19.75		0.0
	1	186	19.64		0.0
	90	0	19.68	0-1	0.0
	90	49	19.80	0	0.0
	90	98	19.63	0-1	0.0
	180	0	19.61		0.0
DFT-s-OFDM 16QAM	1	1	19.69	0-1	0.0
CP-OFDM QPSK	1	1	20.03	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 94 of 222

Table H-173
NR Band n66 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n66 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.89	0	0.0
	1	80	19.84		0.0
	1	158	19.82		0.0
	80	0	19.73	0-1	0.0
	80	40	19.83	0	0.0
	80	80	19.64	0-1	0.0
	160	0	19.79		0.0
DFT-s-OFDM 16QAM	1	1	19.74	0-1	0.0
CP-OFDM QPSK	1	1	19.87	0-1.5	0.0

Table H-174
NR Band n66 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 25 MHz Bandwidth

NR Band n66 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.92	0	0.0
	1	67	19.92		0.0
	1	131	19.85		0.0
	64	0	19.78	0-1	0.0
	64	35	19.84	0	0.0
	64	69	19.66	0-1	0.0
	128	0	19.70		0.0
DFT-s-OFDM 16QAM	1	1	19.77	0-1	0.0
CP-OFDM QPSK	1	1	19.94	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 95 of 222

Table H-175

NR Band n66 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n66 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	344000 (1720 MHz)	349000 (1745 MHz)	354000 (1770 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.05	19.75	19.66	0	0.0
	1	53	20.09	19.82	19.72		0.0
	1	104	20.13	19.75	19.52		0.0
	50	0	19.95	19.67	19.65	0-1	0.0
	50	28	20.04	19.76	19.70	0	0.0
	50	56	19.94	19.66	19.50	0-1	0.0
	100	0	20.07	19.81	19.64		0.0
DFT-s-OFDM 16QAM	1	1	19.83	19.68	19.49	0-1	0.0
CP-OFDM QPSK	1	1	19.91	19.81	19.70	0-1.5	0.0

Table H-176

NR Band n66 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n66 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343500 (1717.5 MHz)	349000 (1745 MHz)	354500 (1772.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.39	20.24	20.04	0	0.0
	1	40	20.09	20.06	20.01		0.0
	1	77	20.13	20.02	20.02		0.0
	36	0	20.00	20.04	19.91	0-1	0.0
	36	22	20.16	20.18	20.00	0	0.0
	36	43	19.98	19.99	19.92	0-1	0.0
	75	0	20.03	20.03	19.88		0.0
DFT-s-OFDM 16QAM	1	1	20.00	20.02	20.06	0-1	0.0
CP-OFDM QPSK	1	1	20.29	20.36	20.06	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 96 of 222

Table H-177

NR Band n66 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n66 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343000 (1715 MHz)	349000 (1745 MHz)	355000 (1775 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.26	20.11	20.24	0	0.0
	1	26	20.28	20.15	20.01		0.0
	1	50	20.23	20.10	19.97		0.0
	25	0	20.12	20.19	20.08	0-1	0.0
	25	14	20.25	20.23	20.02	0	0.0
	25	27	20.19	20.11	20.02	0-1	0.0
	50	0	20.12	20.09	19.97		0.0
DFT-s-OFDM 16QAM	1	1	20.07	20.03	19.97	0-1	0.0
CP-OFDM QPSK	1	1	20.26	20.23	20.23	0-1.5	0.0

Table H-178

NR Band n66 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n66 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	342500 (1712.5 MHz)	349000 (1745 MHz)	355500 (1777.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.15	20.24	20.01	0	0.0
	1	13	20.30	20.37	20.13		0.0
	1	23	20.12	20.26	20.04		0.0
	12	0	20.13	20.17	20.06	0-1	0.0
	12	7	20.20	20.33	20.18	0	0.0
	12	13	20.09	20.19	20.00	0-1	0.0
	25	0	20.15	20.22	20.04		0.0
DFT-s-OFDM 16QAM	1	1	20.07	20.17	20.03	0-1	0.0
CP-OFDM QPSK	1	1	20.20	20.48	20.23	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 97 of 222

Table H-179
NR Band n66 Ant F Measured P_{Limit} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n66 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.51	0	0.0
	1	108	18.36		0.0
	1	214	18.20		0.0
	108	0	18.39	0-1	0.0
	108	54	18.40	0	0.0
	108	108	18.17	0-1	0.0
	216	0	18.38		0.0
DFT-s-OFDM 16QAM	1	1	18.36	0-1	0.0
CP-OFDM QPSK	1	1	18.53	0-1.5	0.0

Table H-180
NR Band n66 Ant F Measured P_{Limit} for DSI = 1 (Head) - 35 MHz Bandwidth

NR Band n66 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.76	0	0.0
	1	94	18.67		0.0
	1	186	18.55		0.0
	90	0	18.72	0-1	0.0
	90	49	18.77	0	0.0
	90	98	18.57	0-1	0.0
	180	0	18.55		0.0
DFT-s-OFDM 16QAM	1	1	18.76	0-1	0.0
CP-OFDM QPSK	1	1	18.85	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 98 of 222

Table H-181
NR Band n66 Ant F Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n66 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.78	0	0.0
	1	80	18.80		0.0
	1	158	18.76		0.0
	80	0	18.75	0-1	0.0
	80	40	18.70	0	0.0
	80	80	18.54	0-1	0.0
	160	0	18.68		0.0
DFT-s-OFDM 16QAM	1	1	18.76	0-1	0.0
CP-OFDM QPSK	1	1	18.94	0-1.5	0.0

Table H-182
NR Band n66 Ant F Measured P_{Limit} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n66 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.92	0	0.0
	1	67	18.81		0.0
	1	131	18.66		0.0
	64	0	18.76	0-1	0.0
	64	35	18.68	0	0.0
	64	69	18.59	0-1	0.0
	128	0	18.60		0.0
DFT-s-OFDM 16QAM	1	1	18.84	0-1	0.0
CP-OFDM QPSK	1	1	19.03	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 99 of 222

Table H-183
NR Band n66 Ant F Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n66 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	344000 (1720 MHz)	349000 (1745 MHz)	354000 (1770 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.59	18.86	18.52	0	0.0
	1	53	18.57	18.72	18.50		0.0
	1	104	18.63	18.66	18.50		0.0
	50	0	18.60	18.62	18.44	0-1	0.0
	50	28	18.71	18.74	18.54	0	0.0
	50	56	18.53	18.56	18.41	0-1	0.0
	100	0	18.59	18.66	18.49		0.0
DFT-s-OFDM 16QAM	1	1	18.57	18.59	18.40	0-1	0.0
CP-OFDM QPSK	1	1	18.72	19.01	18.65	0-1.5	0.0

Table H-184
NR Band n66 Ant F Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n66 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343500 (1717.5 MHz)	349000 (1745 MHz)	354500 (1772.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.96	18.77	18.49	0	0.0
	1	40	18.70	18.68	18.53		0.0
	1	77	18.73	18.49	18.60		0.0
	36	0	18.61	18.58	18.47	0-1	0.0
	36	22	18.71	18.75	18.45	0	0.0
	36	43	18.50	18.59	18.41	0-1	0.0
	75	0	18.66	18.63	18.52		0.0
DFT-s-OFDM 16QAM	1	1	18.65	18.66	18.56	0-1	0.0
CP-OFDM QPSK	1	1	18.93	18.94	18.79	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 100 of 222

Table H-185
NR Band n66 Ant F Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n66 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343000 (1715 MHz)	349000 (1745 MHz)	355000 (1775 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.72	18.70	18.52	0	0.0
	1	26	18.65	18.71	18.57		0.0
	1	50	18.59	18.56	18.42		0.0
	25	0	18.55	18.69	18.49	0-1	0.0
	25	14	18.69	18.74	18.59	0	0.0
	25	27	18.60	18.75	18.47	0-1	0.0
	50	0	18.64	18.64	18.51		0.0
DFT-s-OFDM 16QAM	1	1	18.59	18.59	18.48	0-1	0.0
CP-OFDM QPSK	1	1	18.83	18.87	18.73	0-1.5	0.0

Table H-186
NR Band n66 Ant F Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

NR Band n66 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	342500 (1712.5 MHz)	349000 (1745 MHz)	355500 (1777.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.64	18.50	18.67	0	0.0
	1	13	18.68	18.73	18.62		0.0
	1	23	18.63	18.53	18.38		0.0
	12	0	18.63	18.63	18.45	0-1	0.0
	12	7	18.69	18.71	18.59	0	0.0
	12	13	18.64	18.63	18.44	0-1	0.0
	25	0	18.60	18.62	18.47		0.0
DFT-s-OFDM 16QAM	1	1	18.50	18.56	18.37	0-1	0.0
CP-OFDM QPSK	1	1	18.69	18.79	18.64	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 101 of 222

H.2.7 NR Band n25

Table H-187

NR Band n25 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 35 MHz Bandwidth

NR Band n25 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.67	0	0.0
	1	94	17.85		0.0
	1	186	17.77		0.0
	90	0	17.88	0-1	0.0
	90	49	17.87	0	0.0
	90	98	17.87	0-1	0.0
	180	0	17.75		0.0
DFT-s-OFDM 16QAM	1	1	17.64	0-1	0.0
CP-OFDM QPSK	1	1	17.97	0-1.5	0.0

Table H-188

NR Band n25 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n25 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.77	0	0.0
	1	80	17.86		0.0
	1	158	17.69		0.0
	80	0	17.83	0-1	0.0
	80	40	17.87	0	0.0
	80	80	17.75	0-1	0.0
	160	0	17.78		0.0
DFT-s-OFDM 16QAM	1	1	17.69	0-1	0.0
CP-OFDM QPSK	1	1	17.94	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 102 of 222

Table H-189
NR Band n25 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 25 MHz Bandwidth

NR Band n25 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.89	0	0.0
	1	67	17.83		0.0
	1	131	17.68		0.0
	64	0	17.82	0-1	0.0
	64	35	17.81	0	0.0
	64	69	17.74	0-1	0.0
	128	0	17.68		0.0
DFT-s-OFDM 16QAM	1	1	17.65	0-1	0.0
CP-OFDM QPSK	1	1	17.94	0-1.5	0.0

Table H-190
NR Band n25 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n25 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	372000 (1860 MHz)	376500 (1882.5 MHz)	381000 (1905 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.88	17.68	17.63	0	0.0
	1	53	17.80	17.61	17.58		0.0
	1	104	17.73	17.61	17.67		0.0
	50	0	17.85	17.77	17.66	0-1	0.0
	50	28	17.82	17.74	17.68	0	0.0
	50	56	17.87	17.67	17.59	0-1	0.0
	100	0	17.80	17.71	17.64		0.0
DFT-s-OFDM 16QAM	1	1	17.79	17.51	17.52	0-1	0.0
CP-OFDM QPSK	1	1	17.82	17.78	17.80	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 103 of 222

Table H-191

NR Band n25 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n25 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371500 (1857.5 MHz)	376500 (1882.5 MHz)	381500 (1907.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.91	17.78	17.70	0	0.0
	1	40	17.83	17.70	17.61		0.0
	1	77	17.81	17.63	17.59		0.0
	36	0	17.94	17.82	17.71	0-1	0.0
	36	22	17.73	17.73	17.64	0	0.0
	36	43	17.88	17.71	17.64	0-1	0.0
	75	0	17.86	17.72	17.61		0.0
DFT-s-OFDM 16QAM	1	1	17.77	17.65	17.53	0-1	0.0
CP-OFDM QPSK	1	1	17.99	17.85	17.78	0-1.5	0.0

Table H-192

NR Band n25 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n25 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371000 (1855 MHz)	376500 (1882.5 MHz)	382000 (1910 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.94	17.75	17.61	0	0.0
	1	26	17.97	17.79	17.65		0.0
	1	50	17.90	17.73	17.61		0.0
	25	0	17.99	17.80	17.67	0-1	0.0
	25	14	17.89	17.75	17.53	0	0.0
	25	27	17.95	17.74	17.62	0-1	0.0
	50	0	17.97	17.76	17.63		0.0
DFT-s-OFDM 16QAM	1	1	17.89	17.63	17.51	0-1	0.0
CP-OFDM QPSK	1	1	17.97	17.86	17.72	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 104 of 222

Table H-193
NR Band n25 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n25 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	370500 (1852.5 MHz)	376500 (1882.5 MHz)	382500 (1912.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.99	17.93	17.59	0	0.0
	1	13	17.79	17.77	17.60		0.0
	1	23	17.87	17.88	17.52		0.0
	12	0	17.81	17.79	17.55	0-1	0.0
	12	7	17.81	17.71	17.51	0	0.0
	12	13	17.76	17.69	17.50	0-1	0.0
	25	0	17.85	17.81	17.59		0.0
DFT-s-OFDM 16QAM	1	1	17.97	17.76	17.44	0-1	0.0
CP-OFDM QPSK	1	1	18.09	18.03	17.73	0-1.5	0.0

Table H-194
NR Band n25 Ant A Measured P_{Max} for DSI = 1 (Head) - 35 MHz Bandwidth

NR Band n25 35 MHz Bandwidth						
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			376500 (1882.5 MHz)			
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	23.49	0	0.0	
	1	94	23.62		0.0	
	1	186	23.48		0.0	
	90	0	22.55	0-1	1.0	
	90	49	23.51	0	0.0	
	90	98	22.45	0-1	1.0	
	180	0	22.50		1.0	
DFT-s-OFDM 16QAM	1	1	22.52	0-1	1.0	
CP-OFDM QPSK	1	1	22.09	0-1.5	1.5	

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 105 of 222

Table H-195
NR Band n25 Ant A Measured P_{Max} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n25 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.57	0	0.0
	1	80	23.45		0.0
	1	158	23.46		0.0
	80	0	22.62	0-1	1.0
	80	40	23.47	0	0.0
	80	80	22.55	0-1	1.0
	160	0	22.45		1.0
DFT-s-OFDM 16QAM	1	1	22.55	0-1	1.0
CP-OFDM QPSK	1	1	22.05	0-1.5	1.5

Table H-196
NR Band n25 Ant A Measured P_{Max} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n25 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.68	0	0.0
	1	67	23.53		0.0
	1	131	23.49		0.0
	64	0	22.51	0-1	1.0
	64	35	23.50	0	0.0
	64	69	22.46	0-1	1.0
	128	0	22.43		1.0
DFT-s-OFDM 16QAM	1	1	22.54	0-1	1.0
CP-OFDM QPSK	1	1	22.08	0-1.5	1.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 106 of 222

Table H-197
NR Band n25 Ant A Measured P_{Max} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n25 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	372000 (1860 MHz)	376500 (1882.5 MHz)	381000 (1905 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.54	23.49	23.35	0	0.0
	1	53	23.47	23.33	23.19		0.0
	1	104	23.40	23.31	22.52		0.0
	50	0	22.55	22.48	22.35	0-1	1.0
	50	28	23.52	23.45	23.36	0	0.0
	50	56	22.62	22.45	22.41	0-1	1.0
	100	0	22.49	22.45	22.40		1.0
DFT-s-OFDM 16QAM	1	1	22.60	22.34	22.35	0-1	1.0
CP-OFDM QPSK	1	1	22.02	22.05	21.95	0-1.5	1.5

Table H-198
NR Band n25 Ant A Measured P_{Max} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n25 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371500 (1857.5 MHz)	376500 (1882.5 MHz)	381500 (1907.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.65	23.51	23.36	0	0.0
	1	40	23.47	23.39	22.91		0.0
	1	77	23.40	23.40	22.55		0.0
	36	0	22.52	22.43	22.33	0-1	1.0
	36	22	23.52	23.48	23.35	0	0.0
	36	43	22.55	22.45	22.34	0-1	1.0
	75	0	22.57	22.38	22.34		1.0
DFT-s-OFDM 16QAM	1	1	22.66	22.40	22.35	0-1	1.0
CP-OFDM QPSK	1	1	22.25	22.03	22.03	0-1.5	1.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 107 of 222

Table H-199
NR Band n25 Ant A Measured P_{Max} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n25 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371000 (1855 MHz)	376500 (1882.5 MHz)	382000 (1910 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.60	23.42	23.20	0	0.0
	1	26	23.65	23.43	22.86		0.0
	1	50	23.51	23.39	22.49		0.0
	25	0	22.63	22.34	22.41	0-1	1.0
	25	14	23.55	23.38	23.23	0	0.0
	25	27	22.62	22.43	22.30	0-1	1.0
	50	0	22.62	22.40	22.39		1.0
DFT-s-OFDM 16QAM	1	1	22.56	22.42	22.13	0-1	1.0
CP-OFDM QPSK	1	1	22.29	22.04	21.78	0-1.5	1.5

Table H-200
NR Band n25 Ant A Measured P_{Max} for DSI = 1 (Head) - 5 MHz Bandwidth

NR Band n25 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	370500 (1852.5 MHz)	376500 (1882.5 MHz)	382500 (1912.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.62	23.59	23.28	0	0.0
	1	13	23.45	23.35	22.89		0.0
	1	23	23.53	23.42	22.55		0.0
	12	0	22.49	22.42	22.24	0-1	1.0
	12	7	23.39	23.43	23.20	0	0.0
	12	13	22.38	22.34	22.23	0-1	1.0
	25	0	22.48	22.49	22.35		1.0
DFT-s-OFDM 16QAM	1	1	22.60	22.61	22.11	0-1	1.0
CP-OFDM QPSK	1	1	22.26	22.13	21.76	0-1.5	1.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 108 of 222

Table H-201
NR Band n25 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 35 MHz Bandwidth

NR Band n25 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	20.01	0	0.0
	1	94	20.17		0.0
	1	186	20.06		0.0
	90	0	20.04	0-1	0.0
	90	49	20.09	0	0.0
	90	98	20.02	0-1	0.0
	180	0	20.02		0.0
DFT-s-OFDM 16QAM	1	1	20.03	0-1	0.0
CP-OFDM QPSK	1	1	20.16	0-1.5	0.0

Table H-202
NR Band n25 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n25 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	20.08	0	0.0
	1	80	20.09		0.0
	1	158	20.10		0.0
	80	0	19.85	0-1	0.0
	80	40	20.04	0	0.0
	80	80	19.94	0-1	0.0
	160	0	19.96		0.0
DFT-s-OFDM 16QAM	1	1	19.90	0-1	0.0
CP-OFDM QPSK	1	1	20.10	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 109 of 222

Table H-203
NR Band n25 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 25 MHz Bandwidth

NR Band n25 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	20.00	0	0.0
	1	67	20.11		0.0
	1	131	20.12		0.0
	64	0	19.85	0-1	0.0
	64	35	19.97	0	0.0
	64	69	20.04	0-1	0.0
	128	0	20.00		0.0
DFT-s-OFDM 16QAM	1	1	19.97	0-1	0.0
CP-OFDM QPSK	1	1	20.26	0-1.5	0.0

Table H-204
NR Band n25 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n25 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	372000 (1860 MHz)	376500 (1882.5 MHz)	381000 (1905 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.90	19.86	20.04	0	0.0
	1	53	19.96	20.07	20.04		0.0
	1	104	19.81	20.02	20.03		0.0
	50	0	19.81	19.83	19.88	0-1	0.0
	50	28	19.98	19.91	20.01	0	0.0
	50	56	19.85	19.97	19.94	0-1	0.0
	100	0	19.99	19.91	20.11		0.0
DFT-s-OFDM 16QAM	1	1	19.75	19.77	19.95	0-1	0.0
CP-OFDM QPSK	1	1	20.00	20.03	20.10	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 110 of 222

Table H-205

NR Band n25 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n25 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371500 (1857.5 MHz)	376500 (1882.5 MHz)	381500 (1907.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.06	19.88	20.00	0	0.0
	1	40	19.95	19.96	19.99		0.0
	1	77	19.93	19.93	19.94		0.0
	36	0	19.90	19.94	19.99	0-1	0.0
	36	22	20.04	20.12	20.09	0	0.0
	36	43	19.89	19.92	19.80	0-1	0.0
	75	0	19.89	19.92	19.90		0.0
DFT-s-OFDM 16QAM	1	1	19.91	19.88	19.96	0-1	0.0
CP-OFDM QPSK	1	1	19.99	20.11	20.03	0-1.5	0.0

Table H-206

NR Band n25 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n25 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371000 (1855 MHz)	376500 (1882.5 MHz)	382000 (1910 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.86	19.97	20.00	0	0.0
	1	26	19.97	20.06	20.04		0.0
	1	50	19.95	19.98	20.01		0.0
	25	0	19.88	19.98	19.83	0-1	0.0
	25	14	19.92	20.04	19.96	0	0.0
	25	27	19.94	19.93	19.82	0-1	0.0
	50	0	19.95	19.95	19.84		0.0
DFT-s-OFDM 16QAM	1	1	19.89	19.91	19.90	0-1	0.0
CP-OFDM QPSK	1	1	20.02	20.02	20.03	0-1.5	0.0

FCC ID A3LSMS938U

RF EXPOSURE PART 1 TEST REPORT

Approved by:

Technical Manager

DUT Type:

Portable Handset

APPENDIX H:

Page 111 of 222

Table H-207

NR Band n25 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n25 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	370500 (1852.5 MHz)	376500 (1882.5 MHz)	382500 (1912.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.83	19.93	19.84	0	0.0
	1	13	19.76	20.02	19.90		0.0
	1	23	19.84	19.92	19.80		0.0
	12	0	19.84	19.96	19.87	0-1	0.0
	12	7	19.93	19.97	19.97	0	0.0
	12	13	19.89	19.95	19.94	0-1	0.0
	25	0	19.85	19.98	19.78		0.0
DFT-s-OFDM 16QAM	1	1	19.94	20.02	19.82	0-1	0.0
CP-OFDM QPSK	1	1	20.06	20.22	19.98	0-1.5	0.0

Table H-208

NR Band n25 Ant F Measured P_{Limit} for DSI = 1 (Head) - 35 MHz Bandwidth

NR Band n25 35 MHz Bandwidth						
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			376500 (1882.5 MHz)			
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.54	0	0.0	
	1	94	18.56		0.0	
	1	186	18.53		0.0	
	90	0	18.49	0-1	0.0	
	90	49	18.58	0	0.0	
	90	98	18.52	0-1	0.0	
	180	0	18.48		0.0	
DFT-s-OFDM 16QAM	1	1	18.52	0-1	0.0	
CP-OFDM QPSK	1	1	18.57	0-1.5	0.0	

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 112 of 222

Table H-209
NR Band n25 Ant F Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n25 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.40	0	0.0
	1	80	18.45		0.0
	1	158	18.47		0.0
	80	0	18.30	0-1	0.0
	80	40	18.38	0	0.0
	80	80	18.45	0-1	0.0
	160	0	18.29		0.0
DFT-s-OFDM 16QAM	1	1	18.35	0-1	0.0
CP-OFDM QPSK	1	1	18.44	0-1.5	0.0

Table H-210
NR Band n25 Ant F Measured P_{Limit} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n25 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.46	0	0.0
	1	67	18.54		0.0
	1	131	18.55		0.0
	64	0	18.31	0-1	0.0
	64	35	18.35	0	0.0
	64	69	18.40	0-1	0.0
	128	0	18.45		0.0
DFT-s-OFDM 16QAM	1	1	18.29	0-1	0.0
CP-OFDM QPSK	1	1	18.53	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 113 of 222

Table H-211
NR Band n25 Ant F Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n25 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	372000 (1860 MHz)	376500 (1882.5 MHz)	381000 (1905 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.33	18.24	18.33	0	0.0
	1	53	18.27	18.46	18.43		0.0
	1	104	18.25	18.44	18.41		0.0
	50	0	18.29	18.32	18.33	0-1	0.0
	50	28	18.25	18.45	18.39	0	0.0
	50	56	18.33	18.32	18.28	0-1	0.0
	100	0	18.37	18.39	18.35		0.0
DFT-s-OFDM 16QAM	1	1	18.11	18.22	18.39	0-1	0.0
CP-OFDM QPSK	1	1	18.39	18.40	18.59	0-1.5	0.0

Table H-212
NR Band n25 Ant F Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n25 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371500 (1857.5 MHz)	376500 (1882.5 MHz)	381500 (1907.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.43	18.48	18.28	0	0.0
	1	40	18.24	18.37	18.40		0.0
	1	77	18.39	18.40	18.40		0.0
	36	0	18.19	18.35	18.32	0-1	0.0
	36	22	18.44	18.41	18.38	0	0.0
	36	43	18.31	18.38	18.19	0-1	0.0
	75	0	18.21	18.32	18.27		0.0
DFT-s-OFDM 16QAM	1	1	18.15	18.32	18.30	0-1	0.0
CP-OFDM QPSK	1	1	18.38	18.44	18.56	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 114 of 222

Table H-213
NR Band n25 Ant F Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n25 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371000 (1855 MHz)	376500 (1882.5 MHz)	382000 (1910 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.40	18.33	18.44	0	0.0
	1	26	18.39	18.41	18.43		0.0
	1	50	18.30	18.36	18.41		0.0
	25	0	18.28	18.36	18.25	0-1	0.0
	25	14	18.40	18.44	18.32	0	0.0
	25	27	18.37	18.35	18.17	0-1	0.0
	50	0	18.37	18.32	18.18		0.0
DFT-s-OFDM 16QAM	1	1	18.28	18.30	18.09	0-1	0.0
CP-OFDM QPSK	1	1	18.58	18.55	18.43	0-1.5	0.0

Table H-214
NR Band n25 Ant F Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

NR Band n25 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	370500 (1852.5 MHz)	376500 (1882.5 MHz)	382500 (1912.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.36	18.42	18.26	0	0.0
	1	13	18.26	18.42	18.38		0.0
	1	23	18.22	18.40	18.25		0.0
	12	0	18.25	18.35	18.26	0-1	0.0
	12	7	18.33	18.37	18.29	0	0.0
	12	13	18.27	18.28	18.17	0-1	0.0
	25	0	18.26	18.37	18.17		0.0
DFT-s-OFDM 16QAM	1	1	18.39	18.44	18.23	0-1	0.0
CP-OFDM QPSK	1	1	18.45	18.65	18.57	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 115 of 222

H.2.8 NR Band n30

Table H-215

NR Band n30 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			462000 (2310 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.47	0	0.0
	1	13	19.45		0.0
	1	23	19.26		0.0
	12	0	19.41	0-1	0.0
	12	7	19.45	0	0.0
	12	13	19.34	0-1	0.0
	25	0	19.42		0.0
DFT-s-OFDM 16QAM	1	1	19.53	0-1	0.0
CP-OFDM QPSK	1	1	19.54	0-1.5	0.0

Table H-216

NR Band n30 Ant A Measured P_{Max} for DSI = 1 (Head) - 5 MHz Bandwidth

NR Band n30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			462000 (2310 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	22.05	0	0.0
	1	13	21.92		0.0
	1	23	22.02		0.0
	12	0	21.05	0-1	1.0
	12	7	22.10	0	0.0
	12	13	21.07	0-1	1.0
	25	0	21.08		1.0
DFT-s-OFDM 16QAM	1	1	21.32	0-1	1.0
CP-OFDM QPSK	1	1	20.72	0-1.5	1.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 116 of 222

Table H-217
NR Band n30 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			462000 (2310 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	20.00	0	0.0
	1	13	20.01		0.0
	1	23	19.91		0.0
	12	0	19.91	0-1	0.0
	12	7	20.04	0	0.0
	12	13	19.92	0-1	0.0
	25	0	19.91		0.0
DFT-s-OFDM 16QAM	1	1	19.38	0-1	0.0
CP-OFDM QPSK	1	1	20.09	0-1.5	0.0

Table H-218
NR Band n30 Ant F Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

NR Band n30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			462000 (2310 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.92	0	0.0
	1	13	17.00		0.0
	1	23	16.85		0.0
	12	0	16.88	0-1	0.0
	12	7	16.94	0	0.0
	12	13	16.92	0-1	0.0
	25	0	16.89		0.0
DFT-s-OFDM 16QAM	1	1	16.32	0-1	0.0
CP-OFDM QPSK	1	1	17.01	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 117 of 222

H.2.9 NR Band n7

Table H-219

NR Band n7 Ant B Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 40 MHz Bandwidth

NR Band n7 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.95	0	0.0
	1	108	19.86		0.0
	1	214	19.82		0.0
	108	0	19.96	0-1	0.0
	108	54	19.90	0	0.0
	108	108	19.91	0-1	0.0
	216	0	19.93		0.0
DFT-s-OFDM 16QAM	1	1	19.60	0-1	0.0
CP-OFDM QPSK	1	1	20.33	0-1.5	0.0

Table H-220

NR Band n7 Ant B Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 35 MHz Bandwidth

NR Band n7 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	20.17	0	0.0
	1	94	20.24		0.0
	1	186	20.20		0.0
	90	0	20.28	0-1	0.0
	90	49	20.32	0	0.0
	90	98	20.26	0-1	0.0
	180	0	20.25		0.0
DFT-s-OFDM 16QAM	1	1	19.76	0-1	0.0
CP-OFDM QPSK	1	1	20.59	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 118 of 222

Table H-221
NR Band n7 Ant B Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n7 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	20.27	0	0.0
	1	80	20.29		0.0
	1	158	20.28		0.0
	80	0	20.27	0-1	0.0
	80	40	20.22	0	0.0
	80	80	20.32	0-1	0.0
	160	0	20.20		0.0
DFT-s-OFDM 16QAM	1	1	20.07	0-1	0.0
CP-OFDM QPSK	1	1	20.44	0-1.5	0.0

Table H-222
NR Band n7 Ant B Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 25 MHz Bandwidth

NR Band n7 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	20.32	0	0.0
	1	67	20.34		0.0
	1	131	20.24		0.0
	64	0	20.35	0-1	0.0
	64	35	20.26	0	0.0
	64	69	20.19	0-1	0.0
	128	0	20.26		0.0
DFT-s-OFDM 16QAM	1	1	20.12	0-1	0.0
CP-OFDM QPSK	1	1	20.43	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 119 of 222

Table H-223

NR Band n7 Ant B Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n7 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502000 (2510 MHz)	507000 (2535 MHz)	512000 (2560 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.41	20.24	20.26	0	0.0
	1	53	20.21	20.11	20.21		0.0
	1	104	20.21	20.22	20.36		0.0
	50	0	20.31	20.26	20.31	0-1	0.0
	50	28	20.34	20.28	20.38	0	0.0
	50	56	20.27	20.17	20.41	0-1	0.0
	100	0	20.29	20.15	20.35		0.0
DFT-s-OFDM 16QAM	1	1	20.43	20.10	20.06	0-1	0.0
CP-OFDM QPSK	1	1	20.49	20.35	20.34	0-1.5	0.0

Table H-224

NR Band n7 Ant B Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n7 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501500 (2507.5 MHz)	507000 (2535 MHz)	512500 (2562.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.39	20.28	20.34	0	0.0
	1	40	20.23	20.22	20.31		0.0
	1	77	20.04	20.23	20.45		0.0
	36	0	20.24	20.20	20.43	0-1	0.0
	36	22	20.30	20.28	20.42	0	0.0
	36	43	20.21	20.18	20.29	0-1	0.0
	75	0	20.27	20.12	20.40		0.0
DFT-s-OFDM 16QAM	1	1	20.43	20.14	20.13	0-1	0.0
CP-OFDM QPSK	1	1	20.46	20.37	20.46	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 120 of 222

Table H-225
NR Band n7 Ant B Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n7 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501000 (2505 MHz)	507000 (2535 MHz)	513000 (2565 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.37	20.34	20.39	0	0.0
	1	26	20.33	20.31	20.39		0.0
	1	50	20.28	20.31	20.37		0.0
	25	0	20.34	20.27	20.41	0-1	0.0
	25	14	20.27	20.29	20.23	0	0.0
	25	27	20.31	20.27	20.34	0-1	0.0
	50	0	20.41	20.30	20.34		0.0
DFT-s-OFDM 16QAM	1	1	20.42	20.32	20.33	0-1	0.0
CP-OFDM QPSK	1	1	20.52	20.43	20.42	0-1.5	0.0

Table H-226
NR Band n7 Ant B Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n7 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500500 (2502.5 MHz)	507000 (2535 MHz)	513500 (2567.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.54	20.31	20.47	0	0.0
	1	13	20.54	20.36	20.47		0.0
	1	23	20.50	20.34	20.47		0.0
	12	0	20.34	20.16	20.28	0-1	0.0
	12	7	20.46	20.25	20.39	0	0.0
	12	13	20.35	20.21	20.31	0-1	0.0
	25	0	20.42	20.25	20.39		0.0
DFT-s-OFDM 16QAM	1	1	20.53	20.29	20.44	0-1	0.0
CP-OFDM QPSK	1	1	20.65	20.39	20.50	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 121 of 222

Table H-227
NR Band n7 Ant B Measured P_{Max} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n7 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.06	0	0.0
	1	108	22.99		0.0
	1	214	22.90		0.0
	108	0	22.15	0-1	1.0
	108	54	23.01	0	0.0
	108	108	21.96	0-1	1.0
	216	0	22.07		1.0
DFT-s-OFDM 16QAM	1	1	21.88	0-1	1.0
CP-OFDM QPSK	1	1	21.82	0-1.5	1.5

Table H-228
NR Band n7 Ant B Measured P_{Max} for DSI = 1 (Head) - 35 MHz Bandwidth

NR Band n7 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.34	0	0.0
	1	94	23.55		0.0
	1	186	23.41		0.0
	90	0	22.51	0-1	1.0
	90	49	23.54	0	0.0
	90	98	22.52	0-1	1.0
	180	0	22.32		1.0
DFT-s-OFDM 16QAM	1	1	22.05	0-1	1.0
CP-OFDM QPSK	1	1	22.08	0-1.5	1.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 122 of 222

Table H-229
NR Band n7 Ant B Measured P_{Max} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n7 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.42	0	0.0
	1	80	23.35		0.0
	1	158	23.34		0.0
	80	0	22.43	0-1	1.0
	80	40	23.45	0	0.0
	80	80	22.40	0-1	1.0
	160	0	22.43		1.0
DFT-s-OFDM 16QAM	1	1	22.20	0-1	1.0
CP-OFDM QPSK	1	1	22.09	0-1.5	1.5

Table H-230
NR Band n7 Ant B Measured P_{Max} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n7 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.53	0	0.0
	1	67	23.45		0.0
	1	131	23.44		0.0
	64	0	22.36	0-1	1.0
	64	35	23.38	0	0.0
	64	69	22.38	0-1	1.0
	128	0	22.41		1.0
DFT-s-OFDM 16QAM	1	1	22.28	0-1	1.0
CP-OFDM QPSK	1	1	22.03	0-1.5	1.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 123 of 222

Table H-231
NR Band n7 Ant B Measured P_{Max} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n7 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502000 (2510 MHz)	507000 (2535 MHz)	512000 (2560 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.31	23.41	23.33	0	0.0
	1	53	23.30	23.25	23.41		0.0
	1	104	23.33	23.38	23.36		0.0
	50	0	22.46	22.29	22.44	0-1	1.0
	50	28	23.39	23.31	23.45	0	0.0
	50	56	22.44	22.32	22.52	0-1	1.0
	100	0	22.38	22.34	22.44		1.0
DFT-s-OFDM 16QAM	1	1	22.29	22.32	22.14	0-1	1.0
CP-OFDM QPSK	1	1	21.98	21.85	21.94	0-1.5	1.5

Table H-232
NR Band n7 Ant B Measured P_{Max} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n7 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501500 (2507.5 MHz)	507000 (2535 MHz)	512500 (2562.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.43	23.39	23.51	0	0.0
	1	40	23.38	23.27	23.41		0.0
	1	77	23.29	23.28	23.39		0.0
	36	0	22.34	22.31	22.38	0-1	1.0
	36	22	23.29	23.30	23.50	0	0.0
	36	43	22.36	22.36	22.55	0-1	1.0
	75	0	22.39	22.40	22.48		1.0
DFT-s-OFDM 16QAM	1	1	22.33	22.26	22.38	0-1	1.0
CP-OFDM QPSK	1	1	21.93	21.90	21.94	0-1.5	1.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 124 of 222

Table H-233
NR Band n7 Ant B Measured P_{Max} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n7 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501000 (2505 MHz)	507000 (2535 MHz)	513000 (2565 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.32	23.40	23.48	0	0.0
	1	26	23.41	23.31	23.50		0.0
	1	50	23.31	23.36	23.35		0.0
	25	0	22.40	22.36	22.33	0-1	1.0
	25	14	23.39	23.28	23.30	0	0.0
	25	27	22.26	22.40	22.49	0-1	1.0
	50	0	22.44	22.31	22.39		1.0
DFT-s-OFDM 16QAM	1	1	22.17	22.53	22.44	0-1	1.0
CP-OFDM QPSK	1	1	21.88	21.98	21.93	0-1.5	1.5

Table H-234
NR Band n7 Ant B Measured P_{Max} for DSI = 1 (Head) - 5 MHz Bandwidth

NR Band n7 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500500 (2502.5 MHz)	507000 (2535 MHz)	513500 (2567.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.28	23.40	23.52	0	0.0
	1	13	23.25	23.33	23.32		0.0
	1	23	23.53	23.33	23.04		0.0
	12	0	22.38	22.18	22.32	0-1	1.0
	12	7	23.45	23.30	23.45	0	0.0
	12	13	22.39	22.30	22.42	0-1	1.0
	25	0	22.52	22.33	22.43		1.0
DFT-s-OFDM 16QAM	1	1	22.26	22.50	22.44	0-1	1.0
CP-OFDM QPSK	1	1	21.99	22.01	22.07	0-1.5	1.5

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 125 of 222

Table H-235
NR Band n7 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 40 MHz Bandwidth

NR Band n7 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.49	0	0.0
	1	108	19.33		0.0
	1	214	19.37		0.0
	108	0	19.34	0-1	0.0
	108	54	19.45	0	0.0
	108	108	19.39	0-1	0.0
	216	0	19.42		0.0
DFT-s-OFDM 16QAM	1	1	19.32	0-1	0.0
CP-OFDM QPSK	1	1	19.57	0-1.5	0.0

Table H-236
NR Band n7 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 35 MHz Bandwidth

NR Band n7 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.75	0	0.0
	1	94	19.92		0.0
	1	186	19.90		0.0
	90	0	19.97	0-1	0.0
	90	49	19.91	0	0.0
	90	98	19.78	0-1	0.0
	180	0	19.88		0.0
DFT-s-OFDM 16QAM	1	1	19.70	0-1	0.0
CP-OFDM QPSK	1	1	20.06	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 126 of 222

Table H-237
NR Band n7 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n7 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.46	0	0.0
	1	80	19.39		0.0
	1	158	19.49		0.0
	80	0	19.39	0-1	0.0
	80	40	19.46	0	0.0
	80	80	19.38	0-1	0.0
	160	0	19.43		0.0
DFT-s-OFDM 16QAM	1	1	19.37	0-1	0.0
CP-OFDM QPSK	1	1	19.58	0-1.5	0.0

Table H-238
NR Band n7 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 25 MHz Bandwidth

NR Band n7 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.58	0	0.0
	1	67	19.32		0.0
	1	131	19.44		0.0
	64	0	19.43	0-1	0.0
	64	35	19.45	0	0.0
	64	69	19.38	0-1	0.0
	128	0	19.35		0.0
DFT-s-OFDM 16QAM	1	1	19.34	0-1	0.0
CP-OFDM QPSK	1	1	19.57	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 127 of 222

Table H-239
NR Band n7 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n7 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502000 (2510 MHz)	507000 (2535 MHz)	512000 (2560 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.28	19.39	19.25	0	0.0
	1	53	19.42	19.35	19.36		0.0
	1	104	19.39	19.26	19.39		0.0
	50	0	19.49	19.41	19.32	0-1	0.0
	50	28	19.48	19.33	19.42	0	0.0
	50	56	19.34	19.30	19.32	0-1	0.0
	100	0	19.53	19.45	19.45		0.0
DFT-s-OFDM 16QAM	1	1	19.27	19.23	19.24	0-1	0.0
CP-OFDM QPSK	1	1	19.53	19.57	19.44	0-1.5	0.0

Table H-240
NR Band n7 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n7 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501500 (2507.5 MHz)	507000 (2535 MHz)	512500 (2562.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.48	19.46	19.45	0	0.0
	1	40	19.38	19.28	19.43		0.0
	1	77	19.44	19.29	19.50		0.0
	36	0	19.37	19.31	19.36	0-1	0.0
	36	22	19.59	19.34	19.53	0	0.0
	36	43	19.36	19.29	19.38	0-1	0.0
	75	0	19.40	19.36	19.33		0.0
DFT-s-OFDM 16QAM	1	1	19.27	19.35	19.30	0-1	0.0
CP-OFDM QPSK	1	1	19.65	19.57	19.55	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 128 of 222

Table H-241
NR Band n7 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n7 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501000 (2505 MHz)	507000 (2535 MHz)	513000 (2565 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.43	19.41	19.40	0	0.0
	1	26	19.49	19.32	19.34		0.0
	1	50	19.37	19.25	19.38		0.0
	25	0	19.38	19.33	19.28	0-1	0.0
	25	14	19.44	19.26	19.34	0	0.0
	25	27	19.38	19.31	19.20	0-1	0.0
	50	0	19.39	19.35	19.29		0.0
DFT-s-OFDM 16QAM	1	1	19.32	19.36	19.26	0-1	0.0
CP-OFDM QPSK	1	1	19.59	19.59	19.44	0-1.5	0.0

Table H-242
NR Band n7 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n7 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500500 (2502.5 MHz)	507000 (2535 MHz)	513500 (2567.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.40	19.33	19.35	0	0.0
	1	13	19.48	19.42	19.41		0.0
	1	23	19.37	19.34	19.34		0.0
	12	0	19.46	19.31	19.20	0-1	0.0
	12	7	19.52	19.41	19.36	0	0.0
	12	13	19.42	19.32	19.28	0-1	0.0
	25	0	19.42	19.29	19.28		0.0
DFT-s-OFDM 16QAM	1	1	19.39	19.25	19.25	0-1	0.0
CP-OFDM QPSK	1	1	19.69	19.58	19.54	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 129 of 222

Table H-243
NR Band n7 Ant F Measured P_{Limit} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n7 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.01	0	0.0
	1	108	15.83		0.0
	1	214	15.83		0.0
	108	0	15.88	0-1	0.0
	108	54	15.92	0	0.0
	108	108	15.79	0-1	0.0
	216	0	15.90		0.0
DFT-s-OFDM 16QAM	1	1	15.87	0-1	0.0
CP-OFDM QPSK	1	1	16.11	0-1.5	0.0

Table H-244
NR Band n7 Ant F Measured P_{Limit} for DSI = 1 (Head) - 35 MHz Bandwidth

NR Band n7 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.32	0	0.0
	1	94	16.44		0.0
	1	186	16.39		0.0
	90	0	16.44	0-1	0.0
	90	49	16.49	0	0.0
	90	98	16.30	0-1	0.0
	180	0	16.41		0.0
DFT-s-OFDM 16QAM	1	1	16.22	0-1	0.0
CP-OFDM QPSK	1	1	16.53	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 130 of 222

Table H-245
NR Band n7 Ant F Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n7 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	15.94	0	0.0
	1	80	15.99		0.0
	1	158	15.94		0.0
	80	0	15.93	0-1	0.0
	80	40	16.02	0	0.0
	80	80	15.93	0-1	0.0
	160	0	15.93		0.0
DFT-s-OFDM 16QAM	1	1	15.84	0-1	0.0
CP-OFDM QPSK	1	1	16.20	0-1.5	0.0

Table H-246
NR Band n7 Ant F Measured P_{Limit} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n7 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.07	0	0.0
	1	67	15.97		0.0
	1	131	15.94		0.0
	64	0	15.96	0-1	0.0
	64	35	15.95	0	0.0
	64	69	15.81	0-1	0.0
	128	0	15.82		0.0
DFT-s-OFDM 16QAM	1	1	15.88	0-1	0.0
CP-OFDM QPSK	1	1	15.99	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 131 of 222

Table H-247
NR Band n7 Ant F Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n7 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502000 (2510 MHz)	507000 (2535 MHz)	512000 (2560 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	15.99	15.93	15.89	0	0.0
	1	53	15.93	15.94	15.88		0.0
	1	104	15.94	15.83	15.81		0.0
	50	0	15.91	15.83	15.85	0-1	0.0
	50	28	15.88	15.88	15.95	0	0.0
	50	56	15.84	15.80	15.79	0-1	0.0
	100	0	15.99	15.95	15.81		0.0
DFT-s-OFDM 16QAM	1	1	15.87	15.82	15.77	0-1	0.0
CP-OFDM QPSK	1	1	16.13	16.08	15.98	0-1.5	0.0

Table H-248
NR Band n7 Ant F Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n7 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501500 (2507.5 MHz)	507000 (2535 MHz)	512500 (2562.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	15.96	15.97	15.97	0	0.0
	1	40	15.94	15.80	15.88		0.0
	1	77	15.93	15.86	15.94		0.0
	36	0	15.88	15.82	15.78	0-1	0.0
	36	22	16.05	15.93	15.97	0	0.0
	36	43	15.80	15.76	15.80	0-1	0.0
	75	0	15.94	15.89	15.85		0.0
DFT-s-OFDM 16QAM	1	1	15.92	15.75	15.75	0-1	0.0
CP-OFDM QPSK	1	1	16.04	16.15	16.02	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 132 of 222

Table H-249
NR Band n7 Ant F Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n7 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501000 (2505 MHz)	507000 (2535 MHz)	513000 (2565 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	15.96	15.98	15.87	0	0.0
	1	26	15.93	15.84	15.81		0.0
	1	50	15.98	15.85	15.82		0.0
	25	0	15.88	15.84	15.81	0-1	0.0
	25	14	16.00	15.98	15.89	0	0.0
	25	27	15.82	15.83	15.79	0-1	0.0
	50	0	15.91	15.85	15.75		0.0
DFT-s-OFDM 16QAM	1	1	15.90	15.85	15.64	0-1	0.0
CP-OFDM QPSK	1	1	16.15	16.03	15.95	0-1.5	0.0

Table H-250
NR Band n7 Ant F Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

NR Band n7 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500500 (2502.5 MHz)	507000 (2535 MHz)	513500 (2567.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	15.97	15.86	15.87	0	0.0
	1	13	16.08	15.81	15.93		0.0
	1	23	15.88	15.83	15.70		0.0
	12	0	15.96	15.74	15.72	0-1	0.0
	12	7	16.01	15.84	15.85	0	0.0
	12	13	15.97	15.77	15.75	0-1	0.0
	25	0	15.98	15.80	15.73		0.0
DFT-s-OFDM 16QAM	1	1	15.91	15.79	15.76	0-1	0.0
CP-OFDM QPSK	1	1	16.18	16.08	15.96	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 133 of 222

H.2.10 NR Band n41

Table H-251

NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	508200 (2541 MHz)	528996 (2644.98 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	20.33	20.35	0	0.0
	1	123	20.18	20.12		0.0
	1	243	20.47	20.44		0.0
	120	0	20.13	20.12	0-1	0.0
	120	63	20.20	20.15	0	0.0
	120	125	20.28	20.20	0-1	0.0
	243	0	20.27	20.25		0.0
DFT-s-OFDM 16QAM	1	1	20.28	20.38	0-1	0.0
CP-OFDM QPSK	1	1	20.39	20.47	0-1.5	0.0

Table H-252

NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	507204 (2536.02 MHz)	529998 (2649.99 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	20.43	20.24	0	0.0
	1	109	20.21	20.11		0.0
	1	215	20.48	20.45		0.0
	108	0	20.21	20.07	0-1	0.0
	108	55	20.34	20.21	0	0.0
	108	109	20.32	20.26	0-1	0.0
	216	0	20.33	20.27		0.0
DFT-s-OFDM 16QAM	1	1	20.34	20.24	0-1	0.0
CP-OFDM QPSK	1	1	20.42	20.33	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 134 of 222

Table H-253
NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	506202 (2531.01 MHz)	531000 (2655 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	20.24	20.13	0	0.0
	1	95	20.11	20.09		0.0
	1	187	20.32	20.33		0.0
	90	0	20.13	20.06	0-1	0.0
	90	50	20.27	20.20	0	0.0
	90	99	20.23	20.30	0-1	0.0
	180	0	20.24	20.17		0.0
DFT-s-OFDM 16QAM	1	1	20.20	20.16	0-1	0.0
CP-OFDM QPSK	1	1	20.37	20.21	0-1.5	0.0

Table H-254
NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.24	20.27	20.08	0	0.0
	1	81	20.09	20.19	20.02		0.0
	1	160	20.26	20.20	20.34		0.0
	81	0	20.11	20.24	19.82	0-1	0.0
	81	41	20.15	20.28	19.96	0	0.0
	81	81	20.14	20.19	20.00	0-1	0.0
	162	0	20.21	20.29	19.99		0.0
DFT-s-OFDM 16QAM	1	1	20.22	20.17	19.94	0-1	0.0
CP-OFDM OPSK	1	1	20.25	20.20	19.99	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 135 of 222

Table H-255
NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.44	20.47	20.22	0	0.0
	1	67	20.32	20.40	20.32		0.0
	1	131	20.47	20.46	20.48		0.0
	64	0	20.29	20.38	20.23	0-1	0.0
	64	35	20.38	20.44	20.42	0	0.0
	64	69	20.35	20.36	20.37	0-1	0.0
	128	0	20.38	20.33	20.30		0.0
DFT-s-OFDM 16QAM	1	1	20.39	20.38	20.15	0-1	0.0
CP-OFDM QPSK	1	1	20.43	20.47	20.22	0-1.5	0.0

Table H-256
NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	20.32	20.30	20.35	20.43	0	0.0
	1	60	20.39	20.20	20.26	20.48		0.0
	1	117	20.35	20.36	20.48	20.47		0.0
	54	0	20.35	20.35	20.23	20.43	0-1	0.0
	54	27	20.32	20.37	20.16	20.48	0	0.0
	54	54	20.40	20.38	20.16	20.43	0-1	0.0
	108	0	20.26	20.34	20.28	20.46		0.0
DFT-s-OFDM 16QAM	1	1	20.35	20.36	20.32	20.41	0-1	0.0
CP-OFDM QPSK	1	1	20.38	20.41	20.39	20.45	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 136 of 222

Table H-257
NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	20.19	20.15	20.29	20.11	0	0.0
	1	53	20.10	20.28	20.18	20.22		0.0
	1	104	20.15	20.35	20.15	20.35		0.0
	50	0	20.13	20.22	20.20	20.13	0-1	0.0
	50	28	20.27	20.36	20.17	20.32	0	0.0
	50	56	20.14	20.33	20.15	20.27	0-1	0.0
	100	0	20.25	20.37	20.30	20.30		0.0
DFT-s-OFDM 16QAM	1	1	20.14	20.12	20.23	19.99	0-1	0.0
CP-OFDM QPSK	1	1	20.29	20.28	20.26	20.15	0-1.5	0.0

Table H-258
NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	20.45	20.31	20.13	20.15	20.20	0	0.0
	1	46	20.48	20.47	20.24	20.33	20.38		0.0
	1	90	20.46	20.34	20.16	20.24	20.40		0.0
	45	0	20.47	20.36	20.21	20.22	20.27	0-1	0.0
	45	22	20.43	20.44	20.25	20.30	20.44	0	0.0
	45	45	20.48	20.38	20.18	20.20	20.39	0-1	0.0
	90	0	20.46	20.37	20.22	20.24	20.40		0.0
DFT-s-OFDM 16QAM	1	1	20.42	20.31	20.24	20.23	20.31	0-1	0.0
CP-OFDM QPSK	1	1	20.46	20.49	20.16	20.41	20.38	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 137 of 222

Table H-259
NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	20.48	20.42	20.22	20.19	20.17	0	0.0
	1	39	20.33	20.38	20.17	20.24	20.21		0.0
	1	76	20.36	20.34	20.22	20.16	20.32		0.0
	36	0	20.35	20.25	20.12	20.09	20.10	0-1	0.0
	36	21	20.33	20.39	20.10	20.09	20.19	0	0.0
	36	42	20.31	20.30	20.08	20.08	20.12	0-1	0.0
	75	0	20.42	20.31	20.16	20.14	20.17		0.0
DFT-s-OFDM 16QAM	1	1	20.45	20.31	20.11	20.20	20.19	0-1	0.0
CP-OFDM QPSK	1	1	20.45	20.39	20.15	20.21	20.19	0-1.5	0.0

Table H-260
NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 25 MHz Bandwidth

NR Band n41 25 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	20.48	20.41	20.13	20.20	20.25	0	0.0
	1	33	20.44	20.38	20.15	20.18	20.28		0.0
	1	63	20.39	20.28	20.22	20.23	20.34		0.0
	32	0	20.37	20.27	20.07	20.05	20.13	0-1	0.0
	32	17	20.47	20.34	20.16	20.08	20.23	0	0.0
	32	33	20.34	20.28	20.10	20.10	20.17	0-1	0.0
	64	0	20.40	20.30	20.08	20.06	20.20		0.0
DFT-s-OFDM 16QAM	1	1	20.45	20.28	20.17	20.11	20.22	0-1	0.0
CP-OFDM QPSK	1	1	20.45	20.44	20.21	20.20	20.24	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 138 of 222

Table H-261
NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	20.37	20.15	20.03	20.07	20.18	0	0.0
	1	26	20.35	20.29	20.08	20.12	20.21		0.0
	1	49	20.37	20.23	20.15	20.09	20.18		0.0
	25	0	20.34	20.19	20.04	20.03	20.17	0-1	0.0
	25	13	20.41	20.31	20.06	20.18	20.24	0	0.0
	25	26	20.36	20.22	20.08	20.09	20.16	0-1	0.0
	50	0	20.49	20.32	20.04	20.14	20.18		0.0
DFT-s-OFDM 16QAM	1	1	20.41	20.08	20.01	20.08	20.11	0-1	0.0
CP-OFDM QPSK	1	1	20.49	20.27	20.16	20.06	20.18	0-1.5	0.0

Table H-262
NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	20.38	20.18	20.11	20.11	20.18	0	0.0
	1	19	20.47	20.30	20.14	20.14	20.16		0.0
	1	36	20.48	20.37	20.03	20.14	20.18		0.0
	18	0	20.34	20.13	20.05	20.04	20.13	0-1	0.0
	18	10	20.41	20.38	20.09	20.26	20.28	0	0.0
	18	20	20.34	20.17	20.02	20.06	20.11	0-1	0.0
	36	0	20.40	20.22	20.05	20.06	20.14		0.0
DFT-s-OFDM 16QAM	1	1	20.46	20.14	20.08	20.04	20.14	0-1	0.0
CP-OFDM QPSK	1	1	20.50	20.28	20.07	20.12	20.16	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 139 of 222

Table H-263
NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	20.42	20.14	20.14	20.20	20.07	0	0.0
	1	12	20.31	20.07	20.16	20.18	20.11		0.0
	1	22	20.39	20.14	20.19	20.25	20.19		0.0
	12	0	20.25	20.06	20.01	20.01	20.02	0-1	0.0
	12	6	20.37	20.21	20.14	20.17	20.13	0	0.0
	12	12	20.29	20.15	20.04	20.04	20.05	0-1	0.0
	24	0	20.31	20.07	19.98	20.03	20.08		0.0
DFT-s-OFDM 16QAM	1	1	20.31	20.14	20.03	20.12	20.15	0-1	0.0
CP-OFDM QPSK	1	1	20.40	20.26	20.24	20.20	20.21	0-1.5	0.0

Table H-264
NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	508200 (2541 MHz)	528996 (2644.98 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.35	17.37	0	0.0
	1	123	17.10	17.14		0.0
	1	243	17.37	17.48		0.0
	120	0	17.09	17.09	0-1	0.0
	120	63	17.14	17.13	0	0.0
	120	125	17.22	17.20	0-1	0.0
	243	0	17.24	17.24		0.0
DFT-s-OFDM 16QAM	1	1	17.29	17.35	0-1	0.0
CP-OFDM QPSK	1	1	17.37	17.46	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 140 of 222

Table H-265
NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	507204 (2536.02 MHz)	529998 (2649.99 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.35	17.24	0	0.0
	1	109	17.10	17.03		0.0
	1	215	17.43	17.42		0.0
	108	0	17.14	17.00	0-1	0.0
	108	55	17.25	17.08	0	0.0
	108	109	17.24	17.18	0-1	0.0
	216	0	17.32	17.17		0.0
DFT-s-OFDM 16QAM	1	1	17.25	17.18	0-1	0.0
CP-OFDM QPSK	1	1	17.43	17.23	0-1.5	0.0

Table H-266
NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	506202 (2531.01 MHz)	531000 (2655 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.15	17.05	0	0.0
	1	95	17.06	17.06		0.0
	1	187	17.22	17.31		0.0
	90	0	17.17	17.08	0-1	0.0
	90	50	17.13	17.12	0	0.0
	90	99	17.25	17.23	0-1	0.0
	180	0	17.16	17.10		0.0
DFT-s-OFDM 16QAM	1	1	17.23	17.04	0-1	0.0
CP-OFDM QPSK	1	1	17.31	17.18	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 141 of 222

Table H-267
NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.22	17.16	17.03	0	0.0
	1	81	17.00	17.15	16.96		0.0
	1	160	17.28	17.19	17.32		0.0
	81	0	17.02	17.15	16.94	0-1	0.0
	81	41	17.12	17.27	17.04	0	0.0
	81	81	17.09	17.16	17.08	0-1	0.0
	162	0	17.17	17.28	17.11		0.0
DFT-s-OFDM 16QAM	1	1	17.19	17.10	17.00	0-1	0.0
CP-OFDM QPSK	1	1	17.24	17.30	17.02	0-1.5	0.0

Table H-268
NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.41	17.36	17.16	0	0.0
	1	67	17.17	17.38	17.23		0.0
	1	131	17.43	17.37	17.48		0.0
	64	0	17.32	17.39	17.15	0-1	0.0
	64	35	17.38	17.45	17.37	0	0.0
	64	69	17.28	17.33	17.34	0-1	0.0
	128	0	17.30	17.41	17.21		0.0
DFT-s-OFDM 16QAM	1	1	17.39	17.37	17.13	0-1	0.0
CP-OFDM QPSK	1	1	17.48	17.47	17.26	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 142 of 222

Table H-269
NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	17.35	17.35	17.32	17.33	0	0.0
	1	60	17.30	17.17	17.22	17.34		0.0
	1	117	17.49	17.39	17.36	17.43		0.0
	54	0	17.33	17.18	17.28	17.36	0-1	0.0
	54	27	17.36	17.17	17.21	17.37	0	0.0
	54	54	17.25	17.15	17.22	17.41	0-1	0.0
	108	0	17.39	17.19	17.30	17.34		0.0
DFT-s-OFDM 16QAM	1	1	17.32	17.16	17.28	17.36	0-1	0.0
CP-OFDM QPSK	1	1	17.38	17.31	17.37	17.42	0-1.5	0.0

Table H-270
NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	17.20	17.01	17.29	17.08	0	0.0
	1	53	17.09	17.26	17.16	17.23		0.0
	1	104	17.15	17.25	17.08	17.35		0.0
	50	0	17.13	17.15	17.19	17.08	0-1	0.0
	50	28	17.19	17.29	17.24	17.30	0	0.0
	50	56	17.14	17.31	17.09	17.27	0-1	0.0
	100	0	17.26	17.30	17.25	17.29		0.0
DFT-s-OFDM 16QAM	1	1	17.17	17.07	17.12	16.98	0-1	0.0
CP-OFDM QPSK	1	1	17.33	17.12	17.36	17.10	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 143 of 222

Table H-271

NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	17.46	17.22	17.11	17.05	17.20	0	0.0
	1	46	17.48	17.43	17.18	17.19	17.29		0.0
	1	90	17.35	17.26	17.14	17.15	17.27		0.0
	45	0	17.41	17.27	17.11	17.03	17.23	0-1	0.0
	45	22	17.45	17.31	17.15	17.24	17.34	0	0.0
	45	45	17.48	17.32	17.20	17.17	17.33	0-1	0.0
	90	0	17.47	17.31	17.15	17.11	17.36		0.0
DFT-s-OFDM 16QAM	1	1	17.41	17.36	17.09	17.16	17.32	0-1	0.0
CP-OFDM QPSK	1	1	17.47	17.40	17.18	17.32	17.39	0-1.5	0.0

Table H-272

NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	17.31	17.12	17.23	17.17	17.25	0	0.0
	1	39	17.24	17.12	17.11	17.11	17.26		0.0
	1	76	17.27	17.00	17.13	17.01	17.31		0.0
	36	0	17.23	17.11	17.06	17.00	17.17	0-1	0.0
	36	21	17.28	17.12	17.14	17.10	17.16	0	0.0
	36	42	17.17	17.15	17.07	17.07	17.12	0-1	0.0
	75	0	17.27	17.17	17.03	17.10	17.22		0.0
DFT-s-OFDM 16QAM	1	1	17.38	17.19	17.04	17.12	17.14	0-1	0.0
CP-OFDM QPSK	1	1	17.49	17.25	17.21	17.28	17.34	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 144 of 222

Table H-273

NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n41 25 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	17.45	17.17	17.21	17.15	17.21	0	0.0
	1	33	17.48	17.24	17.12	17.12	17.09		0.0
	1	63	17.45	17.21	17.17	17.07	17.20		0.0
	32	0	17.42	17.16	17.04	17.02	17.09	0-1	0.0
	32	17	17.47	17.30	17.16	17.14	17.14	0	0.0
	32	33	17.30	17.21	17.11	17.09	17.16	0-1	0.0
	64	0	17.36	17.13	17.03	16.98	17.10		0.0
DFT-s-OFDM 16QAM	1	1	17.37	17.27	17.08	17.06	17.20	0-1	0.0
CP-OFDM QPSK	1	1	17.42	17.47	17.24	17.21	17.23	0-1.5	0.0

Table H-274

NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	17.25	17.14	17.01	17.01	17.12	0	0.0
	1	26	17.34	17.24	17.09	17.10	17.15		0.0
	1	49	17.27	17.07	17.12	17.00	17.10		0.0
	25	0	17.34	17.15	17.01	17.01	17.10	0-1	0.0
	25	13	17.43	17.08	17.03	17.09	17.23	0	0.0
	25	26	17.32	17.13	17.04	17.04	17.08	0-1	0.0
	50	0	17.47	17.27	17.07	17.06	17.25		0.0
DFT-s-OFDM 16QAM	1	1	17.42	17.07	16.94	16.95	17.01	0-1	0.0
CP-OFDM QPSK	1	1	17.48	17.18	17.17	17.02	17.20	0-1.5	0.0

FCC ID A3LSMS938U

RF EXPOSURE PART 1 TEST REPORT

Approved by:
Technical ManagerDUT Type:
Portable HandsetAPPENDIX H:
Page 145 of 222

Table H-275

NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	17.37	17.23	17.09	17.09	17.16	0	0.0
	1	19	17.32	17.26	17.04	17.14	17.17		0.0
	1	36	17.39	17.32	17.15	17.05	17.15		0.0
	18	0	17.32	17.19	17.06	16.95	17.04	0-1	0.0
	18	10	17.49	17.31	17.22	17.17	17.22	0	0.0
	18	20	17.32	17.24	17.01	17.01	17.07	0-1	0.0
	36	0	17.28	17.25	17.00	16.95	17.07		0.0
DFT-s-OFDM 16QAM	1	1	17.34	17.13	17.08	17.00	17.04	0-1	0.0
CP-OFDM QPSK	1	1	17.48	17.31	17.15	17.15	17.11	0-1.5	0.0

Table H-276

NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	17.21	17.06	17.10	17.05	17.13	0	0.0
	1	12	17.30	17.00	17.02	17.14	17.20		0.0
	1	22	17.36	17.09	17.06	17.14	17.14		0.0
	12	0	17.23	17.00	16.99	17.01	17.01	0-1	0.0
	12	6	17.30	17.11	17.06	17.04	17.12	0	0.0
	12	12	17.25	17.08	16.97	16.97	17.03	0-1	0.0
	24	0	17.22	16.98	16.99	17.01	17.04		0.0
DFT-s-OFDM 16QAM	1	1	17.32	17.01	17.01	17.09	17.08	0-1	0.0
CP-OFDM QPSK	1	1	17.44	17.23	17.09	17.18	17.13	0-1.5	0.0

FCC ID A3LSMS938U

RF EXPOSURE PART 1 TEST REPORT

Approved by:
Technical ManagerDUT Type:
Portable HandsetAPPENDIX H:
Page 146 of 222

Table H-277

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth		
Channel		
Antenna	508200 (2541 MHz)	528996 (2644.98 MHz)
	Conducted Power [dBm]	
SRS #2 Ant B	20.11	20.49
SRS #3 Ant E	18.53	18.75
SRS #4 Ant D	19.92	19.53

Table H-278

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth		
Channel		
Antenna	507204 (2536.02 MHz)	529998 (2649.99 MHz)
	Conducted Power [dBm]	
SRS #2 Ant B	20.07	20.45
SRS #3 Ant E	18.45	18.85
SRS #4 Ant D	19.85	19.61

Table H-279

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth		
Channel		
Antenna	506202 (2531.01 MHz)	531000 (2655 MHz)
	Conducted Power [dBm]	
SRS #2 Ant B	19.99	20.29
SRS #3 Ant E	18.31	18.77
SRS #4 Ant D	19.82	19.60

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 147 of 222

Table H-280

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth			
Channel			
Antenna	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)
	Conducted Power [dBm]		
SRS #2 Ant B	20.03	20.12	20.39
SRS #3 Ant E	18.39	18.66	18.93
SRS #4 Ant D	19.86	19.76	19.86

Table H-281

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth			
Channel			
Antenna	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)
	Conducted Power [dBm]		
SRS #2 Ant B	20.20	20.43	19.77
SRS #3 Ant E	18.50	18.95	18.98
SRS #4 Ant D	19.96	19.97	19.52

Table H-282

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth				
Channel				
Antenna	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)
	Conducted Power [dBm]			
SRS #2 Ant B	20.34	20.46	20.47	20.49
SRS #3 Ant E	18.43	18.69	18.83	18.95
SRS #4 Ant D	19.97	20.10	19.77	19.78

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 148 of 222

Table H-283

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth				
Channel				
Antenna	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)
	Conducted Power [dBm]			
SRS #2 Ant B	20.06	20.12	20.32	20.31
SRS #3 Ant E	18.39	18.67	18.82	18.95
SRS #4 Ant D	19.93	19.98	19.72	19.55

Table H-284

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth					
Channel					
Antenna	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	20.20	20.38	20.37	20.30	20.48
SRS #3 Ant E	18.30	18.42	18.66	18.55	18.88
SRS #4 Ant D	19.77	19.85	19.78	19.50	19.68

Table H-285

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth					
Channel					
Antenna	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	19.94	20.16	20.21	20.41	20.47
SRS #3 Ant E	18.49	18.63	18.84	18.82	18.97
SRS #4 Ant D	19.89	19.95	19.91	19.54	19.77

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 149 of 222

Table H-286

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 25 MHz Bandwidth

NR Band n41 25 MHz Bandwidth					
Channel					
Antenna	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	19.97	19.92	20.17	20.31	20.48
SRS #3 Ant E	18.41	18.51	18.75	18.76	18.97
SRS #4 Ant D	19.84	19.89	19.91	19.56	19.59

Table H-287

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth					
Channel					
Antenna	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	19.97	20.12	20.15	20.31	20.45
SRS #3 Ant E	18.35	18.41	18.77	18.67	18.98
SRS #4 Ant D	19.87	19.90	19.80	19.51	19.68

Table H-288

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth					
Channel					
Antenna	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	19.99	19.96	20.21	20.35	20.44
SRS #3 Ant E	18.36	18.41	18.71	18.72	18.95
SRS #4 Ant D	19.82	19.84	19.82	19.54	19.72

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 150 of 222

Table H-289

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth					
Channel					
Antenna	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	19.96	20.19	20.22	20.42	20.49
SRS #3 Ant E	18.36	18.50	18.82	18.73	18.97
SRS #4 Ant D	19.89	19.86	19.87	19.55	19.80

Table H-290

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth		
Channel		
Antenna	508200 (2541 MHz)	528996 (2644.98 MHz)
	Conducted Power [dBm]	
SRS #2 Ant B	17.03	17.42
SRS #3 Ant E	15.42	15.71
SRS #4 Ant D	16.84	16.66

Table H-291

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth		
Channel		
Antenna	507204 (2536.02 MHz)	529998 (2649.99 MHz)
	Conducted Power [dBm]	
SRS #2 Ant B	17.06	17.42
SRS #3 Ant E	15.40	15.75
SRS #4 Ant D	16.80	16.50

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 151 of 222

Table H-292
NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth		
Channel		
Antenna	506202 (2531.01 MHz)	531000 (2655 MHz)
	Conducted Power [dBm]	
SRS #2 Ant B	16.99	17.22
SRS #3 Ant E	15.27	15.78
SRS #4 Ant D	16.75	16.57

Table H-293
NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth			
Channel			
Antenna	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)
	Conducted Power [dBm]		
SRS #2 Ant B	16.95	17.05	17.49
SRS #3 Ant E	15.33	15.57	15.90
SRS #4 Ant D	16.84	16.79	16.77

Table H-294
NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth			
Channel			
Antenna	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)
	Conducted Power [dBm]		
SRS #2 Ant B	17.07	17.34	17.49
SRS #3 Ant E	15.53	15.93	15.97
SRS #4 Ant D	16.97	16.89	16.87

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 152 of 222

Table H-295
NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth				
Channel				
Antenna	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)
	Conducted Power [dBm]			
SRS #2 Ant B	17.34	17.47	17.46	17.49
SRS #3 Ant E	15.42	15.71	15.80	15.91
SRS #4 Ant D	17.08	17.09	16.76	16.87

Table H-296
NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth				
Channel				
Antenna	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)
	Conducted Power [dBm]			
SRS #2 Ant B	17.08	17.11	17.26	17.44
SRS #3 Ant E	15.45	15.63	15.76	15.91
SRS #4 Ant D	16.90	16.96	16.61	16.80

Table H-297
NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth					
Channel					
Antenna	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	17.20	17.36	17.37	17.24	17.49
SRS #3 Ant E	15.29	15.40	15.62	15.54	15.85
SRS #4 Ant D	16.79	16.85	16.76	16.50	16.70

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 153 of 222

Table H-298

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth					
Channel					
Antenna	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	16.79	17.03	17.21	17.30	17.46
SRS #3 Ant E	15.45	15.60	15.79	15.78	15.95
SRS #4 Ant D	16.88	16.97	16.92	16.54	16.72

Table H-299

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n41 25 MHz Bandwidth					
Channel					
Antenna	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	16.90	17.07	17.03	17.28	17.46
SRS #3 Ant E	15.39	15.53	15.76	15.69	15.94
SRS #4 Ant D	16.83	16.90	16.85	16.53	16.76

Table H-300

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth					
Channel					
Antenna	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	17.02	17.12	17.09	17.33	17.48
SRS #3 Ant E	15.29	15.49	15.72	15.58	15.99
SRS #4 Ant D	16.90	16.76	16.79	16.52	16.69

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 154 of 222

Table H-301

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth					
Channel					
Antenna	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	16.93	17.05	17.06	17.33	17.48
SRS #3 Ant E	15.28	15.55	15.75	15.67	15.96
SRS #4 Ant D	16.84	16.76	16.78	16.50	16.64

Table H-302

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth					
Channel					
Antenna	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	16.99	17.05	17.18	17.38	17.48
SRS #3 Ant E	15.34	15.44	15.79	15.69	15.99
SRS #4 Ant D	16.89	16.86	16.87	16.50	16.79

Table H-303

NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	508200 (2541 MHz)	528996 (2644.98 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	20.95	20.82	0	0.0
	1	123	20.70	20.74		0.0
	1	243	20.66	20.80		0.0
	120	0	20.70	20.61	0-1	0.0
	120	63	20.69	20.67	0	0.0
	120	125	20.77	20.74	0-1	0.0
	243	0	20.74	20.63		0.0
DFT-s-OFDM 16QAM	1	1	20.95	20.85	0-1	0.0
CP-OFDM QPSK	1	1	20.91	20.81	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 155 of 222

Table H-304
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	507204 (2536.02 MHz)	529998 (2649.99 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	20.92	20.60	0	0.0
	1	109	20.59	20.55		0.0
	1	215	20.65	20.63		0.0
	108	0	20.77	20.57	0-1	0.0
	108	55	20.65	20.61	0	0.0
	108	109	20.73	20.65	0-1	0.0
	216	0	20.71	20.53		0.0
DFT-s-OFDM 16QAM	1	1	20.77	20.54	0-1	0.0
CP-OFDM QPSK	1	1	20.93	20.63	0-1.5	0.0

Table H-305
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	506202 (2531.01 MHz)	531000 (2655 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	20.65	20.63	0	0.0
	1	95	20.45	20.71		0.0
	1	187	20.53	20.84		0.0
	90	0	20.62	20.65	0-1	0.0
	90	50	20.52	20.72	0	0.0
	90	99	20.61	20.77	0-1	0.0
	180	0	20.59	20.74		0.0
DFT-s-OFDM 16QAM	1	1	20.64	20.60	0-1	0.0
CP-OFDM OPSK	1	1	20.86	20.81	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 156 of 222

Table H-306
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.85	20.76	20.63	0	0.0
	1	81	20.59	20.63	20.59		0.0
	1	160	20.70	20.71	20.69		0.0
	81	0	20.78	20.72	20.61	0-1	0.0
	81	41	20.55	20.58	20.57	0	0.0
	81	81	20.69	20.65	20.73	0-1	0.0
	162	0	20.66	20.70	20.59		0.0
DFT-s-OFDM 16QAM	1	1	20.80	20.64	20.60	0-1	0.0
CP-OFDM QPSK	1	1	20.95	20.83	20.69	0-1.5	0.0

Table H-307
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.98	20.88	20.84	0	0.0
	1	67	20.84	20.80	20.87		0.0
	1	131	20.91	20.86	20.98		0.0
	64	0	20.95	20.87	20.96	0-1	0.0
	64	35	20.91	20.87	20.95	0	0.0
	64	69	20.98	20.94	20.95	0-1	0.0
	128	0	20.97	20.86	21.00		0.0
DFT-s-OFDM 16QAM	1	1	20.90	20.81	20.81	0-1	0.0
CP-OFDM QPSK	1	1	20.93	20.99	20.98	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 157 of 222

Table H-308
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	20.91	20.87	20.64	20.77	0	0.0
	1	60	20.64	20.64	20.44	20.78		0.0
	1	117	20.72	20.70	20.63	20.87		0.0
	54	0	20.85	20.72	20.61	20.65	0-1	0.0
	54	27	20.70	20.56	20.49	20.65	0	0.0
	54	54	20.73	20.66	20.58	20.75	0-1	0.0
	108	0	20.81	20.69	20.64	20.72		0.0
DFT-s-OFDM 16QAM	1	1	20.92	20.72	20.53	20.64	0-1	0.0
CP-OFDM QPSK	1	1	20.95	20.85	20.69	20.78	0-1.5	0.0

Table H-309
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	20.95	20.89	20.73	20.70	0	0.0
	1	53	20.86	20.87	20.76	20.77		0.0
	1	104	20.84	20.78	20.71	20.71		0.0
	50	0	20.96	20.98	20.78	20.77	0-1	0.0
	50	28	20.92	20.95	20.84	20.81	0	0.0
	50	56	20.95	20.89	20.77	20.83	0-1	0.0
	100	0	20.95	20.95	20.76	20.81		0.0
DFT-s-OFDM 16QAM	1	1	20.98	20.93	20.63	20.69	0-1	0.0
CP-OFDM QPSK	1	1	20.99	20.96	20.78	20.77	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 158 of 222

Table H-310
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	20.77	20.52	20.51	20.41	20.54	0	0.0
	1	46	20.76	20.60	20.55	20.52	20.59		0.0
	1	90	20.64	20.47	20.47	20.47	20.51		0.0
	45	0	20.82	20.63	20.58	20.44	20.49	0-1	0.0
	45	22	20.73	20.61	20.54	20.46	20.49	0	0.0
	45	45	20.69	20.59	20.53	20.49	20.53	0-1	0.0
	90	0	20.74	20.56	20.58	20.37	20.53		0.0
DFT-s-OFDM 16QAM	1	1	20.71	20.57	20.47	20.33	20.48	0-1	0.0
CP-OFDM QPSK	1	1	20.85	20.66	20.63	20.45	20.56	0-1.5	0.0

Table H-311
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	20.97	20.68	20.92	20.94	20.91	0	0.0
	1	39	20.94	20.83	20.82	20.84	20.88		0.0
	1	76	20.92	20.83	20.90	20.98	20.90		0.0
	36	0	20.96	20.81	20.83	20.83	20.86	0-1	0.0
	36	21	20.90	20.85	20.78	20.89	20.92	0	0.0
	36	42	20.91	20.89	20.85	20.89	20.97	0-1	0.0
	75	0	20.97	20.84	20.86	20.84	20.97		0.0
DFT-s-OFDM 16QAM	1	1	20.96	20.94	20.88	20.80	20.90	0-1	0.0
CP-OFDM QPSK	1	1	20.99	20.97	21.00	20.90	20.94	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 159 of 222

Table H-312
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 25 MHz Bandwidth

NR Band n41 25 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	20.99	20.80	20.81	20.61	20.76	0	0.0
	1	33	20.94	20.84	20.78	20.60	20.67		0.0
	1	63	20.82	20.73	20.75	20.61	20.64		0.0
	32	0	20.99	20.72	20.66	20.58	20.58	0-1	0.0
	32	17	20.94	20.74	20.57	20.50	20.55	0	0.0
	32	33	20.95	20.76	20.75	20.61	20.65	0-1	0.0
	64	0	20.98	20.70	20.69	20.60	20.67		0.0
DFT-s-OFDM 16QAM	1	1	20.98	20.67	20.70	20.58	20.70	0-1	0.0
CP-OFDM QPSK	1	1	21.00	20.77	20.80	20.66	20.72	0-1.5	0.0

Table H-313
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	20.79	20.41	20.64	20.46	20.56	0	0.0
	1	26	20.77	20.46	20.60	20.52	20.58		0.0
	1	49	20.71	20.42	20.63	20.63	20.53		0.0
	25	0	20.77	20.48	20.55	20.53	20.55	0-1	0.0
	25	13	20.71	20.48	20.54	20.51	20.56	0	0.0
	25	26	20.82	20.51	20.55	20.54	20.62	0-1	0.0
	50	0	20.78	20.54	20.60	20.56	20.55		0.0
DFT-s-OFDM 16QAM	1	1	20.73	20.46	20.56	20.47	20.51	0-1	0.0
CP-OFDM QPSK	1	1	20.85	20.55	20.66	20.56	20.55	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 160 of 222

Table H-314
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	20.75	20.55	20.61	20.62	20.51	0	0.0
	1	19	20.74	20.60	20.60	20.60	20.44		0.0
	1	36	20.75	20.61	20.63	20.57	20.56		0.0
	18	0	20.77	20.66	20.65	20.58	20.61	0-1	0.0
	18	10	20.73	20.66	20.65	20.55	20.57	0	0.0
	18	20	20.74	20.67	20.66	20.58	20.59	0-1	0.0
	36	0	20.71	20.59	20.50	20.52	20.54		0.0
DFT-s-OFDM 16QAM	1	1	20.78	20.49	20.51	20.50	20.59	0-1	0.0
CP-OFDM QPSK	1	1	20.86	20.57	20.62	20.62	20.63	0-1.5	0.0

Table H-315
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	20.74	20.52	20.60	20.60	20.49	0	0.0
	1	12	20.74	20.40	20.54	20.57	20.53		0.0
	1	22	20.76	20.52	20.61	20.60	20.61		0.0
	12	0	20.82	20.50	20.60	20.59	20.51	0-1	0.0
	12	6	20.76	20.45	20.54	20.52	20.54	0	0.0
	12	12	20.87	20.45	20.64	20.61	20.64	0-1	0.0
	24	0	20.82	20.49	20.48	20.53	20.47		0.0
DFT-s-OFDM 16QAM	1	1	20.79	20.50	20.54	20.50	20.59	0-1	0.0
CP-OFDM QPSK	1	1	20.88	20.53	20.67	20.57	20.54	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 161 of 222

Table H-316
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	508200 (2541 MHz)	528996 (2644.98 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	21.94	21.72	0	0.0
	1	123	21.67	21.77		0.0
	1	243	21.70	21.86		0.0
	120	0	21.78	21.67	0-1	0.0
	120	63	21.62	21.63	0	0.0
	120	125	21.72	21.74	0-1	0.0
	243	0	21.69	21.72		0.0
DFT-s-OFDM 16QAM	1	1	21.96	21.82	0-1	0.0
CP-OFDM QPSK	1	1	21.93	21.92	0-1.5	0.0

Table H-317
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	507204 (2536.02 MHz)	529998 (2649.99 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	21.90	21.72	0	0.0
	1	109	21.63	21.53		0.0
	1	215	21.76	21.63		0.0
	108	0	21.76	21.50	0-1	0.0
	108	55	21.72	21.61	0	0.0
	108	109	21.71	21.63	0-1	0.0
	216	0	21.81	21.58		0.0
DFT-s-OFDM 16QAM	1	1	21.86	21.50	0-1	0.0
CP-OFDM QPSK	1	1	21.97	21.54	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 162 of 222

Table H-318
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	506202 (2531.01 MHz)	531000 (2655 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	21.81	21.68	0	0.0
	1	95	21.57	21.66		0.0
	1	187	21.69	21.85		0.0
	90	0	21.77	21.68	0-1	0.0
	90	50	21.72	21.69	0	0.0
	90	99	21.78	21.74	0-1	0.0
	180	0	21.82	21.73		0.0
DFT-s-OFDM 16QAM	1	1	21.91	21.54	0-1	0.0
CP-OFDM QPSK	1	1	21.95	21.76	0-1.5	0.0

Table H-319
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	21.86	21.74	21.64	0	0.0
	1	81	21.66	21.61	21.57		0.0
	1	160	21.77	21.67	21.78		0.0
	81	0	21.83	21.70	21.67	0-1	0.0
	81	41	21.61	21.54	21.60	0	0.0
	81	81	21.77	21.66	21.74	0-1	0.0
	162	0	21.78	21.67	21.60		0.0
DFT-s-OFDM 16QAM	1	1	21.84	21.73	21.62	0-1	0.0
CP-OFDM OPSK	1	1	21.95	21.81	21.76	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 163 of 222

Table H-320
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	21.99	21.91	21.88	0	0.0
	1	67	21.94	21.80	21.85		0.0
	1	131	21.88	21.90	21.91		0.0
	64	0	21.94	21.92	21.98	0-1	0.0
	64	35	21.99	21.92	21.97	0	0.0
	64	69	21.92	21.87	21.99	0-1	0.0
	128	0	22.00	21.93	21.96		0.0
DFT-s-OFDM 16QAM	1	1	21.92	21.86	21.87	0-1	0.0
CP-OFDM QPSK	1	1	21.98	21.96	21.99	0-1.5	0.0

Table H-321
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	21.96	21.84	21.74	21.68	0	0.0
	1	60	21.77	21.64	21.56	21.72		0.0
	1	117	21.89	21.66	21.77	21.52		0.0
	54	0	21.96	21.71	21.65	21.68	0-1	0.0
	54	27	21.68	21.60	21.53	21.63	0	0.0
	54	54	21.81	21.65	21.60	21.74	0-1	0.0
	108	0	21.82	21.64	21.66	21.76		0.0
DFT-s-OFDM 16QAM	1	1	21.90	21.66	21.71	21.71	0-1	0.0
CP-OFDM QPSK	1	1	21.98	21.85	21.73	21.79	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 164 of 222

Table H-322
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)		
Conducted Power [dBm]								
DFT-s-OFDM QPSK	1	1	21.95	21.81	21.70	21.79	0	0.0
	1	53	21.90	21.82	21.70	21.72		0.0
	1	104	21.80	21.77	21.73	21.47		0.0
	50	0	21.95	21.92	21.72	21.88	0-1	0.0
	50	28	21.99	21.94	21.73	21.95	0	0.0
	50	56	21.91	21.92	21.75	21.99	0-1	0.0
	100	0	21.99	21.99	21.76	21.88		0.0
DFT-s-OFDM 16QAM	1	1	21.93	21.82	21.65	21.81	0-1	0.0
CP-OFDM QPSK	1	1	21.96	21.94	21.71	21.87	0-1.5	0.0

Table H-323
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	21.87	21.56	21.55	21.34	21.42	0	0.0
	1	46	21.80	21.73	21.56	21.47	21.55		0.0
	1	90	21.68	21.59	21.51	21.45	21.58		0.0
	45	0	21.89	21.64	21.54	21.48	21.45	0-1	0.0
	45	22	21.73	21.63	21.51	21.47	21.52	0	0.0
	45	45	21.78	21.60	21.52	21.49	21.54	0-1	0.0
	90	0	21.78	21.64	21.49	21.53	21.52		0.0
DFT-s-OFDM 16QAM	1	1	21.81	21.49	21.52	21.33	21.44	0-1	0.0
CP-OFDM QPSK	1	1	21.89	21.66	21.66	21.48	21.45	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 165 of 222

Table H-324

NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	21.93	21.86	21.97	21.91	21.95	0	0.0
	1	39	21.98	21.80	21.82	21.86	21.85		0.0
	1	76	21.97	21.81	21.92	21.98	21.72		0.0
	36	0	21.93	21.84	21.91	21.85	21.91	0-1	0.0
	36	21	21.92	21.77	21.87	21.83	21.95	0	0.0
	36	42	21.94	21.92	21.92	21.87	21.94	0-1	0.0
	75	0	21.99	21.86	21.88	21.90	21.99		0.0
DFT-s-OFDM 16QAM	1	1	21.96	21.91	21.97	21.87	21.64	0-1	0.0
CP-OFDM QPSK	1	1	21.99	21.95	21.99	21.96	21.59	0-1.5	0.0

Table H-325

NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n41 25 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	21.93	21.76	21.72	21.63	21.73	0	0.0
	1	33	21.95	21.88	21.70	21.57	21.74		0.0
	1	63	21.87	21.81	21.66	21.57	21.67		0.0
	32	0	21.91	21.77	21.72	21.50	21.67	0-1	0.0
	32	17	21.81	21.71	21.58	21.46	21.63	0	0.0
	32	33	21.85	21.78	21.61	21.65	21.70	0-1	0.0
	64	0	21.89	21.79	21.67	21.52	21.71		0.0
DFT-s-OFDM 16QAM	1	1	21.97	21.68	21.55	21.50	21.72	0-1	0.0
CP-OFDM QPSK	1	1	21.99	21.77	21.69	21.64	21.51	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 166 of 222

Table H-326

NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	21.67	21.46	21.51	21.55	21.53	0	0.0
	1	26	21.70	21.55	21.53	21.54	21.61		0.0
	1	49	21.64	21.54	21.57	21.59	21.60		0.0
	25	0	21.71	21.58	21.64	21.52	21.59	0-1	0.0
	25	13	21.68	21.57	21.51	21.48	21.48	0	0.0
	25	26	21.67	21.60	21.64	21.53	21.61	0-1	0.0
	50	0	21.74	21.65	21.56	21.57	21.54		0.0
DFT-s-OFDM 16QAM	1	1	21.75	21.47	21.50	21.44	21.50	0-1	0.0
CP-OFDM QPSK	1	1	21.87	21.55	21.61	21.59	21.60	0-1.5	0.0

Table H-327

NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	21.81	21.55	21.57	21.58	21.62	0	0.0
	1	19	21.72	21.59	21.54	21.54	21.57		0.0
	1	36	21.75	21.62	21.57	21.57	21.56		0.0
	18	0	21.87	21.69	21.62	21.60	21.55	0-1	0.0
	18	10	21.86	21.59	21.59	21.60	21.61	0	0.0
	18	20	21.83	21.69	21.58	21.62	21.61	0-1	0.0
	36	0	21.71	21.55	21.57	21.56	21.56		0.0
DFT-s-OFDM 16QAM	1	1	21.76	21.55	21.61	21.57	21.35	0-1	0.0
CP-OFDM QPSK	1	1	21.85	21.65	21.60	21.62	21.44	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 167 of 222

Table H-328
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	21.65	21.42	21.70	21.48	21.54	0	0.0
	1	12	21.66	21.47	21.54	21.54	21.52		0.0
	1	22	21.68	21.46	21.60	21.50	21.63		0.0
	12	0	21.71	21.48	21.60	21.58	21.59	0-1	0.0
	12	6	21.67	21.46	21.53	21.50	21.52	0	0.0
	12	12	21.74	21.44	21.61	21.59	21.68	0-1	0.0
	24	0	21.64	21.51	21.55	21.45	21.53		0.0
DFT-s-OFDM 16QAM	1	1	21.80	21.45	21.54	21.48	21.40	0-1	0.0
CP-OFDM QPSK	1	1	21.80	21.51	21.61	21.59	21.45	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 168 of 222

Table H-329

NR Band n41 PC2 Antenna F & D Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) and
 NR Band n41 PC2 Antenna E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) and P_{Limit}
 for DSI = 1 (Head) - 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth		
Channel		
Antenna	508200 (2541 MHz)	528996 (2644.98 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	20.05	19.59
SRS #3 Ant D	20.54	20.14
SRS #4 Ant E	17.82	17.32

Table H-330

NR Band n41 PC2 Antenna F & D Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) and
 NR Band n41 PC2 Antenna E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) and P_{Limit}
 for DSI = 1 (Head) - 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth		
Channel		
Antenna	507204 (2536.02 MHz)	529998 (2649.99 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	20.06	19.56
SRS #3 Ant D	20.54	20.17
SRS #4 Ant E	17.86	17.20

Table H-331

NR Band n41 PC2 Antenna F & D Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) and
 NR Band n41 PC2 Antenna E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) and P_{Limit}
 for DSI = 1 (Head) - 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth		
Channel		
Antenna	506202 (2531.01 MHz)	531000 (2655 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	20.05	19.73
SRS #3 Ant D	20.59	20.17
SRS #4 Ant E	17.86	17.02

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 169 of 222

Table H-332

NR Band n41 PC2 Antenna F & D Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) and
 NR Band n41 PC2 Antenna E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) and P_{Limit}
 for DSI = 1 (Head) - 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth			
Channel			
Antenna	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)
	Conducted Power [dBm]		
SRS #2 Ant F	19.97	19.95	19.70
SRS #3 Ant D	20.49	20.27	20.08
SRS #4 Ant E	17.86	18.10	17.65

Table H-333

NR Band n41 PC2 Antenna F & D Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) and
 NR Band n41 PC2 Antenna E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) and P_{Limit}
 for DSI = 1 (Head) - 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth			
Channel			
Antenna	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)
	Conducted Power [dBm]		
SRS #2 Ant F	20.21	20.20	20.00
SRS #3 Ant D	20.81	20.54	20.34
SRS #4 Ant E	18.11	18.28	17.78

Table H-334

NR Band n41 PC2 Antenna F & D Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) and
 NR Band n41 PC2 Antenna E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) and P_{Limit}
 for DSI = 1 (Head) - 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth				
Channel				
Antenna	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)
	Conducted Power [dBm]			
SRS #2 Ant F	20.14	20.25	19.91	19.89
SRS #3 Ant D	20.83	20.67	20.38	20.32
SRS #4 Ant E	18.05	18.22	18.28	17.78

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 170 of 222

Table H-335

NR Band n41 PC2 Antenna F & D Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) and
 NR Band n41 PC2 Antenna E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) and P_{Limit}
 for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth				
Channel				
Antenna	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)
	Conducted Power [dBm]			
SRS #2 Ant F	20.11	20.21	19.84	19.83
SRS #3 Ant D	20.66	20.54	20.25	20.20
SRS #4 Ant E	17.98	18.08	18.15	17.80

Table H-336

NR Band n41 PC2 Antenna F & D Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) and
 NR Band n41 PC2 Antenna E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) and P_{Limit}
 for DSI = 1 (Head) - 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth					
Channel					
Antenna	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	20.00	20.13	20.09	19.70	19.80
SRS #3 Ant D	20.72	20.62	20.47	20.22	20.19
SRS #4 Ant E	18.00	18.16	18.16	18.04	17.82

Table H-337

NR Band n41 PC2 Antenna F & D Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) and
 NR Band n41 PC2 Antenna E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) and P_{Limit}
 for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth					
Channel					
Antenna	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	20.03	20.16	20.07	19.66	19.85
SRS #3 Ant D	20.71	20.64	20.43	20.26	20.21
SRS #4 Ant E	18.00	18.13	18.17	18.19	17.74

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 171 of 222

Table H-338

NR Band n41 PC2 Antenna F & D Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) and
 NR Band n41 PC2 Antenna E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) and P_{Limit}
 for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n41 25 MHz Bandwidth					
Channel					
Antenna	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	20.04	20.14	20.06	19.65	19.70
SRS #3 Ant D	20.71	20.61	20.43	20.22	20.18
SRS #4 Ant E	17.97	18.11	18.18	18.23	17.75

Table H-339

NR Band n41 PC2 Antenna F & D Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) and
 NR Band n41 PC2 Antenna E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) and P_{Limit}
 for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth					
Channel					
Antenna	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	20.02	20.10	20.01	19.60	19.74
SRS #3 Ant D	20.57	20.59	20.32	20.09	20.05
SRS #4 Ant E	17.85	18.17	18.24	18.16	17.67

Table H-340

NR Band n41 PC2 Antenna F & D Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) and
 NR Band n41 PC2 Antenna E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) and P_{Limit}
 for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth					
Channel					
Antenna	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	20.00	20.06	20.03	19.60	19.75
SRS #3 Ant D	20.63	20.49	20.32	20.12	20.06
SRS #4 Ant E	17.92	18.16	18.20	18.16	17.79

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 172 of 222

Table H-341

NR Band n41 PC2 Antenna F & D Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) and
 NR Band n41 PC2 Antenna E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) and P_{Limit}
 for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth					
Channel					
Antenna	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	20.04	20.09	20.04	19.64	19.76
SRS #3 Ant D	20.67	20.54	20.27	20.06	20.03
SRS #4 Ant E	17.88	18.12	18.17	18.11	17.77

Table H-342

NR Band n41 PC2 Antenna F & D Path 2 Measured P_{Limit} for DSI = 1 (Head) - 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth		
Channel		
Antenna	508200 (2541 MHz)	528996 (2644.98 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	17.00	16.59
SRS #3 Ant D	21.54	21.13

Table H-343

NR Band n41 PC2 Antenna F & D Path 2 Measured P_{Limit} for DSI = 1 (Head) - 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth		
Channel		
Antenna	507204 (2536.02 MHz)	529998 (2649.99 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	17.00	16.64
SRS #3 Ant D	21.56	21.13

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 173 of 222

Table H-344

NR Band n41 PC2 Antenna F & D Path 2 Measured P_{Limit} for DSI = 1 (Head) - 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth		
Channel		
Antenna	506202 (2531.01 MHz)	531000 (2655 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	16.99	16.65
SRS #3 Ant D	21.57	21.19

Table H-345

NR Band n41 PC2 Antenna F & D Path 2 Measured P_{Limit} for DSI = 1 (Head) - 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth			
Channel			
Antenna	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)
	Conducted Power [dBm]		
SRS #2 Ant F	16.95	16.91	16.66
SRS #3 Ant D	21.52	21.27	21.11

Table H-346

NR Band n41 PC2 Antenna F & D Path 2 Measured P_{Limit} for DSI = 1 (Head) - 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth			
Channel			
Antenna	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)
	Conducted Power [dBm]		
SRS #2 Ant F	17.17	17.18	16.92
SRS #3 Ant D	21.79	21.52	21.34

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 174 of 222

Table H-347

NR Band n41 PC2 Antenna F & D Path 2 Measured P_{Limit} for DSI = 1 (Head) - 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth				
Channel				
Antenna	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)
	Conducted Power [dBm]			
SRS #2 Ant F	17.13	17.29	16.91	16.87
SRS #3 Ant D	21.84	21.66	21.39	21.34

Table H-348

NR Band n41 PC2 Antenna F & D Path 2 Measured P_{Limit} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth				
Channel				
Antenna	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)
	Conducted Power [dBm]			
SRS #2 Ant F	17.10	17.18	16.79	16.81
SRS #3 Ant D	21.68	21.57	21.27	21.23

Table H-349

NR Band n41 PC2 Antenna F & D Path 2 Measured P_{Limit} for DSI = 1 (Head) - 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth					
Channel					
Antenna	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	16.99	17.10	17.06	16.70	16.83
SRS #3 Ant D	21.67	21.67	21.49	21.24	21.17

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 175 of 222

Table H-350

NR Band n41 PC2 Antenna F & D Path 2 Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth					
Channel					
Antenna	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	16.97	17.17	17.02	16.65	16.85
SRS #3 Ant D	21.72	21.67	21.42	21.25	21.19

Table H-351

NR Band n41 PC2 Antenna F & D Path 2 Measured P_{Limit} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n41 25 MHz Bandwidth					
Channel					
Antenna	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	17.05	17.11	17.05	16.61	16.77
SRS #3 Ant D	21.75	21.61	21.42	21.21	21.19

Table H-352

NR Band n41 PC2 Antenna F & D Path 2 Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth					
Channel					
Antenna	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	16.97	17.08	16.96	16.53	16.73
SRS #3 Ant D	21.62	21.61	21.35	21.11	21.07

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 176 of 222

Table H-353

NR Band n41 PC2 Antenna F & D Path 2 Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth					
Channel					
Antenna	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	16.99	17.05	16.91	16.56	16.76
SRS #3 Ant D	21.61	21.53	21.33	21.14	21.09

Table H-354

NR Band n41 PC2 Antenna F & D Path 2 Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth					
Channel					
Antenna	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	17.04	17.02	16.97	16.56	16.75
SRS #3 Ant D	21.69	21.54	21.30	21.08	21.09

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 177 of 222

H.2.11 NR Band n48

Table H-355

NR Band n48 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n48 30 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637668 (3565.02 MHz)	640334 (3605.01 MHz)	643000 (3645 MHz)	645666 (3684.99 MHz)		
Conducted Power [dBm]								
DFT-s-OFDM QPSK	1	1	20.33	20.34	20.42	20.38	0	0.0
	1	39	20.34	20.23	20.20	20.25		0.0
	1	76	20.46	20.23	20.25	20.40		0.0
	36	0	20.39	20.27	20.37	20.38	0-1	0.0
	36	21	20.41	20.25	20.27	20.33	0	0.0
	36	42	20.48	20.24	20.25	20.34	0-1	0.0
	75	0	20.43	20.30	20.24	20.35		0.0
DFT-s-OFDM 16QAM	1	1	20.36	20.36	20.44	20.40	0-1	0.0
CP-OFDM QPSK	1	1	20.34	20.30	20.36	20.37	0-1.5	0.0

Table H-356

NR Band n48 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n48 20 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637334 (3560.01 MHz)	640222 (3603.33 MHz)	643112 (3646.68 MHz)	646000 (3690 MHz)		
Conducted Power [dBm]								
DFT-s-OFDM QPSK	1	1	20.06	20.04	20.07	20.11	0	0.0
	1	26	20.16	19.99	20.00	20.12		0.0
	1	49	20.23	20.02	19.96	20.05		0.0
	25	0	20.09	20.06	20.10	20.20	0-1	0.0
	25	13	20.15	20.01	20.04	20.18	0	0.0
	25	26	20.25	19.98	20.03	20.16	0-1	0.0
	50	0	20.17	20.03	19.97	20.19		0.0
DFT-s-OFDM 16QAM	1	1	20.07	20.15	20.08	20.23	0-1	0.0
CP-OFDM QPSK	1	1	20.08	20.09	20.07	20.22	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 178 of 222

Table H-357

NR Band n48 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n48 15 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637168 (3557.52 MHz)	640166 (3602.49 MHz)	643166 (3647.49 MHz)	646166 (3692.49 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	20.26	20.19	20.19	20.26	0	0.0
	1	19	20.23	20.09	20.01	20.19		0.0
	1	36	20.37	20.09	20.05	20.23		0.0
	18	0	20.28	20.18	20.06	20.29	0-1	0.0
	18	10	20.29	20.11	20.05	20.28	0	0.0
	18	20	20.37	20.12	20.11	20.25	0-1	0.0
	36	0	20.30	20.17	20.07	20.27		0.0
DFT-s-OFDM 16QAM	1	1	20.32	20.23	20.22	20.42	0-1	0.0
CP-OFDM QPSK	1	1	20.24	20.19	20.17	20.36	0-1.5	0.0

Table H-358

NR Band n48 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n48 10 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637000 (3555 MHz)	640112 (3601.68 MHz)	643222 (3648.33 MHz)	646332 (3694.98 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	20.34	20.25	20.26	20.36	0	0.0
	1	12	20.35	20.29	20.18	20.41		0.0
	1	22	20.43	20.27	20.21	20.36		0.0
	12	0	20.35	20.31	20.25	20.36	0-1	0.0
	12	6	20.32	20.18	20.18	20.29	0	0.0
	12	12	20.30	20.24	20.21	20.39	0-1	0.0
	24	0	20.29	20.16	20.26	20.37		0.0
DFT-s-OFDM 16QAM	1	1	20.36	20.34	20.40	20.47	0-1	0.0
CP-OFDM QPSK	1	1	20.35	20.30	20.35	20.45	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 179 of 222

Table H-359
NR Band n48 Ant F Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n48 30 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637668 (3565.02 MHz)	640334 (3605.01 MHz)	643000 (3645 MHz)	645666 (3684.99 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	16.76	16.88	16.87	16.76	0	0.0
	1	39	16.89	16.69	16.66	16.81		0.0
	1	76	16.97	16.73	16.66	16.98		0.0
	36	0	16.89	16.79	16.77	16.86	0-1	0.0
	36	21	16.89	16.69	16.75	16.78	0	0.0
	36	42	16.95	16.71	16.66	16.80	0-1	0.0
	75	0	16.93	16.74	16.76	16.81		0.0
DFT-s-OFDM 16QAM	1	1	16.83	16.90	16.88	16.85	0-1	0.0
CP-OFDM QPSK	1	1	16.83	16.83	16.88	16.87	0-1.5	0.0

Table H-360
NR Band n48 Ant F Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n48 20 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637334 (3560.01 MHz)	640222 (3603.33 MHz)	643112 (3646.68 MHz)	646000 (3690 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	16.57	16.50	16.53	16.58	0	0.0
	1	26	16.77	16.50	16.36	16.58		0.0
	1	49	16.82	16.44	16.39	16.53		0.0
	25	0	16.80	16.57	16.46	16.61	0-1	0.0
	25	13	16.86	16.51	16.51	16.62	0	0.0
	25	26	16.88	16.54	16.46	16.60	0-1	0.0
	50	0	16.82	16.53	16.52	16.60		0.0
DFT-s-OFDM 16QAM	1	1	16.75	16.61	16.52	16.67	0-1	0.0
CP-OFDM QPSK	1	1	16.72	16.52	16.53	16.62	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 180 of 222

Table H-361
NR Band n48 Ant F Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n48 15 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637168 (3557.52 MHz)	640166 (3602.49 MHz)	643166 (3647.49 MHz)	646166 (3692.49 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	16.75	16.70	16.68	16.71	0	0.0
	1	19	16.78	16.56	16.50	16.60		0.0
	1	36	16.87	16.63	16.46	16.62		0.0
	18	0	16.73	16.64	16.60	16.71	0-1	0.0
	18	10	16.84	16.57	16.54	16.67	0	0.0
	18	20	16.84	16.60	16.52	16.69	0-1	0.0
	36	0	16.81	16.61	16.49	16.67		0.0
DFT-s-OFDM 16QAM	1	1	16.77	16.72	16.61	16.79	0-1	0.0
CP-OFDM QPSK	1	1	16.76	16.65	16.68	16.76	0-1.5	0.0

Table H-362
NR Band n48 Ant F Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n48 10 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637000 (3555 MHz)	640112 (3601.68 MHz)	643222 (3648.33 MHz)	646332 (3694.98 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	16.82	16.67	16.84	16.96	0	0.0
	1	12	16.84	16.61	16.70	16.87		0.0
	1	22	16.88	16.59	16.71	16.89		0.0
	12	0	16.80	16.63	16.73	16.84	0-1	0.0
	12	6	16.78	16.65	16.68	16.74	0	0.0
	12	12	16.84	16.72	16.64	16.82	0-1	0.0
	24	0	16.80	16.74	16.71	16.73		0.0
DFT-s-OFDM 16QAM	1	1	16.76	16.83	16.81	16.91	0-1	0.0
CP-OFDM QPSK	1	1	16.82	16.83	16.82	16.86	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 181 of 222

Table H-363
NR Band n48 Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 30 MHz Bandwidth

NR Band n48 30 MHz Bandwidth				
Channel				
Antenna	637668 (3565.02 MHz)	640334 (3605.01 MHz)	643000 (3645 MHz)	645666 (3684.99 MHz)
	Conducted Power [dBm]			
SRS #2 Ant C	15.48	15.44	15.18	15.19
SRS #3 Ant I	19.48	19.45	19.51	19.52
SRS #4 Ant D	15.00	14.97	15.07	15.16

Table H-364
NR Band n48 Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 20 MHz Bandwidth

NR Band n48 20 MHz Bandwidth				
Channel				
Antenna	637334 (3560.01 MHz)	640222 (3603.33 MHz)	643112 (3646.68 MHz)	646000 (3690 MHz)
	Conducted Power [dBm]			
SRS #2 Ant C	15.44	15.39	15.17	15.12
SRS #3 Ant I	19.46	19.52	19.46	19.35
SRS #4 Ant D	14.98	14.93	15.03	15.02

Table H-365
NR Band n48 Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 15 MHz Bandwidth

NR Band n48 15 MHz Bandwidth				
Channel				
Antenna	637168 (3557.52 MHz)	640166 (3602.49 MHz)	643166 (3647.49 MHz)	646166 (3692.49 MHz)
	Conducted Power [dBm]			
SRS #2 Ant C	15.46	15.43	15.15	15.12
SRS #3 Ant I	19.42	19.49	19.53	19.33
SRS #4 Ant D	15.00	14.97	15.02	15.09

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 182 of 222

Table H-366
NR Band n48 Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 10 MHz Bandwidth

NR Band n48 10 MHz Bandwidth				
Channel				
Antenna	637000 (3555 MHz)	640112 (3601.68 MHz)	643222 (3648.33 MHz)	646332 (3694.98 MHz)
	Conducted Power [dBm]			
SRS #2 Ant C	15.48	15.40	15.07	15.14
SRS #3 Ant I	19.52	19.50	19.40	19.35
SRS #4 Ant D	15.02	14.99	15.00	15.07

Table H-367
NR Band n48 Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n48 30 MHz Bandwidth				
Channel				
Antenna	637668 (3565.02 MHz)	640334 (3605.01 MHz)	643000 (3645 MHz)	645666 (3684.99 MHz)
	Conducted Power [dBm]			
SRS #2 Ant C	11.98	11.71	11.65	11.65
SRS #3 Ant I	15.98	15.91	15.88	15.96
SRS #4 Ant D	11.46	11.44	11.58	11.62

Table H-368
NR Band n48 Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n48 20 MHz Bandwidth				
Channel				
Antenna	637334 (3560.01 MHz)	640222 (3603.33 MHz)	643112 (3646.68 MHz)	646000 (3690 MHz)
	Conducted Power [dBm]			
SRS #2 Ant C	11.99	11.72	11.57	11.56
SRS #3 Ant I	15.90	15.96	15.90	15.77
SRS #4 Ant D	11.46	11.42	11.53	11.46

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 183 of 222

Table H-369

NR Band n48 Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n48 15 MHz Bandwidth				
Channel				
Antenna	637168 (3557.52 MHz)	640166 (3602.49 MHz)	643166 (3647.49 MHz)	646166 (3692.49 MHz)
	Conducted Power [dBm]			
SRS #2 Ant C	11.98	11.77	11.56	11.61
SRS #3 Ant I	15.86	15.91	15.85	15.77
SRS #4 Ant D	11.48	11.42	11.49	11.53

Table H-370

NR Band n48 Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n48 10 MHz Bandwidth				
Channel				
Antenna	637000 (3555 MHz)	640112 (3601.68 MHz)	643222 (3648.33 MHz)	646332 (3694.98 MHz)
	Conducted Power [dBm]			
SRS #2 Ant C	11.97	11.72	11.59	11.52
SRS #3 Ant I	15.89	15.96	15.84	15.87
SRS #4 Ant D	11.53	11.44	11.42	11.55

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 184 of 222

H.2.12 NR Band n77

Table H-371
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 90 MHz Bandwidth

NR Band n77 DoD 90 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.72	0	0.0
	1	123	18.69		0.0
	1	243	18.99		0.0
	120	0	18.72	0-1	0.0
	120	63	18.69	0	0.0
	120	125	18.87	0-1	0.0
	243	0	18.68		0.0
DFT-s-OFDM 16QAM	1	1	18.77	0-1	0.0
CP-OFDM QPSK	1	1	18.86	0-1.5	0.0

Table H-372
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 80 MHz Bandwidth

NR Band n77 DoD 80 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.62	0	0.0
	1	109	18.56		0.0
	1	215	18.77		0.0
	108	0	18.71	0-1	0.0
	108	55	18.62	0	0.0
	108	109	18.72	0-1	0.0
	216	0	18.67		0.0
DFT-s-OFDM 16QAM	1	1	18.63	0-1	0.0
CP-OFDM QPSK	1	1	18.66	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 185 of 222

Table H-373
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 70 MHz Bandwidth

NR Band n77 DoD 70 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.58	0	0.0
	1	95	18.57		0.0
	1	187	18.71		0.0
	90	0	18.66	0-1	0.0
	90	50	18.62	0	0.0
	90	99	18.68	0-1	0.0
	180	0	18.67		0.0
DFT-s-OFDM 16QAM	1	1	18.60	0-1	0.0
CP-OFDM QPSK	1	1	18.72	0-1.5	0.0

Table H-374
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 60 MHz Bandwidth

NR Band n77 DoD 60 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.53	0	0.0
	1	81	18.47		0.0
	1	160	18.65		0.0
	81	0	18.65	0-1	0.0
	81	41	18.54	0	0.0
	81	81	18.60	0-1	0.0
	162	0	18.54		0.0
DFT-s-OFDM 16QAM	1	1	18.57	0-1	0.0
CP-OFDM QPSK	1	1	18.62	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 186 of 222

Table H-375
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 50 MHz Bandwidth

NR Band n77 DoD 50 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.81	0	0.0
	1	67	18.80		0.0
	1	131	18.78		0.0
	64	0	18.92	0-1	0.0
	64	35	18.82	0	0.0
	64	69	18.84	0-1	0.0
	128	0	18.84		0.0
DFT-s-OFDM 16QAM	1	1	18.70	0-1	0.0
CP-OFDM QPSK	1	1	18.83	0-1.5	0.0

Table H-376
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 40 MHz Bandwidth

NR Band n77 DoD 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.58	0	0.0
	1	53	18.68		0.0
	1	104	18.63		0.0
	50	0	18.72	0-1	0.0
	50	28	18.73	0	0.0
	50	56	18.65	0-1	0.0
	100	0	18.66		0.0
DFT-s-OFDM 16QAM	1	1	18.56	0-1	0.0
CP-OFDM QPSK	1	1	18.73	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 187 of 222

Table H-377
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 30 MHz Bandwidth

NR Band n77 DoD 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.63	0	0.0
	1	39	18.68		0.0
	1	76	18.75		0.0
	36	0	18.68	0-1	0.0
	36	21	18.58	0	0.0
	36	42	18.65	0-1	0.0
	75	0	18.68		0.0
DFT-s-OFDM 16QAM	1	1	18.67	0-1	0.0
CP-OFDM QPSK	1	1	18.78	0-1.5	0.0

Table H-378
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 25 MHz Bandwidth

NR Band n77 DoD 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.61	0	0.0
	1	33	18.70		0.0
	1	63	18.70		0.0
	32	0	18.66	0-1	0.0
	32	17	18.55	0	0.0
	32	33	18.74	0-1	0.0
	64	0	18.72		0.0
DFT-s-OFDM 16QAM	1	1	18.72	0-1	0.0
CP-OFDM QPSK	1	1	18.79	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 188 of 222

Table H-379
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 20 MHz Bandwidth

NR Band n77 DoD 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.63	0	0.0
	1	26	18.62		0.0
	1	49	18.67		0.0
	25	0	18.64	0-1	0.0
	25	13	18.54	0	0.0
	25	26	18.66	0-1	0.0
	50	0	18.64		0.0
DFT-s-OFDM 16QAM	1	1	18.64	0-1	0.0
CP-OFDM QPSK	1	1	18.72	0-1.5	0.0

Table H-380
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 15 MHz Bandwidth

NR Band n77 DoD 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.47	0	0.0
	1	19	18.51		0.0
	1	36	18.58		0.0
	18	0	18.61	0-1	0.0
	18	10	18.59	0	0.0
	18	20	18.68	0-1	0.0
	36	0	18.60		0.0
DFT-s-OFDM 16QAM	1	1	18.55	0-1	0.0
CP-OFDM QPSK	1	1	18.67	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 189 of 222

Table H-381
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 10 MHz Bandwidth

NR Band n77 DoD 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.68	0	0.0
	1	12	18.58		0.0
	1	22	18.72		0.0
	12	0	18.67	0-1	0.0
	12	6	18.57	0	0.0
	12	12	18.64	0-1	0.0
	24	0	18.57		0.0
DFT-s-OFDM 16QAM	1	1	18.65	0-1	0.0
CP-OFDM QPSK	1	1	18.69	0-1.5	0.0

Table H-382
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 1 (Head) - 90 MHz Bandwidth

NR Band n77 DoD 90 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.72	0	0.0
	1	123	16.63		0.0
	1	243	16.94		0.0
	120	0	16.62	0-1	0.0
	120	63	16.63	0	0.0
	120	125	16.74	0-1	0.0
	243	0	16.67		0.0
DFT-s-OFDM 16QAM	1	1	16.75	0-1	0.0
CP-OFDM QPSK	1	1	16.73	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 190 of 222

Table H-383
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 1 (Head) - 80 MHz Bandwidth

NR Band n77 DoD 80 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.66	0	0.0
	1	109	16.56		0.0
	1	215	16.69		0.0
	108	0	16.57	0-1	0.0
	108	55	16.58	0	0.0
	108	109	16.64	0-1	0.0
	216	0	16.60		0.0
DFT-s-OFDM 16QAM	1	1	16.60	0-1	0.0
CP-OFDM QPSK	1	1	16.65	0-1.5	0.0

Table H-384
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 1 (Head) - 70 MHz Bandwidth

NR Band n77 DoD 70 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.63	0	0.0
	1	95	16.57		0.0
	1	187	16.70		0.0
	90	0	16.58	0-1	0.0
	90	50	16.55	0	0.0
	90	99	16.59	0-1	0.0
	180	0	16.60		0.0
DFT-s-OFDM 16QAM	1	1	16.60	0-1	0.0
CP-OFDM QPSK	1	1	16.63	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 191 of 222

Table H-385
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 1 (Head) - 60 MHz Bandwidth

NR Band n77 DoD 60 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.59	0	0.0
	1	81	16.57		0.0
	1	160	16.65		0.0
	81	0	16.62	0-1	0.0
	81	41	16.48	0	0.0
	81	81	16.56	0-1	0.0
	162	0	16.55		0.0
DFT-s-OFDM 16QAM	1	1	16.58	0-1	0.0
CP-OFDM QPSK	1	1	16.60	0-1.5	0.0

Table H-386
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 1 (Head) - 50 MHz Bandwidth

NR Band n77 DoD 50 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.78	0	0.0
	1	67	16.81		0.0
	1	131	16.90		0.0
	64	0	16.85	0-1	0.0
	64	35	16.84	0	0.0
	64	69	16.87	0-1	0.0
	128	0	16.84		0.0
DFT-s-OFDM 16QAM	1	1	16.76	0-1	0.0
CP-OFDM QPSK	1	1	16.87	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 192 of 222

Table H-387
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n77 DoD 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.64	0	0.0
	1	53	16.65		0.0
	1	104	16.70		0.0
	50	0	16.65	0-1	0.0
	50	28	16.64	0	0.0
	50	56	16.60	0-1	0.0
	100	0	16.57		0.0
DFT-s-OFDM 16QAM	1	1	16.70	0-1	0.0
CP-OFDM QPSK	1	1	16.67	0-1.5	0.0

Table H-388
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n77 DoD 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.62	0	0.0
	1	39	16.58		0.0
	1	76	16.64		0.0
	36	0	16.59	0-1	0.0
	36	21	16.60	0	0.0
	36	42	16.64	0-1	0.0
	75	0	16.62		0.0
DFT-s-OFDM 16QAM	1	1	16.71	0-1	0.0
CP-OFDM QPSK	1	1	16.70	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 193 of 222

Table H-389
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n77 DoD 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.67	0	0.0
	1	33	16.65		0.0
	1	63	16.72		0.0
	32	0	16.63	0-1	0.0
	32	17	16.64	0	0.0
	32	33	16.69	0-1	0.0
	64	0	16.67		0.0
DFT-s-OFDM 16QAM	1	1	16.78	0-1	0.0
CP-OFDM QPSK	1	1	16.71	0-1.5	0.0

Table H-390
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n77 DoD 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.55	0	0.0
	1	26	16.57		0.0
	1	49	16.62		0.0
	25	0	16.52	0-1	0.0
	25	13	16.57	0	0.0
	25	26	16.58	0-1	0.0
	50	0	16.57		0.0
DFT-s-OFDM 16QAM	1	1	16.66	0-1	0.0
CP-OFDM QPSK	1	1	16.61	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 194 of 222

Table H-391
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n77 DoD 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.59	0	0.0
	1	19	16.61		0.0
	1	36	16.64		0.0
	18	0	16.57	0-1	0.0
	18	10	16.57	0	0.0
	18	20	16.60	0-1	0.0
	36	0	16.59		0.0
DFT-s-OFDM 16QAM	1	1	16.62	0-1	0.0
CP-OFDM QPSK	1	1	16.60	0-1.5	0.0

Table H-392
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n77 DoD 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.63	0	0.0
	1	12	16.56		0.0
	1	22	16.60		0.0
	12	0	16.58	0-1	0.0
	12	6	16.61	0	0.0
	12	12	16.60	0-1	0.0
	24	0	16.61		0.0
DFT-s-OFDM 16QAM	1	1	16.69	0-1	0.0
CP-OFDM QPSK	1	1	16.65	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 195 of 222

Table H-393

NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 90 MHz Bandwidth

NR Band n77 DoD 90 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	17.95
SRS #3 Ant I	17.94
SRS #4 Ant D	13.45

Table H-394

NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 80 MHz Bandwidth

NR Band n77 DoD 80 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	17.92
SRS #3 Ant I	17.95
SRS #4 Ant D	13.49

Table H-395

NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 70 MHz Bandwidth

NR Band n77 DoD 70 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	17.95
SRS #3 Ant I	17.96
SRS #4 Ant D	13.51

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 196 of 222

Table H-396

NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 60 MHz Bandwidth

NR Band n77 DoD 60 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	17.81
SRS #3 Ant I	17.80
SRS #4 Ant D	13.34

Table H-397

NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 50 MHz Bandwidth

NR Band n77 DoD 50 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	17.98
SRS #3 Ant I	18.02
SRS #4 Ant D	13.60

Table H-398

NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 40 MHz Bandwidth

NR Band n77 DoD 40 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	17.95
SRS #3 Ant I	17.94
SRS #4 Ant D	13.49

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 197 of 222

Table H-399
NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n77 DoD 30 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	17.96
SRS #3 Ant I	17.93
SRS #4 Ant D	13.45

Table H-400
NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 25 MHz Bandwidth

NR Band n77 DoD 25 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	17.96
SRS #3 Ant I	18.04
SRS #4 Ant D	13.51

Table H-401
NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n77 DoD 20 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	17.88
SRS #3 Ant I	17.96
SRS #4 Ant D	13.38

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 198 of 222

Table H-402

NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n77 DoD 15 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	17.96
SRS #3 Ant I	17.97
SRS #4 Ant D	13.43

Table H-403

NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n77 DoD 10 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	17.98
SRS #3 Ant I	17.89
SRS #4 Ant D	13.44

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 199 of 222

Table H-404
NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 90 MHz Bandwidth

NR Band n77 DoD 90 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	21.44
SRS #3 Ant I	15.64
SRS #4 Ant D	11.17

Table H-405
NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 80 MHz Bandwidth

NR Band n77 DoD 80 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	21.46
SRS #3 Ant I	15.68
SRS #4 Ant D	11.17

Table H-406
NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 70 MHz Bandwidth

NR Band n77 DoD 70 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	21.44
SRS #3 Ant I	15.61
SRS #4 Ant D	11.23

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 200 of 222

Table H-407
NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 60 MHz Bandwidth

NR Band n77 DoD 60 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	21.41
SRS #3 Ant I	15.56
SRS #4 Ant D	11.01

Table H-408
NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 50 MHz Bandwidth

NR Band n77 DoD 50 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	21.67
SRS #3 Ant I	15.85
SRS #4 Ant D	11.30

Table H-409
NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n77 DoD 40 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	21.59
SRS #3 Ant I	15.63
SRS #4 Ant D	11.18

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 201 of 222

Table H-410
NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n77 DoD 30 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	21.54
SRS #3 Ant I	15.63
SRS #4 Ant D	11.20

Table H-411
NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n77 DoD 25 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	21.61
SRS #3 Ant I	15.59
SRS #4 Ant D	11.21

Table H-412
NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n77 DoD 20 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	21.47
SRS #3 Ant I	15.48
SRS #4 Ant D	11.09

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 202 of 222

Table H-413
NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n77 DoD 15 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	21.54
SRS #3 Ant I	15.50
SRS #4 Ant D	11.06

Table H-414
NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n77 DoD 10 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	21.56
SRS #3 Ant I	15.54
SRS #4 Ant D	11.12

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 203 of 222

Table H-415
NR Band n77 Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 90 MHz Bandwidth

NR Band n77 90 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.59	18.85	0	0.0
	1	123	18.61	18.92		0.0
	1	243	18.61	18.95		0.0
	120	0	18.61	18.93	0-1	0.0
	120	63	18.55	18.92	0	0.0
	120	125	18.54	18.91	0-1	0.0
	243	0	18.57	18.83		0.0
DFT-s-OFDM 16QAM	1	1	18.60	18.93	0-1	0.0
CP-OFDM QPSK	1	1	18.77	18.98	0-1.5	0.0

Table H-416
NR Band n77 Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 80 MHz Bandwidth

NR Band n77 80 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.32	18.61	0	0.0
	1	109	18.25	18.79		0.0
	1	215	18.48	18.94		0.0
	108	0	18.30	18.81	0-1	0.0
	108	55	18.33	18.91	0	0.0
	108	109	18.30	18.95	0-1	0.0
	216	0	18.38	18.82		0.0
DFT-s-OFDM 16QAM	1	1	18.33	18.60	0-1	0.0
CP-OFDM QPSK	1	1	18.37	18.81	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 204 of 222

Table H-417
NR Band n77 Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 70 MHz Bandwidth

NR Band n77 70 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.40	18.75	0	0.0
	1	95	18.28	18.88		0.0
	1	187	18.38	18.98		0.0
	90	0	18.40	18.92	0-1	0.0
	90	50	18.34	18.94	0	0.0
	90	99	18.35	18.93	0-1	0.0
	180	0	18.41	18.93		0.0
DFT-s-OFDM 16QAM	1	1	18.24	18.77	0-1	0.0
CP-OFDM QPSK	1	1	18.37	18.91	0-1.5	0.0

Table H-418
NR Band n77 Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 60 MHz Bandwidth

NR Band n77 60 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.19	18.62	0	0.0
	1	81	18.14	18.81		0.0
	1	160	18.32	18.92		0.0
	81	0	18.21	18.77	0-1	0.0
	81	41	18.10	18.75	0	0.0
	81	81	18.27	18.85	0-1	0.0
	162	0	18.23	18.82		0.0
DFT-s-OFDM 16QAM	1	1	18.24	18.72	0-1	0.0
CP-OFDM OPSK	1	1	18.42	18.87	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 205 of 222

Table H-419
NR Band n77 Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 50 MHz Bandwidth

NR Band n77 50 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.25	18.87	0	0.0
	1	67	18.38	18.98		0.0
	1	131	18.42	18.94		0.0
	64	0	18.44	18.96	0-1	0.0
	64	35	18.45	18.99	0	0.0
	64	69	18.50	18.97	0-1	0.0
	128	0	18.40	18.98		0.0
DFT-s-OFDM 16QAM	1	1	18.34	18.92	0-1	0.0
CP-OFDM QPSK	1	1	18.44	18.99	0-1.5	0.0

Table H-420
NR Band n77 Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 40 MHz Bandwidth

NR Band n77 40 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.29	18.73	0	0.0
	1	53	18.33	18.93		0.0
	1	104	18.36	18.95		0.0
	50	0	18.30	18.85	0-1	0.0
	50	28	18.29	18.98	0	0.0
	50	56	18.30	18.96	0-1	0.0
	100	0	18.25	18.97		0.0
DFT-s-OFDM 16QAM	1	1	18.17	18.70	0-1	0.0
CP-OFDM OPSK	1	1	18.34	18.78	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 206 of 222

Table H-421
NR Band n77 Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 30 MHz Bandwidth

NR Band n77 30 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.23	18.84	0	0.0
	1	39	18.14	18.88		0.0
	1	76	18.23	18.98		0.0
	36	0	18.15	18.95	0-1	0.0
	36	21	18.19	18.89	0	0.0
	36	42	18.15	18.96	0-1	0.0
	75	0	18.21	18.97		0.0
DFT-s-OFDM 16QAM	1	1	18.18	18.85	0-1	0.0
CP-OFDM QPSK	1	1	18.28	18.94	0-1.5	0.0

Table H-422
NR Band n77 Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 25 MHz Bandwidth

NR Band n77 25 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.26	18.87	0	0.0
	1	33	18.32	18.91		0.0
	1	63	18.23	18.99		0.0
	32	0	18.31	18.92	0-1	0.0
	32	17	18.20	18.81	0	0.0
	32	33	18.31	18.91	0-1	0.0
	64	0	18.25	18.93		0.0
DFT-s-OFDM 16QAM	1	1	18.21	18.85	0-1	0.0
CP-OFDM QPSK	1	1	18.31	18.94	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 207 of 222

Table H-423
NR Band n77 Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 20 MHz Bandwidth

NR Band n77 20 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.11	18.58	0	0.0
	1	26	18.17	18.64		0.0
	1	49	18.14	18.77		0.0
	25	0	18.14	18.66	0-1	0.0
	25	13	18.14	18.67	0	0.0
	25	26	18.23	18.83	0-1	0.0
	50	0	18.26	18.70		0.0
DFT-s-OFDM 16QAM	1	1	18.16	18.62	0-1	0.0
CP-OFDM QPSK	1	1	18.21	18.69	0-1.5	0.0

Table H-424
NR Band n77 Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 15 MHz Bandwidth

NR Band n77 15 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.21	18.73	0	0.0
	1	19	18.21	18.76		0.0
	1	36	18.27	18.90		0.0
	18	0	18.19	18.75	0-1	0.0
	18	10	18.18	18.78	0	0.0
	18	20	18.34	18.91	0-1	0.0
	36	0	18.15	18.71		0.0
DFT-s-OFDM 16QAM	1	1	18.14	18.70	0-1	0.0
CP-OFDM QPSK	1	1	18.24	18.80	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 208 of 222

Table H-425
NR Band n77 Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 10 MHz Bandwidth

NR Band n77 10 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.23	18.75	0	0.0
	1	12	18.22	18.81		0.0
	1	22	18.36	18.88		0.0
	12	0	18.27	18.67	0-1	0.0
	12	6	18.24	18.77	0	0.0
	12	12	18.32	18.87	0-1	0.0
	24	0	18.22	18.77		0.0
DFT-s-OFDM 16QAM	1	1	18.30	18.70	0-1	0.0
CP-OFDM QPSK	1	1	18.31	18.75	0-1.5	0.0

Table H-426
NR Band n77 Antenna F Measured P_{Limit} for DSI = 1 (Head) - 90 MHz Bandwidth

NR Band n77 90 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	16.60	16.96	0	0.0
	1	123	16.57	16.89		0.0
	1	243	16.51	16.95		0.0
	120	0	16.52	16.91	0-1	0.0
	120	63	16.55	16.90	0	0.0
	120	125	16.45	16.97	0-1	0.0
	243	0	16.56	16.89		0.0
DFT-s-OFDM 16QAM	1	1	16.61	16.90	0-1	0.0
CP-OFDM QPSK	1	1	16.67	16.95	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 209 of 222

Table H-427
NR Band n77 Antenna F Measured P_{Limit} for DSI = 1 (Head) - 80 MHz Bandwidth

NR Band n77 80 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	16.30	16.65	0	0.0
	1	109	16.27	16.87		0.0
	1	215	16.38	16.88		0.0
	108	0	16.27	16.76	0-1	0.0
	108	55	16.29	16.75	0	0.0
	108	109	16.23	16.94	0-1	0.0
	216	0	16.31	16.82		0.0
DFT-s-OFDM 16QAM	1	1	16.34	16..70	0-1	0.0
CP-OFDM QPSK	1	1	16.32	16.73	0-1.5	0.0

Table H-428
NR Band n77 Antenna F Measured P_{Limit} for DSI = 1 (Head) - 70 MHz Bandwidth

NR Band n77 70 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	16.35	16.64	0	0.0
	1	95	16.17	16.85		0.0
	1	187	16.27	16.94		0.0
	90	0	16.22	16.81	0-1	0.0
	90	50	16.26	16.81	0	0.0
	90	99	16.18	16.99	0-1	0.0
	180	0	16.30	16.89		0.0
DFT-s-OFDM 16QAM	1	1	16.27	16.76	0-1	0.0
CP-OFDM QPSK	1	1	16.30	16.75	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 210 of 222

Table H-429
NR Band n77 Antenna F Measured P_{Limit} for DSI = 1 (Head) - 60 MHz Bandwidth

NR Band n77 60 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	16.24	16.61	0	0.0
	1	81	16.12	16.78		0.0
	1	160	16.24	16.81		0.0
	81	0	16.13	16.65	0-1	0.0
	81	41	16.09	16.74	0	0.0
	81	81	16.15	16.71	0-1	0.0
	162	0	16.18	16.75		0.0
DFT-s-OFDM 16QAM	1	1	16.25	16.68	0-1	0.0
CP-OFDM QPSK	1	1	16.24	16.74	0-1.5	0.0

Table H-430
NR Band n77 Antenna F Measured P_{Limit} for DSI = 1 (Head) - 50 MHz Bandwidth

NR Band n77 50 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	16.36	16.85	0	0.0
	1	67	16.41	16.96		0.0
	1	131	16.41	16.91		0.0
	64	0	16.40	16.84	0-1	0.0
	64	35	16.33	16.92	0	0.0
	64	69	16.40	16.97	0-1	0.0
	128	0	16.34	16.98		0.0
DFT-s-OFDM 16QAM	1	1	16.37	16.96	0-1	0.0
CP-OFDM QPSK	1	1	16.36	16.94	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 211 of 222

Table H-431
NR Band n77 Antenna F Measured P_{Limit} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n77 40 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	16.31	16.70	0	0.0
	1	53	16.34	16.80		0.0
	1	104	16.30	16.84		0.0
	50	0	16.24	16.84	0-1	0.0
	50	28	16.30	16.92	0	0.0
	50	56	16.22	16.91	0-1	0.0
	100	0	16.30	16.91		0.0
DFT-s-OFDM 16QAM	1	1	16.25	16.57	0-1	0.0
CP-OFDM QPSK	1	1	16.26	16.71	0-1.5	0.0

Table H-432
NR Band n77 Antenna F Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n77 30 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	16.17	16.82	0	0.0
	1	39	16.27	16.79		0.0
	1	76	16.31	16.91		0.0
	36	0	16.14	16.88	0-1	0.0
	36	21	16.22	16.84	0	0.0
	36	42	16.14	16.93	0-1	0.0
	75	0	16.16	16.92		0.0
DFT-s-OFDM 16QAM	1	1	16.18	16.90	0-1	0.0
CP-OFDM QPSK	1	1	16.25	16.87	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 212 of 222

Table H-433
NR Band n77 Antenna F Measured P_{Limit} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n77 25 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	16.22	16.78	0	0.0
	1	33	16.19	16.72		0.0
	1	63	16.22	16.92		0.0
	32	0	16.21	16.87	0-1	0.0
	32	17	16.20	16.82	0	0.0
	32	33	16.23	16.89	0-1	0.0
	64	0	16.18	16.91		0.0
DFT-s-OFDM 16QAM	1	1	16.26	16.89	0-1	0.0
CP-OFDM QPSK	1	1	16.31	16.86	0-1.5	0.0

Table H-434
NR Band n77 Antenna F Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n77 20 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	16.15	16.59	0	0.0
	1	26	16.11	16.62		0.0
	1	49	16.19	16.74		0.0
	25	0	16.14	16.59	0-1	0.0
	25	13	16.16	16.63	0	0.0
	25	26	16.17	16.74	0-1	0.0
	50	0	16.15	16.71		0.0
DFT-s-OFDM 16QAM	1	1	16.18	16.61	0-1	0.0
CP-OFDM QPSK	1	1	16.13	16.67	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 213 of 222

Table H-435
NR Band n77 Antenna F Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n77 15 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	16.24	16.72	0	0.0
	1	19	16.22	16.70		0.0
	1	36	16.21	16.88		0.0
	18	0	16.16	16.77	0-1	0.0
	18	10	16.19	16.69	0	0.0
	18	20	16.25	16.80	0-1	0.0
	36	0	16.12	16.71		0.0
DFT-s-OFDM 16QAM	1	1	16.18	16.69	0-1	0.0
CP-OFDM QPSK	1	1	16.15	16.78	0-1.5	0.0

Table H-436
NR Band n77 Antenna F Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n77 10 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	16.20	16.62	0	0.0
	1	12	16.23	16.75		0.0
	1	22	16.28	16.81		0.0
	12	0	16.19	16.59	0-1	0.0
	12	6	16.20	16.61	0	0.0
	12	12	16.23	16.80	0-1	0.0
	24	0	16.19	16.71		0.0
DFT-s-OFDM 16QAM	1	1	16.24	16.63	0-1	0.0
CP-OFDM QPSK	1	1	16.30	16.72	0-1.5	0.0

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 214 of 222

Table H-437
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 90 MHz Bandwidth

NR Band n77 90 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	16.38	16.90
SRS #3 Ant I	17.49	18.40
SRS #4 Ant D	12.82	13.40

Table H-438
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 80 MHz Bandwidth

NR Band n77 80 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	16.30	16.85
SRS #3 Ant I	17.40	18.42
SRS #4 Ant D	12.91	13.45

Table H-439
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 70 MHz Bandwidth

NR Band n77 70 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	16.43	16.99
SRS #3 Ant I	17.44	18.14
SRS #4 Ant D	12.92	13.43

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 215 of 222

Table H-440
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 60 MHz Bandwidth

NR Band n77 60 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	16.25	16.74
SRS #3 Ant I	17.18	18.07
SRS #4 Ant D	12.76	13.31

Table H-441
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 50 MHz Bandwidth

NR Band n77 50 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	16.65	16.95
SRS #3 Ant I	17.62	18.13
SRS #4 Ant D	13.25	13.42

Table H-442
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 40 MHz Bandwidth

NR Band n77 40 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	16.46	16.84
SRS #3 Ant I	17.38	18.00
SRS #4 Ant D	13.02	13.45

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 216 of 222

Table H-443
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 30 MHz Bandwidth

NR Band n77 30 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	16.42	16.84
SRS #3 Ant I	17.38	17.99
SRS #4 Ant D	13.14	13.41

Table H-444
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 25 MHz Bandwidth

NR Band n77 25 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	16.52	16.79
SRS #3 Ant I	17.36	17.89
SRS #4 Ant D	13.25	13.70

Table H-445
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 20 MHz Bandwidth

NR Band n77 20 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	16.52	16.79
SRS #3 Ant I	17.39	17.98
SRS #4 Ant D	13.11	13.40

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 217 of 222

Table H-446
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 15 MHz Bandwidth

NR Band n77 15 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	16.47	16.79
SRS #3 Ant I	17.36	17.95
SRS #4 Ant D	13.12	13.27

Table H-447
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 10 MHz Bandwidth

NR Band n77 10 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	16.51	16.85
SRS #3 Ant I	17.42	17.97
SRS #4 Ant D	13.23	13.25

Table H-448
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 90 MHz Bandwidth

NR Band n77 90 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	19.78	20.14
SRS #3 Ant I	15.20	16.14
SRS #4 Ant D	10.63	11.17

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 218 of 222

Table H-449
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 80 MHz Bandwidth

NR Band n77 80 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	19.67	20.15
SRS #3 Ant I	15.01	16.11
SRS #4 Ant D	10.57	11.12

Table H-450
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 70 MHz Bandwidth

NR Band n77 70 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	19.93	20.06
SRS #3 Ant I	15.08	15.86
SRS #4 Ant D	10.63	11.15

Table H-451
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 60 MHz Bandwidth

NR Band n77 60 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	19.92	20.09
SRS #3 Ant I	14.87	15.78
SRS #4 Ant D	10.54	11.00

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 219 of 222

Table H-452
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 50 MHz Bandwidth

NR Band n77 50 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	20.04	20.11
SRS #3 Ant I	15.12	15.88
SRS #4 Ant D	10.94	11.24

Table H-453
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n77 40 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	19.91	20.10
SRS #3 Ant I	15.02	15.81
SRS #4 Ant D	10.75	11.08

Table H-454
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n77 30 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	19.77	20.12
SRS #3 Ant I	14.99	15.78
SRS #4 Ant D	10.72	11.29

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 220 of 222

Table H-455
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n77 25 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	19.91	20.10
SRS #3 Ant I	14.90	15.75
SRS #4 Ant D	10.91	11.21

Table H-456
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n77 20 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	19.84	20.05
SRS #3 Ant I	15.26	15.65
SRS #4 Ant D	10.72	10.94

Table H-457
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n77 15 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	19.93	20.07
SRS #3 Ant I	14.97	15.65
SRS #4 Ant D	10.71	10.99

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 221 of 222

Table H-458
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n77 10 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	19.68	20.07
SRS #3 Ant I	15.12	15.69
SRS #4 Ant D	10.84	11.06

FCC ID A3LSMS938U	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 222 of 222