



REPORT No.: SZ23050339W03

# TEST REPORT

**APPLICANT** : BLU Products, Inc.

**PRODUCT NAME** : Smart Phone

**MODEL NAME** : J8L

**BRAND NAME** : BLU

**FCC ID** : YHLBLUJ8LUU

**STANDARD(S)** : 47 CFR Part 15 Subpart C

**RECEIPT DATE** : 2023-07-13

**TEST DATE** : 2023-07-18 to 2023-07-30

**ISSUE DATE** : 2023-08-22



Edited by:

*Su Xiaoxian*

Su Xiaoxian (Rapporteur)

Approved by:

*Shen Junsheng*

Shen Junsheng (Supervisor)

**NOTE:** This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.  
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,  
Block67, BaoAn District, ShenZhen, Guangdong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn





## DIRECTORY

<b>1. Summary of Test Results</b>	<b>4</b>
1.1. Testing Applied Standards	5
1.2. Test Equipment List	6
1.3. Measurement Uncertainty	8
1.4. Testing Laboratory	8
<b>2. General Description</b>	<b>9</b>
2.1. Information of Applicant and Manufacturer	9
2.2. Information of EUT	9
2.3. Channel List of EUT	11
2.4. Test Configuration of EUT	12
2.5. Test Conditions	12
2.6. Test Setup Layout Diagram	12
<b>3. Test Results</b>	<b>15</b>
3.1. Antenna Requirement	15
3.2. Duty Cycle of Test Signal	16
3.3. Maximum Peak Conducted Output Power	17
3.4. Maximum Average Conducted Output Power	18
3.5. 6 dB Bandwidth	19
3.6. Conducted Spurious Emissions and Band Edge	20
3.7. Power Spectral Density	21
3.8. Conducted Emission	22
3.9. Restricted Frequency Bands	23
3.10. Radiated Emission	24
<b>Annex A Test Data and Result</b>	<b>26</b>



REPORT No.: SZ23050339W03

Change History		
Version	Date	Reason for change
1.0	2023-08-22	First edition

# 1. Summary of Test Results

No.	Section	Description	Test Date	Test Engineer	Result	Method Determination /Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS	No deviation
2	N/A	Duty Cycle of Test Signal	Jul. 19, 2023	He Yuyang	PASS	No deviation
3	15.247(b)	Maximum Peak Conducted Output Power	Jul. 19, 2023	He Yuyang	PASS	No deviation
4	15.247(b)	Maximum Average Conducted Output Power	Jul. 19, 2023	He Yuyang	PASS	No deviation
5	15.247(a)	Bandwidth	Jul. 19, 2023	He Yuyang	PASS	No deviation
6	15.247(d)	Conducted Spurious Emission and Band Edge	Jul. 19, 2023	He Yuyang	PASS	No deviation
7	15.247(e)	Power Spectral Density	Jul. 19, 2023	He Yuyang	PASS	No deviation
8	15.207	Conducted Emission	Jul. 19, 2023	Lin Jiayong	PASS	No deviation
9	15.247(d)	Restricted Frequency Bands	Jul. 27, 2023	Su Zhan	PASS	No deviation
10	15.209, 15.247(d)	Radiated Emission	Jul. 30, 2023	Su Zhan	PASS	No deviation

**Note 1:** The tests were performed according to the method of measurements prescribed in ANSIC63.10-2013 and KDB558074 D01 v05r02.

**Note 2:** Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.

**Note 3:** When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.



## 1.1. Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C Radio Frequency Devices



## 1.2. Test Equipment List

### 1.2.1 Conducted Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
EXA Signal Analyzer	MY53470836	N9010A	Agilent	2023.02.27	2024.02.26
RF Cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
Coaxial Cable	CB02	RF02	Morlab	N/A	N/A
SMA Connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

### 1.2.2 Conducted Emission Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	MY56400093	N9038A	KEYSIGHT	2023.02.09	2024.02.08
LISN	8127449	NSLK 8127	Schwarzbeck	2023.02.21	2024.02.20
Pulse Limiter (10dB)	VTSD 9561 F-B #206	VTSD 9561-F	Schwarzbeck	2023.06.27	2024.06.26
RF Coaxial Cable (DC-100MHz)	BNC	MRE04	Qualwave	N/A	N/A

### 1.2.3 List of Software Used

Description	Manufacturer	Software Version
Test System	MaiWei	2.0.0.0
Morlab EMCR V1.2	Morlab	V1.0
TS+ -[JS32-CE]	Tonscend	V2.5.0.0

**1.2.4 Radiated Test Equipments**

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	MY54130016	N9038A	Agilent	2023.06.21	2024.06.20
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2022.05.25	2025.05.24
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2022.02.11	2025.02.10
Test Antenna – Horn	01774	BBHA 9120D	Schwarzbeck	2022.07.13	2025.07.12
Test Antenna – Horn	BBHA9170 #773	BBHA9170	Schwarzbeck	2022.07.14	2025.07.13
Preamplifier (10MHz-6GHz)	46732	S10M100L38 02	LUCIX CORP.	2023.06.27	2024.06.26
Preamplifier (2GHz-18GHz)	61171/61172	S020180L32 03	LUCIX CORP.	2023.06.27	2024.06.26
Preamplifier (18GHz-40GHz)	DS77209	DCLNA0118-40C-S	Decentest	2023.07.04	2024.07.03
RF Coaxial Cable (DC-18GHz)	MRE001	PE330	Pasternack	2023.06.27	2024.06.26
RF Coaxial Cable (DC-18GHz)	MRE002	CLU18	Pasternack	2023.06.27	2024.06.26
RF Coaxial Cable (DC-18GHz)	MRE003	CLU18	Pasternack	2023.06.27	2024.06.26
RF Coaxial Cable (DC-40GHz)	22290045	QA360-40-K K-0.5	Qualwave	2023.06.27	2024.06.26
RF Coaxial Cable (DC-40GHz)	22290046	QA360-40-K KF-2	Qualwave	2023.06.27	2024.06.26
RF Coaxial Cable (DC-18GHz)	22120181	QA500-18-N N-5	Qualwave	2023.06.27	2024.06.26
Notch Filter	N/A	WRCG-2400-2483.5-60SS	Wainwright	N/A	N/A
Anechoic Chamber	N/A	9m*6m*6m	CRT	2022.05.10	2025.05.09



### 1.3. Measurement Uncertainty

Test Items	Uncertainty	Remark
Peak Output Power	$\pm 2.22\text{dB}$	Confidence levels of 95%
Power Spectral Density	$\pm 2.22\text{dB}$	Confidence levels of 95%
Bandwidth	$\pm 5\%$	Confidence levels of 95%
Conducted Spurious Emission	$\pm 2.77\text{dB}$	Confidence levels of 95%
Restricted Frequency Bands	$\pm 5\%$	Confidence levels of 95%
Radiated Emission	$\pm 2.95\text{dB}$	Confidence levels of 95%
Conducted Emission	$\pm 2.44\text{dB}$	Confidence levels of 95%

### 1.4. Testing Laboratory

Laboratory Name	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone	+86 755 36698555
Facsimile	+86 755 36698525
FCC Designation Number	CN1192
FCC Test Firm Registration Number	226174





## 2. General Description

### 2.1. Information of Applicant and Manufacturer

<b>Applicant</b>	BLU Products, Inc.
<b>Applicant Address</b>	8600 NW 36th Street, Suite #200 Doral, FL 33166, USA
<b>Manufacturer</b>	BLU Products, Inc.
<b>Manufacturer Address</b>	8600 NW 36th Street, Suite #200 Doral, FL 33166, USA

### 2.2. Information of EUT

<b>Product Name:</b>	Smart Phone	
<b>Sample No.:</b>	1#	
<b>Hardware Version:</b>	H612A_MB_V1	
<b>Software Version:</b>	BLU_J0170_V13.0.G.01.00_GENERIC_28-06-2023023	
<b>Equipment Type:</b>	Bluetooth LE	
<b>Bluetooth Version:</b>	5.0	
<b>Modulation Type:</b>	GFSK	
<b>Data Rate:</b>	1Mbps, 2Mbps	
<b>Operating Frequency Range:</b>	2402MHz-2480MHz	
<b>Antenna Type:</b>	PIFA Antenna	
<b>Antenna Gain:</b>	1.30dBi	
<b>Accessory Information:</b>	Battery	
	<b>Brand Name:</b>	BLU
	<b>Model No.:</b>	C876445200L
	<b>Serial No.:</b>	N/A
	<b>Capacity:</b>	2000mAh
	<b>Rated Voltage:</b>	3.7V
	<b>Charge Limit:</b>	4.2V
	<b>Manufacturer:</b>	Shenzhen Aerospace Electronic Co.,Ltd.



<b>Accessory Information:</b>	AC Adapter	
	Brand Name:	BLU
	Model No.:	US-HY-1000
	Serial No.:	N/A
	Rated Output:	5.0V $\equiv$ 1000mA
	Rated Input:	100-240V $\sim$ 50/60Hz, 0.3A
	Manufacturer:	Shenzhen Zhongfu core Technology Co., LTD

**Note 1:** We use the dedicated software to control the EUT continuous transmission.

**Note 2:** For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



## 2.3.Channel List of EUT

BLE 1Mbps							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
<b>0</b>	<b>2402</b>	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	<b>19</b>	<b>2440</b>	29	2460	<b>39</b>	<b>2480</b>

BLE 2Mbps							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
<b>1</b>	<b>2404</b>	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	<b>38</b>	<b>2478</b>
9	2420	<b>19</b>	<b>2440</b>	29	2460		
10	2422	20	2442	30	2462		

**Note 1:** The black bold channels were selected for test.

## 2.4. Test Configuration of EUT


Test mode is used to control the EUT under the maximum power level during test.

## 2.5. Test Conditions


Temperature (°C)	15-35
Relative Humidity (%)	30-60
Atmospheric Pressure (kPa)	86-106

## 2.6. Test Setup Layout Diagram

### 2.6.1. Conducted Measurement




### 2.6.2. Conducted Emission Measurement




### 2.6.3.Radiation Measurement


1) For radiated emissions from 9kHz to 30MHz



2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz





## 3. Test Results

### 3.1. Antenna Requirement

#### 3.1.1. Requirement

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

#### 3.1.2. Test Result

Inside of the EUT has a PIFA antenna coupled with the metal shrapnel. Please refer to the EUT photos.

## 3.2. Duty Cycle of Test Signal

### 3.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration ( $T$ ) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed  $T$  at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle ( $D$ ). Within this sub clause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than  $\pm 2\%$ ; otherwise, the duty cycle is considered to be non constant.

### 3.2.2. Test Result

Refer to Annex A.1 in this report.





### **3.3. Maximum Peak Conducted Output Power**

#### **3.3.1. Requirement**

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

#### **3.3.2. Test Procedures**

KDB 558074 Section 8.3.1 was used in order to prove compliance.

#### **3.3.3. Test Setup Layout**

Refer to chapter 2.6.1 in this report.

#### **3.3.4. Test Result**

Refer to Annex A.2 in this report.



## **3.4. Maximum Average Conducted Output Power**

### **3.4.1. Requirement**

According to FCC section 15.247(b)(3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum average conducted output power of the intentional radiator shall not exceed 1 Watt.

### **3.4.2. Test Procedures**

KDB 558074 Section 8.3.2 was used in order to prove compliance.

### **3.4.3. Test Setup Layout**

Refer to chapter 2.6.1 in this report.

### **3.4.4. Test Result**

Refer to Annex A.3 in this report.



## 3.5.6 dB Bandwidth

### 3.5.1.Requirement

According to FCC section 15.247(a) (2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

### 3.5.1.Test Procedures

The steps for the first option are as follows:

- a) Set analyzer center frequency to channel center frequency
- b) Set RBW to 100kHz
- c) Set VBW to 300kHz
- d) Detector = peak.
- e) Trace mode = max hold
- f) Sweep time = auto couple
- g) Allow the trace to fully stabilize
- h) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e.,  $RBW = 100\text{ kHz}$ ,  $VBW \geq 3 \times RBW$ , and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be  $\geq 6\text{ dB}$ .

### 3.5.2.Test Setup Layout

Refer to chapter 2.6.1 in this report.

### 3.5.3.Test Result

Refer to Annex A.4 in this report.



## **3.6. Conducted Spurious Emissions and Band Edge**

### **3.6.1. Requirement**

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

### **3.6.2. Test Procedures**

KDB 558074 Section 8.5 and 8.7 was used in order to prove compliance.

### **3.6.3. Test Setup Layout**

Refer to chapter 2.6.1 in this report.

### **3.6.4. Test Result**

Refer to Annex A.5 and A.6 in this report.



## **3.7. Power Spectral Density**

### **3.7.1. Requirement**

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### **3.7.2. Test Procedures**

The measured power spectral density was calculated by the reading of the spectrum analyzer and calibration. Following is the test procedure for PSD test:

- a) Set analyzer center frequency to channel center frequency
- b) Set span to 1.5 times DTS
- c) Set RBW to 3kHz
- d) Set VBW to 10kHz
- e) Detector = peak
- f) Sweep time = auto couple
- g) Trace mode = max hold
- h) Allow trace to fully stabilize
- i) Use the peak marker function to determine the maximum amplitude level within the RBW

### **3.7.3. Test Setup Layout**

Refer to chapter 2.6.1 in this report.

### **3.7.4. Test Result**

Refer to Annex A.7 in this report.

## 3.8. Conducted Emission

### 3.8.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50 $\Omega$  line impedance stabilization network (LISN).

Frequency Range (MHz)	Conducted Limit (dB $\mu$ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

Note:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

### 3.8.2. Test Procedures

The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10: 2013.

### 3.8.3. Test Setup Layout

Refer to chapter 2.6.2 in this report.

### 3.8.4. Test Result

Refer to Annex A.8 in this report.

## 3.9. Restricted Frequency Bands

### 3.9.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

### 3.9.2. Test Procedures

The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for  $f \geq 1\text{GHz}$ , 100 kHz for  $f < 1\text{GHz}$

VBW = 3 MHz

Sweep = auto

Detector function = peak/average

Trace = max hold

Allow the trace to stabilize

### 3.9.3. Test Setup Layout

Refer to chapter 2.6.3 in this report.

### 3.9.4. Test Result

Refer to Annex A.8 in this report.

## 3.10. Radiated Emission

### 3.10.1.Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ( $\mu\text{V/m}$ )	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

**Note1:** For above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

**Note2:**For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).





### **3.10.2.Test Procedures**

The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz. The antenna to EUT distance is 3meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 30MHz, the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9kHz-90 kHz, 110kHz-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements and as applicable for average measurements.

The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions. For measurements above 1 GHz, keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

### **3.10.3.Test Setup Layout**

Refer to chapter 2.6.3 in this report.

### **3.10.4.Test Result**

Refer to Annex A.9 in this report.



## Annex A Test Data and Result


### A.1. Duty Cycle of Test Signal

Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	BLE 1M	2402	Ant1	61.29	2.13	2.63
NVNT	BLE 1M	2440	Ant1	61.29	2.13	2.63
NVNT	BLE 1M	2480	Ant1	61.9	2.08	2.56
NVNT	BLE 2M	2404	Ant1	31.75	4.98	5
NVNT	BLE 2M	2440	Ant1	32.26	4.91	5
NVNT	BLE 2M	2478	Ant1	32.26	4.91	5




## Test Graphs


## Duty Cycle NVNT BLE 1M 2402MHz Ant1




## Duty Cycle NVNT BLE 1M 2440MHz Ant1



## Duty Cycle NVNT BLE 1M 2480MHz Ant1




## Duty Cycle NVNT BLE 2M 2404MHz Ant1








## Duty Cycle NVNT BLE 2M 2440MHz Ant1



## Duty Cycle NVNT BLE 2M 2478MHz Ant1



**A.2. Maximum Peak Conducted Output Power**


Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (mW)	Limit Conducted (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	-2.24	0	-2.24	0.6	30	Pass
NVNT	BLE 1M	2440	Ant1	-3.27	0	-3.27	0.47	30	Pass
NVNT	BLE 1M	2480	Ant1	-3.53	0	-3.53	0.44	30	Pass
NVNT	BLE 2M	2404	Ant1	-1.89	0	-1.89	0.65	30	Pass
NVNT	BLE 2M	2440	Ant1	-3.19	0	-3.19	0.48	30	Pass
NVNT	BLE 2M	2478	Ant1	-3.48	0	-3.48	0.45	30	Pass

## Test Graphs

## Peak Power NVNT BLE 1M 2402MHz Ant1



## Peak Power NVNT BLE 1M 2440MHz Ant1



### Peak Power NVNT BLE 1M 2480MHz Ant1




### Peak Power NVNT BLE 2M 2404MHz Ant1





### Peak Power NVNT BLE 2M 2440MHz Ant1



### Peak Power NVNT BLE 2M 2478MHz Ant1



**A.3. Maximum Average Conducted Output Power**

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (mW)	Limit Conducted (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	-4.75	2.13	-2.62	0.55	30	Pass
NVNT	BLE 1M	2440	Ant1	-5.58	2.13	-3.45	0.45	30	Pass
NVNT	BLE 1M	2480	Ant1	-5.97	2.08	-3.89	0.41	30	Pass
NVNT	BLE 2M	2404	Ant1	-7.16	4.98	-2.18	0.61	30	Pass
NVNT	BLE 2M	2440	Ant1	-8.46	4.91	-3.55	0.44	30	Pass
NVNT	BLE 2M	2478	Ant1	-8.61	4.91	-3.7	0.43	30	Pass




## Test Graphs


## Average Power NVNT BLE 1M 2402MHz Ant1



## Average Power NVNT BLE 1M 2440MHz Ant1



## Average Power NVNT BLE 1M 2480MHz Ant1




## Average Power NVNT BLE 2M 2404MHz Ant1





## Average Power NVNT BLE 2M 2440MHz Ant1



## Average Power NVNT BLE 2M 2478MHz Ant1




**A.4. 6 dB Bandwidth**

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 1M	2402	Ant1	0.674	0.5	Pass
NVNT	BLE 1M	2440	Ant1	0.672	0.5	Pass
NVNT	BLE 1M	2480	Ant1	0.659	0.5	Pass
NVNT	BLE 2M	2404	Ant1	1.119	0.5	Pass
NVNT	BLE 2M	2440	Ant1	1.12	0.5	Pass
NVNT	BLE 2M	2478	Ant1	1.143	0.5	Pass



## Test Graphs

## -6dB Bandwidth NVNT BLE 1M 2402MHz Ant1




## -6dB Bandwidth NVNT BLE 1M 2440MHz Ant1





## -6dB Bandwidth NVNT BLE 1M 2480MHz Ant1



## -6dB Bandwidth NVNT BLE 2M 2404MHz Ant1








## -6dB Bandwidth NVNT BLE 2M 2440MHz Ant1



## -6dB Bandwidth NVNT BLE 2M 2478MHz Ant1




**A.5. Conducted Spurious Emissions**


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-35.44	-20	Pass
NVNT	BLE 1M	2440	Ant1	-34	-20	Pass
NVNT	BLE 1M	2480	Ant1	-34.33	-20	Pass
NVNT	BLE 2M	2404	Ant1	-36.13	-20	Pass
NVNT	BLE 2M	2440	Ant1	-34.33	-20	Pass
NVNT	BLE 2M	2478	Ant1	-34.3	-20	Pass

## Test Graphs


## Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Ref




## Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Emission



## Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Ref



## Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Emission






## Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Ref



## Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Emission






## Tx. Spurious NVNT BLE 2M 2404MHz Ant1 Ref




## Tx. Spurious NVNT BLE 2M 2404MHz Ant1 Emission



## Tx. Spurious NVNT BLE 2M 2440MHz Ant1 Ref



## Tx. Spurious NVNT BLE 2M 2440MHz Ant1 Emission






## Tx. Spurious NVNT BLE 2M 2478MHz Ant1 Ref



## Tx. Spurious NVNT BLE 2M 2478MHz Ant1 Emission







REPORT No.: SZ23050339W03

#### A.6. Band Edge


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-52.68	-20	Pass
NVNT	BLE 1M	2480	Ant1	-51.14	-20	Pass
NVNT	BLE 2M	2404	Ant1	-52.08	-20	Pass
NVNT	BLE 2M	2478	Ant1	-50.6	-20	Pass

## Test Graphs


## Band Edge NVNT BLE 1M 2402MHz Ant1 Ref




## Band Edge NVNT BLE 1M 2402MHz Ant1 Emission



### Band Edge NVNT BLE 1M 2480MHz Ant1 Ref




### Band Edge NVNT BLE 1M 2480MHz Ant1 Emission



### Band Edge NVNT BLE 2M 2404MHz Ant1 Ref



### Band Edge NVNT BLE 2M 2404MHz Ant1 Emission






### Band Edge NVNT BLE 2M 2478MHz Ant1 Ref



### Band Edge NVNT BLE 2M 2478MHz Ant1 Emission




**A.7. Power Spectral Density**

Condition	Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm/3kHz)	Duty Factor (dB)	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	BLE 1M	2402	Ant1	-17.03	0	-17.03	8	Pass
NVNT	BLE 1M	2440	Ant1	-18.03	0	-18.03	8	Pass
NVNT	BLE 1M	2480	Ant1	-18.29	0	-18.29	8	Pass
NVNT	BLE 2M	2404	Ant1	-19.22	0	-19.22	8	Pass
NVNT	BLE 2M	2440	Ant1	-20.51	0	-20.51	8	Pass
NVNT	BLE 2M	2478	Ant1	-20.79	0	-20.79	8	Pass



## Test Graphs

## PSD NVNT BLE 1M 2402MHz Ant1




## PSD NVNT BLE 1M 2440MHz Ant1



## PSD NVNT BLE 1M 2480MHz Ant1




## PSD NVNT BLE 2M 2404MHz Ant1






## PSD NVNT BLE 2M 2440MHz Ant1



## PSD NVNT BLE 2M 2478MHz Ant1





### A.8. Conducted Emission

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Set RBW=9kHz, VBW=30kHz. Refer to recorded points and plots below.

**Note:** Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

#### A. Test Setup:

Test Mode: EUT + Adapter + Earphone + BT TX

Test voltage: AC 120V/60Hz


The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V]} = U_R + L_{\text{Cable loss}} \text{ [dB]} + A_{\text{Factor}}$$

$U_R$ : Receiver Reading


$A_{\text{Factor}}$ : Voltage division factor of LISN

## B. Test Plot:



(L Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.2631	35.82	25.77	61.33	51.33	Line	PASS
2	0.5671	27.85	22.03	56.00	46.00		PASS
3	1.1541	35.76	24.61	56.00	46.00		PASS
4	2.0294	31.43	20.63	56.00	46.00		PASS
5	3.1516	27.12	16.42	56.00	46.00		PASS
6	22.8417	45.96	35.68	60.00	50.00		PASS



(N Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.2045	41.52	30.08	63.43	53.43	Neutral	PASS
2	0.5104	34.19	28.46	56.00	46.00		PASS
3	1.2285	36.51	26.57	56.00	46.00		PASS
4	2.0541	32.97	24.92	56.00	46.00		PASS
5	22.8430	40.36	31.63	60.00	50.00		PASS
6	28.9343	39.45	34.39	60.00	50.00		PASS



### A.9. Restricted Frequency Bands

The lowest and highest channels are tested to verify the Restricted Frequency Bands.

The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V/m}] = U_R + A_T + A_{\text{Factor}} [\text{dB}]; A_T = L_{\text{Cable loss}} [\text{dB}] - G_{\text{preamp}} [\text{dB}]$$

$A_T$ : Total correction Factor except Antenna

$U_R$ : Receiver Reading

$G_{\text{preamp}}$ : Preamplifier Gain


$A_{\text{Factor}}$ : Antenna Factor at 3m

Note: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (vertical) was recorded in this test report.


#### 1Mbps

Channel	Frequency (MHz)	Detector	Receiver Reading $U_R$ (dB $\mu$ V)	$A_T$ (dB)	$A_{\text{Factor}}$ (dB@3m)	Max. Emission E (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Verdict
		PK/ AV						
0	2388.82	PK	23.64	6.74	27.20	57.58	74	PASS
0	2389.34	AV	10.81	6.74	27.20	44.75	54	PASS
39	2483.57	PK	23.43	6.74	27.20	57.37	74	PASS
39	2483.59	AV	10.47	6.74	27.20	44.41	54	PASS







(PEAK, Channel 0)



(AVERAGE, Channel 0)



(PEAK, Channel 39)




(AVERAGE, Channel 39)






2Mbps


Channel	Frequency (MHz)	Detector	Receiver Reading $U_R$ (dB $\mu$ V)	$A_T$ (dB)	$A_{Factor}$ (dB@3m)	Max. Emission $E$ (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Verdict
		PK/ AV						
1	2359.89	PK	24.13	6.74	27.20	58.07	74	PASS
1	2389.46	AV	10.84	6.74	27.20	44.78	54	PASS
38	2495.25	PK	24.21	6.74	27.20	58.15	74	PASS
38	2483.66	AV	10.47	6.74	27.20	44.41	54	PASS




(PEAK, Channel 0)



(AVERAGE, Channel 0)



(PEAK, Channel 39)





## A.10. Radiated Emission

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak (or average) limit, it is unnecessary to perform an quasi-peak measurement (or average).

The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V/m}] = U_R + A_T + A_{\text{Factor}} [\text{dB}]; A_T = L_{\text{Cable loss}} [\text{dB}] - G_{\text{preamp}} [\text{dB}]$$

$A_T$ : Total correction Factor except Antenna

$U_R$ : Receiver Reading

$G_{\text{preamp}}$ : Preamplifier Gain

$A_{\text{Factor}}$ : Antenna Factor at 3m

During the test, the total correction Factor  $A_T$  and  $A_{\text{Factor}}$  were built in test software.

**Note1:** All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.


**Note2:** For the frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

**Note3:** For the frequency, which started from 18GHz to 10th harmonic of the highest frequency, was pre-scanned and the result which was 20dB lower than the limit was not recorded.



# 1Mbps

## Plot for Channel 0



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
99.840	33.23	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1578.667	46.23	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2337.067	46.70	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5763.160	47.28	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8433.520	46.83	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12292.760	47.04	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
102.750	32.36	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1489.067	46.10	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
1904.533	46.79	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5757.000	46.78	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8633.720	46.63	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12486.800	47.50	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel 19



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
101.780	33.15	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1991.467	46.77	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2453.867	46.71	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5686.160	46.38	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8378.080	46.29	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12144.920	47.16	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
106.630	31.99	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1682.133	46.85	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
2453.333	47.09	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5328.880	46.47	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8439.680	46.96	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
13068.920	47.72	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel 39



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
106.630	32.17	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1515.733	46.84	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
1907.733	46.77	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5664.600	47.06	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8448.920	46.77	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12178.800	47.45	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
107.600	32.11	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1582.400	45.87	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
2048.533	46.69	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5405.880	46.04	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8442.760	47.61	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12311.240	46.85	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)



**2Mbps**

## Plot for Channel 1



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
98.870	32.00	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1665.067	46.72	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2227.733	47.68	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5658.440	46.81	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8411.960	46.97	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
13062.760	47.65	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
101.780	32.32	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1627.200	46.38	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
2460.800	47.21	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5390.480	46.51	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
7909.920	46.70	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12517.600	46.76	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel 19



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
101.780	31.40	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1193.600	46.05	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
1881.600	46.86	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5710.800	47.22	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8408.880	46.75	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
11741.440	47.39	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
108.570	33.76	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1156.800	46.22	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
1904.533	46.90	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5787.800	47.55	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8445.840	46.68	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12132.600	47.19	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel 38



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
104.690	31.31	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1195.733	46.52	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2406.933	47.59	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5575.280	46.93	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
7959.200	47.07	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12677.760	47.50	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
96.930	31.51	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1661.333	46.19	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
2020.800	47.46	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5763.160	46.77	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
7928.400	46.88	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12298.920	47.36	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)

END OF REPORT