



Test report No.: 2380887R-RFUSV01S-A

TEST REPORT

Product Name	Wireless headphone
Trademark	ASUS
Model and /or type reference	R55ES(L), R55ES(R)
FCC ID	MSQ-RCTWSNEL MSQ-RCTWSNER
Applicant's name / address	ASUSTeK COMPUTER INC. 1F., No. 15, Lide Rd., Beitou Dist., Taipei City 112, Taiwan
Manufacturer's name	ASUSTeK COMPUTER INC.
Test method requested, standard	FCC CFR Title 47 Part 15 Subpart C ANSI C63.4: 2014, ANSI C63.10: 2013
Verdict Summary	IN COMPLIANCE
Documented By (Senior Project Specialist / Genie Chang)	<i>Genie Chang</i>
Tested By (Senior Engineer / Ivan Chuang)	<i>Ivan Chuang</i>
Approved By (Senior Engineer / Jack Hsu)	<i>Jack Hsu</i>
Date of Receipt	2023/08/29
Date of Issue	2023/12/15
Report Version	V1.0

INDEX

	Page
1. General Information	6
1.1. EUT Description	6
1.2. Tested System Details	8
1.3. Configuration of Tested System	9
1.4. EUT Exercise Software	9
1.5. Test Facility	10
1.6. List of Test Equipment	11
1.7. Uncertainty	12
2. Conducted Emission	13
2.1. Test Setup	13
2.2. Limits	13
2.3. Test Procedure	14
2.4. Test Result of Conducted Emission	15
3. Peak Power Output	16
3.1. Test Setup	16
3.2. Limit	16
3.3. Test Procedure	16
3.4. Test Result of Peak Power Output	17
4. Radiated Emission	23
4.1. Test Setup	23
4.2. Limits	24
4.3. Test Procedure	25
4.4. Test Result of Radiated Emission	26
5. RF Antenna Conducted Test	37
5.1. Test Setup	37
5.2. Limits	37
5.3. Test Procedure	37
5.4. Test Result of RF Antenna Conducted Test	38
6. Band Edge	44
6.1. Test Setup	44
6.2. Limit	45
6.3. Test Procedure	45

6.4. Test Result of Band Edge	46
7. Channel Number	82
7.1. Test Setup	82
7.2. Limit	82
7.3. Test Procedure	82
7.4. Test Result of Channel Number	83
8. Channel Separation	89
8.1. Test Setup	89
8.2. Limit	89
8.3. Test Procedure	89
8.4. Test Result of Channel Separation	90
9. Dwell Time	96
9.1. Test Setup	96
9.2. Limit	96
9.3. Test Procedure	96
9.4. Test Result of Dwell Time	97
10. Occupied Bandwidth	103
10.1. Test Setup	103
10.2. Limits	103
10.3. Test Procedure	103
10.4. Test Result of Occupied Bandwidth	104
11. Duty Cycle	110
11.1. Test Setup	110
11.2. Test Result of Duty Cycle	111

Appendix 1: EUT Test Photographs

Appendix 2: Product Photos-Please refer to the file: 2380887R-Product Photos

Competences and Guarantees

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

General conditions

1. The test results relate only to the samples tested.
2. The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.
3. This report must not be used to claim product endorsement by TAF or any agency of the government.
4. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.
5. Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Revision History

Report No.	Version	Description	Issued Date
2380887R-RFUSV01S-A	V1.0	Initial issue of report.	2023/12/15

1. General Information

1.1. EUT Description

Product Name	Wireless headphone
Trademark	ASUS
Model and /or type reference	R55ES(L), R55ES(R)
EUT Rated Voltage	DC 3.85V by Battery
EUT Test Voltage	DC 3.85V by Battery
Frequency Range	2402-2480 MHz
Channel Number	79 CH
Type of Modulation	GFSK(1 Mbps) / π / 4DQPSK(2 Mbps) / 8DPSK(3 Mbps)
Channel Control	Auto
Wireless headphone	ASUS / R55ES(L)
Wireless headphone	ASUS / R55ES(R)
Wireless Charge Case	ASUS / R55ES
USB Cable	ASUS / R55ES, Shielded, 0.6m
USB-C Wireless Dongle	ASUS / R55ES-D
USB-C to USB-A adaptor dongle	ASUS / R55ES
Battery	Hynotech / CH1154AA

Antenna List

No.	Manufacturer	Part No.	Antenna Type	Peak Gain
1	Cicent (Right)	102BK3F1421	Monopole	-1.2 dBi for 2400 MHz
2	Cicent (Left)	102BK3F1420	Monopole	-0.2 dBi for 2400 MHz

Note: 1. The antenna of EUT conforms to FCC 15.203.

2. The antenna gain as by the manufacturer provided.

Center Frequency of Each Channel:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	01	2403	02	2404	03	2405
04	2406	05	2407	06	2408	07	2409
08	2410	09	2411	10	2412	11	2413
12	2414	13	2415	14	2416	15	2417
16	2418	17	2419	18	2420	19	2421
20	2422	21	2423	22	2424	23	2425
24	2426	25	2427	26	2428	27	2429
28	2430	29	2431	30	2432	31	2433
32	2434	33	2435	34	2436	35	2437
36	2438	37	2439	38	2440	39	2441
40	2442	41	2443	42	2444	43	2445
44	2446	45	2447	46	2448	47	2449
48	2450	49	2451	50	2452	51	2453
52	2454	53	2455	54	2456	55	2457
56	2458	57	2459	58	2460	59	2461
60	2462	61	2463	62	2464	63	2465
64	2466	65	2467	66	2468	67	2469
68	2470	69	2471	70	2472	71	2473
72	2474	73	2475	74	2476	75	2477
76	2478	77	2479	78	2480	--	--

Note:

1. The EUT is a Wireless headphone with built-in 2.4G wireless and Bluetooth transceiver, this report for Bluetooth V2.1+EDR.
2. The radiation measurements are performed in X, Y, Z axis positioning. Only the worst case is shown in the report.
3. Regarding to the operation frequency, the lowest, middle and highest frequency are selected to perform the test
4. The spectrum plot against conducted item only shows the worst case.
5. DEKRA has evaluated each test mode. Only the worst case is shown in the report.
6. These tests were conducted on a sample for the purpose of demonstrating compliance of transmitter with Part 15 Subpart C Paragraph 15.247 for spread spectrum devices.

Test Mode	Mode 1	Transmit-1 Mbps
		Transmit-2 Mbps
		Transmit-3 Mbps
	Mode 2	Charger mode

1.2. Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product		Manufacturer	Model No.	Serial No.	Power Cord
1	Notebook PC	DELL	Latitude 5580	2HRD7H2	N/A
2	Test Fixture	Mercury Electronics	FT232RL USB To UART	N/A	N/A


Cable Type		Cable Description
A	USB Cable	Shielded, 1.8m
B	Signal Cable	Non-shielded, 0.07m

Charger mode


Product		Manufacturer	Model No.	Serial No.	Power Cord
1	Power Adapter	Apple	A1385	N/A	N/A
2	Wireless Charge Case	ASUS	R55ES	N/A	N/A

Cable Type		Cable Description
A	USB Cable	Shielded, 1.8m
B	USB Cable	Shielded, 0.6m

1.3. Configuration of Tested System



Charger mode



1.4. EUT Exercise Software

1.	Setup the EUT as shown in Section 1.3.
2.	Execute software “Airoha Tool Kit Version 3.5.6” on the Notebook PC.
3.	Configure the test mode, the test channel, and the data rate.
4.	Press “OK” to start the continuous transmit.
5.	Verify that the EUT works properly.

1.5. Test Facility

Ambient conditions in the laboratory:

Performed Item	Items	Required	Actual
Conducted Emission	Temperature (°C)	10~40 °C	26.7 °C
	Humidity (%RH)	10~90 %	58.0 %
Radiated Emission	Temperature (°C)	10~40 °C	21.6 °C
	Humidity (%RH)	10~90 %	63.8 %
Conductive	Temperature (°C)	10~40 °C	26.7 °C
	Humidity (%RH)	10~90 %	58.0 %

USA	FCC Registration Number: TW0033
Canada	CAB Identifier Number: TW3023 / Company Number: 26930

Site Description	Accredited by TAF
	Accredited Number: 3023

Test Laboratory	DEKRA Testing and Certification Co., Ltd.
	Linkou Laboratory
Address	No.5-22, Ruishukeng Linkou District, New Taipei City, 24451, Taiwan, R.O.C.
Performed Location	No. 26, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan, R.O.C.
Phone Number	+886-3-275-7255
Fax Number	+886-3-327-8031

1.6. List of Test Equipment

For Conduction Measurements / HY-SR01

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
V	EMI Test Receiver	R&S	ESR7	101601	2023/06/20	2024/06/19
V	Two-Line V-Network	R&S	ENV216	101306	2023/03/16	2024/03/15
V	Two-Line V-Network	R&S	ENV216	101307	2023/08/17	2024/08/16
V	Coaxial Cable	SUHNER	RG400 BNC	RF001	2023/01/10	2024/01/09

Note:

1. All equipments are calibrated every one year.
2. The test instruments marked with “V” are used to measure the final test results.
3. Test Software Version: e3 230303 dekra V9.

For Conducted Measurements / HY-SR02

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
V	Spectrum Analyzer	R&S	FSV30	103466	2022/12/22	2023/12/21
V	Peak Power Analyzer	KEYSIGHT	8990B	MY51000539	2023/05/15	2024/05/14
V	Power Sensor	KEYSIGHT	N1923A	MY59240002	2023/05/18	2024/05/17
V	Power Sensor	KEYSIGHT	N1923A	MY59240003	2023/05/18	2024/05/17

Note:

1. All equipments are calibrated every one year.
2. The test instruments marked with “V” are used to measure the final test results.
3. Test Software Version: RF Conducted Test Tools R3 V3.0.0.14.

For Radiated Measurements /HY-CB02

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
V	Loop Antenna	AMETEK	HLA6121	49611	2023/02/21	2024/02/20
V	Bi-Log Antenna	SCHWARZBECK	VULB9168	9168-0678	2021/09/23	2023/09/22
V	Horn Antenna	RF SPIN	DRH18-E	210503A18ES	2023/02/24	2024/02/23
V	Horn Antenna	Com-Power	AH-840	101101	2021/11/30	2023/11/29
V	Pre-Amplifier	SGH	EM330	60736	2023/01/10	2024/01/09
V	Pre-Amplifier	SGH	PRAMP118	20200203	2023/01/10	2024/01/09
V	Pre-Amplifier	EMCI	EMC05820SE	980285	2023/01/10	2024/01/09
V	Pre-Amplifier	EMCI	EMC184045SE	980369	2023/01/10	2024/01/09
	Coaxial Cable	EMCI	EMC102-KM-KM-600	1160314		
	Coaxial Cable	EMCI	EMC102-KM-KM-7000	170242		
V	Filter	MICRO TRONICS	BRM50702	G249	2023/01/05	2024/01/04
	Filter	MICRO TRONICS	BRM50716	G187	2023/01/05	2024/01/04
V	EMI Test Receiver	R&S	ESR7	101601	2023/06/20	2024/06/19
V	Spectrum Analyzer	R&S	FSV3044	101113	2023/02/04	2024/02/03
V	Coaxial Cable	SGH	HA800	GD20110223-2	2023/01/10	2024/01/09
	Coaxial Cable	SGH	HA800	GD20110222-4		
	Coaxial Cable	SGH	SGH18	2021005-2		
	Coaxial Cable	SGH	SGH18	202108-5		

Note:

1. Bi-Log Antenna and Horn Antenna (AH-840) is calibrated every two years, the other equipments are calibrated every one year.
2. The test instruments marked with “V” are used to measure the final test results.
3. Test Software Version: e3 230303 dekra V9.

1.7. Uncertainty

Uncertainties have been calculated according to the DEKRA internal document.


The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Test Item	Uncertainty
Conducted Emission	± 3.50 dB
Peak Power Output	± 1.05 dB
Radiated Emission	9 kHz~30 MHz: ± 3.88 dB 30 MHz~1 GHz: ± 4.42 dB 1 GHz~18 GHz: ± 4.28 dB 18 GHz~40 GHz: ± 3.90 dB
RF Antenna Conducted Test	± 2.14 dB
Band Edge	For Radiated: 9 kHz~30 MHz: ± 3.88 dB 30 MHz~1 GHz: ± 4.42 dB 1 GHz~18 GHz: ± 4.28 dB 18 GHz~40 GHz: ± 3.90 dB For Conducted: ± 2.14 dB
Channel Number	N/A
Channel Separation	± 1580.61 Hz
Dwell Time	± 0.53 %
Occupied Bandwidth	± 1580.61 Hz
Duty Cycle	± 0.53 %

2. Conducted Emission

2.1. Test Setup



2.2. Limits

FCC Part 15 Subpart C Paragraph 15.207 (dB μ V) Limit		
Frequency MHz	Limits	
	QP	AV
0.15 - 0.50	66-56	56-46
0.50 - 5.0	56	46
5.0 - 30	60	50

Remarks: In the above table, the tighter limit applies at the band edges.

2.3. Test Procedure


The EUT and Peripherals are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm /50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs.)

Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all the interface cables must be changed according to ANSI C63.4: 2014 on conducted measurement.

Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.


The EUT setup and the test procedure are according to ANSI C63.4, 2014 to comply with the requirements of FCC 47CFR Subpart C.

2.4. Test Result of Conducted Emission



3. Peak Power Output

3.1. Test Setup



3.2. Limit

The maximum peak power shall be less 1 Watt, for all other frequency hopping systems in the 2400-2483.5MHz band: 0.125 watts.

3.3. Test Procedure

Tested according to FHSS test procedure of KDB 558074 section 9 (b for compliance to FCC 47CFR 15.247 requirements.

3.4. Test Result of Peak Power Output

Product : Wireless headphone
Test Item : Peak Power Output
Test Mode : Transmit-1 Mbps_Right
Test Date : 2023/11/22

Channel No.	Frequency (MHz)	Measurement (dBm)	Required Limit	Result
00	2402	9.26	0.125Watt = 21 dBm	Pass
39	2441	9.32	0.125Watt = 21 dBm	Pass
78	2480	9.39	0.125Watt = 21 dBm	Pass

Product : Wireless headphone
Test Item : Peak Power Output
Test Mode : Transmit-2 Mbps_Right
Test Date : 2023/11/22

Channel No.	Frequency (MHz)	Measurement (dBm)	Required Limit	Result
00	2402	10.95	0.125Watt = 21 dBm	Pass
39	2441	11.02	0.125Watt = 21 dBm	Pass
78	2480	11.10	0.125Watt = 21 dBm	Pass

Product : Wireless headphone
Test Item : Peak Power Output
Test Mode : Transmit-3 Mbps_Right
Test Date : 2023/11/22

Channel No.	Frequency (MHz)	Measurement (dBm)	Required Limit	Result
00	2402	8.94	0.125Watt = 21 dBm	Pass
39	2441	9.03	0.125Watt = 21 dBm	Pass
78	2480	9.05	0.125Watt = 21 dBm	Pass

Product : Wireless headphone
Test Item : Peak Power Output
Test Mode : Transmit-1 Mbps_Left
Test Date : 2023/11/22

Channel No.	Frequency (MHz)	Measurement (dBm)	Required Limit	Result
00	2402	9.30	0.125Watt = 21 dBm	Pass
39	2441	9.43	0.125Watt = 21 dBm	Pass
78	2480	9.56	0.125Watt = 21 dBm	Pass

Product : Wireless headphone
Test Item : Peak Power Output
Test Mode : Transmit-2 Mbps_Left
Test Date : 2023/11/22

Channel No.	Frequency (MHz)	Measurement (dBm)	Required Limit	Result
00	2402	10.73	0.125Watt = 21 dBm	Pass
39	2441	10.84	0.125Watt = 21 dBm	Pass
78	2480	10.95	0.125Watt = 21 dBm	Pass


Product : Wireless headphone
Test Item : Peak Power Output
Test Mode : Transmit-3 Mbps_Left
Test Date : 2023/11/22

Channel No.	Frequency (MHz)	Measurement (dBm)	Required Limit	Result
00	2402	8.95	0.125Watt = 21 dBm	Pass
39	2441	9.21	0.125Watt = 21 dBm	Pass
78	2480	9.33	0.125Watt = 21 dBm	Pass


4. Radiated Emission

4.1. Test Setup


Radiated Emission Under 30 MHz



Radiated Emission Below 1 GHz



Radiated Emission Above 1 GHz



4.2. Limits

➤ General Radiated Emission Limits

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

FCC Part 15 Subpart C Paragraph 15.209 Limits		
Frequency MHz	Field strength (microvolts/meter)	Measurement distance (meter)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remarks:

1. RF Voltage (dBμV) = 20 log RF Voltage (μV)
2. In the Above Table, the tighter limit applies at the band edges.
3. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

4.3. Test Procedure

The EUT was setup according to ANSI C63.10, 2013 and tested compliance to FCC 47CFR 15.247 requirements.

Measuring the frequency range below 1 GHz, the EUT is placed on a turn table which is 0.8 meter above ground, when measuring the frequency range above 1GHz, the EUT is placed on a turn table which is 1.5 meter above ground.

The turn table is rotated 360 degrees to determine the position of the maximum emission level.

The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned between 1 meter and 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10: 2013 on radiated measurement.

The resolution bandwidth below 30 MHz setting on the field strength meter is 9kHz and 30 MHz~1 GHz is 120 kHz and above 1 GHz is 1 MHz.

Radiated emission measurements below 30 MHz are made using Loop Antenna and 30 MHz~1 GHz are made using broadband Bilog antenna and above 1 GHz are made using Horn Antennas.


The measurement is divided into the Preliminary Measurement and the Final Measurement.


The suspected frequencies are searched for in Preliminary Measurement with the measurement antenna kept pointed at the source of the emission both in azimuth and elevation, with the polarization of the antenna oriented for maximum response. The antenna is pointed at an angle towards the source of the emission, and the EUT is rotated in both height and polarization to maximize the measured emission. The emission is kept within the illumination area of the 3 dB bandwidth of the antenna.

The measurement frequency range form 9 kHz - 10th Harmonic of fundamental was investigated.


4.4. Test Result of Radiated Emission

Right






Site :HY-CB01
Condition :3m ,HORIZONTAL
Mode :TX_bt2m_2441MHz
TEST BY :Sam



Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.


Site :HY-CB01
Condition :3m ,VERTICAL
Mode :TX_bt2m_2441MHz
TEST BY :Sam



Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.


Site :HY-CB01
Condition :3m ,HORIZONTAL
Mode :TX_bt2m_2480MHz
TEST BY :Sam



Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.


Site :HY-CB01
Condition :3m ,VERTICAL
Mode :TX_bt2m_2480MHz
TEST BY :Sam



Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.


Site :HY-CB02
Condition :3m ,HORIZONTAL
mode :TX_bt3m_2402MHz
Test by :Rock



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB	
1	4804.000	40.80	74.00	-33.20	50.36	-9.56	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.


Site :HY-CB02
Condition :3m ,VERTICAL
mode :TX_bt3m_2402MHz
Test by :Rock



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB	
1	4804.000	40.51	74.00	-33.49	50.07	-9.56	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.


Site :HY-CB02
Condition :3m ,HORIZONTAL
mode :TX_bt3m_2441MHz
Test by :Rock



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB	
1	4882.000	40.72	74.00	-33.28	50.07	-9.35	Peak


Note:
1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Site :HY-CB02
Condition :3m ,VERTICAL
mode :TX_bt3m_2441MHz
Test by :Rock




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB	
1	4882.000	40.10	74.00	-33.90	49.45	-9.35	Peak


Note:
1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.



Left




Site :HY-CB02
Condition :3m ,HORIZONTAL
mode :TX_bt1m_2480MHz
Test by :Rock



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB	
1	4960.000	40.75	74.00	-33.25	49.63	-8.88	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.


Site :HY-CB02
Condition :3m ,VERTICAL
mode :TX_bt1m_2480MHz
Test by :Rock



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB	
1	4960.000	40.30	74.00	-33.70	49.18	-8.88	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.


Site :HY-CB01
Condition :3m ,HORIZONTAL
Mode :TX_bt2m_2482MHz
TEST BY :Sam



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB	
1	4804.000	41.49	74.00	-32.51	55.04	-13.55	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.


Site :HY-CB01
Condition :3m ,VERTICAL
Mode :TX_bt2m_2482MHz
TEST BY :Sam



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB	
1	4804.000	39.40	74.00	-34.60	52.95	-13.55	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.


Site :HY-CB01
Condition :3m ,HORIZONTAL
Mode :TX_bt2m_2441MHz
TEST BY :Sam



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB	
1	4882.000	39.51	74.00	-34.49	52.87	-13.36	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.


Site :HY-CB01
Condition :3m ,VERTICAL
Mode :TX_bt2m_2441MHz
TEST BY :Sam



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB	
1	4882.000	40.60	74.00	-33.40	53.96	-13.36	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.


Site :HY-CB01
Condition :3m ,HORIZONTAL
Mode :TX_bt2m_2480MHz
TEST BY :Sam



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB	
1	4960.000	40.69	74.00	-33.31	53.89	-13.20	Peak


Note:
1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.


Site :HY-CB01
Condition :3m ,VERTICAL
Mode :TX_bt2m_2480MHz
TEST BY :Sam




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB	
1	4960.000	40.78	74.00	-33.22	53.98	-13.20	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.






Site :HY-CB02
Condition :3m ,HORIZONTAL
mode :charge mode
Test by :Rock



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB	
1	31.261	28.26	40.00	-11.74	48.53	-20.27	QP
2	148.437	18.91	43.50	-24.59	37.56	-18.65	QP
3	296.944	18.97	46.00	-27.03	37.32	-18.35	QP
4	582.318	25.53	46.00	-20.47	36.97	-11.44	QP
5	746.539	27.78	46.00	-18.22	36.40	-8.62	QP
6	950.530	29.77	46.00	-16.23	36.09	-6.32	QP

Note:
1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission under 30MHz was not included since the emission levels are very low against the limit.

Site :HY-CB02
Condition :3m ,VERTICAL
mode :charge mode
Test by :Rock




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB	
1	31.455	27.04	40.00	-12.96	47.29	-20.25	QP
2	60.555	24.43	40.00	-15.57	43.81	-19.38	QP
3	148.437	22.06	43.50	-21.44	40.71	-18.65	QP
4	557.971	24.58	46.00	-21.42	36.82	-12.24	QP
5	742.562	28.50	46.00	-17.50	37.15	-8.65	QP
6	950.530	30.26	46.00	-15.74	36.58	-6.32	QP

Note:
1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission under 30MHz was not included since the emission levels are very low against the limit.

5. RF Antenna Conducted Test

5.1. Test Setup



5.2. Limits


According to FCC Section 15.247(d). In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

5.3. Test Procedure

Tested according to FHSS test procedure of KDB558074 section 9 b) for compliance to FCC 47CFR 15.247 requirements.

5.4. Test Result of RF Antenna Conducted Test


Product : Wireless headphone
Test Item : RF Antenna Conducted Test
Test Mode : Transmit-1 Mbps_Right
Test Date : 2023/09/05



Date: 5.SEP.2023 10:40:24

Product : Wireless headphone
Test Item : RF Antenna Conducted Test
Test Mode : Transmit-2 Mbps_Right
Test Date : 2023/09/05


Channel 00



Date: 24.NOV.2023 00:09:32

Product : Wireless headphone
Test Item : RF Antenna Conducted Test
Test Mode : Transmit-3 Mbps_Right
Test Date : 2023/09/05


Channel 78



Date: 5 SEP.2023 12:47:19

Product : Wireless headphone
Test Item : RF Antenna Conducted Test
Test Mode : Transmit-1 Mbps_Left
Test Date : 2023/09/05


Channel 78



Date: 5.SEP.2023 09:49:26

Product : Wireless headphone
Test Item : RF Antenna Conducted Test
Test Mode : Transmit-2 Mbps_Left
Test Date : 2023/09/05


Channel 00



Date: 23.NOV.2023 21:48:55

Product : Wireless headphone
Test Item : RF Antenna Conducted Test
Test Mode : Transmit-3 Mbps_Left
Test Date : 2023/09/05

Channel 78




Date: 5 SEP.2023 09:58:19


6. Band Edge

6.1. Test Setup

RF Conducted Measurement



RF Radiated Measurement:



6.2. Limit

According to FCC Section 15.247(d). In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

6.3. Test Procedure

The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.


The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.10: 2013 on radiated measurement.

The bandwidth setting below 1 GHz and above 1 GHz on the field strength meter is 120 kHz and 1MHz, respectively.

6.4. Test Result of Band Edge

Site :HY-CB02
 Condition :3m ,Horizontal
 mode :TX_bt1m_2402MHz
 Test by :Rock



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2349.400	42.36	74.00	-31.64	35.29	7.07	Peak
2	2402.000	95.29	77.00	18.29	88.56	6.73	Peak


Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Horizontal-Average Detector (Right):

Frequency (MHz)	Peak Measurement (dBμV/m)	Duty Cycle Factor (dB)	Measurement Level (dBμV/m)	Margin (dB)	Limit (dBμV/m)
2349.4	42.36	-15.249	27.111	-26.889	54.000
2402	95.29	-15.249	80.041	--	--

Site :HY-CB02
 Condition :3m ,VERTICAL
 mode :TX_bt1m_2402MHz
 Test by :Rock



No.	Frequency	Level	Limit Line	Over Limit	Read Level	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2355.000	42.39	74.00	-31.61	35.35	7.04	Peak
2	2402.000	101.73	77.00	24.73	95.00	6.73	Peak


Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Vertical-Average Detector (Right):

Frequency (MHz)	Peak Measurement (dBμV/m)	Duty Cycle Factor (dB)	Measurement Level (dBμV/m)	Margin (dB)	Limit (dBμV/m)
2355	42.39	-15.249	27.141	-26.859	54.000
2402	101.73	-15.249	86.481	--	--

Site :HY-CB02
 Condition :3m ,Horizontal
 mode :TX_bt1m_2480MHz
 Test by :Rock



No.	Frequency	Level	Limit Line	Over Limit	Read Level	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2480.200	98.02	77.00	21.02	91.12	6.90	Peak
2	2485.400	42.66	74.00	-31.34	35.75	6.91	Peak


Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Horizontal-Average Detector (Right):

Frequency (MHz)	Peak Measurement (dBμV/m)	Duty Cycle Factor (dB)	Measurement Level (dBμV/m)	Margin (dB)	Limit (dBμV/m)
2480.2	98.02	-15.249	82.771	--	--
2485.4	42.66	-15.249	27.411	-26.589	54.000

Site :HY-CB02
 Condition :3m ,Vertical
 mode :TX_bt1m_2480MHz
 Test by :Rock



No.	Frequency	Level	Limit Line	Over Limit	Read Level	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2480.200	98.32	77.00	21.32	91.42	6.90	Peak
2	2485.000	42.81	74.00	-31.19	35.90	6.91	Peak


Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Vertical-Average Detector (Right):

Frequency (MHz)	Peak Measurement (dBμV/m)	Duty Cycle Factor (dB)	Measurement Level (dBμV/m)	Margin (dB)	Limit (dBμV/m)
2480.2	98.32	-15.249	83.071	--	--
2485	42.81	-15.249	27.561	-26.439	54.000

Site :HY-CB01
 Condition :3m ,Horizontal
 Mode :TX_bt2m_2402MHZ
 TEST BY :Sam



No.	Frequency	Level	Limit Line	Over Limit	Read Level	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2373.200	53.50	74.00	-20.50	47.79	5.71	Peak
2	2402.000	103.98	-----	-----	98.35	5.63	Peak


Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Horizontal-Average Detector (Right):

Frequency (MHz)	Peak Measurement (dBμV/m)	Duty Cycle Factor (dB)	Measurement Level (dBμV/m)	Margin (dB)	Limit (dBμV/m)
2373.2	53.5	-16.863	36.637	-17.363	54.000
2402	103.98	-16.863	87.117	--	--

Site :HY-CB01
 Condition :3m ,Vertical
 Mode :TX_bt2m_2402MHZ
 TEST BY :Sam



No.	Frequency	Level	Limit Line	Over Limit	Read Level	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2327.400	52.60	74.00	-21.40	46.85	5.75	Peak
2	2402.000	100.31	-----	-----	94.68	5.63	Peak


Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Vertical-Average Detector (Right):

Frequency (MHz)	Peak Measurement (dBμV/m)	Duty Cycle Factor (dB)	Measurement Level (dBμV/m)	Margin (dB)	Limit (dBμV/m)
2327.4	52.6	-16.863	35.737	-18.263	54.000
2402	100.31	-16.863	83.447	--	--

Site :HY-CB01
 Condition :3m ,Horizontal
 Mode :TX_bt2m_2480MHZ
 TEST BY :Sam



No.	Frequency	Level	Limit Line	Over Limit	Read Level	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2480.000	102.42	-----	-----	96.75	5.67	Peak
2	2507.800	53.33	74.00	-20.67	47.58	5.75	Peak


Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Horizontal-Average Detector (Right):

Frequency (MHz)	Peak Measurement (dBμV/m)	Duty Cycle Factor (dB)	Measurement Level (dBμV/m)	Margin (dB)	Limit (dBμV/m)
2480	102.42	-16.863	85.557	--	--
2507.8	53.33	-16.863	36.467	-17.533	54.000

Site :HY-CB01
 Condition :3m ,Vertical
 Mode :TX_bt2m_2480MHZ
 TEST BY :Sam



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2480.200	99.52	-----	-----	93.85	5.67	Peak
2	2487.000	52.93	74.00	-21.07	47.24	5.69	Peak


Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Vertical-Average Detector (Right):

Frequency (MHz)	Peak Measurement (dBμV/m)	Duty Cycle Factor (dB)	Measurement Level (dBμV/m)	Margin (dB)	Limit (dBμV/m)
2480.2	99.52	-16.863	82.657	--	--
2487	52.93	-16.863	36.067	-17.933	54.000

Site :HY-CB02
 Condition :3m ,Horizontal
 mode :TX_bt3m_2402MHz
 Test by :Rock



No.	Frequency	Level	Limit Line	Over Limit	Read Level	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2383.200	42.16	74.00	-31.84	35.32	6.84	Peak
2	2401.800	102.45	77.00	25.45	95.72	6.73	Peak


Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Horizontal-Average Detector (Right):

Frequency (MHz)	Peak Measurement (dBμV/m)	Duty Cycle Factor (dB)	Measurement Level (dBμV/m)	Margin (dB)	Limit (dBμV/m)
2383.2	42.16	-18.771	23.389	-30.611	54.000
2401.8	102.45	-18.771	83.679	--	--

Site :HY-CB02
 Condition :3m ,Vertical
 mode :TX_bt3m_2402MHz
 Test by :Rock



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	Limit	Level	dB	
1	2318.000	42.10	74.00	-31.90	35.19	6.91	Peak
2	2401.800	101.68	77.00	24.68	94.95	6.73	Peak


Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Vertical-Average Detector (Right):

Frequency (MHz)	Peak Measurement (dBμV/m)	Duty Cycle Factor (dB)	Measurement Level (dBμV/m)	Margin (dB)	Limit (dBμV/m)
2318	42.1	-18.771	23.329	-30.671	54.000
2401.8	101.68	-18.771	82.909	--	--

Site :HY-CB02
 Condition :3m ,Horizontal
 mode :TX_bt3m_2480MHz
 Test by :Rock



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	Limit	Level	dB	
1	2480.200	98.24	77.00	21.24	91.34	6.90	Peak
2	2484.200	42.25	74.00	-31.75	35.34	6.91	Peak


Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Horizontal-Average Detector (Right):

Frequency (MHz)	Peak Measurement (dBμV/m)	Duty Cycle Factor (dB)	Measurement Level (dBμV/m)	Margin (dB)	Limit (dBμV/m)
2480.2	98.24	-18.771	79.469	--	--
2484.2	42.25	-18.771	23.479	-30.521	54.000

Site :HY-CB02
 Condition :3m ,VERTICAL
 mode :TX_bt3m_2480MHz
 Test by :Rock



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	Limit	Level	dB	
1	2480.200	98.25	77.00	21.25	91.35	6.90	Peak
2	2484.200	42.05	74.00	-31.95	35.14	6.91	Peak


Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Vertical-Average Detector (Right):

Frequency (MHz)	Peak Measurement (dBμV/m)	Duty Cycle Factor (dB)	Measurement Level (dBμV/m)	Margin (dB)	Limit (dBμV/m)
2480.2	98.25	-18.771	79.479	--	--
2484.2	42.05	-18.771	23.279	-30.721	54.000

Site :HY-CB02
 Condition :3m ,Horizontal
 mode :TX_bt1m_2402MHz
 Test by :Rock



No.	Frequency	Level	Limit Line	Over Limit	Read Level	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2374.400	43.27	74.00	-30.73	36.36	6.91	Peak
2	2402.000	100.76	-----	-----	94.03	6.73	Peak


Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Horizontal-Average Detector (Left):

Frequency (MHz)	Peak Measurement (dBμV/m)	Duty Cycle Factor (dB)	Measurement Level (dBμV/m)	Margin (dB)	Limit (dBμV/m)
2374.4	43.27	-15.249	28.021	-25.979	54.000
2402	100.76	-15.249	85.511	--	--

Site :HY-CB02
 Condition :3m ,VERTICAL
 mode :TX_bt1m_2402MHz
 Test by :Rock



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2342.800	42.27	74.00	-31.73	35.23	7.04	Peak
2	2401.800	100.47	-----	-----	93.74	6.73	Peak


Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Vertical-Average Detector (Left):

Frequency (MHz)	Peak Measurement (dBμV/m)	Duty Cycle Factor (dB)	Measurement Level (dBμV/m)	Margin (dB)	Limit (dBμV/m)
2342.8	42.27	-15.249	27.021	-26.979	54.000
2401.8	100.47	-15.249	85.221	--	--

Site :HY-CB02
 Condition :3m ,HORIZONTAL
 mode :TX_bt1m_2480MHz
 Test by :Rock



No.	Frequency	Level	Limit Line	Over Limit	Read Level	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2480.400	98.89	-----	-----	91.99	6.90	Peak
2	2483.600	43.39	74.00	-30.61	36.48	6.91	Peak


Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Horizontal-Average Detector (Left):

Frequency (MHz)	Peak Measurement (dBμV/m)	Duty Cycle Factor (dB)	Measurement Level (dBμV/m)	Margin (dB)	Limit (dBμV/m)
2480.4	98.89	-15.249	83.641	--	--
2483.6	43.39	-15.249	28.141	-25.859	54.000

Site :HY-CB02
 Condition :3m ,VERTICAL
 mode :TX_bt1m_2480MHz
 Test by :Rock



No.	Frequency	Level	Limit Line	Over Limit	Read Level	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2480.000	97.28	-----	-----	90.38	6.90	Peak
2	2484.200	42.58	74.00	-31.42	35.67	6.91	Peak


Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Vertical-Average Detector (Left):

Frequency (MHz)	Peak Measurement (dBμV/m)	Duty Cycle Factor (dB)	Measurement Level (dBμV/m)	Margin (dB)	Limit (dBμV/m)
2480	97.28	-15.249	82.031	--	--
2484.2	42.58	-15.249	27.331	-26.669	54.000

Site :HY-CB01
 Condition :3m ,Horizontal
 Mode :TX_bt2m_2402MHZ
 TEST BY :Sam



No.	Frequency	Level	Limit Line	Over Limit	Read Level	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2320.600	53.75	74.00	-20.25	48.00	5.75	Peak
2	2402.000	101.56	-----	-----	95.93	5.63	Peak


Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Horizontal-Average Detector (Left):

Frequency (MHz)	Peak Measurement (dBμV/m)	Duty Cycle Factor (dB)	Measurement Level (dBμV/m)	Margin (dB)	Limit (dBμV/m)
2320.6	53.75	-18.892	34.858	-19.142	54.000
242.2	101.56	-18.892	82.668	--	--

Site :HY-CB01
 Condition :3m ,Vertical
 Mode :TX_bt2m_2402MHZ
 TEST BY :Sam



No.	Frequency	Level	Limit Line	Over Limit	Read Level	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2344.400	53.26	74.00	-20.74	47.48	5.78	Peak
2	2402.000	102.94	-----	-----	97.31	5.63	Peak


Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Vertical-Average Detector (Left):

Frequency (MHz)	Peak Measurement (dBμV/m)	Duty Cycle Factor (dB)	Measurement Level (dBμV/m)	Margin (dB)	Limit (dBμV/m)
2344.4	53.26	-18.892	34.368	-19.632	54.000
2402	102.94	-18.892	84.048	--	--

Site :HY-CB01
 Condition :3m ,Horizontal
 Mode :TX_bt2m_2480MHZ
 TEST BY :Sam



No.	Frequency	Level	Limit Line	Over Limit	Read Level	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2480.400	98.58	-----	-----	92.91	5.67	Peak
2	2504.400	53.69	74.00	-20.31	47.95	5.74	Peak


Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Horizontal-Average Detector (Left):

Frequency (MHz)	Peak Measurement (dBμV/m)	Duty Cycle Factor (dB)	Measurement Level (dBμV/m)	Margin (dB)	Limit (dBμV/m)
2480.4	98.58	-18.892	79.688	--	--
2504.4	53.69	-18.892	34.798	-19.202	54.000

Site :HY-CB01
 Condition :3m ,Vertical
 Mode :TX_bt2m_2480MHZ
 TEST BY :Sam



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2480.200	99.12	-----	-----	93.45	5.67	Peak
2	2485.400	53.90	74.00	-20.10	48.21	5.69	Peak


Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Vertical-Average Detector (Left):

Frequency (MHz)	Peak Measurement (dBμV/m)	Duty Cycle Factor (dB)	Measurement Level (dBμV/m)	Margin (dB)	Limit (dBμV/m)
248.2	99.12	-18.892	80.228	--	--
2485.4	53.9	-18.892	35.008	-18.992	54.000

Site :HY-CB02
 Condition :3m ,Horizontal
 mode :TX_bt3m_2402MHz
 Test by :Rock



No.	Frequency	Level	Limit Line	Over Limit	Read Level	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2338.200	42.26	74.00	-31.74	35.25	7.01	Peak
2	2402.000	100.57	-----	-----	93.84	6.73	Peak


Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Horizontal-Average Detector (Left):

Frequency (MHz)	Peak Measurement (dBμV/m)	Duty Cycle Factor (dB)	Measurement Level (dBμV/m)	Margin (dB)	Limit (dBμV/m)
2338.2	42.26	-18.771	23.489	-30.511	54.000
2402	100.57	-18.771	81.799	--	--

Site :HY-CB02
 Condition :3m ,VERTICAL
 mode :TX_bt3m_2402MHz
 Test by :Rock



No.	Frequency	Level	Limit Line	Over Limit	Read Level	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2333.200	42.21	74.00	-31.79	35.22	6.99	Peak
2	2402.000	100.65	-----	-----	93.92	6.73	Peak


Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Vertical-Average Detector (Left):

Frequency (MHz)	Peak Measurement (dBμV/m)	Duty Cycle Factor (dB)	Measurement Level (dBμV/m)	Margin (dB)	Limit (dBμV/m)
2333.2	42.21	-18.771	23.439	-30.561	54.000
2402	100.65	-18.771	81.879	--	--

Site :HY-CB02
 Condition :3m ,HORIZONTAL
 mode :TX_bt3m_2480MHz
 Test by :Rock



No.	Frequency	Level	Limit Line	Over Limit	Read Level	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2480.400	99.42	-----	-----	92.52	6.90	Peak
2	2483.600	42.79	74.00	-31.21	35.88	6.91	Peak


Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Horizontal-Average Detector (Left):

Frequency (MHz)	Peak Measurement (dBμV/m)	Duty Cycle Factor (dB)	Measurement Level (dBμV/m)	Margin (dB)	Limit (dBμV/m)
2480.4	99.42	-18.771	80.649	--	--
2483.6	42.79	-18.771	24.019	-29.981	54.000

Site :HY-CB02
 Condition :3m ,VERTICAL
 mode :TX_bt3m_2480MHz
 Test by :Rock



No.	Frequency	Level	Limit Line	Over Limit	Read Level	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2480.400	97.74	-----	-----	90.84	6.90	Peak
2	2489.400	42.41	74.00	-31.59	35.50	6.91	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission levels of other frequencies are very lower than the limit and not show in test report.


Vertical-Average Detector (Left):

Frequency (MHz)	Peak Measurement (dBμV/m)	Duty Cycle Factor (dB)	Measurement Level (dBμV/m)	Margin (dB)	Limit (dBμV/m)
2480.4	97.74	-18.771	78.969	--	--
2489.4	42.41	-18.771	23.639	-30.361	54.000


Product : Wireless headphone
Test Item : Band Edge
Test Mode : Transmit-1 Mbps (Hopping off)_Right
Test Date : 2023/09/05

Measurement Level	Result
Δ (dB)	
> 20	PASS

Channel 00




Channel 78




Product : Wireless headphone
 Test Item : Band Edge
 Test Mode : Transmit-2 Mbps (Hopping off)_Right
 Test Date : 2023/09/05

Measurement Level Δ (dB)	Result
> 20	PASS

Channel 00




Channel 78




Product : Wireless headphone
Test Item : Band Edge
Test Mode : Transmit-3 Mbps (Hopping off)_Right
Test Date : 2023/09/05

Measurement Level Δ (dB)	Result
> 20	PASS

Channel 00




Channel 78




Product : Wireless headphone
Test Item : Band Edge
Test Mode : Transmit-1 Mbps (Hopping off)_Left
Test Date : 2023/09/05

Measurement Level Δ (dB)	Result
> 20	PASS

Channel 00




Channel 78




Product : Wireless headphone
Test Item : Band Edge
Test Mode : Transmit-2 Mbps (Hopping off)_Left
Test Date : 2023/11/23

Measurement Level Δ (dB)	Result
> 20	PASS

Channel 00




Channel 78




Product : Wireless headphone
Test Item : Band Edge
Test Mode : Transmit-3 Mbps (Hopping off)_Left
Test Date : 2023/09/05

Measurement Level Δ (dB)	Result
> 20	PASS

Channel 00




Channel 78



Product : Wireless headphone
 Test Item : Band Edge
 Test Mode : Transmit-1 Mbps (Hopping on)_Right
 Test Date : 2022/12/09

Measurement Level Δ (dB)	Result
> 20	PASS

Channel Hopping




Date: 5.SEP.2023 12:50:14

Product : Wireless headphone
 Test Item : Band Edge
 Test Mode : Transmit-2 Mbps (Hopping on)_Right
 Test Date : 2023/11/24

Measurement Level Δ (dB)	Result
> 20	PASS

Channel Hopping




Date: 24.NOV.2023 00:20:48

Product : Wireless headphone
 Test Item : Band Edge
 Test Mode : Transmit-3 Mbps (Hopping on)_Right
 Test Date : 2023/09/05

Measurement Level Δ (dB)	Result
> 20	PASS

Channel Hopping




Date: 5.SEP.2023 12:57:36

Product : Wireless headphone
 Test Item : Band Edge
 Test Mode : Transmit-1 Mbps (Hopping on)_Left
 Test Date : 2023/09/05

Measurement Level Δ (dB)	Result
> 20	PASS

Channel Hopping




Date: 5.SEP.2023 10:02:01

Product : Wireless headphone
Test Item : Band Edge
Test Mode : Transmit-2 Mbps (Hopping on)_Left
Test Date : 2023/11/23

Measurement Level Δ (dB)	Result
> 20	PASS

Channel Hopping




Date: 23.NOV.2023 22:08:16

Product : Wireless headphone
Test Item : Band Edge
Test Mode : Transmit-3 Mbps (Hopping on)_Left
Test Date : 2023/09/05

Measurement Level Δ (dB)	Result
> 20	PASS


Channel Hopping



Date: 5.SEP.2023 10:08:02

7. Channel Number

7.1. Test Setup



7.2. Limit

Frequency hopping systems operating in the 2400-2483.5 MHz bands shall use at least 15 hopping frequencies.

7.3. Test Procedure


Tested according to FHSS test procedure of KDB558074 section 9 (b for compliance to FCC 47CFR 15.247 requirements.

7.4. Test Result of Channel Number

Product : Wireless headphone
 Test Item : Channel Number
 Test Mode : Transmit-1 Mbps_Right
 Test Date : 2023/09/05


Frequency Range (MHz)	Measurement (Hopping Channel)	Required Limit (Hopping Channel)	Result
2402 ~ 2480	79	>15	Pass

2402 MHz



Date: 5 SEP 2023 12:49:05

2480 MHz



Date: 5 SEP 2023 12:51:32