



No. I20Z60640-SEM08

For

BLU Products, Inc.

Smart Phone

Model name: B130DL

With

Hardware Version: V1.0

Software Version: BLU_B130DL_V10.0.02.05.02.02

FCC ID: YHLBLUB130DL

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Test Laboratory:

CTTL, Telecommunication Technology Labs, CAICT


No. 51, Xueyuan Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504


Email: ctl_terminals@caict.ac.cn, website: www.caict.ac.cn



Picture 1: Constituents of the sample



Picture 2: Left Hand Touch Cheek Position



Picture 3: Left Hand Tilt 15° Position




Picture 4: Right Hand Touch Cheek Position




Picture 5: Right Hand Tilt 15° Position

Test positions for body:


The Body SAR is tested at the following 9 test positions all with the distance =10mm/15mm/0mm between the EUT and the phantom bottom:



Picture 6: Front 10mm




Picture 7: Rear 10mm




Picture 8: Left 10mm




Picture 9: Right 10mm




Picture 10: Top 10mm




Picture 10: Bottom 10mm



Picture 11: Front 15mm




Picture 12: Rear 15mm



Picture 13: Bottom 0mm



Picture 14: Bottom 10mm with Headset



Picture 15: Rear 15mm with Headset