

# TEST REPORT

Product Name : Speaker box  
Model Number : PRO I, PRO II, PRO III, PRO IV, PRO V, PRO VI, PRO VII  
FCC ID : 2AXSN-PROI

Prepared for : ELECTRON-X LLC  
Address : 6005 Milwee st ste 911, Houston, Texas, United States

Prepared by : EMTEK (SHENZHEN) CO., LTD.  
Address : Building 69, Majialong Industry Zone, Nanshan District,  
Shenzhen, Guangdong, China

Tel: (0755) 26954280  
Fax: (0755) 26954282

Report Number : ES201126010W  
Date(s) of Tests : November 26, 2020 to December 10, 2020  
Date of Issue : December 11, 2020

## Table of Contents

<b>1 TEST RESULT CERTIFICATION.....</b>	<b>3</b>
<b>2 EUT TECHNICAL DESCRIPTION .....</b>	<b>4</b>
<b>3 SUMMARY OF TEST RESULT .....</b>	<b>5</b>
<b>4 TEST METHODOLOGY .....</b>	<b>6</b>
4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS .....	6
4.2 MEASUREMENT EQUIPMENT USED.....	6
4.3 DESCRIPTION OF TEST MODES .....	7
<b>5 FACILITIES AND ACCREDITATIONS .....</b>	<b>8</b>
5.1 FACILITIES.....	8
5.2 LABORATORY ACCREDITATIONS AND LISTINGS.....	8
<b>6 TEST SYSTEM UNCERTAINTY .....</b>	<b>8</b>
<b>7 SETUP OF EQUIPMENT UNDER TEST.....</b>	<b>9</b>
7.1 RADIO FREQUENCY TEST SETUP 1 .....	9
7.2 RADIO FREQUENCY TEST SETUP 2 .....	9
7.3 CONDUCTED EMISSION TEST SETUP .....	10
7.4 SUPPORT EQUIPMENT .....	11
<b>8 FREQUENCY HOPPING SYSTEM REQUIREMENTS.....</b>	<b>12</b>
8.1 STANDARD APPLICABLE .....	12
8.2 EUT PSEUDORANDOM FREQUENCY HOPPING SEQUENCE.....	12
8.3 EQUAL HOPPING FREQUENCY USE .....	13
8.4 FREQUENCY HOPPING SYSTEM .....	13
<b>9 TEST REQUIREMENTS .....</b>	<b>14</b>
9.1 20DB BANDWIDTH .....	14
9.2 CARRIER FREQUENCY SEPARATION .....	18
9.3 NUMBER OF HOPPING FREQUENCIES .....	22
9.4 AVERAGE TIME OF OCCUPANCY (DWELL TIME).....	24
9.5 MAXIMUM PEAK CONDUCTED OUTPUT POWER.....	27
9.6 CONDUCTED SPURIOUS EMISSION .....	31
9.7 RADIATED SPURIOUS EMISSION.....	38
9.8 CONDUCTED EMISSION TEST .....	51
9.9 ANTENNA APPLICATION .....	54

## 1 TEST RESULT CERTIFICATION

Applicant : ELECTRON-X LLC  
 Address : 6005 Milwee st ste 911, Houston, Texas, United States  
 Manufacturer : NINGBO CENTRAL STAR ELECTRONIC TECHNOLOGY CO.,LTD  
 Address : #1501 No.7 Building, Smart Park of Ningbo, China 315000  
 EUT : Speaker box  
 Model Name : PRO I, PRO II, PRO III, PRO IV, PRO V, PRO VI, PRO VII  
 Trademark : N/A

Measurement Procedure Used:


APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 2, Subpart J	PASS
FCC 47 CFR Part 15, Subpart C	

The above equipment was tested by EMTEK(SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2 and Part 15.247.

The test results of this report relate only to the tested sample identified in this report.

Date of Test : November 26, 2020 to December 10, 2020

Prepared by :   
Sewen Guo /Editor

Reviewer :   
Joe Xia/Editor

Approve & Authorized Signer :   
  
Lisa Wang/Manager

## 2 EUT TECHNICAL DESCRIPTION

Characteristics	Description
<b>Product Name</b>	Speaker box
<b>Model number</b>	PRO I, PRO II, PRO III, PRO IV, PRO V, PRO VI, PRO VII (Note: The seven models differ only in appearance, We prepared model PRO I for EMC test.)
<b>Sample Number</b>	1#
<b>Device Type</b>	Bluetooth V4.2
<b>Data Rate</b>	1Mbps for GFSK modulation 2Mbps for pi/4-DQPSK modulation
<b>Modulation</b>	GFSK pi/4-DQPSK
<b>Operating Frequency Range</b>	2402-2480MHz
<b>Number of Channels</b>	79 channels
<b>Max Transmit Power</b>	1.514 dBm
<b>Antenna Type</b>	PCB Antenna
<b>Gain</b>	-0.58 dBi
<b>Power supply</b>	AC 120V/60Hz
<b>Temperature Range</b>	-40°C to +85°C
<b>Date of Received</b>	November 26, 2020

**Note:** for more details, please refer to the User's manual of the EUT.

### 3 SUMMARY OF TEST RESULT

FCC PartClause	Test Parameter	Verdict	Remark
15.247(a)(1)	20 dB Bandwidth	PASS	
15.247(a)(1)	Carrier Frequency Separation	PASS	
15.247(a)(1)	Number of Hopping Frequencies	PASS	
15.247(a)(1)	Average Time of Occupancy (Dwell Time)	PASS	
15.247(b)(1)	Maximum Peak Conducted Output Power	PASS	
15.247(c)	Conducted Spurious Emissions	PASS	
15.247(d)	Radiated Spurious Emissions	PASS	
15.209			
15.207	Conducted Emission	PASS	
15.203	Antenna Application	PASS	
NOTE1:N/A (Not Applicable)			

#### RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for FCC ID: 2AXSN-PROI filing to comply with Section 15.247 of the FCC Part 15, Subpart C.

## 4 TEST METHODOLOGY

### 4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards:  
 FCC 47 CFR Part 2, Subpart J  
 FCC 47 CFR Part 15, Subpart C  
 KDB 558074 D01 15.247 Meas Guidance V05r02

### 4.2 MEASUREMENT EQUIPMENT USED

#### 4.2.1 Radiated Emission Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	DUE CAL.
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	May 16, 2020	May 15, 2021
Pre-Amplifier	HP	8447F	2944A07999	May 16, 2020	May 15, 2021
Bilog Antenna	Schwarzbeck	VULB9163	142	May 16, 2020	May 15, 2021
Loop Antenna	ARA	PLA-1030/B	1029	May 16, 2020	May 15, 2021
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170399	May 16, 2020	May 15, 2021
Horn Antenna	Schwarzbeck	BBHA 9120	D143	May 16, 2020	May 15, 2021
Cable	Schwarzbeck	AK9513	ACRX1	May 16, 2020	May 15, 2021
Cable	Rosenberger	N/A	FP2RX2	May 16, 2020	May 15, 2021
Cable	Schwarzbeck	AK9513	CRPX1	May 16, 2020	May 15, 2021
Cable	Schwarzbeck	AK9513	CRRX2	May 16, 2020	May 15, 2021

#### 4.2.2 Radio Frequency Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	DUE CAL.
Spectrum Analyzer	Agilent	E4407B	88156318	May 16, 2020	May 15, 2021
Signal Analyzer	Agilent	N9010A	My53470879	May 16, 2020	May 15, 2021
Power meter	Anritsu	ML2495A	0824006	May 16, 2020	May 15, 2021
Power sensor	Anritsu	MA2411B	0738172	May 16, 2020	May 15, 2021
Spectrum Analyzer	Rohde & Schwarz	FSV40	100967	May 16, 2020	May 15, 2021

#### 4.2.3 Conducted Emission Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LASTCAL.	DUE CAL.
Test Receiver	Rohde & Schwarz	ESCS30	828985/018	May 16, 2020	May 15, 2021
L.I.S.N.	Schwarzbeck	NNLK8129	8129203	May 16, 2020	May 15, 2021
50Ω Coaxial Switch	Anritsu	MP59B	M20531	May 16, 2020	May 15, 2021
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100006	May 16, 2020	May 15, 2021
Voltage Probe	Rohde & Schwarz	TK9416	N/A	May 16, 2020	May 15, 2021
I.S.N	Rohde & Schwarz	ENY22	1109.9508.02	May 16, 2020	May 15, 2021

**Remark:** Each piece of equipment is scheduled for calibration once a year.

#### 4.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (1Mbps for Bluetooth GFSK modulation; 2Mbps for Bluetooth pi/4-DQPSK modulation) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for Bluetooth V4.2

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	39	2441	...	...
1	2403	40	2442	76	2478
2	2404	41	2443	77	2479
...	...	...	...	78	2480

Note:  $fc = 2402\text{MHz} + (k-1) \times 1\text{MHz}$  k=1 to 79

Test Frequency and Channel for Bluetooth V4.2

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	39	2441	78	2480

#### 4.4 TEST SOFTWARE

Item	Software
Conducted Emission :	EMTEK(Ver.CON-03A1)-Shenzhen
Radiated Emission:	EMTEK(Ver.RA-03A1)-Shenzhen

## 5 FACILITIES AND ACCREDITATIONS

### 5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

Building 69, Majialong Industry Zone District, Nanshan District, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 32.

### 5.2 LABORATORY ACCREDITATIONS AND LISTINGS

#### Site Description

EMC Lab. : Accredited by CNAS, 2018.11.30  
 The certificate is valid until 2022.10.28  
 The Laboratory has been assessed and proved to be in compliance with  
 CNAS-CL01:2018 (identical to ISO/IEC 17025:2017)  
 The Certificate Registration Number is L2291

Accredited by FCC  
 Designation Number: CN1204  
 Test Firm Registration Number: 882943

Accredited by A2LA, August 25, 2020  
 The Certificate Number is 4321.01

Accredited by Industry Canada  
 The Conformity Assessment Body Identifier is CN0008.

Name of Firm : EMTEK (SHENZHEN) CO., LTD.  
 Site Location : Building 69, Majialong Industry Zone, Nanshan District, Shenzhen,  
 Guangdong, China

## 6 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:


Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-5}$
Maximum Peak Output Power Test	$\pm 1.0$ dB
Conducted Emissions Test	$\pm 2.0$ dB
Radiated Emission Test	$\pm 2.0$ dB
Occupied Bandwidth Test	$\pm 1.0$ dB
Band Edge Test	$\pm 3$ dB
All emission, radiated	$\pm 3$ dB
Antenna Port Emission	$\pm 3$ dB
Temperature	$\pm 0.5$ °C
Humidity	$\pm 3$ %

Measurement Uncertainty for a level of Confidence of 95%

## 7 SETUP OF EQUIPMENT UNDER TEST

### 7.1 RADIO FREQUENCY TEST SETUP 1

The Bluetooth component's antenna port(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



### 7.2 RADIO FREQUENCY TEST SETUP 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 32.

Below 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.


30MHz-1GHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


Above 1GHz:

The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


(a) Radiated Emission Test Set-Up, Frequency Below 30MHz



(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(c) Radiated Emission Test Set-Up, Frequency above 1000MHz




### 7.3 CONDUCTED EMISSION TEST SETUP

The mains cable of the EUT (Game fitness board) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.1 m.

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.



#### 7.4 SUPPORT EQUIPMENT

**EUT Cable List and Details**

Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

**Auxiliary Cable List and Details**

Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

**Auxiliary Equipment List and Details**

Description	Manufacturer	Model	Serial Number
/	/	/	/

**Notes:**

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

## 8 FREQUENCY HOPPING SYSTEM REQUIREMENTS

### 8.1 Standard Applicable

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

### 8.2 EUT Pseudorandom Frequency Hopping Sequence


The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels.

The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master; the phase in the hopping sequence is determined by the Bluetooth clock of the master. The channel is divided into time slots where each slot corresponds to an RF hop frequency. Consecutive hops correspond to different RF hop frequencies. The normal hop is 1 600 hops/s.


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage, and the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones. Number of shift register stages: 9

Length of pseudo-random sequence:  $2^9 - 1 = 524$  bits

Longest sequence of zeros: 8 (non-inverted signal)



*Linear Feedback Shift Register for Generation of the PRBS sequence*



Each frequency used equally on the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

### 8.3 Equal Hopping Frequency Use

All Bluetooth units participating in the piconet are time and hop-synchronized to the channel.

Example of a 79 hopping sequence in data mode:

35, 27, 6, 44, 14, 61, 74, 32, 1, 11, 23, 2, 55, 65, 29, 3, 9, 52, 78, 58, 40, 25, 0, 7, 18, 26, 76, 60, 47, 50, 2, 5, 16, 37, 70, 63, 66, 54, 20, 13, 4, 8, 15, 21, 26, 10, 73, 77, 67, 69, 43, 24, 57, 39, 46, 72, 48, 33, 17, 31, 75, 19, 41, 62, 68, 28, 51, 66, 30, 56, 34, 59, 71, 22, 49, 64, 38, 45, 36, 42, 53

Each Frequency used equally on the average by each transmitter

### 8.4 Frequency Hopping System

This transmitter device is frequency hopping device, and complies with FCC part 15.247 rule.

This device uses Bluetooth radio which operates in 2400-2483.5 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 79 bands (1 MHz each; centred from 2402 to 2480 MHz) in the range 2,400-2,483.5 MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock.

Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH- enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.

## 9 TEST REQUIREMENTS

### 9.1 20DB BANDWIDTH

#### 9.1.1 Applicable Standard

According to FCC Part 15.247(a)(1) and 558074 D01 15.247 Meas Guidance V05r02

#### 9.1.2 Conformance Limit

No limit requirement.

#### 9.1.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

#### 9.1.4 Test Procedure

The EUT was operating in Bluetooth V4.2 and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 30 kHz.

Set the video bandwidth (VBW) =100kHz.

Set Span= approximately 2 to 3 times the 20 dB bandwidth

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the markerdeltafunction, and move the marker to the other side of the emission, until it is (asclose as possible to) even with the reference marker level. The marker-delta reading atthis point is the 20 dB bandwidth of the emission.



If this value varies with differentmodes of operation (e.g., data rate, modulation format, etc.), repeat this test for eachvariation.



Measure and record the results in the test report.


### Test Results

Temperature: 25°C      Test Date: December 01,2020  
Humidity: 45%      Test By: XW

Modulation Mode	Channel Number	Channel Frequency (MHz)	20dB Bandwidth (kHz)
GFSK	0	2402	846.734
	39	2441	909.017
	78	2480	870.452
pi/4-DQPSK	0	2402	1198.000
	39	2441	1255.000
	78	2480	1295.000

Test Model	20dB Bandwidth		GFSK Modulation											
	Channel 0: 2402MHz													
	<p> Agilent</p> <p>Ch Freq 2.402 GHz Trig Free Occupied Bandwidth</p> <p>Center 2.402000000 GHz</p> <p>Ref 12 dBm #Atten 20 dB Mkr1 2.4020150 GHz -2.45 dBm</p>  <p>10 dB/ Offst 2 dB</p> <p>Center 2.402 GHz Span 3 MHz #Res BW 30 kHz #VBW 100 kHz Sweep 5 ms (401 pts)</p> <table border="1"> <tr> <td>Occupied Bandwidth</td> <td>Occ BW % Pwr</td> <td>99.00 %</td> </tr> <tr> <td>805.5149 kHz</td> <td>x dB</td> <td>-20.00 dB</td> </tr> <tr> <td>Transmit Freq Error</td> <td>21.658 kHz</td> <td></td> </tr> <tr> <td>x dB Bandwidth</td> <td>846.743 kHz</td> <td></td> </tr> </table>	Occupied Bandwidth	Occ BW % Pwr	99.00 %	805.5149 kHz	x dB	-20.00 dB	Transmit Freq Error	21.658 kHz		x dB Bandwidth	846.743 kHz		<p>Freq/Channel</p> <p>Center Freq 2.40200000 GHz</p> <p>Start Freq 2.40050000 GHz</p> <p>Stop Freq 2.40350000 GHz</p> <p>CF Step 300.000000 kHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Scale Type Log Lin</p>
Occupied Bandwidth	Occ BW % Pwr	99.00 %												
805.5149 kHz	x dB	-20.00 dB												
Transmit Freq Error	21.658 kHz													
x dB Bandwidth	846.743 kHz													
	<p>20dB Bandwidth</p> <p>Channel 39: 2441MHz</p> <p> Agilent</p> <p>Ch Freq 2.441 GHz Trig Free Occupied Bandwidth</p> <p>Center 2.441000000 GHz</p> <p>Ref 12 dBm #Atten 20 dB Mkr1 2.4410150 GHz -2.173 dBm</p>  <p>10 dB/ Offst 2 dB</p> <p>Center 2.441 GHz Span 3 MHz #Res BW 30 kHz #VBW 100 kHz Sweep 5 ms (401 pts)</p> <table border="1"> <tr> <td>Occupied Bandwidth</td> <td>Occ BW % Pwr</td> <td>99.00 %</td> </tr> <tr> <td>850.5830 kHz</td> <td>x dB</td> <td>-20.00 dB</td> </tr> <tr> <td>Transmit Freq Error</td> <td>23.973 kHz</td> <td></td> </tr> <tr> <td>x dB Bandwidth</td> <td>909.017 kHz</td> <td></td> </tr> </table>	Occupied Bandwidth	Occ BW % Pwr	99.00 %	850.5830 kHz	x dB	-20.00 dB	Transmit Freq Error	23.973 kHz		x dB Bandwidth	909.017 kHz		<p>Freq/Channel</p> <p>Center Freq 2.44100000 GHz</p> <p>Start Freq 2.43950000 GHz</p> <p>Stop Freq 2.44250000 GHz</p> <p>CF Step 300.000000 kHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Scale Type Log Lin</p>
Occupied Bandwidth	Occ BW % Pwr	99.00 %												
850.5830 kHz	x dB	-20.00 dB												
Transmit Freq Error	23.973 kHz													
x dB Bandwidth	909.017 kHz													

Test Model	20dB Bandwidth													
	Channel 78: 2480MHz	GFSK Modulation												
	<p> Agilent</p> <p>Ch Freq 2.48 GHz Trig Free Occupied Bandwidth</p> <p>Center 2.480000000 GHz</p>  <p>Ref 12 dBm #Atten 20 dB #Peak Log 10 dB/ Offst 2 dB Center 2.48 GHz #Res BW 30 kHz #VBW 100 kHz Span 3 MHz Sweep 5 ms (401 pts)</p> <table border="1"> <tr> <td>Occupied Bandwidth</td> <td>Occ BW % Pwr</td> <td>99.00 %</td> </tr> <tr> <td>859.2164 kHz</td> <td>x dB</td> <td>-20.00 dB</td> </tr> <tr> <td>Transmit Freq Error</td> <td>20.000 kHz</td> <td></td> </tr> <tr> <td>x dB Bandwidth</td> <td>870.452 kHz</td> <td></td> </tr> </table>	Occupied Bandwidth	Occ BW % Pwr	99.00 %	859.2164 kHz	x dB	-20.00 dB	Transmit Freq Error	20.000 kHz		x dB Bandwidth	870.452 kHz		<p>Freq/Channel</p> <p>Center Freq 2.48000000 GHz</p> <p>Start Freq 2.47850000 GHz</p> <p>Stop Freq 2.48150000 GHz</p> <p>CF Step 300.000000 kHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Scale Type Log Lin</p>
Occupied Bandwidth	Occ BW % Pwr	99.00 %												
859.2164 kHz	x dB	-20.00 dB												
Transmit Freq Error	20.000 kHz													
x dB Bandwidth	870.452 kHz													
	20dB Bandwidth													
	Channel 0: 2402MHz	pi/4-DQPSK Modulation												
	<p> Agilent</p> <p>Ch Freq 2.402 GHz Trig Free Occupied Bandwidth</p> <p>Center 2.402000000 GHz</p>  <p>Ref 12 dBm #Atten 20 dB #Peak Log 10 dB/ Offst 2 dB Center 2.402 GHz #Res BW 30 kHz #VBW 100 kHz Span 3 MHz Sweep 5 ms (401 pts)</p> <table border="1"> <tr> <td>Occupied Bandwidth</td> <td>Occ BW % Pwr</td> <td>99.00 %</td> </tr> <tr> <td>1.1357 MHz</td> <td>x dB</td> <td>-20.00 dB</td> </tr> <tr> <td>Transmit Freq Error</td> <td>25.399 kHz</td> <td></td> </tr> <tr> <td>x dB Bandwidth</td> <td>1.198 MHz</td> <td></td> </tr> </table>	Occupied Bandwidth	Occ BW % Pwr	99.00 %	1.1357 MHz	x dB	-20.00 dB	Transmit Freq Error	25.399 kHz		x dB Bandwidth	1.198 MHz		<p>Freq/Channel</p> <p>Center Freq 2.40200000 GHz</p> <p>Start Freq 2.40050000 GHz</p> <p>Stop Freq 2.40350000 GHz</p> <p>CF Step 300.000000 kHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Scale Type Log Lin</p>
Occupied Bandwidth	Occ BW % Pwr	99.00 %												
1.1357 MHz	x dB	-20.00 dB												
Transmit Freq Error	25.399 kHz													
x dB Bandwidth	1.198 MHz													



## 9.2 CARRIER FREQUENCY SEPARATION

### 9.2.1 Applicable Standard

According to FCC Part 15.247(a)(1) and 558074 D01 15.247 Meas Guidance V05r02

### 9.2.2 Conformance Limit

Frequency hopping systems operating in the 2400-2483.5MHz band shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

In case of an output power less than 125mW, the frequency hopping system may have channels separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

### 9.2.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

### 9.2.4 Test Procedure

■ According to FCC Part 15.247(a)(1)

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:  
Set the RBW = 100kHz. Set VBW = 300kHz.

Set the span = wide enough to capture the peaks of two adjacent channels

Set Sweep time = auto couple.

Set Detector = peak. Set Trace mode = max hold.

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.



## Test Results


Temperature: 25°C  
Humidity: 45%


Test Date: December 01, 2020  
Test By: XW

Modulation Mode	Channel Number	Channel Frequency (MHz)	Measurement Bandwidth (kHz)	Limit (kHz)	Verdict
GFSK	0	2402	997.5	>564.49	PASS
	39	2441	1005.0	>606.01	PASS
	78	2480	1005.0	>580.30	PASS
pi/4-DQPSK	0	2402	1012.5	>798.67	PASS
	39	2441	1012.5	>836.67	PASS
	78	2480	1012.5	>863.33	PASS

Note: Limit = 20dB bandwidth \* 2/3, if it is greater than 25kHz and the output power is less than 125mW (21dBm).

Test Model	Carrier Frequency Separation		GFSK Modulation	
	Channel 0: 2402MHz			
	<p></p> <p>The screenshot shows a spectrum analysis plot for Channel 0 at 2.402 GHz. The Y-axis is labeled 'dB/Offst' with values 10, 2, and -2. The X-axis is labeled 'Center 2.402 GHz' and 'Span 3 MHz'. The plot displays two peaks, with markers indicating a frequency separation of 997.5 kHz between them. The center frequency is set to 2.40250000 GHz.</p>	<p><b>Freq/Channel</b></p> <p><b>Center Freq</b> 2.40250000 GHz</p> <p><b>Start Freq</b> 2.40100000 GHz</p> <p><b>Stop Freq</b> 2.40400000 GHz</p> <p><b>CF Step</b> 300.000000 kHz Auto Man</p> <p><b>Freq Offset</b> 0.00000000 Hz</p> <p><b>Signal Track</b> On Off</p> <p><b>Scale Type</b> Log Lin</p>		
	<p></p> <p>The screenshot shows a spectrum analysis plot for Channel 39 at 2.4415 GHz. The Y-axis is labeled 'dB/Offst' with values 10, 2, and -2. The X-axis is labeled 'Center 2.442 GHz' and 'Span 3 MHz'. The plot displays two peaks, with markers indicating a frequency separation of 1.0050 MHz between them. The center frequency is set to 2.44150000 GHz.</p>	<p><b>Freq/Channel</b></p> <p><b>Center Freq</b> 2.44150000 GHz</p> <p><b>Start Freq</b> 2.44000000 GHz</p> <p><b>Stop Freq</b> 2.44300000 GHz</p> <p><b>CF Step</b> 300.000000 kHz Auto Man</p> <p><b>Freq Offset</b> 0.00000000 Hz</p> <p><b>Signal Track</b> On Off</p> <p><b>Scale Type</b> Log Lin</p>		



Test Model	Carrier Frequency Separation										
	Channel 39: 2441MHz										
	pi/4-DQPSK Modulation										
	<p> Agilent</p> <p>Ref 10 dBm      #Atten 20 dB      Mkr1 <math>\Delta</math> 1.0125 MHz Peak Log -0.063 dB</p> <p>10 dB/ Offst 2 dB</p> <p>M1 S2      1R S3 FC      1 AA</p> <p>Center 2.441500000 GHz</p> <p>Center 2.442 GHz      #Res BW 100 kHz      #VBW 300 kHz      Span 3 MHz      Sweep 5 ms (401 pts)</p>	<table border="1"> <thead> <tr> <th>Freq/Channel</th> </tr> </thead> <tbody> <tr> <td>Center Freq 2.44150000 GHz</td> </tr> <tr> <td>Start Freq 2.44000000 GHz</td> </tr> <tr> <td>Stop Freq 2.44300000 GHz</td> </tr> <tr> <td>CF Step 300.000000 kHz</td> </tr> <tr> <td>Auto Man</td> </tr> <tr> <td>Freq Offset 0.00000000 Hz</td> </tr> <tr> <td>Signal Track On Off</td> </tr> <tr> <td>Scale Type Log Lin</td> </tr> </tbody> </table>	Freq/Channel	Center Freq 2.44150000 GHz	Start Freq 2.44000000 GHz	Stop Freq 2.44300000 GHz	CF Step 300.000000 kHz	Auto Man	Freq Offset 0.00000000 Hz	Signal Track On Off	Scale Type Log Lin
Freq/Channel											
Center Freq 2.44150000 GHz											
Start Freq 2.44000000 GHz											
Stop Freq 2.44300000 GHz											
CF Step 300.000000 kHz											
Auto Man											
Freq Offset 0.00000000 Hz											
Signal Track On Off											
Scale Type Log Lin											
	<p> Agilent</p> <p>Ref 10 dBm      #Atten 20 dB      Mkr1 <math>\Delta</math> 1.0125 MHz Peak Log -0.167 dB</p> <p>10 dB/ Offst 2 dB</p> <p>M1 S2      1R S3 FC      1 AA</p> <p>Center 2.479500000 GHz</p> <p>Center 2.479 GHz      #Res BW 100 kHz      #VBW 300 kHz      Span 3 MHz      Sweep 5 ms (401 pts)</p>	<table border="1"> <thead> <tr> <th>Freq/Channel</th> </tr> </thead> <tbody> <tr> <td>Center Freq 2.47950000 GHz</td> </tr> <tr> <td>Start Freq 2.47800000 GHz</td> </tr> <tr> <td>Stop Freq 2.48100000 GHz</td> </tr> <tr> <td>CF Step 300.000000 kHz</td> </tr> <tr> <td>Auto Man</td> </tr> <tr> <td>Freq Offset 0.00000000 Hz</td> </tr> <tr> <td>Signal Track On Off</td> </tr> <tr> <td>Scale Type Log Lin</td> </tr> </tbody> </table>	Freq/Channel	Center Freq 2.47950000 GHz	Start Freq 2.47800000 GHz	Stop Freq 2.48100000 GHz	CF Step 300.000000 kHz	Auto Man	Freq Offset 0.00000000 Hz	Signal Track On Off	Scale Type Log Lin
Freq/Channel											
Center Freq 2.47950000 GHz											
Start Freq 2.47800000 GHz											
Stop Freq 2.48100000 GHz											
CF Step 300.000000 kHz											
Auto Man											
Freq Offset 0.00000000 Hz											
Signal Track On Off											
Scale Type Log Lin											

### 9.3 NUMBER OF HOPPING FREQUENCIES

#### 9.3.1 Applicable Standard

According to FCC Part 15.247(a)(1) (iii)and 558074 D01 15.247 Meas Guidance V05r02

#### 9.3.2 Conformance Limit

Frequency hopping systems operating in the 2400-2483.5MHz band shall use at least 15 channels.

#### 9.3.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

#### 9.3.4 Test Procedure

- According to FCC Part15.247(a)(1)(iii)

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW = 100kHz

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. It may prove necessary to break the span up to sections, inorder to clearly show all of the hopping frequencies.


### Test Results

Temperature: 25°C  
Humidity: 45 %

Test Date: December 01,2020  
Test By: XW

Hopping Channel Frequency Range	Quantity of Hopping Channel	Quantity of Hopping Channel limit
2402-2480 (GFSK)	79	>15

Note: Note: Both BR & EDR mode has same result .



## 9.4 AVERAGE TIME OF OCCUPANCY (DWELL TIME)

### 9.4.1 Applicable Standard

According to FCC Part 15.247(a)(1)(iii) and 558074 D01 15.247 Meas Guidance V05r02

### 9.4.2 Conformance Limit

For frequency hopping systems operating in the 2400-2483.5MHz band, the averagetime of occupancy on any channel shall not be greater than 0.4s within a period of 0.4smultiplied by the number of hopping channels employed.

### 9.4.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

### 9.4.4 Test Procedure

- According to FCC Part15.247(a)(1)(iii)

The EUT must have its hopping function enabled. Use the following spectrum analyzersettings:

Span = zero span, centered on a hopping channel

RBW = 1 MHz

VBW  $\geq$  RBW

Sweep = as necessary to capture the entire dwell time per hopping channel

Detector function = peak

Trace = max hold

If possible, use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphsof this Section.

### 9.4.5 Test Results

Temperature: 25°C  
Humidity: 45 %

Test Date: December 01,2020  
Test By: XW


Modulation Mode	Channel Number	Packet type	Pluse width (ms)	DwellTime (ms)	Limit (ms)	Verdict
GFSK	0	DH1	0.43	137.60	<400	PASS
	0	DH3	1.68	268.80	<400	PASS
	0	DH5	2.93	312.53	<400	PASS


Note1: DwellTime(DH1)=PW\*(1600/2/79)\*31.6

DwellTime(DH3)=PW\*(1600/4/79)\*31.6

DwellTime(DH5)=PW\*(1600/6/79)\*31.6

Note2: Bluetooth (GFSK, pi/4-DQPSK)mode have been tested, and the worst results has been recorded on the follow page.





## 9.5 MAXIMUM PEAK CONDUCTED OUTPUT POWER

### 9.5.1 Applicable Standard

According to FCC Part 15.247(b)(1) and 558074 D01 15.247 Meas Guidance V05r02

### 9.5.2 Conformance Limit

The max For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

### 9.5.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

### 9.5.4 Test Procedure

- According to FCC Part15.247(b)(1)

As an alternative to a peak power measurement, compliance with the limit can be based on a measurement of the maximum conducted output power.

Use the following spectrum analyzer settings:

Set Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel(about 10MHz)

Set RBW > the 20 dB bandwidth of the emission being measured(about 3MHz)

Set VBW ≥ RBW

Set Sweep = auto

Set Detector function = peak

Set Trace = max hold

Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emissionto determine the peak amplitude level.

## Test Results

Temperature: 25°C

Humidity: 45 %

Test Date:



December 01,2020



Test By:



XW

Operation Mode	Channel Number	Channel Frequency (MHz)	MeasurementLevel (dBm)	Limit (dBm)	Verdict
GFSK	0	2402	0.894	21	PASS
	39	2441	0.973	21	PASS
	78	2480	0.884	21	PASS
pi/4-DQPSK	0	2402	1.514	21	PASS
	39	2441	1.139	21	PASS
	78	2480	1.077	21	PASS

Note:N/A

Test Model	Maximum PeakConducted Output Power		GFSK
	Channel 0: 2402MHz		
	<p> Agilent</p> <p>Ref 10 dBm      #Atten 20 dB      Mkr1 2.402225 GHz      0.894 dBm</p> <p>Peak Log 10 dB/Offst 2 dB</p>  <p>M1 S2 S3 FC AA</p> <p>Center 2.402000000 GHz</p> <p>Center 2.402 GHz      VBW 3 MHz      Span 10 MHz      Sweep 4 ms (401 pts)</p>	<p><b>Freq/Channel</b></p> <p><b>Center Freq</b> 2.40200000 GHz</p> <p><b>Start Freq</b> 2.39700000 GHz</p> <p><b>Stop Freq</b> 2.40700000 GHz</p> <p><b>CF Step</b> 1.00000000 MHz Auto Man</p> <p><b>Freq Offset</b> 0.00000000 Hz</p> <p><b>Signal Track</b> On Off</p> <p><b>Scale Type</b> Log Lin</p>	
	<p> Agilent</p> <p>Ref 10 dBm      #Atten 20 dB      Mkr1 2.441225 GHz      0.973 dBm</p> <p>Peak Log 10 dB/Offst 2 dB</p>  <p>M1 S2 S3 FC AA</p> <p>Center 2.441000000 GHz</p> <p>Center 2.441 GHz      VBW 3 MHz      Span 10 MHz      Sweep 4 ms (401 pts)</p>	<p><b>Freq/Channel</b></p> <p><b>Center Freq</b> 2.44100000 GHz</p> <p><b>Start Freq</b> 2.43600000 GHz</p> <p><b>Stop Freq</b> 2.44600000 GHz</p> <p><b>CF Step</b> 1.00000000 MHz Auto Man</p> <p><b>Freq Offset</b> 0.00000000 Hz</p> <p><b>Signal Track</b> On Off</p> <p><b>Scale Type</b> Log Lin</p>	

Test Model	Maximum PeakConducted Output Power	
	Channel 78: 2480MHz	
	GFSK	
	 <p>Agilent</p> <p>Mkr1 2.480175 GHz 0.884 dBm</p> <p>Ref 10 dBm #Atten 20 dB</p> <p>Peak Log 10 dB/Offst 2 dB</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.48000000 GHz</p> <p>Center 2.48 GHz #Res BW 3 MHz VBW 3 MHz Sweep 4 ms (401 pts)</p> <p>Span 10 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.48000000 GHz</p> <p>Start Freq 2.47500000 GHz</p> <p>Stop Freq 2.48500000 GHz</p> <p>CF Step 1.00000000 MHz Auto</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Scale Type Log Lin</p>	
	 <p>Agilent</p> <p>Mkr1 2.402250 GHz 1.514 dBm</p> <p>Ref 10 dBm #Atten 20 dB</p> <p>Peak Log 10 dB/Offst 2 dB</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.40200000 GHz</p> <p>Center 2.402 GHz #Res BW 3 MHz VBW 3 MHz Sweep 4 ms (401 pts)</p> <p>Span 10 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.40200000 GHz</p> <p>Start Freq 2.39700000 GHz</p> <p>Stop Freq 2.40700000 GHz</p> <p>CF Step 1.00000000 MHz Auto</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Scale Type Log Lin</p>	pi/4-DQPSK

Test Model	Maximum PeakConducted Output Power		pi/4-DQPSK
	Channel 39: 2441MHz		
	<p> Agilent</p> <p>Ref 10 dBm      #Atten 20 dB      Mkr1 2.440925 GHz      1.139 dBm</p> <p>Peak Log 10 dB/Offst 2 dB</p>  <p>M1 S2 S3 FC AA</p> <p>Center 2.441000000 GHz</p> <p>Center 2.441 GHz      #Res BW 3 MHz      VBW 3 MHz      Span 10 MHz      Sweep 4 ms (401 pts)</p>	<p><b>Freq/Channel</b></p> <p><b>Center Freq</b> 2.44100000 GHz</p> <p><b>Start Freq</b> 2.43600000 GHz</p> <p><b>Stop Freq</b> 2.44600000 GHz</p> <p><b>CF Step</b> 1.00000000 MHz Auto Man</p> <p><b>Freq Offset</b> 0.00000000 Hz</p> <p><b>Signal Track</b> On Off</p> <p><b>Scale Type</b> Log Lin</p>	
	<p> Agilent</p> <p>Ref 10 dBm      #Atten 20 dB      Mkr1 2.480225 GHz      1.077 dBm</p> <p>Peak Log 10 dB/Offst 2 dB</p>  <p>M1 S2 S3 FC AA</p> <p>Center 2.480000000 GHz</p> <p>Center 2.48 GHz      #Res BW 3 MHz      VBW 3 MHz      Span 10 MHz      Sweep 4 ms (401 pts)</p>	<p><b>Freq/Channel</b></p> <p><b>Center Freq</b> 2.48000000 GHz</p> <p><b>Start Freq</b> 2.47500000 GHz</p> <p><b>Stop Freq</b> 2.48500000 GHz</p> <p><b>CF Step</b> 1.00000000 MHz Auto Man</p> <p><b>Freq Offset</b> 0.00000000 Hz</p> <p><b>Signal Track</b> On Off</p> <p><b>Scale Type</b> Log Lin</p>	

## 9.6 CONDUCTED SUPRIOUS EMISSION

### 9.6.1 Applicable Standard

According to FCC Part 15.247(d) and 558074 D01 15.247 Meas Guidance V05r02

### 9.6.2 Conformance Limit

According to FCC Part 15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted, provided the transmitter demonstrates compliance with the peak conducted power limits.

### 9.6.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

### 9.6.4 Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer

#### ■ Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DSS channel center frequency.

Set Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel.

Set the RBW = 100 kHz. Set the VBW  $\geq$  3 x RBW.

Set Detector = peak. Set Sweep time = auto couple.

Set Trace mode = max hold. Allow trace to fully stabilize.

Use the peak marker function to determine the maximum Maximumconductedlevel.

Note that the channel found to contain the maximum conducted level can be used to establish the reference level.

#### ■ Band-edge Compliance of RF Conducted Emissions

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the emission operating on the channel closest to the band-edge, as well as any modulation products which fall outside of the authorized band of operation

Set RBW  $\geq$  1% of the span=100kHzSet VBW  $\geq$  RBW

Set Sweep = autoSetDetector function = peakSetTrace = max hold

Allow the trace to stabilize. Set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. The marker-delta value now displayed must comply with the limit specified in this Section.

Now, using the same instrument settings, enable the hopping function of the EUT. Allow the trace to stabilize. Follow the same procedure listed above to determine if any spurious emissions caused by the hopping function also comply with the specified limit.

#### ■ ConductedSpurious RF Conducted Emission

Use the following spectrum analyzer settings:


Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic.(30MHz to 25GHz).Set RBW = 100 kHzSetVBW $\geq$  RBW



Set Sweep = autoSetDetector function = peakSetTrace = max hold



Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded. The level displayed must comply with the limit specified in this Section.


### 9.6.5 Test Results


Bluetooth (GFSK, pi/4-DQPSK) mode have been tested, and the worst result(GFSK)was report as below:




Test Model	Band-edge Conducted Emissions		GFSK
	Channel 0: 2402MHz		
	<p><b>Agilent</b></p> <p>Ref 10 dBm      #Atten 20 dB      Mkr1 2.4000000 GHz      -26.64 dBm</p> <p>Peak Log 10 dB/Offst 2 dB</p> <p>Dl -21.5 dBm</p> <p>M1 S2 S3 FC AA</p> <p>Start 2.390000000 GHz</p> <p>Start 2.39 GHz      #Res BW 100 kHz      #VBW 300 kHz      Stop 2.403 GHz      Sweep 4 ms (401 pts)</p> 	<p><b>Freq/Channel</b></p> <p><b>Center Freq</b> 2.39650000 GHz</p> <p><b>Start Freq</b> 2.390000000 GHz</p> <p><b>Stop Freq</b> 2.403000000 GHz</p> <p><b>CF Step</b> 1.300000000 MHz Auto</p> <p><b>Freq Offset</b> 0.000000000 Hz</p> <p><b>Signal Track</b> On Off</p> <p><b>Scale Type</b> Log Lin</p>	
	<p><b>Agilent</b></p> <p>Ref 10 dBm      #Atten 20 dB      Mkr1 2.4410350 GHz      -1.348 dBm</p> <p>Peak Log 10 dB/Offst 2 dB</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.441000000 GHz</p> <p>Center 2.441 GHz      #Res BW 100 kHz      #VBW 300 kHz      Span 7 MHz      Sweep 5 ms (401 pts)</p> 	<p><b>Freq/Channel</b></p> <p><b>Center Freq</b> 2.441000000 GHz</p> <p><b>Start Freq</b> 2.437500000 GHz</p> <p><b>Stop Freq</b> 2.444500000 GHz</p> <p><b>CF Step</b> 700.0000000 kHz Auto</p> <p><b>Freq Offset</b> 0.000000000 Hz</p> <p><b>Signal Track</b> On Off</p> <p><b>Scale Type</b> Log Lin</p>	

Test Model	Conducted Spurious RF Conducted Emission		GFSK	
	Channel 39: 2441MHz			
	 <p>Agilent</p> <p>Ref 10 dBm #Atten 20 dB Mkr1 4.883 GHz -36.6 dBm</p> <p>Peak Log 10 dB/Offst 2 dB DI -21.3 dBm</p> <p>M1 S2 S3 FC AA</p> <p>Start 30.000000000 MHz</p> <p>Start 30 MHz Stop 25 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 2.587 s (8192 pts)</p>	<b>Freq/Channel</b> <b>Center Freq</b> <b>Start Freq</b> <b>Stop Freq</b> <b>CF Step</b> <b>Freq Offset</b> <b>Signal Track</b> <b>Scale Type</b>		
	 <p>Agilent</p> <p>Ref 10 dBm #Atten 20 dB Mkr1 2.4800175 GHz -1.351 dBm</p> <p>Peak Log 10 dB/Offst 2 dB</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.480000000 GHz</p> <p>Center 2.48 GHz #Res BW 100 kHz #VBW 300 kHz Span 7 MHz Sweep 5 ms (401 pts)</p>	<b>Freq/Channel</b> <b>Center Freq</b> <b>Start Freq</b> <b>Stop Freq</b> <b>CF Step</b> <b>Freq Offset</b> <b>Signal Track</b> <b>Scale Type</b>		







## 9.7 RADIATED SPURIOUS EMISSION

### 9.7.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and 558074 D01 15.247 Meas Guidance V05r02

### 9.7.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).  
According to FCC Part15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part15.209,the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength ( $\mu$ V/m)	Field Strength ( $dB\mu$ V/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log ( $\mu$ V/m)	300
0.490-1.705	24000/F(KHz)	20 log ( $\mu$ V/m)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

### 9.7.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

### 9.7.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for  $f \geq 1$  GHz(1GHz to 25GHz), 100 kHz for  $f < 1$  GHz(30MHz to 1GHz)

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2013 respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from  $20\log(\text{dwell time}/100 \text{ ms})$ , in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

### 9.7.5 Test Results

#### ■ Spurious Emission below 30MHz(9KHz to 30MHz)

Temperature:	24 °C	Test Date:	December 01,2020
Humidity:	55 %	Test By:	XW
Test mode:	TX Mode		

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance}/\text{test distance})(\text{ dB})$ ;  
Limit line=Specific limits(dBuV) + distance extrapolation factor

#### ■ Spurious Emission Above 1GHz(1GHz to 25GHz)

Bluetooth (GFSK, pi/4-DQPSK, non hopping) mode have been tested, and the worst result(GFSK)was report as below:

Temperature:	24 °C	Test Date:	December 01,2020
Humidity:	55 %	Test By:	XW
Test mode:	GFSK	Frequency:	Channel 0: 2402MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
5195.955	V	53.06	44.56	74.00	54.00	-20.94	-9.44
11385.43	V	54.53	46.31	74.00	54.00	-19.47	-7.69
17905.48	V	57.31	49.82	74.00	54.00	-16.69	-4.18
10944.62	H	52.62	43.59	74.00	54.00	-21.38	-10.41
13474.62	H	52.09	44.64	74.00	54.00	-21.91	-9.36
17905.48	H	55.14	46.77	74.00	54.00	-18.86	-7.23

Temperature: 24°C  
 Humidity: 55 %  
 Test mode: GFSK

Test Date: December 01,2020  
 Test By: XW  
 Frequency: Channel 39: 2441MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
6430.836	V	52.36	43.69	74.00	54.00	-21.64	-10.31
11566.68	V	53.76	44.95	74.00	54.00	-20.24	-9.05
16031.35	V	54.25	45.76	74.00	54.00	-19.75	-8.24
5168.671	H	50.72	41.32	74.00	54.00	-23.28	-12.68
11597.17	H	55.30	46.87	74.00	54.00	-18.70	-7.13
14203.04	H	55.92	44.55	74.00	54.00	-18.08	-9.45

Temperature: 24°C  
 Humidity: 55 %  
 Test mode: GFSK

Test Date: December 01,2020  
 Test By: XW  
 Frequency: Channel 78: 2480MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4865.018	V	43.75	42.33	74.00	54.00	-30.25	-11.67
11031.40	V	55.12	46.53	74.00	54.00	-18.88	-7.47
17952.67	V	54.57	44.72	74.00	54.00	-19.43	-9.28
9645.521	H	53.77	44.16	74.00	54.00	-20.23	-9.84
13439.19	H	55.38	46.27	74.00	54.00	-18.62	-7.73
18000.00	H	54.74	45.39	74.00	54.00	-19.26	-8.61

- Note:** (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).  
 (2) Emission Level= Reading Level+Correct Factor +Cable Loss.  
 (3) Correct Factor= Ant\_F + Cab\_L - Preamp  
 (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz  
 Bluetooth (GFSK, pi/4-DQPSK) mode have been tested, and the worst result(GFSK, Hopping)  
 was report as below:

Temperature:	24°C	Test Date:	December 01,2020
Humidity:	55%	Test By:	XW
Test mode:	GFSK	Frequency:	Channel 0: 2402MHz

Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	Over(dB)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)	Over (dB)
2386.230	H	48.88	74.00	-25.12	39.69	54.00	-14.31
2388.077	V	47.53	74.00	-26.47	37.88	54.00	-16.12


Temperature:	24°C	Test Date:	December 01,2020
Humidity:	55%	Test By:	XW
Test mode:	GFSK	Frequency:	Channel 78: 2480MHz


Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	Over(dB)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)	Over (dB)
2483.500	H	53.47	74.00	-20.53	44.23	54.00	-9.77
2483.575	V	49.68	74.00	-24.32	40.19	54.00	-13.81


Temperature:	24°C	Test Date:	December 01,2020
Humidity:	55%	Test By:	XW
Test mode:	GFSK	Frequency:	Hopping

Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	Over(dB)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)	Over (dB)
2390.000	H	42.55	74.00	-31.45	32.11	54.00	-21.89
2483.500	H	47.95	74.00	-26.05	38.64	54.00	-15.36
2390.000	V	40.74	74.00	-33.26	30.21	54.00	-23.79
2483.500	V	43.63	74.00	-30.37	33.45	54.00	-20.55

- Note:**
- (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).
  - (2) Emission Level= Reading Level+Correct Factor +Cable Loss.
  - (3) Correct Factor= Ant\_F + Cab\_L - Preamp
  - (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.










■ Spurious Emission below 1GHz(30MHz to 1GHz)

Bluetooth (GFSK, pi/4-DQPSK) mode have been tested, and the worst result(GFSK) recorded was report as below:







Site Radiated Emission 3m #1

Polarization: **Horizontal**

Temperature: 24

Limit: (RE)FCC PART 15 C


Power: AC 120V/60Hz

Humidity: 55 %

Mode: TX 2441MHz

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Detector	Height cm	Table Degree	Comment
1		180.0164	55.61	-25.81	29.80	43.50	-13.70	QP			
2		300.3672	51.09	-20.19	30.90	46.00	-15.10	QP			
3	I	360.4476	61.10	-19.40	41.70	46.00	-4.30	QP			
4		420.5803	54.00	-18.00	36.00	46.00	-10.00	QP			
5	*	480.5276	58.99	-16.59	42.40	46.00	-3.60	QP			
6		601.4265	51.58	-13.98	37.60	46.00	-8.40	QP			



Site Radiated Emission 3m #1

Polarization: **Vertical**

Temperature: 24

Limit: ( RE)FCC PART 15 C


Power: AC 120V/60Hz


Humidity: 55 %

Mode:TX 2441MHz

Note:

No.	Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Antenna Height	Table Degree	Comment
			dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	
1	*	180.0164	63.61	-25.81	37.80	43.50	-5.70	QP		
2		243.3771	48.60	-22.60	26.00	46.00	-20.00	QP		
3		300.3672	49.09	-20.19	28.90	46.00	-17.10	QP		
4		312.1794	37.89	-19.89	18.00	46.00	-28.00	QP		
5		360.4476	44.40	-19.40	25.00	46.00	-21.00	QP		
6		480.5276	47.09	-16.59	30.50	46.00	-15.50	QP		





## 9.8 CONDUCTED EMISSION TEST

### 9.8.1 Applicable Standard

According to FCC Part 15.207(a)

### 9.8.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit		Average
	Quasi-peak		
0.15-0.5	66-56		56-46
0.5-5.0	56		46
5.0-30.0	60		50

Note: 1. The lower limit shall apply at the transition frequencies  
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 9.8.3 Test Configuration


Test according to clause 7.3 conducted emission test setup

### 9.8.4 Test Procedure

The EUT was placed on a table which is 0.1m above ground plane.  
Maximum procedure was performed on the highest emissions to ensure EUT compliance.  
Repeat above procedures until all frequency measured were complete.

### 9.8.5 Test Results

Pass.



Site: site #1

Phase: L1

Temperature: 24

Limit: (CE)FCC PART 15.207\_QP


Power: AC 120V/60Hz

Humidity: 50 %

Mode: TX

Note:

No.	Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Comment
			dBuV	dB	dBuV	dB	Detector	
1	*	0.1500	51.80	10.10	61.90	66.00	-4.10	QP
2		0.1500	24.40	10.10	34.50	56.00	-21.50	AVG
3		0.1632	49.90	10.10	60.00	65.30	-5.30	QP
4		0.1632	22.80	10.10	32.90	55.30	-22.40	AVG
5		0.1820	48.20	10.09	58.29	64.39	-6.10	QP
6		0.1820	19.30	10.09	29.39	54.39	-25.00	AVG
7		0.2150	46.90	10.09	56.99	63.01	-6.02	QP
8		0.2150	17.40	10.09	27.49	53.01	-25.52	AVG
9		0.2430	44.40	10.09	54.49	61.99	-7.50	QP
10		0.2430	14.20	10.09	24.29	51.99	-27.70	AVG
11		0.2820	43.30	10.09	53.39	60.76	-7.37	QP
12		0.2820	13.60	10.09	23.69	50.76	-27.07	AVG



Site site #1

Phase: *N*

Temperature: 24

Limit: (CE)FCC PART 15.207\_QP

Power: AC 120V/60Hz

Humidity: 50 %

Mode: TX

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV	dBuV	dB		
1	*	0.1500	51.20	10.07	61.27	66.00	-4.73		QP
2		0.1500	23.00	10.07	33.07	56.00	-22.93		AVG
3		0.1620	47.70	10.08	57.78	65.36	-7.58		QP
4		0.1620	21.70	10.08	31.78	55.36	-23.58		AVG
5		0.2061	46.00	10.08	56.08	63.36	-7.28		QP
6		0.2061	17.70	10.08	27.78	53.36	-25.58		AVG
7		0.2505	45.60	10.09	55.69	61.74	-6.05		QP
8		0.2505	13.30	10.09	23.39	51.74	-28.35		AVG
9		0.3420	42.60	10.09	52.69	59.15	-6.46		QP
10		0.3420	11.00	10.09	21.09	49.15	-28.06		AVG
11		0.4304	39.40	10.10	49.50	57.24	-7.74		QP
12		0.4304	9.20	10.10	19.30	47.24	-27.94		AVG

## 9.9 ANTENNA APPLICATION

### 9.9.1 Antenna Requirement

Standard	Requirement
FCC CRF Part15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### 9.9.2 Result

PASS.

The EUT has 1 antenna: a PCB Antenna gain is -0.58 dBi;

- Note:
- Antenna use a permanently attached antenna which is not replaceable.
  - Not using a standard antenna jack or electrical connector for antenna replacement
  - The antenna has to be professionally installed (please provide method of installation)

which in accordance to section 15.203, please refer to the internal photos.

\*\*\* End of Report \*\*\*

# 声 明

## Statement

1. 本报告无授权批准人签字及“检验报告专用章”无效；

This report will be void without authorized signature or special seal for testing report.

2. 未经许可本报告不得部分复制；

This report shall not be copied partly without authorization.

3. 本报告的检测结果仅对送测样品有效，委托方对样品的代表性和资料的真实性负责；

The test results or observations are applicable only to tested sample. Client shall be responsible for representativeness of the sample and authenticity of the material.

4. 本检测报告中检测项目标注有特殊符号则该项目不在资质认定范围内，仅作为客户委托、科研、教学或内部质量控制等目的使用；

The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.

5. 本检测报告以实测值进行符合性判定，未考虑不确定度所带来的风险，本实验室不承担相关责任，特别约定、标准或规范中有明确规定的除外；

The test results or observations are provided in accordance with measured value, without taking risks caused by uncertainty into account. Without explicit stipulation in special agreements, standards or regulations, EMTEK shall not assume any responsibility.

6. 对本检测报告若有异议，请于收到报告之日起 20 日内提出；

Objections shall be raised within 20 days from the date receiving the report.