

# FCC Test Report

Report No.: AGC00319241102FE01

FCC ID		2A300RB58
APPLICATION PURPOSE	:	Original Equipment
PRODUCT DESIGNATION	:	Two Way Radio
BRAND NAME	:	RETEVIS
MODEL NAME	:	RB58
APPLICANT	:	Shenzhen Ysair Technology Co., LTD
DATE OF ISSUE	:	Feb. 08, 2025
STANDARD(S)	:	FCC Part 15 Subpart B
<b>REPORT VERSION</b>	:	V1.0







## **Report Revise Record**

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Feb. 08, 2025	Valid	Initial Release



# **Table of Contents**

1. General Information	4
2. Product Information	5
2.1 Product Technical Description	5
2.2 Auxiliary Surrounding Description	5
2.2 Test Methodology	6
2.3 Description of Test Modes	6
3. Test Environment	7
3.1 Address of The Test Laboratory	7
3.2 Test Facility	7
3.3 Environmental Conditions	8
3.4 Measurement Uncertainty	8
3.5 List of Equipment Used	9
4. Summary of Test Results	
5. Radiated Emission Measurements	11
5.1 Provisions Applicable	11
5.2 Measurement Setup	
5.3 Measurement Procedure	
5.4 Measurement Result	
6. Conducted Emission Measurements	
6.1 Provisions Applicable	
6.2 Measurement Setup	
6.3 Measurement Procedure	
6.4 Measurement Result	
7. Antenna Conducted Power for Receivers	
7.1 Provisions Applicable	
7.2 Measurement Setup	
7.3 Measurement Procedure	
7.4 Measurement Result	
8. Scanning Receivers and Frequency Converters Used with Scanning Receivers	
8.1 Provisions Applicable	
8.2 Measurement Setup	
8.3 Measurement Procedure	
8.4 Measurement Result	
Appendix I: Photographs of Test Setup	
Appendix II: Photographs of Test EUT	



## **1. General Information**

Shenzhen Ysair Technology Co., LTD			
Room 403, 4th Floor, Building 4, Yunli Intelligent Park, No. 3 Changfa Middle Road, Yangmei Community, Bantian Street, Longgang District, Shenzhen			
Shenzhen Ysair Technology Co., LTD			
Room 403, 4th Floor, Building 4, Yunli Intelligent Park, No. 3 Changfa Middle Road, Yangmei Community, Bantian Street, Longgang District, Shenzhen			
N/A			
N/A			
Two Way Radio			
RETEVIS			
RB58			
N/A			
N/A			
Nov. 26, 2024			
Nov. 26, 2024~Jan. 22, 2025			
No any deviation from the test method			
Normal			
Pass			
AGCTR-ER-FCC-CSR-V1.0			

Note: The test results of this report relate only to the tested sample identified in this report.

Bibo zhang Prepared By Bibo Zhang Feb. 08, 2025 (Project Engineer) lvin Lin **Reviewed By** Calvin Liu Feb. 08, 2025 (Reviewer) Approved By Angela Li Feb. 08, 2025 (Authorized Officer)



## 2. Product Information

#### 2.1 Product Technical Description

Housing Type	Plastic and metal		
Receive Frequency Range	400-470MHz (Scanning Receiver)		
Highest Operating Frequency	Greater than 108MHz		
Equipment Type Table-Top			
Hardware Version	V1.01.02.007_20241213		
Software Version	RB58-M-1 V4.0		
Power Supply	DC 3.7V 1800mAh by battery		
Adapter Information	Input: AC 100-240V 50/60Hz, 0.35A Output: DC 5V 2A		

#### I/O Port Information ( Applicable

Not Applicable)

I/O Port of EUT						
I/O Port Type Q'TY Cable Tested with						
Antenna Port	1	0	1			
Type C Port	1	1.2m unshielded	1			
Earphone Port	1	0	1			

## 2.2 Auxiliary Surrounding Description

The Following Peripheral Devices and Interface Cables Were Connected During the Measurement:

- Test Accessories Come From The Laboratory
- ☑ Test Accessories Come From The Manufacturer

No.	Equipment	Manufacturer	Model No.	Specification Information	Cable
1	Battery	Retevis	BL58	DC 3.7V 1800mAh	
2	Adapter	N/A	A70-050200U-EU1	Input: AC 100-240V 50/60Hz 0.35A Output: DC 5V 2A	



## 2.2 Test Methodology

The tests were performed according to following standards:

No.	Identity	Document Title
1	FCC 47 CFR Part 15	Radio Frequency Devices
2	ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

#### 2.3 Description of Test Modes

No.	Test Mode	Remark
1	Scanning mode	Worst
2	Scanning stopped/Receiving at low channel of 400 MHz to 470 MHz	
3	Scanning stopped/Receiving at middle channel of 400 MHz to 470 MHz	
4	Scanning stopped/Receiving at high channel of 400 MHz to 470 MHz	

Note: Only the result of the worst case was recorded in the report.



## 3. Test Environment

#### 3.1 Address of The Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

#### 3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

#### A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

#### FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

#### IC-Registration No.: 24842 (CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



#### **3.3 Environmental Conditions**

	Normal Conditions
Temperature range (°C)	15 - 35
Relative humidity range	20 % - 75 %
Pressure range (kPa)	86 - 106

#### **3.4 Measurement Uncertainty**

The reported uncertainty of measurement y  $\pm$ U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty		
Uncertainty of Conducted Emission	$U_c = \pm 2.9 \text{ dB}$		
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.9 \text{ dB}$		
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.9 \text{ dB}$		



#### 3.5 List of Equipment Used

•	Radiated Emission							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)	
	AGC-EM-E046	EMI Test Receiver	R&S	ESCI	10096	2024-02-01	2025-01-31	
$\boxtimes$	AGC-EM-E116	EMI Test Receiver	R&S	ESCI	100034	2024-05-24	2025-05-23	
$\boxtimes$	AGC-EM-E061	Spectrum Analyzer	Agilent	N9010A	MY53470504	2024-05-28	2025-05-27	
$\boxtimes$	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023-05-11	2025-05-10	
$\boxtimes$	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023-05-11	2025-05-10	
$\boxtimes$	AGC-EM-E029	Broadband Ridged Horn Antenna	ETS	3117	00034609	2023-03-23	2025-03-22	
$\boxtimes$	AGC-EM-E146	Pre-amplifier	ETS	3117-PA	00246148	2024-07-24	2026-07-23	
$\boxtimes$	AGC-ER-A004	Power Splitter	Agilent	11667B	N/A	2024-05-23	2025-05-22	
$\boxtimes$	AGC-EM-E002	Wireless Connectivity Tester	HP	8920B	US35010161	2024-05-24	2025-05-23	

•	AC Power Line	Conducted Emissi	on				
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
$\square$	AGC-EM-E045	EMI Test Receiver	R&S	ESPI	101206	2024-05-28	2025-05-27
$\boxtimes$	AGC-EM-E023	AMN	R&S	100086	ESH2-Z5	2024-05-28	2025-05-27

• Tes	st Software				
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Version Information
$\boxtimes$	AGC-EM-S004	RE Test System	Tonscend	TS <sup>+</sup> Ver2.1(JS32-RE)	4.0.0.0
	AGC-EM-S003	RE Test System	FARA	EZ-EMC	V.RA-03A
$\boxtimes$	AGC-EM-S011	RSE Test System	Tonscend	TS <sup>+</sup> Ver2.1(JS36-RSE)	4.0.0.0
$\square$	AGC-EM-S001	CE Test System	R&S	ES-K1	V1.71



# 4. Summary of Test Results

Item	FCC Rules	Description Of Test	Class/Severity	Result
1	Section 15.107	Radiated Emission	Class B	Pass
2	Section 15.109	Conducted Emission	Class B	Pass
3	§15.111	Antenna Conducted Power for Receivers	/	Pass
4	§15.121(b)	Scanning receivers and frequency converters used with scanning receivers	/	Pass




## 5. Radiated Emission Measurements

#### **5.1 Provisions Applicable**


#### FCC CFR Title 47 Part 15 Subpart B Section 15.109:

Frequency Range	Class B Limit (dBuV/m @3m)	Class A Limit (dBuV/m @3m)	Value
30MHz-88MHz	40.00	50.00	Quasi-peak
88MHz-216MHz	43.50	53.50	Quasi-peak
216MHz-960MHz	46.00	56.00	Quasi-peak
960MHz-1GHz	54.00	64.00	Quasi-peak
Above 1GHz	54.00	60.00	Average
	74.00	80.00	Peak

#### 5.2 Measurement Setup



#### Radiated Emission Measurements Test Setup for 30MHz to 1GHz



## Radiated Emission Measurements Test Setup for above 1GHz



#### 5.3 Measurement Procedure

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.4.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4. The EUT received power by AC 120V/60Hz.
- 5. The antenna was placed at 3 meter away from the EUT as stated in FCC Part 15. The antenna connected to the Analyzer via a cable and at times a pre-amplifier would be used.
- 6. The Analyzer / Receiver quickly scanned from 30MHz to 1000MHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- 7. The test mode(s) were scanned during the test:
- 8. Recorded at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit and Q.P./Peak reading is presented. For emissions below 1GHz, use 120KHz RBW and VBW>=3RBW for QP reading.
- 9. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
- 10. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 11. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 12. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 13. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.
- 14. The test data of the worst case condition (mode 1) was reported on the following Data page.

## **EMI Test Receiver Setup:**

During the radiated emission test, the EMI test receiver was set with the following configurations:


Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
Above T GHz	1MHz	10 Hz	/	Ave.




#### **5.4 Measurement Result**

			Ra	diated Em	ission 30MHz	-1GHz Test R	esult		
Test N	lode	Mode 1				Polarity:		Horizonta	I
	130				FCC Part 1	5B			
	120								
	110								
	90								
[₩/	80 70								
Level[dBµV/m]	60								
Le	50 40								5
	30	K	- <b>*</b>	* m	n number	Ν	- And -	har mar man and har	June -
	10			J 0000	Mr.	and the second second second			
	-10								
	30M			100M	Frequency[	Hz]			1G
			orizontal PK						
Final	Data List								
NO.	Freq. [MHz]		_evel 3µV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	36.79	2	23.96	11.23	40.00	16.04	100	3	Horizontal
2	46.49	2	28.49	13.47	40.00	11.51	100	86	Horizontal
3	60.07	2	23.54	17.86	40.00	16.46	100	152	Horizontal
4	83.35	2	23.88	12.64	40.00	16.12	100	232	Horizontal
5	141.55	5 3	31.36	16.13	43.50	12.14	100	69	Horizontal
6	861.29	) 3	36.06	29.97	46.00	9.94	100	15	Horizontal

## **RESULT: PASS**









			Rad	diated Emi	ssion Above1	GHz Te	st Resu	ılt		
Test M	lode	Mod	e 1			Pola	arity:		Horizonta	l
	130				FCC Part 15B					
	120 110									
	100 90									
	80									
	[W, 70 60 50									
	40	mon	and the and the and the and	which is not man and a state of the	which with which we have been a provided in	renyigestephilogenticyt	antication of the state of the	and and the second s	wwwwwww	wate
	20									
	-10									
	1G			20	Frequency[Hz]	3G		4G	5G	6G
		<ul> <li>PK Limit</li> <li>AV Detect</li> </ul>		orizontal PK						
Final	Data List									
NO.	Freq [MHz		Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Mar [dE		Height [cm]	Angle [°]	Polarity
1	1241.04	821	33.06	-17.95	74.00	40.9	94	100	40	Horizontal
2	1786.15	7231	35.09	-15.18	74.00	38.9	91	100	240	Horizontal
3	2342.268	8454	38.80	-12.58	74.00	35.2	20	100	300	Horizontal
4	3374.474	4895	37.92	-10.97	74.00	36.	08	100	100	Horizontal
5	4569.713	3943	40.57	-7.86	74.00	33.4	43	100	190	Horizontal
6	5875.97	5195	43.33	-5.77	74.00	30.	67	100	360	Horizontal



			Rad	diated Emis	ssion Above1	GHz T	est Res	ult			
Test M	lode	Mod	e 1			Po	larity:		Ver	tical	
	130 120 110 90 80 70 60 50 40 30 20 10 -10 16	- PK Limit		contract of the second se	FCC Part 15B			46		5G	6G
Final	Data List										
NO.	Freq [MHz		Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]		argin 1B]	Heigh [cm]	t A	ngle [°]	Polarity
1	1252.05	5041	32.76	-17.93	74.00	41	.24	100		260	Vertical
2	1784.15	6831	35.08	-15.19	74.00	38	8.92	100	2	220	Vertical
3	2339.26	7854	37.37	-12.59	74.00	36	5.63	100		140	Vertical
4	3366.47	3295	39.00	-10.99	74.00	35	5.00	100	2	260	Vertical
5	4564.71	2943	39.65	-7.87	74.00	34	.35	100	:	300	Vertical
6	5658.93	1786	42.13	-6.41	74.00	31	.87	100		0	Vertical

## Note:

- 1. Factor=Antenna Factor + Cable loss Amplifier gain, Margin= Limit-Measurement.
- 2. The "Factor" value can be calculated automatically by software of measurement system.



## 6. Conducted Emission Measurements

#### **6.1 Provisions Applicable**


FCC CFR Title 47 Part 15 Subpart B Section 15.107: For Class B Limits:

Frequency	Maximum RF Line Voltage			
Frequency	Q.P. (dBµV)	Average (dBµV)		
150kHz~500kHz	66-56	56-46		
500kHz~5MHz	56	46		
5MHz~30MHz	60	50		

For Class A Limits:

Frequency	Maximum RF Line Voltage			
Frequency	Q.P. (dBµV)	Average (dBµV)		
150kHz~500kHz	79	66		
500kHz~30MHz	73	60		

#### 6.2 Measurement Setup






#### **6.3 Measurement Procedure**

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.4.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4. The EUT received AC 120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5. All support equipment received AC power from a second LISN, if any.
- 6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test data of the worst case condition (Mode 1) was reported on the following Data page.



#### **6.4 Measurement Result**



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com

 Web: http://www.agccert.com/





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com



## 7. Antenna Conducted Power for Receivers

#### 7.1 Provisions Applicable

The antenna conducted power of the receiver as defined in §15.111 shall not exceed the values given in the following tables

Frequency Range	9 KHz to 2GHz
Limit	2.0 nW (-57 dBm )

#### 7.2 Measurement Setup

	Spectrum analyzer	
	EUT	
Restored to	Non-Conducted Table	

#### 7.3 Measurement Procedure

- 1. The receiver antenna terminal connected to a spectrum analyzer.
- 2. Receiver set as follow:

Frequency range	RBW (kHz)	VBW (kHz)	
9 kHz ~ 150 kHz	1	3	
150 kHz ~ 30 MHz	10	30	
30 MHz ~ 1000 MHz	100	300	
1000 MHz ~ 3000 MHz	1000	3000	

3. The test data of the worst case condition (mode 1) was reported on the following Data page.




#### 7.4 Measurement Result

Frequency Avg Type: Log-Pwr Avg|Hold:>100/100 Start Freq 9.000 kHz Trig: Free Run TYF PNO: Wide 😱 IFGain:Low Atten: 6 dB Auto Tune Mkr1 9.273 kHz -76.826 dBm 10 dB/div Ref -37.00 dBm **Center Freq** 79.500 kHz Start Freq 9.000 kHz Stop Freq 150.000 kHz man man m wv CF Step 14.100 kHz Marman Markan ale Auto Man Freq Offset 0 Hz Stop 150.00 kHz Sweep 136.0 ms (30000 pts) Start 9.00 kHz #Res BW 1.0 kHz #VBW 3.0 kHz Test\_Graph\_RX\_FrequencyRange\_9kHz-150kHz - Swept SA gilent Spectrum Analyzer c 26, 2024 Frequency Avg Type: Log-Pwr Avg|Hold:>100/100 Start Freq 150.000 kHz RACE 123 TYPE MWW Trig: Free Run Atten: 6 dB PNO: Fast 😱 IFGain:Low DET Mkr1 160.0 kHz -79.943 dBm Auto Tune Ref -37.00 dBm 10 dB/div **Center Freq** 15.075000 MHz Start Freq 150.000 kHz Stop Freq 30.000000 MHz CF Step 2.985000 MHz Auto Man **Freq Offset** 0 Hz Start 150 kHz #Res BW 10 kHz Stop 30.00 MHz #VBW 30 kHz Sweep 286.0 ms (30000 pts) STATUS Test\_Graph\_RX\_FrequencyRange\_150kHz-30MHz

#### Test Graphs of Antenna Conducted Power for Receivers








## 8. Scanning Receivers and Frequency Converters Used with Scanning Receivers

#### 8.1 Provisions Applicable

Except as provided in paragraph (c) of this section, scanning receivers shall reject any signals from the Cellular Radiotelephone Service frequency bands that are 38 dB or lower based upon a 12 dB SINAD measurement, which is considered the threshold where a signal can be clearly discerned from any interference that may be present.

#### 8.2 Measurement Setup



#### 8.3 Measurement Procedure

- 1) Connected the EUT as shown in the above block diagram.
- 2) Apply a RF signal to the receiver input port at lowest, middle and highest channel frequencies of receiver operation band.
- 3) Adjust the audio output level of the receiver to it's rated value with the distortion less than 10%.
- 4) Adjust the RF Signal Generator Output Power to produce 12 dB SINAD without the audio output power dropping by more than 3 dB. This output level of the RF SG at each channel frequency is the sensitivity of the receiver.
- 5) Select the lowest or worse-case sensitivity level for all of the bands as the reference sensitivity.
- 6) Adjust the RF Signal Generator output to a level of +60 dB above the reference sensitivity obtained in step 5) and its frequency to the frequency points in the cellular band.
- 7) Set the Receiver squelch to threshold, the signal required to open the squelch must be lower than the reference sensitivity level.
- 8) Set the receiver in a scanning mode and allow it to scan through it's complete receiving range.
- 9) If the receiver unsquelched or stopped on any frequency, receiving at this frequency, then adjust the signal generator output level until 12 dB SINAD is produced, this level is the spurious value and the difference between the reference sensitivity and the spurious value is the rejection ratio and must be at least 38dB.
- 10) Repeat above procedure at the frequencies 824.5, 836.0, and 848.5 MHz for the mobile band, and 869.1, 881.5, and 893.5MHz for the cellular base band.



#### **8.4 Measurement Result**

Scanning Frequency Band (MHz)	Test Frequency of Cellular Band (MHz)	Spurious Value of Cellular Frequency (dBm)	Reference Sensitivity (dBm)	Measurement Result (dB)	Limit (dB)
400-470	824.5/836.0/848.5	>-44	-107	<-63	<-38
400-470	869.1/881.5/893.5	>-44	-107	<-63	<-38

Note:

1. Measurement Result = Rejection Ratio

2. Reference Sensitivity is the recorded value when the signal-to-noise ratio is 12dB.

3. Measurement Result = Reference Sensitivity- Spurious Value.



Report No.: AGC00319241102FE01 Page 26 of 26

# Appendix I: Photographs of Test Setup

Refer to the Report No.: AGC00319241102AP03

## Appendix II: Photographs of Test EUT

Refer to the Report No.: AGC00319241102AP02

-----End of Report-----



## Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").

2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.

3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.

4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.

5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.

6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.

7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.

8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.

9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.