

Report No: TW2203329-04E File reference No: 2022-05-10

Applicant: Shenzhen Jingwah Information Technology Co., Ltd.

Product: Tablet PC

Model No: K13

Trademark: TechPad

Test Standards: FCC Part 15 Subpart E, Paragraph 15.407

Test result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.10, FCC Part 15 Subpart C, Paragraph 15.247 regulations for the evaluation of

electromagnetic compatibility

Approved By

Term long

Terry Tang

Manager

Dated: May 10, 2022

Results appearing herein relate only to the sample tested

The technical reports is issued errors and omissions exempt and is subject to withdrawal at

SHENZHEN TIMEWAY TESTING LABORATORIES

Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le Village, Nanshan District, Shenzhen, China

Tel (755) 83448688, Fax (755) 83442996, E-Mail:info@timeway-lab.com

Date: 2022-05-10



Page 2 of 166

Special Statement:

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meet with ISO/IEC-17025 requirements, which is approved by CNAL. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAS-LAB Code: L2292

The EMC Laboratory has been assessed and in compliance with CNAS-CL01 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of testing Laboratories.

FCC-Registration No.: 744189

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 744189.

Industry Canada (IC) — Registration No.:5205A

The EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 5205A.

A2LA (Certification Number:5013.01)

The EMC Laboratory has been accredited by the American Association for Laboratory Accreditation (A2LA). Certification Number:5013.01

Page 3 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Test Report Conclusion

Content

1.0	General Details	4
1.1	Test Lab Details.	4
1.2	Applicant Details	4
1.3	Description of EUT	4
1.4	Submitted Sample.	6
1.5	Test Duration.	6
1.6	Test Uncertainty.	6
1.7	Test By	6
2.0	List of Measurement Equipment	7
3.0	Technical Details	8
3.1	Summary of Test Results.	8
3.2	Test Standards.	8
4.0	EUT Modification.	8
5.0	Power Line Conducted Emission Test.	9
5.1	Schematics of the Test.	9
5.2	Test Method and Test Procedure.	9
5.3	Configuration of the EUT.	9
5.4	EUT Operating Condition.	10
5.5	Conducted Emission Limit.	10
5.6	Test Result.	10
6.0	Undesirable Emission and Restrict band.	13
7.0	Bandwidth Measurement.	38
8.0	Peak Transmit Power Measurement.	121
9.0	Peak Power Spectral Density Measurement	127
10.0	Frequency Stability	162
11.0	Antenna Requirement.	165
12.0	FCC ID Label.	166
13.0	Photo of Test Setup and EUT View.	167

Date: 2022-05-10



1.0 General Details

1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TESTING LABORATORIES.

Address: Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le

Village, Nanshan District, Shenzhen, China

Telephone: (755) 83448688 Fax: (755) 83442996

Site Listed with Federal Communications commission (FCC)

Registration Number: 744189 For 3m Anechoic Chamber

Site Listed with Industry Canada of Ottawa, Canada

Registration Number: IC: 5205A

For 3m Anechoic Chamber

1.2 Applicant Details

Applicant: Shenzhen Jingwah Information Technology Co., Ltd.

Address: 6F, Bldg.4, Jinghua Square, No. 168, Zhenzhong Rd., Fuqiang Community, Huaqiangbei, Futian

District, Shenzhen

Telephone: -Fax: -
1.3 Description of EUT

Product: Tablet PC

Manufacturer: Shenzhen Jingwah Information Technology Co., Ltd.

Address: 6F, Bldg.4, Jinghua Square, No. 168, Zhenzhong Rd., Fuqiang Community,

Huaqiangbei, Futian District, Shenzhen

Trademark: TechPad
Additional Trademark: N/A
Model Number: K13
Additional Model Number: N/A

raditional Wodel (Valloe), 14/1

Hardware Version: TH1330-RK3566-V3.1

Software Version: Android 11

Serial No.: JK132203000001~UP

Rating: DC3.7V, 3A

Battery: DC3.7V, 10000mAh Li-ion battery
Power Supply: Model: TPQ-228F050300UW01;

Input: 100-240V~, 50/60Hz, 0.5A; Output: DC3.7V, 3A

Type of Modulation IEEE 802.11a/n (HT20/HT40): OFDM (64QAM, 16QAM, QPSK, BPSK);

IEEE 802.11ac: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM

Frequency Band 1: 5180MHz-5240MHz;

Band 4: 5745MHz-5825MHz

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Date: 2022-05-10



Air Data Rate IEEE 802.11a: 54, 48,36, 24, 18, 12, 9, 6 Mbps

IEEE 802.11n/HT20: mcs0-mcs15 IEEE 802.11n/HT40: mcs0-mcs15 IEEE 802.11ac: NSS1 mcs0-mcs9

Antenna: Integral Antenna. The gain of the antennas is 0.8dBi (Declared by the applicant)

Test Mode: During testing, EUT was set to 100% duty cycle. 6Mbps air data rate was the worst case

for 802.11a mode; mcs0 air data rate was the worst case for 802.11n mode; NSS1 mcs0

air data rate was the worst case for 802.11ac mode;

Frequency Selection By software

Each Channel Operation Frequency

Each Channel Operation Frequency							
	Band 1						
802.11a / 11n HT2	20 / 802.11ac VHT20	802.11n HT ²	40 / 802.11acVHT40	802.11ac VHT80			
Channel	Frequency	Channel	Frequency	Channel	Frequency		
36	5180MHz	38	5190 MHz	42	5210 MHz		
40	5200 MHz	46	5230 MHz				
44	5220 MHz						
48	5240 MHz						
		Е	Sand 4	•			
802.11a / 11n HT2	20 / 802.11ac VHT20	802.11n HT40 / 802.11acVHT40		802.11ac VHT80			
Channel	Frequency	Channel	Frequency	Channel	Frequency		
149	5745 MHz	151	5755 MHz	155	5775 MHz		
153	5765 MHz	159	5795 MHz				
157	5785 MHz						
161	5825 MHz						

The selected test channels as follows:

	Band 1							
802.11a /	802.11a / 11n HT20 802.11n HT40			802.11	ac VHT80			
Channel	Frequency	Channel	Frequency	Channel	Frequency			
36	5180MHz	38	5190 MHz	42	5210 MHz			
40	5200 MHz	46	5230 MHz					
48	5240 MHz							

	Band 4							
802.11a /	11n HT20	802.11n HT40		802.11ac VHT80				
Channel	Frequency	Channel Frequency		Channel	Frequency			
149	5745 MHz	151	5755 MHz	155	5775 MHz			
153	5765 MHz	159	5795 MHz					

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: TW2203329-04E Page 6 of 166

Date: 2022-05-10



161	5825 MHz		
101	3823 MHZ		

Note: 802.11ac VHT20/VHT40 is similar with 802.11n HT20/HT40.

1.4 Submitted Sample: 2 Samples

1.5 Test Duration

2022-03-23 to 2022-05-10

1.6 Test Uncertainty

Conducted Emissions Uncertainty = 3.6dB

Radiated Emissions below 1GHz Uncertainty =4.7dB

Radiated Emissions above 1GHz Uncertainty =6.0dB

Conducted Power Uncertainty =6.0dB

Occupied Channel Bandwidth Uncertainty =5%

Note: The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

1.7 Test Engineer

The sample tested by

Print Name: Andy Xing

Date: 2022-05-10



2.0 Test Equipment	:				
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	R&S	ESPI 3	100379	2021-06-18	2022-06-17
LISN	R&S	EZH3-Z5	100294	2021-06-18	2022-06-17
LISN	R&S	EZH3-Z5	100253	2021-06-18	2022-06-17
Impuls-Begrenzer	R&S	ESH3-Z2	100281	2021-06-18	2022-06-17
Loop Antenna	EMCO	6507	00078608	2021-06-18	2024-06-17
Spectrum	R&S	FSIQ26	100292	2021-06-18	2022-06-17
Horn Antenna	A-INFO	LB-180400-KF	J211060660	2021-06-18	2022-06-17
Horn Antenna	R&S	BBHA 9120D	9120D-631	2021-07-02	2024-07-01
Power meter	Anritsu	ML2487A	6K00003613	2021-06-18	2022-06-17
Power sensor	Anritsu	MA2491A	32263	2021-06-18	2022-06-17
Bilog Antenna	Schwarebeck	VULB9163	9163/340	2021-07-02	2024-07-01
9*6*6 Anechoic			N/A	2021-07-02	2022-07-01
EMI Test Receiver	RS	ESVB	826156/011	2021-06-18	2022-06-17
EMI Test Receiver	RS	ESH3	860904/006	2021-06-18	2022-06-17
Spectrum	HP/Agilent	ESA-L1500A	US37451154	2021-06-18	2022-06-17
Spectrum	HP/Agilent	E4407B	MY50441392	2021-06-18	2022-06-17
Spectrum	RS	FSP	1164.4391.38	2022-01-14	2023-01-13
DE C-1-1-	71 1:	ZT26-NJ-NJ-8		2021 07 19	2022 07 17
RF Cable	Zhengdi	M/FA		2021-06-18	2022-06-17
RF Cable	Zhengdi	7m		2021-06-18	2022-06-17
RF Switch	EM	EMSW18	060391	2021-06-18	2022-06-17
Pre-Amplifier	Schwarebeck	BBV9743	#218	2021-06-18	2022-06-17
Pre-Amplifier	HP/Agilent	8449B	3008A00160	2021-06-18	2022-06-17
LISN	SCHAFFNER	NNB42	00012	2022-01-05	2023-01-04

2.2 Automation Test Software

For Conducted Emission Test

Name	Version
EZ-EMC	Ver.EMC-CON 3A1.1

For Radiated Emissions

Name	Version
EMI Test Software BL410-EV18.91	V18.905
EMI Test Software BL410-EV18.806 High Frequency	V18.06

The report refers only to the sample tested and does not apply to the bulk.

This report released in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.

Page 8 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



3.0 **Technical Details**

3.1 **Summary of test results**

The EUT has been tested according to the following specifications:					
Standard	Test Type	Result	Notes		
FCC Part 15, Paragraph 15.407	Conducted Emission Test	Pass	Complies		
FCC Part 15 Subpart E Paragraph 15.407 (b1/4/5/6/7), Part 15.205 and Part 15.209	Undesirable Emission and Restrict band	Pass	Complies		
FCC Part 15, Paragraph 15.407 (a1/2/3)	Peak Transmit Power	Pass	Complies		
FCC Part 15, Paragraph 15.407 (a)(6)	Peak Power Excursion	Pass	Complies		
FCC Part 15, Paragraph 15.407 (a/1/2/3)	Peak Power Spectral Density	Pass	Complies		
FCC Part 15, Paragraph 15.407(g)	Frequency Stability	Pass	Complies		

3.2 **Test Standards**

FCC Part 15 Subpart & Subpart C, Paragraph 15.247, ANSI C63.10:2013 and ANSI C63.4:2014 789033 D02 General UNII Test Procedures New Rules v01r04

4.0 **EUT Modification**


No modification by SHENZHEN TIMEWAY TESTING LABORATORIES.

Date: 2022-05-10



5. Power Line Conducted Emission Test

5.1 Schematics of the test




EUT: Equipment Under Test

5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.10-2009. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.10-2013.

Test Voltage: DC3.7V, 60Hz Block diagram of Test setup



5.3 Configuration of the EUT

The EUT was configured according to ANSI C63.10-2013. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

A. EUT

Device	Manufacturer	Model	FCC ID
Tablet PC	Shenzhen Jingwah Information Technology Co., Ltd.	K13	RBD-K13

Report No.: TW2203329-04E Page 10 of 166

Date: 2022-05-10



B. Internal Device

Device	Manufacturer	Model	Rating

C. Peripherals

Device	Manufacturer	Model	Rating

5.4 EUT Operating Condition

Operating condition is according to ANSI C63.10 -2013.

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition
- 5.5 Power line conducted Emission Limit according to Paragraph 15.207

Frequency	Limits (c	Limits (dB μ V)			
(MHz)	Quasi-peak Level	Average Level			
0.15 ~ 0.50	66.0~56.0*	56.0~46.0*			
$0.50 \sim 5.00$	56.0	46.0			
5.00 ~ 30.00	60.0	50.0			

Notes:

- 1. *Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

5.6 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.

Note: Only the worst case was recorded in the test report.

Date: 2022-05-10



A: Conducted Emission on Live Terminal (150kHz to 30MHz)


EUT Operating Environment

Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 kPa

EUT set Condition: Keeping WIFI Transmitting

Results: Pass

Please refer to following diagram for individual



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.4659	27.44	9.77	37.21	56.59	-19.38	QP	Р
2	0.4659	15.84	9.77	25.61	46.59	-20.98	AVG	Р
3	1.1991	30.76	9.79	40.55	56.00	-15.45	QP	Р
4	1.1991	16.97	9.79	26.76	46.00	-19.24	AVG	Р
5	4.5443	29.11	9.91	39.02	56.00	-16.98	QP	Р
6	4.5443	20.13	9.91	30.04	46.00	-15.96	AVG	Р
7	9.1932	37.81	10.12	47.93	60.00	-12.07	QP	Р
8	9.1932	29.95	10.12	40.07	50.00	-9.93	AVG	Р

Date: 2022-05-10



B: Conducted Emission on Neutral Terminal (150kHz to 30MHz)


EUT Operating Environment

Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 kPa

EUT set Condition: Keeping WIFI Transmitting

Results: Pass

Please refer to following diagram for individual



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.2670	26.64	9.75	36.39	61.21	-24.82	QP	Р
2	0.2670	16.21	9.75	25.96	51.21	-25.25	AVG	Р
3	2.7123	27.17	9.83	37.00	56.00	-19.00	QP	Р
4	2.7123	16.49	9.83	26.32	46.00	-19.68	AVG	Р
5	6.1395	31.11	9.98	41.09	60.00	-18.91	QP	Р
6	6.1395	22.17	9.98	32.15	50.00	-17.85	AVG	Р
7	10.4061	37.57	10.18	47.75	60.00	-12.25	QP	Р
8	10.4061	29.40	10.18	39.58	50.00	-10.42	AVG	Р

Date: 2022-05-10




6 Undesirable Emission and Restrict band

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.10-2013. The radiated test was performed at Timeway Laboratory. This site is on file with the FCC laboratory division, Registration No.744189
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.10-2013.
- (3) The frequency spectrum from 30 MHz to 40 GHz was investigated. All readings from 30 MHz to 1 GHz are Quasi-peak values with a resolution bandwidth of 120 kHz. For measurement above 1GHz, peak values with RBW=1MHz, VBW=3MHz and PK detector.

 Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "QP" in the data table.
- (6) The antenna polarization: Vertical polarization and Horizontal polarization.

Block diagram of Test setup


For radiated emissions from 9kHz to 30MHz




Date: 2022-05-10



For radiated emissions from 30MHz to1GHz



For radiated emissions above 1GHz



- 6.2 Configuration of The EUT
 Same as section 5.3 of this report
- 6.3 EUT Operating Condition
 Same as section 5.4 of this report.
- 6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

Page 15 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Frequencies in restricted band are complied to limit on Paragraph 15.209

Frequency Range (MHz)	Distance (m)	Field strength (dB μ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

- (1) For transmitters operating in the 5.15-5.25 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27dBm/MHz
- (2) For transmitters operating in the 5.725-5.825 GHz band: all emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an EIRP of -17dBm/MHz; for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an EIRP of -27dBm/MHz.

Note: 1. RF Voltage (dBuV) = 20 log RF Voltage (uV)

- 2. In the Above Table, the higher limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.

Note: Only the worst case was recorded in the test report. and 802.11a is the worst case.

Report No.: TW2203329-04E Page 16 of 166

Date: 2022-05-10



Test result

General Radiated Emission Data and Harmonics Radiated Emission Data

Radiated Emission In Horizontal (30MHz----1000MHz)

EUT set Condition: Keeping WIFI Transmitting

Results: Pass

Page 17 of 166


Report No.: TW2203329-04E

Date: 2022-05-10



Test Figure:

H



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(0)	(cm)		
1	67.821	25.91	-14.55	40.0	-14.09	Peak	186.00	100	Horizontal	Pass
2	149.038	30.19	-17.11	43.5	-13.31	Peak	123.00	100	Horizontal	Pass
3	215.951	34.00	-13.60	43.5	-9.50	Peak	130.00	100	Horizontal	Pass
4	407.963	37.56	-8.47	46.0	-8.44	Peak	133.00	100	Horizontal	Pass
5	455.966	33.68	-7.95	46.0	-12.32	Peak	219.00	100	Horizontal	Pass
6	971.877	39.73	-1.62	54.0	-14.27	Peak	46.00	100	Horizontal	Pass

Page 18 of 166


Report No.: TW2203329-04E

Date: 2022-05-10



Test Figure:

V




No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(o)	(cm)		
1	34.364	36.96	-14.17	40.0	-3.04	Peak	268.00	100	Vertical	Pass
2	54.729	34.86	-11.72	40.0	-5.14	Peak	313.00	100	Vertical	Pass
3	94.731	37.63	-14.32	43.5	-5.87	Peak	320.00	100	Vertical	Pass
4	215.951	27.21	-13.60	43.5	-16.29	Peak	342.00	100	Vertical	Pass
5	407.963	34.83	-8.47	46.0	-11.17	Peak	150.00	100	Vertical	Pass
6	486.513	33.53	-7.25	46.0	-12.47	Peak	324.00	100	Vertical	Pass

Date: 2022-05-10




Please refer to the following test plots for details:

CH36 for 11a at 6Mbps: Horizontal



CH36 for 11a at 6Mbps: Vertical




Page 20 of 166

Report No.: TW2203329-04E


Date: 2022-05-10



CH40 for 11a at 6Mbps: Horizontal




CH40 for 11a at 6Mbps: Vertical




Date: 2022-05-10



CH48 for 11a at 6Mbps: Horizontal



CH48 for 11g at 6Mbps: Vertical



Note: 1. For radiated Emissions from 18-40GHz and below 30MHz, it is only the floor noise and less than the limit for more than 20dB. No necessary to take down.

2. 802.11a is the worst case.

Date: 2022-05-10



Restricted band Measurement							
EUT	Та	iblet PC	Test Mode:	Channel 36 (5180MHz)-11a			
Mode	Keeping	g Transmitting	Input Voltage	DC3.7V			
Temperature	24	deg. C,	Humidity	56% RH			
Test Result:		Pass	Detector	PK			
5150	PK (dBµV/m)	45.5 (PK)	T ::4	27 JD /MIL_			
	EIRP (dBm)	-49.7	Limit	-27dBm/MHz			
Polarity	Но	orizontal		-			

Remark: 1. According to KDB 789033 D02 General UNII Test Procedures New Rules v01 section G) d) (ii), for measurement above 1000MHz@3m distance, the limit of EIRP is calculated as follows:

 $EIRP[dBm] = E[dB\mu V/m] - 95.2$

For Example, if $E[dB\mu V/m] = 45.5 dB\mu V/m$,

 $EIRP[dBm] = E[dB\mu V/m] - 95.2=45.5-95.2=-49.7dBm$

2. RBW=1MHz, VBW=3MHz

Restricted band Measurement						
EUT	Та	ıblet PC	Test Mode:	Channel 36 (5180MHz)-11a		
Mode	Keeping	Transmitting	Input Voltage	DC3.7V		
Temperature	24	deg. C,	Humidity	56% RH		
Test Result:		Pass	Detector	PK		
5150	PK (dBμV/m)	42.3 (PK)	T in it	27 ID /MII		
	EIRP (dBm) -52.9		Limit	-27dBm/MHz		
Polarity	Vertical			-		

Remark: 1. According to KDB 789033 D02 General UNII Test Procedures New Rules v01 section G) d) (ii), for measurement above 1000MHz@3m distance, the limit of EIRP is calculated as follows:

 $EIRP[dBm] = E[dB\mu V/m] - 95.2$

For Example, if $E[dB\mu V/m] = 42.3 dB\mu V/m$,

 $EIRP[dBm] = E[dB\mu V/m] - 95.2=42.3-95.2=-52.9dBm$

Date: 2022-05-10



Restricted band Measurement							
EUT	Та	iblet PC	Test Mode:	Channel 48 (5240MHz)-11a			
Mode	Keeping	Transmitting	Input Voltage	DC3.7V			
Temperature	24	deg. C,	Humidity	56% RH			
Test Result:		Pass	Detector	PK			
5250	PK (dBµV/m)	49.8 (PK)	T ::4	27 10 / MII			
	EIRP (dBm) -45.4		Limit	-27dBm/MHz			
Polarity	Но	orizontal					

Remark: 1. According to KDB 789033 D02 General UNII Test Procedures New Rules v01 section G) d) (ii), for measurement above 1000MHz@3m distance, the limit of EIRP is calculated as follows:

 $EIRP[dBm] = E[dB\mu V/m] - 95.2$

For Example, if $E[dB\mu V/m] = 49.8 dB\mu V/m$,

 $EIRP[dBm] = E[dB\mu V/m] - 95.2=49.8-95.2=-45.4dBm$

2. RBW=1MHz, VBW=3MHz

Restricted band Measurement							
EUT	Та	iblet PC	Test Mode:	Channel 48 (5240MHz)-11a			
Mode	Keeping	g Transmitting	Input Voltage	DC3.7V			
Temperature	24	deg. C,	Humidity	56% RH			
Test Result:		Pass	Detector	PK			
5250	PK (dBµV/m)	46.7 (PK)	T in it	27 ID /MII			
	EIRP (dBm) -48.5		Limit	-27dBm/MHz			
Polarity	Vertical						

Remark: 1. According to KDB 789033 D02 General UNII Test Procedures New Rules v01 section G) d) (ii), for measurement above 1000MHz@3m distance, the limit of EIRP is calculated as follows:

 $EIRP[dBm] = E[dB\mu V/m] - 95.2$

For Example, if $E[dB\mu V/m] = 46.7dB\mu V/m$,

 $EIRP[dBm] = E[dB\mu V/m] - 95.2=46.7-95.2=-48.5dBm$

Date: 2022-05-10



Restricted band Measurement							
EUT	Ta	ablet PC	Test Mode:	Channel 149 (5745MHz)-11a			
Mode	Keeping	g Transmitting	Input Voltage	DC3.7V			
Temperature	24	l deg. C,	Humidity	56% RH			
Test Result:		Pass	Detector	PK			
5725	PK (dBµV/m)	53.4 (PK)	T in it	17.1D /A (II			
	EIRP (dBm) -41.8		Limit	-17dBm/MHz			
Polarity	Horizontal						

Remark: 1. According to KDB 789033 D02 General UNII Test Procedures New Rules v01 section G) d) (ii), for measurement above 1000MHz@3m distance, the limit of EIRP is calculated as follows:

 $EIRP[dBm] = E[dB\mu V/m] - 95.2$

For Example, if $E[dB\mu V/m] = 53.4 dB\mu V/m$,

 $EIRP[dBm] = E[dB\mu V/m] - 95.2=53.4-95.2=-41.8dBm$

2. RBW=1MHz, VBW=3MHz

Restricted band Measurement							
EUT	Та	ıblet PC	Test Mode:	Channel 149 (5745MHz)-11a			
Mode	Keeping	Transmitting	Input Voltage	DC3.7V			
Temperature	24	deg. C,	Humidity	56% RH			
Test Result:		Pass	Detector	PK			
5725	PK (dBµV/m)	47.2(PK)	T :	17.10/МП			
	EIRP (dBm) -48.0		Limit	-17dBm/MHz			
Polarity	Vertical						

Remark: 1. According to KDB 789033 D02 General UNII Test Procedures New Rules v01 section G) d) (ii), for measurement above 1000MHz@3m distance, the limit of EIRP is calculated as follows:

 $EIRP[dBm] = E[dB\mu V/m] - 95.2$

For Example, if $E[dB\mu V/m] = 47.2 dB\mu V/m$,

 $EIRP[dBm] = E[dB\mu V/m] - 95.2 = 47.2 - 95.2 = -48.0 dBm$

Date: 2022-05-10



Restricted band Measurement					
EUT	Та	ablet PC	Test Mode:	Channel 161 (5825MHz)-11a	
Mode	Keeping Transmitting		Input Voltage	DC3.7V	
Temperature	24 deg. C,		Humidity	56% RH	
Test Result:		Pass	Detector	PK	
5850	PK (dBµV/m)	55.2 (PK)	T ::4	17.10 /4.411	
	EIRP (dBm)	-40.0	Limit	-17dBm/MHz	
Polarity	Но	orizontal			

Remark: 1. According to KDB 789033 D02 General UNII Test Procedures New Rules v01 section G) d) (ii), for measurement above 1000MHz@3m distance, the limit of EIRP is calculated as follows:

 $EIRP[dBm] = E[dB\mu V/m] - 95.2$

For Example, if $E[dB\mu V/m] = 55.2 dB\mu V/m$,

 $EIRP[dBm] = E[dB\mu V/m] - 95.2=55.2-95.2=-40.0dBm$

2. RBW=1MHz, VBW=3MHz

Restricted band Measurement					
EUT	Tablet PC		Test Mode:	Channel 161 (5825MHz)-11a	
Mode	Keeping Transmitting		Input Voltage	DC3.7V	
Temperature	24 deg. C,		Humidity	56% RH	
Test Result:		Pass	Detector	PK	
5850	PK (dBµV/m)	PK (dBμV/m) 50.4 (PK)		17.10 /4.01	
	EIRP (dBm) -44.8		Limit	-17dBm/MHz	
Polarity	Vertical				

Remark: 1. According to KDB 789033 D02 General UNII Test Procedures New Rules v01 section G) d) (ii), for measurement above 1000MHz@3m distance, the limit of EIRP is calculated as follows:

 $EIRP[dBm] = E[dB\mu V/m] - 95.2$

For Example, if $E[dB\mu V/m]=50.4 dB\mu V/m$,

 $EIRP[dBm] = E[dB\mu V/m] - 95.2 = 50.4 - 95.2 = -44.8 dBm$

Date: 2022-05-10



Restricted band Measurement					
EUT	Tablet PC		Test Mode:	Channel 36	
				(5180MHz)-11n/HT20	
Mode	Keeping Transmitting		Input Voltage	DC3.7V	
Temperature	24 deg. C,		Humidity	56% RH	
Test Result:		Pass	Detector	PK	
5150	PK (dBµV/m)	46.6(PK)	T toota	27 10/MII	
	EIRP (dBm) -48.3		Limit	-27dBm/MHz	
Polarity	Horizontal				

Remark: 1. According to KDB 789033 D02 General UNII Test Procedures New Rules v01 section G) d) (ii), for measurement above 1000MHz@3m distance, the limit of EIRP is calculated as follows:

 $EIRP[dBm] = E[dB\mu V/m] - 95.2$

For Example, if $E[dB\mu V/m] = 46.6 dB\mu V/m$,

 $EIRP[dBm] = E[dB\mu V/m] - 95.2=46.6-95.2=-48.6dBm$

2. RBW=1MHz, VBW=3MHz

Restricted band Measurement					
EUT	Та	ablet PC	Test Mode:	Channel 36	
				(5180MHz)-11n/HT20	
Mode	Keeping Transmitting		Input Voltage	DC3.7V	
Temperature	24 deg. C,		Humidity	56% RH	
Test Result:		Pass	Detector	PK	
5150	PK (dBµV/m)	43.9 (PK)	T :	27.10/2411	
	EIRP (dBm) -51.3		Limit	-27dBm/MHz	
Polarity		Vertical			

Remark: 1. According to KDB 789033 D02 General UNII Test Procedures New Rules v01 section G) d) (ii), for measurement above 1000MHz@3m distance, the limit of EIRP is calculated as follows:

 $EIRP[dBm] = E[dB\mu V/m] - 95.2$

For Example, if $E[dB\mu V/m] = 43.9dB\mu V/m$,

 $EIRP[dBm] = E[dB\mu V/m] - 95.2 = 43.9 - 95.2 = -51.3 dBm$

Date: 2022-05-10



Restricted band Measurement					
EUT	Tablet PC		Test Mode:	Channel 48 (5240MHz)-	
				11n/HT20	
Mode	Keeping Transmitting		Input Voltage	DC3.7V	
Temperature	24 deg. C,		Humidity	56% RH	
Test Result:		Pass	Detector	PK	
5250	PK (dBµV/m)	47.7 (PK)	T in it	27 10/MII	
	EIRP (dBm) -47.5		Limit	-27dBm/MHz	
Polarity	Horizontal				

Remark: 1. According to KDB 789033 D02 General UNII Test Procedures New Rules v01 section G) d) (ii), for measurement above 1000MHz@3m distance, the limit of EIRP is calculated as follows:

 $EIRP[dBm] = E[dB\mu V/m] - 95.2$

For Example, if $E[dB\mu V/m] = 47.7 dB\mu V/m$,

 $EIRP[dBm] = E[dB\mu V/m] - 95.2=47.7-95.2=-47.5dBm$

2. RBW=1MHz, VBW=3MHz

Restricted band Measurement					
EUT	Tablet PC		Test Mode:	Channel 48 (5240MHz)-	
				11n/HT20	
Mode	Keeping Transmitting		Input Voltage	DC3.7V	
Temperature	24 deg. C,		Humidity	56% RH	
Test Result:		Pass	Detector	PK	
5250	PK (dBµV/m)	44.1(PK)	T :	27 10/MII	
	EIRP (dBm) -51.1		Limit	-27dBm/MHz	
Polarity	7	Vertical			

Remark: 1. According to KDB 789033 D02 General UNII Test Procedures New Rules v01 section G) d) (ii), for measurement above 1000MHz@3m distance, the limit of EIRP is calculated as follows:

 $EIRP[dBm] = E[dB\mu V/m] - 95.2$

For Example, if $E[dB\mu V/m] = 44.1dB\mu V/m$,

 $EIRP[dBm] = E[dB\mu V/m] - 95.2 = 44.1 - 95.2 = -51.1dBm$

Date: 2022-05-10



Restricted band Measurement					
EUT	Та	ablet PC	Test Mode:	Channel 149 (5745MHz)-	
				11n/HT20	
Mode	Keeping Transmitting		Input Voltage	DC3.7V	
Temperature	24 deg. C,		Humidity	56% RH	
Test Result:		Pass	Detector	PK	
5725	PK (dBµV/m)	50.3 (PK)	T :	17.10/МП	
	EIRP (dBm) -44.9		Limit	-17dBm/MHz	
Polarity	Horizontal				

Remark: 1. According to KDB 789033 D02 General UNII Test Procedures New Rules v01 section G) d) (ii), for measurement above 1000MHz@3m distance, the limit of EIRP is calculated as follows:

 $EIRP[dBm] = E[dB\mu V/m] - 95.2$

For Example, if $E[dB\mu V/m] = 50.3 dB\mu V/m$,

 $EIRP[dBm] = E[dB\mu V/m] - 95.2=50.3-95.2=-44.9dBm$

2. RBW=1MHz, VBW=3MHz

Restricted band Measurement					
EUT	Ta	Tablet PC		Channel 149 (5745MHz)-	
				11n/HT20	
Mode	Keeping Transmitting		Input Voltage	DC3.7V	
Temperature	24 deg. C,		Humidity	56% RH	
Test Result:		Pass	Detector	PK	
5725	PK (dBµV/m)	46.4 (PK)	T in it	17.10/МП	
	EIRP (dBm) -48.8		Limit	-17dBm/MHz	
Polarity	7	Vertical			

Remark: 1. According to KDB 789033 D02 General UNII Test Procedures New Rules v01 section G) d) (ii), for measurement above 1000MHz@3m distance, the limit of EIRP is calculated as follows:

 $EIRP[dBm] = E[dB\mu V/m] - 95.2$

For Example, if $E[dB\mu V/m] = 46.4dB\mu V/m$,

 $EIRP[dBm] = E[dB\mu V/m] - 95.2 = 46.4 - 95.2 = -48.8 dBm$

Date: 2022-05-10



Restricted band Measurement					
EUT	Tablet PC		Test Mode:	Channel 161 (5825MHz)-	
				11n/HT20	
Mode	Keeping Transmitting		Input Voltage	DC3.7V	
Temperature	24 deg. C,		Humidity	56% RH	
Test Result:		Pass	Detector	PK	
5850	PK (dBµV/m)	50.5 (PK)	T :	17 ID. /MI	
	EIRP (dBm) -44.7		Limit	-17dBm/MHz	
Polarity	Но	Horizontal			

Remark: 1. According to KDB 789033 D02 General UNII Test Procedures New Rules v01 section G) d) (ii), for measurement above 1000MHz@3m distance, the limit of EIRP is calculated as follows:

 $EIRP[dBm] = E[dB\mu V/m] - 95.2$

For Example, if $E[dB\mu V/m] = 50.5dB\mu V/m$,

 $EIRP[dBm] = E[dB\mu V/m] - 95.2=50.5-95.2=-44.7dBm$

2. RBW=1MHz, VBW=3MHz

Restricted band Measurement					
EUT	Tablet PC		Test Mode:	Channel 161 (5825MHz)-	
				11n/HT20	
Mode	Keeping Transmitting		Input Voltage	DC3.7V	
Temperature	24 deg. C,		Humidity	56% RH	
Test Result:		Pass	Detector	PK	
5850	PK (dBµV/m)	46.4 (PK)	T ::4	1710 - A411	
	EIRP (dBm)	-48.8	Limit	-17dBm/MHz	
Polarity	1	Vertical			

Remark: 1. According to KDB 789033 D02 General UNII Test Procedures New Rules v01 section G) d) (ii), for measurement above 1000MHz@3m distance, the limit of EIRP is calculated as follows:

 $EIRP[dBm] = E[dB\mu V/m] - 95.2$

For Example, if $E[dB\mu V/m] = 46.4dB\mu V/m$,

 $EIRP[dBm] = E[dB\mu V/m] - 95.2 = 46.4 - 95.2 = -48.8 dBm$

Date: 2022-05-10



Restricted band Measurement					
EUT	Та	ablet PC	Test Mode:	Channel 38	
				(5190MHz)-11n/HT40	
Mode	Keeping Transmitting		Input Voltage	DC3.7V	
Temperature	24 deg. C,		Humidity	56% RH	
Test Result:		Pass	Detector	PK	
5150	PK (dBµV/m)	44.8 (PK)	T in it	27 ID/MII	
	EIRP (dBm) -50.7		Limit	-27dBm/MHz	
Polarity	Но	Horizontal			

Remark: 1. According to KDB 789033 D02 General UNII Test Procedures New Rules v01 section G) d) (ii), for measurement above 1000MHz@3m distance, the limit of EIRP is calculated as follows:

 $EIRP[dBm] = E[dB\mu V/m] - 95.2$

For Example, if $E[dB\mu V/m] = 44.8 dB\mu V/m$,

 $EIRP[dBm] = E[dB\mu V/m] - 95.2=44.8-95.2=-50.4 dBm$

2. RBW=1MHz, VBW=3MHz

Restricted band Measurement					
EUT	Та	ablet PC	Test Mode:	Channel 38	
				(5190MHz)-11n/HT40	
Mode	Keeping Transmitting		Input Voltage	DC3.7V	
Temperature	24 deg. C,		Humidity	56% RH	
Test Result:		Pass	Detector	PK	
5150	PK (dBµV/m)	42.2 (PK)	T :	27 10/MII	
	EIRP (dBm) -53.0		Limit	-27dBm/MHz	
Polarity	Vertical				

Remark: 1. According to KDB 789033 D02 General UNII Test Procedures New Rules v01 section G) d) (ii), for measurement above 1000MHz@3m distance, the limit of EIRP is calculated as follows:

 $EIRP[dBm] = E[dB\mu V/m] - 95.2$

For Example, if $E[dB\mu V/m] = 42.2dB\mu V/m$,

 $EIRP[dBm] = E[dB\mu V/m] - 95.2 = 42.2 - 95.2 = -53.0 dBm$

Date: 2022-05-10



Restricted band Measurement							
EUT	Tablet PC		Test Mode:	Channel 46 (5230MHz)-			
				11n/HT40			
Mode	Keeping Transmitting		Input Voltage	DC3.7V			
Temperature	24 deg. C,		Humidity	56% RH			
Test Result:		Pass	Detector	PK			
5250	PK (dBµV/m)	48.6(PK)	T :	27 ID /MII			
	EIRP (dBm)	-46.6	Limit	-27dBm/MHz			
Polarity	Horizontal						

Remark: 1. According to KDB 789033 D02 General UNII Test Procedures New Rules v01 section G) d) (ii), for measurement above 1000MHz@3m distance, the limit of EIRP is calculated as follows:

 $EIRP[dBm] = E[dB\mu V/m] - 95.2$

For Example, if $E[dB\mu V/m] = 48.6 dB\mu V/m$,

 $EIRP[dBm] = E[dB\mu V/m] - 95.2=48.6-95.2=-46.6 dBm$

2. RBW=1MHz, VBW=3MHz

Restricted band Measurement							
EUT	Tablet PC		Test Mode:	Channel 46 (5230MHz)-			
				11n/HT40			
Mode	Keeping Transmitting		Input Voltage	DC3.7V			
Temperature	24 deg. C,		Humidity	56% RH			
Test Result:		Pass	Detector	PK			
5250	PK (dBµV/m)	45.3(PK)	T :	27 10/MII			
	EIRP (dBm)	-49.9	Limit	-27dBm/MHz			
Polarity	Vertical						

Remark: 1. According to KDB 789033 D02 General UNII Test Procedures New Rules v01 section G) d) (ii), for measurement above 1000MHz@3m distance, the limit of EIRP is calculated as follows:

 $EIRP[dBm] = E[dB\mu V/m] - 95.2$

For Example, if $E[dB\mu V/m] = 45.3dB\mu V/m$,

 $EIRP[dBm] = E[dB\mu V/m] - 95.2 = 45.3 - 95.2 = -49.9 dBm$

Date: 2022-05-10



Restricted band Measurement							
EUT	Tablet PC		Test Mode:	Channel 151 (5755MHz)-			
				11n/HT40			
Mode	Keeping Transmitting		Input Voltage	DC3.7V			
Temperature	24 deg. C,		Humidity	56% RH			
Test Result:		Pass	Detector	PK			
5725	PK (dBµV/m)	51.4(PK)	T 112	1710 (MII)			
	EIRP (dBm) -43.8		Limit	-17dBm/MHz			
Polarity	Horizontal						

Remark: 1. According to KDB 789033 D02 General UNII Test Procedures New Rules v01 section G) d) (ii), for measurement above 1000MHz@3m distance, the limit of EIRP is calculated as follows:

 $EIRP[dBm] = E[dB\mu V/m] - 95.2$

For Example, if $E[dB\mu V/m] = 51.4 \ dB\mu V/m$,

 $EIRP[dBm] = E[dB\mu V/m] - 95.2=51.4 - 95.2= -43.8dBm$

2. RBW=1MHz, VBW=3MHz

Restricted band Measurement						
EUT	Tablet PC		Test Mode:	Channel 151 (5755MHz)-		
				11n/HT40		
Mode	Keeping Transmitting		Input Voltage	DC3.7V		
Temperature	24 deg. C,		Humidity	56% RH		
Test Result:	Pass		Detector	PK		
5725	PK (dBµV/m)	46.7(PK)	T in it	17.10/МП		
	EIRP (dBm)	-48.5	Limit	-17dBm/MHz		
Polarity	Vertical					

Remark: 1. According to KDB 789033 D02 General UNII Test Procedures New Rules v01 section G) d) (ii), for measurement above 1000MHz@3m distance, the limit of EIRP is calculated as follows:

 $EIRP[dBm] = E[dB\mu V/m] - 95.2$

For Example, if $E[dB\mu V/m] = 46.7dB\mu V/m$,

 $EIRP[dBm] = E[dB\mu V/m] - 95.2 = 46.7 - 95.2 = -48.5 dBm$

Date: 2022-05-10



Restricted band Measurement						
EUT	Tablet PC		Test Mode:	Channel 159 (5795MHz)-		
				11n/HT40		
Mode	Keeping Transmitting		Input Voltage	DC3.7V		
Temperature	24 deg. C,		Humidity	56% RH		
Test Result:		Pass	Detector	PK		
5850	PK (dBµV/m)	53.4 (PK)	T :	17 ID/MII		
	EIRP (dBm)	-41.8	Limit	-17dBm/MHz		
Polarity	Horizontal					

Remark: 1. According to KDB 789033 D02 General UNII Test Procedures New Rules v01 section G) d) (ii), for measurement above 1000MHz@3m distance, the limit of EIRP is calculated as follows:

 $EIRP[dBm] = E[dB\mu V/m] - 95.2$

For Example, if $E[dB\mu V/m] = 53.4 dB\mu V/m$,

 $EIRP[dBm] = E[dB\mu V/m] - 95.2=53.4-95.2=-41.8dBm$

2. RBW=1MHz, VBW=3MHz

Restricted band Measurement						
EUT	Tablet PC		Test Mode:	Channel 159 (5795MHz)-		
				11n/HT40		
Mode	Keeping Transmitting		Input Voltage	DC3.7V		
Temperature	24 deg. C,		Humidity	56% RH		
Test Result:		Pass	Detector	PK		
5850	PK (dBµV/m)	47.3(PK)	T :	17.10/МП		
	EIRP (dBm)	-47.9	Limit	-17dBm/MHz		
Polarity	Vertical					

Remark: 1. According to KDB 789033 D02 General UNII Test Procedures New Rules v01 section G) d) (ii), for measurement above 1000MHz@3m distance, the limit of EIRP is calculated as follows:

 $EIRP[dBm] = E[dB\mu V/m] - 95.2$

For Example, if $E[dB\mu V/m] = 47.3 dB\mu V/m$,

 $EIRP[dBm] = E[dB\mu V/m] - 95.2 = 47.3 - 95.2 = -47.9 dBm$

Date: 2022-05-10



Restricted band Measurement							
EUT	Tablet PC		Test Mode:	Channel 42			
				(5210MHz)-11ac/VHT80			
Mode	Keeping	g Transmitting	Input Voltage	DC3.7V			
Temperature	24 deg. C,		Humidity	56% RH			
Test Result:		Pass	Detector	PK			
5150	PK (dBµV/m)	47.7 (PK)	T in it	27 ID /MII			
	EIRP (dBm)	-47.5	Limit	-27dBm/MHz			
Polarity	Horizontal			-			

Remark: 1. According to KDB 789033 D02 General UNII Test Procedures New Rules v01 section G) d) (ii), for measurement above 1000MHz@3m distance, the limit of EIRP is calculated as follows:

 $EIRP[dBm] = E[dB\mu V/m] - 95.2$

For Example, if $E[dB\mu V/m] = 47.7 dB\mu V/m$,

 $EIRP[dBm] = E[dB\mu V/m] - 95.2=47.7-95.2=-47.5dBm$

2. RBW=1MHz, VBW=3MHz

Restricted band Measurement						
EUT	Tablet PC		Test Mode:	Channel 42 (5210MHz)-		
				11ac/VHT80		
Mode	Keeping Transmitting		Input Voltage	DC3.7V		
Temperature	24 deg. C,		Humidity	56% RH		
Test Result:		Pass	Detector	PK		
5150	PK (dBµV/m)	45.7 (PK)	T ''4	27 10/MII		
	EIRP (dBm)	-49.5	Limit	-27dBm/MHz		
Polarity	Vertical			1		

Remark: 1. According to KDB 789033 D02 General UNII Test Procedures New Rules v01 section G) d) (ii), for measurement above 1000MHz@3m distance, the limit of EIRP is calculated as follows:

 $EIRP[dBm] = E[dB\mu V/m] - 95.2$

For Example, if $E[dB\mu V/m] = 45.7 dB\mu V/m$,

 $EIRP[dBm] = E[dB\mu V/m] - 95.2 = 45.7 - 95.2 = -49.5 dBm$

Date: 2022-05-10



Restricted band Measurement						
EUT	Tablet PC		Test Mode:	Channel 155 (5775MHz)-		
				11ac/VHT80		
Mode	Keeping Transmitting		Input Voltage	DC3.7V		
Temperature	24 deg. C,		Humidity	56% RH		
Test Result:		Pass	Detector	PK		
5850	PK (dBµV/m)	52.1 (PK)	T ''/	17.10/МП		
	EIRP (dBm) -43.1		Limit	-17dBm/MHz		
Polarity	Horizontal					

Remark: 1. According to KDB 789033 D02 General UNII Test Procedures New Rules v01 section G) d) (ii), for measurement above 1000MHz@3m distance, the limit of EIRP is calculated as follows:

 $EIRP[dBm] = E[dB\mu V/m] - 95.2$

For Example, if $E[dB\mu V/m] = 52.1 \ dB\mu V/m$,

 $EIRP[dBm] = E[dB\mu V/m] - 95.2=52.1-95.2=-43.1 dBm$

2. RBW=1MHz, VBW=3MHz

Restricted band Measurement							
EUT	Tablet PC		Test Mode:	Channel 157 (5775MHz)-			
				11ac/VHT80			
Mode	Keeping Transmitting		Input Voltage	DC3.7V			
Temperature	24 deg. C,		Humidity	56% RH			
Test Result:		Pass	Detector	PK			
5850	PK (dBµV/m)	47.6 (PK)	T 11	17 ID /MII			
	EIRP (dBm)	-47.6	Limit	-17dBm/MHz			
Polarity	Vertical						

Remark: 1. According to KDB 789033 D02 General UNII Test Procedures New Rules v01 section G) d) (ii), for measurement above 1000MHz@3m distance, the limit of EIRP is calculated as follows:

 $EIRP[dBm] = E[dB\mu V/m] - 95.2$

For Example, if $E[dB\mu V/m] = 47.6dB\mu V/m$,


 $EIRP[dBm] = E[dB\mu V/m] - 95.2 = 47.6 - 95.2 = -47.6 dBm$

Date: 2022-05-10



7.0 Emission Bandwidth

7.1 Test Setup



7.3 Test Procedure for Emission Bandwidth

- 1. Set RBW = approximately 1% of the emission bandwidth.
- 2. Set VBW> RBW
- 3 Detector = Peak
- 4. Trace mode = max hold.
- 5. Sweep = auto couple.
- 6. Allow the trace to stabilize.
- 7. Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

7.4 Test Procedure for Minimum Bandwidth for the Band 5725-5850MHz

- 1. Set RBW = 100 kHz.
- 2. Set $VBW \ge 3 \times RBW$.
- 3. Detector = Peak.
- 4. Trace mode = max hold.
- 5. Sweep = auto couple.
- 6. Allow the trace to stabilize.
- 7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.5 Test Procedure for 99% Bandwidth

- 1. Set center frequency to the nominal EUT channel center frequency
- 2. Set span = 1.5 times to 5.0 times OBW
- 3. Set RBW= 1% TO 5% of the OBW
- 4. Set $VBW \ge 3 \times RBW$
- 5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Other, peak detection and max mode (until trace stabilizes) shall be used.
- 6. Use the 99% power bandwidth function of the instrument

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 37 of 166 Report No.: TW2203329-04E

Date: 2022-05-10



7.6 Test Result

EUT		Tablet PC			Model	K13			
Mode		802.11a			Input Voltage	DC3.7V			
Temperature			24 deg. C,			56% RH			
Channel	Channel Frequency (MHz)		Data Transfer Rate (Mbps)	Bandwidth (MHz)	Minimum Limi (MHz)	t Pass/ Fail			
26dB Bar	26dB Bandwidth								
36	5180		6	22.61		Pass			
40	5200		6	22.61		Pass			
48	5240		6	22.61		Pass			
99% Bandwidth									
36	5180		6	16.89		Pass			
40	5200		6	16.89		Pass			
48	5240		6	16.89		Pass			

Report No.: TW2203329-04E


Date: 2022-05-10



Test Figure:

26dB Bandwidth

Channel 36



7.MAY.2022 17:57:13 Date:


Page 39 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 40



7.MAY.2022 18:07:39 Date:


Page 40 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 48



Date: 7.MAY.2022 18:16:44

Page 41 of 166

Report No.: TW2203329-04E


Date: 2022-05-10



Test Figure:

99% Bandwidth

Channel 36



7.MAY.2022 17:57:58 Date:


Page 42 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 40



7.MAY.2022 18:07:25 Date:


Page 43 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 48



7.MAY.2022 18:17:02 Date:

Page 44 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



EUT		Tablet PC		Model	K13	
Mode			802.11a	ı	Input Voltage	DC3.7V
Temperature		24 deg. C,		Humidity	56% RH	
Channel	Channel Frequency (MHz)		Data Transfer Rate (Mbps)	Bandwidth (MHz)	Minimum Limi (MHz)	it Pass/ Fail
26dB Bar	ndwidth					
149	149 5745		6	22.55		Pass
153	5765		6	22.48		Pass
161	5825		6	22.48		Pass
6dB Band	dwidth					
149	5745		6	16.29	0.5	Pass
153	5765		6	16.37	0.5	Pass
161	5825		6	16.29	0.5	Pass
99% Ban	dwidth					
149	5745		6	16.89		Pass
153	5765		6	16.89		Pass
161	5825		6	16.89		Pass

Page 45 of 166

Report No.: TW2203329-04E


Date: 2022-05-10



Test Figure:

26dB Bandwidth

Channel 149



9.MAY.2022 15:50:42 Date:


Page 46 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 153



Date: 9.MAY.2022 15:54:15


Page 47 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 161



Date: 9.MAY.2022 15:59:11

Page 48 of 166

Report No.: TW2203329-04E


Date: 2022-05-10



Test Figure:

6dB Bandwidth

Channel 149



9.MAY.2022 14:05:42 Date:


Page 49 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 153



Date: 9.MAY.2022 14:14:06


Page 50 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 161



Date: 9.MAY.2022 14:18:23

Page 51 of 166

Report No.: TW2203329-04E


Date: 2022-05-10



Test Figure:

99% Bandwidth

Channel 149



9.MAY.2022 15:51:06 Date:


Page 52 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 153



Date: 9.MAY.2022 15:53:55


Page 53 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 161



Date: 9.MAY.2022 15:59:28 Report No.: TW2203329-04E Page 54 of 166

Date: 2022-05-10



EUT			Tablet PC		Model	K13
Mode			802.11n H	TT20	Input Voltage	DC3.7V
Temperature			24 deg. C,			56% RH
Channel	Channel Frequency (MHz)		Data Transfer Rate (Mbps)	Bandwidth (MHz)	Minimum Limit (MHz)	Pass/ Fail
26dB Bar	ndwidth					
36	5180		mcs0	23.27		Pass
40	5200		mcs0	23.21		Pass
48	5240		mcs0	23.21		Pass
99% Ban	dwidth					
36	5180		mcs0	18.04		Pass
40		5200	mcs0	18.04		Pass
48		5240	mcs0	18.04		Pass

Report No.: TW2203329-04E


Date: 2022-05-10



Test Configure

26dB Bandwidth

Channel 36



7.MAY.2022 18:48:01 Date:


Page 56 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 40



7.MAY.2022 18:40:35 Date:


Page 57 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 48



Date: 7.MAY.2022 18:27:33 Report No.: TW2203329-04E


Date: 2022-05-10



Test Configure

99% Bandwidth

Channel 36



7.MAY.2022 18:47:46 Date:


Page 59 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 40



7.MAY.2022 18:40:46 Date:


Page 60 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 48



7.MAY.2022 18:27:08 Date:

Page 61 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



EUT			Tablet F	PC C	Model	K13
Mode		802.11n HT20			Input Voltage	DC3.7V
Temperature		24 deg. C,		Humidity	56% RH	
Channel	Channel Frequency (MHz)		Data Transfer Rate (Mbps)	Bandwidth (MHz)	Minimum Limit (MHz)	Pass/ Fail
26dB Bar	ndwidth					
149		5745	6	23.27		Pass
153	5765		6	23.15		Pass
161	5825		6	23.15		Pass
6dB Band	dwidth					
149	5745		6	17.58	0.5	Pass
153	5765		6	17.62	0.5	Pass
161	5825		6	17.49	0.5	Pass
99% Ban	dwidth					
149	5745		6	18.04		Pass
153	5765		6	18.04		Pass
161	5825		6	18.04		Pass

Report No.: TW2203329-04E


Date: 2022-05-10



Test Configure

26dB Bandwidth

Channel 149



9.MAY.2022 16:12:46 Date:


Page 63 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 153



Date: 9.MAY.2022 16:08:06


Page 64 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 161



Date: 9.MAY.2022 16:06:05

Page 65 of 166

Report No.: TW2203329-04E


Date: 2022-05-10



Test Configure

6dB Bandwidth

Channel 149



9.MAY.2022 14:37:12 Date:


Page 66 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 153



Date: 9.MAY.2022 14:28:28


Page 67 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 161



Date: 9.MAY.2022 14:23:39 Report No.: TW2203329-04E


Date: 2022-05-10



Test Configure

99% Bandwidth

Channel 149



9.MAY.2022 16:12:32 Date:


Page 69 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 153



Date: 9.MAY.2022 16:08:23


Page 70 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 161



Date: 9.MAY.2022 16:05:51 Report No.: TW2203329-04E Page 71 of 166

Date: 2022-05-10



EUT		Tablet PC			Model	K13
Mode		802.11n HT40			Input Voltage	DC3.7V
Temperature		24 deg. C,			Humidity	56% RH
Channel	Channel Frequency (MHz)		Data Transfer Rate (Mbps)	Bandwidth (MHz)	Minimum Limit (MHz)	Pass/ Fail
26dB Bar	ndwidth					
38	5190		mcs0	45.57		Pass
46	5230		mcs0	45.57		Pass
99% Ban	dwidth				_	
38	5190		mcs0	37.27		Pass
46		5230	mcs0	37.27		Pass

Page 72 of 166

Report No.: TW2203329-04E


Date: 2022-05-10



Test Configure

26dB Bandwidth

Channel 38



9.MAY.2022 10:46:18 Date:


Page 73 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 46



Date: 9.MAY.2022 10:48:05

Page 74 of 166

Report No.: TW2203329-04E


Date: 2022-05-10



Test Configure

99% Bandwidth

Channel 38



9.MAY.2022 10:46:00 Date:


Page 75 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 46



Date: 9.MAY.2022 10:48:20 Report No.: TW2203329-04E Page 76 of 166

Date: 2022-05-10



EUT		Tablet PC			Model	K13	
Mode		802.11n HT40			Input Voltage	DC3.7V	
Temperature			24 deg.	C,	Humidity	56% RH	
Channel	Channel Frequency (MHz)		Data Transfer Rate (Mbps)	Bandwidth (MHz)	Minimum Limit (MHz)	Pass/ Fail	
26dB Bar	ndwidth						
151	5755		mcs0	45.57		Pass	
159	5795		mcs0	45.57		Pass	
6dB Band	dwidth						
151	5755		mcs0	36.31	0.5	Pass	
159	5795		mcs0	35.90	0.5	Pass	
99% Bandwidth							
151		5755	mcs0	37.27		Pass	
159	5795		mcs0	37.27		Pass	

Page 77 of 166

Report No.: TW2203329-04E


Date: 2022-05-10



Test Configure

26dB Bandwidth

Channel 151



9.MAY.2022 15:43:37 Date:


Page 78 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 159



Date: 9.MAY.2022 15:38:32

Page 79 of 166

Report No.: TW2203329-04E


Date: 2022-05-10



Test Configure

6dB Bandwidth

Channel 151



9.MAY.2022 14:56:10 Date:


Page 80 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 159



Date: 9.MAY.2022 14:59:36

Page 81 of 166

Report No.: TW2203329-04E


Date: 2022-05-10



Test Configure

99% Bandwidth

Channel 151



9.MAY.2022 15:43:52 Date:


Page 82 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 159



Date: 9.MAY.2022 15:38:07 Report No.: TW2203329-04E Page 83 of 166

Date: 2022-05-10



EUT			Tablet PC		Model	K13		
Mode	Mode		802.11ac VHT20		Input Voltage	DC3.7V		
Temperature			24 deg.	С,	Humidity	56% RH		
Channel	Channel Frequency (MHz)		Data Transfer Rate (Mbps)	Bandwidth (MHz)	Minimum Limit (MHz)	Pass/ Fail		
26dB Bar	ndwidth							
36	5180		mcs0	23.87		Pass		
40	5200		mcs0	23.81		Pass		
48	5240		mcs0	23.87		Pass		
99% Bandwidth								
36	5180		mcs0	18.22		Pass		
40		5200	mcs0	18.22		Pass		
48		5240	mcs0	18.22		Pass		

Page 84 of 166

Report No.: TW2203329-04E


Date: 2022-05-10



Test Configure

26dB Bandwidth

Channel 36



9.MAY.2022 10:14:50 Date:


Page 85 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 40



9.MAY.2022 10:24:39 Date:


Page 86 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 48



Date: 9.MAY.2022 10:40:52

Page 87 of 166

Report No.: TW2203329-04E


Date: 2022-05-10



Test Configure

99% Bandwidth

Channel 36



9.MAY.2022 10:15:10 Date:


Page 88 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 40



9.MAY.2022 10:24:24 Date:


Page 89 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 48



Date: 9.MAY.2022 10:41:06 Report No.: TW2203329-04E Page 90 of 166

Date: 2022-05-10



EUT		Tablet PC			Model	K13
Mode		802.11ac VHT20			Input Voltage	DC3.7V
Temperature			24 deg.	C,	Humidity	56% RH
Channel	Channel Frequency (MHz)		Data Transfer Rate (Mbps)	Bandwidth (MHz)	Minimum Limit (MHz)	Pass/ Fail
26dB Bar	ndwidth					
149		5745	6	23.81		Pass
153	5765		6	23.81		Pass
161		5825	6	23.69		Pass
6dB Band	dwidth					
149	5745		6	17.52	0.5	Pass
153	5765		6	17.58	0.5	Pass
161	5825		6	17.56	0.5	Pass
99% Ban	dwidth					
149		5745	6	18.22		Pass
153		5765	6	18.22		Pass
161	5825		6	18.16		Pass

Page 91 of 166

Report No.: TW2203329-04E


Date: 2022-05-10



Test Configure

26dB Bandwidth

Channel 149



9.MAY.2022 16:14:49 Date:


Page 92 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 153



Date: 9.MAY.2022 16:17:40


Page 93 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 161



Date: 9.MAY.2022 16:19:59

Page 94 of 166

Report No.: TW2203329-04E


Date: 2022-05-10



Test Configure

6dB Bandwidth

Channel 149



9.MAY.2022 14:40:20 Date:


Page 95 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 153



Date: 9.MAY.2022 14:43:30


Page 96 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 161



Date: 9.MAY.2022 14:51:16

Page 97 of 166

Report No.: TW2203329-04E


Date: 2022-05-10



Test Configure

99% Bandwidth

Channel 149



9.MAY.2022 16:15:13 Date:


Page 98 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 153



Date: 9.MAY.2022 16:17:22


Page 99 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 161



Date: 9.MAY.2022 16:20:12

Page 100 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



EUT		Tablet PC			Model	K13
Mode		802.11ac VHT40			Input Voltage	DC3.7V
Temperature		24 deg. C,			Humidity	56% RH
Channel	Channel Frequency (MHz)		Data Transfer Rate (Mbps)	Bandwidth (MHz)	Minimum Limit (MHz)	Pass/ Fail
26dB Bar	ndwidth					
38	5190		mcs0	45.57		Pass
46	5230		mcs0	45.57		Pass
99% Ban	dwidth					
38		5190	mcs0	37.27		Pass
46		5230	mcs0	37.15		Pass

Page 101 of 166

Report No.: TW2203329-04E


Date: 2022-05-10



Test Configure

26dB Bandwidth

Channel 38



9.MAY.2022 10:59:04 Date:


Page 102 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 46



Date: 9.MAY.2022 10:53:52

Page 103 of 166

Report No.: TW2203329-04E


Date: 2022-05-10



Test Configure

99% Bandwidth

Channel 38



9.MAY.2022 10:59:21 Date:


Page 104 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 46



Date: 9.MAY.2022 10:53:38 Report No.: TW2203329-04E Page 105 of 166

Date: 2022-05-10



EUT		Tablet PC			Model	K13		
Mode		802.11ac VHT40			Input Voltage	DC3.7V		
Temperature			24 deg.	. C,	Humidity	56% RH		
Channel	Channel Frequency (MHz)		Data Transfer Rate (Mbps)	Bandwidth (MHz)	Minimum Limit (MHz)	Pass/ Fail		
26dB Bar	ndwidth							
151	5755		mcs0	45.45		Pass		
159	5795		mcs0	45.45		Pass		
6dB Band	dwidth							
151	5755		mcs0	36.23	0.5	Pass		
159	5795		mcs0	36.14	0.5	Pass		
99% Bandwidth								
151		5755	mcs0	37.27		Pass		
159		5795	mcs0	37.15		Pass		

Page 106 of 166

Report No.: TW2203329-04E


Date: 2022-05-10



Test Configure

26dB Bandwidth

Channel 151



9.MAY.2022 15:29:35 Date:


Page 107 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 159



Date: 9.MAY.2022 15:33:06

Page 108 of 166

Report No.: TW2203329-04E


Date: 2022-05-10



Test Configure

6dB Bandwidth

Channel 151



9.MAY.2022 15:04:57 Date:


Page 109 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 159



Date: 9.MAY.2022 15:02:43

Page 110 of 166

Report No.: TW2203329-04E


Date: 2022-05-10



Test Configure

99% Bandwidth

Channel 151



9.MAY.2022 15:29:16 Date:


Page 111 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 159



Date: 9.MAY.2022 15:33:17

Page 112 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



EUT			Tablet P	С	Model	K13	
Mode 802.11ac VHT80 Input			Input Voltage	DC3.7V			
Temperati	ure		24 deg. (C,	Humidity	56% RH	
Channel		el Frequency (MHz)	Data Transfer Rate (Mbps)	Bandwidth (MHz)	Minimum Limi (MHz)	t Pass/ Fail	
26dB Bar	ndwidth						
42		5210	mcs0	86.09		Pass	
99% Bandwidth							
42	42 5210		mcs0	75.99		Pass	

Page 113 of 166

Report No.: TW2203329-04E


Date: 2022-05-10



Test Configure

26dB Bandwidth

Channel 42



9.MAY.2022 11:02:50 Date:

Page 114 of 166

Report No.: TW2203329-04E


Date: 2022-05-10



Test Configure

99% Bandwidth

Channel 42



9.MAY.2022 11:02:36 Date:

Page 115 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



EUT			Tablet	PC	Model	K13						
Mode	Mode			VHT80	Input Voltage	DC3.7V						
Temperat	ure		24 deg	g. C,	Humidity	56% RH						
Channel		Channel Frequency (MHz)		Bandwidth (MHz)	Minimum Limit (MHz)	Pass/ Fail						
26dB Bar	ndwidth											
155	55 5775		5775		5775		5775		mcs0	86.09	-	Pass
6dB Ban	dwidth											
155		5775	mcs0	75.71	0.5	Pass						
99% Ban	99% Bandwidth											
155		5775	mcs0	75.99		Pass						

Page 116 of 166

Report No.: TW2203329-04E


Date: 2022-05-10



Test Configure

26dB Bandwidth

Channel 155



9.MAY.2022 15:24:31 Date:

Page 117 of 166


Report No.: TW2203329-04E

Date: 2022-05-10



6dB Bandwidth

Channel 155



Date: 9.MAY.2022 15:07:44

Page 118 of 166

Report No.: TW2203329-04E


Date: 2022-05-10



Test Configure

99% Bandwidth

Channel 155



9.MAY.2022 15:25:01 Date:


Report No.: TW2203329-04E

Date: 2022-05-10



8.0 Peak Transmit Power Measurement

8.1 Test Setup



8.2 Limits of Peak Transmit Power Measurement

Operation Band		EUT Category	Limit	
		Outdoor Access Point	1 Watt (30 dBm) ≤ (Max. e.i.r.p 125mW	
			(21 dBm) at any elevation angle above 30	
			degrees as measured from the horizon)	
U-NII-1		Fixed point-to-point Access Point	1 Watt (30 dBm)	
		Indoor Access Point	1 Watt (30 dBm)	
	√	Mobile and Portable client device	250mW (24 dBm)	
U-NII-2A			250mW (24 dBm) or 11 dBm+10 log B*	
U-NII-2C			250mW (24 dBm) or 11 dBm+10 log B*	
U-NII-3			1 Watt (30 dBm)	

Note: Where B is the 26dB emission bandwidth in MHz.

8.3 Test Procedure

The RF power output was measured with a Spectrum analyzer connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate centre frequency.

Note: the average power was measured

Page 120 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



8.4Test Results

EU	T	Tablet PC	Model	K13	
Mod	de	802.11a	Test Voltage	DC3.7V	
Temper	rature	24 deg. C,	Humidity	56% RH	
Channel	Frequen (MHz)		m) Limit (dBm)) Pass/ Fail	
36	5180	8.61	24	Pass	
40	5200	8.39	24	Pass	
48	5240	8.33	24	Pass	
149	5745	11.52	30	Pass	
153	5765	11.37	30	Pass	
161	5825	10.95	30	Pass	

Note: 1. At finial test to get the worst-case emission at 6Mbps for CH36, CH40, CH48, CH149, CH153 and CH161

- 2. The result basic equation calculation as follow: Average Power Output = AV Power Reading + Cable loss + Attenuator
- 3. The worse case was recorded

Page 121 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



EU	T		Tablet PC	Model		K13	
Mod	de		802.11n HT20	Test Voltage			DC3.7V
Temper	rature		24 deg. C,	Hun	nidity		56% RH
Channel	Freque (MHz	-	Power (dBm)		Limit (d	Bm)	Pass/ Fail
36	5180)	8.15		24		Pass
40	5200	8.03		24		Pass	
48	5240)	7.95		24		Pass
149	5745	5	11.27	11.27 30		Pass	
153	5765	5	11.08		30		Pass
161	5825 11.16			30		Pass	

Note: 1. At finial test to get the worst-case emission at mcs0 for CH36, CH40, CH48, CH149, CH153 and CH161

2. The result basic equation calculation as follow:

Average Power Output = AV Power Reading + Cable loss + Attenuator

3. The worse case was recorded

Report No.: TW2203329-04E Page 122 of 166

Date: 2022-05-10



EU	Т		Tablet PC	Model		K13
Mod	de		802.11n HT40	Т	est Voltage	DC3.7V
Temper	rature		24 deg. C,]	Humidity	56% RH
Channel	Frequer (MHz		Power (dBm)		Limit (dBm	Pass/ Fail
38	5190)	7.56		24	Pass
46	5230)	7.34		24	Pass
151	5755	5	10.43		30	Pass
159	5795	5	10.29		30	Pass

Note: 1. At finial test to get the worst-case emission at mcs0 for CH38, CH46, CH151, CH159 and CH161

2. The result basic equation calculation as follow: Average Power Output = AV Power Reading + Cable loss + Attenuator

3. The worse case was recorded

Page 123 of 166

Date: 2022-05-10

Report No.: TW2203329-04E



EU'	Т		Tablet PC	Model	K13	
Mod	de		802.11ac VHT20	Test Voltage	DC3.7V	
Temper	rature		24 deg. C,	Humidity	56% RH	
Channel	Frequer (MHz	-	Power (dBm)	Limit (dBı	Pass/ Fail	
36	5180)	8.22	24	Pass	
40	5200)	8.35	24	Pass	
48	5240)	8.09	24	Pass	
149	5745		11.18	30	Pass	
153	5765		10.93	30	Pass	
161	5825		10.87	30	Pass	

Note: 1. At finial test to get the worst-case emission at mcs0 for CH36, CH40, CH48, CH149, CH153 and CH161

2. The result basic equation calculation as follow: Average Power Output = AV Power Reading + Cable loss + Attenuator

3. The worse case was recorded

Page 124 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



EU	T		Tablet PC		Model		K13	
Mod	de		802.11ac VHT40	Test Voltage			DC3.7V	
Temper	rature		24 deg. C,]	Humidity		56% RH	
Channel	Freque (MH	-	Power (dBm)		Limit (dBm)		Pass/ Fail	
38	5190)	7.96		24		Pass	
46	5230)	7.80		24		Pass	
151	5755	5	10.29		30		Pass	
159	5795	5	10.37		30		Pass	

Note: 1. At finial test to get the worst-case emission at mcs0 for CH38, CH46, CH151, CH159 and CH161

2. The result basic equation calculation as follow: Average Power Output = AV Power Reading + Cable loss + Attenuator

3. The worse case was recorded

EU	T		Tablet PC		Model		K13
Mod	de		802.11ac VHT80	Test Voltage			DC3.7V
Temper	rature		24 deg. C,	I	Humidity		56% RH
Channel	Freque (MH		Power (dBm)		Limit (dBm)		Pass/ Fail
42	5210)	6.35		24		Pass
155	577:	5	9.58		30		Pass

Note: 1. At finial test to get the worst-case emission at mcs0 s for CH42 and CH155

- 2. The result basic equation calculation as follow: Average Power Output = AV Power Reading + Cable loss + Attenuator
- 3. The worse case was recorded

Page 125 of 166


Report No.: TW2203329-04E

Date: 2022-05-10



9. Power Spectral Density Measurement

9.1 Test Setup



9.2 Limits of Power Spectral Density Measurement

Operation Band		EUT Category	Limit
		Outdoor Access Point	
II NIII 1	Fixed point-to-point Access Point		17dBm/MHz
U-NII-1		Indoor Access Point	
	√	Mobile and Portable client device	11dBm/MHz
U-NII-2A			11dBm/MHz
U-NII-2C			11dBm/MHz
U-NII-3			30dBm/500kHz

9.3 Test Procedure

- 1. The EUT was directly connected to the spectrum analyzer
- 2. Set the RBW = 1MHz or 500kHz
- 3. Set the VBW =3MHz or 2MHz
- 4. Set the span to encompass the entire emissions bandwidth (EBW) of the signal
- 5. Detector = RMS
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the peak marker function to determine the maximum amplitude level.

Page 126 of 166 Report No.: TW2203329-04E

Date: 2022-05-10



9.4Test Result

EUT			Tablet PC	Model	K	.13
Mode	;		802.11a 6Mbps	Test Voltage	DC:	3.7V
Temperat	ture		24 deg. C,	Humidity	56%	6 RH
Channel		quency (Hz)	Power Spectral Density(dBm/MHz)	Limit (dBm/MHz)		Pass/ Fail
36	5	180	-3.09	11		Pass
40	5	200	-2.60	11		Pass
48	5	240	-2.55	11		Pass
Channel		quency (Hz)	Power Spectral Density(dBm/500kHz)	Limit (dBm/500kHz)		Pass/ Fail
149	5	745	-4.80	30		Pass
153	5	765	-4.64	30		Pass
161	5	825	-4.35	30		Pass

Page 127 of 166


Report No.: TW2203329-04E

Date: 2022-05-10



9.5 Plots of Power Spectral Density Measurement

1.802.11a at 6Mbps of CH36



Date:

9.MAY.2022 12:16:37


Page 128 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



2.802.11a at 6Mbps of CH40



9.MAY.2022 12:17:19 Date:


Page 129 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



3.802.11a at 6Mbps of CH48



Date: 9.MAY.2022 12:17:47


Page 130 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



4.802.11a at 6Mbps of CH149



Date: 9.MAY.2022 17:50:41


Page 131 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



5.802.11a at 6Mbps of CH153



Date: 9.MAY.2022 17:53:45


Page 132 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



6.802.11a at 6Mbps of CH161



Date: 9.MAY.2022 17:54:24

Page 133 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



EUT		Tablet PC		Model	K13	3
Mode			802.11n HT20 mcs0	Test Voltage	DC3.	7V
Temperat	ture		24 deg. C,	Humidity	56%]	RH
Channel	Freque	ency	Power Spectral	Limit		Pass/ Fail
	(MH	z)	Density(dBm/MHz)	(dBm/MH	z)	
36	5180	0	-2.91	11		Pass
40	5200	0	-2.84	11	11	
48	5240	0	-2.55	11		Pass
Channel	Freque	ency	Power Spectral	Limit		Pass/ Fail
	(MH	(z)	Density(dBm/500kHz)	(dBm/500kl	Hz)	
149	574:	5	-4.40	30	30	
153	576:	5	-4.41	30	30	
161	582:	5	-4.96	30		Pass

Page 134 of 166


Report No.: TW2203329-04E

Date: 2022-05-10



Test Plots

1.802.11n at mcs0 of CH36



Date: 9.MAY.2022 12:16:02


Page 135 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



2.802.11n at mcs0 of CH40



9.MAY.2022 12:12:17 Date:


Page 136 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



3.802.11n at mcs0 of CH48



Date: 9.MAY.2022 12:10:58


Page 137 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



4.802.11n at mcs0 of CH149



Date: 9.MAY.2022 17:51:26


Page 138 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



5.802.11n at mcs0 of CH153



Date: 9.MAY.2022 17:53:05


Page 139 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



6.802.11n at mcs0 of CH161



Date: 9.MAY.2022 17:55:00

Page 140 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



EUT		Tablet PC	Model	K13	
Mode	:	802.11n HT40 mcs0	Test Voltage	DC3.7V	
Temperat	ture	24 deg. C,	Humidity	56% RH	
Channel	Frequency	Power Spectral	Limit	Pass/ Fail	
	(MHz)	Density(dBm/MHz)	(dBm/MHz)		
38	5190	-5.84	11	Pass	
46	5230	-5.02	11	Pass	
Channel	Frequency	Power Spectral	Limit Pass/ Fail (dBm/500kHz)		
	(MHz)	Density(dBm/500kHz)			
151	5755	-7.45	30	Pass	
159	5795	-6.80	30	30 Pass	

Page 141 of 166


Report No.: TW2203329-04E

Date: 2022-05-10



Test Plots

1.802.11n HT40 at mcs0 of CH38



Date: 9.MAY.2022 12:18:24


Page 142 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



2.802.11n HT40 at mcs0 of CH46



9.MAY.2022 12:19:07 Date:


Page 143 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



3.802.11n HT40 at mcs0 of CH151



Date: 9.MAY.2022 17:49:48


Page 144 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



4.802.11n HT40 at mcs0 of CH159



Date: 9.MAY.2022 17:49:07

Page 145 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



EUT		Tablet PC	Model	K13	
Mode	1	802.11ac VHT20	Test Voltage	DC3.7V	
Temperat	ture	24 deg. C,	Humidity	56% RH	
Channel	Frequency (MHz)	Power Spectral Density(dBm/MHz)	Limit (dBm/MHz)	Pass/ Fail	
36	5180	-2.78	11	Pass	
40	5200	-2.67	11	Pass	
48	5240	-2.60	11	Pass	
Channel	Frequency Power Spectral Limit I (MHz) Density(dBm/500kHz) (dBm/500kHz)		Pass/ Fail		
149	5745	-4.59	30	Pass	
153	5765	-4.26	30	Pass	
161	5825	-4.11	30	Pass	

Page 146 of 166


Report No.: TW2203329-04E

Date: 2022-05-10



Test Plots

1.802.11ac at mcs0 of CH36



Date: 9.MAY.2022 12:08:33


Page 147 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



2.802.11ac at mcs0 of CH40



9.MAY.2022 12:06:48 Date:


Page 148 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



3.802.11ac at mcs0 of CH48



9.MAY.2022 12:09:20 Date:


Page 149 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



4.802.11ac at mcs0 of CH149



Date: 9.MAY.2022 17:52:11


Page 150 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



5.802.11ac at mcs0 of CH153



Date: 9.MAY.2022 17:52:37


Page 151 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



6.802.11ac at mcs0 of CH161



Date: 9.MAY.2022 17:55:31

Page 152 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



EUT		Tablet PC	Model		3
Mode	:	802.11ac VHT40	Test Voltage	DC3.	7V
Temperat	ture	24 deg. C,	Humidity	56% I	RH
Channel	Frequency	Power Spectral	Limit		Pass/ Fail
	(MHz)	Density(dBm/MHz)	(dBm/MH	z)	
38	5190	-5.90	11		Pass
46	5230	-5.44	11		Pass
Channel	Frequency	Power Spectral	Limit		Pass/ Fail
	(MHz)	Density(dBm/500kHz)	(dBm/500k)	dBm/500kHz)	
151	5755	-7.07	30		Pass
159	5795	-7.12	30		Pass

Page 153 of 166


Report No.: TW2203329-04E

Date: 2022-05-10



Test Plots

1.802.11ac at mcs0 of CH38



Date: 9.MAY.2022 12:21:57


Page 154 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



2.802.11ac at mcs0 of CH46



9.MAY.2022 12:20:55 Date:


Page 155 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



3.802.11ac at mcs0 of CH151



Date: 9.MAY.2022 17:48:06


Page 156 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



4.802.11ac at mcs0 of CH159



Date: 9.MAY.2022 17:48:36 Page 157 of 166

Date: 2022-05-10

Report No.: TW2203329-04E



EUT		Tablet PC	Model	K13	
Mode		802.11ac VHT80	Test Voltage	DC3.7V	
Temperat	ture	24 deg. C,	Humidity	56% RH	
Channel	Frequency	Power Spectral	L	imit	Pass/ Fail
	(MHz)	Density(dBm/MHz)	(dBm	n/MHz)	
42	5210	-8.74		11	Pass
Channel	Frequency	Power Spectral	L	imit	Pass/ Fail
	(MHz)	Density(dBm/500kHz)	(dBm/	500kHz)	
155	5775	-10.06		30	Pass

Page 158 of 166


Report No.: TW2203329-04E

Date: 2022-05-10



Test Plots

1.802.11ac at mcs0Mbps of CH42



Date: 9.MAY.2022 12:23:02


Page 159 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



2.802.11ac at mcs0Mbps of CH155



Date: 9.MAY.2022 17:46:48 Report No.: TW2203329-04E

Date: 2022-05-10



Page 160 of 166

10.0 Frequency Stability

10.1 Limits of Frequency Stability Measurement

The frequency tolerance of the carrier signal shall be maintained within \pm 0.02% of the operating frequency over a temperature variation of \pm 30 degrees to 50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees

10.2 Test Procedure

- 1. The EUT was placed inside the environmental test chamber and powered by nominal DC voltage.
- 2. Turn the EUT on and couple its output to a spectrum analyzer.
- 3. Turn the EUT off and set the chamber to the highest temperature specified.
- 4. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 minutes.
- 5. Repeat step 2 and 3 with the temperature chamber set to the lowest temperature.
- 6. The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.

Report No.: TW2203329-04E

Date: 2022-05-10



11.3 Test Result

Channel 36 (5180MHz)

Voltage vs. Frequency Stability

Voltage	Measurement Frequency (MHz)
3.7V	5180.0343
3.3V	5180.0329
4.2V	5180.0350
Max. Deviation (MHz)	0.0350
Max. Deviation (ppm)	6.76

Rated working voltage: DC3.7V

Temperature vs. Frequency Stability

Temperature (°C)	Measurement Frequency (MHz)
-30	5180.0352
-20	5180.0346
-10	5180.0367
0	5180.0329
10	5180.0338
20	5180.0322
30	5180.0341
40	5180.0356
50	5180.0361
Max. Deviation (MHz)	0.0367
Max. Deviation (ppm)	7.08

Page 162 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



Channel 149 (5745MHz)

Voltage vs. Frequency Stability

Voltage	Measurement Frequency (MHz)
3.7V	5745.0516
3.3V	5745.0533
4.2V	5745.0507
Max. Deviation (MHz)	0.0533
Max. Deviation (ppm)	9.28

Rated working voltage: DC3.7V

Temperature vs. Frequency Stability

Temperature (°C)	Measurement Frequency (MHz)
-30	5745.0489
-20	5745.0506
-10	5745.0513
0	5745.0477
10	5745.0523
20	5745.0512
30	5745.0495
40	5745.0511
50	5745.0526
Max. Deviation (MHz)	0.0526
Max. Deviation (ppm)	9.16

Report No.: TW2203329-04E

Date: 2022-05-10



Page 163 of 166

11.0 Antenna Requirement

11.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitter antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the mount in dB that the directional gain of the antenna exceeds 6 dBi.

11.2 Antenna Connected construction

Integral antennas used. The gain of the antennas is 2.0dBi maximum. (Declared by the applicant)

Report No.: TW2203329-04E Page 164 of 166

Date: 2022-05-10




12.0 FCC ID Label

FCC ID: RBD-K13

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Mark Location:



Page 165 of 166

Report No.: TW2203329-04E

Date: 2022-05-10



13.0 Photo of testing

Conducted Emission Test Setup:




Report No.: TW2203329-04E

Date: 2022-05-10



Radiated Emission Test Setup



Photos of EUT

Please see test report TW2203329-01E

-- End of the report--

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the propert. discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.