

# **FCC Test Report**

Report No.: AGC10232250201FR01

**FCC ID** : 2AEAN-0440

**APPLICATION PURPOSE**: Original Equipment

**PRODUCT DESIGNATION**: PROFESSIONAL WIRELESS MICROPHONE SYSTEM

**BRAND NAME** : RØDE

**MODEL NAME** : RØDELINK II TRANSMITTER

**APPLICANT**: Rode Microphones

**DATE OF ISSUE** : Feb. 18, 2025

**STANDARD(S)** : FCC Part 15 Subpart C §15.247

**REPORT VERSION**: V1.0

Attestation Of Global Compliance (Shenzhen) Co., Ltd



Page 2 of 67

# **Report Revise Record**

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Feb. 18, 2025	Valid	Initial Release




# **Table of Contents**

1. General Information	5
2. Product Information	6
2.1 Product Technical Description	6
2.2 Test Frequency List	6
2.3 Related Submittal(S) / Grant (S)	7
2.4 Test Methodology	7
2.5 Special Accessories	7
2.6 Equipment Modifications	7
2.7 Antenna Requirement	7
3. Test Environment	8
3.1 Address of the Test Laboratory	8
3.2 Test Facility	8
3.3 Environmental Conditions	9
3.4 Measurement Uncertainty	9
3.5 List of Equipment Use	10
4.System Test Configuration	12
4.1 EUT Configuration	12
4.2 EUT Exercise	12
4.3 Configuration of Tested System	12
4.4 Equipment Used In Tested System	12
4.5 Summary of Test Results	13
5. Description of Test Modes	14
6. Duty Cycle Measurement	15
7. RF Output Power Measurement	16
7.1 Provisions Applicable	16
7.2 Measurement Procedure	16
7.3 Measurement Setup (Block Diagram of Configuration)	16
7.4 Measurement Result	17
8. 6dB Bandwidth Measurement	21
8.1 Provisions Applicable	21
8.2 Measurement Procedure	21
8.3 Measurement Setup (Block Diagram of Configuration)	21
8.4 Measurement Results	22
9. Power Spectral Density Measurement	29
9.1 Provisions Applicable	29
9.2 Measurement Procedure	
9.3 Measurement Setup (Block Diagram of Configuration)	
9.4 Measurement Results	30
10. Conducted Band Edge and Out-of-Band Emissions	34
10.1 Provisions Applicable	34


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Web: http://www.agccert.com/





.2 Measurement Procedure	34
.1 Measurement Limit	
.2 Measurement Procedure	46
.3 Measurement Setup (Block Diagram of Configuration)	49
.4 Measurement Result	50
Power Line Conducted Emission Test	
.1 Measurement Limit	63
.2 Measurement Setup (Block Diagram of Configuration)	63
.3 Preliminary Procedure of Line Conducted Emission Test	
.4 Final Procedure of Line Conducted Emission Test	64
.5 Measurement Results	65
ndix I: Photographs of Test Setup	67
ndix II: Photographs of Test EUT	67
	2 Measurement Procedure





# 1. General Information

Applicant	Rode Microphones	
Address	107 Carnarvon Street, Silverwater 2128, Australia	
Manufacturer	Rode Microphones	
Address	107 Carnarvon Street, Silverwater 2128, Australia	
Factory	Rode Microphones	
Address	107 Carnarvon Street, Silverwater 2128, Australia	
Product Designation	PROFESSIONAL WIRELESS MICROPHONE SYSTEM	
Brand Name	RØDE	
Test Model	RØDELINK II TRANSMITTER	
Series Model(s)	N/A	
Difference Description	N/A	
Date of receipt of test item	Feb. 05, 2025	
Date of Test	Feb. 05, 2025~Feb. 18, 2025	
Deviation from Standard	No any deviation from the test method	
Condition of Test Sample	Normal	
Test Result	Pass	
Test Report Form No	AGCER-FCC-BLE-V1	

Note: The test results of this report relate only to the tested sample identified in this report.

Prepared By	Jouk Gai	
	Jack Gui (Project Engineer)	Feb. 18, 2025
Reviewed By	Calin Lin	
	Calvin Liu (Reviewer)	Feb. 18, 2025
Approved By	Angole Li	
	Angela Li (Authorized Officer)	Feb. 18, 2025





Page 6 of 67

# 2. Product Information

# 2.1 Product Technical Description

Equipment Type	Custom for 2.4GHz
Frequency Band	2400MHz-2483.5MHz
Operation Frequency Range	2402MHz-2480MHz
Modulation	GFSK
Number of channels	40
Maximum Transmitter Power	Chain A:-0.257dBm
Maximum Hansimiler Fower	Chain B: 0.479dBm
Hardware Version	V1.0
Software Version	V1.0
Antonna Decignation	FPC Antenna for ANT 1 (Chain A Port)
Antenna Designation	PCB Antenna for ANT 2 (Chain B Port)
Antenna Gain	ANT 1 (Chain A Port): 2.404dBi
Antenna Gam	ANT 2 (Chain B Port):-0.804dBi
Power Supply	DC 5V from Adapter and DC 3.7V by Battery

# 2.2 Test Frequency List

2402 MHz 2404 MHz
2404 MHz
·
2440MHz
· ·
2478 MHz
2480 MHz



Page 7 of 67

#### 2.3 Related Submittal(S) / Grant (S)

This submittal(s) (test report) is intended for FCC ID: **2AEAN-0440**, filing to comply with Part 2, Part 15 of the Federal Communication Commission rules.

#### 2.4 Test Methodology

The tests were performed according to following standards:

No.	Identity	Document Title			
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations			
2	FCC 47 CFR Part 15	Radio Frequency Devices			
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices			
4	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on Digital Transmission Systems, Frequency Hopping Spread Spectrum system, and Hybrid system devices operating under Section 15.247 of the FCC rules			

#### 2.5 Special Accessories

Not available for this EUT intended for grant.

#### 2.6 Equipment Modifications

Not available for this EUT intended for grant.

#### 2.7 Antenna Requirement

## Standard Requirement

#### 15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

# 15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi

#### EUT Antenna:

The non-detachable antenna inside the device cannot be replaced by the user at will. The gain of the antenna 1 is 2.404dBi and antenna 2 is -0.804dBi



Page 8 of 67

#### 3. Test Environment

#### 3.1 Address of the Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

#### 3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to follow CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories).

## A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to follow ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

#### FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

#### IC-Registration No.: 24842 (CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



Page 9 of 67


#### 3.3 Environmental Conditions

	Normal Conditions
Temperature range (℃)	15 - 35
Relative humidity range	20 % - 75 %
Pressure range (kPa)	86 - 106
Power supply	DC 3.7V

# 3.4 Measurement Uncertainty

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

i.	
Item	Measurement Uncertainty
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 2.9 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.9 \text{ dB}$
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.9 \text{ dB}$
Uncertainty of total RF Power, Conducted	$U_c = \pm 0.8 \text{ dB}$
Uncertainty of RF Power Density, Conducted	$U_c = \pm 2.6 \text{ dB}$
Uncertainty of Spurious Emissions, Conducted	$U_c = \pm 2 \%$
Uncertainty of Occupied Channel Bandwidth	$U_c = \pm 2 \%$
Uncertainty of Dwell Time	$U_c = \pm 2 \%$





## 3.5 List of Equipment Use

RF Conducted Test System							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
$\boxtimes$	AGC-ER-E036	Spectrum Analyzer	Agilent	N9020A	MY49100060	2025-01-30	2026-01-29
$\boxtimes$	AGC-ER-E062	Power Sensor	Agilent	U2021XA	MY54110007	2025-01-14	2026-01-13
$\boxtimes$	AGC-ER-E063	Power Sensor	Agilent	U2021XA	MY54110009	2025-01-14	2026-01-13
$\boxtimes$	AGC-ER-A001	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2025-06-08
$\boxtimes$	AGC-ER-E083	Signal Generator	Agilent	E4421B	US39340815	2024-05-23	2025-05-22
	N/A	RF Connection Cable	N/A	1#	N/A	Each time	N/A
	N/A	RF Connection Cable	N/A	2#	N/A	Each time	N/A

• F	Radiated Spurious Emission						
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
$\boxtimes$	AGC-EM-E046	EMI Test Receiver	R&S	ESCI	10096	2025-01-14	2026-01-13
$\boxtimes$	AGC-EM-E116	EMI Test Receiver	R&S	ESCI	100034	2024-05-24	2025-05-23
$\boxtimes$	AGC-EM-E061	Spectrum Analyzer	Agilent	N9010A	MY53470504	2024-05-28	2025-05-27
$\boxtimes$	AGC-EM-E086	Loop Antenna	ZHINAN	ZN30900C	18051	2024-03-05	2026-03-04
$\boxtimes$	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023-05-11	2025-05-10
	AGC-EM-E029	Broadband Ridged Horn Antenna	ETS	3117	00034609	2024-03-31	2025-03-30
$\boxtimes$	AGC-EM-E082	Horn Antenna	SCHWARZBECK	BBHA 9170	#768	2023-09-24	2025-09-23
$\boxtimes$	AGC-EM-E146	Pre-amplifier	ETS	3117-PA	00246148	2024-07-24	2026-07-23
$\boxtimes$	AGC-EM-A119	2.4G Filter	SongYi	N/A	N/A	2024-05-23	2025-05-22
$\boxtimes$	AGC-EM-A138	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2025-06-08
$\boxtimes$	AGC-EM-A139	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2025-06-08

<ul><li>A</li></ul>	AC Power Line Conducted Emission								
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)		
	AGC-EM-E045	EMI Test Receiver	R&S	ESPI	101206	2024-05-28	2025-05-27		
$\boxtimes$	AGC-EM-A130	6dB Attenuator	Eeatsheep	LM-XX-6-5W	DC-6GZ	2023-06-09	2025-06-08		
	AGC-EM-E023	AMN	R&S	100086	ESH2-Z5	2024-05-28	2025-05-27		



Page 11 of 67

• Tes	Test Software							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Version Information			
$\boxtimes$	AGC-EM-S001	CE Test System	R&S	ES-K1	V1.71			
$\boxtimes$	AGC-EM-S003	RE Test System	FARA	EZ-EMC	VRA-03A			
$\boxtimes$	AGC-ER-S012	BT/WIFI Test System	Tonscend	JS1120-2	2.6			
$\boxtimes$	AGC-EM-S011	RSE Test System	Tonscend	TS+-Ver2.1(JS36-RSE)	4.0.0.0			



Page 12 of 67

# 4. System Test Configuration

# 4.1 EUT Configuration


The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

#### 4.2 EUT Exercise


The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

## 4.3 Configuration of Tested System

Radiated Emission Configure:



Conducted Emission Configure:



## 4.4 Equipment Used In Tested System

The following peripheral devices and interface cables were connected during the measurement:

☐ Test Accessories Come From The Laboratory

No	Equipment	Manufacturer	Model No.	Specification Information	Cable
1	Adapter	HUAWEI	HW-200440C00	Input(AC):100V-240V 50/60Hz 2.4A Output(DC):USB-C(5V/3A;9V/3A;10V/4A ;11V/6A;12V/3A;15V/3A;20V4.4A) USB-A(5V/2A;10V/4A;11V/6A;20V/4.4A)	unshielded

#### ☐ Test Accessories Come From The Manufacturer


No.	Equipment	Manufacturer	Model No.	Specification Information	Cable
1	Battery	Phenix New Energy (Huizhou) Co., Ltd.	LB-2	DC 3.7V 1100mAh	



Page 13 of 67

## 4.5 Summary of Test Results

Item	FCC Rules	Description of Test	Result
1	§15.203&15.247(b)(4)	Antenna Equipment	Pass
2	§15.247 (b)(3)	RF Output Power	Pass
3	§15.247 (a)(2)	6 dB Bandwidth	Pass
4	§15.247 (e)	Power Spectral Density	Pass
5	§15.247 (d)	Conducted Band Edge and Out-of-Band Emissions	Pass
6	§15.209	Radiated Emission& Band Edge	Pass
7	§15.207	AC Power Line Conducted Emission	Pass





# 5. Description of Test Modes

Summary Table of Test Cases				
Test Item	Data Rate / Modulation			
rest item	SRD 2.4G /GFSK			
	Mode 1: SRD 2.4G CH00_2402 MHz (Battery powered or AC/DC adapter)			
Radiated & Conducted Test Cases	Mode 2: SRD 2.4G CH19_2440 MHz(Battery powered or AC/DC adapter)			
1001 00000	Mode 3: SRD 2.4G CH39_2480 MHz (Battery powered or AC/DC adapter)			
AC Conducted Emission	Mode 1: SRD 2.4G Link + Battery + USB Cable (Charging from AC Adapter)			

#### Note:

- 1. Only the result of the worst case was recorded in the report, if no other cases.
- 2. The battery is full-charged during the test.
- 3. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 4. For Conducted Test method, a temporary antenna connector is provided by the manufacture.

  Software Setting Diagram

```
DANKERS SCIENCY DIAGRAC-10232-25-02-01 RØDE PROFESSIONAL WIRELESS MICROPHONE SYSTEM RODELINK II TRANSMITTER/RODELINK-II--- 定数体/RODELINK-II RF Testexe RODELINK II TS Script Rev 2 (Now Support RX only mode); RF power setting is from 0 to 100 6-47-110 RODELink II TX Firmware Version: 0.23 RF ID is: DB.50. IB.80 Eattery: 4.145V, 89.00%, 24.0 Deg. C Mode: GFSK, Antenna: 1, Frequency: 40, Power: 30 Mode: GFSK All done.
```



Page 15 of 67


## 6. Duty Cycle Measurement

The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = Peak. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Operating mode	T(µs)	Duty Cycle (%)	Duty Cycle Factor (dB)	1/ T Minimum VBW (kHz)
SRD 2.4G_Chain A	873.6	86	0.66	1.14
SRD 2.4G_Chain B	873.8	86	0.66	1.14

#### Remark:

- 1. Duty Cycle factor = 10 \* log (1/ Duty cycle)
- 2. The duty cycle of each frequency band mode reflects the determination requirements of the low channel measurement value
- The test plots as follows:





Page 16 of 67

# 7. RF Output Power Measurement

# 7.1 Provisions Applicable

For DTSs employing digital modulation techniques operating in the bands 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W.


#### 7.2 Measurement Procedure

For Peak Power, the testing follows ANSI C63.10 Section 11.9.1.1 Method Max peak power:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Set the RBW≥DTS bandwidth
- 3. Set the VBW≥[3 x RBW].
- 4. Span≥[3 x RBW].
- 5. Sweep= auto couple.
- 6. Detector Function= Peak.
- 7. Trace mode= Max hold.
- 8. Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.
- ☐ For Average power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G:
- 1. The RF output of EUT was connected to the power meter by RF cable and attenuator.
- 2. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- Measure the conducted output power and record the results in the test report.

#### 7.3 Measurement Setup (Block Diagram of Configuration)


☐ For Average power test setup





Page 17 of 67


# 



## 7.4 Measurement Result

Test Data of Conducted Output Power-Chain A							
Test Mode	Test Frequency (MHz)	Peak Power (dBm)	Limits (dBm)	Pass or Fail			
	2402	-0.462	≤30	Pass			
GFSK	2440	-0.352	≤30	Pass			
	2480	-0.257	≤30	Pass			

Test Data of Conducted Output Power-Chain B							
Test Mode	Test Frequency (MHz)	Peak Power (dBm)	Limits (dBm)	Pass or Fail			
	2402	0.479	≤30	Pass			
GFSK	2440	-0.070	≤30	Pass			
	2480	-0.093	≤30	Pass			






**Test Graphs of Conducted Output Power** 























Page 21 of 67

#### 8. 6dB Bandwidth Measurement


# 8.1 Provisions Applicable


The minimum 6dB bandwidth shall be 500 kHz.

#### **8.2 Measurement Procedure**

- The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
- The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss
  was compensated to the results for each measurement.
- 2. Set to the maximum power setting and enable the EUT transmit continuously.
- 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
- For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the OBW and set the Video bandwidth (VBW) ≥ 3 \* RBW.
- 5. Measure and record the results in the test report.

# 8.3 Measurement Setup (Block Diagram of Configuration)









#### 8.4 Measurement Results

Test Data of Occupied Bandwidth and DTS Bandwidth-Chain A							
Test Mode	Test Frequency (MHz)	Occupied Bandwidth (MHz)	DTS BW (MHz)	DTS BW Limits	Pass or Fail		
	2402	1.050	0.710	≥0.5	Pass		
GFSK	2440	1.062	0.704	≥0.5	Pass		
	2480	1.058	0.708	≥0.5	Pass		

Test Data of Occupied Bandwidth and DTS Bandwidth-Chain B							
Test Mode	Test Frequency (MHz)	Occupied Bandwidth (MHz)	DTS BW (MHz)	DTS BW Limits	Pass or Fail		
	2402	1.053	0.710	≥0.5	Pass		
GFSK	2440	1.057	0.708	≥0.5	Pass		
	2480	1.053	0.709	≥0.5	Pass		


**Test Graphs of Occupied Bandwidth** 











































Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/









Page 29 of 67

# 9. Power Spectral Density Measurement


#### 9.1 Provisions Applicable


The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

#### 9.2 Measurement Procedure

- The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
- The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss
  was compensated to the results for each measurement.
- 2. Set to the maximum power setting and enable the EUT transmit continuously.
- Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz in order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
- 4. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
- 5. Measure and record the results in the test report.
- 6. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

# 9.3 Measurement Setup (Block Diagram of Configuration)








#### 9.4 Measurement Results

Test Data of Conducted Output Power Spectral Density-Chain A						
Test Mode	Test Frequency (MHz)	Limit (dBm/3kHz)	Pass or Fail			
	2402	-12.864	<b>≤8</b>	Pass		
GFSK	2440	-12.641	≪8	Pass		
	2480	-13.019	≪8	Pass		


Test Data of Conducted Output Power Spectral Density-Chain B				
Test Mode	Test Frequency (MHz)	Power density (dBm/3kHz)	Limit (dBm/3kHz)	Pass or Fail
GFSK_1Mbps	2402	-11.912	<b>≤8</b>	Pass
	2440	-11.888	≪8	Pass
	2480	-12.265	≪8	Pass


**Test Graphs of Conducted Output Power Spectral Density** 


















Test Graph SRD 2.4G Chain B 2440 PSD









Page 34 of 67

# 10. Conducted Band Edge and Out-of-Band Emissions


# 10.1 Provisions Applicable


The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the PSD procedure.

#### 10.2 Measurement Procedure

- Reference level measurement
- 1. Set instrument center frequency to DTS channel center frequency
- 2. Set the span to ≥ 1.5 times the DTS bandwidth
- 3. Set the RBW = 100 kHz
- Set the VBW ≥ 3 x RBW
- 5. Detector = peak
- 6. Sweep time = auto couple
- 7. Trace mode = max hold
- 8. Allow trace to fully stabilize
- Emission level measurement
- 1. Set the center frequency and span to encompass frequency range to be measured
- 2. RBW = 100kHz
- 3. VBW = 300kHz
- 4. Detector = Peak
- 5. Trace mode = max hold
- 6. Sweep time = auto couple
- 7. The trace was allowed to stabilize

#### 10.3 Measurement Setup (Block Diagram of Configuration)








## 10.4 Measurement Results

## Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test\_Graph\_SRD 2.4G\_Chain A\_2402\_1Mbps\_Lower Band Emissions



0 Hz






Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test\_Graph\_SRD 2.4G\_Chain A\_2440\_Reference Level


#VBW 300 kHz


Span 3.000 MHz Sweep 2.000 ms (30000 pts)


Center 2.440000 GHz #Res BW 100 kHz














Freq Offset

Span 2.370 GHz

Sweep 228.0 ms (30000 pts)






Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Test Graph SRD 2.4G Chain A 2480 1Mbps Lower Band Emissions

#VBW 300 kHz


Center 1.215 GHz #Res BW 100 kHz
























**CF Step** 237.000000 MHz <u>to</u> Man

Freq Offset

<u>Auto</u>

Span 2.370 GHz

Sweep 228.0 ms (30000 pts)






Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Graph SRD 2.4G Chain B 2440 1Mbps Lower Band Emissions

#VBW 300 kHz

Center 1.215 GHz #Res BW 100 kHz




CF Step 300.000 kHz Man

Freq Offset 0 Hz

<u>Auto</u>

Span 3.000 MHz Sweep 2.000 ms (30000 pts)






Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Test Graph SRD 2.4G Chain B 2480 Reference Level


#VBW 300 kHz


Center 2.480000 GHz #Res BW 100 kHz



















Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands








Toot or april of the first of t



Freq Offset





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test\_Graph\_SRD 2.4G\_Chain B\_2480\_Higher Band Edge Emissions



Page 46 of 67

## 11. Radiated Spurious Emission

### 11.1 Measurement Limit

FCC Part 15.209 Limit in the below table to be followed

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

#### **11.2 Measurement Procedure**

- The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- The height of the broadband receiving antenna was varied between one meter and four meters above 3. ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds.



Page 47 of 67

- 8. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 9. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the guasi-peak method for below 1GHz.
- 10. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 11. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.

The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting		
Start ~Stop Frequency	9kHz~150kHz/RB 200Hz for QP		
Start ~Stop Frequency	150kHz~30MHz/RB 9kHz for QP		
Start ~Stop Frequency	30MHz~1000MHz/RB 120kHz for QP		
Start ~Stop Frequency	1GHz~26.5GHz 1MHz/3MHz for Peak, 1MHz/3MHz for Average		

Receiver Parameter	Setting
Start ~Stop Frequency	9kHz~150kHz/RB 200Hz for QP
Start ~Stop Frequency	150kHz~30MHz/RB 9kHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120kHz for QP



Page 48 of 67

#### Quasi-Peak Measurements below 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. Span was set greater than 1MHz
- 3. RBW = as shown in the table above
- 4. Detector = CISPR quasi-peak
- 5. Sweep time = auto couple
- 6. Trace was allowed to stabilize

#### Peak Measurements above 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW = 3MHz
- 4. Detector = peak
- 5. Sweep time = auto couple
- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize


#### Average Measurements above 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3.  $VBW \ge [3 \times RBW]$
- 4. Detector = Power averaging (rms)
- 5. Averaging type = power (i.e., rms)
- 6. Sweep time = auto
- 7. Perform a trace average of at least 100 traces.
- 8. The applicable correction factor is [10\*log (1 / D)], where D is the duty cycle. The factor had been edited in the "Input Correction" of the Spectrum Analyzer.




# 11.3 Measurement Setup (Block Diagram of Configuration)


Radiated Emission Test Setup 9kHz-30MHz



## Radiated Emission Test Setup 30MHz-1000MHz



#### Radiated Emission Test Setup Above 1000MHz





5

614.2142

863.0562

Report No.: AGC10232250201FR01


Page 50 of 67

#### 11.4 Measurement Result

#### **Radiated Emission Below 30MHz**

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.

Radiated Emission Test Results at 30MHz-1GHz						
EUT Name	PROFESSIONAL WIRELESS MICROPHONE SYSTEM	Model Name	RØDELINK II TRANSMITTER			
Temperature	17.8℃	Relative Humidity	51.2%			
Pressure	960hPa	Test Voltage	DC 3.7V by battery			
Test Mode	Mode 1	Antenna Polarity	Horizontal			



NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	45.5348	19.16	13.51	40.00	20.84	100	180	Horizontal
2	98.4866	21.41	15.97	43.50	22.09	100	110	Horizontal
3	191.7450	24.53	13.55	43.50	18.97	100	100	Horizontal
4	441 7426	31 29	25.04	46.00	14 71	100	230	Horizontal

46.00

46.00

14.38

7.55

100

100

180

190

Horizontal

Horizontal


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

31.62

38.45


25.17

29.13





Radiated Emission Test Results at 30MHz-1GHz						
EUT Name	PROFESSIONAL WIRELESS MICROPHONE SYSTEM	Model Name	RØDELINK II TRANSMITTER			
Temperature	17.8℃	Relative Humidity	51.2%			
Pressure	960hPa	Test Voltage	DC 3.7V by battery			
Test Mode	Mode 1	Antenna Polarity	Vertical			



Final I	Final Data List							
NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	32.0667	23.98	14.28	40.00	16.02	100	50	Vertical
2	63.9828	23.63	17.06	40.00	16.37	100	260	Vertical
3	128.1130	27.07	17.90	43.50	16.43	100	280	Vertical
4	191.7450	31.20	18.15	43.50	12.3	100	180	Vertical
5	440.1963	31.96	26.09	46.00	14.04	100	170	Vertical
6	863.0562	40.16	27.98	46.00	5.84	100	150	Vertical

### **RESULT: Pass**

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. All antenna and modes had been pre-tested. The antenna 2 mode 1 is the worst case and recorded in the report.



Page 52 of 67

### **Radiated Emissions Test Results for Above 1GHz**

EUT Name	PROFESSIONAL WIRELESS MICROPHONE SYSTEM	Model Name	RØDELINK II TRANSMITTER
Temperature	25℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 1	Antenna Polarity	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	
4804.000	49.63	0.08	49.71	74.00	-24.29	peak
4804.000	40.39	0.08	40.47	54.00	-13.53	AVG
7206.000	48.77	2.21	50.98	74.00	-23.02	peak
7206.000	40.52	2.21	42.73	54.00	-11.27	AVG
Dana and a				1		<u></u>

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

EUT Name	PROFESSIONAL WIRELESS MICROPHONE SYSTEM	Model Name	RØDELINK II TRANSMITTER
Temperature	25℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 1	Antenna Polarity	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Marg n	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	
4804.000	49.63	0.08	49.71	74.00	-24.29	peak
4804.000	40.26	0.08	40.34	54.00	-13.66	AVG
7206.000	48.96	2.21	51.17	74.00	-22.83	peak
7206.000	41.21	2.21	43.42	54.00	-10.58	AVG

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

### **RESULT: Pass**



Page 53 of 67

#### Radiated Emissions Test Results for Above 1GHz

EUT Name	PROFESSIONAL WIRELESS MICROPHONE SYSTEM	Model Name	RØDELINK II TRANSMITTER
Temperature	25℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 2	Antenna Polarity	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	
4880.000	49.59	0.08	49.67	74.00	-24.33	peak
4880.000	40.33	0.08	40.41	54.00	-13.59	AVG
7320.000	48.79	2.21	51.00	74.00	-23.00	peak
7320.000	40.31	2.21	42.52	54.00	-11.48	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT Name	PROFESSIONAL WIRELESS MICROPHONE SYSTEM	Model Name	RØDELINK II TRANSMITTER
Temperature	25℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 2	Antenna Polarity	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	
4880.000	50.11	0.08	50.19	74.00	-23.81	peak
4880.000	39.74	0.08	39.82	54.00	-14.18	AVG
7320.000	49.36	2.21	51.57	74.00	-22.43	peak
7320.000	39.52	2.21	41.73	54.00	-12.27	AVG
Pomark:	-			_		

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

# **RESULT: Pass**



Page 54 of 67

### **Radiated Emissions Test Results for Above 1GHz**

EUT Name	PROFESSIONAL WIRELESS MICROPHONE SYSTEM	Model Name	RØDELINK II TRANSMITTER
Temperature	25℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 3	Antenna Polarity	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	
4960.000	50.14	0.22	50.36	74.00	-23.64	peak
4960.000	40.57	0.22	40.79	54.00	-13.21	AVG
7440.000	49.96	2.64	52.6	74.00	-21.40	peak
7440.000	38.75	2.64	41.39	54.00	-12.61	AVG
D					l .	•

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

EUT Name	PROFESSIONAL WIRELESS MICROPHONE SYSTEM	Model Name	RØDELINK II TRANSMITTER
Temperature	25℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 3	Antenna Polarity	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	
4960.000	50.33	0.22	50.55	74.00	-23.45	peak
4960.000	39.79	0.22	40.01	54.00	-13.99	AVG
7440.000	49.61	2.64	52.25	74.00	-21.75	peak
7440.000	40.51	2.64	43.15	54.00	-10.85	AVG
Domorle						

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

### **RESULT: Pass**


#### Note:

- 1. The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.
- 2. Factor = Antenna Factor + Cable loss Pre-amplifier gain, Margin = Emission Level-Limit.
- 3. The "Factor" value can be calculated automatically by software of measurement system.




EUT Name	PROFESSIONAL WIRELESS MICROPHONE SYSTEM	Model Name	RØDELINK II TRANSMITTER
Temperature	25℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 1	Antenna Polarity	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement




### **RESULT: Pass**




EUT Name	PROFESSIONAL WIRELESS MICROPHONE SYSTEM	Model Name	RØDELINK II TRANSMITTER
Temperature	25℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 1	Antenna Polarity	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement




### **RESULT: Pass**




EUT Name	PROFESSIONAL WIRELESS MICROPHONE SYSTEM	Model Name	RØDELINK II TRANSMITTER
Temperature	25℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 3	Antenna Polarity	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement




### **RESULT: Pass**




EUT Name	PROFESSIONAL WIRELESS MICROPHONE SYSTEM	Model Name	RØDELINK II TRANSMITTER
Temperature	25℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 3	Antenna Polarity	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement




### **RESULT: Pass**



EUT Name	PROFESSIONAL WIRELESS MICROPHONE SYSTEM	Model Name	RØDELINK II TRANSMITTER
Temperature	25℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 1	Antenna Polarity	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement




### **RESULT: Pass**




EUT Name	PROFESSIONAL WIRELESS MICROPHONE SYSTEM	Model Name	RØDELINK II TRANSMITTER
Temperature	25℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 1	Antenna Polarity	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement




### **RESULT: Pass**




EUT Name	PROFESSIONAL WIRELESS MICROPHONE SYSTEM	Model Name	RØDELINK II TRANSMITTER
Temperature	25℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 3	Antenna Polarity	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement




### **RESULT: Pass**




EUT Name	PROFESSIONAL WIRELESS MICROPHONE SYSTEM	Model Name	RØDELINK II TRANSMITTER
Temperature	25℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 3	Antenna Polarity	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement



#### **RESULT: Pass**

Note: The factor had been edited in the "Input Correction" of the Spectrum Analyzer.



### 12. AC Power Line Conducted Emission Test


#### 12.1 Measurement Limit

F	Maximum RF Line Voltage						
Frequency	Q.P. (dBµV)	Average (dBμV)					
150kHz~500kHz	66-56	56-46					
500kHz~5MHz	56	46					
5MHz~30MHz	60	50					

#### Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

# 12.2 Measurement Setup (Block Diagram of Configuration)





Page 64 of 67

### 12.3 Preliminary Procedure of Line Conducted Emission Test

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

#### 12.4 Final Procedure of Line Conducted Emission Test

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.
- 4. AC Conducted emission is calculated by the following equation:
  - Measurement-Level(dBµV)=Receiver reading(dBµV)+Transd (dB)
  - Transd (dB)=AMN Factor(dB)+Cable Loss(dB)+Attenuation(dB)
  - Margin= Limit-Level



#### 12.5 Measurement Results

est Mode	N	1ode 1									LI	SN	Li	ne				Hot s	Side	
-	evel [	dΒμV]									•									
80	r																		. – – –	
70	L		<u>.</u>		 	 	:-			-¦					¦	 				;
60			į.	<u> </u>	<u>.</u>	-	_ i_	i i		_i	i	i		<u> </u>	<u> </u>	ij	<u> </u>		i	i
50		+			-		-	1 1		1	- 1			1	1	 			-	
	[							1-1		!					!	!!	!!		- !	
40			- <del></del>				-			-				·		1	- + -!			
30	~~	~~~~	<u>۱</u>	-	, m			أسأر	March March	-; •!-	;			; 	i	((·	- <del> </del> -   -			·
20			<del>~~</del> *	~~~	~~		~~i~	+	and the second s	ΙX	Mary dist	4	lije,		di Jes	1 — — I		хх	ullu a se	- 1
10				·	<u> </u>						-		-		1	1 1		-		
0		- <del>-</del>	·	·	<del>-</del>	ii	<del> -</del> -	-i-i-			j	·i·		<u>-</u>	i	i – –i	- +			
-10	150k	3	00k	400k	60	0k	8001	C 1N	1	2M	3M	41	1 5	M 6	M	81	1 10M		20M	30M
	1001		OUN	400K		OI.	0001			uency [						011			2011	30111

# MEASUREMENT RESULT: "agc\_fin"

2025/2/8 2	1:28					
Frequenc MH	-	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.34600	0 20.60	6.1	59	38.5	QP	L1
0.59000	0 19.40	6.2	56	36.6	QP	L1
1.31000	0 20.70	6.2	56	35.3	QP	L1
2.13400	0 15.60	6.2	56	40.4	QP	L1
12.40200	0 14.90	6.8	60	45.1	QP	L1
13.97400	0 15.20	6.8	60	44.8	OP	L1

# MEASUREMENT RESULT: "agc fin2"


2025/2/8 2 Frequence Mi			Limit dBµV	Margin dB	Detector	Line
0.3580			49 46	32.2 24.6		L1 L1
1.29000	00 15.70	6.2	46	30.3	AV	L1
2.13400	00 10.90	6.2	46	35.1	AV	L1
12.24200 13.85400			50 50	41.6 40.9	AV AV	L1 L1

#### **RESULT: Pass**

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/





# MEASUREMENT RESULT: "agc\_fin2"

2025/2/8 21:35 Frequency Level Transd Limit Margin Detector Line dΒμV MHzdΒμ∇ dΒ dΒ 0.362000 16.60 6.1 49 32.1 ΑV Ν 0.550000 16.00 6.2 46 30.0 ΑV Ν 0.942000 15.30 6.2 46 30.7 ΑV Ν 2.230000 10.70 6.3 46 35.3 ΑV Ν 12.074000 7.50 6.8 50 42.5 ΑV Ν 13.954000 9.60 6.8 50 40.4 ΑV

### **RESULT: PASS**



Page 67 of 67

Appendix I: Photographs of Test Setup

Refer to the Report No.: AGC10232250201AP01

**Appendix II: Photographs of Test EUT** 

Refer to the Report No.: AGC10232250201AP02

----End of Report----



# Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.