

Supplemental “Transmit Simultaneously” Test Report

Report No.: RF191227E09-2

FCC ID: 2AF5PMH7021

Test Model: MH7021

Series Model: MH702XY (where X can be 0, 1, 2, 3, or 4, and Y can be A, B, C, D or blank)

Received Date: Dec. 27, 2019

Test Date: Feb. 11 to 13, 2020

Issued Date: Mar. 11, 2020

Applicant: MTRLC LLC

Address: 225 Franklin St. 26th Floor Boston, MA 02110

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwa.

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan.

**FCC Registration /
Designation Number:** 723255 / TW2022



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

| | |
|--|-----------|
| Release Control Record | 3 |
| 1 Certificate of Conformity | 4 |
| 2 Summary of Test Results | 5 |
| 2.1 Measurement Uncertainty | 5 |
| 2.2 Modification Record | 5 |
| 3 General Information | 6 |
| 3.1 General Description of EUT | 6 |
| 3.1.1 Test Mode Applicability and Tested Channel Detail | 8 |
| 3.2 Description of Support Units | 10 |
| 3.2.1 Configuration of System under Test | 11 |
| 4 Test Types and Results | 12 |
| 4.1 Radiated Emission and Bandedge Measurement | 12 |
| 4.1.1 Limits of Radiated Emission and Bandedge Measurement | 12 |
| 4.1.2 Test Instruments | 13 |
| 4.1.3 Test Procedures | 14 |
| 4.1.4 Deviation from Test Standard | 14 |
| 4.1.5 Test Setup | 15 |
| 4.1.6 EUT Operating Conditions | 16 |
| 4.1.7 Test Results | 17 |
| 4.2 Conducted Emission Measurement | 20 |
| 4.2.1 Limits of Conducted Emission Measurement | 20 |
| 4.2.2 Test Instruments | 20 |
| 4.2.3 Test Procedures | 21 |
| 4.2.4 Deviation from Test Standard | 21 |
| 4.2.5 Test Setup | 21 |
| 4.2.6 EUT Operating Conditions | 21 |
| 4.2.7 Test Results | 22 |
| 4.3 Conducted Out of Band Emission Measurement | 24 |
| 4.3.1 Limits of Conducted Out of Band Emission Measurement | 24 |
| 4.3.2 Test Setup | 24 |
| 4.3.3 Test Instruments | 24 |
| 4.3.4 Test Procedures | 24 |
| 4.3.5 Deviation from Test Standard | 24 |
| 4.3.6 EUT Operating Conditions | 24 |
| 4.3.7 Test Results | 24 |
| 5 Pictures of Test Arrangements | 26 |
| Appendix – Information of the Testing Laboratories | 27 |

Release Control Record

| Issue No. | Description | Date Issued |
|---------------|-------------------|---------------|
| RF191227E09-2 | Original release. | Mar. 11, 2020 |

1 Certificate of Conformity

Product: AC2200 Tri-band Mesh WiFi

Brand: Motorola

Test Model: MH7021

Series Model: MH702XY (where X can be 0, 1, 2, 3, or 4, and Y can be A, B, C, D or blank)

Sample Status: ENGINEERING SAMPLE

Applicant: MTRLC LLC

Test Date: Feb. 11 to 13, 2020

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)
47 CFR FCC Part 15, Subpart E (Section 15.407)
ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Vivian Huang , **Date:** Mar. 11, 2020
Vivian Huang / Specialist

Approved by : Clark Lin , **Date:** Mar. 11, 2020
Clark Lin / Technical Manager

2 Summary of Test Results

| FCC Part 15, Subpart C, E (SECTION 15.247, 15.407) | | | |
|--|--|--------|---|
| FCC Clause | Test Item | Result | Remarks |
| 15.207 15.407(b)(6) | AC Power Conducted Emission | PASS | Meet the requirement of limit. Minimum passing margin is -30.31 dB at 0.37656 MHz. |
| 15.205 / 15.209 / 15.247(d) 15.407(b) (1/2/3/4(i/ii)/6) | Radiated Emissions and Band Edge Measurement | PASS | Meet the requirement of limit. Minimum passing margin is -5.2 dB at 40.02 MHz. |

Note:

Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| Measurement | Frequency | Expanded Uncertainty (k=2) (\pm) |
|------------------------------------|----------------|--------------------------------------|
| Conducted Emissions at mains ports | 150kHz ~ 30MHz | 1.8 dB |
| Radiated Emissions up to 1 GHz | 9kHz ~ 30MHz | 3.0 dB |
| | 30MHz ~ 1GHz | 5.1 dB |
| Radiated Emissions above 1 GHz | 1GHz ~ 6GHz | 5.1 dB |
| | 6GHz ~ 18GHz | 5.0 dB |
| | 18GHz ~ 40GHz | 5.2 dB |

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

| | |
|-----------------------|--|
| Product | AC2200 Tri-band Mesh WiFi |
| Brand | Motorola |
| Test Model | MH7021 |
| Series Model | MH702XY (where X can be 0, 1, 2, 3, or 4, and Y can be A, B, C, D or blank) |
| Status of EUT | ENGINEERING SAMPLE |
| Power Supply Rating | 12Vdc from power adapter |
| Modulation Type | CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM 256QAM for OFDM in 11ac mode and VHT20/40 in 2.4GHz |
| Modulation Technology | DSSS, OFDM |
| Operating Frequency | 2.4GHz: 2.412 ~ 2.462GHz 5GHz: 5.18 ~ 5.24GHz, 5.745 ~5.825GHz |
| Antenna Type | Refer to Note |
| Antenna Connector | Refer to Note |
| Accessory Device | Adapter x1 |
| Data Cable Supplied | NA |

Note:

1. The EUT has below radios as following table:

| Radio 1 | Radio 2 |
|-------------------------------|----------------|
| WLAN (2.4GHz) +WLAN (5GHz LB) | WLAN (5GHz HB) |

2. Simultaneously transmission condition.

| Condition | Technology | | |
|--|---------------|----------------|----------------|
| 1 | WLAN (2.4GHz) | WLAN (5GHz LB) | WLAN (5GHz HB) |
| Note: The emission of the simultaneous operation has been evaluated and no non-compliance was found. | | | |

3. The EUT has following model names, which are identical to each other in all aspects except for the following information:

| Brand Name | Model Name | Difference |
|------------|---|---|
| Motorola | MH7021 | MH7021 x 1, black and white |
| | MH702XY (where X can be 0, 1, 2, 3, or 4, and Y can be A, B, C, D or blank) | for identical hardware for marketing purposes |

From the above models, model: MH7021 was selected as representative model for the test and its data are recorded in this report.

4. The EUT power needs to be supplied from a power adapters, the information is as below table:

| No. | Brand | Model No. | Spec. |
|-----|---------------------------------------|-------------------|--|
| 1 | Shenzhen Gongjin Electronics Co., Ltd | S24B72-120A200-0K | Input: 100-240Vac, 0.8A, 50/60Hz Output: 12Vdc, 2A DC Output cable: Unshielded, 1.5m |

5. The antennas provided to the EUT, please refer to the following table:

| Antenna No | Brand | Antenna Gain (dBi) | Frequency range (GHz) | Antenna Type | Connector Type | *Cable Length (mm) | Cable Loss (dB) |
|---------------------|-------------------------------|--------------------|-----------------------|--------------|----------------|--------------------|-----------------|
| ANT 1 (2.4GHz/5GHz) | WALSIN TECHNOLOGY CORPORATION | 2.88 | 2.4~2.5 | PCB | I-pex | 85±3 | 0.23 |
| | | 4.31 | 5.15~5.85 | | | | 0.36 |
| ANT 2 (2.4GHz/5GHz) | | 3 | 2.4~2.5 | PCB | I-pex | 125±3 | 0.31 |
| | | 5.27 | 5.15~5.85 | | | | 0.5 |
| ANT 3(5GHz) | | 5.19 | 5.15~5.85 | METAL TUBE | I-pex | 110±3 | 0.47 |
| ANT 4(5GHz) | | 5.37 | 5.15~5.85 | METAL TUBE | I-pex | 110±3 | 0.47 |

6. The EUT incorporates a MIMO function:

| 2.4GHz Band | | |
|------------------|-----------------------|-----|
| MODULATION MODE | TX & RX CONFIGURATION | |
| 802.11b | 2TX | 2RX |
| 802.11g | 2TX | 2RX |
| 802.11n (HT20) | 2TX | 2RX |
| 802.11n (HT40) | 2TX | 2RX |
| VHT20 | 2TX | 2RX |
| VHT40 | 2TX | 2RX |
| 5GHz Band | | |
| MODULATION MODE | TX & RX CONFIGURATION | |
| 802.11a | 2TX | 2RX |
| 802.11n (HT20) | 2TX | 2RX |
| 802.11n (HT40) | 2TX | 2RX |
| 802.11ac (VHT20) | 2TX | 2RX |
| 802.11ac (VHT40) | 2TX | 2RX |
| 802.11ac (VHT80) | 2TX | 2RX |

Note:

- All of modulation mode support beamforming function except 802.11a/b/g modulation mode.
- The EUT support Beamforming and CDD mode, therefore both mode were investigated and the worst case scenario was identified. The worst case data were presented in test report.

7. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.

3.1.1 Test Mode Applicability and Tested Channel Detail

| EUT Configure Mode | Applicable To | | | | Description |
|--------------------|---------------|-------|-----|----|-------------|
| | RE \geq 1G | RE<1G | PLC | OB | |
| - | √ | √ | √ | √ | - |

Where **RE \geq 1G**: Radiated Emission above 1GHz
RE<1G: Radiated Emission below 1GHz
PLC: Power Line Conducted Emission
OB: Conducted Out-Band Emission Measurement

Radiated Emission Test (Above 1GHz):

- ☒ The tested configurations represent the worst-case mode from all possible combinations by the maximum power.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| MODE | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE |
|---|-------------------|----------------|-----------------------|-----------------|
| 802.11b + 802.11ac (VHT20) + 802.11ac (VHT40) | 1 to 11 | 6 | DSSS | DBPSK |
| | 36 to 48 | 48 | OFDM | BPSK |
| | 151 to 159 | 159 | OFDM | BPSK |

Radiated Emission Test (Below 1GHz):

- ☒ The tested configurations represent the worst-case mode from all possible combinations by the maximum power.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| MODE | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE |
|---|-------------------|----------------|-----------------------|-----------------|
| 802.11b + 802.11ac (VHT20) + 802.11ac (VHT40) | 1 to 11 | 6 | DSSS | DBPSK |
| | 36 to 48 | 48 | OFDM | BPSK |
| | 151 to 159 | 159 | OFDM | BPSK |

Power Line Conducted Emission Test:

- ☒ The tested configurations represent the worst-case mode from all possible combinations by the maximum power.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| MODE | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE |
|---|-------------------|----------------|-----------------------|-----------------|
| 802.11b + 802.11ac (VHT20) + 802.11ac (VHT40) | 1 to 11 | 6 | DSSS | DBPSK |
| | 36 to 48 | 48 | OFDM | BPSK |
| | 151 to 159 | 159 | OFDM | BPSK |

Conducted Out-Band Emission Measurement:

- ☒ The tested configurations represent the worst-case mode from all possible combinations by the maximum power.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| MODE | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE |
|----------------------------------|-------------------|----------------|-----------------------|-----------------|
| 802.11b + 802.11ac (VHT20) | 1 to 11 | 6 | DSSS | DBPSK |
| | 36 to 48 | 48 | OFDM | BPSK |

Test Condition:

| Applicable To | Environmental Conditions | Input Power | Tested By |
|---------------|--------------------------|--------------|--------------|
| RE \geq 1G | 25deg. C, 75%RH | 120Vac, 60Hz | Nelson Teng |
| RE<1G | 23deg. C, 67%RH | 120Vac, 60Hz | Kevin Ko |
| PLC | 25deg. C, 75%RH | 120Vac, 60Hz | Kevin Ko |
| OB | 25deg. C, 60%RH | 120Vac, 60Hz | Robert Cheng |

3.2 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


| ID | Product | Brand | Model No. | Serial No. | FCC ID | Remarks |
|----|---------|-------|-----------|------------|---------|-----------------|
| A. | Laptop | DELL | E5430 | HYV4VY1 | FCC DoC | Provided by Lab |
| B. | Laptop | DELL | E5430 | 4N1SKV1 | FCC DoC | Provided by Lab |

Note:

1. All power cords of the above support units are non-shielded (1.8m).

| ID | Descriptions | Qty. | Length (m) | Shielding (Yes/No) | Cores (Qty.) | Remarks |
|----|--------------|------|------------|--------------------|--------------|--------------------|
| 1. | RJ-45 Cable | 1 | 10 | No | 0 | Provided by Lab |
| 2. | DC Cable | 1 | 1.5 | No | 0 | Supplied by client |
| 3. | RJ-45 Cable | 1 | 10 | No | 0 | Provided by Lab |

3.2.1 Configuration of System under Test



4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table.

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009 ~ 0.490 | 2400/F(kHz) | 300 |
| 0.490 ~ 1.705 | 24000/F(kHz) | 30 |
| 1.705 ~ 30.0 | 30 | 30 |
| 30 ~ 88 | 100 | 3 |
| 88 ~ 216 | 150 | 3 |
| 216 ~ 960 | 200 | 3 |
| Above 960 | 500 | 3 |

Note:

- The lower limit shall apply at the transition frequencies.
- Emission level (dBuV/m) = 20 log Emission level (uV/m).
- For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Limits of unwanted emission out of the restricted bands

| Applicable To | | Limit | |
|---|-----------------|---|---|
| 789033 D02 General UNII Test Procedure New Rules v02r01 | | Field Strength at 3m | |
| | | PK:74 (dBuV/m) | AV:54 (dBuV/m) |
| Frequency Band | Applicable To | EIRP Limit | Equivalent Field Strength at 3m |
| 5150~5250 MHz | 15.407(b)(1) | PK:-27 (dBm/MHz) | PK:68.2(dBuV/m) |
| 5250~5350 MHz | 15.407(b)(2) | | |
| 5470~5725 MHz | 15.407(b)(3) | | |
| 5725~5850 MHz | 15.407(b)(4)(i) | PK:-27 (dBm/MHz) ^{*1} PK:10 (dBm/MHz) ^{*2} PK:15.6 (dBm/MHz) ^{*3} PK:27 (dBm/MHz) ^{*4} | PK: 68.2(dBuV/m) ^{*1} PK:105.2 (dBuV/m) ^{*2} PK: 110.8(dBuV/m) ^{*3} PK:122.2 (dBuV/m) ^{*4} |
| ^{*1} beyond 75 MHz or more above of the band edge. ^{*2} below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above. ^{*3} below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above. ^{*4} from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge. | | | |

Note:

The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts).}$$

4.1.2 Test Instruments

| DESCRIPTION & MANUFACTURER | MODEL NO. | SERIAL NO. | CALIBRATED DATE | CALIBRATED UNTIL |
|--------------------------------------|----------------------|-------------|-----------------|------------------|
| Test Receiver Keysight | N9038A | MY54450088 | July 03, 2019 | July 02, 2020 |
| Pre-Amplifier EMCi | EMC001340 | 980142 | May 30, 2019 | May 29, 2020 |
| Loop Antenna Electro-Metrics | EM-6879 | 269 | Sep. 16, 2019 | Sep. 15, 2020 |
| RF Cable | NA | LOOPCAB-001 | Jan. 08, 2020 | Jan. 07, 2021 |
| RF Cable | NA | LOOPCAB-002 | Jan. 08, 2020 | Jan. 07, 2021 |
| Pre-Amplifier Mini-Circuits | ZFL-1000VH2B | AMP-ZFL-05 | Apr. 30, 2019 | Apr. 29, 2020 |
| Trilog Broadband Antenna SCHWARZBECK | VULB 9168 | 9168-361 | Nov. 11, 2019 | Nov. 10, 2020 |
| RF Cable | 8D | 966-3-1 | Mar. 18, 2019 | Mar. 17, 2020 |
| RF Cable | 8D | 966-3-2 | Mar. 18, 2019 | Mar. 17, 2020 |
| RF Cable | 8D | 966-3-3 | Mar. 18, 2019 | Mar. 17, 2020 |
| Fixed attenuator Mini-Circuits | UNAT-5+ | PAD-3m-3-01 | Sep. 26, 2019 | Sep. 25, 2020 |
| Horn_Antenna SCHWARZBECK | BBHA9120-D | 9120D-406 | Nov. 24, 2019 | Nov. 23, 2020 |
| Pre-Amplifier EMCi | EMC12630SE | 980384 | Jan. 15, 2020 | Jan. 14, 2021 |
| RF Cable | EMC104-SM-SM-1200 | 160922 | Jan. 15, 2020 | Jan. 14, 2021 |
| RF Cable | EMC104-SM-SM-2000 | 180601 | June 10, 2019 | June 09, 2020 |
| RF Cable | EMC104-SM-SM-6000 | 180602 | June 10, 2019 | June 09, 2020 |
| Spectrum Analyzer Keysight | N9030A | MY54490679 | July 17, 2019 | July 16, 2020 |
| Pre-Amplifier EMCi | EMC184045SE | 980387 | Jan. 15, 2020 | Jan. 14, 2021 |
| Horn_Antenna SCHWARZBECK | BBHA 9170 | BBHA9170519 | Nov. 24, 2019 | Nov. 23, 2020 |
| RF Cable | EMC102-KM-KM-1200 | 160924 | Jan. 15, 2020 | Jan. 14, 2021 |
| RF Cable | EMC102-KM-KM-4500 | 181205 | Aug. 26, 2019 | Aug. 25, 2020 |
| Software | ADT_Radiated_V8.7.08 | NA | NA | NA |
| Antenna Tower & Turn Table Max-Full | MF-7802 | MF780208406 | NA | NA |
| Boresight Antenna Fixture | FBA-01 | FBA-SIP01 | NA | NA |

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in 966 Chamber No. 3.
3. Loop antenna was used for all emissions below 30 MHz.
4. Tested Date: Feb. 12, 2020

4.1.3 Test Procedures

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- Placed the EUT on the testing table.
- Controlling software (QRCT_V 3.0-00264) has been activated to set the EUT under transmission condition continuously at specific channel frequency.

4.1.7 Test Results

Above 1GHz Data:

| | | | |
|------------------------|--------------|--------------------------|---------------------------|
| FREQUENCY RANGE | 1GHz ~ 40GHz | DETECTOR FUNCTION | Peak (PK) Average (AV) |
|------------------------|--------------|--------------------------|---------------------------|

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | | | | | | |
|---|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 4874.00 | 41.3 PK | 74.0 | -32.7 | 1.78 H | 125 | 39.2 | 2.1 |
| 2 | 4874.00 | 34.3 AV | 54.0 | -19.7 | 1.78 H | 125 | 32.2 | 2.1 |
| 3 | 7311.00 | 42.1 PK | 74.0 | -31.9 | 1.18 H | 294 | 34.0 | 8.1 |
| 4 | 7311.00 | 31.0 AV | 54.0 | -23.0 | 1.18 H | 294 | 22.9 | 8.1 |
| 5 | #10480.00 | 48.3 PK | 68.2 | -19.9 | 1.68 H | 222 | 35.8 | 12.5 |
| 6 | 11590.00 | 48.8 PK | 74.0 | -25.2 | 1.69 H | 82 | 36.5 | 12.3 |
| 7 | 11590.00 | 38.0 AV | 54.0 | -16.0 | 1.69 H | 82 | 25.7 | 12.3 |
| 8 | 15720.00 | 46.3 PK | 74.0 | -27.7 | 1.25 H | 360 | 34.1 | 12.2 |
| 9 | 15720.00 | 40.3 AV | 54.0 | -13.7 | 1.25 H | 360 | 28.1 | 12.2 |
| 10 | #17385.00 | 49.4 PK | 68.2 | -18.8 | 3.21 H | 278 | 32.9 | 16.5 |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | | | | | | |
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 4874.00 | 41.6 PK | 74.0 | -32.4 | 1.03 V | 208 | 39.5 | 2.1 |
| 2 | 4874.00 | 37.5 AV | 54.0 | -16.5 | 1.03 V | 208 | 35.4 | 2.1 |
| 3 | 7311.00 | 42.0 PK | 74.0 | -32.0 | 1.00 V | 161 | 33.9 | 8.1 |
| 4 | 7311.00 | 31.6 AV | 54.0 | -22.4 | 1.00 V | 161 | 23.5 | 8.1 |
| 5 | #10480.00 | 47.6 PK | 68.2 | -20.6 | 2.11 V | 200 | 35.1 | 12.5 |
| 6 | 11590.00 | 46.4 PK | 74.0 | -27.6 | 3.65 V | 258 | 34.1 | 12.3 |
| 7 | 11590.00 | 38.6 AV | 54.0 | -15.4 | 3.65 V | 258 | 26.3 | 12.3 |
| 8 | 15720.00 | 47.9 PK | 74.0 | -26.1 | 1.03 V | 215 | 35.7 | 12.2 |
| 9 | 15720.00 | 43.2 AV | 54.0 | -10.8 | 1.03 V | 215 | 31.0 | 12.2 |
| 10 | #17385.00 | 48.5 PK | 68.2 | -19.7 | 2.62 V | 142 | 32.0 | 16.5 |

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value


Below 1GHz Data:

| | | | |
|------------------------|-------------|--------------------------|-----------------|
| FREQUENCY RANGE | 9kHz ~ 1GHz | DETECTOR FUNCTION | Quasi-Peak (QP) |
|------------------------|-------------|--------------------------|-----------------|

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | | | | | | |
|---|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 40.02 | 34.8 QP | 40.0 | -5.2 | 1.00 H | 194 | 43.0 | -8.2 |
| 2 | 96.20 | 34.3 QP | 43.5 | -9.2 | 2.00 H | 349 | 46.7 | -12.4 |
| 3 | 159.91 | 29.6 QP | 43.5 | -13.9 | 1.50 H | 118 | 36.8 | -7.2 |
| 4 | 332.98 | 29.6 QP | 46.0 | -16.4 | 1.50 H | 218 | 34.9 | -5.3 |
| 5 | 495.60 | 31.7 QP | 46.0 | -14.3 | 1.00 H | 176 | 33.3 | -1.6 |
| 6 | 659.77 | 34.1 QP | 46.0 | -11.9 | 1.50 H | 256 | 32.3 | 1.8 |

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




| | | | |
|------------------------|-------------|--------------------------|-----------------|
| FREQUENCY RANGE | 9kHz ~ 1GHz | DETECTOR FUNCTION | Quasi-Peak (QP) |
|------------------------|-------------|--------------------------|-----------------|

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | | | | | | |
|---|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 38.08 | 33.6 QP | 40.0 | -6.4 | 1.50 V | 0 | 41.8 | -8.2 |
| 2 | 147.78 | 30.3 QP | 43.5 | -13.2 | 1.00 V | 360 | 37.4 | -7.1 |
| 3 | 369.40 | 29.7 QP | 46.0 | -16.3 | 1.00 V | 192 | 34.3 | -4.6 |
| 4 | 515.58 | 31.8 QP | 46.0 | -14.2 | 1.50 V | 208 | 32.9 | -1.1 |
| 5 | 639.72 | 34.0 QP | 46.0 | -12.0 | 1.00 V | 324 | 32.3 | 1.7 |
| 6 | 703.86 | 35.3 QP | 46.0 | -10.7 | 1.00 V | 360 | 32.7 | 2.6 |

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

| Frequency (MHz) | Conducted Limit (dBuV) | |
|-----------------|------------------------|---------|
| | Quasi-peak | Average |
| 0.15 - 0.5 | 66 - 56 | 56 - 46 |
| 0.50 - 5.0 | 56 | 46 |
| 5.0 - 30.0 | 60 | 50 |

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

| DESCRIPTION & MANUFACTURER | MODEL NO. | SERIAL NO. | CALIBRATED DATE | CALIBRATED UNTIL |
|--|-------------------------|------------|-----------------|------------------|
| Test Receiver R&S | ESCS 30 | 847124/029 | Oct. 23, 2019 | Oct. 22, 2020 |
| Line-Impedance Stabilization Network (for EUT) R&S | ESH3-Z5 | 848773/004 | Oct. 23, 2019 | Oct. 22, 2020 |
| Line-Impedance Stabilization Network (for Peripheral) R&S | ESH3-Z5 | 835239/001 | Mar. 17, 2019 | Mar. 16, 2020 |
| 50 ohms Terminator | 50 | 3 | Oct. 23, 2019 | Oct. 22, 2020 |
| RF Cable | 5D-FB | COCCAB-001 | Sep. 27, 2019 | Sep. 26, 2020 |
| Fixed attenuator EMCI | STI02-2200-10 | 003 | Mar. 14, 2019 | Mar. 13, 2020 |
| Software BVADT | BVADT_Cond_ V7.3.7.4 | NA | NA | NA |

Note:

1. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Conduction 1.
- 3 Tested Date: Feb. 11, 2020

4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Conditions

Same as 4.1.6.


4.2.7 Test Results

| Phase | Line (L) | Detector Function | Quasi-Peak (QP) / Average (AV) |
|-------|----------|-------------------|--------------------------------|
|-------|----------|-------------------|--------------------------------|

| Phase Of Power : Line (L) | | | | | | | | | | |
|---------------------------|-----------------|------------------------|----------------------|--------|-----------------------|-------|--------------|-------|-------------|--------|
| No | Frequency (MHz) | Correction Factor (dB) | Reading Value (dBuV) | | Emission Level (dBuV) | | Limit (dBuV) | | Margin (dB) | |
| | | | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. |
| 1 | 0.15781 | 9.99 | 16.67 | -2.07 | 26.66 | 7.92 | 65.58 | 55.58 | -38.92 | -47.66 |
| 2 | 0.18906 | 9.99 | 18.15 | -9.64 | 28.14 | 0.35 | 64.08 | 54.08 | -35.94 | -53.73 |
| 3 | 0.37656 | 10.00 | 11.85 | -11.23 | 21.85 | -1.23 | 58.35 | 48.35 | -36.50 | -49.58 |
| 4 | 6.66016 | 10.43 | 12.84 | -10.11 | 23.27 | 0.32 | 60.00 | 50.00 | -36.73 | -49.68 |
| 5 | 8.18359 | 10.53 | 13.27 | -10.34 | 23.80 | 0.19 | 60.00 | 50.00 | -36.20 | -49.81 |
| 6 | 10.27344 | 10.67 | 13.41 | -9.62 | 24.08 | 1.05 | 60.00 | 50.00 | -35.92 | -48.95 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




| | | | |
|-------|-------------|-------------------|--------------------------------|
| Phase | Neutral (N) | Detector Function | Quasi-Peak (QP) / Average (AV) |
|-------|-------------|-------------------|--------------------------------|

| Phase Of Power : Neutral (N) | | | | | | | | | | |
|------------------------------|-----------------|------------------------|----------------------|--------------|-----------------------|-------------|--------------|--------------|---------------|---------------|
| No | Frequency (MHz) | Correction Factor (dB) | Reading Value (dBuV) | | Emission Level (dBuV) | | Limit (dBuV) | | Margin (dB) | |
| | | | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. |
| 1 | 0.15000 | 9.99 | 15.74 | -3.77 | 25.73 | 6.22 | 66.00 | 56.00 | -40.27 | -49.78 |
| 2 | 0.22031 | 9.99 | 15.78 | -8.90 | 25.77 | 1.09 | 62.81 | 52.81 | -37.04 | -51.72 |
| 3 | 0.37656 | 10.01 | 18.03 | -8.49 | 28.04 | 1.52 | 58.35 | 48.35 | -30.31 | -46.83 |
| 4 | 6.33984 | 10.36 | 10.60 | -10.73 | 20.96 | -0.37 | 60.00 | 50.00 | -39.04 | -50.37 |
| 5 | 9.03906 | 10.52 | 13.48 | -10.17 | 24.00 | 0.35 | 60.00 | 50.00 | -36.00 | -49.65 |
| 6 | 11.69531 | 10.67 | 12.15 | -10.37 | 22.82 | 0.30 | 60.00 | 50.00 | -37.18 | -49.70 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




4.3 Conducted Out of Band Emission Measurement

4.3.1 Limits of Conducted Out of Band Emission Measurement

Below 30dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedures

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW \geq 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW \geq 300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

4.3.5 Deviation from Test Standard

No deviation.


4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.

4.3.7 Test Results

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 30dB offset below D1. It shows compliance with the requirement.

2.4GHz_802.11b CH6 + 5GHz_802.11ac (VHT20) CH48



5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---