

TEST REPORT

Report Number: 15605547-E2V2

- Applicant : SAMSUNG ELECTRONICS CO., LTD. 129 SAMSUNG-RO, YEONGTONG-GU SUWON-SI, GYEONGGI-DO, 16677, KOREA
 - Model : SM-X620
 - FCC ID : A3LSMX620
 - IC : 649E-SMX620
- **EUT Description** : BT/BLE Tablet + DTS/UNII a/b/g/n/ac/ax and Digitizer
- Test Standard(s) : FCC 47 CFR PART 15 SUBPART C ISED RSS-247 ISSUE 3 ISED RSS-GEN ISSUE 5 + A1 + A2

Date Of Issue: 2025-03-03

Prepared by: UL VERIFICATION SERVICES INC. 47173 Benicia Street Fremont, CA 94538 U.S.A. TEL: (510) 319-4000 FAX: (510) 661-0888



.

REVISION HISTORY

Rev.	Date	Revisions	Revised By
V1	2025-02-25	Initial Issue	
V2	2025-03-03	Section 9.5.3 & .4 updated Section 10.4 Updated	Henry Lau

Page 2 of 78

TABLE OF CONTENTS

TABLE OF CONTENTS 3 1. ATTESTATION OF TEST RESULTS. 5 2. TEST RESULTS SUMMARY 7 3. TEST METHODOLOGY 7 4. FACILITIES AND ACCREDITATION 7 5. DECISION RULES AND MEASUREMENT UNCERTAINTY. 8 5.1. METROLOGICAL TRACEABILITY 8 5.2. DECISION RULES 8 5.3. MEASUREMENT UNCERTAINTY 8 5.4. SAMPLE CALCULATION 9 6. EQUIPMENT UNDER TEST 10 6.1. EUT DESCRIPTION 10 6.2. MAXIMUM OUTPUT POWER 10 6.3. DESCRIPTION OF AVAILABLE ANTENNAS AND CABLE LOSS 10 6.4. WORST-CASE CONFIGURATION AND MODE 10 6.5. DESCRIPTION OF TEST SETUP 11 7. TEST AND MEASUREMENT EQUIPMENT 14 8. MEASUREMENT METHOD 15 9. ANTENNA PORT TEST RESULTS 16 9.1. ON TIME AND DUTY CYCLE 16 9.2. 99% BANDWIDTH 18 9.2.1. BLE (125kbps) 22 9.3. 6 dB BANDWIDTH 22 9.3. 6 LE (1Mbps) 23 9.2.4. BLE (20kbps) 23 9.3. 6 LE (1Mbps) 23	REVIS	ON HISTORY	2
1. ATTESTATION OF TEST RESULTS. 5 2. TEST RESULTS SUMMARY 7 3. TEST METHODOLOGY 7 4. FACILITIES AND ACCREDITATION 7 5. DECISION RULES AND MEASUREMENT UNCERTAINTY 8 5.1. METROLOGICAL TRACEABILITY 8 5.2. DECISION RULES 8 5.3. MEASUREMENT UNCERTAINTY 8 5.4. SAMPLE CALCULATION 9 6. EQUIPMENT UNDER TEST 10 6.1. EUT DESCRIPTION 10 6.2. MAXIMUM OUTPUT POWER 10 6.3. DESCRIPTION OF AVAILABLE ANTENNAS AND CABLE LOSS 10 6.4. WORST-CASE CONFIGURATION AND MODE 10 6.5. DESCRIPTION OF TEST SETUP. 11 7. TEST AND MEASUREMENT EQUIPMENT 14 8. MEASUREMENT METHOD 15 9. ANTENNA PORT TEST RESULTS 16 9.1. ON TIME AND DUTY CYCLE 16 9.2. 99% BANDWIDTH 18 9.2.1. BLE (125kbps) 22 9.3. 6 dB BANDWIDTH 22 9.3. BLE (1Mbps) 22 9.3. BLE (1Mbps) 23 9.3. BLE (1Mbps) 24 9.3. BLE (1Mbps) 24 </th <th>TABLE</th> <th>OF CONTENTS</th> <th>3</th>	TABLE	OF CONTENTS	3
2. TEST RESULTS SUMMARY 7 3. TEST METHODOLOGY 7 4. FACILITIES AND ACCREDITATION 7 5. DECISION RULES AND MEASUREMENT UNCERTAINTY 8 5.1. METROLOGICAL TRACEABILITY 8 5.2. DECISION RULES 8 5.3. MEASUREMENT UNCERTAINTY 8 5.4. SAMPLE CALCULATION 9 6. EQUIPMENT UNDER TEST 10 6.1. EUT DESCRIPTION 10 6.2. MAXIMUM OUTPUT POWER 10 6.3. DESCRIPTION OF AVAILABLE ANTENNAS AND CABLE LOSS 10 6.4. WORST-CASE CONFIGURATION AND MODE 10 6.5. DESCRIPTION OF TEST SETUP 11 7. TEST AND MEASUREMENT EQUIPMENT 14 8. MEASUREMENT METHOD 15 9. ANTENNA PORT TEST RESULTS 16 9.1. ON TIME AND DUTY CYCLE 16 9.2.99% BANDWIDTH 18 9.2.1. BLE (125kbps) 20 9.2.3. BLE (1Mbps) 20 9.3.1 BLE (125kbps) 21 9.3.2. BLE (10bps) 21 9.3.3. BLE (11Mbps) 22 9.4.1 BLE (125kbps) 24 9.3.4. BLE (215kbps) 25 <th>1. AT</th> <th>TESTATION OF TEST RESULTS</th> <th>5</th>	1. AT	TESTATION OF TEST RESULTS	5
3. TEST METHODOLOGY	2. TE	ST RESULTS SUMMARY	7
4. FACILITIES AND ACCREDITATION	3. TE	ST METHODOLOGY	7
5. DECISION RULES AND MEASUREMENT UNCERTAINTY. 8 5.1. METROLOGICAL TRACEABILITY. 8 5.2. DECISION RULES. 8 5.3. MEASUREMENT UNCERTAINTY. 8 5.4. SAMPLE CALCULATION. 9 6. EQUIPMENT UNDER TEST 10 6.1. EUT DESCRIPTION. 10 6.2. MAXIMUM OUTPUT POWER. 10 6.3. DESCRIPTION OF AVAILABLE ANTENNAS AND CABLE LOSS. 10 6.4. WORST-CASE CONFIGURATION AND MODE. 10 6.5. DESCRIPTION OF TEST SETUP. 11 7. TEST AND MEASUREMENT EQUIPMENT 14 8. MEASUREMENT METHOD 15 9. ANTENNA PORT TEST RESULTS 16 9.1. ON TIME AND DUTY CYCLE. 16 9.2.99% BANDWIDTH 18 9.2.1. BLE (125kbps). 18 9.2.2. BLE (500kbps). 18 9.2.3. BLE (1Mbps) 20 9.2.4. BLE (20kbps). 21 9.3.6 dB BANDWIDTH 22 9.3.1. BLE (125kbps). 23 9.3.2. BLE (500kbps). 23 9.3.4. BLE (215kbps). 25 9.3.4. BLE (215kbps). 26 9.4. OUTPUT POWER. 27	4. FA	CILITIES AND ACCREDITATION	7
5.1. METROLOGICAL TRACEABILITY 8 5.2. DECISION RULES 8 5.3. MEASUREMENT UNCERTAINTY 8 5.4. SAMPLE CALCULATION 9 6. EQUIPMENT UNDER TEST 10 6.1. EUT DESCRIPTION 10 6.2. MAXIMUM OUTPUT POWER 10 6.3. DESCRIPTION OF AVAILABLE ANTENNAS AND CABLE LOSS 10 6.4. WORST-CASE CONFIGURATION AND MODE 10 6.5. DESCRIPTION OF TEST SETUP 11 7. TEST AND MEASUREMENT EQUIPMENT 14 8. MEASUREMENT METHOD 15 9. ANTENNA PORT TEST RESULTS 16 9.1. ON TIME AND DUTY CYCLE 16 9.2.2. BLE (100kbps) 18 9.2.3. BLE (10bkps) 20 9.2.4. BLE (200kbps) 21 9.3.1. BLE (125kbps) 23 9.3.2. BLE (200kbps) 23 9.3.4. BLE (125kbps) 23 9.3.4. BLE (200kbps) 24 9.3.3. BLE (110bkps) 25<	5. DE	CISION RULES AND MEASUREMENT UNCERTAINTY	8
5.2. DECISION RULES	5.1.	METROLOGICAL TRACEABILITY	8
5.3. MEASUREMENT UNCERTAINTY	5.2.	DECISION RULES	8
5.4. SAMPLE CALCULATION	5.3.	MEASUREMENT UNCERTAINTY	8
6. EQUIPMENT UNDER TEST 10 6.1. EUT DESCRIPTION 10 6.2. MAXIMUM OUTPUT POWER 10 6.3. DESCRIPTION OF AVAILABLE ANTENNAS AND CABLE LOSS 10 6.4. WORST-CASE CONFIGURATION AND MODE 10 6.5. DESCRIPTION OF TEST SETUP 11 7. TEST AND MEASUREMENT EQUIPMENT 14 8. MEASUREMENT METHOD 15 9. ANTENNA PORT TEST RESULTS 16 9.1. ON TIME AND DUTY CYCLE 16 9.2. 99% BANDWIDTH 18 9.2.1. BLE (125kbps) 18 9.2.2. BLE (500kbps) 19 9.3.1 BLE (1Mbps) 20 9.2.4. BLE (2Mbps) 21 9.3.1 BLE (125kbps) 23 9.3.2. BLE (500kbps) 24 9.3.3. BLE (1Mbps) 25 9.3.4. BLE (2Mbps) 26 9.4.1 BLE (125kbps) 26 9.4.1 BLE (125kbps) 27 9.4.1 BLE (125kbps) 26 9.4.1 BLE (125kbps) 27 9.4.1 BLE (125kbps) 27 9.4.1 BLE (125kbps) 27 9.4.1 BLE (125kbps) 27 9.4.1 BLE (125kbps) 27<	5.4.	SAMPLE CALCULATION	9
6.1. EUT DESCRIPTION	6. EC	UIPMENT UNDER TEST	10
6.2. MAXIMUM OUTPUT POWER	6.1.	EUT DESCRIPTION	
6.3. DESCRIPTION OF AVAILABLE ANTENNAS AND CABLE LOSS. 10 6.4. WORST-CASE CONFIGURATION AND MODE 10 6.5. DESCRIPTION OF TEST SETUP 11 7. TEST AND MEASUREMENT EQUIPMENT 14 8. MEASUREMENT METHOD 15 9. ANTENNA PORT TEST RESULTS 16 9.1. ON TIME AND DUTY CYCLE 16 9.2. 99% BANDWIDTH 18 9.2.1. BLE (125kbps) 18 9.2.2. BLE (500kbps) 19 9.2.3. BLE (1Mbps) 20 9.2.4. BLE (2Mbps) 21 9.3.1 BLE (125kbps) 23 9.3.2. BLE (500kbps) 24 9.3.3. BLE (1Mbps) 25 9.3.4. BLE (2Mbps) 26 9.4.1. BLE (125kbps) 27 9.4.1. BLE (125kbps) 27 Page 3 of 78 27	6.2.	MAXIMUM OUTPUT POWER	
6.4. WORST-CASE CONFIGURATION AND MODE 10 6.5. DESCRIPTION OF TEST SETUP 11 7. TEST AND MEASUREMENT EQUIPMENT 14 8. MEASUREMENT METHOD 15 9. ANTENNA PORT TEST RESULTS 16 9.1. ON TIME AND DUTY CYCLE 16 9.2. 99% BANDWIDTH 18 9.2.1. BLE (125kbps) 18 9.2.2. BLE (500kbps) 19 9.2.3. BLE (1Mbps) 20 9.2.4. BLE (2Mbps) 21 9.3.6 dB BANDWIDTH 22 9.3.1. BLE (125kbps) 23 9.3.2. BLE (500kbps) 24 9.3.3. BLE (1Mbps) 25 9.3.4. BLE (2Mbps) 25 9.3.4. BLE (2Mbps) 26 9.4.1. BLE (125kbps) 27 9.4.1. BLE (125kbps) 27 9.4.1. BLE (125kbps) 27	6.3.	DESCRIPTION OF AVAILABLE ANTENNAS AND CABLE LOSS	
6.5. DESCRIPTION OF TEST SETUP. 11 7. TEST AND MEASUREMENT EQUIPMENT 14 8. MEASUREMENT METHOD 15 9. ANTENNA PORT TEST RESULTS 16 9.1. ON TIME AND DUTY CYCLE. 16 9.2. 99% BANDWIDTH 18 9.2.1. BLE (125kbps) 18 9.2.2. BLE (500kbps) 19 9.2.3. BLE (1Mbps) 20 9.2.4. BLE (2Mbps) 21 9.3.6 dB BANDWIDTH 22 9.3.1. BLE (125kbps) 23 9.3.2. BLE (500kbps) 23 9.3.3. BLE (1Mbps) 23 9.3.4. BLE (2Mbps) 24 9.3.4. BLE (2Mbps) 25 9.3.4. BLE (2Mbps) 26 9.4.1. BLE (125kbps) 27 9.4.1. BLE (125kbps) 27 9.4.1. BLE (125kbps) 27 9.3 of 78 27	6.4.	WORST-CASE CONFIGURATION AND MODE	
7. TEST AND MEASUREMENT EQUIPMENT 14 8. MEASUREMENT METHOD 15 9. ANTENNA PORT TEST RESULTS 16 9.1. ON TIME AND DUTY CYCLE 16 9.2. 99% BANDWIDTH 18 9.2.1. BLE (125kbps) 18 9.2.2. BLE (500kbps) 19 9.2.3. BLE (1Mbps) 20 9.2.4. BLE (2Mbps) 21 9.3. 6 dB BANDWIDTH 22 9.3.1. BLE (125kbps) 23 9.3.2. BLE (500kbps) 24 9.3.3. BLE (1Mbps) 25 9.3.4. BLE (2Mbps) 26 9.4. OUTPUT POWER 27 9.4.1. BLE (125kbps) 27 Page 3 of 78 27	6.5.	DESCRIPTION OF TEST SETUP	
8. MEASUREMENT METHOD 15 9. ANTENNA PORT TEST RESULTS 16 9.1. ON TIME AND DUTY CYCLE 16 9.2. 99% BANDWIDTH 18 9.2.1. BLE (125kbps) 18 9.2.2. BLE (500kbps) 19 9.2.3. BLE (1Mbps) 20 9.2.4. BLE (2Mbps) 21 9.3.6 dB BANDWIDTH 22 9.3.1. BLE (125kbps) 23 9.3.2. BLE (500kbps) 23 9.3.3. BLE (1Mbps) 23 9.3.4. BLE (2Mbps) 24 9.3.4. BLE (2Mbps) 25 9.3.4. BLE (2Mbps) 26 9.4. OUTPUT POWER 27 9.4.1. BLE (125kbps) 27 Page 3 of 78 27	7. TE	ST AND MEASUREMENT EQUIPMENT	14
9. ANTENNA PORT TEST RESULTS 16 9.1. ON TIME AND DUTY CYCLE 16 9.2. 99% BANDWIDTH 18 9.2.1. BLE (125kbps) 18 9.2.2. BLE (500kbps) 19 9.2.3. BLE (1Mbps) 20 9.2.4. BLE (2Mbps) 21 9.3.6 dB BANDWIDTH 22 9.3.1. BLE (125kbps) 23 9.3.2. BLE (500kbps) 23 9.3.3. BLE (11Mbps) 23 9.3.4. BLE (200kbps) 24 9.3.3. BLE (1Mbps) 25 9.3.4. BLE (2Mbps) 25 9.4.1 BLE (125kbps) 26 9.4.1 BLE (125kbps) 27 Page 3 of 78 27	8. ME	EASUREMENT METHOD	15
9.1. ON TIME AND DUTY CYCLE 16 9.2. 99% BANDWIDTH 18 9.2.1. BLE (125kbps) 18 9.2.2. BLE (500kbps) 19 9.2.3. BLE (1Mbps) 20 9.2.4. BLE (2Mbps) 21 9.3.6 dB BANDWIDTH 22 9.3.1. BLE (125kbps) 23 9.3.2. BLE (500kbps) 23 9.3.3. BLE (125kbps) 23 9.3.4. BLE (2Mbps) 25 9.3.4. BLE (2Mbps) 26 9.4.1 BLE (125kbps) 27 Page 3 of 78 27	9. AN	ITENNA PORT TEST RESULTS	16
9.2. 99% BANDWIDTH 18 9.2.1. BLE (125kbps) 18 9.2.2. BLE (500kbps) 19 9.2.3. BLE (1Mbps) 20 9.2.4. BLE (2Mbps) 21 9.3. 6 dB BANDWIDTH 22 9.3.1. BLE (125kbps) 23 9.3.2. BLE (500kbps) 24 9.3.3. BLE (500kbps) 25 9.3.4. BLE (2Mbps) 26 9.4.1 BLE (125kbps) 27 Page 3 of 78 27	9.1.	ON TIME AND DUTY CYCLE	
9.2.1. BLE (125kbps) 18 9.2.2. BLE (500kbps) 19 9.2.3. BLE (1Mbps) 20 9.2.4. BLE (2Mbps) 21 9.3. 6 dB BANDWIDTH 22 9.3.1. BLE (125kbps) 23 9.3.2. BLE (500kbps) 23 9.3.3. BLE (500kbps) 24 9.3.4. BLE (2Mbps) 25 9.3.4. BLE (2Mbps) 26 9.4.1. BLE (125kbps) 27 Page 3 of 78 27	9.2.	99% BANDWIDTH	
9.2.3. BLE (1Mbps) 20 9.2.4. BLE (2Mbps) 21 9.3. 6 dB BANDWIDTH 22 9.3.1. BLE (125kbps) 23 9.3.2. BLE (500kbps) 24 9.3.3. BLE (1Mbps) 25 9.3.4. BLE (2Mbps) 26 9.4.1. BLE (125kbps) 27 9.4.1. BLE (125kbps) 27 Page 3 of 78 27	9.2 9.2	2.1. BLE (125kbps) 2.2. BLE (500kbps)	
9.2.4. BLE (2Mbps) 21 9.3. 6 dB BANDWIDTH 22 9.3.1. BLE (125kbps) 23 9.3.2. BLE (500kbps) 24 9.3.3. BLE (1Mbps) 25 9.3.4. BLE (2Mbps) 26 9.4.1. BLE (125kbps) 27 9.4.1. BLE (125kbps) 27 Page 3 of 78 27	9.2	2.3. BLE (1Mbps)	20
9.3. 6 dB BANDWIDTH	9.2	2.4. BLE (2Mbps)	21
9.3.2. BLE (500kbps)	9.3. 9.3	6 dB BANDWIDTH	
9.3.3. BLE (1Mbps) 25 9.3.4. BLE (2Mbps) 26 9.4. OUTPUT POWER 27 9.4.1. BLE (125kbps) 27 Page 3 of 78	9.3	3.2. BLE (500kbps)	24
9.4. OUTPUT POWER	9.3 9.3	3.3. BLE (1Mbps) 3.4 BLF (2Mbps)	25 26
9.4.1. BLE (125kbps)	94	OUTPUT POWER	27
Page 3 of 78	9.4	I.1. BLE (125kbps)	27
		Page 3 of 78	

47173 Benicia Street, Fremont, CA 94538, USA

TEL:(510) 319-4000

FAX:(510) 661-0888

	9.4.2. 9.4.3. 9.4.4.	BLE (500kbps) BLE (1Mbps) BLE (2Mbps)	27 28 28
9.5 (((5. A\ 9.5.1. 9.5.2. 9.5.3. 9.5.4.	VERAGE POWER BLE (125kbps) BLE (500kbps) BLE (1Mbps) BLE (2Mbps)	29 29 30 30
9.6 9 9 9	6. PC 9.6.1. 9.6.2. 9.6.3. 9.6.4.	OWER SPECTRAL DENSITY BLE (125kbps) BLE (500kbps) BLE (1Mbps) BLE (2Mbps)	31 31 32 33 34
9.7 9.7 9.7	7. C(9.7.1. 9.7.2. 9.7.3. 9.7.4.	ONDUCTED SPURIOUS EMISSIONS BLE (125kbps) BLE (500kbps) BLE (1Mbps) BLE (2Mbps)	35 36 37 38 39
10.	RAD	NATED TEST RESULTS	40
10	.1. TF	RANSMITTER ABOVE 1 GHz	
-	10.1.1.	BLE (125kbps) BLE (500kbps)	
	10.1.3.	BLE (1Mbps)	
	10.1.4.	BLE (2Mbps)	60
10	.2. W	ORST CASE BELOW 30MHz	70
10	.3. W	ORST CASE BELOW 1 GHz	71
10	.4. W	ORST CASE 18-26 GHz	73
11.	AC F	POWER LINE CONDUCTED EMISSIONS	75
12.	SET	UP PHOTOS	78

Page 4 of 78

Complies

1. ATTESTATION OF TEST RESULTS

COMPANY NAME:	SAMSUNG ELECTRONICS CO., LTD 129 SAMSUNG-RO, YEONGTONG-O SUWON-SI, GYEONGGI-DO, 16677,	D. GU KOREA	
EUT DESCRIPTION:	BT/BLE Tablet + DTS/UNII a/b/g/n/ac	/ax and Digitizer	
MODEL:	SM-X620		
SERIAL NUMBER:	Conducted: R32XC0045HM Radiated: R32XC0045X8		
SAMPLE RECEIPT DATE:	2024-12-13		
DATE TESTED:	2025-01-14 to 2025-02-13		
	APPLICABLE STANDARDS		
S	FANDARD	TEST RESULTS	
CFR 47 I	Part 15 Subpart C	Complies	
ISED R	SS-247 Issue 3	Complies	

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

ISED RSS-GEN Issue 5 + A1 + A2

The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise.

This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document.

Page 5 of 78

TEL:(510) 319-4000

Approved & Released For UL Verification Services Inc. By:

no deluck

Francisco de Anda Staff Engineer Consumer Technology Division UL Verification Services Inc.

Prepared By:

Gerardo Abrego Senior Test Engineer Consumer Technology Division UL Verification Services Inc.

Reviewed By:

ma

Henry Lau Senior Project Engineer Consumer Technology Division UL Verification Services Inc.

Page 6 of 78

TEL:(510) 319-4000

FAX:(510) 661-0888

2. TEST RESULTS SUMMARY

This report contains data provided by the customer which can impact the validity of results. UL Verification Services Inc. is only responsible for correctly integrating customer-provided data with measurements performed by UL Verification Services Inc.

Below is a list of the data provided by the customer:

- 1) Antenna gain and type (see section 6.3)
- 2) Cable Loss (see section 6.3)

FCC Clause	ISED Clause	Requirement	Result	Comment
See Comment		Duty Cycle	Reporting	ANSI C63.10 Section
		Duty Oycic	purposes only	11.6.
_	PSS-CEN 6 7	99% OBW	Reporting	ANSI C63.10 Section
-	N33-GEN 0.7	9978 OBW	purposes only	6.9.3.
15.247 (a) (2)	RSS-247 5.2 (a)	6dB BW	Complies	None.
15.247 (b) (3)	RSS-247 5.4 (d)	Output Power	Complies	None.
See Comment		Average power	Reporting	Per ANSI C63.10,
			purposes only	Section 11.9.2.3.2.
15.247 (e)	RSS-247 5.2 (b)	PSD	Complies	None.
15.247 (d)	RSS-247 5.5	Conducted Spurious Emissions	Complies	None.
15.209, 15.205	RSS-GEN 8.9, 8.10	Radiated Emissions	Complies	None.
15.207	RSS-Gen 8.8	AC Mains Conducted Emissions	Complies	None.

3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with

- FCC CFR 47 Part 2
- FCC CFR 47 Part 15
- ANSI C63.10-2020
- KDB 558074 D01 15.247 Meas Guidance
- KDB 414788 D01 Radiated Test Site
- RSS-247 Issue 3
- RSS-GEN Issue 5 + A1 + A2

4. FACILITIES AND ACCREDITATION

UL Verification Services Inc. is accredited by A2LA, Certificate Number 0751.05, for all testing performed within the scope of this report. Testing was performed at the locations noted below.

	Address	ISED CABID	ISED Company Number	FCC Registration
\boxtimes	Building 1: 47173 Benicia Street, Fremont, CA 94538, USA			
	Building 2: 47266 Benicia Street, Fremont, CA 94538, USA			
	Building 3: 843 Auburn Court, Fremont, CA 94538, USA	US0104	2324A	550739
\boxtimes	Building 4: 47658 Kato Rd, Fremont, CA 94538, USA			
	Building 5: 47670 Kato Rd, Fremont, CA 94538, USA			

Page 7 of 78

UL VERIFICATION SERVICES INC. 47173 Benicia Street, Fremont, CA 94538, USA

TEL:(510) 319-4000

FAX:(510) 661-0888

5. DECISION RULES AND MEASUREMENT UNCERTAINTY

5.1. METROLOGICAL TRACEABILITY

All test and measuring equipment utilized to perform the tests documented in this report are calibrated on a regular basis, with a maximum time between calibrations of one year or the manufacturers' recommendation, whichever is less, and where applicable is traceable to recognized national standards.

5.2. DECISION RULES

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4:2012 Clause 8.2. (Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

5.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	U _{Lab}
Radio Frequency (Spectrum Analyzer)	141.16 Hz
Occupied Bandwidth	1.22%
Power Spectral Density	2.47 dB
RF Power Measurement Direct Method Using Power Meter	1.3 dB (PK) / 0.45 dB (AV)
Unwanted Emissions, Conducted	1.94 dB
Worst Case Conducted Disturbance, 9kHz to 0.15 MHz	3.78 dB
Worst Case Conducted Disturbance, 0.15 to 30 MHz	3.40 dB
Worst Case Radiated Disturbance, 9kHz to 30 MHz	2.87 dB
Worst Case Radiated Disturbance, 30 to 1000 MHz	6.01 dB
Worst Case Radiated Disturbance, 1000 to 18000 MHz	4.73 dB
Worst Case Radiated Disturbance, 18000 to 26000 MHz	4.51 dB
Time Domain Measurements	3.39%
Temperature	0.57°C
Relative Humidity	3.39%
DC Supply Voltages	0.57%

Uncertainty figures are valid to a confidence level of 95%.

Page 8 of 78

TEL:(510) 319-4000

5.4. SAMPLE CALCULATION

RADIATED EMISSIONS

Where relevant, the following sample calculation is provided: Field Strength (dBuV/m) = Measured Voltage (dBuV) + Antenna Factor (dB/m) + Cable Loss (dB) – Preamp Gain (dB) 36.5 dBuV + 18.7 dB/m + 0.6 dB - 26.9 dB = 28.9 dBuV/m

MAINS CONDUCTED EMISSIONS

Where relevant, the following sample calculation is provided: Final Voltage (dBuV) = Measured Voltage (dBuV) + Cable Loss (dB) + Limiter Factor (dB) + LISN Insertion Loss. 36.5 dBuV + 0 dB + 10.1 dB + 0 dB = 46.6 dBuV

Page 9 of 78

6. EQUIPMENT UNDER TEST

6.1. EUT DESCRIPTION

The EUT is a BT/BLE Tablet + DTS/UNII a/b/g/n/ac/ax and Digitizer.

6.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

Frequency	Mode	Output Power	Output Power
Range		(dBm)	(mW)
(MHz)			
	BLE (125kbps)	12.30	16.98
2402 - 2480	BLE (500kbps)	12.36	17.22
	BLE (1Mbps)	15.49	35.40
2404 - 2478	BLE (2Mbps)	15.89	38.82

The EUT does not support Primary PHY channels (2402[37] / 2426[38] / 2480[39] MHz) at the BLE 2Mbps data-rate. BLE 2Mbps channels used for testing are from 2404 – 2478 MHz

6.3. DESCRIPTION OF AVAILABLE ANTENNAS AND CABLE LOSS

The antenna(s) gain, type and cable loss, as provided by the manufacturer' are as follows:

The radio utilizes an internal antenna, with a maximum gain of -3.7dBi. Cable loss: 0.7dB.

6.4. WORST-CASE CONFIGURATION AND MODE

Radiated emissions below 1GHz, above 18GHz, and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

Band edge was performed with the EUT set to transmit at the highest power on low and high channels for all modes.

For radiated emissions between 1GHz and 18GHz, 125kbps and 2Mbps were tested to cover worst case PSD and worst-case power.

The fundamental of the EUT was investigated in three orthogonal orientations X,Y,Z, it was determined that Y orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in Y orientation.

EUT supports the following data rates:

• 125kbps

Page 10 of 78

UL VERIFICATION SERVICES INC. 47173 Benicia Street, Fremont, CA 94538, USA

TEL:(510) 319-4000

FAX:(510) 661-0888

- 500kbps
- 1Mbps
- 2Mbps

6.5. DESCRIPTION OF TEST SETUP

SUPPORT TEST EQUIPMENT							
Description Manufacturer Model Serial Number FCC ID/ DoC							
AC Adapter	Samsung	EP-TA800	R37WBAA004BDKA	N/A			
S-Pen	Samsung	N/A	N/A	N/A			
Keyboard	Samsung	DX625	N/A	N/A			

	I/O CABLES (RF CONDUCTED TEST)							
Cable No. Port # of Identical Ports Connector Type Cable Type Cable Length (m) Remarks								
1	Antenna	1	RF	Unshielded	0.2	N/A		
2	USB-C	1	USB-C	Shielded	1	EUT to AC/DC adapter		

I/O CABLES (RF RADIATED and AC LINE CONDUCTED TEST)						
Cable No. Port # of Identical Ports Connector Type Cable Type Cable Length (m) Remarks						
1	USB-C	1	USB-C	Shielded	1	N/A

TEST SETUP

The EUT is a stand-alone device configured and tested in a worst-case setup. Worst case is using Y orientation with AC charger, keyboard and pen attached to the EUT. Test software exercised the radio card.

Page 11 of 78

TEL:(510) 319-4000

SETUP DIAGRAM



Page 12 of 78

UL VERIFICATION SERVICES INC. 47173 Benicia Street, Fremont, CA 94538, USA

TEL:(510) 319-4000

FAX:(510) 661-0888



Page 13 of 78

7. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

TEST EQUIPMENT LIST							
Description	Manufacturer	Model	ID Num	Cal Due	Last Cal		
Antenna, Passive Loop 30Hz - 1MHz	ELECTRO METRICS	EM-6871	219908	2025-05-31	2023-05-31		
Antenna, Passive Loop 100KHz - 30MHz	ELECTRO METRICS	EM-6872	219910	2025-05-31	2023-05-31		
Antenna, Broadband Hybrid, 30MHz to 2000MHz	Sunol Sciences Corp.	JB1	80293	2025-04-30	2023-04-11		
Amplifier,9KHz to 1GHz, 32dB	SONOMA INSTRUMENT	310	170647	2025-03-31	2024-03-25		
Antenna, Horn 1- 18GHz	ETS-Lindgren	3117	80707	2025-06-30	2024-06-07		
Antenna, Horn 1- 18GHz	ETS-Lindgren	3117	206808	2025-04-30	2024-04-23		
RF Filter Box, 1- 18GHz	UL-FR1	n/a	171875	2025-03-31	2024-03-23		
RF Filter Box, 1- 18GHz	UL-FR1	SAC 8 port rf box 1	197920	2025-03-31	2024-03-30		
EMI TEST RECEIVER, with B8 option	Rohde & Schwarz	ESW44	245268	2025-02-28	2024-02-15		
EMI TEST RECEIVER	Rohde & Schwarz	ESW44	225688	2025-02-28	2024-02-11		
Antenna, Horn 18 to 26.5GHz	A.R.A.	MWH-1826/B	199658	2025-02-28	2024-02-02		
Amplifier 18-26.5GHz, +5Vdc, -54dBm P1dB	AMPLICAL	AMP18G26.5- 60	234683	2025-05-31	2024-05-13		
Spectrum Analyzer, PXA, 3Hz to 44GHz	Keysight Technologies Inc	N9030A	80396	2025-02-28	2024-02-21		
Power Meter, P- series single channel	Keysight Technologies Inc	N1921A	90391	2025-06-30	2024-06-17		
Power Sensor, P - series, 50MHz to 18GHz, Wideband	Keysight Technologies Inc	N1911A	90754	2025-01-31*	2024-01-25		
10dB Fixed Attenuator	Pasternack Enterprises	PE7087-10	236188	Verified	Before Use		
	Α	C Line Conduct	ted				
LISN	Fischer Custom Communications, Inc	FCC-LISN- 50/250-25-2- 01-480V	175765	2026-01-31	2025-01-28		
EMI TEST RECEIVER	Rohde & Schwarz	ESR	171646	2025-02-28	2024-02-27		
Transient Limiter TE		TBFL1	207996	2025-09-30	2024-09-24		
	ULI	TEST SOFTWAR	E LIST				
Radiated Software	UL	UL EMC	Ver 202	4-08-15, 2023-03,	, 2023-05-01		
Antenna Port Software	UL	UL RF	Ver 2022-08-16				
AC Line Conducted Software	UL	UL EMC	Rev 9.5, 2023-03				

*Tests performed within cal. date.

Page 14 of 78

UL VERIFICATION SERVICES INC. 47173 Benicia Street, Fremont, CA 94538, USA

TEL:(510) 319-4000

FAX:(510) 661-0888

8. MEASUREMENT METHOD

On Time and Duty Cycle: ANSI C63.10 Section 11.6.

<u>6 dB BW:</u> ANSI C63.10 Subclause -11.8.1 RBW ≥ DTS BW

Output Power: ANSI C63.10 Subclause -11.9.1.2 Method PKPM1 Peak-reading power meter Output Power: ANSI C63.10 Subclause -11.9.2.3.2 Method AVGPM-G (Measurement using a gated RF average-reading power meter)

PSD: ANSI C63.10 Subclause -11.10.2 Method PKPSD (peak PSD)

Radiated emissions non-restricted frequency bands: ANSI C63.10 Subclause -11.11

Radiated emissions restricted frequency bands: ANSI C63.10 Subclause -11.12.1

Conducted emissions in restricted frequency bands: ANSI C63.10 Subclause -11.12.2

Band-edge: ANSI C63.10 Subclause -6.10.5.2 Peak detection

Band-edge: ANSI C63.10 Subclause -6.10.5.2 Reduced VBW averaging

AC Power Line Conducted Emissions: ANSI C63.10 Section 6.2.

Radiated Spurious Emissions Below 30MHz: ANSI C63.10 Section 6.4

Page 15 of 78

TEL:(510) 319-4000

FAX:(510) 661-0888

9. ANTENNA PORT TEST RESULTS

9.1. ON TIME AND DUTY CYCLE

LIMITS

None; for reporting purposes only.

PROCEDURE

KDB 558074 Zero-Span Spectrum Analyzer Method.

ON TIME AND DUTY CYCLE RESULTS

Mode	ON Time	Period	Duty Cycle	Duty	Duty Cycle	1/T
	т		x	Cycle	Correction Factor	Minimum VBW
	(msec)	(msec)	(linear)	(%)	(dB)	(kHz)
125kbps	3.104					0.322
500kbps	1.066					0.938
1Mbps	0.390					2.564
2Mbps	0.203					4.926

The Duty Cycle is non-constant and < 98% due to a 200ms off time therefore 1/T method was used for averaging.



Page 16 of 78

UL VERIFICATION SERVICES INC. 47173 Benicia Street, Fremont, CA 94538, USA

TEL:(510) 319-4000

FAX:(510) 661-0888

MultiView Spectrum X Receiver		MultiView Spectrum	X Receiver	ĸ		
Ref Level 132.00 dBµV RBW 10 MHz SGL		Ref Level 132.00 dBµV	 RBW 10 MHz 	SGL	_	
Att 25 dB = SWT 5 ms = VBW 10 MHz Input 1 AC PS Off Notch Off	Frequency 2.4400000 GHz	 Att 25 dB = SWT Input 1 AC PS 	5 ms • VBW 10 MHz Off Notch Off		Fre	equency 2.4400000 GHz
1 Zero Span	1Pk Cirw	1 Zero Span	,			1Pk Clrw
120 dBµV	390.065 us	120 dBµV				203,367 us
110 dBµV H1 D2 H3 D4 H9 D6 H7 D8 H9 D10	M1[1] 103:74 dBpV	110 dBµV M1 D0	M3 pt M5	D6 N7 D8	M9 010	M1[1] 107:44 dBpV
100 (Buy	727.621 µs	100 dBuV	° .	° °		723.454 µs
90 dBµV		90 dsµV				
80 dbµV		00 d8µ/v				
70 dBµ/v		70 d8µV		and the second second second	A Contractor of the	
ted and interest interest white	deal and this		nalising provide the	NUMBER OF STREET	NUMBER OF STREET, STREE	pression and a second second
50 d8µV		50 d8µV				
40 dbµV		40 d8µ//				
20.45 (7		30 d8.//				
CE 2.44 GHz 6000 pts	500.0 us/	CF 2.44 GHz		6000 pts		500.0 µs/
2 Marker Table		2 Marker Table				
Type Ref Trc X-Value Y-Value Function	Function Result	Type Ref Trc	X-Value 723.454 IIS 10	Y-Value 7.44 dBuV	Function	Function Result
D2 M1 1 390.065 µs 0.70 dB		D2 M1 1	203.367 µs	0.27 dB		
M3 1 1.352725 ms 103.76 dBµV		D4 M3 1	.348558 ms 10	0.24 dBpV		
M5 1.97783 ms 103.80 dBµV		M5 1 1	.973662 ms 10	7.46 dBµV		
M7 1 2.602934 ms 103.71 dBµV		M7 1 2	.598766 ms 10	7.45 dBµV		
D8 M7 1 390.065 µs 0.71 dB		D8 M7 1 M0 1 3	203.367 µs	0.23 dB 7.41 dBuV		
D10 M9 1 390.065 µs 0.68 dB		D10 M9 1	203.367 µs	0.31 dB		
Ready Ready	2025-02-13 Ref Level RBW			Ready	2025-02	13 Ref Lovel RBW
01:46:05 AM 02/13/2025		01:55:42 AM 02/13/2025				
1Mbpc				2Mhno		
TMDps				ZIVIDPS		

Page 17 of 78

TEL:(510) 319-4000

9.2. 99% **BANDWIDTH**

LIMITS

None; for reporting purposes only.

RESULTS

9.2.1. BLE (125kbps)

Channel	Frequency	99% Bandwidth
	(MHz)	(MHz)
Low	2402	1.0433
Middle	2440	1.0450
High	2480	1.0381



Page 18 of 78

UL VERIFICATION SERVICES INC. 47173 Benicia Street, Fremont, CA 94538, USA

TEL:(510) 319-4000

FAX:(510) 661-0888

9.2.2. BLE (500kbps)

Channel	Frequency	99% Bandwidth
	(MHZ)	(MHZ)
Low	2402	1.0116
Middle	2440	1.0143
High	2480	1.0087





Page 19 of 78

UL VERIFICATION SERVICES INC. 47173 Benicia Street, Fremont, CA 94538, USA

TEL:(510) 319-4000

FAX:(510) 661-0888

9.2.3. BLE (1Mbps)

Channel	Frequency	99% Bandwidth
	(MHz)	(MHz)
Low	2402	1.0323
Middle	2440	1.0327
High	2480	1.0333





Page 20 of 78

UL VERIFICATION SERVICES INC. 47173 Benicia Street, Fremont, CA 94538, USA

TEL:(510) 319-4000

FAX:(510) 661-0888

9.2.4. BLE (2Mbps)

Channel	Frequency	99% Bandwidth
	(MHz)	(MHz)
Low	2404	2.0451
Middle	2440	2.0421
High	2478	2.0451





Page 21 of 78

UL VERIFICATION SERVICES INC. 47173 Benicia Street, Fremont, CA 94538, USA

TEL:(510) 319-4000

FAX:(510) 661-0888

9.3. 6 dB BANDWIDTH

LIMITS

FCC §15.247 (a) (2)

RSS-247 5.2 (a)

The minimum 6 dB bandwidth shall be at least 500 kHz.

RESULTS

Page 22 of 78

TEL:(510) 319-4000

9.3.1. BLE (125kbps)

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2402	0.6840	0.5
Middle	2440	0.6750	0.5
High	2480	0.6690	0.5





Page 23 of 78

UL VERIFICATION SERVICES INC. 47173 Benicia Street, Fremont, CA 94538, USA

TEL:(510) 319-4000

9.3.2. BLE (500kbps)

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2402	0.6810	0.5
Middle	2440	0.6870	0.5
High	2480	0.7170	0.5





Page 24 of 78

UL VERIFICATION SERVICES INC. 47173 Benicia Street, Fremont, CA 94538, USA

TEL:(510) 319-4000

9.3.3. BLE (1Mbps)

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2402	0.7110	0.5
Middle	2440	0.6810	0.5
High	2480	0.6780	0.5





Page 25 of 78

UL VERIFICATION SERVICES INC. 47173 Benicia Street, Fremont, CA 94538, USA

TEL:(510) 319-4000

9.3.4. BLE (2Mbps)

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2404	1.2180	0.5
Middle	2440	1.0680	0.5
High	2478	1.0920	0.5





Page 26 of 78

UL VERIFICATION SERVICES INC. 47173 Benicia Street, Fremont, CA 94538, USA

9.4. OUTPUT POWER

LIMITS

FCC §15.247 (b) (3)

RSS-247 5.4 (d)

The maximum antenna gain is less than or equal to 6 dBi, therefore the limit is 30 dBm.

TEST PROCEDURE

The transmitter output is connected to a power meter.

The power output was measured on the EUT antenna port using an SMA cable with a 10dB attenuator connected to a power meter via a wideband power sensor. Peak output power was read directly from a power meter.

RESULTS

9.4.1. BLE (125kbps)

Tested By:	45256 JB
Date:	2025-01-15

Channel	Frequency (MHz)	Peak Power Reading (dBm)	Limit (dBm)	Margin (dB)
Low	2402	11.920	30	-18.080
Middle	2440	12.300	30	-17.700
High	2480	11.880	30	-18.120

9.4.2. BLE (500kbps)

Tested By:	45256 JB
Date:	2025-01-15

Channel	Frequency	Peak Power Reading	Limit	Margin
	(MHz)	(dBm)	(dBm)	(dB)
Low	2402	12.030	30	-17.970
Middle	2440	12.360	30	-17.640
High	2480	11.920	30	-18.080

Page 27 of 78

UL VERIFICATION SERVICES INC. 47173 Benicia Street, Fremont, CA 94538, USA

TEL:(510) 319-4000

FAX:(510) 661-0888

9.4.3. BLE (1Mbps)

Tested By:	45256 JB
Date:	2025-01-15

Channel	Frequency (MHz)	Peak Power Reading (dBm)	Limit (dBm)	Margin (dB)
Low	2402	15.380	30	-14.620
Middle	2440	15.490	30	-14.510
High	2480	15.360	30	-14.640

9.4.4. BLE (2Mbps)

Tested By:	45256 JB
Date:	2025-01-15

Channel	Frequency	Peak Power Reading	Limit	Margin
	(MHz)	(dBm)	(dBm)	(dB)
Low	2404	15.630	30	-14.370
Middle	2440	15.680	30	-14.320
High	2478	15.890	30	-14.110

Page 28 of 78

9.5. AVERAGE POWER

LIMITS

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a power meter.

The power output was measured on the EUT antenna port using an SMA cable with a 10dB attenuator connected to a power meter via a wideband power sensor. Gated average output power was read directly from a power meter.

RESULTS

9.5.1. BLE (125kbps)

Tested By:	45256 JB
Date:	2025-01-15

Channel	Frequency	AV power
	(MHz)	(dBm)
Low	2402	11.65
Middle	2440	12.04
High	2480	11.55

9.5.2. BLE (500kbps)

Tested By:	45256 JB
Date:	2025-01-15

Channel	Frequency	AV power
	(MHz)	(dBm)
Low	2402	11.74
Middle	2440	12.11
High	2480	11.65

Page 29 of 78

9.5.3. BLE (1Mbps)

Tested By:	45256 JB
Date:	2025-01-15

Channel	Frequency	AV power
	(MHz)	(dBm)
Low	2402	15.25
Middle	2440	15.32
High	2480	15.17

9.5.4. BLE (2Mbps)

Tested By:	45256 JB
Date:	2025-01-15

Channel	Frequency	AV power	
	(MHz)	(dBm)	
Low	2404	15.39	
Middle	2440	15.52	
High	2478	15.74	

Page 30 of 78

9.6. POWER SPECTRAL DENSITY

LIMITS

FCC §15.247 (e)

RSS-247 (5.2) (b)

The power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

RESULTS

9.6.1. BLE (125kbps)

Channel	Frequency	PSD	Limit	Margin
	(MHz)	(dBm/3kHz)	(dBm/3kHz)	(dB)
Low	2402	4.937	8	-3.06
Middle	2440	5.257	8	-2.74
High	2480	5.507	8	-2.49



47173 Benicia Street, Fremont, CA 94538, USA

TEL:(510) 319-4000

FAX:(510) 661-0888

9.6.2. BLE (500kbps)

Channel	Frequency	PSD	Limit	Margin
	(MHz)	(dBm/3kHz)	(dBm/3kHz)	(dB)
Low	2402	4.601	8	-3.40
Middle	2440	5.054	8	-2.95
High	2480	5.346	8	-2.65





Page 32 of 78

UL VERIFICATION SERVICES INC. 47173 Benicia Street, Fremont, CA 94538, USA

9.6.3. BLE (1Mbps)

Channel	Frequency	PSD	Limit	Margin
	(MHz)	(dBm/3kHz)	(dBm/3kHz)	(dB)
Low	2402	0.376	8	-7.62
Middle	2440	0.806	8	-7.19
High	2480	1.164	8	-6.84





Page 33 of 78

UL VERIFICATION SERVICES INC. 47173 Benicia Street, Fremont, CA 94538, USA

9.6.4. BLE (2Mbps)

Channel	Frequency	PSD	Limit	Margin
	(MHz)	(dBm/3kHz)	(dBm/3kHz)	(dB)
Low	2404	-2.669	8	-10.67
Middle	2440	-2.161	8	-10.16
High	2478	-1.769	8	-9.77





Page 34 of 78

UL VERIFICATION SERVICES INC. 47173 Benicia Street, Fremont, CA 94538, USA

9.7. CONDUCTED SPURIOUS EMISSIONS

LIMITS

FCC §15.247 (d)

RSS-247 5.5

Output power was measured based on the use of a peak measurement, therefore the required attenuation is 20 dBc.

RESULTS

Page 35 of 78

TEL:(510) 319-4000

FAX:(510) 661-0888

9.7.1. BLE (125kbps)



Page 36 of 78

UL VERIFICATION SERVICES INC. 47173 Benicia Street, Fremont, CA 94538, USA

TEL:(510) 319-4000

FAX:(510) 661-0888