



ShenZhen Electronic Product Quality Testing Center

CONFORMANCE TEST REPORT FOR HUMAN EXPOSURE TO ELECTROMAGNETIC FIELDS

SAR06_010

Guangzhou Jinpeng Telecommunication Industrial Co.,Ltd

CDMA 1X mobile phone

Type Name: T100

FCC ID: T2M01200603

Hardware Version: P2.3

Software Version: 2.0.31.53.1

Date of Issue: 2006-3-10





GENERAL SUMMARY

Product Name	CDMA 1X mobile phone	Development Stage	MP
Standard(s)	<p>47CFR § 2.1093: Radiofrequency Radiation Exposure Evaluation: Portable Devices</p> <p>FCC OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01): Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields</p> <p>ANSI C95.1-1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.</p> <p>IEEE 1528-2003: Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques.</p>		
Conclusion	<p>Localized Specific Absorption Rate (SAR) of this portable wireless equipment has been measured in all cases requested by the relevant standards cited in Clause 5.2 of this test report. Maximum localized SAR is below exposure limits specified in the relevant standards cited in Clause 5.1 of this test report.</p> <p>General Judgment: Pass</p> <p style="text-align: right;">Date of issue: Mar 10th, 2006</p>		
Comment	<p>TX Freq. Band: 825.25 MHz —847.75 MHz</p> <p>RX Freq. Band: 870.25 MHz —892.75 MHz</p> <p>Antenna Character : build inside</p> <p>The test result only responds to the measured sample.</p>		
<div style="display: flex; justify-content: space-between; align-items: flex-start;"> <div style="width: 45%;"> <p>Tested by: <u>Li Jun Liang</u></p> <p style="text-align: center;">Lijun Liang</p> </div> <div style="width: 45%; text-align: right;"> <p>Date: <u>Mar 10th, 2006</u></p> </div> </div> <div style="display: flex; justify-content: space-between; align-items: flex-start; margin-top: 10px;"> <div style="width: 45%;"> <p>Checked by: <u>Smart Li</u></p> <p style="text-align: center;">Smart Li</p> </div> <div style="width: 45%; text-align: right;"> <p>Date: <u>Mar 10, 2006</u></p> </div> </div> <div style="display: flex; justify-content: space-between; align-items: flex-start; margin-top: 10px;"> <div style="width: 45%;"> <p>Approved by: <u>Keqin Wang</u></p> <p style="text-align: center;">Keqin Wang</p> </div> <div style="width: 45%; text-align: right;"> <p>Date: <u>Mar. 11, 2006</u></p> </div> </div>			

Contents

1. GENERAL CONDITIONS

2. ADMINISTRATIVE DATA

- 2.1. Identification of the Responsible Testing Laboratory
- 2.2. Identification of the Responsible Testing Location(s)
- 2.3. Organization Item
- 2.4. Identification of Applicant
- 2.5. Identification of Manufacture

3. EQUIPMENT UNDER TEST (EUT)

- 3.1. Identification of the Equipment under Test
- 3.2. Identification of all used Test Sample of the Equipment under Test

4. OPERATIONAL CONDITIONS DURING TEST

- 4.1. Schematic Test Configuration
- 4.2. SAR Measurement System

5. CHARACTERISTICS OF THE TEST

- 5.1. Applicable Limit Regulations
- 5.2. Applicable Measurement Standards

6. LABORATORY ENVIRONMENT

7. TEST RESULTS

- 7.1. Dielectric Performance
- 7.2. Summary of Measurement Results
- 7.3. Conclusion

8. MEASUREMENT UNCERTAINTY

9. MAIN TEST INSTRUMENTS

This Test Report consists of the following Annexes:

Annex A: Accreditation Certificate

Annex B: Test Layout

Annex C: Sample Photographs

Annex D: Graph Test Results

1 . GENERAL CONDITIONS

1.1 This report only refers to the item that has undergone the test.

1.2 This report standalone dose not constitute or imply by its own an approval of the product by the certification Bodies or competent Authorities.

1.3 This document is only valid if complete; no partial reproduction can be made without written approval of Shenzhen Electronic Product Quality Testing Center.

1.4 This report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of Shenzhen Electronic Product Quality Testing Center and the Accreditation Bodies, if it applies.

2. Administrative Data

2.1. Identification of the Responsible Testing Laboratory

Company Name: ShenZhen Electronic Product Quality Testing Center
Department: Testing Department
Address: Electronic Testing Building, ShaHe Road, NanShan District,
ShenZhen, P. R. China
Telephone: +86-755-26628676
Fax: +86-755-26627238
**Responsible Test Lab
Managers:** Mr. Wang Keqin

2.2. Identification of the Responsible Testing Location(s)

Company Name: ShenZhen Electronic Product Quality Testing Center
Address: Electronic Testing Building, ShaHe Road, NanShan District,
ShenZhen, P. R. China

2.3. Organization Item

S.E.T Report No.: SAR06_010
S.E.T Project Leader: Mr. Li Sixiong
**S.E.T Responsible for
accreditation scope:** Mr. Wang Keqin
Start of Testing: 2005-3-1
End of Testing: 2006-3-4

2.4. Identification of Applicant

Company Name: Guangzhou Jinpeng Telecommunication Industrial Co.,Ltd
Address: No.9 Shenzhou Road, Science City, Guangzhou, P.R.China
Contact person: Zhu yanfei
Telephone: +8620 85571601-8100
Fax: +8620 32068126

2.5. Identification of Manufacture

Company Name: Guangzhou Jinpeng Telecommunication Industrial Co.,Ltd
Address: No.9 Shenzhou Road, Science City, Guangzhou, P.R.China
Contact person: Zhu yanfei
Telephone: +8620 85571601-8100
Fax: +8620 32068126

Notes: This data is based on the information by the applicant.

3. Equipment Under Test (EUT)

3.1. Identification of the Equipment under Test

Brand Name: JinPeng
Type Name: T100
Marking Name: T100

General description:

Test frequency	CDMA 800MHz
Battery type	JP-B00906500
Battery specification	650mAh 3.7V
Antenna specification	Build inside
Operation mode	Call established
Modulation mode	CDMA
Max. Power(ERP)	0.210w(23.22dBm)

3.2. Identification of all used Test Sample of the Equipment under Test

EUT Code	ESN	Hardware Version	Software Version	MIN
N.A.	00000000	P2.3	2.0.31.53.1	404001056000000

4 OPERATIONAL CONDITIONS DURING TEST

4.1 Schematic Test Configuration

During SAR test, EUT is in Traffic Mode (Channel Allocated) at Normal Voltage Condition. A communication link is set up with a System Simulator (SS) by air link, and a call is established.

The TCH is allocated to 9, 384 and 758 respectively in the case of CDMA 800 MHz. The EUT is commanded to operate at maximum transmitting power.

The EUT shall use its internal transmitter. The antenna(s), battery and accessories shall be those specified by the manufacturer. The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power output. If a wireless link is used, the antenna connected to the output of the base station simulator shall be placed at least 50 cm away from the handset.

The signal transmitted by the simulator to the antenna feeding point shall be lower than the output power level of the handset by at least 35 dB.

4.2 SAR Measurement System

The SAR measurement system being used is the IndexSAR SARA2 system, which consists of a




Figure1. SAR Lab Test Measurement Set-up

Mitsubishi RV-E2 6-axis robot arm and controller, IndexSAR probe and amplifier and SAM phantom

Head Shape. The system is controlled remotely from a PC, which contains the software to control the robot and data acquisition equipment. The software also displays the data obtained from test scans, and determine the averaged SAR values (averaging region 1 gram or 10 gram) for compliance testing.

The measurements are done by two scan: first a coarse scan (2-Division) determines the region of the maximum SAR, afterwards the averaged SAR is measured in a second scan within the shape of a cube. The measurement time takes about 20 minutes.

4.2.1 Robot system specification

The robot is used to articulate the probe to programmed positions inside the phantom head to obtain the SAR readings from the DUT.



Robot and Stand

Type	Mitsubishi Movemaster RV-2A / 6 axis vertical articulated robot
Dimensions (robot)	Height: 790mm (in home position)
Dimensions (robot stand)	1010L x 450W x 820H mm
Weight	Approx. 36 kg
Position repeatability	+/- 0.04mm
Drive Method	AC servomotor
Expandability	Extra axis expansion capability for probe calibration applications E-Field probe



Robot Controller Unit

Type	CR1 - 571
Dimensions	212W x 290D x 151H mm
Weight	8 kg
Power source	single-phase 100 - 240 VAC

4.2.2 Probe and amplifier specification

IXP-050 Indexsar isotropic immersible SAR probe

The probes are constructed using three orthogonal dipole sensors arranged on an interlocking, triangular prism core. The probes have built-in shielding against static charges and are contained within a PEEK

cylindrical enclosure material at the tip (showed in figure 2). The system uses diode compression potential (DCP) to determine SAR values for different types of modulation. Crest factor is not used for determining SAR values. The DCP for different types of modulation is determined during the probe calibration procedure.

E-filed Probe



Type

Three orthogonal dipole sensors arranged on triangular, interlocking substrates

Dimensions

Overall length: 350mm

Tip length: 10mm

Body diameter: 12mm

Tip diameter: 5mm

Distance from probe tip to dipole centers: 2.5mm

Interfacing

Lemo 6 pole latching connector for interfacing to high impedance amplifier

Isotropy

+/- 0.5dB in brain liquids (rotation about probe axis)

typically +/- 0.15dB

+/- 0.5dB in brain liquids (rotation normal to probe axis)

Calibration

Indexsar calibration in brain tissue simulating liquids at frequency of 900MHz, 1800MHz and 1900MHz

Dynamic Range

0.001W/kg to 100W/kg in liquid. Linearity +/- 0.2W/kg





Figure2. Specification and characterisation parameters of indexsar probe


IFA-010 Amplifier

The amplifier unit has a multi-pole connector to connect to the probe and a multiplexer selects between the 3-channel single-ended inputs. A 16-bit AtoD converter with programmable gain is used along with an on-board micro-controller with non-volatile firmware. Battery life is around 150 hours and data are transferred to the PC via 3m of duplex optical fibre and a self-powered RS232 to optical converter.



Probe Amplifier and PC Interface

Type	High impedance inputs with 3 independent x,y,z sensor channels giving simultaneous measurement data every 2ms. Reads true average of modulated signals without the need for duty cycle corrections
Ranges	Software selectable of x1 to 63
Cable	Optical cable with self-powered 9 way RS232 converter. 3m cable length supplied as standard. Other lengths to order.
Power Requirements	2 x AAA batteries giving approximately 100 hours usage.



'Word' report format

The results of each frequency scan are presented in a Microsoft 'Word' document with all the necessary measurement parameters automatically tabulated. Users can customise the layout and in some cases language changes are possible.

4.2.3 Phantoms and simulant liquid

4.2.3.1 SAR head phantom (SAM)

The Indexsar SAM Upright Phantom is fabricated to the shape defined in these CAD files by Antennessa.



Head Phantom

Type 2	Upright SAM phantom
Dimensions	Height: 320mm Baseplate diameter: 275mm
Weight	empty: 1.2 kg filled: 7.2 kg
Wall thickness	2.0 mm \pm 0.2
Construction	Low loss resin / Strengthened saggital seam


It is mounted on the base table, which holds the robotic positioner. Both mechanical and laser-based

registration systems are utilised to register the phantom position in relationship to the robot co-ordinate system. In the SARA2 implementation, the SAM phantom is mounted on a supporting table made of low dielectric loss material, which includes mounting brackets for DUT positioners, dipole holders and (optionally) a shelf for supporting larger devices like laptop computers.

4.2.3.2 Box phantom

The box phantom used for body testing and for validation is manufactured from Perspex.

IXB – 070 Specification and characterisation parameters

	Constructional details	
	Internal dimensions:	200mm x 200mm x 200mm
	Thickness of base:	2mm +/- 0.2mm
	Wall thickness:	4mm
	Material:	PMMA
	Frequency range	300MHz – 6GHz
	Dielectric properties	Relative permittivity 2.7 Loss tangent <0.02



Tissue-simulant volume required for 150mm depth (6 litres)

4.2.3.3 Simulant liquids

Simulant liquids that are used for testing at frequencies of PCS 1900MHz, which are made mainly of sugar, salt and water solutions may be left in the phantoms. Approximately 7litres are needed for an upright head compared to about 7litres for a horizontal bath phantom.

Ingredients (% by weight)	Frequency(MHz)	
	800	
Tissue Type	Head	Body
Water	40.92	56.0
Salt(NaCl)	1.48	0.76
Sugar	56.5	41.76
HEC	1	1.21
Bacterial de	0.0	0.0
DGBE	0.0	0.0
Acticide SPX	0.1	0.27
Dielectric Constant	41.44	52.99
Conductivity (S/m)	0.99	1.12

4.2.4 SAR measurement procedure




Channel	Left				Right			
	Cheek		Tilt		Cheek		Tilt	
	Retracted	Extended	Retracted	Extended	Retracted	Extended	Retracted	Extended
Mode 1:								
High			S2(-1.4dB)	S2(-0.4dB)			S2(-2.2dB)	S2(-1.4dB)
Middle	S1(-4dB)	S1(-4dB)	S1(-1.5dB)	S1(-0.5dB)	S1(-5dB)	S1(-5dB)	S1(-2.5dB)	S1(-1.5dB)
Low			S2(-1.3dB)	S2(-0.7dB)			S2(-2.7dB)	S2(-0.6dB)
Mode 2:								
High			S2(-2.7dB)	S2(-1.1dB)				
Middle	S1(-5dB)	S1(-5dB)	S1(-2.5dB)	S1(-1dB)	S1(-6dB)	S1(-6dB)	S1(-5dB)	S1(-5dB)
Low			S2(-2.2dB)	S2(-0.8dB)				

After an area scan has been done at a fixed distance of 8mm from the surface of the phantom on the source side, a 3D scan is set up around the location of the maximum spot SAR. First, a point within the scan area is visited by the probe and a SAR reading taken at the start of testing. At the end of testing, the probe is returned to the same point and a second reading is taken. Comparison between these start and end readings enables the power drift during measurement to be assessed.

Above is the scanning procedure flow chart and table from the IEEE P2.3528 standard. This is the procedure for which all compliant testing should be carried out to ensure that all variations of the device position and transmission behaviour are tested.

4.2.5 Validation testing using box phantoms

The following procedure, recommended for performing validation tests using box phantoms is based on the procedures described in the draft IEEE standard P1528. Setup according to the setup diagram below :



With the SG and Amp and with directional coupler in place, set up the source signal at the relevant

frequency and use a power meter to measure the power at the end of the SMA cable that you intend to connect to the balanced dipole. Adjust the SG to make this, say, 0.25W (24 dBm). If this level is too high to read directly with the power meter sensor, insert a calibrated attenuator (e.g. 10 or 20 dB) and make a suitable correction to the power meter reading.


Note 1: In this method, the directional coupler is used for monitoring rather than setting the exact feed power level. If, however, the directional coupler is used for power measurement, you should check the frequency range and power rating of the coupler and measure the coupling factor (referred to output) at the test frequency using a VNA.

Note 2: Remember that the use of a 3dB attenuator (as shown in Figure 8.1 of P1528) means that you need an RF amplifier of 2 times greater power for the same feed power. The other issue is the cable length. You might get up to 1dB of loss per meter of cable, so the cable length after the coupler needs to be quite short.

Note 3: For the validation testing done using CW signals, most power meters are suitable. However, if you are measuring the output of a modulated signal from either a signal generator or a handset, you must ensure that the power meter correctly reads the modulated signals.

4.2.5.1 Setting up the box phantom for validation testing

The main purpose of the box phantom is for validation of the system. By placing the box phantom in place of the upright head, using the box phantom dipole holder the system can now be used to check that the probe and software are giving accurate readings.



4.2.5.2 Equipments and results of validation testing

Equipments :

name	Type and specification
Signal generator	SML02
Directional coupler	450MHz-3GHz
Amplifier	3W 502(10-2500MHz)
Reference dipole	IXD-190 antenna
	IXD-090 antenna

Results :

Frequency	Target value (1g)	Test value (1g)
800	10.8	10.91

4.2.6 SARA2 Interpolation and Extrapolation schemes

SARA2 software contains support for both 2D cubic B-spline interpolation as well as 3D cubic B-spline interpolation. In addition, for extrapolation purposes, a general n-th order polynomial fitting routine is implemented following a singular value decomposition algorithm. A 4th order polynomial fit is used by default for data extrapolation, but a linear-logarithmic fitting function can be selected as an option. The polynomial fitting procedures have been tested by comparing the fitting coefficients generated by the SARA2 procedures with those obtained using the polynomial fit functions of Microsoft Excel when applied to the same test input data.

4.2.7 Interpolation of 2D area scan

The 2D cubic B-spline interpolation is used after the initial area scan at fixed distance from the phantom shell wall. The initial scan data are collected with approx. 10mm spatial resolution and spline interpolation is used to find the location of the local maximum to within a 1mm resolution for positioning the subsequent 3D scanning.

4.2.8 Extrapolation of 3D scan

For the 3D scan, data are collected on a spatially regular 3D grid having (by default) 6.4 mm steps in the lateral dimensions and 3.5 mm steps in the depth direction (away from the source). SARA2 enables full control over the selection of alternative step sizes in all directions.

The digitised shape of the head is available to the SARA2 software, which decides which points in the 3D array are sufficiently well within the shell wall to be 'visited' by the SAR probe. After the data collection, the data are extrapolated in the depth direction to assign values to points in the 3D array closer to the shell wall. A notional extrapolation value is also assigned to the first point outside the shell wall so that subsequent interpolation schemes will be applicable right up to the shell wall boundary.

4.2.9 Interpolation of 3D scan and volume averaging

The procedure used for defining the shape of the volumes used for SAR averaging in the SARA2 software follow the method of adapting the surface of the 'cube' to conform with the curved inner surface of the phantom. This is called, here, the conformal scheme.

For each row of data in the depth direction, the data are extrapolated and interpolated to less than 1mm spacing and average values are calculated from the phantom surface for the row of data over distances corresponding to the requisite depth for 10g and 1g cubes. This results in two 2D arrays of data, which are then cubic B-spline interpolated to sub mm lateral resolution. A search routine then moves an

averaging square around through the 2D array and records the maximum value of the corresponding 1g and 10g volume averages. For the definition of the surface in this procedure, the digitized position of the head shell surface is used for measurement in head-shaped phantoms. For measurements in rectangular, box phantoms, the distance between the phantom wall and the closest set of gridded data points is entered into the software. For measurements in box-shaped phantoms, this distance is under the control of the user. The effective distance must be greater than 2.5mm as this is the tip-sensor distance and to avoid interface proximity effects, it should be at least 5mm. A value of 6 or 8mm is recommended. This distance is called **dbe**.

For automated measurements inside the head, the distance cannot be less than 2.5mm, which is the radius of the probe tip and to avoid interface proximity effects, a minimum clearance distance of x mm is retained. The actual value of **dbe** will vary from point to point depending upon how the spatially regular 3D grid points fit within the shell. The greatest separation is when a grid point is just not visited due to the probe tip dimensions. In this case the distance could be as large as the step-size plus the minimum clearance distance (i.e with $x=5$ and a step size of 3.5, **dbe** will be between 3.5 and 8.5mm).

The default step size (**dstep**) used is 3.5mm, but this is under user-control. The compromise is with time of scan, so it is not practical to make it much smaller or scan times become long and power-drop influences become larger.

The robot positioning system specification for the repeatability of the positioning (**dss**) is ± 0.04 mm.

The phantom shell is made by an industrial moulding process from the CAD files of the SAM shape, with both internal and external moulds. For the upright phantoms, the external shape is subsequently digitized on a Mitutoyo CMM machine (Euro an ultrasonic sensor indicate that the shell thickness (**dph**) away from the ear is 2.0 ± 0.1 mm. The ultrasonic measurements were calibrated using additional mechanical measurements on available cut surfaces of the phantom shells. See support document IXS-020x.

For the upright phantom, the alignment is based upon registration of the rotation axis of the phantom on its 253mm diameter baseplate bearing and the position of the probe axis when commanded to go to the axial position. A laser alignment tool is provided (procedure detailed elsewhere). This enables the registration of the phantom tip (**dmis**) to be assured to within approx. 0.2mm. This alignment is done with reference to the actual probe tip after installation and probe alignment. The rotational positioning of the phantom is variable – offering advantages for special studies, but locating pins ensure accurate repositioning at the principal positions (LH and RH ears).



4.2.10 Probe anisotropy and boundary proximity influence correction software (Virtual Probe Miniaturization VPM software)

Indexsar Report IXS0223 provides a background to the factors affecting measurements at high frequencies when using SAR probes of size 8 – 5mm tip diameter. Although the Indexsar probes are at the smaller end of this range, SAR probes are not isotropic in 5GHz phantom field gradients and ad

1) At >5GHz, the SAR field decays to 1/e of its value within 3-4mm of the surface of a phantom with a source adjacent. So, measurements are significantly affected by small errors in the separation distances employed between the probe and the phantom surface. The distance between the probe tip and the plane of the sensors should be allowed for using the same value as that declared in the probe calibration document. Distances between the probe tip and phantom surface should be measured accurately to 0.1mm. The best way to assure this is to use the robot to position the probe in light contact with the phantom wall and then to withdraw the probe by the selected amount under robot control.

2) The preferred test geometry at 5GHz is for testing at the bottom of an open phantom. If tests at the side of a phantom are performed, it will be necessary to apply VPM corrections as described below. In either case, careful monitoring of probe spacing from the phantom is required. Probe isotropy is improved for measuring fields polarized either normal to or parallel to the probe axis. If the source polarization is known, this arrangement should be established, if possible.

3) The probe calibration factors including boundary correction terms should be carefully entered from the calibration document. The probe calibration factors require that the probe be oriented in a known rotational position. The red spot on the Indexsar probe should be aligned facing away from the robot arm.

4) The latest SARA2 software (VPM editions) contain support for correcting for probe anisotropy in strong field gradients and include a procedure for correcting for boundary proximity influences. As noted above, the probe has to be oriented in a given rotational position and some familiarity with the new measurement procedures is necessary. The calculations can be performed either with or without the extended correction schemes applied.

5) If boundary corrections are used, it may be preferable to go rather closer to the phantom surface than is usually recommended and to perform scans using small steps between the measurement planes so that good data on the SAR profiles are collected within the first 10mm of the phantom depth.

5 CHARACTERISTICS OF THE TEST

5.1 Applicable Limit Regulations

47CFR § 2.1093: Radiofrequency Radiation Exposure Evaluation: Portable Devices

FCC OET Bulletin 65(Edition 97-01), Supplement C(Edition 01-01): Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields

ANSI C95.1–1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

It specifies the maximum exposure limit of **1.6 W/kg** as averaged over any 1 gram of tissue for portable devices being used within 20 cm of the user in the uncontrolled environment.

5.2 Applicable Measurement Standards

IEEE 1528–2003: Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques.

They specify the measurement method for demonstration of compliance with the SAR limits for such equipments.

6 LABORATORY ENVIRONMENT

Table: The Ambient Conditions during SAR Test

Temperature	Min. = 15 ° C, Max. = 30 ° C
Relative humidity	Min. = 30%, Max. = 70%
Ground system resistance	< 0.5
Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards.	

7 TEST RESULTS

7.1 Dielectric Performance

The measured 1-gram averaged SAR values of the device against the head and the body are provided in Tables 1 and 2 respectively. The humidity and ambient temperature of test facility were 49% ~59% and 21.1 °C ~21.8°C respectively. The SAM head phantom (SN 0380 SH) were full of the head tissue simulating liquid. The depth of the body tissue was 15.1cm. The distance between the back of the device and the bottom of the flat phantom is 1.5cm. A base station simulator was used to control the device during the SAR measurement. The phone was supplied with full-charged battery for each measurement.

For head measurement, the device was tested at the lowest, middle and highest frequencies in the transmit band.

Table 1: Dielectric Performance of Head Tissue Simulating Liquid

Temperature: 21.1~21.8 ° C, humidity: 49~59%.			
/	Frequency	Permittivity	Conductivity (S/m)
Target value	800 MHZ	41.5	0.97
Validation value (Mar 4)	800 MHZ	41.23	0.959

For body-worn measurements, the device was tested against flat phantom representing the user body. Under measurement phone was put on in the belt holder.

Table 2: Dielectric Performance of Body Tissue Simulating Liquid

Temperature: 21.1~21.8 ° C, humidity: 49~59%.			
/	Frequency	Permittivity	Conductivity (S/m)
Target value	800 MHz	55.0	1.05
Validation value (Mar 1)	800 MHz	55.21	1.047

7.2 Summary of Measurement Results (CDMA 800 MHz Band)

Table 3: SAR Values (CDMA 800 MHz Band), Measured against the head.

Temperature: 21.1~21.8 ° C, humidity: 49~59%		
Limit of SAR (W/kg)	1 g Average	
	1.6	
Test Case	Measurement Result	
	1 g Average (W/kg)	Power level (dBm)
Left head, Touch cheek, Top frequency	1.394	21.80
Left head, Touch cheek, Mid frequency	1.417	23.12
Left head, Touch cheek, Bottom frequency	1.432	20.45
Left head, Tilt 15 Degree, Top frequency	0.843	21.80
Left head, Tilt 15 Degree, Mid frequency	0.787	23.12
Left head, Tilt 15 Degree, Bottom frequency	1.045	20.45
Right head, Touch cheek, Top frequency	1.072	21.80
Right head, Touch cheek, Mid frequency	1.183	23.12
Right head, Touch cheek, Bottom frequency	0.593	20.45
Right head, Tilt 15 Degree, Top frequency	0.556	21.80
Right head, Tilt 15 Degree, Mid frequency	0.767	23.12
Right head, Tilt 15 Degree, Bottom frequency	0.364	20.45

Table 4: SAR Values (CDMA 800 MHz Band), Measured against the body

Temperature: 21.1~21.8 ° C, humidity: 49~59%		
Limit of SAR (W/kg)	1 g Average	
	1.6	
Test Case	Measurement Result	
	1 g Average (W/kg)	Power level (dBm)
Side, Top frequency	0.659	21.80
Side, Mid frequency	0.916	23.12
Side, Bottom frequency	0.850	20.45

7.3 Conclusion

Localized Specific Absorption Rate (SAR) of this portable wireless device has been measured in all cases requested by the relevant standards cited in Clause 5.2 of this report. Maximum localized SAR is **below** exposure limits specified in the relevant standards cited in Clause 5.1 of this test report.

8 Measurement Uncertainty

No	Uncertainty Component	Type	Uncertainty Value (%)	Probability Distribution	k	c_i	Standard Uncertainty (%) $u_i(\%)$	Degree of freedom V_{eff} or v_i
Measurement System								
1	- Probe Calibration	B	3.6	N	1	1	3.60	∞
2	- Axial isotropy	B	4.23	R	$\sqrt{3}$	$\sqrt{1-cp}$	0.00	∞
3	- Hemispherical Isotropy	B	10.7	R	$\sqrt{3}$	\sqrt{cp}	6.18	∞
4	- Boundary Effect	B	1.7	R	$\sqrt{3}$	1	0.98	∞
5	- Linearity	B	2.98	R	$\sqrt{3}$	1	1.69	∞
6	- System Detection Limits	B	0.00	R	$\sqrt{3}$	1	0.00	∞
7	- Readout Electronics	B	0.00	N	1	1	0.00	∞
8	- Response Time	B	0.00	R	$\sqrt{3}$	1	0.00	∞
9	- Integration Time	B	0.00	R	$\sqrt{3}$	1	0.00	∞
10	- RF Ambient Conditions	B	0.00	R	$\sqrt{3}$	1	0.00	∞
11	- Probe Position Mechanical tolerance	B	1.14	R	$\sqrt{3}$	1	0.33	∞
12	- Probe Position with respect to Phantom Shell	B	2.86	R	$\sqrt{3}$	1	0.83	∞
13	- Extrapolation, Interpolation and Integration Algorithms for Max. SAR evaluation	B	3.6	R	$\sqrt{3}$	1	2.08	∞
Uncertainties of the DUT								
14	- Position of the DUT	A	0.00	N	1	1	0.00	0
15	- Holder of the DUT	A	0.00	N	1	1	0.00	0
16	- Output Power Variation – SAR drift measurement	B	5.0	R	$\sqrt{3}$	1	2.89	∞

Phantom and Tissue Parameters								
17	- Phantom Uncertainty(shape and thickness tolerances)	B	1.43	R	$\sqrt{3}$	1	0.83	∞
18	- Liquid Conductivity Target – tolerance	B	5.0	R	$\sqrt{3}$	0.7	2.02	∞
19	- Liquid Conductivity – measurement Uncertainty)	B	2.0	R	$\sqrt{3}$	0.7	0.81	∞
20	- Liquid Permittivity Target tolerance	B	5.0	R	$\sqrt{3}$	0.6	1.73	∞
21	- Liquid Permittivity – measurement uncertainty	B	1.0	R	$\sqrt{3}$	0.6	0.35	∞
Combined Standard Uncertainty				RSS			±8.95%	
Expanded uncertainty (Confidence interval of 95 %)				K= 2.003935			±17.9%	

9 MAIN TEST INSTRUMENTS

No.	EQUIPMENT	TYPE	Due Date
1	E-Field SAR Probe	IXP-050 (SN 0177)	2006-03-23
2	Six-axis AC Servo industrial robot	RV-2A (SN AN406018)	2006-03-23
3	Mobile Phone Tester	4405 (SN 0811211)	2006-03-23
4	System Validation Dipole 800MHZ	IXD-090 (SN 0093)	2006-03-23
5	Probe Amplifier and PC Interface	IFA-010 (SN 0027)	2006-03-23
6	SAM Head Phantom	SN 0380 SH	2006-03-23
7	Box Phantom	IXB-070	2006-03-23



ANNEX A
of
ShenZhen Electronic Product Quality Testing Center

CONFORMANCE TEST REPORT FOR
HUMAN EXPOSURE TO ELECTROMAGNETIC FIELDS

SAR06_010

Guangzhou Jineng Telecommunication Industrial Co.,Ltd

CDMA 1X mobile phone

Accreditation Certificate

This Annex consists of 2 pages
Date of Report: 2006-3-10





**ACCREDITATION CERTIFICATE
OF CHINA NATIONAL ACCREDITATION BOARD
FOR LABORATORIES
(No.L1659)**

This is to certify that

Shenzhen Electronic Product Quality Testing Center
Electronic Testing Building, Shahe Road, Xili, Nanshan District,
Shenzhen, Guangdong, China

has been assessed and proved to be in compliance with CNAL/AC01:
2003 Accreditation Criteria for Testing and Calibration Laboratories
(identical to ISO/IEC17025: 1999 *General Requirements for the
Competence of Testing and Calibration Laboratories*).

Accreditation scope of the laboratory is listed in the attachment.

Date of Issue: 2004.10.09

Date of Expiry: 2009.10.08

Wei Hao

Secretary General of CNAL



ANNEX B
of
ShenZhen Electronic Product Quality Testing Center

CONFORMANCE TEST REPORT FOR
HUMAN EXPOSURE TO ELECTROMAGNETIC FIELDS

SAR06_010

Guangzhou Jineng Telecommunication Industrial Co.,Ltd

CDMA 1X mobile phone

Type Name: T100

Hardware Version : P2.3

Software Version : 2.0.31.53.1

TEST LAYOUT

This Annex consists of 5 pages

Date of Report: 2006-3-10





Fig.1 SARA2 System Test Layout



Fig.2 The depth of head tissue in SAM



Fig.3 EUT Left Head Touch Cheek Position



Fig.4 EUT Left Head Tilt15 Position



Fig.5 EUT Right Head Touch Cheek Position



Fig.6 EUT Right Head Tilt15 Position



Fig.7 spacer 1.5cm




Fig.8 the depth of body tissue




Fig.9 Side Position



ANNEX C
of
ShenZhen Electronic Product Quality Testing Center

CONFORMANCE TEST REPORT FOR
HUMAN EXPOSURE TO ELECTROMAGNETIC FIELDS

SAR06_010

Guangzhou Jineng Telecommunication Industrial Co.,Ltd

CDMA 1X mobile phone

Type Name: T100

Hardware Version : P2.3

Software Version : 2.0.31.53.1

Sample Photographs

This Annex consists of 3 pages

Date of Report: 2006-3-10



No. SAR06--010

1. Photograph of the Equipment under Test

1.1. Appearance



No. SAR06--010

1.2 Inside





ANNEX D
of
ShenZhen Electronic Product Quality Testing Center

CONFORMANCE TEST REPORT FOR
HUMAN EXPOSURE TO ELECTROMAGNETIC FIELDS

SAR06_010

Guangzhou Jineng Telecommunication Industrial Co.,Ltd

CDMA 1X mobile phone

Type Name: T100

Hardware Version : P2.3

Software Version : 2.0.31.53.1

Graph Test Results


This Annex consists of 16 pages

Date of Report : 2006-3-10




SAR Test CDMA 800 LH_TouchCheek (Bottom Channel)

System / software:	SARA2 / 2.40 VPM	Input Power Drift:	-0.03dB
Date / Time:	2006-3-4 15:05:39	DUT Battery Model/No:	
Filename:	JinPeng-T100_800LH_TouchCheek_B.txt	Probe Serial Number:	0177
Ambient Temperature:	21.6°C	Liquid Simulant:	Head tissue
Device Under Test:	JinPeng-T100	Relative Permittivity:	41.23
Relative Humidity:	58%	Conductivity:	.959
Phantom S/No:	Head_380SH.csv	Liquid Temperature:	21.0°C
Phantom Rotation:	0°	Max SAR Y-axis Location:	-25.83 mm
DUT Position:	JinPeng-800LH_TouchCheek_B	Max SAR Z-axis Location:	-145.00 mm
Antenna Configuration:	Build inside	Max E Field:	39.59 V/m
Test Frequency:	800MHz	SAR 1g:	1.432 W/kg
Air Factors:	417.2 / 368.0 / 414.8	SAR 10g:	1.011 W/kg
Conversion Factors:	.286 / .286 / .286	SAR Start:	0.829 W/kg
Type of Modulation:	CDMA	SAR End:	0.821 W/kg
Modn. Duty Cycle:		SAR Drift during Scan:	-1.01 %
Diode Compression Factors (V*200):	20 / 20 / 20	Probe battery last changed:	20/05/05
Input Power Level:	-21.35dBm	Extrapolation:	poly4




SAR Test CDMA 800 LH_TouchCheek (Middle Channel)

System / software:	SARA2 / 2.40 VPM	Input Power Drift:	-0.07dB
Date / Time:	2006-3-4 14:53:40	DUT Battery Model/No:	
Filename:	JinPeng-T100_800LH_TouchCheek_M.txt	Probe Serial Number:	0177
Ambient Temperature:	21.6°C	Liquid Simulant:	Head tissue
Device Under Test:	JinPeng-T100	Relative Permittivity:	41.23
Relative Humidity:	58%	Conductivity:	.959
Phantom S/No:	Head_380SH.csv	Liquid Temperature:	21.0°C
Phantom Rotation:	0°	Max SAR Y-axis Location:	-27.67 mm
DUT Position:	JinPeng-800LH_TouchCheek_M	Max SAR Z-axis Location:	-145.00 mm
Antenna Configuration:	Build inside	Max E Field:	39.64 V/m
Test Frequency:	800MHz	SAR 1g:	1.417 W/kg
Air Factors:	417.2 / 368.0 / 414.8	SAR 10g:	1.029 W/kg
Conversion Factors:	.286 / .286 / .286	SAR Start:	0.851 W/kg
Type of Modulation:	CDMA	SAR End:	0.832 W/kg
Modn. Duty Cycle:		SAR Drift during Scan:	-2.20 %
Diode Compression Factors (V*200):	20 / 20 / 20	Probe battery last changed:	20/05/05
Input Power Level:	-22.29dBm	Extrapolation:	poly4




SAR Test CDMA 800 LH_TouchCheek (Top Channel)

System / software:	SARA2 / 2.40 VPM	Input Power Drift:	-0.03dB
Date / Time:	2006-3-4 14:40:47	DUT Battery Model/No:	
Filename:	JinPeng-T100_800LH_TouchCheek_T.txt	Probe Serial Number:	0177
Ambient Temperature:	21.7°C	Liquid Simulant:	Head tissue
Device Under Test:	JinPeng-T100	Relative Permittivity:	41.23
Relative Humidity:	58%	Conductivity:	.959
Phantom S/No:	Head_380SH.csv	Liquid Temperature:	21.0°C
Phantom Rotation:	0°	Max SAR Y-axis Location:	-25.83 mm
DUT Position:	JinPeng-800LH_TouchCheek_T	Max SAR Z-axis Location:	-145.00 mm
Antenna Configuration:	Build inside	Max E Field:	39.58 V/m
Test Frequency:	800MHz	SAR 1g:	1.394 W/kg
Air Factors:	417.2 / 368.0 / 414.8	SAR 10g:	1.033 W/kg
Conversion Factors:	.286 / .286 / .286	SAR Start:	0.844 W/kg
Type of Modulation:	CDMA	SAR End:	0.835 W/kg
Modn. Duty Cycle:		SAR Drift during Scan:	-1.05 %
Diode Compression Factors (V*200):	20 / 20 / 20	Probe battery last changed:	20/05/05
Input Power Level:	-20.70dBm	Extrapolation:	poly4




SAR Test CDMA 800 LH_Tilt15 (Bottom Channel)

System / software:	SARA2 / 2.40 VPM	Input Power Drift:	0.03dB
Date / Time:	2006-3-4 15:18:26	DUT Battery Model/No:	
Filename:	JinPeng-T100_800LH_Tilt15_B.txt	Probe Serial Number:	0177
Ambient Temperature:	21.6°C	Liquid Simulant:	Head tissue
Device Under Test:	JinPeng-T100	Relative Permittivity:	41.23
Relative Humidity:	59%	Conductivity:	.959
Phantom S/No:	Head_380SH.csv	Liquid Temperature:	21.0°C
Phantom Rotation:	0°	Max SAR Y-axis Location:	-18.50 mm
DUT Position:	JinPeng-800LH_Tilt15_B	Max SAR Z-axis Location:	-139.00 mm
Antenna Configuration:	Build inside	Max E Field:	39.55 V/m
Test Frequency:	800MHz	SAR 1g:	1.045 W/kg
Air Factors:	417.2 / 368.0 / 414.8	SAR 10g:	0.626 W/kg
Conversion Factors:	.286 / .286 / .286	SAR Start:	0.505 W/kg
Type of Modulation:	CDMA	SAR End:	0.510 W/kg
Modn. Duty Cycle:		SAR Drift during Scan:	0.95 %
Diode Compression Factors (V*200):	20 / 20 / 20	Probe battery last changed:	20/05/05
Input Power Level:	-21.09dBm	Extrapolation:	poly4




SAR Test CDMA 800 LH_Tilt15 (Middle Channel)

System / software:	SARA2 / 2.40 VPM	Input Power Drift:	-0.07dB
Date / Time:	2006-3-4 15:32:03	DUT Battery Model/No:	
Filename:	JinPeng-T100_800LH_Tilt15_M.txt	Probe Serial Number:	0177
Ambient Temperature:	21.6°C	Liquid Simulant:	Head tissue
Device Under Test:	JinPeng-T100	Relative Permittivity:	41.23
Relative Humidity:	59%	Conductivity:	.959
Phantom S/No:	Head_380SH.csv	Liquid Temperature:	21.0°C
Phantom Rotation:	0°	Max SAR Y-axis Location:	-18.50 mm
DUT Position:	JinPeng-800LH_Tilt15_M	Max SAR Z-axis Location:	-139.00 mm
Antenna Configuration:	Build inside	Max E Field:	29.88 V/m
Test Frequency:	800MHz	SAR 1g:	0.787 W/kg
Air Factors:	417.2 / 368.0 / 414.8	SAR 10g:	0.558 W/kg
Conversion Factors:	.286 / .286 / .286	SAR Start:	0.449 W/kg
Type of Modulation:	CDMA	SAR End:	0.438 W/kg
Modn. Duty Cycle:		SAR Drift during Scan:	-2.41 %
Diode Compression Factors (V*200):	20 / 20 / 20	Probe battery last changed:	20/05/05
Input Power Level:	-22.79dBm	Extrapolation:	poly4




SAR Test CDMA 800 LH_Tilt15 (Top Channel)

System / software:	SARA2 / 2.40 VPM	Input Power Drift:	-0.09dB
Date / Time:	2006-3-4 15:55:47	DUT Battery Model/No:	
Filename:	JinPeng-T100_800LH_Tilt15_T.txt	Probe Serial Number:	0177
Ambient Temperature:	21.7°C	Liquid Simulant:	Head tissue
Device Under Test:	JinPeng-T100	Relative Permittivity:	41.23
Relative Humidity:	59%	Conductivity:	.959
Phantom S/No:	Head_380SH.csv	Liquid Temperature:	21.0°C
Phantom Rotation:	0°	Max SAR Y-axis Location:	-20.33 mm
DUT Position:	JinPeng-800LH_Tilt15_T	Max SAR Z-axis Location:	-139.00 mm
Antenna Configuration:	Build inside	Max E Field:	31.36 V/m
Test Frequency:	800MHz	SAR 1g:	0.843 W/kg
Air Factors:	417.2 / 368.0 / 414.8	SAR 10g:	0.617 W/kg
Conversion Factors:	.286 / .286 / .286	SAR Start:	0.504 W/kg
Type of Modulation:	CDMA	SAR End:	0.489 W/kg
Modn. Duty Cycle:		SAR Drift during Scan:	-3.05 %
Diode Compression Factors (V*200):	20 / 20 / 20	Probe battery last changed:	20/05/05
Input Power Level:	-19.44dBm	Extrapolation:	poly4




SAR Test CDMA 800 RH_TouchCheek (Bottom Channel)

System / software:	SARA2 / 2.40 VPM	Input Power Drift:	-0.11dB
Date / Time:	2006-3-4 11:53:39	DUT Battery Model/No:	
Filename:	JinPeng-T100_800RH_TouchCheek_B.txt	Probe Serial Number:	0177
Ambient Temperature:	21.8°C	Liquid Simulant:	Head tissue
Device Under Test:	JinPeng-T100	Relative Permittivity:	41.21
Relative Humidity:	55%	Conductivity:	.959
Phantom S/No:	Head_380SH.csv	Liquid Temperature:	21.1°C
Phantom Rotation:	180°	Max SAR Y-axis Location:	27.67 mm
DUT Position:	JinPeng-T100_800RH_TouchCheek_B	Max SAR Z-axis Location:	-140.50 mm
Antenna Configuration:	Build inside	Max E Field:	25.31 V/m
Test Frequency:	800MHz	SAR 1g:	0.593 W/kg
Air Factors:	417.2 / 368.0 / 414.8	SAR 10g:	0.409 W/kg
Conversion Factors:	.286 / .286 / .286	SAR Start:	0.301 W/kg
Type of Modulation:	CDMA	SAR End:	0.290 W/kg
Modn. Duty Cycle:		SAR Drift during Scan:	-3.47 %
Diode Compression Factors (V*200):	20 / 20 / 20	Probe battery last changed:	20/05/05
Input Power Level:	-19.66dBm	Extrapolation:	poly4




SAR Test CDMA 800 RH_TouchCheek (Middle Channel)

System / software:	SARA2 / 2.40 VPM	Input Power Drift:	-0.03dB
Date / Time:	2006-3-4 11:27:53	DUT Battery Model/No:	
Filename:	JinPeng-T100_800RH_TouchCheek_M.txt	Probe Serial Number:	0177
Ambient Temperature:	21.7°C	Liquid Simulant:	Head tissue
Device Under Test:	JinPeng-T100	Relative Permittivity:	41.21
Relative Humidity:	54%	Conductivity:	.959
Phantom S/No:	Head_380SH.csv	Liquid Temperature:	21.1°C
Phantom Rotation:	180°	Max SAR Y-axis Location:	27.67 mm
DUT Position:	JinPeng-T100_800RH_TouchCheek_M	Max SAR Z-axis Location:	-140.50 mm
Antenna Configuration:	Build inside	Max E Field:	35.74 V/m
Test Frequency:	800MHz	SAR 1g:	1.183 W/kg
Air Factors:	417.2 / 368.0 / 414.8	SAR 10g:	0.847 W/kg
Conversion Factors:	.286 / .286 / .286	SAR Start:	0.632 W/kg
Type of Modulation:	CDMA	SAR End:	0.627 W/kg
Modn. Duty Cycle:		SAR Drift during Scan:	-0.85 %
Diode Compression Factors (V*200):	20 / 20 / 20	Probe battery last changed:	20/05/05
Input Power Level:	-19.09dBm	Extrapolation:	poly4




SAR Test CDMA 800 RH_TouchCheek (Top Channel)

System / software:	SARA2 / 2.40 VPM	Input Power Drift:	0.01dB
Date / Time:	2006-3-4 11:40:14	DUT Battery Model/No:	
Filename:	JinPeng-T100_800RH_TouchCheek_T.txt	Probe Serial Number:	0177
Ambient Temperature:	21.7°C	Liquid Simulant:	Head tissue
Device Under Test:	JinPeng-T100	Relative Permittivity:	41.21
Relative Humidity:	54%	Conductivity:	.959
Phantom S/No:	Head_380SH.csv	Liquid Temperature:	21.1°C
Phantom Rotation:	180°	Max SAR Y-axis Location:	27.67 mm
DUT Position:	JinPeng-T100_800RH_TouchCheek_T	Max SAR Z-axis Location:	-140.50 mm
Antenna Configuration:	Build inside	Max E Field:	34.03 V/m
Test Frequency:	800MHz	SAR 1g:	1.072 W/kg
Air Factors:	417.2 / 368.0 / 414.8	SAR 10g:	0.760 W/kg
Conversion Factors:	.286 / .286 / .286	SAR Start:	0.568 W/kg
Type of Modulation:	CDMA	SAR End:	0.568 W/kg
Modn. Duty Cycle:		SAR Drift during Scan:	0.08 %
Diode Compression Factors (V*200):	20 / 20 / 20	Probe battery last changed:	20/05/05
Input Power Level:	-19.04dBm	Extrapolation:	poly4




SAR Test CDMA 800 RH_Tilt15 (Bottom Channel)

System / software:	SARA2 / 2.40 VPM	Input Power Drift:	-0.05dB
Date / Time:	2006-3-4 13:55:15	DUT Battery Model/No:	
Filename:	JinPeng-T100_800RH_Tilt15_B.txt	Probe Serial Number:	0177
Ambient Temperature:	21.8°C	Liquid Simulant:	Head tissue
Device Under Test:	JinPeng-T100	Relative Permittivity:	41.21
Relative Humidity:	55%	Conductivity:	.959
Phantom S/No:	Head_380SH.csv	Liquid Temperature:	21.1°C
Phantom Rotation:	180°	Max SAR Y-axis Location:	20.33 mm
DUT Position:	JinPeng-T100_800RH_Tilt15_B	Max SAR Z-axis Location:	-134.50 mm
Antenna Configuration:	Build inside	Max E Field:	20.98 V/m
Test Frequency:	800MHz	SAR 1g:	0.364 W/kg
Air Factors:	417.2 / 368.0 / 414.8	SAR 10g:	0.250 W/kg
Conversion Factors:	.286 / .286 / .286	SAR Start:	0.192 W/kg
Type of Modulation:	CDMA	SAR End:	0.189 W/kg
Modn. Duty Cycle:		SAR Drift during Scan:	-1.62 %
Diode Compression Factors (V*200):	20 / 20 / 20	Probe battery last changed:	20/05/05
Input Power Level:	-19.43dBm	Extrapolation:	poly4




SAR Test CDMA 800 RH_Tilt15 (Middle Channel)

System / software:	SARA2 / 2.40 VPM	Input Power Drift:	-0.05dB
Date / Time:	2006-3-4 14:09:52	DUT Battery Model/No:	
Filename:	JinPeng-T100_800RH_Tilt15_M.txt	Probe Serial Number:	0177
Ambient Temperature:	21.8°C	Liquid Simulant:	Head tissue
Device Under Test:	JinPeng-T100	Relative Permittivity:	41.21
Relative Humidity:	55%	Conductivity:	.959
Phantom S/No:	Head_380SH.csv	Liquid Temperature:	21.1°C
Phantom Rotation:	180°	Max SAR Y-axis Location:	20.33 mm
DUT Position:	JinPeng-T100_800RH_Tilt15_M	Max SAR Z-axis Location:	-136.00 mm
Antenna Configuration:	Build inside	Max E Field:	29.73 V/m
Test Frequency:	800MHz	SAR 1g:	0.767 W/kg
Air Factors:	417.2 / 368.0 / 414.8	SAR 10g:	0.537 W/kg
Conversion Factors:	.286 / .286 / .286	SAR Start:	0.412 W/kg
Type of Modulation:	CDMA	SAR End:	0.406 W/kg
Modn. Duty Cycle:		SAR Drift during Scan:	-1.44 %
Diode Compression Factors (V*200):	20 / 20 / 20	Probe battery last changed:	20/05/05
Input Power Level:	-18.36dBm	Extrapolation:	poly4




SAR Test CDMA 800 RH_Tilt15 (Top Channel)

System / software:	SARA2 / 2.40 VPM	Input Power Drift:	-0.02dB
Date / Time:	2006-3-4 14:22:14	DUT Battery Model/No:	
Filename:	JinPeng-T100_800RH_Tilt15_T.txt	Probe Serial Number:	0177
Ambient Temperature:	21.8°C	Liquid Simulant:	Head tissue
Device Under Test:	JinPeng-T100	Relative Permittivity:	41.21
Relative Humidity:	54%	Conductivity:	.959
Phantom S/No:	Head_380SH.csv	Liquid Temperature:	21.1°C
Phantom Rotation:	180°	Max SAR Y-axis Location:	22.17 mm
DUT Position:	JinPeng-T100_800RH_Tilt15_T	Max SAR Z-axis Location:	-137.50 mm
Antenna Configuration:	Build inside	Max E Field:	25.14 V/m
Test Frequency:	800MHz	SAR 1g:	0.556 W/kg
Air Factors:	417.2 / 368.0 / 414.8	SAR 10g:	0.384 W/kg
Conversion Factors:	.286 / .286 / .286	SAR Start:	0.287 W/kg
Type of Modulation:	CDMA	SAR End:	0.285 W/kg
Modn. Duty Cycle:		SAR Drift during Scan:	-0.75 %
Diode Compression Factors (V*200):	20 / 20 / 20	Probe battery last changed:	20/05/05
Input Power Level:	-19.51dBm	Extrapolation:	poly4




SAR Test CDMA 800 Side (Bottom Channel)

System / software:	SARA2 / 2.40 VPM	Input Power Drift:	-0.10dB
Date / Time:	2006-3-1 14:07:59	DUT Battery Model/No:	
Filename:	JinPeng-T100_800Body_Side_B.txt	Probe Serial Number:	0177
Ambient Temperature:	21.7°C	Liquid Simulant:	Body tissue
Device Under Test:	JinPeng-T100	Relative Permittivity:	55.21
Relative Humidity:	54%	Conductivity:	1.047
Phantom S/No:	HeadBox75mm.csv	Liquid Temperature:	21.1°C
Phantom Rotation:	0°	Max SAR X-axis Location:	-1.71 mm
DUT Position:	JinPeng-T100_800Body_Side_B	Max SAR Y-axis Location:	1.71 mm
Antenna Configuration:	Build inside	Max E Field:	25.90 V/m
Test Frequency:	800MHz	SAR 1g:	0.850 W/kg
Air Factors:	417 / 368 / 414	SAR 10g:	0.592 W/kg
Conversion Factors:	.271 / .271 / .271	SAR Start:	0.228 W/kg
Type of Modulation:	CDMA	SAR End:	0.220 W/kg
Modn. Duty Cycle:		SAR Drift during Scan:	-3.27 %
Diode Compression Factors (V*200):	20 / 20 / 20	Probe battery last changed:	20/05/05
Input Power Level:	-22.20dBm	Extrapolation:	poly4



SAR Test CDMA 800 Side (Middle Channel)

System / software:	SARA2 / 2.40 VPM	Input Power Drift:	-0.03dB
Date / Time:	2006-3-1 14:24:32	DUT Battery Model/No:	
Filename:	JinPeng-T100_800Body_Side_M.txt	Probe Serial Number:	0177
Ambient Temperature:	21.6°C	Liquid Simulant:	Body tissue
Device Under Test:	JinPeng-T100	Relative Permittivity:	55.21
Relative Humidity:	54%	Conductivity:	1.047
Phantom S/No:	HeadBox75mm.csv	Liquid Temperature:	21.1°C
Phantom Rotation:	0°	Max SAR X-axis Location:	-1.71 mm
DUT Position:	JinPeng-T100_800Body_Side_M	Max SAR Y-axis Location:	1.71 mm
Antenna Configuration:	Build inside	Max E Field:	26.80 V/m
Test Frequency:	800MHz	SAR 1g:	0.916 W/kg
Air Factors:	417 / 368 / 414	SAR 10g:	0.633 W/kg
Conversion Factors:	.271 / .271 / .271	SAR Start:	0.240 W/kg
Type of Modulation:	CDMA	SAR End:	0.238 W/kg
Modn. Duty Cycle:		SAR Drift during Scan:	-1.09 %
Diode Compression Factors (V*200):	20 / 20 / 20	Probe battery last changed:	20/05/05
Input Power Level:	-21.85dBm	Extrapolation:	poly4



SAR Test CDMA 800 Side (Top Channel)

System / software:	SARA2 / 2.40 VPM	Input Power Drift:	-0.01dB
Date / Time:	2006-3-1 14:35:09	DUT Battery Model/No:	
Filename:	JinPeng-T100_800Body_Side_T.txt	Probe Serial Number:	0177
Ambient Temperature:	21.6°C	Liquid Simulant:	Body tissue
Device Under Test:	JinPeng-T100	Relative Permittivity:	55.21
Relative Humidity:	54%	Conductivity:	1.047
Phantom S/No:	HeadBox75mm.csv	Liquid Temperature:	21.1°C
Phantom Rotation:	0°	Max SAR X-axis Location:	-3.43 mm
DUT Position:	JinPeng-T100_800Body_Side_T	Max SAR Y-axis Location:	0.00 mm
Antenna Configuration:	Build inside	Max E Field:	23.27 V/m
Test Frequency:	800MHz	SAR 1g:	0.659 W/kg
Air Factors:	417 / 368 / 414	SAR 10g:	0.453 W/kg
Conversion Factors:	.271 / .271 / .271	SAR Start:	0.177 W/kg
Type of Modulation:	CDMA	SAR End:	0.176 W/kg
Modn. Duty Cycle:		SAR Drift during Scan:	-0.24 %
Diode Compression Factors (V*200):	20 / 20 / 20	Probe battery last changed:	20/05/05
Input Power Level:	-21.03dBm	Extrapolation:	poly4

