

Report No.	AA515581
Specifications	FCC Part 15.231(c), Certification
Test Method	ANSI C63.4 1992
Applicant address	9F-3, No. 16, Jain Ba Rd, Chung Ho City, Taipei Hsien, Taiwan 235, R.O.C.
Applicant	TopSeed Technology Corp.
Items tested	TopSeed RF Remote Pointer – BD Type
Model No.	TSBD-401 (Sample # AA5581)
Product No.	RCBD0002-402
Results	<b>Compliance</b> (As detailed within this report)
Date	07/17/2002 (month / day / year) (Sample received) 07/18/2002 (month / day / year) (Test)
Prepared by	Project Engineer  _____
Authorized by	General Manager (Frank Tsai)  _____
Issue date	July 31, 2002 (month / day / year)
<b>Modifications</b>	<b>None</b>
Tested by	Training Research Co., Ltd.
Office at	255 Nanyang Street, Shijr, Taipei Hsien 221, Taiwan, R.O.C.
Chamber at	255 Nanyang Street, Shijr, Taipei Hsien 221, Taiwan, R.O.C.

**Conditions of issue:**

- (1) **This test report shall not be reproduced except in full, without written approval of TRC. And the test result contained within this report only relate to the sample submitted for testing.**
- (2) **This report must not be used by the client to claim product endorsement by NVLAP or any agency of U.S. Government.**

**FCC ID: PTITSBD-401**

---

Report No.: AA515581 (Version 2)

Training Research Co., Ltd., TEL: 886-2-26935155, Fax: 886-2-26934440

## ***Table of Contents***

<b>Tables of Contents .....</b>	<b>2</b>
<b>Chapter 1 General .....</b>	<b>4</b>
1.1 Introduction .....	4
1.2 Description of EUT .....	4
1.3 Description of Support Equipment .....	4
1.4 Test Procedure .....	5
1.5 Location of the Test Site .....	5
1.6 General Test Condition .....	5
<b>Chapter 2 Transmitter Duty Cycle Measurements .....</b>	<b>6</b>
2.1 Test Condition and Setup .....	6
2.2 List of Instruments .....	6
2.3 Test Configuration .....	7
2.4 Test Result .....	7
<b>Chapter 3 Transmitter Bandwidth Measurements .....</b>	<b>9</b>
3.1 Test Condition and Setup .....	9
3.2 Test Result .....	9
<b>Chapter 4 Conducted Emissions Measurements .....</b>	<b>11</b>
<b>Chapter 5 Radiated Emissions Measurements .....</b>	<b>12</b>
5.1 General Configuration .....	12
5.2 Test Condition and Setup .....	12
5.3 List of Test Instruments .....	14
5.4 Test Instruments Configuration .....	15
5.5 Test Result of Radiated Emissions .....	17

## **Table**

Table 1	Open Field Radiated Emissions For 30MHz ~ 1GHz [HORIZONTAL]	17
Table 2	Open Field Radiated Emissions For 30MHz ~ 1GHz [VERTICAL]	17
Table 3	Open Field Radiated Emissions For 1GHz ~ 18GHz [HORIZONTAL]	18
Table 4	Open Field Radiated Emissions For 1GHz ~ 18GHz [VERTICAL]	18

## Chapter 1 General

### 1.1 Introduction

The following measurement report is submitted on behalf of applicant in support of an International Periodic Radiator certification with *Part 2 Subpart J and Part 15 Subpart A and C* of the Commission's Rules and Regulations.

### 1.2 Description of EUT

<b>EUT</b>	:	TopSeed RF Remote Pointer – BD Type
<b>Model No.</b>	:	TSBD-401
<b>Product No.</b>	:	RCBD0002-402
<b>FCC ID</b>	:	PTITSBD-401
<b>Frequency Range</b>	:	Operated in 433.92 MHz
<b>Power Type</b>	:	Powered by 3V batteries
<b>Applicant</b>	:	TopSeed Technology Corp. 9F-3, No. 16, Jain Ba Rd, Chung Ho City, Taipei Hsien, Taiwan 235, R.O.C.

The fundamental frequency of transmitter emitted is due to a press on button of the EUT. The emitting time of fundamental frequency is less than 5 seconds is pursuant to FCC Part 15.231(a). There are security codes for avoiding the possibility of duplicating codes in adjacent systems. The coding must be matching with the companion receiver.

While testing the EUT was adjusted to transmit the maximum emission.

### 1.3 Description of Support Equipment

The EUT itself forms a system. No support equipment is required for its normal operation.

## **1.4 Test Procedure**

All measurements contained in this report were performed according to the techniques described in measurement procedure of *ANSI C63.4 1992 section 13*

## **1.5 Location of the Test Site**

The radiated emissions measurements required by the rules were performed on the **three-meter, Anechoic Chamber (Registration Number: 93906)** maintained by *Training Research Co., Ltd.* - 255 Nanyang Street, Shijr, Taipei Hsien 221, Taiwan, R.O.C., Complete description and measurement data have been filed with the commission. The conducted power line emissions tests and other test items were performed in an anechoic chamber also located at Training Research Co., Ltd.

255 Nanyang Street, Shijr, Taipei Hsien 221, Taiwan, R.O.C., *Training Research Co., Ltd.* is listed by the FCC as a facility available to do measurement work for the others on a contract basis.

## **1.6 General Test Condition**

The conditions under which the EUT operates were varied to determine their effect on the equipment's emission characteristics. The final configuration of the test system and the mode of operation used during these tests were chosen as that which produced highest emission levels. However, only those conditions that the EUT was considered likely encounter in normal use were investigated.

## **Chapter 2 Transmitter Duty Cycle Measurements**

### **2.1 Test Condition and Setup**

The duty cycle measurements were performed in a shielded enclosure. The EUT was placed on a wooded table which is 0.8 meters height and a bi-log periodic antenna was used distance about 3 meters for receiving. While testing EUT was set to transmit continuously. Various key configurations were also investigated to find the maximum duty cycle.

The resolution bandwidth and video bandwidth of the spectrum analyzer was set to 1MHz to encompass all significant spectral components during the test. The analyzer operated in linear scale and zero span mode after tuning to the transmitter carrier frequency. The spectrum analyzer measured pulse width. The pulse width was determined by the difference between the two half voltage points on a pulse.

The duty cycle was determined by the following equation:

$$\text{Duty Cycle (\%)} = \frac{\text{Total on interval in a complete pulse train}}{\text{Length of a complete pulse train}} \times 100\%$$


To calculate the actual field intensity, the duty cycle correction factor in decibel is needed for later use and be obtained from following conversion:

$$\text{Duty Cycle Correction Factor (dB)} = 20 \times \log_{10} \text{Duty Cycle}$$

### **2.2 List of Test Instruments**

Instrument Name	Model No.	Brand	Serial No.	Last time	Next time
EMI Receiver	8546A	H P	3520A00242	06/29/02	06/29/03
RF Filter Section	85460A	H P	3448A00217	06/29/02	06/29/03
Bi-log Antenna	CBL6141A	Schaffner	4206	03/09/02	03/09/03

## 2.3 Test Instruments Configuration



## 2.4 Test Result

Following is the test result, which produce maximum duty cycle:

Total on interval in a complete pulse train = 9.350 ms



Length of a complete pulse train = 17.325 ms

Duty Cycle (%) =  $9.350 \text{ ms} / 17.325 \text{ ms} * 100\% = 0.53968$

Duty Cycle Correction Factor (dB) =  $20 * \text{Log } 0.53968 = -5.3573$

A plot is attached on the following page.

Fig 1. Receiver: Picture of the Duty Cycle Test





## **Chapter 3 FCC Part 15.231(c): Transmitter Bandwidth Measurements**

### **3.1 Test Condition & Setup**

The test setup used to transmitter bandwidth measurement was the same with duty cycle test, except there is no need for digital oscilloscope in the bandwidth test. For detailed description, please reference to section 2.1, 2.2 and 2.3 on page 6 and 7 of this report.

The resolution bandwidth of the spectrum analyzer was set to 100KHz, which is greater 5 percent of the maximum permitted bandwidth that required by the ANSI C63.4 section13. Bandwidth is determined at the point 20dB down from the modulator carrier. The maximum permitted bandwidth specified by the rule was 0.25% of the center frequency of the EUT, e.g.  $433.92 \text{ MHz} * 0.25\% = 1084.875 \text{ kHz}$ . The detector function was set to peak and hold mode to clearly observe the components.


### **3.2 Test Result**

Measured Transmitter Bandwidth: 390 kHz

Permitted Maximum Bandwidth: 1084.875 kHz

A plot attached on the following page.

Fig 2. Receiver: Plot of the Transmitter Bandwidth Measurement



## ***Chapter 4 Conducted Emissions Measurements***

The EUT operates solely by the battery. According to the rule of section 15.207(c). The EUT exempt to the power line conducted test.

## ***Chapter 5 Radiated Emissions Measurements***

### **5.1 General Configuration**

Prior to open-field testing, the EUT was placed in a shielded enclosure and scanned at a close distance to determine its emission characteristics. The physical arrangement of the EUT was varied (within the scope of arrangements likely to be encountered in actual use) to determine the effect on the unit's emanations in amplitude, directivity, and frequency. The exact system configuration that produced the highest emissions was noted so it could be reproduced later during the final tests. This was done to ensure that the final measurements would demonstrate the worst-case interference potential of the EUT.

### **5.2 Test Condition and Setup**

Final radiation measurements were made on a three-meter, anechoic chamber. The EUT was placed on a non-conductive turntable that is 0.8 meters height, top surface 1.0 x 1.5 meter. The spectrum was examined from 30MHz to 18GHz order to check the whole spectrum that could be generated from the EUT. During the test, EUT was set to transmit continuously and the switch was positioned to yield the maximum duty cycle that had measured before radiated emissions test. The test battery was a totally brand-new one.

A nonconductive material surrounded the EUT to supporting the EUT for standing on three orthogonal planes. At each condition, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters to find the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarizations.

**(Note: The EUT to transmit continuously was just for the testing only)**

The field strength below 1GHz was measured by Schaffner Bi-Log Periodic Antenna (model: CBL6141A) at 3 meter, and the EMCO Double Ridged Guide Antenna (model: 3115) was used in frequencies 1 ~ 18 GHz at a distance of 1 meter. All test results were extrapolated equivalent signal at 3 meters utilizing an inverse linear distance extrapolated factor (20dB/decade).

Appropriate preamplifiers were used for improving sensitivity and precautions were taken to avoid overloading or desensitizing the spectrum analyzer. No post-detector video filters were used in the test. The spectrum analyzer's 6dB bandwidth was set to 3 M and the spectrum was operated in the peak detection mode, for frequencies both below and up 1GHz. (The average levels were obtained by subtracting the duty cycle correction factor from the peak readings.)

The following procedures were used to convert the emission levels measured in decibels referenced to 1 micro-volt (dBμV) into field intensity in micro-volts pre meter (μV/m).

- (1) The actual field intensity in decibels referenced to 1 micro-volt per meter (dBμV/m) is determined by algebraically adding the measured reading in dBμV, the correction factor (dB), duty cycle correction factor (dB), and distance extrapolation factor (dB) at the appropriate frequency:

**30 MHz ~ 1GHz:**

Correction factor = Antenna factor + (Cable Loss – Amplitude gain)

Corrected Amplitude = Reading Amplitude – Correction Factors

(For example: 30MHz correction factor = 15.5 + (-15.26) = 0.24 dB/m)

**Above 1GHz**

1. Correction Factors = Antenna Factor + Cable Loss – Distance Extrapolation

Factor (9.54dB) – Amplifier Gain

2. Peak Amplitude + Correction Factor = Corrected

- (2) The field intensity in micro-volts per meter can then be determined by the following equation:

$$FI(\mu V/m) = 10^{FI(dB\mu V/m) / 20}$$

The FCC specified emission limits were calculated according the EUT operating frequency and obtained by following linear interpolation equations:

**(a) For fundamental frequency:**

$f_{EUT}$ : EUT Operating Frequency Emission Limit ( $\mu V/m$ )

$$= [f_{EUT}(MHz) - 260(MHz)] \times \frac{12500(\mu V/m) - 3750(\mu V/m)}{470(MHz) - 260(MHz)} + 3750(\mu V/m)$$

**(b) For spurious frequencies:**

$f_{EUT}$ : EUT Operating Frequency Emission Limit ( $\mu V/m$ )

$$= [f_{EUT}(MHz) - 260(MHz)] \times \frac{1250(\mu V/m) - 375(\mu V/m)}{470(MHz) - 260(MHz)} + 375(\mu V/m)$$

### 5.3 List of Test Instruments


Instrument Name	Model No.	Brand	Serial No.	Last time	Next time
EMI Receiver	8546A	H P	3520A00242	06/29/02	06/29/03
RF Filter Section	85460A	H P	3448A00217	06/29/02	06/29/03
Bi-log Antenna	CBL6141A	Schaffner	4206	03/09/02	03/09/03
Switch/Control Unit (> 30MHz)	3488A	HP	N/A	11/20/01	11/20/02
Auto Switch Box (> 30MHz)	ASB-01	TRC	9904-01	11/20/01	11/20/02
Spectrum Analyzer	8564E	HP	US36433002	08/01/01	08/01/02
Microwave Preamplifier	83051A	HP	3232A00347	08/01/01	08/01/02
Horn Antenna	3115	EMCO	9704 – 5178	08/01/01	08/01/02
Anechoic Chamber (cable calibrated together)				05/20/02	05/20/03

---

**Report No.: AA515581 (Version 2)**

**Training Research Co., Ltd., TEL: 886-2-26935155, Fax: 886-2-26934440**

## 5.4 Test Instruments Configuration



***Radiated Test Placement: (Photographs)***



---

***Report No.: AA515581 (Version 2)***

***Training Research Co., Ltd., TEL: 886-2-26935155, Fax: 886-2-26934440***



## 5.5 Test Result of Radiated Emissions

The highest peak values of radiated emissions from the EUT at various antenna heights, antenna polarization, EUT orientation, etc. are recorded on the following.

Test Conditions: Testing Room: Temperature: 27 ° C Humidity: 71 % RH

**Table 1 Open Field Radiated Emissions For 30MHz to 1GHz [Horizontal]**

Radiated Emission				Correction Factors	Duty Cycle Correction	Corrected Amplitude	FCC Class B ( 3 M )	
Frequency (MHz)	Amplitude (dBμV/m)	Ant. H. (cm)	Table ( ° )	(dB)	(dB)	(dBì V/m)	Limit (dBμV/m)	Margin (dB)
433.86	52.55	1.00	75	26.96	-5.36	74.15	80.82	-6.67
---								

**Table 2 Open Field Radiated Emissions For 30MHz to 1GHz [Vertical]**

Radiated Emission				Correction Factors	Duty Cycle Correction	Corrected Amplitude	FCC Class B ( 3 M )	
Frequency (MHz)	Amplitude (dBμV/m)	Ant. H. (cm)	Table ( ° )	(dB)	(dB)	(dBì V/m)	Limit (dBμV/m)	Margin (dB)
433.86	37.83	1.00	4	25.80	-5.36	58.27	80.82	-22.55
---								

Note:

1. Margin = Amplitude – limit, *if margin is minus means under limit.*
2. Corrected Amplitude = Reading Amplitude + |Correction Factors |+ Duty cycle
3. Correction factor = Antenna factor + (Cable Loss – Amplitude gain)

---

**Report No.: AA515581 (Version 2)**

**Training Research Co., Ltd., TEL: 886-2-26935155,Fax: 886-2-26934440**

**Table 3 Open Field Radiated Emissions for 1GHz to 18GHz [Horizontal]**

Radiated Emission				Correction Factors	Duty Cycle Correction	Corrected Amplitude	FCC Class B ( 3 M )	
Frequency (MHz)	Amplitude (dBμV/m)	Ant. H. (cm)	Table ( ° )	(dB)	(dB)	(dBì V/m)	Limit (dBμV/m)	Margin (dB)
1.731	34.74	1.00	86	0.00	-5.36	29.38	60.82	-31.44
2.167	42.07	1.00	284	0.00	-5.36	36.71	60.82	-24.11
3.036	38.41	1.00	291	0.00	-5.36	33.05	60.82	-27.77
3.471	35.91	1.00	78	0.00	-5.36	30.55	60.82	-30.27
4.339	37.74	1.00	118	0.00	-5.36	32.38	60.82	-28.44
---								

**Table 4 Open Field Radiated Emissions For 1GHz to 18GHz [Vertical]**

Radiated Emission				Correction Factors	Duty Cycle Correction	Corrected Amplitude	FCC Class B ( 3 M )	
Frequency (MHz)	Amplitude (dBμV/m)	Ant. H. (cm)	Table ( ° )	(dB)	(dB)	(dBì V/m)	Limit (dBμV/m)	Margin (dB)
2.169	35.74	1.00	116	0.00	-5.36	30.38	60.82	-30.44
3.036	34.74	1.00	257	0.00	-5.36	29.38	60.82	-31.44
4.339	37.57	1.00	34	0.00	-5.36	32.21	60.82	-28.61
---								

Note:

1. Margin = Corrected – Limit.
2. Peak Amplitude + Correction Factor = Corrected

---

**Report No.: AA515581 (Version 2)**

**Training Research Co., Ltd., TEL: 886-2-26935155,Fax: 886-2-26934440**