

Antenna Report

Report Number:

F231415E5

Equipment under Test (EUT):

Level Probing Radar

**Micropilot FMR20B
Antenna**

Applicant:

Endress+Hauser SE+Co. KG

Manufacturer:

Endress+Hauser SE+Co. KG

References

[1] None (According customer requirements)

Tested and
written by

Signature

Reviewed and
approved by:

Signature

This test report is only valid in its original form.

Any reproduction of its contents in extracts without written permission of the accredited test laboratory PHOENIX TESTLAB GmbH is prohibited.

The test results herein refer only to the tested sample. PHOENIX TESTLAB GmbH is not responsible for any generalisations or conclusions drawn from these test results concerning further samples. Any modification of the tested samples is prohibited and leads to the invalidity of this test report. Each page necessarily contains the PHOENIX TESTLAB Logo and the TEST REPORT NUMBER.

Contents:	Page
1 Identification	4
1.1 Applicant.....	4
1.2 Manufacturer	4
1.3 Test Laboratory	4
1.4 AUT (Antenna under test)	5
1.5 Technical Data of Equipment	6
1.6 Dates	6
2 Operational States	7
3 Additional Information	7
4 Antenna photographs.....	8
4.1 Internal photographs	8
5 Antenna Charts.....	9
5.1 Results (Max. Gain).....	9
5.2 Antenna Diagrams EUT Position	10
5.2.1 Test Setup Photos	10
5.2.2 Azimuth charts of transmitter	11
5.2.2.1 Frequency near bottom (f_{low})	11
5.2.2.2 Frequency near middle (f_{mid})	12
5.2.2.3 Frequency near top (f_{high})	14
6 Test Equipment used for Tests	16
7 Report History.....	16

1 Identification

1.1 Applicant

Name:	Endress+Hauser SE+Co. KG
Address:	Hauptstr. 1
Country:	79689 Maulburg
Name for contact purposes:	Germany
Phone:	Mr. Ralf REIMELT
eMail address:	ralf.reimelt@endress.com
Applicant represented during the test by the following person:	None

1.2 Manufacturer

Name:	Endress+Hauser SE+Co. KG
Address:	Hauptstr. 1
Country:	79689 Maulburg
Name for contact purposes:	Germany
Phone:	Mr. Ralf REIMELT
eMail address:	ralf.reimelt@endress.com
Manufacturer represented during the test by the following person:	None

1.3 Test Laboratory

The tests were carried out by: **PHOENIX TESTLAB GmbH**
Königswinkel 10
32825 Blomberg
Germany

1.4 AUT (Antenna under test)

Test object: *1	Level Probing Radar
Model name: *1	Micropilot
Model number: *1	FMR20B
Order number: *2	- *2

*1 Declared by the applicant

*2 No information provided by the applicant

		EUT number	
		1 (radiated)	2 (conducted)
Serial number: *		FMR20B_HA2W_0276	FMR20B_EUT2C
PCB identifier: *	Sensor board:	71574004	71574004
	Power board:	71502179	71502179
	Main board:	71499710	71499710
	Terminal board:	71581272	71581272
Hardware version: *		V01.00.00	V01.00.00
Software version: *		V01.00.00	V01.00.00

* Declared by the applicant

Two EUTs were used for the tests.

Note: PHOENIX TESTLAB GmbH does not take samples. The samples used for tests are provided exclusively by the applicant.

1.5 Technical Data of Equipment

General	
Frequency Range *	2402 MHz to 2480 MHz

* Declared by the applicant

Ports / Connectors				
Identification	Connector		Length during test	Shielding (Yes / No)
	EUT	Ancillary		
---	---	---	---	---

Equipment used for testing	
USB-2-Serial converter* ¹	USB-2-Serial converter* ¹
Laptop computer * ²	Laptop computer * ²

*¹ Provided by the applicant

*² Provided by the laboratory

1.6 Dates


Date of receipt of test sample:	02.09.2024
Start of test:	07.10.2024
End of test:	07.10.2024

2 Operational States

During the antenna chart measurements, the antenna was supplied with a CW rf-signal generated by the EU with a level as shown in the chapter below its antenna connector.

3 Additional Information


Conducted measurements were done with a modified sample as provided by the applicant.



4 Antenna photographs

4.1 Internal photographs

Internal photos were provided by the applicant



EUT PCB (PCB side with antenna trace)

5 Antenna Charts

5.1 Results (Max. Gain)

Antenna gain calculation				
		f_{low}	f_{mid}	f_{high}
Conducted output power [dBm]		1.8	1.8	1.9
Radiated EIRP [dBm EIRP]		4.3	4.2	3.6
Antenna Gain [dBi]		2.5	2.4	1.7
Position		Pos 3	Pos 3	Pos 3
Position of maximum gain	Azimuth	211	209	210
	Polarisation	Horizontal	Horizontal	Horizontal


Conducted f_{low}	MultiView ☐ Receiver Meas BW (6dB) 1 MHz Att 20 dB Input 1 AC Meas Time 50 ms Notch Off PS On Step TD Scan Automatic Preamp Off Frequency 2.4020000 GHz 1 Bargraph Pk+ 1.81 dBm 1.8 2.4020000 GHz -95 -80 -70 -60 -50 -40 -30 -20 -10 5 AV 1.79 dBm 1.8 2.4020000 GHz -95 -80 -70 -60 -50 -40 -30 -20 -10 5 RMS 1.79 dBm 1.8 2.4020000 GHz -95 -80 -70 -60 -50 -40 -30 -20 -10 5
	MultiView ☐ Receiver Meas BW (6dB) 1 MHz Att 20 dB Input 1 AC Meas Time 50 ms Notch Off PS On Step TD Scan Automatic Preamp Off Frequency 2.4400000 GHz 1 Bargraph Pk+ 1.85 dBm 1.9 2.4400000 GHz -95 -80 -70 -60 -50 -40 -30 -20 -10 5 AV 1.83 dBm 1.8 2.4400000 GHz -95 -80 -70 -60 -50 -40 -30 -20 -10 5 RMS 1.83 dBm 1.8 2.4400000 GHz -95 -80 -70 -60 -50 -40 -30 -20 -10 5
	MultiView ☐ Receiver Meas BW (6dB) 1 MHz Att 20 dB Input 1 AC Meas Time 50 ms Notch Off PS On Step TD Scan Automatic Preamp Off Frequency 2.4800000 GHz 1 Bargraph Pk+ 1.93 dBm 1.9 2.4800000 GHz -95 -80 -70 -60 -50 -40 -30 -20 -10 5 AV 1.90 dBm 1.9 2.4800000 GHz -95 -80 -70 -60 -50 -40 -30 -20 -10 5 RMS 1.90 dBm 1.9 2.4800000 GHz -95 -80 -70 -60 -50 -40 -30 -20 -10 5

Test equipment (please refer to chapter 7 for details)

1 - 12


5.2 Antenna Diagrams EUT Position


5.2.1 Test Setup Photos

Setup Photos		
Position 1		
Position 2		
Position 3		


5.2.2 Azimuth charts of transmitter

5.2.2.1 Frequency near bottom (f_{low})






5.2.2.2 Frequency near middle (f_{mid})



Antenna chart of transmitter


f_{mid} , horizontal, pos. 2

Azimuth Chart: 90deg, Horizontal




f_{mid} , vertical, pos. 2

Azimuth Chart: 90deg, Vertical




f_{mid} , horizontal, pos. 3

Azimuth Chart: 0deg, Horizontal





f_{mid} , vertical, pos. 3

Azimuth Chart: 0deg, Vertical



5.2.2.3 Frequency near top (f_{high})





6 Test Equipment used for Tests

No.	Test equipment	Type	Manufacturer	Serial No.	PM. No.	Cal. Date	Cal Due
1	RF cable	Sucoflex 102	Suhner	521885/2	483401	Calibration not necessary	
2	Horn antenna 1 GHz - 18 GHz	3115	EMCO Elektronik GmbH	9609-4918	480183	13.02.2024	02.2027
3	Software	EMC32 V10.60.20	Rohde & Schwarz	---	483261	Calibration not necessary	
4	RF cable	SF106B/11N/11N /4500.0	Huber & Suhner	500218/6B	482415	Calibration not necessary	
5	Antenna support	AS620P	Deisel	620/375	480325	Calibration not necessary	
6	Fully anechoic chamber M20	B83117-E2439- T232	Albatross Projects	103	480303	Calibration not necessary	
7	Turntable	DS420 HE	Deisel	420/620/00	480315	Calibration not necessary	
8	Multiple Control Unit	MCU	Maturo GmbH	MCU/043/97110 7	480832	Calibration not necessary	
9	EMI Receiver / Spectrum Analyser	ESW44	Rohde & Schwarz	101635	482467	27.02.2024	02.2026
10	Positioner	TDF 1.5- 10Kg	Maturo	15920215	482034	Calibration not necessary	
11	Horn antenna 1 GHz - 18 GHz	3115	EMCO Elektronik GmbH	9609-4922	480184	14.11.2022	11.2025
12	Microwave CW generator	83650L	Agilent	3844A00554	480333	27.02.2024	02.2026

7 Report History

Report Number	Date	Comment
F231415E5	17.01.2025	Initial Test Report
-	-	-
-	-	-

--- end of test report ---