



RF EXPOSURE EVALUATION

FCC ID: 2AK9F-38108

Product Name	:	Smart Watch
Model Name	:	38108, M03
Bluetooth Version	:	BDR+EDR, BLE
Operating frequency	:	2402-2480MHz
Numbers of Channel	:	79 channels for BDR+EDR 40 channels For DTS
Antenna Type	:	Chip Antenna
Antenna Gain	:	1.9dBi
Type of Modulation	:	GFSK, $\pi/4$ -DQPSK, 8DPSK For DSS GFSK For DTS
Power supply	:	Input:DC5V 500mA Li-ion Battery :572024 Voltage: 3.8V Capacity:270mAh
Hardware Version	:	V1
Software Version	:	V1



Standard Requirement

According to § 15.247(i) and § 1.1307b(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See KDB 447498 D01 General RF Exposure Guidance v06, section 4. 3. 1.

The 1-g and 10-g SAR test exclusion thresholds for 100MHz to 6GHz at test separation distances $\leq 50\text{mm}$ are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g SAR extremity SAR, where}$$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison.

The test exclusions are applicable only when the minimum test separation distance is $\leq 50\text{mm}$ and for transmission frequencies between 100MHz and 6GHz. When the minimum test separation distance is $< 5\text{mm}$, a distance of 5mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

Channel (MHz)	Maximum output power (dBm)	Tune up tolerance (dBm)	Max Tune Up Power (mW)	Distance (mm)	Calculation results	Limit	Operating Mode
2402	0.05	0.05 ± 1	1.273503	5	0.394745	3	BLE
2402	1.81	1.81 ± 1	1.909853	5	0.591993	3	BT

The sample support one BLE modular and BT modular, they supports difference antenna, need consider simultaneous transmission;

$$\sum \text{of (the highest measured or estimated SAR}_{\text{BLE}} + \text{SAR}_{\text{BT}}) / 1.6 = (0.0805 + 0.0537) / 1.6 = 0.1 < 1.0;$$

Signature

Simon Pu

Manager

Date: 2023-08-17