



FCC RADIO TEST REPORT

Applicant : PERFORMANCE DESIGNED PRODUCTS, LLC

Address : 14144 Ventura Blvd, Suite 200 Sherman. Oaks CA
91423 United States Of America

Equipment : Airlite Pro Wireless Headset for PlayStation

Model No. : 052-017

Trade Name : PDP

FCC ID : X5B-052017

I HEREBY CERTIFY THAT :

The sample was received on Jun. 20, 2022 and the testing was completed on Jul. 05, 2022 at CerpPASS Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of CerpPASS Technology Corp., the test report shall not be reproduced except in full.

Approved by:

Mark Liao / Supervisor

Laboratory Accreditation:

CerpPASS Technology Corporation Test Laboratory





CONTENTS

1. Summary of Test Procedure and Test Results	5
1.1 Applicable Standards	5
2. Test Configuration of Equipment under Test	6
2.1 Feature of Equipment under Test.....	6
2.2 Carrier Frequency of Channels.....	7
2.3 Test Mode and Test Software	8
2.4 Description of Test System.....	9
2.5 General Information of Test.....	10
2.6 Measurement Uncertainty	11
3. Test Equipment and Ancillaries Used for Tests	12
4. Antenna Requirements.....	14
4.1 Standard Applicable	14
4.2 Antenna Construction and Directional Gain.....	14
5. Test of AC Power Line Conducted Emission	15
5.1 Test Limit	15
5.2 Test Procedures	15
5.3 Typical Test Setup	16
5.4 Test Result and Data.....	17
5.5 Test Photographs	19
6. Test of Spurious Emission (Radiated)	20
6.1 Test Limit	20
6.2 Test Procedures	21
6.3 Typical Test Setup	22
6.4 Test Result and Data (9kHz ~ 30MHz).....	24
6.5 Test Result and Data (30MHz ~ 1GHz)	24
6.6 Test Result and Data (1GHz ~ 25GHz).....	26
6.7 Restricted Bands of Operation	32
6.8 Test Photographs (30MHz ~ 1GHz)	33
6.9 Test Photographs (1GHz ~ 25GHz)	34
7. Test of Spurious Emission (Conducted).....	36
7.1 Test Limit	36
7.2 Test Procedure	36
7.3 Test Setup Layout	36
7.4 Test Result and Data.....	36
8. On Time, Duty Cycle and Measurement methods	39
8.1 Test Limit	39
8.2 Test Procedure	39
8.3 Test Setup Layout	39
8.4 Test Result and Data.....	39
9. 6dB Bandwidth Measurement Data.....	41
9.1 Test Limit	41



9.2	Test Procedures	41
9.3	Test Setup Layout	41
9.4	Test Result and Data.....	41
10.	Maximum Average Output Power	43
10.1	Test Limit	43
10.2	Test Procedures	43
10.3	Test Setup Layout	43
10.4	Test Result and Data.....	43
11.	Power Spectral Density	44
11.1	Test Limit	44
11.2	Test Procedures	44
11.3	Test Setup Layout	44
11.4	Test Result and Data.....	44



History of this test report

Report No.	Issued Date	Description
22060154-TRFCC03	Aug. 22, 2022	Original
22060154-TRFCC03-A	Sep. 06, 2022	Delete Data Rate



1. Summary of Test Procedure and Test Results

1.1 Applicable Standards

ANSI C63.10:2013

FCC Rules and Regulations Part 15 Subpart C §15.247

FCC Rule	Description of Test	Result
15.203	. Antenna Requirement	PASS
15.207	. AC Power Line Conducted Emission	PASS
15.209 15.205	. Radiated Spurious Emission	PASS
15.247(d)	. Conducted Spurious Emission	PASS
15.247(a)(2)	. 6dB Bandwidth	PASS
15.247(b)	. Maximum Output Power	PASS
15.247(e)	. Power Spectral Density	PASS
2.1091	. Radio Frequency Exposure	PASS

*The lab has reduced the uncertainty risk factor from test equipment, environment and staff technicians which according to the standard on contract. Therefore, the test result will only be determined by standard requirement.



2. Test Configuration of Equipment under Test

2.1 Feature of Equipment under Test

Operation Frequency Range	2400MHz -2483.5MHz
Center Frequency Range	2403.35MHz-2477.35MHz
Modulation Type	$\pi/4$ -DQPSK
Antenna Type	PCB Antenna
Antenna Gain	ANT A:5.48 dBi , ANT B: 2.08dBi
Type-C USB Cable	Brand: ADJ Model: #1
Airlite Pro Wireless Dongle for PlayStation	Brand: PDP Model: 052-017T

Note:

1. The EUT is 1TX diversity , Only use one of them at a time
2. For more details, please refer to the User's manual of the EUT.



2.2 Carrier Frequency of Channels

Channel	Frequency (MHz) Modulated	Channel	Frequency (MHz) Modulated
*1	2403.35	*20	2441.35
2	2405.35	21	2443.35
3	2407.35	22	2445.35
4	2409.35	23	2447.35
5	2411.35	24	2449.35
6	2413.35	25	2451.35
7	2415.35	26	2453.35
8	2417.35	27	2455.35
9	2419.35	28	2457.35
10	2421.35	29	2459.35
11	2423.35	30	2461.35
12	2425.35	31	2463.35
13	2427.35	32	2465.35
14	2429.35	33	2467.35
15	2431.35	34	2469.35
16	2433.35	35	2471.35
17	2435.35	36	2473.35
18	2437.35	37	2475.35
19	2439.35	*38	2477.35

Note: Channels remarked * are selected to perform test.



2.3 Test Mode and Test Software

- During testing, the interface cables and equipment positions were varied according to ANSI C63.10.
- The complete test system included Notebook and EUT for RF test.
- An executive program, "Avnera Continue Power ver. 2020.11.4.1" under Windows OS system was executed to transmit and receive data via 2.4G.
- The following test modes were performed for the test:

Conducted Emissions from the AC mains power ports	
Test Mode	Operating Description
1	Normal Mode, From Adapter (120V/60Hz)
2	Normal Mode, From Adapter (240V/60Hz)
caused "Test Mode 2" generated the worst case, it was reported as the final data.	
Radiation Emissions (Below 1GHz)	
Test Mode	Operating Description
1	Normal Mode, From Adapter (120V/60Hz)
2	Normal Mode, From Adapter (240V/60Hz)
caused "Test Mode 1" generated the worst case, it was reported as the final data.	
Radiation Emissions (1GHz ~ 25GHz)	
Test Mode	Operating Description
1	$\pi/4$ -DQPSK, From System (120V/60Hz) ANT A
2	$\pi/4$ -DQPSK, From System (120V/60Hz) ANT B
caused "Test Mode 1" generated the worst case, they were reported as the final data.	
RF Conducted	
1	$\pi/4$ -DQPSK, From System (120V/60Hz) ANT A
2	$\pi/4$ -DQPSK, From System (120V/60Hz) ANT B
Two antenna "Test Mode 1" generated the largest case, they were reported as the final data.	

Note:

- There are two kinds of test voltage: AC 120V / 60Hz and AC 240V / 60Hz.
For AC Power Line Conducted Emission, AC 240V / 60Hz is worst case.
For Radiated Spurious Emission(Below 1GHz & 1GHz ~ 25GHz), AC 120V / 60Hz is worst case.

Modulation Type	TX CONFIGURATION
$\pi/4$ -DQPSK	1TX



2.4 Description of Test System

RF Conducted				
Equipment	Brand	Model	Length/Type	Power cord/Length/Type
Notebook	Lenovo	S1GL2W	N/A	Adapter / 1.8m / NS
Type-C USB Cable(Blue)	kolin	KEX-DLCP08	1m / NS	N/A
Radiated Emissions(ABOVE1G)				
Equipment	Brand	Model	Length/Type	Power cord/Length/Type
Notebook	ASUS	P2430U	N/A	Adapter / 1.8m / NS
USB Cable(A to B)	iMAX	N/A	1.5m / NS	N/A
Radiated Emissions(BELOW1G)				
Equipment	Brand	Model	Length/Type	Power cord/Length/Type
Adapter	Noratec	NT-K240	N/A	N/A
Notebook	ASUS	P2430U	N/A	Adapter / 1.8m / NS
USB Cable(A to B)	iMAX	N/A	1.5m / NS	N/A
USB Cable(A to B)	BENEVO	BUSB0301AMFB	1m / NS	N/A
AC Power Line Conducted Emission				
Equipment	Brand	Model	Length/Type	Power cord/Length/Type
Notebook	ASUS	P2430U	N/A	Adapter / 1.8m / NS
Adapter	Noratec	NT-K240	N/A	N/A



2.5 General Information of Test

Test Site	Cerpass Technology Corporation Test Laboratory Address: No.10, Ln. 2, Lianfu St., Luzhu Dist., Taoyuan City 33848, Taiwan (R.O.C.) Tel:+886-3-3226-888 Fax:+886-3-3226-881	
	FCC	TW1439, TW1079
	IC	4934E-1, 4934E-2
	VCCI	T-2205 for Telecommunication test C-4663 for Conducted emission test R-4218 for Radiated emission test G-10812, G-10813 for radiated disturbance above 1GHz
Frequency Range Investigated:	Conducted: from 150kHz to 30 MHz Radiation: from 30 MHz to 25,000MHz	
Test Distance:	The test distance of radiated emission from antenna to EUT is 3 M.	

Test Item	Test Site	Test period	Environmental Conditions	Tested By
RF Conducted	RFCON01-NK	2022/07/05	25.4℃ / 57%	Dian Chen
Radiated Emissions	3M02-NK	2022/07/04	25℃ / 44%	Dian Chen
AC Power Line Conducted Emission	CON01-NK	2022/07/01	23℃ / 57%	Dian Chen



2.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Measurement Item	Uncertainty
AC Power Line Conduction(150K~30MHz)	±3.12dB
Radiated Spurious Emission(9KHz~30MHz)	±3.4dB
Radiated Spurious Emission(30MHz~1GHz)	±5.7dB
Radiated Spurious Emission(1GHz~25GHz)	±6.8dB
Conducted Spurious Emission	±1.8dB
6dB Bandwidth	±4.4%
20dB Bandwidth	±4.4%
Occupied Bandwidth	±4.4%
Peak Output Power(Conducted Power Meter)	±1.1dB
Dwell Time / Deactivation Time	±1.2%
Power Spectral Density	±1.8dB
Duty Cycle	±1.2%



3. Test Equipment and Ancillaries Used for Tests

Test Item	Radiated Emissions				
Test Site	Semi Anechoic Room(3M02-NK)				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
Bilog Antenna	Schwarzbeck	VULB9168	275	2021/11/05	2022/11/04
Active Loop Antenna	EMCO	6507	40855	2022/05/25	2023/05/24
Horn Antenna	EMCO	3115	31601	2021/10/14	2022/10/13
Horn Antenna	EMCO	3116	31974	2021/10/04	2022/10/03
EMI Receiver	ROHDE & SCHWARZ	ESCI	100821	2021/11/16	2022/11/15
Spectrum Analyzer	ROHDE & SCHWARZ	FSV 40-N	102151	2021/08/06	2022/08/05
Preamplifier	Agilent	8449B	3008A01954	2022/03/17	2023/03/16
Preamplifier	EMC INSTRUMENTS	EMC184045	980065	2021/11/16	2022/11/15
Preamplifier	EM Electronics corp.	EM330	60658	2021/10/13	2022/10/12
Cable-6m(9k~300M)	NA	EMC5D-BM-BM-6	130605	2021/09/22	2022/09/21
Cable-3in1(30M-1G)	HARBOUR INDUSTRIES	LL142	CCE1315	2022/03/21	2023/03/20
Cable-0.5m(1G-40G)	HUBER SUHNER	SUCOFLEX 102	MY4569/2	2021/09/03	2022/09/02
Cable-1m(1G-40G)	HUBER SUHNER	SUCOFLEX 102	MY5739/2	2021/09/03	2022/09/02
Cable-6m(1G-40G)	HUBER SUHNER	SUCOFLEX 102	MY5740/2	2021/09/03	2022/09/02
Cable-0.5m(1G-40G)	HUBER SUHNER	SUCOFLEX 104	805443/4	2022/01/11	2023/01/10
Cable-3m(1G-40G)	HUBER SUHNER	SUCOFLEX 104	805796/4	2022/01/11	2023/01/10
Cable-8m(1G-26.5G)	WOKEN	WCBA-WCA203SM	CCE1374	2022/04/25	2023/04/24
E3	AUDIX	v8.2014-8-6	RK-000529	NA	NA

Test Item	RF Conducted				
Test Site	RFCON01-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
Spectrum Analyzer	ROHDE & SCHWARZ	FSP 40	100047	2022/03/04	2023/03/03
Attenuator	KEYSIGHT	8491B	MY39250703	2022/04/12	2023/04/11
Cable-0.5m(1G-26.5G)	HUBER SUHNER	SUCOFLEX 102	28422/2	2022/04/09	2023/04/08
Power Meter	Anritsu	ML2495A	1224005	2022/04/12	2023/04/11
Power Sensor	Anritsu	MA2411B	1207295	2022/04/12	2023/04/11
Switch Box	Theda	1-4	TW5451159	NA	NA



Test Item	AC Power Line Conducted Emission				
Test Site	CON01-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
EMI Receiver	ROHDE & SCHWARZ	ESCI	101200	2021/08/30	2022/08/29
Line Impedance Stabilization Network	Schwarzbeck	NSLK 8127	8127-516	2021/10/05	2022/10/04
Pulse Limiter	ROHDE & SCHWARZ	ESH3-Z2	101933	2021/09/15	2022/09/14
Cable-6m(9k~300M)	NA	EMC5D-BM-BM-6	130605	2021/09/22	2022/09/21
E3	AUDIX	v8.2014-8-6	RK-000531	NA	NA



4. Antenna Requirements

4.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.2 Antenna Construction and Directional Gain

Antenna Type	PCB Antenna
Antenna Gain	ANT A :5.48 dBi ANT B: 2.08 dBi



5. Test of AC Power Line Conducted Emission

5.1 Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz, according to the methods defined in ANSI C63.10-2013. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.

Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50

*Decreases with the logarithm of the frequency.

5.2 Test Procedures


- The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- Connect EUT to the power mains through a line impedance stabilization network (LISN).
- All the support units are connecting to the other LISN.
- The LISN provides 50 ohm coupling impedance for the measuring instrument.
- The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
- Both sides of AC line were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched.
- Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.





5.4 Test Result and Data

Power	:	From Adapter (AC 240V / 60Hz)	Pol/Phase	:	LINE
Test Mode	:	Mode 2		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.20	9.95	1.26	11.21	53.60	-42.39	Average	P
2	0.20	9.95	19.31	29.26	63.60	-34.34	QP	P
3	0.36	9.96	1.51	11.47	48.71	-37.24	Average	P
4	0.36	9.96	16.87	26.83	58.71	-31.88	QP	P
5	0.47	9.96	-0.50	9.46	46.48	-37.02	Average	P
6	0.47	9.96	10.87	20.83	56.48	-35.65	QP	P
7	0.59	9.97	11.31	21.28	46.00	-24.72	Average	P
8	0.59	9.97	19.05	29.02	56.00	-26.98	QP	P
9	0.75	9.98	3.49	13.47	46.00	-32.53	Average	P
10	0.75	9.98	11.57	21.55	56.00	-34.45	QP	P
11	3.83	10.20	0.57	10.77	46.00	-35.23	Average	P
12	3.83	10.20	11.60	21.80	56.00	-34.20	QP	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=(LISN or ISM or Current Probe)Factor + Cable Loss



Power	:	From Adapter (AC 240V / 60Hz)	Pol/Phase	:	NEUTRAL
Test Mode	:	Mode 2		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV)	Limit (dBUV)	Margin (dB)	Detector	P/F
1	0.18	9.93	4.42	14.35	54.49	-40.14	Average	P
2	0.18	9.93	21.13	31.06	64.49	-33.43	QP	P
3	0.32	9.93	9.40	19.33	49.80	-30.47	Average	P
4	0.32	9.93	18.32	28.25	59.80	-31.55	QP	P
5	0.43	9.94	10.56	20.50	47.16	-26.66	Average	P
6	0.43	9.94	19.56	29.50	57.16	-27.66	QP	P
7	0.59	9.94	15.99	25.93	46.00	-20.07	Average	P
8	0.59	9.94	23.99	33.93	56.00	-22.07	QP	P
9	1.00	9.97	4.53	14.50	46.00	-31.50	Average	P
10	1.00	9.97	14.48	24.45	56.00	-31.55	QP	P
11	3.77	10.12	5.20	15.32	46.00	-30.68	Average	P
12	3.77	10.12	16.21	26.33	56.00	-29.67	QP	P

Note: Level=Reading+Factor

Margin=Level-Limit

Factor=(LISN or ISN or Current Probe)Factor + Cable Loss



6. Test of Spurious Emission (Radiated)

6.1 Test Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3



6.2 Test Procedures

- a. The EUT was placed on a rotatable table top 0.8 meter above ground.
- b. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- f. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
- h. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- i. "Cone of radiation" has been considered to be 3dB bandwidth of the measurement antenna.


Note:

- 1.The supporting fixture shall permit orientation of the EUT in each of three orthogonal axis positions such that emissions from the EUT are maximized.
(Z-AXIS is the worst.)
- 2.Due to the test software function limit the operation band setting(200dBuV/m).
There's no corresponding limitation in the actual test item.




6.3 Typical Test Setup

Below 30MHz test setup




30MHz- 1GHz Test Setup





Above 1GHz Test Setup






6.4 Test Result and Data (9kHz ~ 30MHz)

The 9kHz - 30MHz spurious emission is under limit 20dB more.

6.5 Test Result and Data (30MHz ~ 1GHz)

Power	:	From Adapter (AC 120V / 60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	198.78	-13.15	43.23	30.08	43.50	-13.42	Peak	100	360	P
2	210.42	-13.60	44.66	31.06	43.50	-12.44	Peak	100	360	P
3	311.30	-9.77	39.69	29.92	46.00	-16.08	Peak	100	360	P
4	573.20	-3.48	33.33	29.85	46.00	-16.15	Peak	100	360	P
5	697.36	-1.31	33.60	32.29	46.00	-13.71	Peak	100	360	P
6	743.92	-0.41	33.21	32.80	46.00	-13.20	Peak	100	360	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From Adapter (AC 120V / 60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	210.42	-13.60	45.36	31.76	43.50	-11.74	Peak	100	0	P
2	311.30	-9.77	41.66	31.89	46.00	-14.11	Peak	100	0	P
3	697.36	-1.31	34.38	33.07	46.00	-12.93	Peak	100	0	P
4	743.92	-0.41	33.97	33.56	46.00	-12.44	Peak	100	0	P
5	780.70	0.31	36.67	36.98	46.00	-7.02	Peak	100	0	P
6	800.18	0.47	37.01	37.48	46.00	-8.52	Peak	100	0	P

Note: Level=Reading+Factor


Margin=Level-limit

Factor=Antenna Factor + cable loss - Amplifier Factor



6.6 Test Result and Data (1GHz ~ 25GHz)

Power	:	From System (AC 120V / 60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1, CH01		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-2.64	42.77	40.13	54.00	-13.87	Average	100	179	P
2	2390.00	-2.64	56.42	53.78	74.00	-20.22	Peak	100	179	P
3	2403.35	-2.61	96.18	93.57	200.00	-106.43	Average	100	179	P
4	2403.35	-2.61	100.51	97.90	200.00	-102.10	Peak	100	179	P
5	4806.70	4.97	39.28	44.25	54.00	-9.75	Average	100	86	P
6	4806.70	4.97	45.25	50.22	74.00	-23.78	Peak	100	86	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V / 60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1, CH01		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-2.64	45.84	43.20	54.00	-10.80	Average	100	89	P
2	2390.00	-2.64	59.52	56.88	74.00	-17.12	Peak	100	89	P
3	2403.35	-2.61	100.87	98.26	200.00	-101.74	Average	100	89	P
4	2403.35	-2.61	105.18	102.57	200.00	-97.43	Peak	100	89	P
5	4806.70	4.97	39.21	44.18	54.00	-9.82	Average	100	98	P
6	4806.70	4.97	45.14	50.11	74.00	-23.89	Peak	100	98	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V / 60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1, CH20		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-2.64	40.67	38.03	54.00	-15.97	Average	108	68	P
2	2390.00	-2.64	54.38	51.74	74.00	-22.26	Peak	108	68	P
3	2441.35	-2.56	96.40	93.84	200.00	-106.16	Average	108	68	P
4	2441.35	-2.56	100.73	98.17	200.00	-101.83	Peak	108	68	P
5	2483.50	-2.39	40.11	37.72	54.00	-16.28	Average	108	68	P
6	2483.50	-2.39	54.93	52.54	74.00	-21.46	Peak	108	68	P
7	4882.70	5.22	42.53	47.75	54.00	-6.25	Average	109	87	P
8	4882.70	5.22	47.23	52.45	74.00	-21.55	Peak	109	87	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V / 60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1, CH20		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-2.64	42.45	39.81	54.00	-14.19	Average	100	92	P
2	2390.00	-2.64	55.10	52.46	74.00	-21.54	Peak	100	92	P
3	2441.35	-2.56	100.83	98.27	200.00	-101.73	Average	100	92	P
4	2441.35	-2.56	105.15	102.59	200.00	-97.41	Peak	100	92	P
5	2483.50	-2.39	40.58	38.19	54.00	-15.81	Average	100	92	P
6	2483.50	-2.39	54.31	51.92	74.00	-22.08	Peak	100	92	P
7	4682.70	5.22	46.61	46.03	54.00	-7.97	Average	100	91	P
8	4682.70	5.22	46.52	51.74	74.00	-22.26	Peak	100	91	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V / 60Hz)	Pol/Phase	:	VERTICAL
Test Mode	:	Mode 1, CH38		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2477.35	-2.41	96.41	94.00	200.00	-106.00	Average	117	138	P
2	2477.35	-2.41	100.17	97.76	200.00	-102.24	Peak	117	138	P
3	2483.50	-2.39	46.56	44.17	54.00	-9.83	Average	117	138	P
4	2483.50	-2.39	59.15	56.76	74.00	-17.24	Peak	117	138	P
5	4954.70	5.52	43.39	48.91	54.00	-5.09	Average	100	87	P
6	4954.70	5.52	47.53	53.05	74.00	-20.95	Peak	100	87	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	:	From System (AC 120V / 60Hz)	Pol/Phase	:	HORIZONTAL
Test Mode	:	Mode 1, CH38		:	



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2477.35	-2.41	99.99	97.58	200.00	-102.42	Average	100	93	P
2	2477.35	-2.41	104.32	101.91	200.00	-98.09	Peak	100	93	P
3	2483.50	-2.39	50.81	48.42	54.00	-5.58	Average	100	93	P
4	2483.50	-2.39	62.79	60.40	74.00	-13.60	Peak	100	93	P
5	4954.70	5.52	40.81	46.33	54.00	-7.67	Average	103	93	P
6	4954.70	5.52	46.23	51.75	74.00	-22.25	Peak	103	93	P

Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



6.7 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.09000 – 0.11000	16.42000 – 16.42300	399.9 – 410.0	4.500 – 5.250
0.49500 – 0.505**	16.69475 – 16.69525	608.0 – 614.0	5.350 – 5.460
2.17350 – 2.19050	16.80425 – 16.80475	960.0 – 1240.0	7.250 – 7.750
4.12500 – 4.12800	25.50000 – 25.67000	1300.0 – 1427.0	8.025 – 8.500
4.17725 – 4.17775	37.50000 – 38.25000	1435.0 – 1626.5	9.000 – 9.200
4.20725 – 4.20775	73.00000 – 74.60000	1645.5 – 1646.5	9.300 – 9.500
6.21500 – 6.21800	74.80000 – 75.20000	1660.0 – 1710.0	10.600 – 12.700
6.26775 – 6.26825	108.00000 – 121.94000	1718.8 – 1722.2	13.250 – 13.400
6.31175 – 6.31225	123.00000 – 138.00000	2200.0 – 2300.0	14.470 – 14.500
8.29100 – 8.29400	149.90000 – 150.05000	2310.0 – 2390.0	15.350 – 16.200
8.36200 – 8.36600	156.52475 – 156.52525	2483.5 – 2500.0	17.700 – 21.400
8.37625 – 8.38675	156.70000 – 156.90000	2655.0 – 2900.0	22.010 – 23.120
8.41425 – 8.41475	162.01250 – 167.17000	3260.0 – 3267.0	23.600 – 24.000
12.29000 – 12.29300	167.72000 – 173.20000	3332.0 – 3339.0	31.200 – 31.800
12.51975 – 12.52025	240.00000 – 285.00000	3345.8 – 3358.0	36.430 – 36.500
12.57675 – 12.57725	322.00000 – 335.40000	3600.0 – 4400.0	Above 38.6
13.36000 – 13.41000			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz



7. Test of Spurious Emission (Conducted)

7.1 Test Limit

According to the methods defined in ANSI C63.10-2013 Section 11.11.1


Below –30dB of the highest emission level of operating band (In 100 kHz Resolution Bandwidth)

7.2 Test Procedure

According to the methods defined in ANSI C63.10-2013 Section 11.11.2 & 11.11.3







- The transmitter output was connected to the spectrum analyzer via a low loss cable.
- Set RBW of spectrum analyzer to 100 KHz and VBW of spectrum analyzer to 300 KHz with convenient frequency span including 100 KHz bandwidth from band edge.
- Peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 30dB relative to the maximum measured in-band peak PSD level.
- The band edges was measured and recorded.

7.3 Test Setup Layout






7.4 Test Result and Data

Note: Test plots refer to the following pages.

Modulation Type: $\pi/4$ -DQPSK
CH01Modulation Type: $\pi/4$ -DQPSK
CH20



Modulation Type: $\pi/4$ -DQPSK
CH38





8. On Time, Duty Cycle and Measurement methods


8.1 Test Limit

None; for reporting purposes only.

8.2 Test Procedure

According to the methods defined in ANSI C63.10-2013 Section 11.6
Zero-Span Spectrum Analyzer Method.

8.3 Test Setup Layout




8.4 Test Result and Data

Modulation Type	On Time (ms)	Period Time (ms)	Duty Cycle (%)
$\pi/4$ -DQPSK	100.00	100.00	100.00%



Modulation Type: $\pi/4$ -DQPSK





9. 6dB Bandwidth Measurement Data

9.1 Test Limit


The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

9.2 Test Procedures

According to the methods defined in ANSI C63.10-2013 Section 11.8




- The transmitter output was connected to the spectrum analyzer.
- Set RBW of spectrum analyzer to 100 KHz and VBW to 300 KHz.
- The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.
- The 6dB Bandwidth was measured and recorded.

9.3 Test Setup Layout



9.4 Test Result and Data

Modulation Type	Channel	Frequency (MHz)	6dB Bandwidth (KHz)	Limit (KHz)
$\pi/4$ -DQPSK	1	2403.35	1605.00	500
	20	2441.35	1623.00	500
	38	2477.35	1590.00	500

Modulation Type: $\pi/4$ -DQPSK
CH01Modulation Type: $\pi/4$ -DQPSK
CH20Modulation Type: $\pi/4$ -DQPSK
CH38



10. Maximum Average Output Power

10.1 Test Limit


The Maximum Output Power Measurement is 30dBm.

10.2 Test Procedures

According to the methods defined in ANSI C63.10-2013 Section 11.9.2.3.2

The antenna port (RF output) of the EUT was connected to the input (RF input) of a power meter. Power was read directly from the meter and cable loss connection was added to the reading to obtain power at the EUT antenna terminal. The EUT Output Power was set to maximum to produce the worse case test result.

10.3 Test Setup Layout



10.4 Test Result and Data

Power Set	Modulation Type	Channel	Frequency (MHz)	Power Output (dBm)	Power Output (mW)
				Average	Average
Default Power	$\pi/4$ -DQPSK	1	2403.35	4.26	2.667
Default Power		20	2441.35	3.78	2.388
Default Power		38	2477.35	2.98	1.986



11. Power Spectral Density

11.1 Test Limit


The Maximum of Power Spectral Density Measurement is 8dBm.

If transmitting antennas of directional gain greater than 6 dBi are used, the power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi

11.2 Test Procedures




According to the methods defined in ANSI C63.10-2013 Section 11.10.1

11.3 Test Setup Layout



11.4 Test Result and Data

Modulation Type	Channel	Frequency (MHz)	Maximum Power Density of 10KHz Bandwidth(dBm)	Limit
$\pi/4$ -DQPSK	1	2403.35	-17.73	8.00
	20	2441.35	-18.26	8.00
	38	2477.35	-19.23	8.00

Modulation Type: $\pi/4$ -DQPSK
CH01Modulation Type: $\pi/4$ -DQPSK
CH20Modulation Type: $\pi/4$ -DQPSK
CH38

-----THE END OF REPORT-----