

# TEST REPORT

**Reference No.** ..... : WTH23X05106882W001  
**FCC ID** ..... : 2ADXCLKV699R  
**Applicant** ..... : Shenzhen Lenkeng Technology Co.,Ltd  
**Address** ..... : West 4F,Jingguangxia Culture&Tech Park, 3 Guangxia Road, Shenzhen , China  
**Manufacturer** ..... : The same as Applicant  
**Address** ..... : The same as Applicant  
**Product Name** ..... : HDMI Wireless Extender  
**Model No.** ..... : LKV699-RX  
**Standards** ..... : FCC Part 15.407  
**Date of Receipt sample** .... : 2023-05-17  
**Date of Test** ..... : 2023-05-17 to 2023-07-20  
**Date of Issue** ..... : 2023-07-20  
**Test Report Form No.** ..... : WTX\_Part 15\_407W  
**Test Result** ..... : Pass

**Remarks:**

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

**Prepared By:**

**Waltek Testing Group (Shenzhen) Co., Ltd.**

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,  
Block 70 Bao'an District, Shenzhen, Guangdong, China  
Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:



Dashan Chen

Approved by:



Silin Chen

## **TABLE OF CONTENTS**

<b>1. GENERAL INFORMATION .....</b>	<b>5</b>
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	5
1.2 TEST STANDARDS.....	6
1.3 TEST METHODOLOGY.....	6
1.4 TABLE FOR PARAMETERS OF TEST SOFTWARE SETTING .....	6
1.5 EUT OPERATING DURING TEST .....	7
1.6 TEST FACILITY .....	7
1.7 EUT SETUP AND TEST MODE.....	8
1.8 MEASUREMENT UNCERTAINTY .....	9
1.9 TEST EQUIPMENT LIST AND DETAILS .....	10
<b>2. SUMMARY OF TEST RESULTS .....</b>	<b>13</b>
<b>3. ANTENNA REQUIREMENT .....</b>	<b>14</b>
3.1 STANDARD APPLICABLE.....	14
3.2 EVALUATION INFORMATION .....	14
<b>4. AUTOMATICALLY DISCONTINUE TRANSMISSION .....</b>	<b>15</b>
4.1 STANDARD APPLICABLE.....	15
4.2 SUMMARY OF TEST RESULTS .....	15
<b>5. POWER SPECTRAL DENSITY .....</b>	<b>16</b>
5.1 STANDARD APPLICABLE.....	16
5.2 TEST PROCEDURE.....	16
5.3 SUMMARY OF TEST RESULTS/PLOTS .....	17
<b>6. EMISSION BANDWIDTH AND OCCUPIED BANDWIDTH.....</b>	<b>18</b>
6.1 STANDARD APPLICABLE.....	18
6.2 TEST PROCEDURE.....	18
6.3 SUMMARY OF TEST RESULTS/PLOTS .....	20
<b>7. MAXIMUM CONDUCTED OUTPUT POWER.....</b>	<b>21</b>
7.1 STANDARD APPLICABLE.....	21
7.2 TEST PROCEDURE.....	21
7.3 SUMMARY OF TEST RESULTS/PLOTS .....	22
<b>8. RADIATED SPURIOUS EMISSIONS.....</b>	<b>23</b>
8.1 STANDARD APPLICABLE.....	23
8.2 TEST PROCEDURE.....	23
8.3 TEST RECEIVER SETUP .....	25
8.4 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	25
8.5 SUMMARY OF TEST RESULTS/PLOTS .....	26
<b>9. FREQUENCY STABILITY .....</b>	<b>54</b>
9.1 STANDARD APPLICABLE.....	54
9.2 TEST PROCEDURE.....	54
9.3 SUMMARY OF TEST RESULTS/PLOTS .....	54
<b>10 CONDUCTED EMISSIONS .....</b>	<b>55</b>
10.1 TEST PROCEDURE.....	55
10.2 BASIC TEST SETUP BLOCK DIAGRAM.....	55
10.3 TEST RECEIVER SETUP .....	55
10.4 SUMMARY OF TEST RESULTS/PLOTS .....	55
<b>APPENDIX SUMMARY .....</b>	<b>58</b>
<b>APPENDIX A.....</b>	<b>59</b>
<b>APPENDIX B .....</b>	<b>70</b>
<b>APPENDIX C .....</b>	<b>91</b>
<b>APPENDIX D.....</b>	<b>102</b>

Reference No.: WTH23X05106882W001

**APPENDIX PHOTOGRAPHS.....103**

## Report version

Version No.	Date of issue	Description
Rev.00	2023-07-20	Original
/	/	/

## 1. GENERAL INFORMATION

---

### 1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT	
Product Name:	HDMI Wireless Extender
Trade Name:	/
Model No.:	LKV699-RX
Adding Model(s):	/
Rated Voltage:	DC5V
Battery capacity:	/
Power Adapter Model:	NBS12E050200VU Input:AC100-240 50/60Hz 0.3A Output:DC5V2.0A
<i>Note: The test data is gathered from a production sample, provided by the manufacturer.</i>	

Technical Characteristics of EUT	
Support Standards:	802.11a, 802.11n-HT20 , 802.11n-HT40, 802.11ac-VHT20, 802.11ac-VHT40, 802.11ac-VHT80
Frequency Range:	5150-5250MHz
RF Output Power:	Antenna 0: 15.86dBm (Conducted) Antenna 1: 15.75dBm (Conducted)
Type of Modulation:	QPSK, 16QAM, 64QAM,256QAM
Type of Antenna:	External Antenna
Antenna Gain:	5.93dBi
<i>Note: The Antenna Gain is provided by the customer and can affect the validity of results.</i>	

## 1.2 Test Standards

The tests were performed according to following standards:

**FCC Rules Part 15.407:** General technical requirements.

**ANSI C63.10-2013:** American National Standard for Testing Unlicensed Wireless Devices.

**KDB789033 D02 v02r01:** Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-Nii) Devices Part 15, Subparte.

**KDB662911 D01 Multiple Transmitter Output v02r01:** Emissions Testing of Transmitters with Multiple Outputs in the Same Band.

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

## 1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, KDB789033 D02 v02r01. The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

## 1.4 Table for parameters of Test Software setting

Enter the fixed frequency using adb.exe, you can start to test. During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Mode	Test Frequency (MHz)		
	NCB: 20MHz		
	5180	5200	5240
802.11a 6Mbps	17	16	16
802.11n-HT20 MCS0	15	15	15
802.11ac-VHT20 MCS0	13	13	13
Mode	NCB: 40MHz		
	5190	5230	
802.11n-HT40 MCS0	14	14	
802.11ac-VHT40 MCS0	12	12	
Mode	NCB: 80MHz		

	5210
802.11ac-VHT80 MCS0/Nss2	11

## **1.5 EUT Operating during test**

EUT was programmed to be in continuously transmitting mode. During the test, EUT operation to normal function and programs under Android were executed.

## **1.6 Test Facility**

### **Address of the test laboratory**

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C. (518101)

### **FCC – Registration No.: 125990**

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

### **Industry Canada (IC) Registration No.: 11464A**

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A and the CAB identifier is CN0057.

## 1.7 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

<b>Test Mode List</b>		
Test Mode	Description	Remark
TM1	802.11a	5180MHz,5200MHz,5240MHz
TM2	802.11n-HT20	5180MHz,5200MHz,5240MHz
TM3	802.11n-HT40	5190MHz,5230MHz
TM4	802.11ac-VHT20	5180MHz,5200MHz,5240MHz
TM5	802.11ac-VHT40	5190MHz,5230MHz
TM6	802.11ac-VHT80	5210MHz

Note 1: All test modes (different data rate and different modulation) are performed, but only the worst case is recorded in this report.

Note 2: The 5GHz WIFI has two antennas and support Multiple Outputs for 802.11n/ac mode for this report; Antenna 0 Gain is 5.93dBi; Antenna 1 Gain is 5.93dBi; For this function is belong to Correlated Categorization equipment.

According to KDB 662911, for same directional gain.

Directional gain =  $G_{ANT} + 10 \log(N_{ANT})$  dBi =  $5.93+10\log(2)$  dBi=8.94dBi

<b>Test Conditions</b>	
Temperature:	22~25 °C
Relative Humidity:	45~55 %.
ATM Pressure:	1019 mbar

<b>EUT Cable List and Details</b>			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
DC Cable	1.5	Unshielded	Without Ferrite
IR blaster extension cable	1.0	Unshielded	Without Ferrite
IR receiver extension cable	1.0	Unshielded	Without Ferrite

<b>Special Cable List and Details</b>			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

<b>Auxiliary Equipment List and Details</b>			
Description	Manufacturer	Model	Serial Number
Notebook	Lenovo	TianYi 100-14IBD	PF0F4ABV
HDMI Wireless Extender	Lenkeng	LKV699 Receiver	/

## 1.8 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	9-150kHz $\pm 3.74\text{dB}$
		0.15-30MHz $\pm 3.34\text{dB}$
Transmitter Spurious Emissions	Radiated	30-200MHz $\pm 4.52\text{dB}$
		0.2-1GHz $\pm 5.56\text{dB}$
		1-6GHz $\pm 3.84\text{dB}$
		6-18GHz $\pm 3.92\text{dB}$

## 1.9 Test Equipment List and Details

Fixed asset Number	Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
WTXE1041A 1001	Communication Tester	Rohde & Schwarz	CMW500	148650	2023-02-25	2024-02-24
WTXE1022A 1002	GSM Tester	Rohde & Schwarz	CMU200	114403	2023-02-25	2024-02-24
WTXE1005A 1005	Spectrum Analyzer	Agilent	N9020A	US471401 02	2023-02-25	2024-02-24
WTXE1084A 1001	Spectrum Analyzer	Agilent	N9020A	MY543205 48	2023-02-25	2024-02-24
WTXE1044A 1001	Signal Generator	Agilent	83752A	3610A014 53	2023-02-25	2024-02-24
WTXE1045A 1001	Vector Signal Generator	Agilent	N5182A	MY470702 02	2023-02-25	2024-02-24
WTXE1018A 1001	Power Divider	Weinschel	1506A	PM204	2023-02-25	2024-02-24
WTXE1045A 1001	Power Divider	RF-Lambda	RFLT4W5M18G	14110400 027	2023-02-25	2024-02-24
<input checked="" type="checkbox"/> Chamber A: Below 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2023-02-25	2024-02-24
WTXE1007A 1001	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/00 5	2023-02-25	2024-02-24
WTXE1007A 1001	Amplifier	HP	8447F	2805A034 75	2023-02-25	2024-02-24
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2021-03-20	2024-03-19
WTXE1010A 1006	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2023-03-20	2026-03-19
<input checked="" type="checkbox"/> Chamber A: Above 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2023-02-25	2024-02-24
WTXE1007A 1001	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/00 5	2023-02-25	2024-02-24
WTXE1065A 1001	Amplifier	C&D	PAP-1G18	14918	2023-02-25	2024-02-24
WTXE1010A 1005	Horn Antenna	ETS	3117	00086197	2021-03-19	2024-03-18
WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2021-03-19	2024-03-18

WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2023-02-25	2024-02-24
<input type="checkbox"/> Chamber B: Below 1GHz						
WTXE1010A 1006	Trilog Broadband Antenna	Schwarz beck	VULB9163(B)	9163-635	2021-04-09	2024-04-08
WTXE1038A 1001	Amplifier	Agilent	8447D	2944A101 79	2023-02-25	2024-02-24
WTXE1001A 1002	EMI Test Receiver	Rohde & Schwarz	ESPI	101391	2023-02-25	2024-02-24
<input type="checkbox"/> Chamber C: Below 1GHz						
WTXE1093A 1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2023-02-25	2024-02-24
WTXE1010A 1013-1	Trilog Broadband Antenna	Schwarz beck	VULB 9168	1194	2021-05-28	2024-05-27
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2021-03-20	2024-03-19
WTXE1007A 1002	Amplifier	HP	8447F	2944A038 69	2023-02-25	2024-02-24
<input type="checkbox"/> Chamber C: Above 1GHz						
WTXE1093A 1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2023-02-25	2024-02-24
WTXE1103A 1005	Horn Antenna	POAM	RTF-11A	LP228060 221	2023-03-10	2026-03-09
WTXE1103A 1006	Amplifier	Tonscend	TAP01018050	AP22E806 235	2023-02-25	2024-02-24
<input checked="" type="checkbox"/> Conducted Room 1#						
WTXE1001A 1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2023-02-25	2024-02-24
WTXE1002A 1001	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2023-02-25	2024-02-24
WTXE1003A 1001	AC LISN	Schwarz beck	NSLK8126	8126-224	2023-02-25	2024-02-24
<input type="checkbox"/> Conducted Room 2#						
WTXE1001A 1004	EMI Test Receiver	Rohde & Schwarz	ESPI	101259	2023-02-25	2024-02-24
WTXE1003A 1003	LISN	Rohde & Schwarz	ENV 216	100097	2023-02-25	2024-02-24

Software List			
Description	Manufacturer	Model	Version
EMI Test Software (Radiated Emission)*	Farad	EZ-EMC	RA-03A1
EMI Test Software (Conducted Emission)*	Farad	EZ-EMC	RA-03A1

\*Remark: indicates software version used in the compliance certification testing.

## 2. SUMMARY OF TEST RESULTS

---

FCC Rules	Description of Test Item	Result
§15.203; §15.405	Antenna Requirement	Compliant
15.407 (c)	Automatically Discontinue Transmission	Compliant
§15.207; §15.407(b)(6)	Conducted Emission	Compliant
§15.407(a)(1),(2)	Power Spectral Density	Compliant
§15.407(e)	Emission Bandwidth and Occupied Bandwidth	Compliant
§15.407(a)(1),(2)	Maximum Conducted Output Power	Compliant
§15.407(b)(1),(2),(3),(4)	Undesirable emission	Compliant
§15.205; §15.407(b)(1),(2),(3)	Radiated Emission	Compliant
§15.407(g)	Frequency Stability	Compliant
§15.407(h)	Dynamic Frequency Selection (DFS)	Compliant

N/A: Not applicable.

## **3. Antenna Requirement**

---

### **3.1 Standard Applicable**

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

### **3.2 Evaluation Information**

This product has two External Antennas, fulfill the requirement of this section.

## **4. Automatically Discontinue Transmission**

---

### **4.1 Standard Applicable**

According to FCC Part 15.407(c), the device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

### **4.2 Summary of Test Results**

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

## 5. Power Spectral Density

---

### 5.1 Standard Applicable

Section 15.407(a) Power limits:

(1) For the band 5.15-5.25GHz.

(iv) For mobile and portable client devices in the 5.15-5.25GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250mW provided the maximum antenna gain does not exceed 6dBi. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(2) For the 5.25-5.35GHz and 5.47-5.725GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250mW or  $11\text{dBm} + 10 \log B$ , where B is the 26dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(3) For the band 5.725-5.85GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30dBm in any 500kHz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

### 5.2 Test Procedure

According to 789033 D02 v02r01 General UNII Test Procedures New Rules v02, the following is the measurement procedure.

For devices operating in the bands 5.15-5.25GHz, 5.25-5.35GHz, and 5.47-5.725GHz, the above procedures make use of 1MHz RBW to satisfy directly the 1MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85GHz, the rules specify a measurement bandwidth of 500kHz. Many spectrum analyzers do not have 500kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1MHz, or 500kHz, "provided that the measured power is integrated over the full

reference bandwidth" to show the total power over the specified measurement bandwidth (i.e., 1MHz, or 500kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500kHz) and integrated over 1 MHz, or 500kHz bandwidth, the following adjustments to the procedures apply:

- a) Set RBW  $\geq 1/T$ , where T is defined in section II.B.I.a).
- b) Set VBW  $\geq 3$  RBW.
- c) If measurement bandwidth of Maximum PSD is specified in 500kHz, add  $10\log(500\text{kHz}/\text{RBW})$  to the measured result, whereas RBW (< 500kHz) is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1MHz, add  $10\log(1\text{MHz}/\text{RBW})$  to the measured result, whereas RBW (< 1MHz) is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100kHz for the sections 5.c) and 5.d) above, since RBW=100kHz is available on nearly all spectrum analyzers.

### **5.3 Summary of Test Results/Plots**

**Please refer to Appendix A**

## 6. Emission Bandwidth and Occupied Bandwidth

---

### 6.1 Standard Applicable

According to 15.407(a) and (e):

(1) For the band 5.15-5.25GHz.

(iv) For mobile and portable client devices in the 5.15-5.25GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250mW provided the maximum antenna gain does not exceed 6dBi. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(2) For the 5.25-5.35GHz and 5.47-5.725GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250mW or  $11\text{dBm} + 10 \log B$ , where B is the 26dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(3) For the band 5.725-5.85GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30dBm in any 500kHz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(e) Within the 5.725-5.85GHz band, the minimum 6dB bandwidth of U-NII devices shall be at least 500kHz.

### 6.2 Test Procedure

According to 789033 D02 v02r0r section C&D, the following is the measurement procedure.

#### 1. Emission Bandwidth (EBW)

- a) Set RBW = approximately 1% of the emission bandwidth.
- b) Set the VBW > RBW.

- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Measure the maximum width of the emission that is 26dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

## 2. Minimum Emission Bandwidth for the band 5.725-5.85GHz

Section 15.407(e) specifies the minimum 6dB emission bandwidth of at least 500KHz for the band 5.715-5.85GHz. The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100kHz.
- b) Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described above.

## D. 99 Percent Occupied Bandwidth

The 99-percent occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5 % of the total mean power of the given emission. Measurement of the 99-percent occupied bandwidth is required only as a condition for using the optional band-edge measurement techniques described in section II.G.3.d). Measurements of 99-percent occupied bandwidth may also optionally be used in lieu of the EBW to 789033 D02 v02r01 General UNII Test Procedures New Rules v01 define the minimum frequency range over which the spectrum is integrated when measuring maximum conducted output power as described in section II.E. However, the EBW must be measured to determine bandwidth dependent limits on maximum conducted output power in accordance with 15.407(a).

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW  $\geq 3 *$  RBW
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).
7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency.

The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency.  
The 99% occupied bandwidth is the difference between these two frequencies.

### **6.3 Summary of Test Results/Plots**

**Please refer to Appendix B**

## 7. Maximum Conducted Output Power

---

### 7.1 Standard Applicable

Section 15.407(a) Power limits:

(1) For the band 5.15-5.25GHz.

(iv) For mobile and portable client devices in the 5.15-5.25GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250mW provided the maximum antenna gain does not exceed 6dBi. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(2) For the 5.25-5.35GHz and 5.47-5.725GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250mW or  $11\text{dBm} + 10 \log B$ , where B is the 26dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(3) For the band 5.725-5.85GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30dBm in any 500kHz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

### 7.2 Test Procedure

According to KDB789033 D02 v02r01 section E, the following is the measurement procedure.

- (i) Set span to encompass the entire emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.
- (ii) Set RBW = 1MHz.
- (iii) Set VBW  $\geq$  3MHz.
- (iv) Number of points in sweep  $\geq$  2 Span / RBW. (This ensures that bin-to-bin spacing is  $\leq$  RBW/2, so that

narrowband signals are not lost between frequency bins.)

(v) Sweep time = auto.

(vi) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.

(vii) If transmit duty cycle < 98 percent, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle  $\geq$  98 percent, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run”.

(viii) Trace average at least 100 traces in power averaging (i.e., RMS) mode.

(ix) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument’s band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at 1 MHz intervals extending across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the spectrum.

### **7.3 Summary of Test Results/Plots**

**Please refer to Appendix C**

## 8. Radiated Spurious Emissions

---

### 8.1 Standard Applicable

According to §15.407(b), undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25GHz band: All emissions outside of the 5.15-5.35GHz band shall not exceed an e.i.r.p. of -27dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35GHz band: All emissions outside of the 5.15-5.35GHz band shall not exceed an e.i.r.p. of -27dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725GHz band: All emissions outside of the 5.47-5.725GHz band shall not exceed an e.i.r.p. of -27dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85GHz band:
  - (i) All emissions shall be limited to a level of -27dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10dBm/MHz at 25MHz above or below the band edge, and from 25MHz above or below the band edge increasing linearly to a level of 15.6dBm/MHz at 5MHz above or below the band edge, and from 5MHz above or below the band edge increasing linearly to a level of 27dBm/MHz at the band edge.

According to §15.407(b)(6), Unwanted emissions below 1GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.

According to §15.407(b)(7), The provisions of §15.205 apply to intentional radiators operating under this section.

789033 D02 v02r01 General UNII Test Procedures New Rules v01

If radiated measurements are performed, field strength is then converted to EIRP as follows:

$$\text{EIRP} = ((E^*d)^2) / 30$$

where:

- E is the field strength in V/m;
- d is the measurement distance in meters;
- EIRP is the equivalent isotropically radiated power in watts.


### 8.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.407(b)(6) and FCC Part 15.209 Limit..


The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle.

The spacing between the peripherals was 10cm.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1GHz.



### 8.3 Test Receiver Setup

During the radiated emission test for above 1GHz, the test receiver was set with the following configurations:

For peak detector:

RBW = 1000kHz, VBW = 3000kHz, Sweep Time = Auto

For average detector:

RBW = 1000kHz, VBW = 10Hz, Sweep Time = Auto

### 8.4 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB $\mu$ V means the emission is 6dB $\mu$ V below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$


## 8.5 Summary of Test Results/Plots

**Note:** this EUT was tested in 3 orthogonal positions and the worst case position data was reported.


- Spurious Emission From 30MHz to 1GHz

- Antenna 0 (worst case)
- 5150-5250MHz

802.11a			
Test Channel	5180MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	45.3755	26.61	-7.68	18.93	40.00	-21.07	--	--	peak
2	105.2718	26.41	-8.44	17.97	43.50	-25.53	--	--	peak
3	244.2321	26.23	-6.50	19.73	46.00	-26.27	--	--	peak
4	332.5187	26.57	-3.74	22.83	46.00	-23.17	--	--	peak
5	457.5073	28.81	-2.06	26.75	46.00	-19.25	--	--	peak
6	651.9417	27.07	2.02	29.09	46.00	-16.91	--	--	peak




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	58.6126	26.70	-8.17	18.53	40.00	-21.47	--	--	peak
2	100.2286	26.79	-8.61	18.18	43.50	-25.32	--	--	peak
3	249.4250	26.00	-6.42	19.58	46.00	-26.42	--	--	peak
4	375.9385	27.77	-3.14	24.63	46.00	-21.37	--	--	peak
5	494.1984	28.13	-1.11	27.02	46.00	-18.98	--	--	peak
6	661.1505	27.82	2.10	29.92	46.00	-16.08	--	--	peak

802.11n-HT20			
Test Channel	5180MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	49.3594	27.46	-7.37	20.09	40.00	-19.91	--	--	peak
2	108.2667	26.54	-8.59	17.95	43.50	-25.55	--	--	peak
3	234.9909	26.36	-6.90	19.46	46.00	-26.54	--	--	peak
4	329.0390	27.14	-3.89	23.25	46.00	-22.75	--	--	peak
5	460.7271	27.30	-2.05	25.25	46.00	-20.75	--	--	peak
6	661.1505	27.75	2.10	29.85	46.00	-16.15	--	--	peak




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	38.3462	26.14	-8.89	17.25	40.00	-22.75	--	--	peak
2	54.0711	26.88	-7.52	19.36	40.00	-20.64	--	--	peak
3	108.6470	27.47	-8.63	18.84	43.50	-24.66	--	--	peak
4	204.9551	25.96	-8.07	17.89	43.50	-25.61	--	--	peak
5	341.9787	25.75	-3.34	22.41	46.00	-23.59	--	--	peak
6	625.0780	27.93	1.50	29.43	46.00	-16.57	--	--	peak

802.11n-HT40			
Test Channel	5190MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	53.8818	26.62	-7.50	19.12	40.00	-20.88	--	--	peak
2	107.1337	26.83	-8.51	18.32	43.50	-25.18	--	--	peak
3	239.9874	26.80	-6.67	20.13	46.00	-25.87	--	--	peak
4	314.3765	25.62	-4.48	21.14	46.00	-24.86	--	--	peak
5	440.1963	27.29	-2.09	25.20	46.00	-20.80	--	--	peak
6	599.3213	28.51	1.38	29.89	46.00	-16.11	--	--	peak




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	39.1616	27.34	-8.73	18.61	40.00	-21.39	--	--	peak
2	103.4421	26.73	-8.45	18.28	43.50	-25.22	--	--	peak
3	187.0958	26.64	-9.00	17.64	43.50	-25.86	--	--	peak
4	364.2595	27.80	-3.49	24.31	46.00	-21.69	--	--	peak
5	647.3856	27.07	1.99	29.06	46.00	-16.94	--	--	peak
6	848.0563	24.34	4.47	28.81	46.00	-17.19	--	--	peak

802.11ac-VHT20			
Test Channel	5180MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	44.2752	27.61	-7.82	19.79	40.00	-20.21	--	--	peak
2	55.2207	26.48	-7.65	18.83	40.00	-21.17	--	--	peak
3	103.8055	26.96	-8.43	18.53	43.50	-24.97	--	--	peak
4	339.5888	26.90	-3.44	23.46	46.00	-22.54	--	--	peak
5	425.0280	26.51	-2.11	24.40	46.00	-21.60	--	--	peak
6	645.1195	27.44	1.94	29.38	46.00	-16.62	--	--	peak




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	54.2610	26.19	-7.53	18.66	40.00	-21.34	--	--	peak
2	105.2718	26.44	-8.44	18.00	43.50	-25.50	--	--	peak
3	223.7334	26.03	-7.46	18.57	46.00	-27.43	--	--	peak
4	389.3549	28.27	-2.83	25.44	46.00	-20.56	--	--	peak
5	432.5457	27.77	-2.09	25.68	46.00	-20.32	--	--	peak
6	656.5300	27.96	2.04	30.00	46.00	-16.00	--	--	peak

802.11ac-VHT40			
Test Channel	5190MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	49.0145	26.76	-7.37	19.39	40.00	-20.61	--	--	peak
2	98.8326	29.00	-8.75	20.25	43.50	-23.25	--	--	peak
3	223.7334	26.03	-7.46	18.57	46.00	-27.43	--	--	peak
4	313.2760	26.76	-4.51	22.25	46.00	-23.75	--	--	peak
5	432.5457	27.77	-2.09	25.68	46.00	-20.32	--	--	peak
6	661.1505	28.75	2.10	30.85	46.00	-15.15	--	--	peak




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	48.3318	26.81	-7.41	19.40	40.00	-20.60	--	--	peak
2	103.0800	26.34	-8.45	17.89	43.50	-25.61	--	--	peak
3	171.3926	26.09	-10.57	15.52	43.50	-27.98	--	--	peak
4	341.9787	25.26	-3.34	21.92	46.00	-24.08	--	--	peak
5	420.5803	26.45	-2.17	24.28	46.00	-21.72	--	--	peak
6	663.4729	27.41	2.10	29.51	46.00	-16.49	--	--	peak

802.11ac-VHT80			
Test Channel	5210MHz	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	39.7147	26.70	-8.63	18.07	40.00	-21.93	--	--	peak
2	99.1797	26.53	-8.71	17.82	43.50	-25.68	--	--	peak
3	136.9392	27.61	-11.72	15.89	43.50	-27.61	--	--	peak
4	237.4760	25.69	-6.78	18.91	46.00	-27.09	--	--	peak
5	377.2591	26.72	-3.11	23.61	46.00	-22.39	--	--	peak
6	625.0780	27.03	1.50	28.53	46.00	-17.47	--	--	peak



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	46.9948	27.48	-7.50	19.98	40.00	-20.02	--	--	peak
2	99.5281	27.89	-8.66	19.23	43.50	-24.27	--	--	peak
3	208.5803	26.41	-8.15	18.26	43.50	-25.24	--	--	peak
4	306.7537	27.54	-4.63	22.91	46.00	-23.09	--	--	peak
5	558.7302	30.08	0.02	30.10	46.00	-15.90	--	--	peak
6	656.5300	27.54	2.04	29.58	46.00	-16.42	--	--	peak


Remark: '-'Means' the test Degree and Height are not recorded by the test software and only show the worst case in the test report.

- Spurious Emission above 1GHz
- Antenna 0(worst case)

## BAND 1


802.11a- Restricted Bandedge

Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)
--------------	-------------------	-----------	------------------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	5145.450	66.96	-2.24	64.72	74.00	-9.28	--	--	peak


802.11a- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	5150.000	46.35	-2.23	44.12	59.50	-15.38	--	--	AVG



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	5150.000	63.85	-2.23	61.62	74.00	-12.38	--	--	peak




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	5150.000	47.76	-2.23	45.53	54.00	-8.47	--	--	AVG




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	5150.000	69.27	-2.23	67.04	74.00	-6.96	--	--	peak

802.11n-HT40- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	5150.000	51.86	-2.23	49.63	54.00	-4.37	--	--	AVG

802.11ac-VHT20- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	5150.000	66.61	-2.23	64.38	74.00	-9.62	--	--	peak

802.11ac-VHT20- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	5150.000	47.76	-2.23	45.53	54.00	-8.47	--	--	AVG




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	5150.000	71.60	-2.23	69.37	74.00	-4.63	--	--	peak

802.11ac-VHT40- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	5150.000	51.28	-2.23	49.05	54.00	-4.95	--	--	AVG

802.11ac-VHT80- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	5148.050	66.70	-2.23	64.47	74.00	-9.53	--	--	peak



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	5149.350	50.83	-2.23	48.60	54.00	-5.40	--	--	AVG

Note: this EUT was tested in the low, high channel and the worst case position data was reported.

- The worse mode Antenna 0
- For the frequency band 5.15-5.25GHz (802.11a)
- Harmonics And Spurious Emissions

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar	Detector
Low Channel (5180MHz)							
10360	58.79	7.11	65.90	74	-8.10	H	PK
10360	41.16	7.11	48.27	54	-5.73	H	AV
10360	57.24	7.11	64.35	74	-9.65	V	PK
10360	38.73	7.11	45.84	54	-8.16	V	AV
Middle Channel (5200MHz)							
10400	58.24	7.22	65.46	74	-8.54	H	PK
10400	38.43	7.22	45.65	54	-8.35	H	AV
10400	56.48	7.22	63.70	74	-10.30	V	PK
10400	40.35	7.22	47.57	54	-6.43	V	AV
High Channel (5240MHz)							
10480	56.28	7.69	63.97	74	-10.03	H	PK
10480	40.19	7.69	47.88	54	-6.12	H	AV
10480	56.53	7.69	64.22	74	-9.78	V	PK
10480	38.58	7.69	46.27	54	-7.73	V	AV

- Out of Band edge for 5150-5250MHz

Test CH.	Test Segment		Result dBm/MHz	Limit dBm/MHz
	MHz			
Lowest	Below 5150		-42.58	-27
Highest	Above 5350		-41.74	-27

Note: the data just list the worst cases

- For the frequency band 5.15-5.25GHz (802.11n HT20)
- Harmonics And Spurious Emissions

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar	Detector
Low Channel (5180MHz)							
10360	58.95	7.11	66.06	74	-7.94	H	PK
10360	38.09	7.11	45.20	54	-8.80	H	AV
10360	55.26	7.11	62.37	74	-11.63	V	PK
10360	38.45	7.11	45.56	54	-8.44	V	AV
Middle Channel (5200MHz)							
10400	55.07	7.22	62.29	74	-11.71	H	PK
10400	39.08	7.22	46.30	54	-7.70	H	AV
10400	55.53	7.22	62.75	74	-11.25	V	PK
10400	38.84	7.22	46.06	54	-7.94	V	AV
High Channel (5240MHz)							
10480	57.33	7.69	65.02	74	-8.98	H	PK
10480	41.18	7.69	48.87	54	-5.13	H	AV
10480	57.04	7.69	64.73	74	-9.27	V	PK
10480	41.41	7.69	49.10	54	-4.90	V	AV

- Out of Band edge 5150-5250MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-39.54	-27
Highest	Above 5350	-40.57	-27

Note: the data just list the worst cases

*Note: this EUT was tested in the low, high channel and the worst case position data was reported.*

- For the frequency band 5.15-5.25GHz (802.11n HT40)
- Harmonics And Spurious Emissions

<b>Frequency</b> <b>(MHz)</b>	<b>Reading</b> <b>(dBuV/m)</b>	<b>Correct</b> <b>dB</b>	<b>Result</b> <b>(dBuV/m)</b>	<b>Limit</b> <b>(dBuV/m)</b>	<b>Margin</b> <b>(dB)</b>	<b>Polar</b>	<b>Detector</b>
Low Channel (5190MHz)							
10380	55.29	7.89	63.18	74	-10.82	H	PK
10380	38.70	7.89	46.59	54	-7.41	H	AV
10380	57.50	7.89	65.39	74	-8.61	V	PK
10380	40.52	7.89	48.41	54	-5.59	V	AV
High Channel (5230MHz)							
10460	56.25	7.97	64.22	74	-9.78	H	PK
10460	41.48	7.97	49.45	54	-4.55	H	AV
10460	55.60	7.97	63.57	74	-10.43	V	PK
10460	41.75	7.97	49.72	54	-4.28	V	AV

- Out of Band edge for 5150-5250MHz

<b>Test CH.</b>	<b>Test Segment</b>		<b>Result</b>	<b>Limit</b>
	<b>MHz</b>		<b>dBm/MHz</b>	<b>dBm/MHz</b>
Lowest	Below 5150		-38.47	-27
Highest	Above 5350		-39.68	-27
Note: the data just list the worst cases				

- For the frequency band 5.15-5.25GHz (802.11ac VHT80)
- Harmonics And Spurious Emissions

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar	Detector
5210MHz							
10420	58.78	7.53	66.31	74	-7.69	H	PK
10420	38.43	7.53	45.96	54	-8.04	H	AV
10420	58.97	7.53	66.50	74	-7.50	H	PK
10420	41.48	7.53	49.01	54	-4.99	H	AV

- Out of Band edge for 5150-5250MHz

Test CH.	Test Segment		Result	Limit
	MHz		dBm/MHz	dBm/MHz
Lowest	Below 5150		-37.49	-27
Highest	Above 5350		-36.31	-27

Note: the data just list the worst cases

*Note: Testing is carried out with frequency rang 9kHz to 40GHz, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*

## **9. Frequency Stability**

---

### **9.1 Standard Applicable**

According to §15.407(g), manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.

### **9.2 Test Procedure**

According to §2.1055, the following test procedure was performed.

The Frequency Stability is measured directly with a Frequency Domain Analyzer. Frequency Deviation in ppm is calculated from the measured peak to peak value.

The Carrier Frequency Stability over Power Supply Voltage and over Temperature is measured with a Frequency Domain Analyzer in histogram mode.

### **9.3 Summary of Test Results/Plots**

**Please refer to Appendix D**


## 10 Conducted Emissions

### 10.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.

### 10.2 Basic Test Setup Block Diagram




### 10.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency .....	150kHz
Stop Frequency .....	30MHz
Sweep Speed .....	Auto
IF Bandwidth.....	10kHz
Quasi-Peak Adapter Bandwidth .....	9kHz
Quasi-Peak Adapter Mode .....	Normal


### 10.4 Summary of Test Results/Plots

Test Mode	Communication	AC120V 60Hz	Polarity:	Neutral
-----------	---------------	-------------	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1860	44.36	10.40	54.76	64.21	-9.45	QP
2*	0.1860	35.26	10.40	45.66	54.21	-8.55	AVG
3	0.2220	29.17	10.37	39.54	52.74	-13.20	AVG
4	0.2420	38.45	10.35	48.80	62.02	-13.22	QP
5	0.4580	33.91	10.25	44.16	56.73	-12.57	QP
6	0.4740	26.07	10.25	36.32	46.44	-10.12	AVG
7	1.0300	23.74	10.14	33.88	56.00	-22.12	QP
8	1.0900	17.33	10.16	27.49	46.00	-18.51	AVG
9	1.9740	16.05	10.33	26.38	46.00	-19.62	AVG
10	2.3740	21.30	10.34	31.64	56.00	-24.36	QP
11	4.9899	19.39	10.38	29.77	56.00	-26.23	QP
12	5.3580	13.95	10.38	24.33	50.00	-25.67	AVG

Test Mode	Communication	AC120V 60Hz	Polarity:	Line
-----------	---------------	-------------	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.1620	45.38	10.40	55.78	65.36	-9.58	QP
2	0.1819	33.72	10.39	44.11	54.39	-10.28	AVG
3	0.4540	23.44	10.25	33.69	46.80	-13.11	AVG
4	0.4620	32.42	10.25	42.67	56.66	-13.99	QP
5	1.0859	23.93	10.16	34.09	56.00	-21.91	QP
6	1.0859	14.10	10.16	24.26	46.00	-21.74	AVG
7	2.2940	19.67	10.33	30.00	56.00	-26.00	QP
8	2.3940	12.46	10.34	22.80	46.00	-23.20	AVG
9	3.5860	10.33	10.36	20.69	46.00	-25.31	AVG
10	3.6860	18.58	10.36	28.94	56.00	-27.06	QP
11	6.2060	7.59	10.38	17.97	50.00	-32.03	AVG
12	7.5700	17.07	10.38	27.45	60.00	-32.55	QP

## APPENDIX SUMMARY

---

Project No.	WTH23X05106882W	Test Engineer	Elin Su
Start date	2023/5/25	Finish date	2023/7/20
Temperature	23°C	Humidity	59%
RF specifications	U-NII		


APPENDIX	Description of Test Item	Result
A	Power Spectral Density	Compliant
B	Emission Bandwidth and Occupied Bandwidth	Compliant
C	Maximum Conducted Output Power	Compliant
D	Frequency Stability	Compliant


## APPENDIX A


---


<b>Power Spectral Density</b>					
<b>U-NII-1:5150-5250MHz</b>					
Operating mode	Test Channel	ANT 0 dBm/MHz	ANT 1 dBm/MHz	Total dBm/MHz	Limit (dBm/MHz)
802.11a	5180	6.38	5.30	/	11
	5200	5.12	5.02	/	11
	5240	5.79	5.28	/	11
802.11n-HT20	5180	3.91	3.56	6.75	11
	5200	4.21	3.77	7.01	11
	5240	4.41	4.20	7.32	11
802.11n-HT40	5190	1.13	0.87	4.01	11
	5230	0.89	1.25	4.08	11
802.11ac-VHT20	5180	1.61	1.39	4.51	11
	5200	1.89	1.71	4.81	11
	5240	2.25	2.42	5.35	11
802.11ac-VHT40	5190	-1.58	-1.30	1.57	11
	5230	-1.42	-1.53	1.54	11
802.11ac-VHT80	5210	-5.63	-5.79	-2.70	11


**ANT 0**  
**5150-5250MHz**















## ANT 1


### 5150-5250MHz











## APPENDIX B


---


### Emission Bandwidth and Occupied Bandwidth


U-NII-1:5150-5250MHz						
Test Mode	Test Channel MHz	ANT 0		ANT 1		Result
		26 dB Bandwidth MHz	99% Bandwidth MHz	26 dB Bandwidth MHz	99% Bandwidth MHz	
802.11a	5180	26.50	18.10	26.40	18.00	Pass
	5200	26.10	18.10	26.60	18.10	Pass
	5240	21.60	17.20	22.50	17.20	Pass
802.11n-HT20	5180	27.40	18.70	27.40	18.70	Pass
	5200	27.60	18.70	27.60	18.70	Pass
	5240	27.30	18.20	27.20	18.20	Pass
802.11n-HT40	5190	41.20	36.20	41.40	36.20	Pass
	5230	41.40	36.20	41.40	36.20	Pass
802.11ac-VHT20	5180	27.60	18.80	27.70	18.80	Pass
	5200	27.60	18.70	26.80	18.70	Pass
	5240	22.10	18.20	28.20	18.20	Pass
802.11ac-VHT40	5190	41.40	36.00	41.00	36.20	Pass
	5230	41.20	36.20	41.20	36.20	Pass
802.11ac-VHT80	5210	81.20	75.60	81.20	75.60	Pass


## ANT 0


### 5150-5250MHz






























## ANT 1


### 5150-5250MHz


























## APPENDIX C


---


### Maximum Conducted Output Power


U-NII-1:5150-5250MHz					
Test mode	Frequency MHz	Output Power dBm		Total dBm	Limit dBm
		ANT 0	ANT 1		
802.11a	5180	15.86	15.26	/	23.98
	5200	15.05	15.51	/	23.98
	5240	15.77	15.75	/	23.98
802.11n-HT20	5180	13.60	13.63	16.63	23.98
	5200	13.58	13.72	16.66	23.98
	5240	13.74	13.57	16.67	23.98
802.11n-HT40	5190	13.14	13.48	16.32	23.98
	5230	13.30	13.61	16.47	23.98
802.11ac-VHT20	5180	12.24	12.02	15.14	23.98
	5200	12.42	12.33	15.39	23.98
	5240	12.56	12.45	15.52	23.98
802.11ac-VHT40	5190	11.06	11.35	14.22	23.98
	5230	11.24	11.13	14.20	23.98
802.11ac-VHT80	5210	10.27	10.43	13.36	23.98


## ANT 0


### 5150-5250MHz















## ANT 1


### 5150-5250MHz











## APPENDIX D

---

### Frequency Stability

U-NII-1:5150-5250MHz worst case at 802.11a middle channel				
Voltage(%)	Power(VDC)	TEMP(°C)	Freq.Dev(Hz)	Deviation
100%	5.0	-30	243	0.0469
100%		-20	158	0.0305
100%		-10	463	0.0894
100%		0	245	0.0473
100%		+10	651	0.1257
100%		+20	421	0.0813
100%		+30	349	0.0674
100%		+40	436	0.0842
100%		+50	254	0.0490
Low power	5.50	+20	194	0.0375
High power	4.50	+20	439	0.0847

## APPENDIX PHOTOGRAPHS

---

Please refer to "ANNEX"

\*\*\*\*\* END OF REPORT \*\*\*\*\*