

Conducted test results

No.1-5154/22-01-08_Annex_MR

October 13, 2023

Test Standard(s)	NA - NI
	FCC 15.247 - NI
	FCC 15.247, ISED RSS247 - NI

This document is electronically signed and valid without handwritten signature.
Public keys for verification of the electronic signatures can be requested at the testing laboratory.

Authorized

Andreas Curette
Testing Manager
Radio Labs

Table of Content

NA # Terminal communication serial ~ Common	3
FCC 15.247 # Maximum peak conducted output power DTS ~ Generic 2G4	5
FCC 15.247 # Bandwidth 6dB DTS ~ Generic 2G4	8
FCC 15.247 # Peak psd DTS ~ Generic 2G4	10
FCC 15.247, ISED RSS247 # Bandwidth 99PCT and 20dB ~ Generic 2G4	12
FCC 15.247 # TX spurious conducted 20dBc ~ Generic 2G4	16
NA # Terminal communication serial ~ Common	19
FCC 15.247 # Maximum peak conducted output power DTS ~ Generic 2G4	21
FCC 15.247 # Bandwidth 6dB DTS ~ Generic 2G4	24
FCC 15.247 # Peak psd DTS ~ Generic 2G4	26
FCC 15.247, ISED RSS247 # Bandwidth 99PCT and 20dB ~ Generic 2G4	28
FCC 15.247 # TX spurious conducted 20dBc ~ Generic 2G4	32
NA # Terminal communication serial ~ Common	35
FCC 15.247 # Maximum peak conducted output power DTS ~ Generic 2G4	37
FCC 15.247 # Bandwidth 6dB DTS ~ Generic 2G4	40
FCC 15.247 # Peak psd DTS ~ Generic 2G4	42
FCC 15.247, ISED RSS247 # Bandwidth 99PCT and 20dB ~ Generic 2G4	44
FCC 15.247 # TX spurious conducted 20dBc ~ Generic 2G4	48
NA # Terminal communication serial ~ Common	51
FCC 15.247 # Maximum peak conducted output power DTS ~ Generic 2G4	53
FCC 15.247 # Bandwidth 6dB DTS ~ Generic 2G4	56
FCC 15.247 # Peak psd DTS ~ Generic 2G4	58
FCC 15.247, ISED RSS247 # Bandwidth 99PCT and 20dB ~ Generic 2G4	60
FCC 15.247 # TX spurious conducted 20dBc ~ Generic 2G4	64

NA # Terminal communication serial ~ Common

References

TC start	06.10.2023 10:27:29
Ambit temp [°C] humidity [rel%]	25.7 36
System version	4.6.2.0
Standard Version	NA NI
Method	
Description	Terminal communication serial
Information	

Test Parameter

Command	cancel
Output result	cancel

Test Parameter

Command	data_rate ieee802154_250Kbit
Output result	data_rate ieee802154_250Kbit Data rate: NRF_RADIO_MODE_IEEE802154_250KBIT

Test Parameter

Command	output_power pos3dBm
Output result	output_power pos3dBm TX power: RADIO_TXPOWER_TXPOWER_Pos3dBm

Test Parameter

Command	start_channel 11
Output result	start_channel 11 Start channel set to: 11

Test Parameter

Command	end_channel 11
Output result	end_channel 11 End channel set to: 11

Test Parameter

Command	transmit_pattern pattern_random
Output result	transmit_pattern pattern_random Transmission pattern: TRANSMIT_PATTERN_RANDOM

Test Parameter

Command	start_duty_cycle_modulated_tx 90
Output result	start_duty_cycle_modulated_tx 90 Requested tx output power: 3 dBm Tx output power set to: 3 dBm

Verdict

INFO

FCC 15.247 # Maximum peak conducted output power DTS ~ Generic 2G4

References

TC start	06.10.2023 10:27:41
Ambit temp [°C] humidity [rel%]	25.7 36
System version	4.6.2.0
Standard Version	FCC 15.247 NI
Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.1 RBW ≥ DTS Bandwidth
Description	FCC 15.247 Max Peak Output Power Conducted DTS4 - Generic 2G4
Information	

EUT Common settings 2G4

Hopping supported	No
Burst length [ms]	2.4
Nominal Bandwidth [MHz]	2.431
User Interaction	No

Test Parameter

Technology to test	Generic 2G4
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2405
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	False Freq [MHz] 2480
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI

Test at TX 2405 MHz

RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	0.82	dBm	INFO
Ref. Frequency	---	---	2405.500	MHz	INFO

READ SA SETTINGS:


RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	5.82 10.8 15
Start [MHz] Stop [MHz]	2402.569 2407.431
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 10001 SWE

DTS Bandwidth

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
DTS Bandwidth (6dB)	---	---	1133	kHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	10.82 10.8 20
Start [MHz] Stop [MHz]	2402.569 2407.431
RBW [MHz] VBW [MHz]	2.000000 5.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 1001 SWE



Peak output power

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Peak Power	---	30.00	0.76	dBm	PASS
Peak Power	---	1000	1.191242	mW	PASS
Frequency at Peak	---	---	2404.505	MHz	INFO

Verdict

PASS

FCC 15.247 # Bandwidth 6dB DTS ~ Generic 2G4

References

TC start	06.10.2023 10:28:25
Ambit temp [°C] humidity [rel%]	25.7 36
System version	4.6.2.0
Standard Version	FCC 15.247 NI
Method	
Description	FCC 15.247 Bandwidth 6DB DTS - Generic 2G4
Information	

EUT Common settings 2G4

Hopping supported	No
Burst length [ms]	2.4
Nominal Bandwidth [MHz]	2.431
User Interaction	No

Test Parameter

Technology to test	Generic 2G4
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2405
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	False Freq [MHz] 2480
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI


Test at TX 2405 MHz

RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	0.82	dBm	INFO
Ref. Frequency	---	---	2405.500	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	5.82 10.8 15
Start [MHz] Stop [MHz]	2402.569 2407.431
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 10001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
DTS Bandwidth (6dB)	500	---	1142	kHz	PASS

Verdict

PASS

FCC 15.247 # Peak psd DTS ~ Generic 2G4

References

TC start	06.10.2023 10:28:56
Ambit temp [°C] humidity [rel%]	25.7 36
System version	4.6.2.0
Standard Version	FCC 15.247 NI
Method	DTS: KDB 558074 D01 V05 - Chapter 8.4 DTS maximum power spectral density level in the fundamental emission
Description	FCC 15.247 Peak psd DTS - Generic 2G4
Information	

EUT Common settings 2G4

Hopping supported	No
Burst length [ms]	2.4
Nominal Bandwidth [MHz]	2.431
User Interaction	No

Test Parameter

Technology to test	Generic 2G4
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2405
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	False Freq [MHz] 2480
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI


Test at TX 2405 MHz

RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	0.87	dBm	INFO
Ref. Frequency	---	---	2404.500	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	5.87 10.8 15
Start [MHz] Stop [MHz]	2403.177 2406.823
RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1000 20 1001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Peak psd	---	8	-14.39	dBm/3KHz	PASS

Verdict

PASS

FCC 15.247, ISED RSS247 # Bandwidth 99PCT and 20dB ~ Generic 2G4

References

TC start	06.10.2023 10:29:37
Ambit temp [°C] humidity [rel%]	25.7 35
System version	4.6.2.0
Standard Version	FCC 15.247, ISED RSS247 NI
Method	
Description	FCC 15.247 Bandwidth 99PCT-20DB DTS - Generic 2G4
Information	

EUT Common settings 2G4

Hopping supported	No
Burst length [ms]	2.4
Nominal Bandwidth [MHz]	2.431
User Interaction	No

Test Parameter

Technology to test	Generic 2G4
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2405
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	False Freq [MHz] 2480
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI


Test at TX 2405 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	0.79	dBm	INFO
Ref. Frequency	---	---	2404.500	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	5.79 10.8 10
Start [MHz] Stop [MHz]	2402.569 2407.431
RBW [MHz] VBW [MHz]	0.050000 0.200000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 10001 SWE







BW within Band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	2383.000	kHz	INFO
T1 99%	2400.000000	---	2403.8148	MHz	PASS
T2 99%	---	2483.500000	2406.1979	MHz	PASS



BW 20dB



BW within Band 20dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 20dB	---	---	2519	kHz	INFO
T1 20dB	2400.000000	---	2403.7529	MHz	PASS
T2 20dB	---	2483.500000	2406.2719	MHz	PASS

Verdict

PASS

FCC 15.247 # TX spurious conducted 20dBc ~ Generic 2G4

References

TC start	06.10.2023 10:30:16
Ambit temp [°C] humidity [rel%]	25.8 35
System version	4.6.2.0
Standard Version	FCC 15.247 NI
Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable
Description	FCC 15.247 TX Emissions Conducted DTS - Generic 2G4
Information	

EUT Common settings 2G4

Hopping supported	No
Burst length [ms]	2.4
Nominal Bandwidth [MHz]	2.431
User Interaction	No

Test Parameter

Technology to test	Generic 2G4
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2405
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	False Freq [MHz] 2480
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer


Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI

Test at TX 2405 MHz

RESULT: Reference Power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	0.81	dBm	INFO
Ref. Frequency	---	---	2405.500	MHz	INFO



TX emissions

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	0.81 0 20
Start [MHz] Stop [MHz]	24530.000 25030.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	200 25 2001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Reference @ 2405.00 MHz	---	---	-3.92	dBm	INFO
No peaks detected	---	---			PASS
Lowest margin to limit 15108.5 MHz	0	---	21.55	dB	INFO

Verdict

PASS

NA # Terminal communication serial ~ Common

References

TC start	06.10.2023 10:36:56
Ambit temp [°C] humidity [rel%]	26.0 35
System version	4.6.2.0
Standard Version	NA NI
Method	
Description	Terminal communication serial
Information	

Test Parameter

Command	cancel
Output result	cancel

Test Parameter

Command	data_rate ieee802154_250Kbit
Output result	data_rate ieee802154_250Kbit Data rate: NRF_RADIO_MODE_IEEE802154_250KBIT

Test Parameter

Command	output_power pos3dBm
Output result	output_power pos3dBm TX power: RADIO_TXPOWER_TXPOWER_Pos3dBm

Test Parameter

Command	start_channel 18
Output result	start_channel 18 Start channel set to: 18

Test Parameter

Command	end_channel 18
Output result	end_channel 18 End channel set to: 18

Test Parameter

Command	transmit_pattern pattern_random
Output result	transmit_pattern pattern_random Transmission pattern: TRANSMIT_PATTERN_RANDOM

Test Parameter

Command	start_duty_cycle_modulated_tx 90
Output result	start_duty_cycle_modulated_tx 90 Requested tx output power: 3 dBm Tx output power set to: 3 dBm

Verdict

INFO

FCC 15.247 # Maximum peak conducted output power DTS ~ Generic 2G4

References

TC start	06.10.2023 10:37:09
Ambit temp [°C] humidity [rel%]	26.0 35
System version	4.6.2.0
Standard Version	FCC 15.247 NI
Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.1 RBW ≥ DTS Bandwidth
Description	FCC 15.247 Max Peak Output Power Conducted DTS4 - Generic 2G4
Information	

EUT Common settings 2G4

Hopping supported	No
Burst length [ms]	2.4
Nominal Bandwidth [MHz]	2.431
User Interaction	No

Test Parameter

Technology to test	Generic 2G4
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2405
Frequency mid to test	True Freq [MHz] 2440
Frequency high to test	False Freq [MHz] 2480
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI

Test at TX 2440 MHz

RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	1.39	dBm	INFO
Ref. Frequency	---	---	2440.500	MHz	INFO

READ SA SETTINGS:


RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	6.39 10.8 15
Start [MHz] Stop [MHz]	2437.569 2442.431
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 10001 SWE

DTS Bandwidth

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
DTS Bandwidth (6dB)	---	---	1204	kHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	11.39 10.8 20
Start [MHz] Stop [MHz]	2437.569 2442.431
RBW [MHz] VBW [MHz]	2.000000 5.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 1001 SWE



Peak output power

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Peak Power	---	30.00	1.29	dBm	PASS
Peak Power	---	1000	1.34586	mW	PASS
Frequency at Peak	---	---	2440.5	MHz	INFO

Verdict

PASS

FCC 15.247 # Bandwidth 6dB DTS ~ Generic 2G4

References

TC start	06.10.2023 10:37:53
Ambit temp [°C] humidity [rel%]	26.0 35
System version	4.6.2.0
Standard Version	FCC 15.247 NI
Method	
Description	FCC 15.247 Bandwidth 6DB DTS - Generic 2G4
Information	

EUT Common settings 2G4

Hopping supported	No
Burst length [ms]	2.4
Nominal Bandwidth [MHz]	2.431
User Interaction	No

Test Parameter

Technology to test	Generic 2G4
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2405
Frequency mid to test	True Freq [MHz] 2440
Frequency high to test	False Freq [MHz] 2480
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI


Test at TX 2440 MHz

RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	1.33	dBm	INFO
Ref. Frequency	---	---	2439.500	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	6.33 10.8 15
Start [MHz] Stop [MHz]	2437.569 2442.431
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 10001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
DTS Bandwidth (6dB)	500	---	1197	kHz	PASS

Verdict

PASS

FCC 15.247 # Peak psd DTS ~ Generic 2G4

References

TC start	06.10.2023 10:38:24
Ambit temp [°C] humidity [rel%]	26.0 35
System version	4.6.2.0
Standard Version	FCC 15.247 NI
Method	DTS: KDB 558074 D01 V05 - Chapter 8.4 DTS maximum power spectral density level in the fundamental emission
Description	FCC 15.247 Peak psd DTS - Generic 2G4
Information	

EUT Common settings 2G4

Hopping supported	No
Burst length [ms]	2.4
Nominal Bandwidth [MHz]	2.431
User Interaction	No

Test Parameter

Technology to test	Generic 2G4
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2405
Frequency mid to test	True Freq [MHz] 2440
Frequency high to test	False Freq [MHz] 2480
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI


Test at TX 2440 MHz

RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	1.37	dBm	INFO
Ref. Frequency	---	---	2439.500	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	6.37 10.8 15
Start [MHz] Stop [MHz]	2438.177 2441.823
RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1000 20 1001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Peak psd	---	8	-14.12	dBm/3KHz	PASS

Verdict

PASS

FCC 15.247, ISED RSS247 # Bandwidth 99PCT and 20dB ~ Generic 2G4

References

TC start	06.10.2023 10:39:05
Ambit temp [°C] humidity [rel%]	26.0 35
System version	4.6.2.0
Standard Version	FCC 15.247, ISED RSS247 NI
Method	
Description	FCC 15.247 Bandwidth 99PCT-20DB DTS - Generic 2G4
Information	

EUT Common settings 2G4

Hopping supported	No
Burst length [ms]	2.4
Nominal Bandwidth [MHz]	2.431
User Interaction	No

Test Parameter

Technology to test	Generic 2G4
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2405
Frequency mid to test	True Freq [MHz] 2440
Frequency high to test	False Freq [MHz] 2480
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI


Test at TX 2440 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	1.33	dBm	INFO
Ref. Frequency	---	---	2439.500	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	6.33 10.8 15
Start [MHz] Stop [MHz]	2437.569 2442.431
RBW [MHz] VBW [MHz]	0.050000 0.200000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 10001 SWE







BW within Band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	2386.000	kHz	INFO
T1 99%	2400.000000	---	2438.8216	MHz	PASS
T2 99%	---	2483.500000	2441.2076	MHz	PASS



BW 20dB



BW within Band 20dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 20dB	---	---	2519	kHz	INFO
T1 20dB	2400.000000	---	2438.7524	MHz	PASS
T2 20dB	---	2483.500000	2441.2719	MHz	PASS

Verdict

PASS

FCC 15.247 # TX spurious conducted 20dBc ~ Generic 2G4

References

TC start	06.10.2023 10:39:44
Ambit temp [°C] humidity [rel%]	26.1 35
System version	4.6.2.0
Standard Version	FCC 15.247 NI
Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable
Description	FCC 15.247 TX Emissions Conducted DTS - Generic 2G4
Information	

EUT Common settings 2G4

Hopping supported	No
Burst length [ms]	2.4
Nominal Bandwidth [MHz]	2.431
User Interaction	No

Test Parameter

Technology to test	Generic 2G4
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2405
Frequency mid to test	True Freq [MHz] 2440
Frequency high to test	False Freq [MHz] 2480
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer


Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI

Test at TX 2440 MHz

RESULT: Reference Power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	1.38	dBm	INFO
Ref. Frequency	---	---	2440.500	MHz	INFO



TX emissions

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	1.38 0 20
Start [MHz] Stop [MHz]	24530.000 25030.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	200 25 2001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Reference @ 2440.25 MHz	---	---	-3.37	dBm	INFO
No peaks detected	---	---			PASS
Lowest margin to limit 15164 MHz	0	---	21.92	dB	INFO

Verdict

PASS

NA # Terminal communication serial ~ Common

References

TC start	06.10.2023 10:46:24
Ambit temp [°C] humidity [rel%]	26.5 35
System version	4.6.2.0
Standard Version	NA NI
Method	
Description	Terminal communication serial
Information	

Test Parameter

Command	cancel
Output result	cancel

Test Parameter

Command	data_rate ieee802154_250Kbit
Output result	data_rate ieee802154_250Kbit Data rate: NRF_RADIO_MODE_IEEE802154_250KBIT

Test Parameter

Command	output_power pos3dBm
Output result	output_power pos3dBm TX power: RADIO_TXPOWER_TXPOWER_Pos3dBm

Test Parameter

Command	start_channel 25
Output result	start_channel 25 Start channel set to: 25

Test Parameter

Command	end_channel 25
Output result	end_channel 25 End channel set to: 25

Test Parameter

Command	transmit_pattern pattern_random
Output result	transmit_pattern pattern_random Transmission pattern: TRANSMIT_PATTERN_RANDOM

Test Parameter

Command	start_duty_cycle_modulated_tx 90
Output result	start_duty_cycle_modulated_tx 90 Requested tx output power: 3 dBm Tx output power set to: 3 dBm

Verdict

INFO

FCC 15.247 # Maximum peak conducted output power DTS ~ Generic 2G4

References

TC start	06.10.2023 10:46:36
Ambit temp [°C] humidity [rel%]	26.5 34
System version	4.6.2.0
Standard Version	FCC 15.247 NI
Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.1 RBW ≥ DTS Bandwidth
Description	FCC 15.247 Max Peak Output Power Conducted DTS4 - Generic 2G4
Information	

EUT Common settings 2G4

Hopping supported	No
Burst length [ms]	2.4
Nominal Bandwidth [MHz]	2.431
User Interaction	No

Test Parameter

Technology to test	Generic 2G4
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2405
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2475
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI

Test at TX 2475 MHz

RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	1.47	dBm	INFO
Ref. Frequency	---	---	2475.500	MHz	INFO

READ SA SETTINGS:


RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	6.47 10.84 15
Start [MHz] Stop [MHz]	2472.569 2477.431
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 10001 SWE

DTS Bandwidth

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
DTS Bandwidth (6dB)	---	---	1132	kHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	11.47 10.84 20
Start [MHz] Stop [MHz]	2472.569 2477.431
RBW [MHz] VBW [MHz]	2.000000 5.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 1001 SWE



Peak output power

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Peak Power	---	30.00	1.36	dBm	PASS
Peak Power	---	1000	1.367729	mW	PASS
Frequency at Peak	---	---	2475.554	MHz	INFO

Verdict

PASS

FCC 15.247 # Bandwidth 6dB DTS ~ Generic 2G4

References

TC start	06.10.2023 10:47:22
Ambit temp [°C] humidity [rel%]	26.6 34
System version	4.6.2.0
Standard Version	FCC 15.247 NI
Method	
Description	FCC 15.247 Bandwidth 6DB DTS - Generic 2G4
Information	

EUT Common settings 2G4

Hopping supported	No
Burst length [ms]	2.4
Nominal Bandwidth [MHz]	2.431
User Interaction	No

Test Parameter

Technology to test	Generic 2G4
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2405
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2475
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI


Test at TX 2475 MHz

RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	1.39	dBm	INFO
Ref. Frequency	---	---	2475.500	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	6.39 10.84 15
Start [MHz] Stop [MHz]	2472.569 2477.431
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 10001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
DTS Bandwidth (6dB)	500	---	1122	kHz	PASS

Verdict

PASS

FCC 15.247 # Peak psd DTS ~ Generic 2G4

References

TC start	06.10.2023 10:47:54
Ambit temp [°C] humidity [rel%]	26.6 34
System version	4.6.2.0
Standard Version	FCC 15.247 NI
Method	DTS: KDB 558074 D01 V05 - Chapter 8.4 DTS maximum power spectral density level in the fundamental emission
Description	FCC 15.247 Peak psd DTS - Generic 2G4
Information	

EUT Common settings 2G4

Hopping supported	No
Burst length [ms]	2.4
Nominal Bandwidth [MHz]	2.431
User Interaction	No

Test Parameter

Technology to test	Generic 2G4
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2405
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2475
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI


Test at TX 2475 MHz

RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	1.38	dBm	INFO
Ref. Frequency	---	---	2475.500	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	6.38 10.84 15
Start [MHz] Stop [MHz]	2473.177 2476.823
RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1000 20 1001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Peak psd	---	8	-13.62	dBm/3KHz	PASS

Verdict

PASS

FCC 15.247, ISED RSS247 # Bandwidth 99PCT and 20dB ~ Generic 2G4

References

TC start	06.10.2023 10:48:35
Ambit temp [°C] humidity [rel%]	26.7 34
System version	4.6.2.0
Standard Version	FCC 15.247, ISED RSS247 NI
Method	
Description	FCC 15.247 Bandwidth 99PCT-20DB DTS - Generic 2G4
Information	

EUT Common settings 2G4

Hopping supported	No
Burst length [ms]	2.4
Nominal Bandwidth [MHz]	2.431
User Interaction	No

Test Parameter

Technology to test	Generic 2G4
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2405
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2475
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI


Test at TX 2475 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	1.45	dBm	INFO
Ref. Frequency	---	---	2475.500	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	6.45 10.84 15
Start [MHz] Stop [MHz]	2472.569 2477.431
RBW [MHz] VBW [MHz]	0.050000 0.200000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 10001 SWE







BW within Band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	2381.000	kHz	INFO
T1 99%	2400.000000	---	2473.8284	MHz	PASS
T2 99%	---	2483.500000	2476.2095	MHz	PASS



BW 20dB



BW within Band 20dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 20dB	---	---	2517	kHz	INFO
T1 20dB	2400.000000	---	2473.7612	MHz	PASS
T2 20dB	---	2483.500000	2476.2777	MHz	PASS

Verdict

PASS

FCC 15.247 # TX spurious conducted 20dBc ~ Generic 2G4

References

TC start	06.10.2023 10:49:14
Ambit temp [°C] humidity [rel%]	26.7 34
System version	4.6.2.0
Standard Version	FCC 15.247 NI
Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable
Description	FCC 15.247 TX Emissions Conducted DTS - Generic 2G4
Information	

EUT Common settings 2G4

Hopping supported	No
Burst length [ms]	2.4
Nominal Bandwidth [MHz]	2.431
User Interaction	No

Test Parameter

Technology to test	Generic 2G4
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2405
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2475
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer


Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI

Test at TX 2475 MHz

RESULT: Reference Power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	1.34	dBm	INFO
Ref. Frequency	---	---	2475.500	MHz	INFO



TX emissions

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	1.34 0 20
Start [MHz] Stop [MHz]	24530.000 25030.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	200 25 2001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Reference @ 2474.75 MHz	---	---	-3.13	dBm	INFO
No peaks detected	---	---			PASS
Lowest margin to limit 15173.5 MHz	0	---	23.26	dB	INFO

Verdict

PASS

NA # Terminal communication serial ~ Common

References

TC start	06.10.2023 10:55:55
Ambit temp [°C] humidity [rel%]	26.9 34
System version	4.6.2.0
Standard Version	NA NI
Method	
Description	Terminal communication serial
Information	

Test Parameter

Command	cancel
Output result	cancel

Test Parameter

Command	data_rate ieee802154_250Kbit
Output result	data_rate ieee802154_250Kbit Data rate: NRF_RADIO_MODE_IEEE802154_250KBIT

Test Parameter

Command	output_power neg12dBm
Output result	output_power neg12dBm TX power: RADIO_TXPOWER_TXPOWER_Neg12dBm

Test Parameter

Command	start_channel 26
Output result	start_channel 26 Start channel set to: 26

Test Parameter

Command	end_channel 26
Output result	end_channel 26 End channel set to: 26

Test Parameter

Command	transmit_pattern pattern_random
Output result	transmit_pattern pattern_random Transmission pattern: TRANSMIT_PATTERN_RANDOM

Test Parameter

Command	start_duty_cycle_modulated_tx 90
Output result	start_duty_cycle_modulated_tx 90 Requested tx output power: -12 dBm Tx output power set to: -12 dBm

Verdict

INFO

FCC 15.247 # Maximum peak conducted output power DTS ~ Generic 2G4

References

TC start	06.10.2023 10:56:07
Ambit temp [°C] humidity [rel%]	27.0 34
System version	4.6.2.0
Standard Version	FCC 15.247 NI
Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.1 RBW ≥ DTS Bandwidth
Description	FCC 15.247 Max Peak Output Power Conducted DTS4 - Generic 2G4
Information	

EUT Common settings 2G4

Hopping supported	No
Burst length [ms]	2.4
Nominal Bandwidth [MHz]	2.431
User Interaction	No

Test Parameter

Technology to test	Generic 2G4
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2405
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2480
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI

Test at TX 2480 MHz

RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	-11.60	dBm	INFO
Ref. Frequency	---	---	2480.600	MHz	INFO

READ SA SETTINGS:


RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	-6.60 10.85 0
Start [MHz] Stop [MHz]	2477.569 2482.431
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 10001 SWE

DTS Bandwidth

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
DTS Bandwidth (6dB)	---	---	1164	kHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	-1.60 10.85 5
Start [MHz] Stop [MHz]	2477.569 2482.431
RBW [MHz] VBW [MHz]	2.000000 5.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 1001 SWE



Peak output power

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Peak Power	---	30.00	-12.26	dBm	PASS
Peak Power	---	1000	0.059429	mW	PASS
Frequency at Peak	---	---	2479.514	MHz	INFO

Verdict

PASS

FCC 15.247 # Bandwidth 6dB DTS ~ Generic 2G4

References

TC start	06.10.2023 10:56:51
Ambit temp [°C] humidity [rel%]	26.9 34
System version	4.6.2.0
Standard Version	FCC 15.247 NI
Method	
Description	FCC 15.247 Bandwidth 6DB DTS - Generic 2G4
Information	

EUT Common settings 2G4

Hopping supported	No
Burst length [ms]	2.4
Nominal Bandwidth [MHz]	2.431
User Interaction	No

Test Parameter

Technology to test	Generic 2G4
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2405
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2480
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI


Test at TX 2480 MHz

RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	-11.51	dBm	INFO
Ref. Frequency	---	---	2479.500	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	-6.51 10.85 0
Start [MHz] Stop [MHz]	2477.569 2482.431
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 10001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
DTS Bandwidth (6dB)	500	---	1159	kHz	PASS

Verdict

PASS

FCC 15.247 # Peak psd DTS ~ Generic 2G4

References

TC start	06.10.2023 10:57:22
Ambit temp [°C] humidity [rel%]	26.9 34
System version	4.6.2.0
Standard Version	FCC 15.247 NI
Method	DTS: KDB 558074 D01 V05 - Chapter 8.4 DTS maximum power spectral density level in the fundamental emission
Description	FCC 15.247 Peak psd DTS - Generic 2G4
Information	

EUT Common settings 2G4

Hopping supported	No
Burst length [ms]	2.4
Nominal Bandwidth [MHz]	2.431
User Interaction	No

Test Parameter

Technology to test	Generic 2G4
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2405
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2480
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI


Test at TX 2480 MHz

RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	-11.70	dBm	INFO
Ref. Frequency	---	---	2479.400	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	-6.70 10.85 0
Start [MHz] Stop [MHz]	2478.177 2481.823
RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1000 20 1001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Peak psd	---	8	-27.2	dBm/3KHz	PASS

Verdict

PASS

FCC 15.247, ISED RSS247 # Bandwidth 99PCT and 20dB ~ Generic 2G4

References

TC start	06.10.2023 10:58:03
Ambit temp [°C] humidity [rel%]	26.9 34
System version	4.6.2.0
Standard Version	FCC 15.247, ISED RSS247 NI
Method	
Description	FCC 15.247 Bandwidth 99PCT-20DB DTS - Generic 2G4
Information	

EUT Common settings 2G4

Hopping supported	No
Burst length [ms]	2.4
Nominal Bandwidth [MHz]	2.431
User Interaction	No

Test Parameter

Technology to test	Generic 2G4
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2405
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2480
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI


Test at TX 2480 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	-11.62	dBm	INFO
Ref. Frequency	---	---	2479.500	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	-6.62 10.85 0
Start [MHz] Stop [MHz]	2477.569 2482.431
RBW [MHz] VBW [MHz]	0.050000 0.200000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 10001 SWE







BW within Band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	2370.000	kHz	INFO
T1 99%	2400.000000	---	2478.8279	MHz	PASS
T2 99%	---	2483.500000	2481.1984	MHz	PASS



BW 20dB



BW within Band 20dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 20dB	---	---	2522	kHz	INFO
T1 20dB	2400.000000	---	2478.7544	MHz	PASS
T2 20dB	---	2483.500000	2481.2768	MHz	PASS

Verdict

PASS

FCC 15.247 # TX spurious conducted 20dBc ~ Generic 2G4

References

TC start	06.10.2023 10:58:42
Ambit temp [°C] humidity [rel%]	26.9 34
System version	4.6.2.0
Standard Version	FCC 15.247 NI
Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable
Description	FCC 15.247 TX Emissions Conducted DTS - Generic 2G4
Information	

EUT Common settings 2G4

Hopping supported	No
Burst length [ms]	2.4
Nominal Bandwidth [MHz]	2.431
User Interaction	No

Test Parameter

Technology to test	Generic 2G4
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2405
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2480
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer


Equipment

Signal analyzer,Rohde&Schwarz,FSV-30,1321.3008K30/103809,3.70
Switch matrix,CTCadvanced,RSM-1 NI DAQ,29655273,NI

Test at TX 2480 MHz

RESULT: Reference Power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	-11.77	dBm	INFO
Ref. Frequency	---	---	2479.500	MHz	INFO



TX emissions

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	-11.77 0 5
Start [MHz] Stop [MHz]	24530.000 25030.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	200 25 2001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Reference @ 2480.00 MHz	---	---	-16.92	dBm	INFO
No peaks detected	---	---			PASS
Lowest margin to limit 2483.75 MHz	0	---	17.01	dB	INFO

Verdict

PASS

- END OF DOCUMENT -