



Test Report - FCC PART 90 Booster Class B (B9B)

Applicant: Fiplex Communications Inc.

Approved for Release By:

Signature: Bruno Clavier

Name & Title: Bruno Clavier, General Manager

Date of Signature 5/12/2022

This test report shall not be reproduced except in full without the written and signed permission of Timco Engineering Inc. (IIA). This test report relates only to the items tested as identified and is not valid for any subsequent changes or modifications made to the equipment under test.



Table of Contents

1.	CUSTOMER INFORMATION.....	5
1.1	TEST RESULT SUMMARY	5
2.	LOCATION OF TESTING	7
2.1	TEST LABORATORY.....	7
2.2	TESTING WAS PERFORMED, REVIEWED BY	7
3.	TEST SAMPLE(S) (EUT/DUT)	8
3.1	DEFINITIONS	8
3.2	DESCRIPTION OF THE EUT	9
3.3	CONFIGURATION OF EUT	10
3.4	TEST SETUP OF EUT	10
4.	TEST METHODS & APPLICABLE REGULATORY LIMITS.....	11
4.1	TEST METHODS/STANDARDS/GUIDANCE:.....	11
4.2	APPLIED LIMITS AND REGULATORY LIMITS:.....	11
5.	MEASUREMENT UNCERTAINTY.....	11
6.	ENVIRONMENTAL CONDITIONS	11
6.1	TEMPERATURE & HUMIDITY	11
7.	LIST OF TEST EQUIPMENT AND TEST FACILITY.....	12
7.1	LIST OF TEST EQUIPMENT	12
8.	TEST RESULTS	13
8.1	POWER AT THE FINAL AMPLIFIER.....	14
8.2	RF OUTPUT POWER & GAIN.....	15
8.3	OUT-OF-BAND REJECTION.....	17
8.3.1	Downlink, 490.25 MHz	18
8.3.2	Downlink, 496.5 MHz	19
8.3.3	Uplink, 493.25 MHz	20
8.3.4	Uplink, 499.5 MHz	21
8.4	BANDWIDTH & EMISSION	22
8.5	INPUT VS OUTPUT SIGNAL COMPARISON	23
8.5.1	6.25 kHz, FM, Input Signal	24
8.5.2	12.5 kHz, FM, Input Signal.....	25
8.5.3	25 kHz, FM, Input Signal.....	26
8.5.4	C4FM, Input Signal.....	27
8.5.5	H-CPM, Input Signal	28
8.5.6	H-DQPSK, Input Signal.....	29
8.5.7	6.25 kHz, FM, DL Mask E, AGC, 490.25 MHz.....	30
8.5.8	6.25 kHz, FM, DL Mask E, AGC +3, 490.25 MHz	31
8.5.9	12.5 kHz, FM, DL Mask D, AGC, 490.25 MHz	32
8.5.10	12.5 kHz, FM, DL Mask D, AGC+3, 490.25 MHz	33



8.5.11	12.5 kHz, C4FM, DL Mask D, AGC, 490.25 MHz.....	34
8.5.12	12.5 kHz, C4FM, DL Mask D, AGC+3, 490.25 MHz.....	35
8.5.13	12.5 kHz, H-CPM, DL Mask D, AGC, 490.25 MHz.....	36
8.5.14	12.5 kHz, H-CPM, DL Mask D, AGC+3, 490.25 MHz.....	37
8.5.15	12.5 kHz, H-DQPSK, DL Mask D, AGC, 490.25 MHz.....	38
8.5.16	12.5 kHz, H-DQPSK, DL Mask D, AGC+3, 490.25 MHz.....	39
8.5.17	25 kHz FM, DL Mask C, AGC, 490.25 MHz.....	40
8.5.18	25 kHz FM, DL Mask C, AGC+3, 490.25 MHz.....	41
8.5.19	6.25 kHz, FM, DL Mask E, AGC, 496.5 MHz.....	42
8.5.20	6.25 kHz, FM, DL Mask E, AGC +3, 496.5 MHz.....	43
8.5.21	12.5 kHz, FM, DL Mask D, AGC, 496.5 MHz.....	44
8.5.22	12.5 kHz, FM, DL Mask D, AGC+3, 496.5 MHz.....	45
8.5.23	12.5 kHz, C4FM, DL Mask D, AGC, 496.5 MHz.....	46
8.5.24	12.5 kHz, C4FM, DL Mask D, AGC+3, 496.5 MHz.....	47
8.5.25	12.5 kHz, H-CPM, DL Mask D, AGC, 496.5 MHz.....	48
8.5.26	12.5 kHz, H-CPM, DL Mask D, AGC+3, 496.5 MHz.....	49
8.5.27	12.5 kHz, H-DQPSK, DL Mask D, AGC, 496.5 MHz.....	50
8.5.28	12.5 kHz, H-DQPSK, DL Mask D, AGC+3, 496.5 MHz.....	51
8.5.29	25 kHz FM, DL Mask C, AGC, 496.5 MHz.....	52
8.5.30	25 kHz FM, DL Mask C, AGC+3, 496.5 MHz.....	53
8.5.31	6.25 kHz, FM, UL Mask E, AGC, 493.25 MHz.....	54
8.5.32	6.25 kHz, FM, UL Mask E, AGC +3, 493.25 MHz.....	55
8.5.33	12.5 kHz, FM, UL Mask D, AGC, 493.25 MHz.....	56
8.5.34	12.5 kHz, FM, UL Mask D, AGC+3, 493.25 MHz.....	57
8.5.35	12.5 kHz, C4FM, UL Mask D, AGC, 493.25 MHz.....	58
8.5.36	12.5 kHz, C4FM, UL Mask D, AGC+3, 493.25 MHz.....	59
8.5.37	12.5 kHz, H-CPM, UL Mask D, AGC, 493.25 MHz.....	60
8.5.38	12.5 kHz, H-CPM, UL Mask D, AGC+3, 493.25 MHz.....	61
8.5.39	12.5 kHz, H-DQPSK, UL Mask D, AGC, 493.25 MHz.....	62
8.5.40	12.5 kHz, H-DQPSK, UL Mask D, AGC+3, 493.25 MHz.....	63
8.5.41	25 kHz FM, UL Mask C, AGC, 493.25 MHz.....	64
8.5.42	25 kHz FM, UL Mask C, AGC+3, 493.25 MHz.....	65
8.5.43	6.25 kHz, FM, UL Mask E, AGC, 499.5 MHz.....	66
8.5.44	6.25 kHz, FM, UL Mask E, AGC +3, 499.5 MHz.....	67
8.5.45	12.5 kHz, FM, UL Mask D, AGC, 499.5 MHz.....	68
8.5.46	12.5 kHz, FM, UL Mask D, AGC+3, 499.5 MHz.....	69
8.5.47	12.5 kHz, C4FM, UL Mask D, AGC, 499.5 MHz.....	70
8.5.48	12.5 kHz, C4FM, UL Mask D, AGC+3, 499.5 MHz.....	71
8.5.49	12.5 kHz, H-CPM, UL Mask D, AGC, 499.5 MHz.....	72
8.5.50	12.5 kHz, H-CPM, UL Mask D, AGC+3, 499.5 MHz.....	73
8.5.51	12.5 kHz, H-DQPSK, UL Mask D, AGC, 499.5 MHz.....	74
8.5.52	12.5 kHz, H-DQPSK, UL Mask D, AGC+3, 499.5 MHz.....	75
8.5.53	25 kHz FM, UL Mask C, AGC, 499.5 MHz.....	76
8.5.54	25 kHz FM, UL Mask C, AGC+3, 499.5 MHz.....	77
8.6	NOISE FIGURE.....	78
8.7	OUT-OF-BAND/OUT-OF-BLOCK EMISSIONS (INTERMODULATION PRODUCTS).....	79



8.7.1	6.25 kHz, Downlink, AGC, 490.25 MHz	80
8.7.2	6.25 kHz, Downlink, AGC+3, 490.25 MHz.....	81
8.7.3	12.5 kHz, Downlink, AGC, 490.25 MHz.....	82
8.7.4	12.5 kHz, Downlink, AGC+3, 490.25 MHz.....	83
8.7.5	25 kHz, Downlink, AGC, 490.25 MHz.....	84
8.7.6	25 kHz, Downlink, AGC+3, 490.25 MHz.....	85
8.7.7	6.25 kHz, Downlink, AGC, 496.5 MHz	86
8.7.8	6.25 kHz, Downlink, AGC+3, 496.5 MHz.....	87
8.7.9	12.5 kHz, Downlink, AGC, 496.5 MHz.....	88
8.7.10	12.5 kHz, Downlink, AGC+3, 496.5 MHz.....	89
8.7.11	25 kHz, Downlink, AGC, 496.5 MHz.....	90
8.7.12	25 kHz, Downlink, AGC+3, 496.5 MHz.....	91
8.7.13	6.25 kHz, Uplink, AGC, 493.25.....	92
8.7.14	6.25 kHz, Uplink, AGC+3, 493.25	93
8.7.15	12.5 kHz, Uplink, AGC, 493.25.....	94
8.7.16	12.5 kHz, Uplink, AGC+3, 493.25.....	95
8.7.17	25 kHz, Uplink, AGC, 493.25	96
8.7.18	25 kHz, Uplink, AGC+3, 493.25	97
8.7.19	6.25 kHz, Uplink, AGC, 499.5 MHz.....	98
8.7.20	6.25 kHz, Uplink, AGC+3, 499.5 MHz.....	99
8.7.21	12.5 kHz, Uplink, AGC, 499.5 MHz.....	100
8.7.22	12.5 kHz, Uplink, AGC+3, 499.5 MHz	101
8.7.23	25 kHz, Uplink, AGC, 499.5 MHz.....	102
8.7.24	25 kHz, Uplink, AGC+3, 499.5 MHz.....	103
8.8	EMISSION MASK, OUT-OF-BAND.....	104
8.8.1	30 MHz to 1 GHz, Downlink, 490.25 MHz	105
8.8.2	1 GHz to 10 th Harmonic, Downlink, 490.25 MHz	106
8.8.3	30 MHz to 1 GHz, Downlink, 496.5 MHz	107
8.8.4	1 GHz to 10 th Harmonic, Downlink, 496.5 MHz	108
8.8.5	30 MHz to 1 GHz, Uplink, 493.25 MHz.....	109
8.8.6	1 GHz to 10 th Harmonic, Uplink, 493.25 MHz.....	110
8.8.7	30 MHz to 1 GHz, Uplink, 499.5 MHz.....	111
8.8.8	1 GHz to 10 th Harmonic, Uplink, 499.5 MHz.....	112
8.9	SPURIOUS RADIATED EMISSIONS.....	113
8.9.1	Downlink, 490.25 MHz	114
8.9.2	Downlink, 496.5 MHz	115
8.9.3	Uplink, 493.25 MHz	116
8.9.4	Uplink, 499.5 MHz	117
9.	ANNEX-A - PHOTOGRAPHS OF THE EUT.....	118
10.	ANNEX-B – TEST SETUP PHOTOGRAPHS.....	118
11.	HISTORY OF TEST REPORT CHANGES.....	118



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

1. Customer Information

Applicant: Fiplex Communications Inc.
Address: 2101 NW 79th Avenue
Miami Florida, 33122, United States

1.1 Test Result Summary

The following test procedure and guidance were used for measuring FCC PART 90 (PRIVATE LAND MOBILE RADIO SERVICES) known as Licensed Land Mobile; ANSI C63.26-2015 and FCC KDB 935210 D05 v01r04 Industrial Signal Boosters. Full test results are available in this report.

No additions to the test methods were needed. There were no deviations, or exclusions from the test methods. No test results are from external providers or from the customer. The test results relate only to the items tested. Timco does not offer opinions and interpretations, only a pass/fail statement.

Applicable Clauses from Part 2		
FCC Part 2 Clauses	Description of the requirements	Result: (Pass, Fail, N/A)
2.202	Bandwidth & Emission	Pass
2.1033 (c)(8)	Power at the Final Amplifier	Pass
2.1046 (a)	RF Output Power	Pass
2.1047	Modulation characteristics	n/a
2.1049	Occupied Bandwidth	Pass
2.1051	Spurious emissions at antenna terminals	Pass
2.1053	Field strength of spurious radiation	Pass
2.1055	Frequency stability	n/a



Applicable Clauses from Part 90 Subpart I		
FCC Part 90 Clauses	Description of the requirements	Result: (Pass, Fail, N/A)
90.205	Transmitter Power	Pass
90.207	Types of Emissions	Pass
90.209	Bandwidth limitations	Pass
90.210	Emission masks, In-band	Pass
90.210	Emission masks, Out-of-band	Pass
90.213	Frequency stability	n/a
90.214	Transient Frequency Behavior	n/a
90.219 (d)(6)(i)	ERP of intermodulation products	n/a
90.219 (d)(6)(ii)	ERP of noise within the passband	n/a
90.219 (d)(6)(iii)	ERP of noise on spectrum < 1 MHz outside of the passband	n/a
90.219 (d)(3)(i), (e)(1)	ERP of Radiated Power	n/a
90.219 (e)(2)	Noise figure	Pass
90.219 (e)(3)	Spurious emissions	Pass
90.219 (e)(4)(i)(ii)(iii)	Retransmitted Signals	Pass
90.221	Adjacent channel power limits	n/a

Note 1: Requirements in Part 90.219 (d) apply at deployment of this EUT, therefore are not applicable at certification.

KDB 935210 D05 v01r04		
FCC KDB 935210 D05 Clauses	Description of the requirements	Result: (Pass, Fail, N/A)
4.1	Test Signals for PLMRS (Input Signals)	Pass
4.2	AGC Threshold	Reported
4.3	Out-of-Band Rejection	Reported
4.4	Input-versus-Output Signal Comparison	Pass
4.5	Output Power	Pass
4.5	Amplifier/Booster Gain (optional)	Reported
4.6	Noise Figure	Pass
4.7.2	Out-of-band/Out-of-block Conducted Emissions (Intermodulation Products)	Pass
4.7.3	EUT Spurious Conducted Emissions	Pass
4.8	Frequency Stability	n/a
4.9	Spurious Radiated Emissions	Pass



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

2. Location of Testing

2.1 Test Laboratory

Timco Engineering Inc. is a subsidiary of Industrial Inspection & Analysis, Inc. ("IIA").

Testing was performed at Timco's permanent laboratory located at 849 NW State Road 45, Newberry, Florida 32669

FCC test firm # 578780

FCC Designation # US1070

FCC site registration is under A2LA certificate # 0955.01

ISED Canada test site registration # 2056A

EU Notified Body # 1177

For all designations see A2LA scope # 0955.01

2.2 Testing was performed, reviewed by

Dates of Testing: 5/4/2022 – 5/9/2022

Signature:

Sr. EMC Engineer
EMC-003838-NE



Name & Title:

Tim Royer, EMC Engineer

Date of Signature

5/12/2022

Signature:

Name & Title:

Kristoffer Costa, EMC Technician

Date of Signature

5/12/2022



3. Test Sample(s) (EUT/DUT)

The test sample was received: 5/3/2022

3.1 Definitions

Signal booster: A device or system that automatically receives, amplifies, and retransmits signals from wireless stations into and out of building interiors, tunnels, shielded outdoor areas and other locations where these signals would otherwise be too weak for reliable communications. Signal booster systems may contain both Class A and Class B signal boosters as components.

Class A signal booster: A signal booster designed to retransmit signals on one or more specific channels. A signal booster is deemed to be a Class A signal booster if none of its passbands exceed 75 kHz.

Class B signal booster: A signal booster designed to retransmit any signals within a wide frequency band. A signal booster is deemed to be a Class B signal booster if it has a passband that exceeds 75 kHz.



3.2 Description of the EUT

A description as well as unambiguous identification of the EUT(s) tested. Where more than one sample is required for technical reasons (such as the use of connected units for the purpose of conducted output power testing where the product units will have integral antennas), each specific test shall identify which unit was tested.

Identification	
FCC ID:	P3TILB4AB
Brief Description	PE287 IN-LINE BOOSTER
Model(s) #	ILB4A-WMO
Firmware version	N/A
Software version	N/A
Serial Number	N/A

Technical Characteristics	
Technology	IN-LINE BOOSTER
Frequency Range	Downlink: 489.5-491 MHz, 496-497 MHz Uplink: 492.5-494 MHz, 499-500 MHz
RF O/P Power (Max.)	DL: 30.88 dBm/ 1.22 W UL: 30.85 dBm/ 1.21 W
Bandwidth & Emission Class	4K00F1E, 11K3F3E, 16K0F3E, 8K10F1D, 8K10F1E, 8K10F1W, 9K80F1D, 9K80F1E, 9K80D7W
Number of Channels	4
Duty Cycle	100%
Antenna Connector	N Type
Voltage Rating (AC or Batt.)	AC

Antenna Characteristics			
Antenna	Frequency Range	Mode / BW	Antenna Gain
1	489.5-491 MHz 496-497 MHz 492.5-494 MHz 499-500 MHz	Operational	0 dBi

- Note: Information such as antenna gain, firmware/software numbers are provide by manufacturer and cannot be validated by the test lab.

Note: This EUT does not include antenna(s).



3.3 Configuration of EUT

Test Modes		
Band (MHz)	Link Direction	Test Frequencies (MHz)
489.5-491 MHz 469-497 MHz	Downlink	490.25 MHz 496.5 MHz
492.5-494 MHz 499-500 MHz	Uplink	493.25 MHz 499.5 MHz

Operating conditions during Testing:

No other modifications of the device under test (including firmware, specific software settings, and input/output signal levels to the EUT) were made.

Peripherals used during Testing:

A laptop was used to control the EUT.

3.4 Test Setup of EUT

Equipment, antenna, and cable arrangement. The setup of the equipment and cable or wire placement on the test site that produces the highest radiated and the highest ac power line conducted emissions shall be shown clearly and described. Information on the orientation of portable equipment during testing shall be included. Drawings or photographs may be used for this purpose.

Test Setups are included in the test report.



4. Test methods & Applicable Regulatory Limits

4.1 Test methods/Standards/Guidance:

Test procedures and guidance for measuring Licensed Part 90 Licensed device:

- 1) ANSI C63.26-2015
- 2) FCC KDB 935210 D05 v01r04 Industrial Signal Boosters

4.2 Applied Limits and Regulatory Limits:

- 1) FCC CFR 47 Part 90 Subpart I, 90.219

5. Measurement Uncertainty

Parameter	Uncertainty (dB)
Conducted Emissions	± 3.14 dB
Radiated Emissions (9kHz – 30 MHz)	± 3.08 dB
Radiated Emissions (30 – 200 MHz)	± 2.16 dB
Radiated Emissions (200 – 1000 MHz)	± 2.15 dB
Radiated Emissions (1 GHz – 18 GHz)	± 2.14 dB
Radiated Emissions (18 GHz – 40 GHz)	± 2.31 dB
Note: The uncertainties provided in this table represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of K=2.	

6. Environmental Conditions

6.1 Temperature & Humidity

Measurements performed at the test site did not exceed the following:

Parameter	Measurement
Temperature	23 C +/- 5%
Humidity	55% +/- 5%
Barometric Pressure	30.05 in Hg
Note: Specific environmental conditions that are applicable to a specific test are available in the test result section.	



7. List of Test Equipment and Test Facility

The test equipment used identified by type, manufacturer, serial number, or other identification and the date on which the next calibration or service check is due.

Description of the firmware or software used to operate EUT for testing purposes.

A complete list of all test equipment used shall be included with the test report. The manufacturer's model and serial numbers, and date of last calibration, and calibration interval shall be included. Measurement cable loss, measuring instrument bandwidth and detector function, video bandwidth, if appropriate, and antenna factors shall also be included where applicable.

7.1 List of Test Equipment

Test Equipment						
Type	Device	Manufacturer	Model	SN#	Current Cal	Cal Due
Antenna, NSA	Log-Periodic 1243	Eaton	96005	1243	5/4/21	5/3/2024
Antenna	Double-Ridged Horn/ETS Horn 1	ETS-Lindgren	3117	00035923	2/25/20	2/24/2023
CHAMBER	CHAMBER	Panashield	3M	N/A	3/12/19	12/21/2023
Receiver	EMI Test Receiver R&S ESU 40	Rohde & Schwarz	ESU 40	100320	5/27/21	5/26/2024
Receiver	EMI Test Receiver R&S ESW44	Rohde & Schwarz	ESW44	103049	10/13/21	10/12/2024
Signal Generator	Signal Generator HP 8648C	HP	8648C	3847A04696	3/31/21	3/30/2024
Signal Generator	Signal Generator HP 8648C	HP	8648C	35537A01679	3/29/19	NCR
Signal Generator	Signal Generator HP 8648C	HP	8648C	35537A01679	3/29/19	NCR

Software			
Software	Author	Version	Validation on
ESU Firmware	Rohde & Schwarz	4.43 SP3; BIOS v5.1-24-3	2018
RSCCommander	Rohde & Schwarz	1.6.4	2014
ScopeExplorer	LeCroy	v2.25.0.0	2009
Field Strength	Timco	v4.10.7.0	2016



8. Test Results

The results of the test are usually indicated in the form of tables, spectrum analyzer plots, charts, sample calculations, as appropriate for each test procedure.

A description and/or a block diagram of the test setup is usually provided.

The measurement results, along with the appropriate limits for comparison, may be presented in tabular or graphical form. In addition, any variation in the measurement environment may be reported if applicable (e.g., a significant change of temperature that could affect the cable loss and amplifier response).

Unless noted otherwise in the referenced standard, the measurements of **ac power-line conducted emissions and conducted power output** will be reported in units of dB μ V. Unless noted otherwise in the referenced standard, the measurements of **radiated emissions** will be reported in units of decibels, referenced to one microvolt per meter (dB μ V/m) for electric fields, or to one ampere per meter (dBA/m) for magnetic fields, at the distance specified in the appropriate standards or requirements. The measurements of antenna-conducted power for receivers may be reported in units of dB μ V if the impedance of the measuring instrument is also reported. Otherwise, antenna-conducted power will be reported in units of decibels referenced to one milliwatt (dBm). All formulas for data conversions and conversion factors, if used, will be included in this measurement report.

Example:

Freq (MHz)	Meter Reading	+ ACF	+CL	= FS
33	20 dB μ V	+ 10.36 dB/m	+0.40 dB	=30.36 dB μ V/m @ 3m

$EIRP = P_{cond} \text{ (dBm)} + dBi$



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

8.1 Power at the Final Amplifier

Limits from FCC Part 2.1033 (c)(8).

No method of measurement is specified. The result has been calculated based on all available information.


Test Results		
EUT Operating Voltage (V)	EUT Current (A)	Power at the Final Amplifier (W)
28 V DC	3.57	100 W



8.2 RF Output Power & Gain

Limits from FCC Parts 2.1046(a), and 90.205 and test procedure from ANSI C63.26-2015 and FCC KDB 935210 D05 v01r04 Industrial Signal Boosters.

Test Setup



Test Results, Power Output


Link Direction	Max Power Output (dBm)	Max Power Output (W)	Tuning Tolerance (dB)
490.25 MHz Downlink	30.88	1.22	+/- 2.0
496.5 MHz Downlink	30.76	1.19	+/- 2.0
493.25 MHz Uplink	30.73	1.18	+/- 2.0
499.5 MHz Uplink	30.85	1.21	+/- 2.0



Test Results, Gain					
Link Direction	Tuned Frequency (MHz)	Input Level	Power Input (dBm)	Power Output (dBm)	Gain (dB)
Downlink	490.25	AGC	-15.2	30.88	46.08
		AGC+3	-12.2	30.87	43.07
		Maximum	0	30.87	30.87
	496.5	AGC	-14.6	30.17	44.77
		AGC+3	-11.6	30.17	41.77
		Maximum	0	30.76	30.76
Uplink	493.25	AGC	-15	30.73	45.73
		AGC+3	-12	30.73	42.73
		Maximum	0	30.73	30.73
	499.5	AGC	-14.6	30.84	45.44
		AGC+3	-11.6	30.84	42.44
		Maximum	0	30.85	30.85

8.3 Out-of-band Rejection


Limits and test method from FCC KDB 935210 D05 v01r04 Industrial Signal Boosters.



Test Results, Out-of-band Rejection and Class of Operation			
Operating Band (MHz)	Link Direction	Passband (kHz)	Class of Operation
489.5-491 MHz 496-497 MHz	Downlink	> 75 kHz	Class B
492.5-494 MHz 499-500 MHz	Uplink	> 75 kHz	Class B




8.3.1 Downlink, 490.25 MHz




Date: 5.MAY.2022 10:23:48

8.3.2 Downlink, 496.5 MHz




Date: 5.MAY.2022 10:10:03

8.3.3 Uplink, 493.25 MHz



Date: 5.MAY.2022 11:14:14

8.3.4 Uplink, 499.5 MHz



Date: 5.MAY.2022 10:56:35



8.4 Bandwidth & Emission

Limits from FCC Parts 90.209 and FCC KDB 935210 D05 v01r04 Industrial Signal Boosters.


Authorized Bandwidth		
Rule Part	Operating Range	Authorized Bandwidth (kHz)
Part 90	489.5-491 MHz 496-497 MHz 492.5-464 MHz 499-500 MHz	20 kHz, 11.25 kHz, 6 kHz

Applicable Input Signals		
Signal	Occupied Bandwidth (kHz)	Representative Emission Designator(s)
CW	n/a	n/a
6.25 kHz FM	4.0	4K00F1E
12.5 kHz FM	7.89	11K3F3E
25 kHz FM	16.0	16K0F3E
C4FM (P25 Phase I)	8.13	8K10F1D, 8K10F1E
HCPM (P25 Phase II SU)	8.01	8K10F1W
HDQPSK (P25 Phase II BS)	9.78	9K80F1D, 9K80F1E, 9K80D7W




8.5 Input VS Output Signal Comparison

Limits from FCC Parts 90.210 and test procedure from ANSI C63.26-2015 and FCC KDB 935210 D05 v01r04 Industrial Signal Boosters.




8.5.1 6.25 kHz, FM, Input Signal



Date: 4.JAN.2021 11:51:31




8.5.2 12.5 kHz, FM, Input Signal



Date: 4.JAN.2021 11:49:22




8.5.3 25 kHz, FM, Input Signal



Date: 4.JAN.2021 11:50:26




8.5.4 C4FM, Input Signal



Date: 4.JAN.2021 11:42:36




8.5.5 H-CPM, Input Signal



Date: 4.JAN.2021 11:43:53




8.5.6 H-DQPSK, Input Signal




Date: 4.JAN.2021 11:45:31

8.5.7 6.25 kHz, FM, DL Mask E, AGC, 490.25 MHz



Date: 6.MAY.2022 10:08:16


8.5.8 6.25 kHz, FM, DL Mask E, AGC +3, 490.25 MHz



Date: 6.MAY.2022 10:09:02




8.5.9 12.5 kHz, FM, DL Mask D, AGC, 490.25 MHz



Date: 6.MAY.2022 11:02:33




8.5.10 12.5 kHz, FM, DL Mask D, AGC+3, 490.25 MHz



Date: 6.MAY.2022 11:03:31




8.5.11 12.5 kHz, C4FM, DL Mask D, AGC, 490.25 MHz



Date: 6.MAY.2022 11:08:54




8.5.12 12.5 kHz, C4FM, DL Mask D, AGC+3, 490.25 MHz



Date: 6.MAY.2022 11:10:03




8.5.13 12.5 kHz, H-CPM, DL Mask D, AGC, 490.25 MHz



Date: 6.MAY.2022 11:11:29




8.5.14 12.5 kHz, H-CPM, DL Mask D, AGC+3, 490.25 MHz



Date: 6.MAY.2022 11:13:38




8.5.15 12.5 kHz, H-DQPSK, DL Mask D, AGC, 490.25 MHz




Date: 6.MAY.2022 11:17:09

8.5.16 12.5 kHz, H-DQPSK, DL Mask D, AGC+3, 490.25 MHz



Date: 6.MAY.2022 11:18:05


8.5.17 25 kHz FM, DL Mask C, AGC, 490.25 MHz



Date: 6.MAY.2022 14:06:04




8.5.18 25 kHz FM, DL Mask C, AGC+3, 490.25 MHz



Date: 6.MAY.2022 14:07:02



8.5.19 6.25 kHz, FM, DL Mask E, AGC, 496.5 MHz



Date: 6.MAY.2022 10:01:18



Ref 30.2 dBm *Att 0 dB RBW 100 Hz VBW 300 Hz SWT 1.2 s Marker 1 [T1] 27.94 dBm

30.2 Offset 40.8 dB LIMIT CHECK PASS OEW 4.054487179 kHz Temp 1 [T1 OEW] 11.06 dBm

20 496.497980769 MHz 11.10 dBm

10 D1 8.58 dBm T1 T2 Temp 2 [T1 OEW] 496.502035256 MHz

0 MASK E 30.2 dBm

-10 30.2 dBm

-20 30.2 dBm

-30 30.2 dBm

-40 30.2 dBm

-50 30.2 dBm

-60 30.2 dBm


Center 496.5 MHz 1 kHz/ Span 10 kHz

Page 43 of 119



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com


8.5.21 12.5 kHz, FM, DL Mask D, AGC, 496.5 MHz



Date: 6.MAY.2022 12:13:01




8.5.22 12.5 kHz, FM, DL Mask D, AGC+3, 496.5 MHz



Date: 6.MAY.2022 12:14:00

8.5.23 12.5 kHz, C4FM, DL Mask D, AGC, 496.5 MHz



Date: 6.MAY.2022 11:59:31




REF 30.2 dBm *Att 5 dB RBW 100 Hz VEW 300 Hz SWT 3 s Marker 1 [T1]
 21.36 dBm
 496.499399038 MHz
 30.2 Offset 40.8 dB
 LIMIT CHECK PASS
 T1 7.892628205 kHz
 Temp 1 [T1 OBW] 5.44 dBm
 496.496073718 MHz
 Temp 2 [T1 OBW] 2.95 dBm
 496.503966346 MHz
 MASK D
 Center 496.5 MHz 2.5 kHz/ Span 25 kHz

Page 47 of 119



8.5.25 12.5 kHz, H-CPM, DL Mask D, AGC, 496.5 MHz




Date: 6.MAY.2022 12:02:44



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

8.5.26 12.5 kHz, H-CPM, DL Mask D, AGC+3, 496.5 MHz




Date: 6.MAY.2022 12:01:38








8.5.29 25 kHz FM, DL Mask C, AGC, 496.5 MHz



Date: 6.MAY.2022 14:15:47




8.5.30 25 kHz FM, DL Mask C, AGC+3, 496.5 MHz



Date: 6.MAY.2022 14:16:47




8.5.31 6.25 kHz, FM, UL Mask E, AGC, 493.25 MHz



Date: 6.MAY.2022 09:59:08




8.5.32 6.25 kHz, FM, UL Mask E, AGC +3, 493.25 MHz



Date: 6.MAY.2022 09:58:52




8.5.33 12.5 kHz, FM, UL Mask D, AGC, 493.25 MHz



Date: 6.MAY.2022 13:15:44




8.5.34 12.5 kHz, FM, UL Mask D, AGC+3, 493.25 MHz



Date: 6.MAY.2022 13:18:00




8.5.35 12.5 kHz, C4FM, UL Mask D, AGC, 493.25 MHz



Date: 6.MAY.2022 13:19:40



8.5.36 12.5 kHz, C4FM, UL Mask D, AGC+3, 493.25 MHz




Date: 6.MAY.2022 13:20:29



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com


8.5.37 12.5 kHz, H-CPM, UL Mask D, AGC, 493.25 MHz



Date: 6.MAY.2022 13:21:33




8.5.38 12.5 kHz, H-CPM, UL Mask D, AGC+3, 493.25 MHz



Date: 6.MAY.2022 13:22:12




8.5.39 12.5 kHz, H-DQPSK, UL Mask D, AGC, 493.25 MHz



Date: 6.MAY.2022 13:23:55


8.5.40 12.5 kHz, H-DQPSK, UL Mask D, AGC+3, 493.25 MHz



Date: 6.MAY.2022 13:25:22




8.5.41 25 kHz FM, UL Mask C, AGC, 493.25 MHz



Date: 6.MAY.2022 14:19:05




8.5.42 25 kHz FM, UL Mask C, AGC+3, 493.25 MHz



Date: 6.MAY.2022 14:21:08




8.5.43 6.25 kHz, FM, UL Mask E, AGC, 499.5 MHz



Date: 6.MAY.2022 09:12:47



8.5.44 6.25 kHz, FM, UL Mask E, AGC +3, 499.5 MHz




Date: 6.MAY.2022 09:14:29



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com


8.5.45 12.5 kHz, FM, UL Mask D, AGC, 499.5 MHz



Date: 6.MAY.2022 12:57:50




8.5.46 12.5 kHz, FM, UL Mask D, AGC+3, 499.5 MHz



Date: 6.MAY.2022 12:59:06



8.5.47 12.5 kHz, C4FM, UL Mask D, AGC, 499.5 MHz




Date: 6.MAY.2022 12:59:59



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com


8.5.48 12.5 kHz, C4FM, UL Mask D, AGC+3, 499.5 MHz



Date: 6.MAY.2022 13:00:45




8.5.49 12.5 kHz, H-CPM, UL Mask D, AGC, 499.5 MHz



Date: 6.MAY.2022 13:03:19


8.5.50 12.5 kHz, H-CPM, UL Mask D, AGC+3, 499.5 MHz



Date: 6.MAY.2022 13:02:36




8.5.51 12.5 kHz, H-DQPSK, UL Mask D, AGC, 499.5 MHz



Date: 6.MAY.2022 13:04:26


8.5.52 12.5 kHz, H-DQPSK, UL Mask D, AGC+3, 499.5 MHz





Date: 6.MAY.2022 13:05:26



8.5.53 25 kHz FM, UL Mask C, AGC, 499.5 MHz




Date: 10.MAY.2022 11:56:19





8.6 Noise Figure

Limits from FCC KDB 935210 D05 v01r04 Industrial Signal Boosters. Test method from "Noise Figure Measurement Accuracy: The Y-Factor Method" by Keysight Technologies.




Test Results, Out-of-band Rejection and Class of Operation			
Operating Band (MHz)	Link Direction	Noise Figure (dB)	Limit (dB)
496.5 MHz	Downlink	8.29	< 9 dB
499.5 MHz	Uplink	6.77	< 9 dB




8.7 Out-of-Band/Out-of-Block Emissions (Intermodulation Products)

Limits from FCC Parts 2.1051, 90.210 and test procedure from ANSI C63.26-2015 and FCC KDB 935210 D05 v01r04 Industrial Signal Boosters.





8.7.1 6.25 kHz, Downlink, AGC, 490.25 MHz




Date: 5.MAY.2022 13:37:18



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

8.7.2 6.25 kHz, Downlink, AGC+3, 490.25 MHz




Date: 5.MAY.2022 13:38:08



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

8.7.3 12.5 kHz, Downlink, AGC, 490.25 MHz




Date: 5.MAY.2022 13:48:41



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com


8.7.4 12.5 kHz, Downlink, AGC+3, 490.25 MHz



Date: 5.MAY.2022 14:21:32



8.7.5 25 kHz, Downlink, AGC, 490.25 MHz




Date: 5.MAY.2022 15:01:27




Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

8.7.6 25 kHz, Downlink, AGC+3, 490.25 MHz



Date: 5.MAY.2022 15:01:59



Ref 37.4 dBm *Att 5 dB VBW 3 kHz SWI 1.15 s Marker 1 [T1] 29.78 dBm

Offset 40.8 dB Marker 2 [T1] -37.24 dBm

496.490634103 MHz

Center 496.5 MHz 10 kHz/ Span 100 kHz

Tx Channel
 Bandwidth 12.5 kHz Power 30.29 dBm


Adjacent Channel
 Bandwidth 10 kHz Lower -31.82 dBm
 Spacing 12.5 kHz Upper -40.93 dBm

Page 86 of 119



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

8.7.8 6.25 kHz, Downlink, AGC+3, 496.5 MHz




Date: 5.MAY.2022 13:36:08



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

8.7.9 12.5 kHz, Downlink, AGC, 496.5 MHz




Date: 5.MAY.2022 14:26:47



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com


8.7.10 12.5 kHz, Downlink, AGC+3, 496.5 MHz



Date: 5.MAY.2022 14:28:03



8.7.11 25 kHz, Downlink, AGC, 496.5 MHz




Date: 5.MAY.2022 14:57:15



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com


8.7.12 25 kHz, Downlink, AGC+3, 496.5 MHz



Date: 5.MAY.2022 14:58:47




8.7.13 6.25 kHz, Uplink, AGC, 493.25



Date: 5.MAY.2022 12:02:50



8.7.14 6.25 kHz, Uplink, AGC+3, 493.25




Date: 5.MAY.2022 12:09:02




Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

8.7.15 12.5 kHz, Uplink, AGC, 493.25




Date: 5.MAY.2022 14:38:17

8.7.16 12.5 kHz, Uplink, AGC+3, 493.25



Date: 5.MAY.2022 14:40:51

8.7.17 25 kHz, Uplink, AGC, 493.25




Date: 5.MAY.2022 14:45:23



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

8.7.18 25 kHz, Uplink, AGC+3, 493.25




Date: 5.MAY.2022 14:46:19




Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

8.7.19 6.25 kHz, Uplink, AGC, 499.5 MHz



Date: 5.MAY.2022 12:12:14



Ref 37.4 dBm *Att 5 dB RBW 300 Hz VBW 3 kHz SWT 1.15 s

Offset 40.8 dB Marker 2 [T1] 30.21 dBm 499.49664615 MHz

Center 499.5 MHz Span 100 kHz 10 kHz/

1 RBW

VIEW

Tx Channel
 Bandwidth 12.5 kHz Power 30.89 dBm


Adjacent Channel
 Bandwidth 10 kHz Lower -30.07 dBm
 Spacing 12.5 kHz Upper -45.46 dBm

Date: 5.MAY.2022 12:11:52



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

8.7.21 12.5 kHz, Uplink, AGC, 499.5 MHz




Date: 5.MAY.2022 14:30:39



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

8.7.22 12.5 kHz, Uplink, AGC+3, 499.5 MHz




Date: 5.MAY.2022 14:33:17



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com


8.7.23 25 kHz, Uplink, AGC, 499.5 MHz



Date: 5.MAY.2022 14:50:58



8.7.24 25 kHz, Uplink, AGC+3, 499.5 MHz




Date: 5.MAY.2022 14:53:41



8.8 Emission Mask, Out-of-Band

Limits from FCC Parts 2.1051, 90.210 and test procedure from ANSI C63.26-2015 and FCC KDB 935210 D05 v01r04 Industrial Signal Boosters.




Note: Testing was done simultaneously on all combinations of Uplinks and Downlinks to address co-location of signals.



Conducted Emissions Spectrum Plots


8.8.1 30 MHz to 1 GHz, Downlink, 490.25 MHz



Date: 5.MAY.2022 09:01:54




8.8.2 1 GHz to 10th Harmonic, Downlink, 490.25 MHz



Date: 5.MAY.2022 09:05:06




8.8.3 30 MHz to 1 GHz, Downlink, 496.5 MHz



Date: 5.MAY.2022 09:21:37




8.8.4 1 GHz to 10th Harmonic, Downlink, 496.5 MHz



Date: 5.MAY.2022 09:16:15




8.8.5 30 MHz to 1 GHz, Uplink, 493.25 MHz



Date: 5.MAY.2022 08:58:50




8.8.6 1 GHz to 10th Harmonic, Uplink, 493.25 MHz



Date: 5.MAY.2022 09:14:15




8.8.7 30 MHz to 1 GHz, Uplink, 499.5 MHz



Date: 5.MAY.2022 08:57:56



8.8.8 1 GHz to 10th Harmonic, Uplink, 499.5 MHz




Date: 5.MAY.2022 09:12:35


8.9 Spurious Radiated Emissions

Limits from FCC Parts 2.1053, 90.219(E) (3) and test procedure from ANSI C63.26-2015 and FCC KDB 935210 D05 v01r04 Industrial Signal Boosters.

Radiated Test Setup, 30 – 1000 MHz



Radiated Test Setup, Above 1000 MHz





Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

Radiated Emissions, Tabular Data, VHF Band

8.9.1 Downlink, 490.25 MHz

Tuned Frequency (MHz)	Emission Frequency (MHz)	Detector	Meter Reading (dBuV)	Antenna Polarity	Coax Loss (dB)	Antenna Correction Factor (dB/m)	Distance (m)	Field Strength (dBuV/m)	ERP (dBm)	Spurious Limit (dBm)	Margin (dB)
490.25	980.50	PK	21.70	H	3.69	22.53	3.00	47.92	-49.45	-13.00	36.45
490.25	980.50	PK	26.79	V	3.69	22.53	3.00	53.01	-44.36	-13.00	31.36
490.25	1470.75	PK	11.70	H	4.41	27.95	3.00	44.06	-53.31	-13.00	40.31
490.25	1470.75	PK	11.56	V	4.41	27.95	3.00	43.92	-53.45	-13.00	40.45
490.25	1961.00	PK	12.26	H	5.14	31.31	3.00	48.71	-48.67	-13.00	35.67
490.25	1961.00	PK	11.90	V	5.14	31.31	3.00	48.35	-49.03	-13.00	36.03
490.25	2451.25	PK	13.33	H	5.61	31.85	3.00	50.79	-46.59	-13.00	33.59
490.25	2451.25	PK	13.54	V	5.61	31.85	3.00	51.00	-46.38	-13.00	33.38
490.25	2941.50	PK	13.81	H	6.29	32.31	3.00	52.41	-44.97	-13.00	31.97
490.25	2941.50	PK	13.94	V	6.29	32.31	3.00	52.54	-44.84	-13.00	31.84
490.25	3431.75	PK	14.63	H	6.86	32.61	3.00	54.11	-43.27	-13.00	30.27
490.25	3431.75	PK	14.68	V	6.86	32.61	3.00	54.16	-43.22	-13.00	30.22
490.25	3922.00	PK	17.53	H	7.13	33.29	3.00	57.96	-39.42	-13.00	26.42
490.25	3922.00	PK	17.28	V	7.13	33.29	3.00	57.71	-39.67	-13.00	26.67
490.25	4412.25	PK	14.94	H	7.29	33.70	3.00	55.93	-41.45	-13.00	28.45
490.25	4412.25	PK	14.60	V	7.29	33.70	3.00	55.59	-41.79	-13.00	28.79
490.25	4902.50	PK	15.05	H	7.51	33.92	3.00	56.48	-40.90	-13.00	27.90
490.25	4902.50	PK	14.90	V	7.51	33.92	3.00	56.33	-41.05	-13.00	28.05



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

8.9.2 Downlink, 496.5 MHz

Tuned Frequency (MHz)	Emission Frequency (MHz)	Detector	Meter Reading (dBuV)	Antenna Polarity	Coax Loss (dB)	Antenna Correction Factor (dB/m)	Distance (m)	Field Strength (dBuV/m)	ERP (dBm)	Spurious Limit (dBm)	Margin (dB)
496.50	993.00	PK	23.91	H	3.73	23.44	3.00	51.08	-46.30	-13.00	33.30
496.50	993.00	PK	28.24	V	3.73	23.44	3.00	55.41	-41.97	-13.00	28.97
496.50	1489.50	PK	11.81	H	4.46	27.83	3.00	44.11	-53.27	-13.00	40.27
496.50	1489.50	PK	11.77	V	4.46	27.83	3.00	44.07	-53.31	-13.00	40.31
496.50	1986.00	PK	12.21	H	5.16	31.31	3.00	48.69	-48.69	-13.00	35.69
496.50	1986.00	PK	12.29	V	5.16	31.31	3.00	48.77	-48.61	-13.00	35.61
496.50	2482.50	PK	13.08	H	5.62	32.13	3.00	50.82	-46.55	-13.00	33.55
496.50	2482.50	PK	13.40	V	5.62	32.13	3.00	51.14	-46.23	-13.00	33.23
496.50	2979.00	PK	14.32	H	6.31	32.45	3.00	53.08	-44.30	-13.00	31.30
496.50	2979.00	PK	14.59	V	6.31	32.45	3.00	53.35	-44.03	-13.00	31.03
496.50	3475.50	PK	14.53	H	6.90	32.65	3.00	54.08	-43.30	-13.00	30.30
496.50	3475.50	PK	14.41	V	6.90	32.65	3.00	53.96	-43.42	-13.00	30.42
496.50	3972.00	PK	17.99	H	7.26	33.38	3.00	58.64	-38.74	-13.00	25.74
496.50	3972.00	PK	17.54	V	7.26	33.38	3.00	58.19	-39.19	-13.00	26.19
496.50	4468.50	PK	15.17	H	7.30	33.82	3.00	56.29	-41.08	-13.00	28.08
496.50	4468.50	PK	14.93	V	7.30	33.82	3.00	56.05	-41.32	-13.00	28.32
496.50	4965.00	PK	15.26	H	7.71	33.96	3.00	56.93	-40.45	-13.00	27.45
496.50	4965.00	PK	15.23	V	7.71	33.96	3.00	56.90	-40.48	-13.00	27.48



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

8.9.3 Uplink, 493.25 MHz

Tuned Frequency (MHz)	Emission Frequency (MHz)	Detector	Meter Reading (dBuV)	Antenna Polarity	Coax Loss (dB)	Antenna Correction Factor (dB/m)	Distance (m)	Field Strength (dBuV/m)	ERP (dBm)	Spurious Limit (dBm)	Margin (dB)
493.25	986.50	PK	26.18	H	3.72	22.92	3.00	52.82	-44.55	-13.00	31.55
493.25	986.50	PK	30.54	V	3.72	22.92	3.00	57.18	-40.19	-13.00	27.19
493.25	1479.75	PK	11.70	H	4.44	27.89	3.00	44.03	-53.35	-13.00	40.35
493.25	1479.75	PK	11.56	V	4.44	27.89	3.00	43.89	-53.49	-13.00	40.49
493.25	1973.00	PK	11.85	H	5.15	31.31	3.00	48.31	-49.06	-13.00	36.06
493.25	1973.00	PK	12.20	V	5.15	31.31	3.00	48.66	-48.71	-13.00	35.71
493.25	2466.25	PK	12.81	H	5.61	31.98	3.00	50.41	-46.97	-13.00	33.97
493.25	2466.25	PK	13.53	V	5.61	31.98	3.00	51.13	-46.25	-13.00	33.25
493.25	2959.50	PK	14.66	H	6.30	32.37	3.00	53.33	-44.05	-13.00	31.05
493.25	2959.50	PK	14.70	V	6.30	32.37	3.00	53.37	-44.01	-13.00	31.01
493.25	3452.75	PK	14.38	H	6.88	32.60	3.00	53.86	-43.51	-13.00	30.51
493.25	3452.75	PK	14.37	V	6.88	32.60	3.00	53.85	-43.52	-13.00	30.52
493.25	3946.00	PK	17.58	H	7.27	33.36	3.00	58.20	-39.17	-13.00	26.17
493.25	3946.00	PK	17.45	V	7.27	33.36	3.00	58.07	-39.30	-13.00	26.30
493.25	4439.25	PK	14.98	H	7.28	33.76	3.00	56.02	-41.36	-13.00	28.36
493.25	4439.25	PK	14.68	V	7.28	33.76	3.00	55.72	-41.66	-13.00	28.66
493.25	4932.50	PK	15.12	H	7.75	33.93	3.00	56.80	-40.57	-13.00	27.57
493.25	4932.50	PK	14.81	V	7.75	33.93	3.00	56.49	-40.88	-13.00	27.88



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

8.9.4 Uplink, 499.5 MHz

Tuned Frequency (MHz)	Emission Frequency (MHz)	Detector	Meter Reading (dBuV)	Antenna Polarity	Coax Loss (dB)	Antenna Correction Factor (dB/m)	Distance (m)	Field Strength (dBuV/m)	ERP (dBm)	Spurious Limit (dBm)	Margin (dB)
499.50	999.00	PK	31.77	H	3.71	23.84	3.00	59.32	-38.06	-13.00	25.06
499.50	999.00	PK	31.03	V	3.71	23.84	3.00	58.58	-38.80	-13.00	25.80
499.50	1498.50	PK	12.00	H	4.49	27.78	3.00	44.26	-53.11	-13.00	40.11
499.50	1498.50	PK	11.99	V	4.49	27.78	3.00	44.25	-53.12	-13.00	40.12
499.50	1998.00	PK	12.27	H	5.17	31.31	3.00	48.76	-48.62	-13.00	35.62
499.50	1998.00	PK	12.35	V	5.17	31.31	3.00	48.84	-48.54	-13.00	35.54
499.50	2497.50	PK	13.99	H	5.62	32.26	3.00	51.87	-45.51	-13.00	32.51
499.50	2497.50	PK	13.62	V	5.62	32.26	3.00	51.50	-45.88	-13.00	32.88
499.50	2997.00	PK	13.55	H	6.32	32.52	3.00	52.39	-44.99	-13.00	31.99
499.50	2997.00	PK	13.88	V	6.32	32.52	3.00	52.72	-44.66	-13.00	31.66
499.50	3496.50	PK	14.63	H	6.91	32.69	3.00	54.23	-43.15	-13.00	30.15
499.50	3496.50	PK	14.16	V	6.91	32.69	3.00	53.76	-43.62	-13.00	30.62
499.50	3996.00	PK	17.04	H	7.26	33.40	3.00	57.70	-39.68	-13.00	26.68
499.50	3996.00	PK	17.09	V	7.26	33.40	3.00	57.75	-39.63	-13.00	26.63
499.50	4495.50	PK	14.53	H	7.32	33.88	3.00	55.73	-41.65	-13.00	28.65
499.50	4495.50	PK	15.28	V	7.32	33.88	3.00	56.48	-40.90	-13.00	27.90
499.50	4995.00	PK	14.87	H	7.61	34.01	3.00	56.49	-40.89	-13.00	27.89
499.50	4995.00	PK	14.91	V	7.61	34.01	3.00	56.53	-40.85	-13.00	27.85



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

9. ANNEX-A - Photographs of the EUT

Photographs of the EUT and any manufacturer supplied accessories to be used with the EUT are in separate supplementary documents labelled EXTERNAL PHOTOS and INTERNAL PHOTOS.

10. ANNEX-B – Test Setup Photographs

Test setup photographs are located in a separate supplementary ANNEX-B document.

11. History of Test Report Changes

Test Report #	Revision #	Description	Date of Issue
TR_2069-22_FCC_PT90_Booster Class B_	1	Initial release	5/10/2022



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

END OF TEST REPORT
