

# Maximum Permissible Exposure Evaluation

## FCC ID: 2BC8R-XD

### 1. Client Information

<b>Applicant</b>	:	Shenzhen Decheng Technology Co. , Ltd.
<b>Address</b>	:	4 F, 1 Guang Ya Yuan Road, Wuhe community, Bantian Street, Longgang District, Shenzhen, China
<b>Manufacturer</b>	:	Shenzhen Decheng Technology Co. , Ltd.
<b>Address</b>	:	4 F, 1 Guang Ya Yuan Road, Wuhe community, Bantian Street, Longgang District, Shenzhen, China

### 2. General Description of EUT

<b>EUT Name</b>	:	XD	
<b>Models No.</b>	:	XD, H13B, H9W, WS5, WS6, U21, U22, X5	
<b>Model Different</b>	:	All PCB boards and circuit diagrams are the same, the only difference is that model name.	
<b>Product Description</b>	:	Operation Frequency:	802.11b/g/n(HT20): 2412MHz~2462MHz 802.11n(HT40): 2422MHz-2452MHz
	:	Antenna Gain:	1.24dBi Ceramic antenna
<b>Power Rating</b>	:	Input: DC 5V	
<b>Software Version</b>	:	V1.4.4	
<b>Hardware Version</b>	:	V0.3	
<b>Connecting I/O Port(S)</b>	:	Please refer to the User's Manual	
<b>Remark</b>	:	the evaluation report used the EUT(202309-0131-1-2#).	

## MPE Calculations for WIFI

### 1. EUT Operation Condition:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

### 2. Exposure Evaluation:

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=(PG)/4\pi R^2$$

Where

**S**: power density

**P**: power input to the antenna

**G**: power gain of the antenna in the direction of interest relative to an isotropic radiator.

**R**: distance to the center of radiation of the antenna

### 3. Simultaneous transmission MPE Considerations

According to KDB447498: All transmitters and antennas in the host must be either evaluated for MPE compliance, by measurement or computational modeling, or qualify for the standalone MPE test exclusion in section 7.1. Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is  $\leq 1.0$ .

This means that:

$$\sum \text{of MPE ratios} \leq 1.0$$

### 4. Test Result:

**2.4G WIFI worst reported.**

Mode	N <sub>TX</sub>	Freq. (MHz)	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (m) [R]	Power Density (W/ m <sup>2</sup> ) [S]
802.11b	1	2412	15.505	16±1	17	1.24	0.2	0.0133
		2437	16.526	17±1	18	1.24	0.2	0.0167
		2462	15.415	15±1	16	1.24	0.2	0.0105
802.11g	1	2412	15.567	16±1	17	1.24	0.2	0.0133
		2437	15.624	16±1	18	1.24	0.2	0.0167
		2462	12.411	12±1	13	1.24	0.2	0.0053
802.11n20	1	2412	14.731	15±1	16	1.24	0.2	0.0105
		2437	15.535	16±1	17	1.24	0.2	0.0133
		2462	12.121	12±1	13	1.24	0.2	0.0053
802.11n40	1	2422	12.834	13±1	14	1.24	0.2	0.0066
		2437	14.535	15±1	16	1.24	0.2	0.0105
		2452	10.352	10±1	11	1.24	0.2	0.0033

**Note:****N<sub>TX</sub>**= Number of Transmit Antennas

RF Output power specifies that Maximum Conducted Peak Output Power.

**5. Conclusion:**

As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),

**Limits for General Population/ Uncontrolled Exposure**

Frequency Range (MHz)	Power density (mW/ cm <sup>2</sup> )
300-1,500	F/1500
1,500-100,000	1.0

For 2.4G WiFi

MPE limit S: 1mW/ cm<sup>2</sup>The MPE is calculated as **0.0167** < **limit 1mW / cm<sup>2</sup>**. So, RF exposure limit warning or SAR test are not required.

The EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47 CFR2.1091 (b).

The RF Exposure Information page from the manual is included here for reference.

**Note**

For a more detailed features description, please refer to the RF Test Report.

**6. Conclusion:**

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

**-----END OF REPORT-----**