



FCC Part 15E Test Report

FCC ID: 2BASB-PKM8720DFC

Applicant: Realsil Microelectronics (suzhou) co. Ltd.

Address: No.128, West Shenhu Road, Suzhou Industrial Park, Jiangsu Province

Manufacturer: Realsil Microelectronics (suzhou) co. Ltd.

Address: No.128, West Shenhu Road, Suzhou Industrial Park, Jiangsu Province

EUT: Wireless module

Trade Mark: 
瑞晟微电子(苏州)有限公司

Model Number: PKM8720DF-C13-F10

Date of Receipt: Mar. 01, 2023

Test Date: Mar. 01, 2023 - Apr. 25, 2023

Date of Report: Apr. 25, 2023

Prepared By: Shenzhen DL Testing Technology Co., Ltd.

Address: 101-201, Building C, Shuanghuan, No.8, Baoqing Road, Baolong Industrial Zone, Baolong Street, Longgang District, Shenzhen, Guangdong, China

Applicable Standards: FCC PART 15 E 15.407
ANSI C63.10:2013

Test Result: Pass

Report Number: DL-20230325008E

Prepared (Test Engineer): Pxing Huang

Reviewer (Supervisor): Jack Bu

Approved (Manager): Jade Yang



This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen DL Testing Technology Co., Ltd.



Table of Contents	Page
1 . SUMMARY OF TEST RESULTS	5
1.1 MEASUREMENT UNCERTAINTY	5
2 . GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST MODES	8
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	9
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	9
2.5 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING	9
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	10
3 . EMC EMISSION TEST	11
3.1 CONDUCTED EMISSION MEASUREMENT	11
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	11
3.1.2 TEST PROCEDURE	11
3.1.3 DEVIATION FROM TEST STANDARD	11
3.1.4 TEST SETUP	12
3.1.5 EUT OPERATING CONDITIONS	12
3.1.6 TEST RESULTS	12
3.2 RADIATED EMISSION MEASUREMENT	15
3.2.1 RADIATED EMISSION LIMITS	15
3.2.2 TEST PROCEDURE	16
3.2.3 DEVIATION FROM TEST STANDARD	16
3.2.4 TEST SETUP	16
3.2.5 EUT OPERATING CONDITIONS	17
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	18
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	19
3.2.8 TEST RESULTS (1GHZ~40GHZ)	21
3.3 RADIATED BAND EMISSION MEASUREMENT	34
3.3.1 TEST REQUIREMENT:	34
3.3.2 TEST PROCEDURE	34
3.3.3 DEVIATION FROM TEST STANDARD	34
3.3.4 TEST SETUP	34
3.3.5 EUT OPERATING CONDITIONS	34
4 . PEAK OUTPUT POWER	37
4.1 APPLIED PROCEDURES / LIMIT	37
4.1.1 TEST PROCEDURE	37
4.1.2 DEVIATION FROM STANDARD	37
4.1.3 TEST SETUP	37



Table of Contents	Page
4.1.4 EUT OPERATION CONDITIONS	37
4.1.5 TEST RESULTS	38
5 . POWER SPECTRAL DENSITY TEST	43
5.1 APPLIED PROCEDURES / LIMIT	43
5.1.1 TEST PROCEDURE	43
5.1.2 DEVIATION FROM STANDARD	43
5.1.3 TEST SETUP	43
5.1.4 EUT OPERATION CONDITIONS	43
5.1.5 TEST RESULTS	44
6 . 6DB&26DB&99% BANDWIDTH TEST	49
6.1 APPLIED PROCEDURES / LIMIT	49
6.1.1 TEST PROCEDURE	49
6.1.2 DEVIATION FROM STANDARD	49
6.1.3 TEST SETUP	49
6.1.4 EUT OPERATION CONDITIONS	50
6.1.5 TEST RESULTS	50
7 . DUTY CYCLE TEST SIGNAL	55
7.1 APPLIED PROCEDURES / LIMIT	55
7.1.1 TEST PROCEDURE	55
7.1.2 DEVIATION FROM STANDARD	55
7.1.3 TEST SETUP	55
7.1.4 EUT OPERATION CONDITIONS	55
7.1.5 TEST RESULTS	56
8 . FREQUENCY STABILITY	58
8.1 APPLIED PROCEDURES / LIMIT	58
8.1.1 TEST PROCEDURE	58
8.1.2 DEVIATION FROM STANDARD	58
8.1.3 TEST SETUP	58
8.1.4 EUT OPERATION CONDITIONS	58
8.1.5 TEST RESULTS	59
9 . TRANSMISSION IN THE ABSENCE OF DATA	61
9.1 STANDARD REQUIREMENT	61
9.2 TEST RESULT	61
10 . ANTENNA REQUIREMENT	61
10.1 STANDARD REQUIREMENT	61
10.2 EUT ANTENNA	61
11 . TEST SEUUP PHOTO	62



Table of Contents	Page
12 . EUT PHOTO	64



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.407) , Subpart E			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.407(b), 15.209	Radiated Spurious Emission	PASS	
15.407 (b)	Band Edge Emission	PASS	
15.407 (a)	Peak Output Power	PASS	
15.407 (a)	Power Spectral Density	PASS	
15.403(i) 15.407(e)	26dB bandwidth and 99%dB Bandwidth 6dB bandwidth and 99%dB Bandwidth	PASS	
15.407(g)	Frequency Stability	PASS	
15.407(c)	Transmission in case of Absence of Information	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

1.1 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$ providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 2.56\text{dB}$
2	RF power,conducted	$\pm 0.42\text{dB}$
3	Spurious emissions,conducted	$\pm 2.76\text{dB}$
4	All emissions,radiated(<1G)	$\pm 3.65\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Product Name:	Wireless module
Trademark	 瑞晟微电子(苏州)有限公司
Model No.:	PKM8720DF-C13-F10
Model Difference	N/A
Operation Frequency:	5180-5240, 5745-5825MHz(802.11a/n(HT20)) 5190-5230, 5755-5795MHz(802.11n(HT40))
Channel numbers:	See channel list
Channel separation:	20MHz/40MHz
Modulation technology:	64QAM, 16QAM, QPSK, BPSK for OFDM
Rate of Transmitter	802.11a: 6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps 802.11n: Up to 500Mbps
Antenna Type:	PCB Antenna
Antenna gain:	3.8dBi
Power supply:	DC 3.3V

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
2. The EUT's all information provided by client.



2. Channel List

Channel List for 802.11a/n(HT20)			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220
40	5200	48	5240

Channel List for 802.11a/n(HT20)			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	161	5805
153	5765	165	5825
157	5785		

Channel List for 802.11n(HT40)			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190	46	5230

Channel List for 802.11n(HT40)			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
151	5755	159	5795



2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Description			
Pretest Mode	Channel	Band 1	Band 4
Mode 1	802.11a/nHT20	CH36, CH44, CH48	CH149, CH157, CH165
Mode 2	802.11nHT40	CH38, CH46	CH151, CH159
Mode 3	Other	Link Mode	


For Radiated Emission			
Pretest Mode	Channel	Band 1	Band 4
Mode 1	802.11a/nHT20	CH36, CH44, CH48	CH149, CH157, CH165
Mode 2	802.11nHT40	CH38, CH46	CH151, CH159
Mode 3	Other	Link Mode	

Note: 1. The measurements are performed at the highest, middle, lowest available channels.
2. During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.




2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



Conducted Spurious Emission Test



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Model/Type No.	Series No.	Note
E-1	Wireless module	PKM8720DF-C13-F10	N/A	EUT
E-2	Adapter	HW-0501000E	N/A	

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the end product.

Max output power Setting			
Test software Version	Test program: AXDN-0002.0		
Mode	802.11a	802.11n HT20	802.11n HT40
Data Rate	6Mbps	MSC0	MSC0
Power Setting of Softwave	60	60	66



2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation test, Band-edge test and 6db bandwidth test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	Agilent	E4408B	MY50140780	Nov. 05, 2022	Nov. 04, 2023
2	Test Receiver (9kHz-7GHz)	R&S	ESRP7	101393	Nov. 05, 2022	Nov. 04, 2023
3	Bilog Antenna (30MHz-1GHz)	R&S	VULB9162	00306	Nov. 05, 2022	Nov. 04, 2023
4	Horn Antenna (1GHz-18GHz)	Schwarzbeck	BBHA9120D	02139	Nov. 05, 2022	Nov. 04, 2023
5	Horn Antenna (18GHz-40GHz)	A.H. Systems	SAS-574	588	Nov. 05, 2022	Nov. 04, 2023
6	Amplifier (9KHz-6GHz)	Schwarzbeck	BBV9743B	00153	Nov. 05, 2022	Nov. 04, 2023
7	Amplifier (1GHz-18GHz)	EMEC	EM01G8GA	00270	Nov. 05, 2022	Nov. 04, 2023
8	Amplifier (18GHz-40GHz)	Quanjuda	DLE-161	97	Nov. 05, 2022	Nov. 04, 2023
9	Loop Antenna (9KHz-30MHz)	Schwarzbeck	FMZB1519B	00014	Nov. 05, 2022	Nov. 04, 2023
10	RF cables1 (9kHz-1GHz)	ChengYu	966	004	Nov. 05, 2022	Nov. 04, 2023
11	RF cables2 (1GHz-40GHz)	ChengYu	966	003	Nov. 05, 2022	Nov. 04, 2023
12	Antenna connector	Florida RF Labs	N/A	RF 01#	Nov. 05, 2022	Nov. 04, 2023
13	Power probe	KEYSIGHT	U2021XA	MY55210018	Nov. 05, 2022	Nov. 04, 2023
14	Signal Analyzer 9kHz-26.5GHz	Agilent	N9020A	MY55370280	Nov. 05, 2022	Nov. 04, 2023
15	Test Receiver 20kHz-40GHz	R&S	ESU 40	100376	Nov. 05, 2022	Nov. 04, 2023
16	D.C. Power Supply	LongWei	PS-305D	010964729	Nov. 05, 2022	Nov. 04, 2023

Conduction Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	843 Shielded Room	ChengYu	843 Room	843	Sep. 20, 2022	Sep. 19, 2025
2	EMI Receiver	R&S	ESR	101421	Nov. 05, 2022	Nov. 04, 2023
3	LISN	R&S	ENV216	102417	Nov. 05, 2022	Nov. 04, 2023
4	843 Cable 1#	ChengYu	CE Cable	001	Nov. 05, 2022	Nov. 04, 2023

Other

Item	Name	Manufacturer	Model	Software version
1	EMC Conduction Test System	FALA	EZ_EMCC	EMC-CON 3A1.1
2	EMC radiation test system	FALA	EZ_EMCC	FA-03A2
3	RF test system	MAIWEI	MTS8310	2.0.0.0
4	RF communication test system	MAIWEI	MTS8200	2.0.0.0



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.5 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



- Note:**
- 1.Support units were connected to second LISN.
 - 2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS


The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V and AC 230V, the worst voltage was AC 120V and the data recording in the report.

3.1.6 TEST RESULTS



Temperature:	25 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 3




Remark:

Margin = Limit – Level, Correct Factor = Cable lose + LISN insertion loss, Level= Reading + Correct factor

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.154500	15.54	10.41	25.95	65.75	-39.80	QP	P	
2	0.154500	5.35	10.41	15.76	55.75	-39.99	AVG	P	
3	0.316500	14.40	9.02	23.42	59.80	-36.38	QP	P	
4	0.316500	2.24	9.02	11.26	49.80	-38.54	AVG	P	
5	1.113000	18.51	9.35	27.86	56.00	-28.14	QP	P	
6 *	1.113000	9.30	9.35	18.65	46.00	-27.35	AVG	P	
7	3.133500	6.06	8.71	14.77	56.00	-41.23	QP	P	
8	3.133500	-8.05	8.71	0.66	46.00	-45.34	AVG	P	
9	8.817000	8.01	9.83	17.84	60.00	-42.16	QP	P	
10	8.817000	-6.73	9.83	3.10	50.00	-46.90	AVG	P	
11	29.584500	7.59	10.90	18.49	60.00	-41.51	QP	P	
12	29.584500	-5.80	10.90	5.10	50.00	-44.90	AVG	P	



Temperature:	25 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 3



Remark:

Margin = Limit – Level, Correct Factor = Cable lose + LISN insertion loss, Level= Reading + Correct factor

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.154500	14.91	10.21	25.12	65.75	-40.63	QP	P	
2	0.154500	5.98	10.21	16.19	55.75	-39.56	AVG	P	
3	0.366000	13.95	9.17	23.12	58.59	-35.47	QP	P	
4	0.366000	2.13	9.17	11.30	48.59	-37.29	AVG	P	
5 *	1.113000	18.20	9.46	27.66	56.00	-28.34	QP	P	
6	1.113000	6.26	9.46	15.72	46.00	-30.28	AVG	P	
7	3.952500	6.33	9.80	16.13	56.00	-39.87	QP	P	
8	3.952500	-8.06	9.80	1.74	46.00	-44.26	AVG	P	
9	11.413500	7.17	10.13	17.30	60.00	-42.70	QP	P	
10	11.413500	-6.82	10.13	3.31	50.00	-46.69	AVG	P	
11	28.864500	7.03	11.03	18.06	60.00	-41.94	QP	P	
12	28.864500	-6.94	11.03	4.09	50.00	-45.91	AVG	P	



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	40GHz
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
- Test the EUT in the lowest channel, the middle channel, the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

**3.2.6 TEST RESULTS (Between 9KHz – 30 MHz)**

Temperature:	20℃	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 3.3V
Test Mode :	Mode 3	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.

**3.2.7 TEST RESULTS (Between 30MHz – 1GHz)**

Temperature:	26℃	Relative Humidity:	54%
Pressure:	1010 hPa	Polarization :	Horizontal
Test Voltage :	DC 3.3V		
Test Mode :	Mode 3		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		60.9174	27.60	-11.42	16.18	40.00	-23.82	QP
2		153.7384	30.80	-16.08	14.72	43.50	-28.78	QP
3		202.8103	31.63	-13.21	18.42	43.50	-25.08	QP
4	*	301.4223	34.33	-10.68	23.65	46.00	-22.35	QP
5		339.5887	33.32	-10.15	23.17	46.00	-22.83	QP
6		385.2803	32.11	-9.51	22.60	46.00	-23.40	QP

Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Level - Limit;



Temperature:	26℃	Relative Humidity:	54%
Pressure:	1010 hPa	Polarization :	Vertical
test voltage :	DC 3.3V		
Test Mode :	Mode 3		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		36.0007	32.72	-13.48	19.24	40.00	-20.76	QP
2	*	55.2207	36.95	-11.55	25.40	40.00	-14.60	QP
3		72.5915	35.38	-15.58	19.80	40.00	-20.20	QP
4		207.1225	36.20	-12.71	23.49	43.50	-20.01	QP
5		296.1836	33.84	-9.70	24.14	46.00	-21.86	QP
6		319.9368	34.89	-9.34	25.55	46.00	-20.45	QP

Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Level - Limit;

**3.2.8 TEST RESULTS (1ghz~40ghZ)**

802.11a band 1

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5180									
V	10360	56.31	49.05	15.3	37.39	59.95	74	-14.05	PK
V	10360	41.22	49.05	15.3	37.39	44.86	54	-9.14	AV
V	15540	56.68	49.16	15.27	40.45	63.24	74	-10.76	PK
V	15540	39.15	49.16	15.27	40.45	45.71	54	-8.29	AV
H	10360	56.07	49.05	15.3	37.39	59.71	74	-14.29	PK
H	10360	40.43	49.05	15.3	37.39	44.07	54	-9.93	AV
H	15540	59.15	49.16	15.27	40.45	65.71	74	-8.29	PK
H	15540	38.06	49.16	15.27	40.45	44.62	54	-9.38	AV
operation frequency:5200									
V	10400	57.45	49.09	15.34	37.42	61.12	74	-12.88	PK
V	10400	39.34	49.09	15.34	37.42	43.01	54	-10.99	AV
V	15600	59.48	49.18	15.29	40.47	66.06	74	-7.94	PK
V	15600	38.13	49.18	15.29	40.47	44.71	54	-9.29	AV
H	10400	56.95	49.09	15.34	37.42	60.62	74	-13.38	PK
H	10400	39.76	49.09	15.34	37.42	43.43	54	-10.57	AV
H	15600	59.41	49.18	15.29	40.47	65.99	74	-8.01	PK
H	15600	38.33	49.18	15.29	40.47	44.91	54	-9.09	AV
operation frequency:5240									
V	10480	58.56	49.11	15.37	37.46	62.28	74	-11.72	PK
V	10480	39.29	49.11	15.37	37.46	43.01	54	-10.99	AV
V	15720	59.13	49.21	15.34	40.51	65.77	74	-8.23	PK
V	15720	38.39	49.21	15.34	40.51	45.03	54	-8.97	AV
H	10480	57.25	49.11	15.37	31.31	54.82	74	-19.18	PK
H	10480	45.54	49.11	15.37	31.31	43.11	54	-10.89	AV
H	15720	57.41	49.21	15.34	40.51	64.05	74	-9.95	PK
H	15720	37.56	49.21	15.34	40.51	44.2	54	-9.80	AV
Remark: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit 2. If peak below the average limit, the average emission was no test. 3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.									



802.11n HT20

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5180									
V	10360	56.17	49.05	15.3	37.39	59.81	74	-14.19	PK
V	10360	38.63	49.05	15.3	37.39	42.27	54	-11.73	AV
V	15540	56.58	49.16	15.27	40.45	63.14	74	-10.86	PK
V	15540	38.25	49.16	15.27	40.45	44.81	54	-9.19	AV
H	10360	56.62	49.05	15.3	37.39	60.26	74	-13.74	PK
H	10360	39.34	49.05	15.3	37.39	42.98	54	-11.02	AV
H	15540	54.13	49.16	15.27	40.45	60.69	74	-13.31	PK
H	15540	38.38	49.16	15.27	40.45	44.94	54	-9.06	AV
operation frequency:5200									
V	10400	56.26	49.09	15.34	37.42	59.93	74	-14.07	PK
V	10400	39.77	49.09	15.34	37.42	43.44	54	-10.56	AV
V	15600	55.35	49.18	15.29	40.47	61.93	74	-12.07	PK
V	15600	38.36	49.18	15.29	40.47	44.94	54	-9.06	AV
H	10400	55.57	49.09	15.34	37.42	59.24	74	-14.76	PK
H	10400	40.35	49.09	15.34	37.42	44.02	54	-9.98	AV
H	15600	55.03	49.18	15.29	40.47	61.61	74	-12.39	PK
H	15600	39.24	49.18	15.29	40.47	45.82	54	-8.18	AV
operation frequency:5240									
V	10480	57.13	49.11	15.37	37.46	60.85	74	-13.15	PK
V	10480	40.58	49.11	15.37	37.46	44.3	54	-9.70	AV
V	15720	54.36	49.21	15.34	40.51	61	74	-13.00	PK
V	15720	38.64	49.21	15.34	40.51	45.28	54	-8.72	AV
H	10480	57.11	49.11	15.37	31.31	54.68	74	-19.32	PK
H	10480	44.69	49.11	15.37	31.31	42.26	54	-11.74	AV
H	15720	55.33	49.21	15.34	40.51	61.97	74	-12.03	PK
H	15720	39.25	49.21	15.34	40.51	45.89	54	-8.11	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11n HT40

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5190									
V	10380	56.73	49.07	15.33	37.41	60.4	74	-13.60	PK
V	10380	39.28	49.07	15.33	37.41	42.95	54	-11.05	AV
V	15570	56.24	49.17	15.28	40.46	62.81	74	-11.19	PK
V	15570	38.36	49.17	15.28	40.46	44.93	54	-9.07	AV
H	10380	56.64	49.07	15.33	37.41	60.31	74	-13.69	PK
H	10380	40.36	49.07	15.33	37.41	44.03	54	-9.97	AV
H	15570	54.61	49.17	15.28	40.46	61.18	74	-12.82	PK
H	15570	38.22	49.17	15.28	40.46	44.79	54	-9.21	AV
operation frequency:5230									
V	10460	57.15	49.11	15.37	37.46	60.87	74	-13.13	PK
V	10460	39.63	49.11	15.37	37.46	43.35	54	-10.65	AV
V	15690	54.48	49.21	15.34	40.51	61.12	74	-12.88	PK
V	15690	38.34	49.21	15.34	40.51	44.98	54	-9.02	AV
H	10460	57.26	49.11	15.37	31.31	54.83	74	-19.17	PK
H	10460	44.87	49.11	15.37	31.31	42.44	54	-11.56	AV
H	15690	55.35	49.21	15.34	40.51	61.99	74	-12.01	PK
H	15690	39.06	49.21	15.34	40.51	45.7	54	-8.30	AV
Remark: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit 2. If peak below the average limit, the average emission was no test. 3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.									



802.11a band 4

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5745									
V	11490	54.23	49.05	15.3	37.39	57.87	74	-16.13	PK
V	11490	41.08	49.05	15.3	37.39	44.72	54	-9.28	AV
V	17235	55.35	49.16	15.27	40.45	61.91	68.2	-6.29	PK
V	17235	40.16	49.16	15.27	40.45	46.72	54	-7.28	AV
H	11490	52.34	49.05	15.3	37.39	55.98	74	-18.02	PK
H	11490	42.16	49.05	15.3	37.39	45.8	54	-8.20	AV
H	17235	51.38	49.16	15.27	40.45	57.94	68.2	-10.26	PK
H	17235	40.24	49.16	15.27	40.45	46.8	54	-7.20	AV
operation frequency:5785									
V	11570	51.06	49.09	15.34	37.42	54.73	74	-19.27	PK
V	11570	41.17	49.09	15.34	37.42	44.84	54	-9.16	AV
V	17355	50.35	49.18	15.29	40.47	56.93	68.2	-11.27	PK
V	17355	40.26	49.18	15.29	40.47	46.84	54	-7.16	AV
H	11570	50.41	49.09	15.34	37.42	54.08	74	-19.92	PK
H	11570	42.03	49.09	15.34	37.42	45.7	54	-8.30	AV
H	17355	48.71	49.18	15.29	40.47	55.29	68.2	-12.91	PK
H	17355	40.16	49.18	15.29	40.47	46.74	54	-7.26	AV
operation frequency:5825									
V	11650	52.03	49.11	15.37	37.46	55.75	74	-18.25	PK
V	11650	41.38	49.11	15.37	37.46	45.1	54	-8.90	AV
V	17475	49.26	49.21	15.34	40.51	55.9	68.2	-12.30	PK
V	17475	40.41	49.21	15.34	40.51	47.05	54	-6.95	AV
H	11650	57.28	49.11	15.37	31.31	54.85	74	-19.15	PK
H	11650	48.02	49.11	15.37	31.31	45.59	54	-8.41	AV
H	17475	49.33	49.21	15.34	40.51	55.97	68.2	-12.23	PK
H	17475	40.16	49.21	15.34	40.51	46.8	54	-7.20	AV
Remark: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit 2. If peak below the average limit, the average emission was no test. 3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.									



802.11n HT20

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5745									
V	11490	49.28	49.05	15.3	37.39	52.92	74	-21.08	PK
V	11490	42.11	49.05	15.3	37.39	45.75	54	-8.25	AV
V	17235	48.56	49.16	15.27	40.45	55.12	68.2	-13.08	PK
V	17235	40.25	49.16	15.27	40.45	46.81	54	-7.19	AV
H	11490	49.33	49.05	15.3	37.39	52.97	74	-21.03	PK
H	11490	41.14	49.05	15.3	37.39	44.78	54	-9.22	AV
H	17235	48.23	49.16	15.27	40.45	54.79	68.2	-13.41	PK
H	17235	40.58	49.16	15.27	40.45	47.14	54	-6.86	AV
operation frequency:5785									
V	11570	52.35	49.09	15.34	37.42	56.02	74	-17.98	PK
V	11570	42.26	49.09	15.34	37.42	45.93	54	-8.07	AV
V	17355	49.18	49.18	15.29	40.47	55.76	68.2	-12.44	PK
V	17355	40.04	49.18	15.29	40.47	46.62	54	-7.38	AV
H	11570	49.35	49.09	15.34	37.42	53.02	74	-20.98	PK
H	11570	43.23	49.09	15.34	37.42	46.9	54	-7.10	AV
H	17355	49.34	49.18	15.29	40.47	55.92	68.2	-12.28	PK
H	17355	40.16	49.18	15.29	40.47	46.74	54	-7.26	AV
operation frequency:5825									
V	11650	51.28	49.11	15.37	37.46	55	74	-19.00	PK
V	11650	41.44	49.11	15.37	37.46	45.16	54	-8.84	AV
V	17475	48.26	49.21	15.34	40.51	54.9	68.2	-13.30	PK
V	17475	40.65	49.21	15.34	40.51	47.29	54	-6.71	AV
H	11650	57.16	49.11	15.37	31.31	54.73	74	-19.27	PK
H	11650	44.34	49.11	15.37	31.31	41.91	54	-12.09	AV
H	17475	49.22	49.21	15.34	40.51	55.86	68.2	-12.34	PK
H	17475	40.38	49.21	15.34	40.51	47.02	54	-6.98	AV
Remark: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit 2. If peak below the average limit, the average emission was no test. 3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.									



802.11n HT40


Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5755									
V	11510	49.13	49.07	15.33	37.41	52.8	74	-21.20	PK
V	11510	41.44	49.07	15.33	37.41	45.11	54	-8.89	AV
V	17265	49.67	49.17	15.28	40.46	56.24	68.2	-11.96	PK
V	17265	40.26	49.17	15.28	40.46	46.83	54	-7.17	AV
H	11510	48.37	49.07	15.33	37.41	52.04	74	-21.96	PK
H	11510	41.15	49.07	15.33	37.41	44.82	54	-9.18	AV
H	17265	49.91	49.17	15.28	40.46	56.48	68.2	-11.72	PK
H	17265	40.26	49.17	15.28	40.46	46.83	54	-7.17	AV
operation frequency:5795									
V	11590	49.18	49.11	15.37	37.46	52.9	74	-21.10	PK
V	11590	41.26	49.11	15.37	37.46	44.98	54	-9.02	AV
V	17385	48.48	49.21	15.34	40.51	55.12	68.2	-13.08	PK
V	17385	40.34	49.21	15.34	40.51	46.98	54	-7.02	AV
H	11590	57.61	49.11	15.37	31.31	55.18	74	-18.82	PK
H	11590	44.76	49.11	15.37	31.31	42.33	54	-11.67	AV
H	17385	48.17	49.21	15.34	40.51	54.81	68.2	-13.39	PK
H	17385	40.23	49.21	15.34	40.51	46.87	54	-7.13	AV
Remark: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit 2. If peak below the average limit, the average emission was no test. 3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.									



For Conducted


During the test, pre-scan the all modulation, the modulation below were found to have the worst test results, as reflected in the report.

Test channel:	Band 1/802.11a Lowest channel
Limits(dB/m):	-27




0.03Hz~40GHz

Test channel:	Band 1/802.11a Middle channel
Limits(dB/m):	-27



0.03GHz~40GHz


Test channel:	Band 1/802.11a Highest channel
Limits(dB/m):	-27



0.03GHz~40GHz




Test channel:	Band 4/802.11a Lowest channel
Limits(dB/m):	-27




0.03Hz~40GHz

Test channel:	Band 4/802.11n(HT40) Lowest channel
Limits(dB/m):	-27



0.03GHz~40GHz

Test channel:	Band 4/802.11ac(HT80)
Limits(dB/m):	-27



0.03GHz~40GHz



3.3 RADIATED BAND EMISSION MEASUREMENT

3.3.1 TEST REQUIREMENT:

RSS-247 Section 5.5

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	5000MHz
Stop Frequency	5420MHz
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

3.3.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 0.1 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.3.3 DEVIATION FROM TEST STANDARD

No deviation

3.3.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



3.3.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

**3.3.6 TEST RESULT**

802.11a

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5180									
V	5150	53.18	49.12	15.6	37.34	57	74	-17	PK
V	5150	39.33	49.12	15.6	37.34	43.15	54	-10.85	AV
V	5145	54.24	49.19	15.24	40.43	60.72	74	-13.28	PK
V	5145	36.36	49.19	15.24	40.43	42.84	54	-11.16	AV
H	5150	52.97	49.12	15.6	37.34	56.79	74	-17.21	PK
H	5150	37.55	49.12	15.6	37.34	41.37	54	-12.63	AV
H	5145	54.32	49.19	15.24	40.43	60.8	74	-13.2	PK
H	5145	33.13	49.19	15.24	40.43	39.61	54	-14.39	AV
operation frequency:5240									
V	5350	53.18	49.13	15.32	37.46	56.83	74	-17.17	PK
V	5350	35.56	49.13	15.32	37.46	39.21	54	-14.79	AV
V	5370	53.28	49.24	15.36	40.51	59.91	74	-14.09	PK
V	5370	32.26	49.24	15.36	40.51	38.89	54	-15.11	AV
H	5350	52.18	49.13	15.32	31.31	49.68	74	-24.32	PK
H	5350	40.24	49.13	15.32	31.31	37.74	54	-16.26	AV
H	5370	52.46	49.24	15.36	40.51	59.09	74	-14.91	PK
H	5370	32.58	49.24	15.36	40.51	39.21	54	-14.79	AV
Remark:									
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit									
2. If peak below the average limit, the average emission was no test.									
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.									



802.11n HT20

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5180									
V	5150	51.26	49.12	15.6	37.34	55.08	74	-18.92	PK
V	5150	33.14	49.12	15.6	37.34	36.96	54	-17.04	AV
V	5145	51.46	49.19	15.24	40.43	57.94	74	-16.06	PK
V	5145	33.18	49.19	15.24	40.43	39.66	54	-14.34	AV
H	5150	51.45	49.12	15.6	37.34	55.27	74	-18.73	PK
H	5150	33.46	49.12	15.6	37.34	37.28	54	-16.72	AV
H	5145	50.18	49.19	15.24	40.43	56.66	74	-17.34	PK
H	5145	32.64	49.19	15.24	40.43	39.12	54	-14.88	AV
operation frequency:5240									
V	5350	53.66	49.13	15.32	37.46	57.31	74	-16.69	PK
V	5350	34.18	49.13	15.32	37.46	37.83	54	-16.17	AV
V	5370	50.23	49.24	15.36	40.51	56.86	74	-17.14	PK
V	5370	33.58	49.24	15.36	40.51	40.21	54	-13.79	AV
H	5350	54.14	49.13	15.32	31.31	51.64	74	-22.36	PK
H	5350	36.26	49.13	15.32	31.31	33.76	54	-20.24	AV
H	5370	51.27	49.24	15.36	40.51	57.9	74	-16.1	PK
H	5370	33.55	49.24	15.36	40.51	40.18	54	-13.82	AV
Remark: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit 2. If peak below the average limit, the average emission was no test. 3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.									



802.11n HT40

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5190									
V	5150	52.16	49.12	15.33	37.41	55.78	74	-18.22	PK
V	5150	34.58	49.12	15.33	37.41	38.2	54	-15.8	AV
V	5145	51.28	49.19	15.28	40.46	57.83	74	-16.17	PK
V	5145	33.63	49.19	15.28	40.46	40.18	54	-13.82	AV
H	5150	52.45	49.12	15.33	37.41	56.07	74	-17.93	PK
H	5150	34.66	49.12	15.33	37.41	38.28	54	-15.72	AV
H	5145	50.47	49.19	15.28	40.46	57.02	74	-16.98	PK
H	5145	33.55	49.19	15.28	40.46	40.1	54	-13.9	AV
operation frequency:5230									
V	5350	53.66	49.13	15.32	37.46	57.31	74	-16.69	PK
V	5350	36.38	49.13	15.32	37.46	40.03	54	-13.97	AV
V	5370	50.15	49.24	15.36	40.51	56.78	74	-17.22	PK
V	5370	33.66	49.24	15.36	40.51	40.29	54	-13.71	AV
H	5350	53.17	49.13	15.32	31.31	50.67	74	-23.33	PK
H	5350	40.25	49.13	15.32	31.31	37.75	54	-16.25	AV
H	5370	51.89	49.24	15.36	40.51	58.52	74	-15.48	PK
H	5370	35.78	49.24	15.36	40.51	42.41	54	-11.59	AV
Remark: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit 2. If peak below the average limit, the average emission was no test. 3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.									



3.3 CONDUCTED BAND EMISSION MEASUREMENT

3.3.1 TEST REQUIREMENT:

FCC Part15 C Section 15.209 and 15.407

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(4) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Spectrum Parameter	Setting	
Attenuation	Auto	
Start Frequency	5150MHz	5725MHz
Stop Frequency	5250MHz	5850MHz
RB / VB (emission in restricted band)	1 MHz / 3 MHz for Peak, 1 MHz / 10Hz for Average	


3.3.2 TEST PROCEDURE

Test method: FCC KDB 789033 G)& Parts 15.407(b)(4) & 15.209(a)

3.3.3 DEVIATION FROM TEST STANDARD

No deviation

3.3.4 TEST SETUP



3.3.5 EUT OPERATING CONDITIONS


The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.




3.3.6 TEST RESULT

The antenna gain is compensated in the test data.

802.11a




5180MHz




5240MHz

802.11n HT20




5180MHz




5240MHz

802.11n HT40




5190MHz




5230MHz



802.11a




5745MHz




5825MHz

802.11n HT20




5745MHz



5825MHz

802.11n HT40



5755MHz



5795MHz



4. AVERAGING OUTPUT POWER

4.1 APPLIED PROCEDURES / LIMIT

For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

4.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the power meter and antenna output port as show in the block diagram below,
- b. Spectrum Setting : RBW > the 20 dB bandwidth of the emission being measured
Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
VBW $\geq$ RBW
Sweep = auto
Detector function = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
Trace = max hold

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP



4.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



4.1.5 TEST RESULTS

Temperature:	25 °C	Relative Humidity:	60%
Pressure:	1012 hPa	Test Voltage :	DC 3.3V

Band	Mode	Test Channel	Averaging Output Power (dBm)	Duty factor (dB)	Total Output Power(dB)	LIMIT (dBm)
Band 1	802.11a	Low	16.537	0	16.537	23.98
		Moddle	17.272	0	17.272	23.98
		High	18.734	0	18.734	23.98
	802.11n HT20	Low	16.503	0	16.503	23.98
		Moddle	17.163	0	17.163	23.98
		High	18.637	0	18.637	23.98
	802.11n HT40	Low	13.017	0	13.017	23.98
		High	14.207	0	14.207	23.98


Band	Mode	Test Channel	Averaging Output Power (dBm)	Duty factor (dB)	Total Output Power(dB)	LIMIT (dBm)
Band 4	802.11a	Low	18.032	0	18.032	30
		Moddle	17.841	0	17.841	30
		High	17.806	0	17.806	30
	802.11n HT20	Low	18.288	0	18.288	30
		Moddle	17.864	0	17.864	30
		High	18.085	0	18.085	30
	802.11n HT40	Low	16.877	0	16.877	30
		High	16.717	0	16.717	30



802.11a




802.11n HT20



5180MHz



5180MHz



5200MHz



5200MHz



5240MHz

5240MHz



802.11n HT40




5190MHz




5230MHz



802.11a




802.11n HT20




5745MHz




5745MHz



5785MHz





5785MHz



5825MHz

5825MHz



802.11n HT40  Center Freq 5.75500000 GHz #Res BW 1 MHz #VBW 3 MHz Span 60 MHz Sweep 1 ms Channel Power 16.88 dBm / 40 MHz Power Spectral Density -59.14 dBm / Hz	
5755MHz  Center Freq 5.79500000 GHz #Res BW 1 MHz #VBW 3 MHz Span 60 MHz Sweep 1 ms Channel Power 16.72 dBm / 40 MHz Power Spectral Density -59.30 dBm / Hz	
5795MHz	



5. POWER SPECTRAL DENSITY TEST

5.1 APPLIED PROCEDURES / LIMIT

In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band.
In addition, the maximum power spectral density shall not exceed 30 dBm in any 500 kHz band.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	= the frequency band of operation
RB	RBW $\geq$ 1MHz for band 1 RBW $\geq$ 510KHz for band 4
VB	VBW $\geq$ 3RBW
Detector	RMS (i.e., power averaging).
Trace	Max Hold
Sweep Time	Auto


5.1.1 TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. The testing follows FCC KDB 789033 D02.
3. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to Spectrum.
4. For U-NII1, U-NII-2A, U-NII-2C Band:
Set RBW=1MHz, VBW=3MHz, where span is enough to capture the entire bandwidth, Sweep time = Auto (601 pts), detector = sample, traces 100 sweeps of video averaging. (SA-2 with the omission of procedure x, the integration with 26dB EBW bandwidth)
For U-NII-3 Band:
Set RBW=510 kHz, VBW=3*RBW, where span is enough to capture the entire bandwidth, Sweep time = Auto (601 pts), detector = sample, traces 100 sweeps of video averaging. (SA-2 with the omission of procedure x, the integration with 26dB EBW bandwidth)
5. Use the cursor on spectrum to peak search the highest level of trace
6. Record the max. reading and add 10 log(1/duty cycle).
we test all antennas, the antenna 1 was worst mode and the data recording in the report.
7. Duty factor Reference is made to the test results in Section 7.1.5.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP



5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


**5.1.5 TEST RESULTS**

	Mode	Test Channel	Reading Level (dBm)	Duty factor (dB)	PSD (dBm/MHz)	Limit (dBm)	Result
Band1	802.11a	Low	1.374	0	1.374	11.00	PASS
		Moddle	1.571	0	1.571	11.00	PASS
		High	1.481	0	1.481	11.00	PASS
	802.11n20	Low	3.039	0	3.039	11.00	PASS
		Moddle	3.925	0	3.925	11.00	PASS
		High	3.177	0	3.177	11.00	PASS
	802.11n40	Low	-3.123	0	-3.123	11.00	PASS
		High	-1.91	0	-1.91	11.00	PASS

	Mode	Test Channel	Reading Level (dBm)	Duty factor (dB)	PSD (dBm/500kHz)	Limit (dBm)	Result
Band4	802.11a	Low	-1.773	0	-1.773	30.00	PASS
		Moddle	-2.306	0	-2.306	30.00	PASS
		High	-2.055	0	-2.055	30.00	PASS
	802.11n20	Low	-2.359	0	-2.359	30.00	PASS
		Moddle	-1.654	0	-1.654	30.00	PASS
		High	-1.331	0	-1.331	30.00	PASS
	802.11n40	Low	-5.383	0	-5.383	30.00	PASS
		High	-4.894	0	-4.894	30.00	PASS




802.11a



802.11n HT20




5180MHz



5180MHz



5200MHz




5200MHz



5240MHz

5240MHz



802.11n HT40 	
5190MHz 	
5230MHz	



802.11a



802.11n HT20



5745MHz



5745MHz



5785MHz



5785MHz



5825MHz

5825MHz



802.11n HT40



5755MHz



5795MHz



6. 6DB&26DB&99% BANDWIDTH TEST

6.1 APPLIED PROCEDURES / LIMIT

The 26 dB bandwidth is used to determine the conducted power limits.

There is no limit bandwidth for U-NII-1, U-NII-2-A and U-NII-2-C.

The minimum of 6dB Bandwidth measurement is 0.5 MHz for U-NII-3

6.1.1 TEST PROCEDURE

6dB Bandwidth	
Spectrum Parameters	Setting
RBW	100KHz
VBW	300KHz
Span	30MHz(20MHz Bandwidth mode) 60MHz(40MHz Bandwidth mode) 120MHz(80MHz Bandwidth mode)
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

26dB Bandwidth	
Spectrum Parameters	Setting
RBW	approximately 1% of the emission bandwidth
VBW	>RBW
Span	30MHz(20MHz Bandwidth mode) 60MHz(40MHz Bandwidth mode) 120MHz(80MHz Bandwidth mode)
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

99% Occupied Bandwidth	
Spectrum Parameters	Setting
RBW	1% to 5% of the OBW
VBW	Approximately three times the RBW
Span	between 1.5 times and 5.0 times the OBW
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP





6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.


6.1.5 TEST RESULTS

		Test Channel	26dB Bandwidth (MHz)	99% Bandwidth (MHz)	Result
Band 1	802.11a	Low	20.24	16.488	Pass
		Middle	20.28	16.484	Pass
		High	20.35	16.479	Pass
	802.11n HT20	Low	21.58	17.688	Pass
		Middle	21.03	17.683	Pass
		High	21.52	17.663	Pass
	802.11n HT40	Low	38.67	35.802	Pass
		High	38.55	35.814	Pass

		Test Channel	6dB Bandwidth (MHz)	6dB Bandwidth Limit (MHz)	Result
Band 4	802.11a	Low	16.482	>0.5	Pass
		Middle	16.485	>0.5	Pass
		High	16.495	>0.5	Pass
	802.11n HT20	Low	17.626	>0.5	Pass
		Middle	17.732	>0.5	Pass
		High	17.63	>0.5	Pass
	802.11n HT40	Low	36.345	>0.5	Pass
		High	36.332	>0.5	Pass



802.11a



802.11n HT20




5180MHz



5180MHz



5200MHz




5200MHz



5240MHz

5240MHz



802.11n HT40 <table><tr><td>Center Freq</td><td>5.19000000 GHz</td><td>Center Freq</td><td>5.19000000 GHz</td><td>Radio Std</td><td>None</td></tr><tr><td>Trig</td><td>Free Run</td><td>Avg/Hold</td><td>100/100</td><td>Radio Device</td><td>BTS</td></tr><tr><td>#F Gain</td><td>Low</td><td>#F Gain</td><td>Low</td><td></td><td></td></tr><tr><td>#F Gain</td><td>Low</td><td>#F Gain</td><td>Low</td><td></td><td></td></tr><tr><td>Ref Offset</td><td>8.5 dB</td><td>Ref Offset</td><td>8.5 dB</td><td></td><td></td></tr><tr><td>Ref</td><td>28.50 dBm</td><td>Ref</td><td>28.50 dBm</td><td></td><td></td></tr><tr><td>Center</td><td>5.19 GHz</td><td>#VBW</td><td>1.2 MHz</td><td>Span</td><td>60 MHz</td></tr><tr><td>#Res BW</td><td>430 kHz</td><td></td><td></td><td>Sweep</td><td>1.333 ms</td></tr><tr><td>Occupied Bandwidth</td><td>35.802 MHz</td><td>Total Power</td><td>16.1 dBm</td><td></td><td></td></tr><tr><td>Transmit Freq Error</td><td>34.711 kHz</td><td>% of OBW Power</td><td>99.00 %</td><td></td><td></td></tr><tr><td>x dB Bandwidth</td><td>38.67 MHz</td><td>x dB</td><td>-26.00 dB</td><td></td><td></td></tr></table>	Center Freq	5.19000000 GHz	Center Freq	5.19000000 GHz	Radio Std	None	Trig	Free Run	Avg/Hold	100/100	Radio Device	BTS	#F Gain	Low	#F Gain	Low			#F Gain	Low	#F Gain	Low			Ref Offset	8.5 dB	Ref Offset	8.5 dB			Ref	28.50 dBm	Ref	28.50 dBm			Center	5.19 GHz	#VBW	1.2 MHz	Span	60 MHz	#Res BW	430 kHz			Sweep	1.333 ms	Occupied Bandwidth	35.802 MHz	Total Power	16.1 dBm			Transmit Freq Error	34.711 kHz	% of OBW Power	99.00 %			x dB Bandwidth	38.67 MHz	x dB	-26.00 dB			
Center Freq	5.19000000 GHz	Center Freq	5.19000000 GHz	Radio Std	None																																																														
Trig	Free Run	Avg/Hold	100/100	Radio Device	BTS																																																														
#F Gain	Low	#F Gain	Low																																																																
#F Gain	Low	#F Gain	Low																																																																
Ref Offset	8.5 dB	Ref Offset	8.5 dB																																																																
Ref	28.50 dBm	Ref	28.50 dBm																																																																
Center	5.19 GHz	#VBW	1.2 MHz	Span	60 MHz																																																														
#Res BW	430 kHz			Sweep	1.333 ms																																																														
Occupied Bandwidth	35.802 MHz	Total Power	16.1 dBm																																																																
Transmit Freq Error	34.711 kHz	% of OBW Power	99.00 %																																																																
x dB Bandwidth	38.67 MHz	x dB	-26.00 dB																																																																
5190MHz <table><tr><td>Center Freq</td><td>5.23000000 GHz</td><td>Center Freq</td><td>5.23000000 GHz</td><td>Radio Std</td><td>None</td></tr><tr><td>Trig</td><td>Free Run</td><td>Avg/Hold</td><td>100/100</td><td>Radio Device</td><td>BTS</td></tr><tr><td>#F Gain</td><td>Low</td><td>#F Gain</td><td>Low</td><td></td><td></td></tr><tr><td>#F Gain</td><td>Low</td><td>#F Gain</td><td>Low</td><td></td><td></td></tr><tr><td>Ref Offset</td><td>8.52 dB</td><td>Ref Offset</td><td>8.52 dB</td><td></td><td></td></tr><tr><td>Ref</td><td>28.52 dBm</td><td>Ref</td><td>28.52 dBm</td><td></td><td></td></tr><tr><td>Center</td><td>5.23 GHz</td><td>#VBW</td><td>1.2 MHz</td><td>Span</td><td>60 MHz</td></tr><tr><td>#Res BW</td><td>430 kHz</td><td></td><td></td><td>Sweep</td><td>1.333 ms</td></tr><tr><td>Occupied Bandwidth</td><td>35.814 MHz</td><td>Total Power</td><td>17.2 dBm</td><td></td><td></td></tr><tr><td>Transmit Freq Error</td><td>25.839 kHz</td><td>% of OBW Power</td><td>99.00 %</td><td></td><td></td></tr><tr><td>x dB Bandwidth</td><td>38.55 MHz</td><td>x dB</td><td>-26.00 dB</td><td></td><td></td></tr></table>	Center Freq	5.23000000 GHz	Center Freq	5.23000000 GHz	Radio Std	None	Trig	Free Run	Avg/Hold	100/100	Radio Device	BTS	#F Gain	Low	#F Gain	Low			#F Gain	Low	#F Gain	Low			Ref Offset	8.52 dB	Ref Offset	8.52 dB			Ref	28.52 dBm	Ref	28.52 dBm			Center	5.23 GHz	#VBW	1.2 MHz	Span	60 MHz	#Res BW	430 kHz			Sweep	1.333 ms	Occupied Bandwidth	35.814 MHz	Total Power	17.2 dBm			Transmit Freq Error	25.839 kHz	% of OBW Power	99.00 %			x dB Bandwidth	38.55 MHz	x dB	-26.00 dB			
Center Freq	5.23000000 GHz	Center Freq	5.23000000 GHz	Radio Std	None																																																														
Trig	Free Run	Avg/Hold	100/100	Radio Device	BTS																																																														
#F Gain	Low	#F Gain	Low																																																																
#F Gain	Low	#F Gain	Low																																																																
Ref Offset	8.52 dB	Ref Offset	8.52 dB																																																																
Ref	28.52 dBm	Ref	28.52 dBm																																																																
Center	5.23 GHz	#VBW	1.2 MHz	Span	60 MHz																																																														
#Res BW	430 kHz			Sweep	1.333 ms																																																														
Occupied Bandwidth	35.814 MHz	Total Power	17.2 dBm																																																																
Transmit Freq Error	25.839 kHz	% of OBW Power	99.00 %																																																																
x dB Bandwidth	38.55 MHz	x dB	-26.00 dB																																																																
5230MHz																																																																			



802.11a



802.11n HT20



5745MHz



5745MHz



5785MHz





5785MHz



5825MHz

5825MHz



802.11n HT40	
	
5755MHz	
	
5795MHz	



7. DUTY CYCLE TEST SIGNAL

7.1 APPLIED PROCEDURES / LIMIT

Pre-analysis Check: While conducting average power measurement, duty cycle of each mode shall be checked to ensure its duty cycle in order to compensate for the loss due to insufficient ratio of duty cycle. All duty cycle is pre-scanned, and result as obtained below shows only the most representative ones where duty cycle is conducted as the given transmission with given virtual operation that expresses the percentage.


7.1.1 TEST PROCEDURE

1. Set RBW = 1 MHz.
2. Set the video bandwidth (VBW) $\geq$ RBW.
3. Detector = Peak.
4. Sweep = auto couple.
5. Allow the trace to stabilize.
6. Span=0

7.1.2 DEVIATION FROM STANDARD

No deviation.

7.1.3 TEST SETUP



7.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

**7.1.5 TEST RESULTS**


Operation Mode		Duty Cycle(%)	Duty Fator (dB) 10 * log (1/ Duty cycle)
Band 1	802.11a	100	0
	802.11n(HT20)	100	0
	802.11n(HT40)	100	0
Band 4	802.11a	100	0
	802.11n(HT20)	100	0
	802.11n(HT40)	100	0



802.11a



802.11n HT20



802.11n HT40





8. FREQUENCY STABILITY

8.1 APPLIED PROCEDURES / LIMIT

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.


8.1.1 TEST PROCEDURE

1. The EUT was placed inside temperature chamber and powered and powered by nominal DC voltage.
2. Set EUT as normal operation.
3. Turn the EUT on and couple its output to spectrum.
4. Turn the EUT off and set the chamber to the highest temperature specified.
5. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT and measure the operating frequency.
6. Repeat step with the temperature chamber set to the lowest temperature.

8.1.2 DEVIATION FROM STANDARD

No deviation.

8.1.3 TEST SETUP



8.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



8.1.5 TEST RESULTS

Test Voltage	Test Temp.	Measured Frequency (MHz)	Spectrum Frequency (MHz)		Δ Frequency (MHz)	
			802.11a	802.11n HT20	802.11a	802.11n HT20
3.63V	-20℃	5180	5180.032	5180.0346	-0.032	-0.0346
		5220	5220.0354	5220.0338	-0.0354	-0.0338
		5240	5240.0238	5240.0235	-0.0238	-0.0235
		5745	5745.0364	5745.0347	-0.0364	-0.0347
		5785	5785.0386	5785.0333	-0.0386	-0.0333
		5825	5825.0314	5825.0365	-0.0314	-0.0365
2.97V	-20℃	5180	5180.0251	5180.0223	-0.0251	-0.0223
		5220	5220.0374	5220.0354	-0.0374	-0.0354
		5240	5240.0265	5240.0261	-0.0265	-0.0261
		5745	5745.0224	5745.0228	-0.0224	-0.0228
		5785	5785.0386	5785.035	-0.0386	-0.035
		5825	5825.0414	5825.0456	-0.0414	-0.0456
3.3V	25℃	5180	5180.0548	5180.0534	-0.0548	-0.0534
		5220	5220.0266	5220.0236	-0.0266	-0.0236
		5240	5240.0352	5240.0318	-0.0352	-0.0318
		5745	5745.0336	5745.0326	-0.0336	-0.0326
		5785	5785.0488	5785.0417	-0.0488	-0.0417
		5825	5825.0241	5825.0234	-0.0241	-0.0234
3.63V	50℃	5180	5180.0316	5180.0367	-0.0316	-0.0367
		5220	5220.0252	5220.0244	-0.0252	-0.0244
		5240	5240.0324	5240.0353	-0.0324	-0.0353
		5745	5745.0661	5745.0635	-0.0661	-0.0635
		5785	5785.0426	5785.0424	-0.0426	-0.0424
		5825	5825.0677	5825.0623	-0.0677	-0.0623
2.97V	50℃	5180	5180.0315	5180.0324	-0.0315	-0.0324
		5220	5220.0213	5220.0266	-0.0213	-0.0266
		5240	5240.0325	5240.0357	-0.0325	-0.0357
		5745	5745.0426	5745.0435	-0.0426	-0.0435
		5785	5785.0248	5785.0254	-0.0248	-0.0254
		5825	5825.0723	5825.0733	-0.0723	-0.0733



Test Voltage	Test Temp.	Measured Frequency (MHz)	Spectrum Frequency (MHz)	Δ Frequency (MHz)
			802.11n HT40	802.11n HT40
3.63V	-20°C	5190	5190.0226	-0.0226
		5230	5230.0324	-0.0324
		5755	5755.0553	-0.0553
		5795	5795.0615	-0.0615
2.97V		5190	5190.0226	-0.0226
		5230	5230.0321	-0.0321
		5755	5755.0244	-0.0244
		5795	5795.0446	-0.0446
3.3V	25°C	5190	5190.0274	-0.0274
		5230	5230.0634	-0.0634
		5755	5755.0251	-0.0251
		5795	5795.0564	-0.0564
3.63V	50°C	5190	5190.0656	-0.0656
		5230	5230.0567	-0.0567
		5755	5755.0462	-0.0462
		5795	5795.0332	-0.0332
2.97V	50°C	5190	5190.0517	-0.0517
		5230	5230.0335	-0.0335
		5755	5755.0324	-0.0324
		5795	5795.0464	-0.0464



9. TRANSMISSION IN THE ABSENCE OF DATA

9.1 STANDARD REQUIREMENT

According to §15.407(c)

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization a description of how this requirement is met.

9.2 TEST RESULT

No non-compliance noted:
Refer to the theory of operation.

10. ANTENNA REQUIREMENT

10.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.



10.2 EUT ANTENNA

The EUT antenna is PCB antenna, It comply with the standard requirement.



11. TEST SEUUP PHOTO

Radiated Measurement Photos









Conducted Measurement Photos








12. EUT PHOTO









***** END OF REPORT *****