



# RF Exposure Evaluation Report

<b>APPLICANT</b>	ADEMCO INC.
<b>ADDRESS</b>	2 CORPORATE CENTER DRIVE SUITE 100 PO BOX 9040 MELVILLE NY 11747
<b>FCC ID</b>	CFS-8DL6CTAR1
<b>MODEL NUMBER</b>	SiXCTA, SiXCT
<b>PRODUCT DESCRIPTION</b>	WIRELESS DOOR/WINDOW CONTACT
<b>DATE SAMPLE RECEIVED</b>	06/04/2019
<b>FINAL TEST DATE</b>	06/07/2019
<b>PREPARED BY</b>	Tim Royer
<b>TEST RESULTS</b>	<input checked="" type="checkbox"/> PASS <input type="checkbox"/> FAIL

Report Number	Report Version	Description	Issue Date
1422AUT19 MPE_TestReport_	Rev1	Initial Issue	07/17/2019

**THE ATTACHED REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL WITHOUT THE WRITTEN APPROVAL OF TIMCO ENGINEERING, INC.**



## TABLE OF CONTENTS

<b>GENERAL REMARKS .....</b>	<b>2</b>
<b>GENERAL INFORMATION .....</b>	<b>3</b>
<b>ANTENNA INFORMATION .....</b>	<b>3</b>
<b>MPE CALCULATION.....</b>	<b>4</b>
<b>MPE LIMITS.....</b>	<b>4</b>
<b>MPE TABLE .....</b>	<b>5</b>
<b>GENERAL UNCONTROLLED EXPOSURE .....</b>	<b>5</b>

## GENERAL REMARKS

### Summary

The device under test does:

- ☒ Fulfill the general approval requirements as identified in this test report and was selected by the customer.
- ☐ Not fulfill the general approval requirements as identified in this test report

### Attestations

This equipment has been tested in accordance with the standards identified in this test report. To the best of my knowledge and belief, these tests were performed using the measurement procedures described in this report.

All instrumentation and accessories used to test products for compliance to the indicated standards are calibrated regularly in accordance with ISO 17025 requirements.

I attest that the necessary measurements were made at:

**Timco Engineering Inc.**  
**849 NW State Road 45**  
**Newberry, FL 32669**  
**Designation #: US1070**

**Prepared by:**



<b>Name and Title</b>	Tim Royer, Project Manager / EMC Testing Engineer
<b>Date</b>	06/7/2019

## GENERAL INFORMATION

<b>EUT Description</b>	WIRELESS DOOR/WINDOW CONTACT		
<b>Model Number</b>	SiXCTA, SiXCT		
<b>EUT Power Source</b>	<input type="checkbox"/> 110–120Vac, 50–60Hz	<input type="checkbox"/> DC Power	<input checked="" type="checkbox"/> Battery Operated
<b>Test Item</b>	<input type="checkbox"/> Engineering Prototype	<input checked="" type="checkbox"/> Pre-Production	<input type="checkbox"/> Production
<b>Type of Equipment</b>	<input checked="" type="checkbox"/> Fixed	<input type="checkbox"/> Mobile	<input type="checkbox"/> Portable
<b>Antenna Connector</b>	Integrated		
<b>Test Conditions</b>	The temperature was 26°C Relative humidity of 50%.		
<b>Modification to the EUT</b>	No Modification to EUT.		
<b>Applicable Standards</b>	FCC CFR 47 Part 2.1091		
<b>Test Facility</b>	Timco Engineering Inc. at 849 NW State Road 45 Newberry, FL 32669 USA. Designation #: US1070		

## ANTENNA INFORMATION

<b>Manufacturer Provides Antenna</b>	<b>Type</b>	<b>Max Gain (dBi)</b>
Yes	Unspecified	0 dBi

### SISO Statement

This equipment has two separate outputs meant to be used as SISO for different service areas. For such equipment, FCC KDB 935210 D02 asks for the following grant condition to be used:

**“This filing has compliance demonstration information and test data only for SISO (single-input single-output) booster system configurations; additional equipment authorization is required to allow this device to be used in MIMO (multiple-input multiple-output) industrial booster systems.”**

## MPE CALCULATION

The minimum separation distance is calculated as follows:


$$E(V/m) = \frac{\sqrt{30 \times P \times G}}{d}$$

$$\text{Power density: } P_d(mW/cm^2) = \frac{E^2}{3770}$$

## MPE LIMITS

**Figure 1. FCC Limits for Maximum Permissible Exposure (MPE)**

*Plane-wave Equivalent Power Density*



## MPE Table

### General Uncontrolled Exposure

The limit for General Uncontrolled Exposure Environment is calculated as shown in FCC Pt. 1.1310, Table B:

Variable	Value
Max Power	0.079 W
Frequency Range	2405 - 2445 MHz
Duty Cycle (at full power)	100%
Max Antenna Gain	0 dB
Coax Loss	0 dB
Power Density	1 mW/cm <sup>2</sup>
Minimum Separation Distance	2.51 cm