

Trimble Navigation Ltd.									
FCC ID: JUP-ELIZABETH35									
Calculate mW/cm2 here. Enter frequency in MHz:									
RF Hazard Distance Calculation									
Calculation of Limits from 1.1310 Table 1									
Controlled									
Uncontrolled									
Ave 6 min									
Ave 30 min									
Occ, mW/c2									
Gen, mW/cm2									
mW/cm2 from Table1: 0.20									
F(MHz)									
Actual F, MHz									
0.3-3									
0.5									
100.0									
100.0									
225.0									
45.0									
30.0-300									
30									
1.0									
0.2									
300-1500									
555									
1.9									
0.37									
1500-100000									
5555									
5.0									
1.0									
Enter P(mW)									
Equivalent dBm									
Enter dBm									
Equivalent Watts									
Basis of Calculations:									
400000									
56.0206									
56.021									
400.0									
E^2/3770 = S, mW/cm2									
E, V/m = (Pwatts*Ggain*30)^.5/d, meters									
d = ((Pwatts*G*30)/3770*S))^0.5									
Pwatts*Ggain = 10^(PdBM-30+GdBi)/10)									
NOTE: For mobile or fixed location transmitters, minimum separation distance is for FCC compliance is 20 cm,									
even if calculations indicate MPE distance is less									