

## 11.1 TEST DATA SUMMARY

Ambient TEMPERATURE (°C) \_\_\_\_\_ 23.0  
Relative HUMIDITY (%) \_\_\_\_\_ 55.5  
Atmospheric PRESSURE (kPa) \_\_\_\_\_ 96.2

Mixture Type: \_\_\_\_\_ Muscle \_\_\_\_\_

Dielectric Constant: \_\_\_\_\_ 54.2 \_\_\_\_\_

Conductivity: \_\_\_\_\_ 1.45 S/m \_\_\_\_\_

Closest Distance (between E-Probe & Phone Antenna): \_\_\_\_\_ 2.6 cm \_\_\_\_\_

### Measurement Results

FREQUENCY		Modulation	POWER (W)	EAR Position	Antenna Position	SAR (W/kg)
MHz	Ch.					
1851.25	25	CDMA	0.35	Left	IN	1.0560
1851.25	25	CDMA	0.35	Left	OUT	1.3263
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak (Brain) Uncontrolled Exposure/General Population				1.6 W/kg (mW/g)		

#### NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. All modes of operation were investigated and the worst-case are reported.
2. Battery condition is fully charged for all readings.
3. Power measured: ☒ Conducted ☐ EIRP ☐ ERP

  
Randy Ortanez  
President & Chief Engineer

PCTEST SEAL

DATE: \_\_\_\_\_ 06-25-98 \_\_\_\_\_