



## RF EXPOSURE REPORT

<b>Applicant</b>	:	Tenetics, LLC
<b>Address of Applicant</b>	:	8630 Guilford Road, Suite M #108, Columbia, MD 21046 USA
<b>Manufacturer</b>	:	Tenetics, LLC
<b>Address of Manufacturer</b>	:	8630 Guilford Road, Suite M #108, Columbia, MD 21046 USA
<b>Equipment under Test</b>	:	wireless internet gateway
<b>Model No.</b>	:	GW3
<b>FCC ID</b>	:	2AA6Q-GW3
<b>Test Standard(s)</b>	:	KDB447498 D01 General RF Exposure Guidance v06
<b>Report No.</b>	:	DDT-RE24092616-2E06
<b>Issue Date</b>	:	2025/02/17
<b>Issue By</b>	:	Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

# REPORT

Table of Contents

1. General Test Information..... 5

1.1. Description of EUT..... 5

1.2. Accessories of EUT ..... 5

1.3. Test laboratory ..... 5

2. RF Exposure evaluation for FCC..... 6

2.1. Assessment procedure ..... 6

2.2. Assess result..... 7

## Test Report Declare

<b>Applicant</b>	:	Tenetics, LLC
<b>Address of Applicant</b>	:	8630 Guilford Road, Suite M #108, Columbia, MD 21046 USA
<b>Equipment under Test</b>	:	wireless internet gateway
<b>Model No.</b>	:	GW3
<b>Manufacturer</b>	:	Tenetics, LLC
<b>Address of Manufacturer</b>	:	8630 Guilford Road, Suite M #108, Columbia, MD 21046 USA

**Test Standard Used:**

KDB447498 D01 General RF Exposure Guidance v06

**We Declare:**

The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

<b>Report No.:</b>	DDT-RE24092616-2E06		
<b>Date of Receipt:</b>	2024/12/04	<b>Date of Test:</b>	2024/12/04~2025/02/17

**Prepared By:****Tiger Mo/Engineer****Approved By:****Damon Hu/EMC Manager**

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	2025/02/17	

## 1. General Test Information

### 1.1. Description of EUT

EUT Name	: wireless internet gateway
Model Number	: GW3
EUT Function Description	: Please reference user manual of this device
Power Supply	: DC 12V power by external adapter or solar panel or a built in 6V sealed lead-acid battery.
Antenna Type	: Internal printed meandered inverted F antenna, : External Zisor 3dBi omni-directional antenna, : External Laird FG0293 5dBi omni-directional antenna
Max Antenna Gain(dBi)	: Internal printed meandered inverted F antenna, Max Gain 2.54dBi : External Zisor 3dBi omni-directional antenna, Max Gain 3dBi : External Laird FG0293 5dBi omni-directional antenna, Max Gain 5dBi

Note: This EUT support Bluetooth, 2.4G WiFi, LTE/Edge, GPS, LoRa.

Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

“☑” means to be chosen or applicable; “☐” means don't to be chosen or not applicable; This note applies to entire report.

### 1.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
Adapter	NetBlt	NBS40C1203 00VU	Input: 100-240V~ 50/60Hz 1.0A Output: 12.0~V3.0A
Solar panel	Zhiwang Energy	ZW-145145- 12V	/
Rechargeable Soeled Lead Acx, Batory	Powersonic	PS-640F1	Cycle use:DC 7.20-7.50V Standby use: DC 6.75-6.90V

### 1.3. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: [ddt@dgddt.com](mailto:ddt@dgddt.com).

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

## 2. RF Exposure evaluation for FCC

### 2.1. Assessment procedure

#### Requirement:

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

#### Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100000			1.0	30

Note: f= frequency in MHz; \*Plane-wave equivalent power density

#### Calculation method

$$E(\text{V/m}) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } S(\text{mW/cm}^2) = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = Peak RF output power (mW)

**G** = EUT Antenna numeric gain (numeric)=

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

We can change the formula to:

$$S = \frac{30 \times P \times G}{377 \times d^2} \quad \text{or, } d = \sqrt{\frac{30 \times P \times G}{377 \times S}}$$

From the peak EUT RF output power, the minimum mobile separation distance,  $d=0.2$  m, as well as the gain of the used antenna, the RF power density can be obtained.

## 2.2. Assess result

Mode	Output power (dBm)	Output power (mW)	tune up power (dBm)	tune up power (mW)	Antenna Gain (dBi)	Antenna Gain (linear)	MPE Values (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
BT	6.42	4.39	8	6.31	2	1.58	0.0020	1
BLE	6.07	4.05	8	6.31	2	1.58	0.0020	1
2.4G WIFI	21.81	151.71	23	199.53	2	1.58	0.0629	1
LTE/Edge	25.97	395.37	27	501.19	6	3.98	0.3971	0.549
LoRa	19.22	83.56	21	125.89	5	3.16	0.0792	0.6

All modes cannot work simultaneously: Software limits the GW3 to using one transmitter at a time: there are separate timeslots for sub-GHz and WiFi or LTE/Edge communication.

Note: The estimation distance is 20 cm

Conclusion: MPE evaluation required since transmitter power is below FCC threshold

-----End Report-----