

Maximum Permissible Exposure Report

1. Product Information

FCC ID:	2AWHBYR-Q100
Product name	Wall Mountable Bluetooth CD Player
Test Model	YR-Q100
Power supply	For adapter : Input: AC 100-240V, 50/60Hz, 0.4A Max Output: DC 5V, 2A For unit: Input: DC 5V, 2A
Operation frequency	2402MHz-2480MHz for Bluetooth
Antenna Type	PCB Antenna
Antenna Gain	BT/BLE PCB Antenna, 0dBi
Hardware version	/
Software version	/
Channel Number	79 Channels for Bluetooth V5.0 (DSS) 40 channels for Bluetooth V5.0(DTS)
Channel Spacing	1MHz For BT(DSS), 2MHz For BLE(DTS)
Exposure category	General population/uncontrolled environment
EUT Type	Production Unit
Device Type	Mobile Device

2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3.1 Refer Evaluation Method

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices

3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

4. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

5. Antenna Information

ES-D4 can only use antennas certificated as follows provided by manufacturer;

Internal Identification	Antenna type and antenna number	Operate frequency band	Maximum antenna gain	Notes
Antenna	PCB Antenna	2000 MHz – 2500 MHz	0 dBi	BT Antenna

6. Conducted Power

[BT Max Conducted Power]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
GFSK	0	2402	0.327
	39	2441	1.533
	78	2480	0.088
$\pi/4$ DQPSK	0	2402	1.122
	39	2441	2.348
	78	2480	0.923
8DPSK	0	2402	1.730
	19	2440	0.145
	39	2480	1.567

[BLE Max Conducted Power]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
BT LE	0	2402	0.563
	19	2440	-0.905
	39	2480	-2.611

7. Measurement Results

BT

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	0.0	1.0	0.0
Tolerance \pm (dB)	1.0	1.0	1.0
$\pi/4$ DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	1.0	2.0	0.0
Tolerance \pm (dB)	1.0	1.0	1.0
8DPSK (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	1.0	0.0	1.0
Tolerance \pm (dB)	1.0	1.0	1.0

BLE

BT LE (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	0.0	0.0	-2.0
Tolerance \pm (dB)	1.0	1.0	1.0

8. Evaluation Results

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r=20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

BT

Band/Mode	f (GHz)	RF output power		Antenna Gain (dBi)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
		dBm	mW				
GFSK	2.441	2.0	1.5849	0.0	100%	0.0003	1.0000
$\pi/4$ DQPSK	2.441	3.0	1.9953	0.0	100%	0.0004	1.0000
8DPSK	2.402	2.0	1.5849	0.0	100%	0.0003	1.0000

BLE

Band/Mode	f (GHz)	RF output power		Antenna Gain (dBi)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
		dBm	mW				
BT LE	2.402	1.0	1.2589	0.0	100%	0.0003	1.0000

Remark:

1. Output power including turn-up tolerance;
2. Output power is burst average power;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer;
4. $MPE\ values = PG/4\pi R^2$

9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----