



RF EXPOSURE REPORT

For

Xiamen Ilead Tek Co., Ltd.

Room 01, Unit 2101, No.50 Chengyi North Street, Software Park Phase III, Xiamen, Fujian,
China

FCC ID: 2ASPY-ALD-Y200

Report Type:	Product Name:
Original Report	PeriPage Mini Printer
Report Number:	XMTN1240325-15534E-RF-03
Report Date:	2024-04-17
Reviewed By:	Stein Peng
Approved By:	Miles Chen
Prepared By:	Bay Area Compliance Laboratories Corp. (Xiamen) Unit 102, No. 902 Meifeng South Road, Binhai West Avenue, Science and Technology Innovation Park, Torch High tech Zone XiaMen Tel: +86-592-3200111 www.baclcorp.com.cn

TABLE OF CONTENTS

REPORT REVISION HISTORY.....3

GENERAL INFORMATION.....4

 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)4

FCC§15.247 (i), §1.1307(b)(1) & §2.1091 – MAXIMUM PERMISSIBLE EXPOSURE (MPE)5

 CALCULATED DATA:.....5

REPORT REVISION HISTORY

Number of Revisions	Report No.	Version	Issue Date	Description
0	XMTN1240325-15534E-RF-03	R1V1	2024-04-17	Initial Release

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product Name:	PeriPage Mini Printer
Tested Model:	ALD-Y200
Multiple Model(s):	A40, P40, ALD-P900
Power Supply:	DC 5V from USB port or 7.4V from battery
Maximum Output Power:	GFSK:-1.71 dBm $\pi/4$ -DQPSK:-1.58dBm 8DPSK:-1.61 dBm BLE:-1.85dBm
Operating Band/Frequency:	2402-2480 MHz
Modulation Type:	BT: GFSK, $\pi/4$ -DQPSK, 8DPSK BLE:GFSK
Antenna Type:	PCB on-board
★Maximum Antenna Gain:	-4.73 dBi
EUT Received Status:	Good
<i>Note:</i> 1. The Maximum Antenna Gain was declared by manufacturer. 2. The model difference please refer to declaration letter. 2. All measurement and test data in this report was gathered from production sample serial number: XMTN1240325-15534E-RF-2. (Assigned by the BACL(Xiamen). The EUT supplied by the applicant was received on 2024-03-25)	

Objective

This test report is prepared for *Xiamen Ilead Tek Co., Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Xiamen) to collect test data is located on the Unit 102, No. 902 Meifeng South Road, Binhai West Avenue, Science and Technology Innovation Park, Torch High tech Zone Xiamen.

Bay Area Compliance Laboratories Corp. (Xiamen) Lab is accredited to ISO/IEC 17025 by A2LA (Certificate Number: 7134.01) and the lab has been recognized as the FCC accredited lab under the KDB 974614 D01, the FCC Designation No. : CN1384.

FCC§15.247 (i), §1.1307(b)(1) & §2.1091 – MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to FCC §1.1307(b)(1) & §2.1091, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Limits for Maximum Permissible Exposure (MPE)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;
According to §1.1307(b)(1) & §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Mode	Frequency (MHz)	Antenna Gain		Tune-up Output Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
BDR (GFSK)	2402-2480	-4.73	0.337	-1.5	0.708	20	0.00005	1
EDR ($\pi/4$ -DQPSK)	2402-2480	-4.73	0.337	-1.5	0.708	20	0.00005	1
EDR (8DPSK)	2402-2480	-4.73	0.337	-1.5	0.708	20	0.00005	1
BLE	2402-2480	-4.73	0.337	-1.5	0.708	20	0.00005	1

Note: 1. The Tune-up output power was declared by the Manufacturer.

Result: The device meets MPE at distance 20cm.

Declarations

1. Bay Area Compliance Laboratories Corp. (Xiamen) is not responsible for authenticity of any information provided by the applicant. Information from the applicant that may affect test results are marked with an asterisk “★”.
2. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested.
3. Unless required by the rule provided by the applicant or product regulations, then decision rule in this report did not consider the uncertainty.
4. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor $k=2$ with the 95.45% confidence interval.
5. This report cannot be reproduced except in full, without prior written approval of Bay Area Compliance Laboratories Corp. (Xiamen).
6. This report is valid only with a valid digital signature. The digital signature may be available only under the adobe software above version 7.0.
7. This report may contain standards and test items that are not covered by the accreditation scope and shall be marked with an asterisk “▲”.

******* END OF REPORT *******