REPORT NUMBER 2158

January 2005

Class II Permissive Change to EMC Technology Test Report Number EMC10831 FCC and TELTest Test Report Number 1664

RADIO PERFORMANCE MEASUREMENTS

On the T2020-M27-J00 Mobile Transceiver

FCC ID: CASTEL0057

SN: 17316192

In accordance with

FCC 47 CFR Parts 90.353

PREPARED BY:

Marcus Ludwig

Hamish Newton

Test Technician

CHECKED & APPROVED BY:

Senior Technician



TELTEST Laboratories

Tait Electronics Limited PO Box 1645 558 Wairakei Road Christchurch New Zealand Phone : (64) (3) 3583399 Fax: (64) (3) 3580432

REPORT ON :

Type Approval Testing of the T2020-M27-J00 (Serial No 17316192) in accordance with:

FCC CFR 47 Parts 90.353

FCC ID: CASTEL0057

PREPARED FOR :

Tait Electronics Ltd PO Box 1645 558 Wairakei Rd Christchurch New Zealand

DISTRIBUTION :

TELTest Laboratory	Mr S Crompton	Copy No 1
Tait Electronics Ltd	Mr. Des Fox	Copy No 2
Tait Electronics Ltd	Mr. Anura Gamalath	Copy No 3

APPROVED :

Hamish Newton

Senior Technician

Date :

All tests reported herein have been performed in accordance with the laboratory's scope of accreditation

This document must not be reproduced except in full, without the written permission of the Compliance Laboratory Manager.

Copy No:

TABLE OF CONTENTS

DECLARATION OF CONFORMITY4		
TEST CONDITIONS	5	
NECESSARY BANDWIDTH AND EMISSION DESIGNATORS	5	
TEST RESULTS	6	
TRANSMITTER OUTPUT POWER (CONDUCTED)	6	
TRANSMITTER AUDIO FREQUENCY RESPONSE - PRE-EMPHASIS	7	
TRANSMITTER MODULATION LIMITING	8	
OCCUPIED BANDWIDTH	9	
ANALOGUE VOICE	10	
FFSK		
TRANSMITTER FREQUENCY STABILITY (TEMPERATURE)		
TRANSMITTER FREQUENCY STABILITY (VOLTAGE)		
TEST EQUIPMENT USED		
APPENDIX A	17	
TEST SETUP DETAILS		

DECLARATION OF CONFORMITY

We, TELTEST LABORATORIES of 558 Wairakei Road, Christchurch New Zealand, declare under our sole responsibility that the product:

Equipment:	Mobile Transceiver
Туре:	T2020
Product code:	T2020-M27-J00
Serial Numbers:	17316192
Quantity:	1

To which this declaration relates is in conformity with the following standards:

FCC CFR 47 Parts 90.353

Signature:_____

S. A. Crompton Compliance Laboratory Manager.

Date:_____

Test Conditions

All testing was performed at the following conditions.

Ambient Temperature	15°C to 30°C
Relative Humidity	20% to 75%
Standard Test Voltage	13.8Vdc

Necessary Bandwidth and Emission Designators

SPECIFICATION: FCC 47 CFR 2.202

The Necessary Bandwidth is the minimum value of the occupied bandwidth sufficient to ensure the transmission of information at the rate and with the quality required for the system employed.

This is calculated using the following formula.

Bn = 2M + 2DK	Where: Bn = Necessary Bandwidth
	M = Maximum modulation frequency
	For Data transmission
	M = B/2
	Where: B = Modulation rate in Baud
	D = Peak deviation
	K = Constant
	For Analogue transmission this is 1
	For Data transmission this is typically 1.2

1. Analogue Voice 12.5kHz Bandwidth

Necessary bandwidth

Emission Designator

M = 3kHz11k0F3E D = 2.5 kHzF3E represents a FM voice transmission Bn = 6 + 5 x 1

=11kHz

2. Fast Frequency Shift Keying (FFSK) 12.5kHz Bandwidth Necessary bandwidth

Emission Designator

M = 1.8 D = 1.5	3 kHz 5kHz (60% of peak deviation)	6k60F2D
-	(,	F2D represents a FM data transmission with the use of a modulating sub carrier
Bn	= 3.6 + 3 x 1 = 6.6 kHz	-

Test Results

TRANSMITTER OUTPUT POWER (CONDUCTED)

SPECIFICATION:

FCC 47 CFR 2.1046

GUIDE:

TIA/EIA-603B 2.2.1

MEASUREMENT PROCEDURE:

- 1. Refer Appendix A for Equipment set up.
- 2. The coaxial attenuator has an impedance of 50 Ohms.
- 3. The unmodulated output power was measured with an RF Power meter.

MEASUREMENT RESULTS:

904.1 MHz	5 W nominal	15 W nominal
POWER (W)	5.2	17.3
Variation from Nominal (%)	4.0	15.3
Measurement Uncertainty (dB)	+0.63 -0.68	

LIMIT CLAUSE:

FCC 47 CFR 90.205

Radio Type:

Frequency Band:

Mobile Transceiver 902 MHz ~ 928 MHz

(o) The output power shall not exceed by more than 20% the manufacturer's rated output power for the particular transmitter.

TELTEST Laboratories Tait Electronics Limited Report Number 2158

TRANSMITTER AUDIO FREQUENCY RESPONSE - PRE-EMPHASIS

SPECIFICATION: FCC 47 CFR 2.1047 (a)

GUIDE:

TIA/EIA-603B 2.2.6

MEASUREMENT PROCEDURE:

1. Refer Appendix A for Equipment set up.

- 2. An audio input tone of 1000Hz was applied with the level set to obtain 20% of maximum deviation. This was used as the 0dB reference point.
- 3. The AF was varied while the audio level was held constant.
- 4. The response in dB relative to 1000Hz was measured.

MEASUREMENT RESULTS:

Refer measurement plot below.

LIMIT CLAUSE:

Tx FREQUENCY:

904.1 MHz

TIA/EIA-603B 3.2.6

12.5 kHz Channel Spacing



TRANSMITTER MODULATION LIMITING

SPECIFICATION: FCC 47 CFR 2.1047 (b)

MEASUREMENT PROCEDURE:

- 1. Refer Appendix A for Equipment set up.
- 2. The modulation response was measured at three audio frequencies while varying the input level.
- 3. Measurements were made for both Positive and Negative Deviation.

MEASUREMENT RESULTS:

Refer measurement plots below.

LIMIT CLAUSE:

TIA/EIA-603B 1.3.4.4

Tx FREQUENCY: 904.1 MHz

12.5 kHz Channel Spacing





TELTEST Laboratories

Tait Electronics Limited Report Number 2158

OCCUPIED BANDWIDTH

SPECIFICATION: FCC 47 CFR 2.1049 (c)

GUIDE: TIA/EIA-603B 2.2.11

MEASUREMENT PROCEDURE:

- 1. Refer Appendix A for Equipment Set up.
- 2. For analogue measurements: The EUT was modulated by a 2500Hz tone at an input level 16dB above a level that produced 50% deviation. The input level was established at the frequency of maximum response of the audio modulating circuit. For Data measurements: The EUT was modulated with an internally generated pseudo random bit sequence at the appropriate Baud rates.
- 3. The Occupied Bandwidth was measured on the Spectrum Analyser, with bandwidth settings as follows.

Emission Mask D – Resolution Bandwidth = 100Hz, Video Bandwidth = 1 kHz Emission Mask B, and C – Resolution bandwidth = 300Hz, Video Bandwidth = 3 kHz

MEASUREMENT RESULTS:

See the plots on the following pages for 12.5 kHz channel spacings.

LIMIT CLAUSE:	FCC 47 CFR 90.210	
EMISSION MASKS		
Emission Mask D	12.5 kHz Channel Spacing	Analogue; FFSK

DATA SPEED: FFSK

1200 bps 12.5 kHz Channel Spacing









TRANSMITTER FREQUENCY STABILITY (TEMPERATURE)

SPECIFICATION: FCC 47 CFR 2.1055 (a) (1)

GUIDE:

TIA/EIA-603B 2.2.2

MEASUREMENT PROCEDURE:

- 1. Refer Appendix A for equipment set up.
- 2. The EUT was tested for frequency error from -30 °C to +50°C in 10 °C increments
- 3. The frequency error was recorded in parts per million (ppm).

MEASUREMENT RESULTS: Refer measurement plots below.

LIMIT CLAUSE:

FCC 47 CFR 90.213

Frequency Range: 902 MHz ~ 928 MHz

Channel Spacing (kHz)	Frequency Error (ppm)
12.5	2.5

15 W

Tx FREQUENCY:

904.1 MHz

12.5 kHz channel Spacing



TRANSMITTER FREQUENCY STABILITY (VOLTAGE)

SPECIFICATION: FCC 47 CFR 2.1055 (d) (1)

GUIDE: TIA/EIA-603B 2.2.2

MEASUREMENT PROCEDURE:

- Refer Appendix A for equipment set up.
 The EUT was tested for frequency error at an input voltage to the radio of 85% to 115%.
- 3. The frequency error was recorded in parts per million (ppm).

MEASUREMENT RESULTS: Frequency Range: 902 MHz ~ 928 MHz

Channel Spacing	FREQUENCY ERROR (ppm) @ 904.1 MHz		
(kHz)	11.7 V DC	13.8 V DC	15.9 V DC
12.5	-0.10	-0.08	-0.10

LIMIT CLAUSE:

FCC 47 CFR 90.213

Channel Spacing (kHz)	Frequency Error (ppm)
12.5	2.5

TEST EQUIPMENT USED

No#	Equipment	Manufacturer	Model No	Serial No#	Tait ID	Cal Due
1	Signal Generator	Hewlett Packard	HP8642B (Opt 001)	2512A00176	E3064	15-Nov-05
11	Modulation Analyser	Hewlett Packard	HP8901B (Opt 002)	2441A00393	E3073	11-Sep-05
13	Audio Analyser	Hewlett Packard	HP8903A	2308A02597	E3074	15-Sep-05
14	Power Head	Hewlett Packard	HP11722A	2320A00688	E3307	08-Nov-05
86	1m Coax Cable (BLUE)	Suhner	Sucoflex 104A	25003/4A	E3690	13-Aug-05
87	Audio Analyser	Hewlett Packard	HP8903B	2818A04275	E3710	12-Nov-05
111	Modulation Analyser	Hewlett Packard	HP8901B (Opt 002)	3704A05837	E3786	06-Nov-05
114	Signal Generator	Rohde & Schwarz	SML03 1090.3000.13	100597	E4050	08-Nov-05
115	Environ. Chamber	Contherm	5400 RHSLT.M	1416	E4051	04-Mar-05

APPENDIX A

TEST SETUP DETAILS

All other testing is performed using the Teltest Radio EVAluation system (TREVA), which is configured as shown below. The Spectrum Analyser is connected to the EUT via the attenuator network for Conducted Emissions testing, and Occupied Bandwidth.

