

**Attachment 1**

**RF EXPOSURE INFORMATION**



**RADIO FREQUENCY EXPOSURE (HAZARD) INFORMATION**

Testing was performed in accordance with the requirements of FCC Part 15.407(f)

Spread spectrum transmitters operating in the 2400 - 2483.5 MHz and 5.150 – 5.350 GHz are required to be operated in a manner that ensures that the public is not exposed to RF energy levels in accordance with CFR 47, Section 1.1307(b)(1).

Transmitter # 1 (WLAN): The antennas are located on the top edge of LCD screen (left and right hand side) and projected distance of less than 20cm from user.

Transmitter # 2 (Bluetooth): The antenna is located under right palm rest corner and projected distance of less than 20cm from user.

The separation distance between the WLAN and BT antennas is less than 20cm. Therefore, they are co-located transmitters. Testing was performed with both WLAN and BT transmitters transmitting continuously.

In accordance with this section and also section 2.1093 this device has been defined as a portable device.

SAR testing was performed in accordance with OET Bulletin 65 and reported under EMC Technologies reports M060759\_Cert\_WM3945ABG\_SAR\_DTS\_2.4G\_5.8G and M060759\_Cert\_WM3945ABG\_SAR\_NII\_5.2G. The highest SAR value is 1.42 mW/g which complies with the FCC human exposure requirements of 47 CFR 2.1093 (d).

