



FCC Part 15C Test Report

FCC ID: 2AD99B002D

Product Name:	IP I/O Door Controller
Trademark:	DoorBird
Model Name :	A1081
Prepared For :	Bird Home Automation GmbH
Address :	Uhlandstr. 165, 10719 Berlin, Germany
Prepared By :	Shenzhen BCTC Testing Co., Ltd.
Address :	BCTC Building & 1-2F, East of B Building, Pengzhou Industrial, Fuyuan 1st Road, Qiaotou Community, Fuyong Street, Bao'an District, Shenzhen, China
Test Date:	Jun. 25, 2019 to Jul. 19, 2019
Date of Report :	Jul. 19, 2019
Report No.:	BCTC-FY190502834E

TEST RESULT CERTIFICATION

Applicant's name Bird Home Automation GmbH
Address Uhlandstr. 165, 10719 Berlin, Germany
Manufacture's Name Bird Home Automation GmbH
Address Uhlandstr. 165, 10719 Berlin, Germany

Product description

Product name IP I/O Door Controller
Trademark DoorBird

Model and/or type
reference A1081

Standards FCC Part15.247
ANSI C63.10:2013

This device described above has been tested by BCTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of BCTC, this document may be altered or revised by BCTC, personal only, and shall be noted in the revision of the document.

Prepared by(Engineer): Cai Fang Zhong

Cai Fang Zhong

Reviewer(Supervisor): Eric Yang

Eric Yang

Approved(Manager): Zero Zhou



Table of Contents	Page
1 . SUMMARY OF TEST RESULTS	6
1.1 TEST FACILITY	7
1.2 MEASUREMENT UNCERTAINTY	7
2 . GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 DESCRIPTION OF TEST MODES	9
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	10
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	11
3 . EMC EMISSION TEST	13
3.1 CONDUCTED EMISSION MEASUREMENT	13
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	13
3.1.2 TEST PROCEDURE	13
3.1.3 DEVIATION FROM TEST STANDARD	13
3.1.4 TEST SETUP	14
3.1.5 EUT OPERATING CONDITIONS	14
3.1.6 TEST RESULTS	15
3.2 RADIATED EMISSION MEASUREMENT	19
3.2.1 RADIATED EMISSION LIMITS	19
3.2.2 TEST PROCEDURE	19
3.2.3 DEVIATION FROM TEST STANDARD	20
3.2.4 TEST SETUP	20
3.2.5 EUT OPERATING CONDITIONS	21
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	22
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	23
3.2.8 TEST RESULTS (1GHZ~25GHZ)	25
3.3 RADIATED BAND EMISSION MEASUREMENT	29
3.3.1 TEST REQUIREMENT:	29
3.3.2 TEST PROCEDURE	29
3.3.3 DEVIATION FROM TEST STANDARD	30
3.3.4 TEST SETUP	30
3.3.5 EUT OPERATING CONDITIONS	30
4 . POWER SPECTRAL DENSITY TEST	32

Table of Contents	Page
4.1 APPLIED PROCEDURES / LIMIT	32
4.1.1 TEST PROCEDURE	32
4.1.2 DEVIATION FROM STANDARD	32
4.1.3 TEST SETUP	32
4.1.4 EUT OPERATION CONDITIONS	32
4.1.5 TEST RESULTS	33
5 . BANDWIDTH TEST	41
5.1 APPLIED PROCEDURES / LIMIT	41
5.1.1 TEST PROCEDURE	41
5.1.2 DEVIATION FROM STANDARD	41
5.1.3 TEST SETUP	41
5.1.4 EUT OPERATION CONDITIONS	41
5.1.5 TEST RESULTS	42
6 . PEAK OUTPUT POWER TEST	50
6.1 APPLIED PROCEDURES/LIMIT	50
6.1.1 TEST PROCEDURE	50
6.1.2 DEVIATION FROM STANDARD	50
6.1.3 TEST SETUP	50
6.1.4 EUT OPERATION CONDITIONS	50
6.1.5 TEST RESULTS	51
7 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	52
7.1 APPLICABLE STANDARD	52
7.2 TEST PROCEDURE	52
7.3 DEVIATION FROM STANDARD	52
7.4 TEST SETUP	52
7.5 EUT OPERATION CONDITIONS	52
7.6 TEST RESULT	52
8 . DUTY CYCLE OF TEST SIGNAL	61
8.1 STANDARD REQUIREMENT	61
8.2 FORMULA:	61
9 . ANTENNA REQUIREMENT	64
9.1 STANDARD REQUIREMENT	64
9.2 EUT ANTENNA	64



Table of Contents

	Page
10 . EUT TEST PHOTO	65
11 . EUT PHOTO	67
APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b)	Peak Output Power	PASS	
15.247 (d)	Radiated Spurious Emission	PASS	
15.247 (e)	Power Spectral Density	PASS	
15.205	Restricted Band of Operation	PASS	
15.247 (d)	Band Edge (Out of Band Emissions)	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

1.1 TEST FACILITY

Shenzhen BCTC Testing Co., Ltd.

Add. : BCTC Building & 1-2F, East of B Building, Pengzhou Industrial, Fuyuan 1st Road, Qiaotou Community, Fuyong Street, Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 712850

IC Registered No.: 23583

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	3m chamber Radiated spurious emission(30MHz-1GHz)	U=4.3dB
2	3m chamber Radiated spurious emission(1GHz-18GHz)	U=4.5dB
3	3m chamber Radiated spurious emission(18GHz-40GHz)	U=3.34dB
4	Conducted Adjacent channel power	U=1.38dB
5	Conducted output power uncertainty Above 1G	U=1.576dB
6	Conducted output power uncertainty below 1G	U=1.28dB
7	humidity uncertainty	U=5.3%
8	Temperature uncertainty	U=0.59℃

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	IP I/O Door Controller	
Trade Name	DoorBird	
Model Name	A1081	
Model Difference	N/A	
Product Description	Operation Frequency:	802.11b/g/n20MHz:2412~2462 MHz 802.11n40MHz:2422~2452 MHz
	Modulation Type:	WIFI: OFDM/DSSS
	Bit Rate of Transmitter	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6Mbps 802.11n Up to 150Mbps
	Number Of Channel	802.11b/g/n20MHz:11 CH 802.11n40MHz: 7 CH
	Antenna Designation:	Please see Note 3.
	Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.	
Channel List	Please refer to the Note 2.	
Ratings	DC 15V 1.0A	
Adapter	Model No.: UT20-150100W Input: 100-240V~50/60Hz, 0.4A Output: DC 15V, 1.0A	
Connecting I/O Port(s)	Please refer to the User's Manual	
Hardware Version:	H1.0	
Software Version:	S1.0	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Channel List for 802.11b/g/n(20)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

Channel List for 802.11n(40)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
03	2422	05	2432	07	2442	09	2452
04	2427	06	2437	08	2447		

3.

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Gain (dBi)	NOTE
1	N/A	N/A	External antenna	1	

2.2 DESCRIPTION OF TEST MODES

Pretest Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n20 CH1/ CH6/ CH11
Mode 4	802.11n40 CH3/ CH6/ CH9
Mode 5	Link Mode

Conducted Emission	
Final Test Mode	Description
Mode 5	Link Mode


For Radiated Emission	
Final Test Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n20 CH1/ CH6/ CH11
Mode 4	802.11n40 CH3/ CH6/ CH9

Note:


- (1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission Test



Radiated Spurious Emission Test



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Device Type	Brand	Model	Series No.	Data Cable
E-1	IP I/O Door Controller	N/A	A1081	N/A	EUT
E-2	Adapter	N/A	UT20-1501 00W	N/A	Auxiliary
E-3	DoorBird	N/A	N/A	N/A	Auxiliary

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	2.2M	DC cable unshielded

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	Agilent	E4407B	MY45109572	Jun. 13, 2019	Jun. 12, 2020
2	Test Receiver (9kHz-7GHz)	R&S	ESR7	101154	Jun. 13, 2019	Jun. 12, 2020
3	Bilog Antenna (30MHz-3GHz)	SCHWARZBECK	VULB9163	VULB9163-942	Jun. 22, 2019	Jun. 21, 2020
4	Horn Antenna (1GHz-18GHz)	SCHWARZBECK	BBHA9120D	1541	Jun. 22, 2019	Jun. 21, 2020
5	Horn Antenna (18GHz-40GHz)	SCHWARZBECK	BBHA9170	822	Jun. 22, 2019	Jun. 21, 2020
6	Amplifier (9KHz-6GHz)	SCHWARZBECK	BBV9744	9744-0037	Jun. 25, 2019	Jun. 24, 2020
7	Amplifier (0.5GHz-18GHz)	SCHWARZBECK	BBV9718	9718-309	Jun. 25, 2019	Jun. 24, 2020
8	Amplifier (18GHz-40GHz)	MITEQ	TTA1840-35-HG	2034381	Jun. 17, 2019	Jun. 16, 2020
9	Loop Antenna (9KHz-30MHz)	SCHWARZBECK	FMZB1519B	014	Jun. 25, 2019	Jun. 24, 2020
10	RF cables1 (9kHz-30MHz)	Huber+Suhnar	9kHz-30MHz	B1702988-0008	Jun. 25, 2019	Jun. 24, 2020
11	RF cables2 (30MHz-1GHz)	Huber+Suhnar	30MHz-1GHz	1486150	Jun. 25, 2019	Jun. 24, 2020
12	RF cables3 (1GHz-40GHz)	Huber+Suhnar	1GHz-40GHz	1607106	Jun. 25, 2019	Jun. 24, 2020
13	Power Metter	Keysight	E4419	\	Jun. 17, 2019	Jun. 16, 2020
14	Power Sensor (AV)	Keysight	E9 300A	\	Jun. 17, 2019	Jun. 16, 2020
15	Signal Analyzer 20kHz-26.5GHz	KEYSIGHT	N9020A	MY49100060	Jun. 13, 2019	Jun. 12, 2020
16	Spectrum Analyzer 9kHz-40GHz	Aglient	FSP40	100363	Jun. 13, 2019	Jun. 12, 2020
17	D.C. Power Supply	LongWei	TPR-6405D	\	\	\
18	Software	Frad	EZ-EMC	FA-03A2 RE	\	\

Conduction Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Test Receiver	R&S	ESR3	102075	Jun. 13, 2019	Jun. 12, 2020
2	LISN	SCHWARZBEC K	NSLK8127	8127739	Jun. 13, 2019	Jun. 12, 2020
3	LISN	R&S	ENV216	101375	Jun. 13, 2019	Jun. 12, 2020
4	RF cables	Huber+Suhnar	9kHz-30MHz	B1702988-00 08	Jun. 25, 2019	Jun. 24, 2020
5	Software	Frad	EZ-EMC	EMC-CON 3A1	\	\

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes


3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V and AC 240V, the worst voltage was AC 120V and the data recording in the report.

3.1.6 TEST RESULTS

Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101kPa	Phase :	L
Test Voltage :	AC120V 60Hz	Test Mode :	Mode 5




Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1660	35.67	9.50	45.17	65.16	-19.99	QP	
2		0.1660	23.70	9.50	33.20	55.16	-21.96	AVG	
3		0.3980	32.15	9.50	41.65	57.90	-16.25	QP	
4		0.3980	23.97	9.50	33.47	47.90	-14.43	AVG	
5		0.9900	24.89	9.57	34.46	56.00	-21.54	QP	
6		0.9900	18.53	9.57	28.10	46.00	-17.90	AVG	
7		2.9700	24.48	9.66	34.14	56.00	-21.86	QP	
8		2.9700	16.20	9.66	25.86	46.00	-20.14	AVG	
9		9.3900	24.14	9.70	33.84	60.00	-26.16	QP	
10		9.3900	21.19	9.70	30.89	50.00	-19.11	AVG	
11		26.6100	37.17	9.73	46.90	60.00	-13.10	QP	
12	*	26.6100	35.14	9.73	44.87	50.00	-5.13	AVG	

Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101kPa	Phase :	N
Test Voltage :	AC120V 60Hz	Test Mode :	Mode 5




Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1620	34.97	9.51	44.48	65.36	-20.88	QP	
2		0.1660	21.50	9.50	31.00	55.16	-24.16	AVG	
3		0.3940	33.02	9.50	42.52	57.98	-15.46	QP	
4		0.3940	24.99	9.50	34.49	47.98	-13.49	AVG	
5		0.9940	31.34	9.57	40.91	56.00	-15.09	QP	
6		0.9940	19.98	9.57	29.55	46.00	-16.45	AVG	
7		2.9780	33.21	9.66	42.87	56.00	-13.13	QP	
8		2.9780	19.66	9.66	29.32	46.00	-16.68	AVG	
9		5.9580	28.83	9.76	38.59	60.00	-21.41	QP	
10		5.9580	18.76	9.76	28.52	50.00	-21.48	AVG	
11		25.8779	38.29	9.74	48.03	60.00	-11.97	QP	
12	*	25.8779	34.14	9.74	43.88	50.00	-6.12	AVG	



Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101kPa	Phase :	L
Test Voltage :	POE power supply	Test Mode :	Mode 5




Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.

No.	Mk.	Freq. MHz	Reading Level	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1770	47.26	9.49	56.75	64.63	-7.88	QP	
2		0.1770	32.93	9.49	42.42	54.63	-12.21	AVG	
3		0.2310	40.73	9.50	50.23	62.41	-12.18	QP	
4		0.2310	21.67	9.50	31.17	52.41	-21.24	AVG	
5		0.7799	22.78	9.63	32.41	56.00	-23.59	QP	
6		0.7799	8.29	9.63	17.92	46.00	-28.08	AVG	
7		3.1425	27.62	9.67	37.29	56.00	-18.71	QP	
8		3.1425	14.89	9.67	24.56	46.00	-21.44	AVG	
9		20.6880	21.47	9.78	31.25	60.00	-28.75	QP	
10		20.6880	10.05	9.78	19.83	50.00	-30.17	AVG	
11		29.2380	28.36	9.71	38.07	60.00	-21.93	QP	
12		29.2380	15.15	9.71	24.86	50.00	-25.14	AVG	



Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101kPa	Phase :	N
Test Voltage :	POE power supply	Test Mode :	Mode 5



Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.

No.	Mk.	Freq. MHz	Reading Level dB	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1722	49.74	9.49	59.23	64.85	-5.62	QP	
2		0.1722	32.28	9.49	41.77	54.85	-13.08	AVG	
3		0.2615	37.37	9.53	46.90	61.38	-14.48	QP	
4		0.2615	18.15	9.53	27.68	51.38	-23.70	AVG	
5		0.7630	24.02	9.64	33.66	56.00	-22.34	QP	
6		0.7630	8.46	9.64	18.10	46.00	-27.90	AVG	
7		2.0225	25.51	9.59	35.10	56.00	-20.90	QP	
8		2.0225	10.95	9.59	20.54	46.00	-25.46	AVG	
9		3.0253	27.80	9.66	37.46	56.00	-18.54	QP	
10		3.0253	15.08	9.66	24.74	46.00	-21.26	AVG	
11		29.0613	27.79	9.71	37.50	60.00	-22.50	QP	
12		29.0613	14.74	9.71	24.45	50.00	-25.55	AVG	

3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	25GHz
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 25GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-chamber test. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8m; above 1GHz, the height was 1.5m, the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.
- g. For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.
The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

Note:


Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Test Voltage :	AC120V 60Hz
Test Mode :	Mode 5	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.

3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)

Temperature :	26℃	Relative Humidity :	54%
Pressure :	101 kPa	Polarization :	Horizontal
Test Voltage :	AC120V 60Hz		
Test Mode :	Mode 5		




Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		34.6385	34.67	-16.41	18.26	40.00	-21.74	QP
2		70.0903	44.53	-18.21	26.32	40.00	-13.68	QP
3		102.0014	53.69	-16.41	37.28	43.50	-6.22	QP
4		197.8928	51.40	-16.43	34.97	43.50	-8.53	QP
5	*	250.3012	57.13	-15.14	41.99	46.00	-4.01	QP
6		625.0780	46.64	-6.67	39.97	46.00	-6.03	QP

Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Polarization :	Vertical
Test Voltage :	AC120V 60Hz		
Test Mode :	Mode 5		



Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		34.6385	48.06	-16.41	31.65	40.00	-8.35	QP
2	!	66.2660	52.62	-17.34	35.28	40.00	-4.72	QP
3	*	95.3265	58.52	-17.13	41.39	43.50	-2.11	QP
4	!	199.9856	56.75	-16.30	40.45	43.50	-3.05	QP
5		250.3010	52.37	-15.14	37.23	46.00	-8.77	QP
6		625.0778	41.52	-6.67	34.85	46.00	-11.15	QP

3.2.8 TEST RESULTS (1GHZ~25GHZ)

802.11b

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2412MHz									
V	4824.00	66.52	39.55	7.85	25.66	60.48	74.00	-13.52	PK
V	4824.00	51.24	39.55	7.85	25.66	45.20	54.00	-8.80	AV
V	7236.00	67.02	38.33	7.52	24.55	60.76	74.00	-13.24	PK
V	7236.00	49.34	38.33	7.52	24.55	43.08	54.00	-10.92	AV
V	15450.00	52.13	35.23	6.75	26.59	50.24	74.00	-23.76	PK
H	4824.00	67.01	39.55	7.85	25.66	60.97	74.00	-13.03	PK
H	4824.00	50.71	39.55	7.85	25.66	44.67	54.00	-9.33	AV
H	7236.00	66.31	38.33	7.52	23.55	59.05	74.00	-14.95	PK
H	7236.00	50.58	38.33	7.52	23.22	42.99	54.00	-11.01	AV
H	15450.00	52.63	35.45	6.75	27.88	51.81	74.00	-22.19	PK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2437MHz									
V	4874.00	66.83	38.89	7.57	25.45	60.96	74.00	-13.04	Pk
V	4874.00	50.49	38.89	7.57	25.45	44.62	54.00	-9.38	AV
V	7311.00	67.42	38.78	7.35	24.78	60.77	74.00	-13.23	Pk
V	7311.00	49.37	38.78	7.35	24.78	42.72	54.00	-11.28	AV
V	15450.00	51.20	35.89	6.42	26.47	48.20	74.00	-25.80	Pk
H	4874.00	65.90	38.89	7.57	25.45	60.03	74.00	-13.97	Pk
H	4874.00	49.55	38.89	7.57	25.45	43.68	54.00	-10.32	AV
H	7311.00	64.98	38.78	7.35	24.78	58.33	74.00	-15.67	Pk
H	7311.00	50.77	38.78	7.35	24.78	44.12	54.00	-9.88	AV
H	15450.00	53.72	36.68	6.42	26.65	50.11	74.00	-23.89	Pk

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel: 2462MHz									
V	4924.00	68.18	38.75	7.46	25.45	62.34	74.00	-11.66	PK
V	4924.00	49.53	38.75	7.46	25.45	43.69	54.00	-10.31	AV
V	7386.00	68.65	38.65	7.22	24.78	62.00	74.00	-12.00	PK
V	7386.00	48.12	38.65	7.22	24.78	41.47	54.00	-12.53	AV
V	15450.00	49.73	35.58	6.35	26.47	46.97	74.00	-27.03	PK
H	4924.00	66.98	38.75	7.46	25.45	61.14	74.00	-12.86	PK
H	4924.00	48.85	38.75	7.46	25.45	43.01	54.00	-10.99	AV
H	7386.00	65.81	38.65	7.22	24.78	59.16	74.00	-14.84	PK
H	7386.00	50.42	38.65	7.22	24.78	43.77	54.00	-10.23	AV
H	15450.00	54.30	36.42	6.32	26.65	50.85	74.00	-23.15	PK

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,

Margin= Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

4. All the ANT have test, only the worst case reported.

802.11g

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2412MHz									
V	4824.00	69.24	39.55	7.85	25.66	63.20	74.00	-10.80	PK
V	4824.00	48.31	39.55	7.85	25.66	42.27	54.00	-11.73	AV
V	7236.00	67.71	38.33	7.52	24.55	61.45	74.00	-12.55	PK
V	7236.00	48.33	38.33	7.52	24.55	42.07	54.00	-11.93	AV
V	15450.00	50.29	35.23	6.75	26.59	48.40	74.00	-25.60	PK
H	4824.00	68.24	39.55	7.85	25.66	62.20	74.00	-11.80	PK
H	4824.00	50.00	39.55	7.85	25.66	43.96	54.00	-10.04	AV
H	7236.00	66.16	38.33	7.52	23.55	58.90	74.00	-15.10	PK
H	7236.00	49.30	38.33	7.52	23.22	41.71	54.00	-12.29	AV
H	15450.00	55.09	35.45	6.75	27.88	54.27	74.00	-19.73	PK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2437MHz									
V	4874.00	69.95	38.89	7.57	25.45	64.08	74.00	-9.92	PK
V	4874.00	46.95	38.89	7.57	25.45	41.08	54.00	-12.92	AV
V	7311.00	68.75	38.78	7.35	24.78	62.10	74.00	-11.90	PK
V	7311.00	48.26	38.78	7.35	24.78	41.61	54.00	-12.39	AV
V	15450.00	50.99	35.89	6.42	26.47	47.99	74.00	-26.01	PK
H	4874.00	66.96	38.89	7.57	25.45	61.09	74.00	-12.91	PK
H	4874.00	50.85	38.89	7.57	25.45	44.98	54.00	-9.02	AV
H	7311.00	66.56	38.78	7.35	24.78	59.91	74.00	-14.09	PK
H	7311.00	49.94	38.78	7.35	24.78	43.29	54.00	-10.71	AV
H	15450.00	55.22	36.68	6.42	26.65	51.61	74.00	-22.39	PK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel: 2462MHz									
V	4924.00	70.30	38.75	7.46	25.45	64.46	74.00	-9.54	PK
V	4924.00	47.95	38.75	7.46	25.45	42.11	54.00	-11.89	AV
V	7386.00	70.18	38.65	7.22	24.78	63.53	74.00	-10.47	PK
V	7386.00	49.56	38.65	7.22	24.78	42.91	54.00	-11.09	AV
V	15450.00	52.31	35.58	6.35	26.47	49.55	74.00	-24.45	PK
H	4924.00	67.85	38.75	7.46	25.45	62.01	74.00	-11.99	PK
H	4924.00	49.91	38.75	7.46	25.45	44.07	54.00	-9.93	AV
H	7386.00	65.89	38.65	7.22	24.78	59.24	74.00	-14.76	PK
H	7386.00	50.49	38.65	7.22	24.78	43.84	54.00	-10.16	AV
H	15450.00	56.08	36.42	6.32	26.65	52.63	74.00	-21.37	PK

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,

Margin= Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

4. All the ANT have test, only the worst case reported.

802.11n(20MHz)

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2412MHz									
V	4824.00	70.50	39.55	7.85	25.66	64.46	74.00	-9.54	PK
V	4824.00	47.68	39.55	7.85	25.66	41.64	54.00	-12.36	AV
V	7236.00	70.31	38.33	7.52	24.55	64.05	74.00	-9.95	PK
V	7236.00	50.88	38.33	7.52	24.55	44.62	54.00	-9.38	AV
V	15450.00	51.53	35.23	6.75	26.59	49.64	74.00	-24.36	PK
H	4824.00	67.40	39.55	7.85	25.66	61.36	74.00	-12.64	PK
H	4824.00	49.67	39.55	7.85	25.66	43.63	54.00	-10.37	AV
H	7236.00	64.39	38.33	7.52	23.55	57.13	74.00	-16.87	PK
H	7236.00	49.45	38.33	7.52	23.22	41.86	54.00	-12.14	AV
H	15450.00	57.37	35.45	6.75	27.88	56.55	74.00	-17.45	PK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2437MHz									
V	4874.00	69.33	38.89	7.57	25.45	63.46	74.00	-10.54	PK
V	4874.00	48.36	38.89	7.57	25.45	42.49	54.00	-11.51	AV
V	7311.00	71.16	38.78	7.35	24.78	64.51	74.00	-9.49	PK
V	7311.00	49.71	38.78	7.35	24.78	43.06	54.00	-10.94	AV
V	15450.00	51.24	35.89	6.42	26.47	48.24	74.00	-25.76	PK
H	4874.00	67.65	38.89	7.57	25.45	61.78	74.00	-12.22	PK
H	4874.00	50.81	38.89	7.57	25.45	44.94	54.00	-9.06	AV
H	7311.00	65.40	38.78	7.35	24.78	58.75	74.00	-15.25	PK
H	7311.00	48.07	38.78	7.35	24.78	41.42	54.00	-12.58	AV
H	15450.00	57.25	36.68	6.42	26.65	53.64	74.00	-20.36	PK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel: 2462MHz									
V	4924.00	68.89	38.75	7.46	25.45	63.05	74.00	-10.95	PK
V	4924.00	47.16	38.75	7.46	25.45	41.32	54.00	-12.68	AV
V	7386.00	71.87	38.65	7.22	24.78	65.22	74.00	-8.78	PK
V	7386.00	48.54	38.65	7.22	24.78	41.89	54.00	-12.11	AV
V	15450.00	51.34	35.58	6.35	26.47	48.58	74.00	-25.42	PK
H	4924.00	69.16	38.75	7.46	25.45	63.32	74.00	-10.68	PK
H	4924.00	51.85	38.75	7.46	25.45	46.01	54.00	-7.99	AV
H	7386.00	66.58	38.65	7.22	24.78	59.93	74.00	-14.07	PK
H	7386.00	49.09	38.65	7.22	24.78	42.44	54.00	-11.56	AV
H	15450.00	58.31	36.42	6.32	26.65	54.86	74.00	-19.14	PK

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,

Margin= Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

4. All the ANT have test, only the worst case reported.

802.11n(40MHz)

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2422MHz									
V	4844.00	68.55	39.55	7.77	25.66	62.43	74.00	-11.57	Pk
V	4844.00	48.51	39.55	7.77	25.66	42.39	54.00	-11.61	AV
V	7266.00	71.06	38.33	7.3	24.55	64.58	74.00	-9.42	Pk
V	7266.00	48.85	38.33	7.3	24.55	42.37	54.00	-11.63	AV
V	15450.00	50.44	35.23	6.6	26.59	48.40	74.00	-25.60	Pk
H	4844.00	68.88	39.55	7.77	25.66	62.76	74.00	-11.24	Pk
H	4844.00	51.70	39.55	7.77	25.66	45.58	54.00	-8.42	AV
H	7266.00	66.53	38.33	7.3	23.55	59.05	74.00	-14.95	Pk
H	7266.00	48.43	38.33	7.3	23.22	40.62	54.00	-13.38	AV
H	15450.00	58.53	35.45	6.6	27.88	57.56	74.00	-16.44	Pk

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2437MHz									
V	4874.00	69.00	38.89	7.57	25.45	63.13	74.00	-10.87	PK
V	4874.00	48.88	38.89	7.57	25.45	43.01	54.00	-10.99	AV
V	7311.00	70.22	38.78	7.35	24.78	63.57	74.00	-10.43	PK
V	7311.00	48.99	38.78	7.35	24.78	42.34	54.00	-11.66	AV
V	15450.00	50.12	35.89	6.42	26.47	47.12	74.00	-26.88	PK
H	4874.00	67.40	38.89	7.57	25.45	61.53	74.00	-12.47	PK
H	4874.00	50.61	38.89	7.57	25.45	44.74	54.00	-9.26	AV
H	7311.00	66.46	38.78	7.35	24.78	59.81	74.00	-14.19	PK
H	7311.00	47.73	38.78	7.35	24.78	41.08	54.00	-12.92	AV
H	15450.00	59.78	36.68	6.42	26.65	56.17	74.00	-17.83	PK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel: 2452MHz									
V	4904.00	69.97	38.75	7.38	25.45	64.05	74.00	-9.95	PK
V	4904.00	48.45	38.75	7.38	25.45	42.53	54.00	-11.47	AV
V	7356.00	70.76	38.65	7.15	24.78	64.04	74.00	-9.96	PK
V	7356.00	49.96	38.65	7.15	24.78	43.24	54.00	-10.76	AV
V	15450.00	49.38	35.58	6.25	26.47	46.52	74.00	-27.48	PK
H	4904.00	68.27	38.75	7.38	25.45	62.35	74.00	-11.65	PK
H	4904.00	49.65	38.75	7.38	25.45	43.73	54.00	-10.27	AV
H	7356.00	68.01	38.65	7.15	24.78	61.29	74.00	-12.71	PK
H	7356.00	48.07	38.65	7.15	24.78	41.35	54.00	-12.65	AV
H	15450.00	59.90	36.42	6.25	26.65	56.38	74.00	-17.62	PK

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
4. All the ANT have test, only the worst case reported.

3.3 RADIATED BAND EMISSION MEASUREMENT

3.3.1 TEST REQUIREMENT:

FCC Part15 C Section 15.209 and 15.205

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

3.3.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.3.3 DEVIATION FROM TEST STANDARD

No deviation

3.3.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



3.3.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

3.3.6 TEST RESULT

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission evel (dBuV/m)	Limits (dBuV/m)		Result
							PK	PK	AV	
802.11b	Low Channel 2412MHz									
	H	2390.00	61.45	38.06	7.42	20.15	50.96	74.00	54.00	PASS
	H	2400.00	55.05	38.06	7.42	20.15	44.56	74.00	54.00	PASS
	V	2390.00	60.40	38.06	7.42	20.15	49.91	74.00	54.00	PASS
	V	2400.00	54.69	38.06	7.42	20.15	44.20	74.00	54.00	PASS
	High Channel 2462MHz									
	H	2483.50	61.88	38.17	7.45	20.54	51.70	74.00	54.00	PASS
	H	2485.50	53.22	38.17	7.45	20.54	43.04	74.00	54.00	PASS
	V	2483.50	61.98	38.2	7.45	20.54	51.77	74.00	54.00	PASS
	V	2485.50	51.63	38.2	7.45	20.54	41.42	74.00	54.00	PASS
802.11g	Low Channel 2412MHz									
	H	2390.00	61.74	38.06	7.42	20.15	51.25	74.00	54.00	PASS
	H	2400.00	51.16	38.06	7.42	20.15	40.67	74.00	54.00	PASS
	V	2390.00	61.70	38.06	7.42	20.15	51.21	74.00	54.00	PASS
	V	2400.00	55.33	38.06	7.42	20.15	44.84	74.00	54.00	PASS
	High Channel 2462MHz									
	H	2483.50	61.94	38.17	7.45	20.54	51.76	74.00	54.00	PASS
	H	2485.50	53.27	38.17	7.45	20.54	43.09	74.00	54.00	PASS
	V	2483.50	61.27	38.2	7.45	20.54	51.06	74.00	54.00	PASS
	V	2485.50	53.53	38.2	7.45	20.54	43.32	74.00	54.00	PASS
802.11n20	Low Channel 2412MHz									
	H	2390.00	61.55	38.06	7.42	20.15	51.06	74.00	54.00	PASS
	H	2400.00	51.23	38.06	7.42	20.15	40.74	74.00	54.00	PASS
	V	2390.00	62.46	38.06	7.42	20.15	51.97	74.00	54.00	PASS
	V	2400.00	55.21	38.06	7.42	20.15	44.72	74.00	54.00	PASS
	High Channel 2462MHz									
	H	2483.50	61.19	38.17	7.45	20.54	51.01	74.00	54.00	PASS
	H	2485.50	51.42	38.17	7.45	20.54	41.24	74.00	54.00	PASS
	V	2483.50	59.81	38.2	7.45	20.54	49.60	74.00	54.00	PASS
	V	2485.50	51.67	38.2	7.45	20.54	41.46	74.00	54.00	PASS
802.11n40	Low Channel 2422MHz									
	H	2390.00	62.93	38.06	7.42	20.15	52.44	74.00	54.00	PASS
	H	2400.00	53.93	38.06	7.42	20.15	43.44	74.00	54.00	PASS
	V	2390.00	61.54	38.06	7.42	20.15	51.05	74.00	54.00	PASS
	V	2400.00	52.34	38.06	7.42	20.15	41.85	74.00	54.00	PASS
	High Channel 2452MHz									
	H	2483.50	61.51	38.17	7.45	20.54	51.33	74.00	54.00	PASS
	H	2485.50	53.39	38.17	7.45	20.54	43.21	74.00	54.00	PASS
	V	2483.50	58.50	38.2	7.45	20.54	48.29	74.00	54.00	PASS
	V	2485.50	54.66	38.2	7.45	20.54	44.45	74.00	54.00	PASS
Remark:										
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit										
2. If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.										
* is stand for AV measured.										

4. POWER SPECTRAL DENSITY TEST

4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS


4.1.1 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP



4.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

Note: Power Spectral Density(dBm)=Reading+Cable Loss

4.1.5 TEST RESULTS


Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC120V 60Hz
Test Mode :	TX b Mode		

Frequency	Power Spectral Density(dBm)	Limit (dBm)	Result
2412 MHz	-9.54	8	PASS
2437 MHz	-11.40	8	PASS
2462 MHz	-11.21	8	PASS






TX CH06



Date: 18.JUL.2019 16:44:22

TX CH11






Date: 18.JUL.2019 16:46:59



Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC120V 60Hz
Test Mode :	TX g Mode		

Frequency	Power Spectral Density(dBm)	Limit (dBm)	Result
2412 MHz	-15.07	8	PASS
2437 MHz	-16.52	8	PASS
2462 MHz	-15.68	8	PASS









Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC120V 60Hz
Test Mode :	TX n Mode(20M)		

Frequency	Power Spectral Density(dBm)	Limit (dBm)	Result
2412 MHz	-15.49	8	PASS
2437 MHz	-16.20	8	PASS
2462 MHz	-15.61	8	PASS






TX CH06



Date: 18.JUL.2019 16:54:42

TX CH11




Date: 18.JUL.2019 16:57:18




Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC120V 60Hz
Test Mode :	TX n Mode(40M)		

Frequency	Power Spectral Density(dBm)	Limit (dBm)	Result
2422 MHz	-16.59	8	PASS
2437 MHz	-16.73	8	PASS
2452 MHz	-17.10	8	PASS






TX CH06



Date: 18.JUL.2019 17:00:49

TX CH09



Date: 18.JUL.2019 16:59:21

5. BANDWIDTH TEST

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

5.1.1 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP



5.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



5.1.5 TEST RESULTS


Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC120V 60Hz
Test Mode :	TX b Mode		

Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
2412	10.02	500	Pass
2437	10.08	500	Pass
2462	10.02	500	Pass






TX CH 06



Date: 18.JUL.2019 09:54:56

TX CH 11




Date: 18.JUL.2019 09:57:43




Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC120V 60Hz
Test Mode :	TX g Mode		

Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
2412	16.50	500	Pass
2437	16.44	500	Pass
2462	16.44	500	Pass






TX CH 06



Date: 18.JUL.2019 10:07:06

TX CH 11




Date: 18.JUL.2019 10:03:15




Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC120V 60Hz
Test Mode :	TX n Mode(20M)		

Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
2412	17.58	500	Pass
2437	17.58	500	Pass
2462	17.58	500	Pass






TX CH 06



Date: 18.JUL.2019 10:18:56

TX CH 11




Date: 18.JUL.2019 10:22:23




Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC120V 60Hz
Test Mode :	TX n Mode(40M)		

Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
2422	36.48	500	Pass
2437	36.36	500	Pass
2452	36.36	500	Pass






TX CH 06



Date: 18.JUL.2019 10:28:16

TX CH 09



Date: 18.JUL.2019 10:25:41

6. PEAK OUTPUT POWER TEST

6.1 APPLIED PROCEDURES/LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

6.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the Power meter

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

6.1.5 TEST RESULTS

Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC120V 60Hz

	Frequency	Maximum Conducted Output Power(PK)	LIMIT
	(MHz)	(dBm)	dBm
802.11b	2412	14.27	30
	2437	14.14	30
	2462	14.26	30
802.11g	2412	13.34	30
	2437	13.28	30
	2462	13.85	30
802.11n20	2412	13.56	30
	2437	13.60	30
	2462	13.68	30
802.11n40	2422	12.46	30
	2437	12.12	30
	2452	12.27	30

7. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE

7.1 APPLICABLE STANDARD

in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in§15.205(a), must also comply with the radiated emission limits specified in15.209(a).

7.2 TEST PROCEDURE

Using the following spectrum analyzer setting:

- a) Set the RBW = 100KHz.
- b) Set the VBW = 300KHz.
- c) Sweep time = auto couple.
- d) Detector function = peak.
- e) Trace mode = max hold.
- f) Allow trace to fully stabilize.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP




7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.6 TEST RESULT




802.11b: Band Edge, Left Side



Date: 18.JUL.2019 11:48:52


802.11b: Band Edge, Right Side



Date: 18.JUL.2019 11:38:42




802.11g: Band Edge, Left Side



Date: 18.JUL.2019 11:29:12


802.11g: Band Edge, Right Side



Date: 18.JUL.2019 11:33:57




802.11n-HT20: Band Edge, Left Side



Date: 18.JUL.2019 11:25:24


802.11n-HT20: Band Edge, Right Side



Date: 18.JUL.2019 11:21:37




802.11n-HT40: Band Edge, Left Side



Date: 18.JUL.2019 10:57:26

802.11n-HT40: Band Edge, Right Side




Date: 18.JUL.2019 11:13:14




CONDUCTED EMISSION MEASUREMENT

802.11b

Low Channel 2412MHz




Date: 18.JUL.2019 17:11:05




Date: 18.JUL.2019 17:57:34

Middle Channel 2437MHz




Date: 18.JUL.2019 18:30:34




Date: 18.JUL.2019 18:33:42

High Channel 2462MHz



Date: 18.JUL.2019 18:36:13




Date: 18.JUL.2019 19:12:10




802.11g

Low Channel 2412MHz




Date: 18.JUL.2019 19:26:42




Date: 18.JUL.2019 19:31:14

Middle Channel 2437MHz




Date: 18.JUL.2019 19:19:21




Date: 18.JUL.2019 19:24:49

High Channel 2462MHz



Date: 18.JUL.2019 19:14:53




Date: 18.JUL.2019 19:17:45


802.11n20



Low Channel 2412MHz




Date: 18.JUL.2019 19:33:14




Date: 18.JUL.2019 19:36:11

Middle Channel 2437MHz




Date: 18.JUL.2019 19:37:34




Date: 18.JUL.2019 19:40:12

High Channel 2462MHz



Date: 18.JUL.2019 19:41:33




Date: 18.JUL.2019 19:45:48




802.11n40

Low Channel 2422MHz




Date: 18.JUL.2019 19:48:35




Date: 18.JUL.2019 19:51:05

Middle Channel 2437MHz




Date: 18.JUL.2019 19:53:25




Date: 18.JUL.2019 19:56:06

High Channel 2452MHz



Date: 18.JUL.2019 19:58:04



Date: 18.JUL.2019 20:00:47

8. DUTY CYCLE OF TEST SIGNAL

8.1 STANDARD REQUIREMENT

Pre-analysis Check: While conducting average power measurement, duty cycle of each mode shall be checked to ensure its duty cycle in order to compensate for the loss due to insufficient ratio of duty cycle.

All duty cycle is pre-scanned, and result as obtained below shows only the most representative ones where duty cycle is conducted as the given transmission with given virtual operation that expresses the percentage.

8.2 FORMULA:

Duty Cycle = $T_{on} / (T_{on} + T_{off})$

Measurement Procedure:

1. Set span = Zero
2. RBW = 8MHz
3. VBW = 8MHz,
4. Detector = Peak


Duty Cycle:

	Duty Cycle	Duty Fator (dB)
802.11b	1	0
802.11g	1	0
802.11n(HT20)	1	0
802.11n(HT40)	1	0




Report No.: BCTC-FY190502834E

802.11b




802.11g






802.11n(HT20)



802.11n(HT40)



9. ANTENNA REQUIREMENT

9.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

9.2 EUT ANTENNA

The EUT antenna is External antenna, It comply with the standard requirement.




10. EUT TEST PHOTO

Conducted Measurement Photos





Radiated Measurement Photos





11. EUT PHOTO





***** END OF REPORT *****