



## 3.5. 20dB Bandwidth

#### **Limit**

N/A

## **Test Configuration**



## **Test Procedure**

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- 6. OCB and 20dB Spectrum Setting:
  - (1) Set RBW = 1% ~ 5% occupied bandwidth.
  - (2) Set the video bandwidth (VBW) ≥ 3 RBW.
  - (3) Detector = Peak.
  - (4) Trace mode = Max hold.
  - (5) Sweep = Auto couple.

Note: The EUT was set to continuously transmitting in each mode and low, Middle and high channel for the test.

## **Test Mode**

Please refer to the clause 2.4.


#### **Test Results**

TestMode	Antenna	Channel	20db EBW[MHz]	FL[MHz]	FH[MHz]	20dB Bandwidth* 2/3(MHz)	Verdict
		2402	0.945	2401.514	2402.459	0.630	PASS
DH5	Ant1	2441	0.948	2440.517	2441.465	0.632	PASS
		2480	0.942	2479.517	2480.459	0.628	PASS
	Ant1	2402	1.299	2401.334	2402.633	0.866	PASS
2DH5		2441	1.305	2440.322	2441.627	0.870	PASS
		2480	1.293	2479.340	2480.633	0.862	PASS
3DH5		2402	1.287	2401.337	2402.624	0.858	PASS
	Ant1	2441	1.260	2440.340	2441.600	0.840	PASS
		2480	1.320	2479.322	2480.642	0.880	PASS













Page 68 of 85

Report No.: CTC20211300E02




## 3.6. Channel Separation

## **Limit**

## FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1)/ RSS-247 5.1 b:

Test Item	Limit	Frequency Range(MHz)	
Channel Separation	>25KHz or >two-thirds of the 20 dB bandwidth Which is greater	2400~2483.5	

## **Test Configuration**



#### **Test Procedure**

- 7. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- 8. Spectrum Setting:
  - (1) Set RBW = 100 kHz.
  - (2) Set the video bandwidth (VBW) ≥ 3 RBW.
  - (3) Detector = Peak.
  - (4) Trace mode = Max hold.
  - (5) Sweep = Auto couple.

## **Test Mode**

Please refer to the clause 2.4.

## **Test Results**

Test Mode	Frequency(MHz)	Result[MHz]	Limit[MHz]	Verdict
GFSK	Hop_2441	1.000	>=0.632	PASS
π/4-DQPSK	Hop_2441	1.014	>=0.870	PASS
8-DPSK	Hop_2441	1.000	>=0.880	PASS








# 3.7. Number of Hopping Channel

#### Limit

## FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(iii)/ RSS-247 5.1 d:

Section Test Item		Limit
15.247 (a)(iii)/ RSS-247 5.1 d:	Number of Hopping Channel	>15

## **Test Configuration**



## **Test Procedure**

- 1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- 2. Spectrum Setting:
  - (1) Peak Detector: RBW=100 kHz, VBW≥RBW, Sweep time= Auto.


## **Test Mode**


Please refer to the clause 2.4.

## **Test Result**

Modulation type	Modulation type Channel number		Result
GFSK	79		
π /4-DQPSK	79	≥15.00	Pass
8DPSK	79		










## 3.8. Dwell Time

#### Limit

Section	Test Item	Limit	
15.247(a)(iii)/ RSS-247 5.1 d	Average Time of Occupancy	0.4 sec	

## **Test Configuration**



## **Test Procedure**

- 1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- 2. Spectrum Setting:
  - (1) Spectrum Setting: RBW=1MHz, VBW≥RBW.
  - (2) Use video trigger with the trigger level set to enable triggering only on full pulses.
  - (3) Sweep Time is more than once pulse time.
- (4) Set the center frequency on any frequency would be measure and set the frequency span to zero.
  - (5) Measure the maximum time duration of one single pulse.
  - (6) Set the EUT for packet transmitting.

## **Test Mode**

Please refer to the clause 2.4.






**Test Result** 


Modulation type	Channel	Frequency (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (ms)	Limit (Second)	Result
	DH1	2441	0.37	118.40	31.60		
GFSK	DH3	2441	1.63	260.80	31.60	≤ 0.40	Pass
	DH5	2441	2.87	306.13	31.60		
	2DH1	2441	0.38	121.60	31.60		
π /4-DQPSK	2DH3	2441	1.63	260.80	31.60	≤ 0.40	Pass
74-DQI OK	2DH5	2441	2.88	307.20	31.60		
	3DH1	2441	0.38	121.60	31.60		
8-DPSK	3DH3	2441	1.63	260.80	31.60	≤ 0.40	Pass
	3DH5	2441	2.88	307.20	31.60		

Note: 1DH1/2DH1/3DH1 Total of Dwell= Pulse Time\*(1600/2)\*31.6/79 1DH3/2DH3/3DH3 Total of Dwell= Pulse Time\*(1600/4)\*31.6/79 1DH5/2DH5/3DH5 Total of Dwell= Pulse Time\*(1600/6)\*31.6/79
































# 3.9. Peak Output Power

## Limit

## FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(1) / RSS-247 5.4 b:

Test Item	Limit	Frequency Range(MHz)	
Peak Output Power	Hopping Channels>75 Pow- er<1W(30dBm) Other <125mW(21dBm)	2400~2483.5	

## **Test Configuration**



## **Test Procedure**

- 1. The EUT was directly connected to the Power Meter and antenna output port as show in the block diagram above.
- 2. Read the power value in the test software and record it.

## **Test Mode**

Please refer to the clause 2.4.

## **Test Result**

Test Mode	Frequency (MHz)	Result[dBm]	Limit[dBm]	Verdict
	2402	4.83	<=21	PASS
GFSK	2441	5.15	<=21	PASS
	2480	4.99	<=21	PASS
	2402	3.64	<=21	PASS
π /4-DQPSK	2441	4.22	<=21	PASS
	2480	3.96	<=21	PASS
	2402	4.14	<=21	PASS
8-DPSK	2441	4.42	<=21	PASS
	2480	4.31	<=21	PASS




# 3.10. Duty Cycle

#### Limit

None, for report purposes only.

#### **Test Configuration**



## **Test Procedure**

- 1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- 2. The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above. The measurement according to section 10.2 of KDB 558074 D01 DTS Meas Guidance v05r02.
- 3. Spectrum Setting:

Set analyzer center frequency to test channel center frequency.

Set the span to 0Hz Set the RBW to 10MHz Set the VBW to 10MHz

Detector: Peak Sweep time: Auto

Allow trace to fully stabilize. Then use the peak marker function to determine the maximum amplitude level.

## **Test Mode**

Please refer to the clause 2.4.

## **Test Result**

Test Mode	Frequency (MHz)	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]	1/T Minimum VBW (kHz)	Final setting For VBW (kHz)
	2402	2.875	5.003	0.57	0.20	1
GFSK	2441	2.879	5.006	0.58	0.20	1
	2480	2.880	5.005	0.58	0.20	1
	2402	2.884	5.005	0.58	0.20	1
π /4-DQPSK	2441	2.883	5.002	0.58	0.20	1
	2480	2.884	5.005	0.58	0.20	1
	2402	2.885	5.005	0.58	0.20	1
8-DPSK	2441	2.887	5.001	0.58	0.20	1
	2480	2.878	4.993	0.58	0.20	1













Page 85 of 85

Report No.: CTC20211300E02



## 3.11. Antenna Requirement

## Requirement

## FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

## FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):

(i) Systems operating in the 2400~2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

#### **Test Result**

Complies

Directional gain =  $G_{ANT}$  = 5dBi

Note: Bluetooth mode only supports SISO mode and does not support MIMO transmission.

