

FCC RF EXPOSURE REPORT

FCC ID: A5M-L06E

Project No. : 2005C026C
Equipment : Integrated TWS Earbuds
Brand Name : Lenovo
Test Model : L06E
Series Model : N/A
Applicant : Lenovo (Beijing) Limited
Address : 201-H2-6, Floor 2, Building 2, No. 6, Shangdi West Road, Haidian District, Beijing, China 100085
Manufacturer : Lenovo (Beijing) Limited
Address : 201-H2-6, Floor 2, Building 2, No. 6, Shangdi West Road, Haidian District, Beijing, China 100085
Factory : Dongguan Luxshare Precision Industry Co., Ltd
Address : 1F, Building 5, No.313, Beihuan Road, Qingxi Town, Dongguan City
Date of Receipt : May 07, 2020
Mar. 25, 2021
Date of Test : May 07, 2020 ~ May 22, 2020
Issued Date : Apr. 30, 2021
Report Version : R00
Test Sample : Engineering Sample No.: DG2020050868
Standard(s) : FCC Guidelines for Human Exposure IEEE C95.1 & KDB447498 D01

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

Vincent Tan

Prepared by : Vincent Tan

Ethan Ma

Approved by : Ethan Ma



Certificate #5123.02

Add: No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, Guangdong, China.

Tel: +86-769-8318-3000

Web: www.newbtl.com

REPORT ISSUED HISTORY

Report Version	Description	Issued Date
R00	Compared with previous test report (BTL-FCCP-3-2005C026), added a battery (Model2: VDL 04220) and added a board (only differ in circuit) which does not affect the test result. So the original test data were saved in this report.	Apr. 30, 2021

1. TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No.3,Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, Guangdong, China.

BTL's Test Firm Registration Number for FCC: 357015

BTL's Designation Number for FCC: CN1240

2. GENERAL CONCLUSION

According to FCC KDB447498 D01, Appendix A, SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

**Appendix A - SAR Test Exclusion Thresholds for 100 MHz - 6 GHz
and ≤ 50 mm**

MHz	5	10	15	20	25	30	35	40	45	50	mm
150	39	77	116	155	194	232	271	310	349	387	SAR Test Exclusion Thresholds (mW)
300	27	55	82	110	137	164	192	219	246	274	
450	22	45	67	89	112	134	157	179	201	224	
835	16	33	49	66	82	98	115	131	148	164	
900	16	32	47	63	79	95	111	126	142	158	
1500	12	24	37	49	61	73	86	98	110	122	
1900	11	22	33	44	54	65	76	87	98	109	
2450	10	19	29	38	48	57	67	77	86	96	
3600	8	16	24	32	40	47	55	63	71	79	
5200	7	13	20	26	33	39	46	53	59	66	
5400	6	13	19	26	32	39	45	52	58	65	
5800	6	12	19	25	31	37	44	50	56	62	

3. TABLE FOR FILED ANTENNA

Ant.	Brand	P/N	Antenna Type	Connector	Gain (dBi)
1	LUXSHARE-ICT	RDNI 908269-001	Internal	N/A	-2

Note: The antenna gain is provided by the manufacturer.

4. TEST RESULTS**For BT:**

Max. Output Power (dBm)	Max. Output Power (mW)	Limit (mW)
4.99	3.16	10

For LE:

Max. Output Power (dBm)	Max. Output Power (mW)	Limit (mW)
4.90	3.09	10

Note:

- (1) Output power including tune up tolerance (Tune up tolerance: ± 1 dBm).
 - (2) The maximum measured output peak power of this EUT is 3.16mW, less than 10mW at 5mm distance.
- Conclusion: No SAR evaluation required since transmitter power is below FCC threshold.

End of Test Report