



# Radio Frequency Exposure Evaluation Report

## FOR:

Crane Payment Innovations

## Model Name:

AIO2210-US101

## Product Description:

ALIO Note is a card reader bezel that incorporates mag stripe, contact, and contactless card reader capabilities in support of unattended cashless sales. It is mechanically mounted on a bill acceptor during normal use further enhancing payment capability at the POS. It utilizes 4g CAT M (Telit module ME910G1WW) cellular radio, NFC (13.56 MHz) to read cards, and BLE (QUALCOMM CSR1010) to support diagnostic capability.

**FCC ID:** QP8ALIONOTEVZ

## Applied Rules and Standards:

CFR 47 Part 2 (2.1093),  
FCC KDB 447498 D01 General RF Exposure Guidance v06

**Report number:** EMC\_MEIGR-011-21001\_FCC\_SAR\_EX

**DATE:** 2021-06-01



A2LA Accredited

## **CETECOM Inc.**

411 Dixon Landing Road • Milpitas, CA 95035 • U.S.A.

Phone: + 1 (408) 586 6200 • Fax: + 1 (408) 586 6299 • E-mail: [info@cetecom.com](mailto:info@cetecom.com) • <http://www.cetecom.com>  
CETECOM Inc. is a Delaware Corporation with Corporation number: 2905571

## Contents

1. Assessment.....	3
2. Administrative Data .....	4
2.1. Identification of the Testing Laboratory Issuing the Test Report .....	4
2.2. Identification of the Client / Manufacturer .....	4
3. Equipment under Assessment.....	5
4. FCC Exemption Limits for Routine Evaluation .....	6
4.1. FCC SAR test exclusions per KDB 447498.....	6
5. Stand-alone Transmission SAR Exclusion Evaluation.....	7
5.1. Justification for using the 5 mm Distance .....	7
5.2. Justification for use of load based time averaging.....	7
5.3. SAR Exclusion Calculation Table.....	8
6. Simultaneous Transmission SAR Exclusion Evaluation .....	9
6.1. FCC 1-g Standalone Transmitter Calculation for Simultaneous Transmitter SAR Exclusion .....	9
6.2. Simultaneous Transmission FCC 1-g SAR Exclusion calculation .....	9
7. Revision History .....	10

## 1. Assessment

The following device was evaluated against the limits for general population uncontrolled exposure specified in CFR 47 Part 2.1093 according to SAR evaluation exclusion requirements specified in FCC regulation as listed in KDB 447498.

The device meets the requirements for SAR exclusion as stipulated by the above given FCC rules.

Company	Description	Model #
Crane Payment Innovations	ALIO Note is a card reader bezel that incorporates mag stripe, contact, and contactless card reader capabilities in support of unattended cashless sales. It is mechanically mounted on a bill acceptor during normal use further enhancing payment capability at the POS. It utilizes 4g CAT M (Telit module ME910G1WW) cellular radio, NFC (13.56 MHz) to read cards, and BLE (QUALCOMM QualCom CSR1010) to support diagnostic capability.	AIO2210-US101

### Responsible for Testing Laboratory:

2021-06-01	Compliance	Kevin Wang (Lab Manager)	
Date	Section	Name	Signature

### Responsible for the Report:

2021-06-01	Compliance	Yuchan Lu (Test Engineer)	
Date	Section	Name	Signature

The test results of this test report relate exclusively to the test item specified in Section 3.

CETECOM Inc. USA does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM Inc. USA.

## 2. Administrative Data

### 2.1. Identification of the Testing Laboratory Issuing the Test Report

<b>Company Name:</b>	CETECOM Inc.
<b>Department:</b>	Compliance
<b>Street Address:</b>	411 Dixon Landing Road
<b>City/Zip Code</b>	Milpitas, CA 95035
<b>Country</b>	USA
<b>Telephone:</b>	+1 (408) 586 6200
<b>Fax:</b>	+1 (408) 586 6299
<b>Lab Manager:</b>	Kevin Wang
<b>Responsible Project Leader:</b>	Rami Saman

### 2.2. Identification of the Client / Manufacturer

<b>Client's Name:</b>	Crane Payment Innovations
<b>Street Address:</b>	3222 Phoenixville Pike, Suite 200
<b>City/Zip Code</b>	Malvern, PA 19355
<b>Country</b>	USA

<b>Manufacturer's Name:</b>	Same as Client
<b>Manufacturers Address:</b>	
<b>City/Zip Code</b>	
<b>Country</b>	

### 3. Equipment under Assessment

<b>Model No</b>	AIO2210-US101
<b>HW Version</b>	G1
<b>SW Version</b>	5.X
<b>FCC-ID</b>	QP8ALIONOTEVZ
<b>Product Description</b>	ALIO Note is a card reader bezel that incorporates mag stripe, contact, and contactless card reader capabilities in support of unattended cashless sales. It is mechanically mounted on a bill acceptor during normal use further enhancing payment capability at the POS. It utilizes 4g CAT M (Telit module ME910G1WW) cellular radio, NFC (13.56 MHz) to read cards, and BLE (QUALCOMM CSR1010) to support diagnostic capability.
<b>Device Category</b>	<input type="checkbox"/> Fixed Installation <input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Mixed Mobile and Portable
<b>Frequency Range / number of channels</b>	CAT-M1 LTE Band 4: 1710.7 – 1754.3 MHz; CAT-M1 LTE Band 13: 779.5 – 784.5 MHz; BT LE: 2402(ch 0) – 2480(ch 39), 40 channels
<b>Type(s) of Modulation</b>	LTE Bands: QPSK Modulation Bluetooth version 4.0: GFSK modulation
<b>Modes of Operation / Declared Output power</b>	CAT-M1 LTE Band 4: 23.86 dBm; CAT-M1 LTE Band 13: 23.04 dBm; BT LE: 9.4 dBm
<b>Max. declared antenna gain</b>	LTE: Taoglas antenna PT# FXUB65 <ul style="list-style-type: none"> <li>• LTE Band 4/13 = 2 dBi Peak</li> <li>• BTLE: pcb strip line antenna, 1.8 dBi</li> </ul>
<b>Minimum distance of antenna or radiating parts to user</b>	20 mm
<b>Power Supply/ Rated Operating Voltage Range</b>	Vmin: 20 VDC/ Vnom: 24 VDC / Vmax: 42 VDC
<b>Operating Temperature Range</b>	Low -15°C, Nominal 25°C, High 60°C
<b>Other Radios included in the device</b>	NFC
<b>Co-located Transmitters / Antennas</b>	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
<b>Sample Revision</b>	<input type="checkbox"/> Prototype <input checked="" type="checkbox"/> Production <input type="checkbox"/> Pre-Production
<b>Exposure Category</b>	<input type="checkbox"/> Occupational/ Controlled <input checked="" type="checkbox"/> General Population/ Uncontrolled

## 4. FCC Exemption Limits for Routine Evaluation

### 4.1. FCC SAR test exclusions per KDB 447498

KDB 447498 D01 General RF Exposure Guidance v06 Section: 4.3.1.

Standalone SAR test exclusion considerations states

- 4) For 100 MHz to 6 GHz and test separation distances  $\leq 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$$

$\leq 3.0$  for 1-g SAR, and  $\leq 7.5$  for 10-g extremity SAR, 30 where

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- The values 3.0 and 7.5 are referred to as *numeric thresholds*.

The test exclusions are applicable only when the minimum *test separation distance* is  $\leq 50$  mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is  $< 5$  mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

**SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and  $\leq 50$  mm**

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

## **5. Stand-alone Transmission SAR Exclusion Evaluation**

### **5.1. Justification for using the 20 mm Distance**

The device intends to be used on human body. The conservative distance of 20 mm is an estimate of how close a human body can be to the device in its typical application.

### **5.2. Justification for use of load based time averaging**

The worst case loading for each of the radios was determined from the following information provided by the manufacturer:

EUT Operating Conditions

Co-transmission is only possible with Cellular and BT LE.

### 5.3. SAR Exclusion Calculation Table

FCC Standalone Transmission SAR Exclusion Calculations								
Band	d [mm]	f [GHz]	Max Power + Tune Up [mW]	Source Based Duty Cycle	Load based duty cycle based on Maximum payload. <sup>2</sup>	Effective Time Average Max Power [mW]	FCC Limit <sup>1</sup> @ 20 mm [mW]	SAR Exclusion applicable (Yes/No)
LTE Band 4	20	1.755	316.23	1.00	0.074	23.40	45.29	Yes
LTE Band 13	20	0.787	316.23	1.00	0.074	23.40	67.63	Yes
BTLE	20	2.48	8.71	1.00	0.05	0.44	38.10	Yes
NFC	20	0.01356	1400	1.00	0.0132	18.48	424.3	Yes

Note 1: The FCC limit was derived by calculating the maximum output power passing the threshold for 1-g SAR exclusion

Note 2: RRC connection setup in LTE:

The connection setup is not be affected by our transmission control mechanism as there is not user plane data involved here.

MSG1 (RACH preamble) is a maximum 2.3 ms in length.

MSG3 (RRC connection request) is a maximum of 100 bits long. In worst-case resource allocation of 16 bits /ms this will lead to a 7 ms transmission time

MSG5 (RRC connection setup complete) is a maximum of 100 Bytes long. In worst-case resource allocation of 16 bits /ms this will lead to a 50 ms transmission time.

In case the RRC connection is not successful because the MSG5 does not get through, a conservative RRC timeout is defined by ALIO with 800 ms. Only after this timer runs down the UE may attempt another connection requests.

59.3 ms in 800 ms leads to a worst-case duty cycle of **7.4%**.

All above values have been taken from the LTE physical layer standard 3GPP TS 36.213 and the LTE MAC layer standard 3GPP TS 36.321.

Transmission of user plane data over LTE:

1) Transmission speed = 230Kbits/ sec.

2) Max bits user data, transmitted / card authorization:

During card authorization, 13,112 bits are transmitted.

At an allocation, 230k bits/second this takes 0.057 seconds of transmission time.

Duty cycle = **5.7%**

Based on customer declaration, the transmission for NFC:

NFC Duty cycle = NFC Transmit time per vend / Vending cycle time until next Vend Start.

NFC Duty cycle = 500ms / 38 second

NFC Duty cycle = 0.0132 or 1.32%



## 6. Simultaneous Transmission SAR Exclusion Evaluation

### 6.1. FCC 1-g Standalone Transmitter Calculation for Simultaneous Transmitter SAR Exclusion

Band	d [mm]	f [GHz]	Max Power + Tune Up [mW]	Source Based Duty Cycle	Load based duty cycle based on Maximum payload.	Effective Time Average Max Power [mW]	FCC 1-g SAR Exclusion calculation [W/kg]
LTE Band 4	20	1.755	316.23	1	0.074	23.40	1.55
LTE Band 13	20	0.787	316.23	1	0.074	23.40	1.04
BTLE	20	2.48	8.71	1	0.05	0.44	0.03

### 6.2. Simultaneous Transmission FCC 1-g SAR Exclusion calculation

Based on the information provided by the manufacturer there is only one mode of possible simultaneous transmission. The mode was evaluated against the FCC 1-g SAR exclusion threshold in the table below.

Transmission Mode	Simultaneous Transmission FCC 1-g SAR Exclusion calculation [W/kg]	FCC 1-g SAR Exclusion Threshold [W/kg]	SAR Exclusion applicable (Yes/No)
LTE B4 and BLE	0.2112	< 0.4	Yes
LTE B13 and BLE	0.1430	< 0.4	Yes

## 7. Revision History

Date	Report Name	Changes to report	Report prepared by
2021-06-01	EMC_MEIGR-011-21001_FCC _SAR_EX	Initial version	Yuchan Lu