

# FCC Test Report

## Report No.: AGC01110211010FE03A

FCC ID	:	2AOKB-A3116L
APPLICATION PURPOSE	:	Class II Permissive Change
PRODUCT DESIGNATION	:	Soundcore Motion +
BRAND NAME	:	soundcore
MODEL NAME	:	A3116, A3116J
APPLICANT	:	Anker Innovations Limited
DATE OF ISSUE	:	Apr. 10, 2025
STANDARD(S)	:	FCC Part 15 Subpart C §15.247
<b>REPORT VERSION</b>	:	V1.0







## **Report Revise Record**

Report Version	Revise Time	Issued Date	Valid Version	Notes	
V1.0	/	Apr. 10, 2025	Valid	Initial Release	

Note: The original test report AGC01110211010FE03 (dated Nov. 09, 2021 and tested from Oct. 20, 2021 to Nov. 09, 2021) was modified on Apr. 10, 2025, including the following changes and additions:

-Updated applicant address and manufacturer address

-Changed battery capacity from 3100mAh to 3050mAh

For the above described change the following tests was considered to be necessary:

Clause	Testing
§15.209	Radiated Spurious Emission



## **Table of Contents**

1. General Information	4
2. Product Information	5
2.1 Product Technical Description	5
2.2 Test Frequency List	5
2.3 Related Submittal(S) / Grant (S)	6
2.4 Test Methodology	6
2.5 Receiver Input Bandwidth	6
2.6 Equally Average Use of Frequencies and Behaviour.	6
2.7 Pseudorandom Frequency Hopping Sequence	7
2.8 Special Accessories	
2.9 Equipment Modifications	8
2.10 Antenna Requirement	
3. Test Environment	9
3.1 Address of The Test Laboratory	9
3.2 Test Facility	9
3.3 Environmental Conditions	
3.4 Measurement Uncertainty	
3.5 List of Equipment Used	11
4.System Test Configuration	
4.1 EUT Configuration	
4.2 EUT Exercise	
4.3 Configuration of Tested System	
4.4 Equipment Used in Tested System	
4.5 Summary of Test Results	
5. Description of Test Modes	14
6. Radiated Spurious Emission	
6.1 Measurement Limit	
6.2 Measurement Procedure	
6.3 Measurement Setup (Block Diagram of Configuration)	
6.4 Measurement Result	19
Appendix I: Photographs of Test Setup	24
Appendix II: Photographs of Test EUT	24



## **1. General Information**

Applicant	Anker Innovations Limited
Address	Unit 56, 8th Floor, Tower 2, Admiralty Centre, 18 Harcourt Road, Hong Kong
Manufacturer	Anker Innovations Limited
Address	Unit 56, 8th Floor, Tower 2, Admiralty Centre, 18 Harcourt Road, Hong Kong
Factory	N/A
Address	N/A
Product Designation	Soundcore Motion +
Brand Name	soundcore
Test Model	A3116
Series Model(s)	A3116J
Difference Description	All the same except for the model name.
Date of receipt of test item	Jan. 15, 2025
Date of Test	Jan. 15, 2025~Feb. 12, 2025
Deviation from Standard	No any deviation from the test method
Condition of Test Sample	Normal
Test Result	Pass
Test Report Form No	AGCER-FCC-BR_EDR-V1

Note: The test results of this report relate only to the tested sample identified in this report.

Bibo zhang Prepared By Bibo Zhang Apr. 10, 2025 (Project Engineer) hin Lin **Reviewed By** Calvin Liu Apr. 10, 2025 (Reviewer) Approved By /mole

Angela Li (Authorized Officer)

Apr. 10, 2025



## 2. Product Information

#### 2.1 Product Technical Description

Frequency Band	2400MHz-2483.5MHz
Operation Frequency Range	2402MHz-2480MHz
Bluetooth Version	V5.0
Modulation Type	BR 🖾 GFSK, EDR 🖾 $\pi$ /4-DQPSK, 🖾 8DPSK
Number of channels	79 Channels
Channel Separation	1 MHz
Maximum Transmitter Power	4.979dBm (Max)
Hardware Version	VA.0
Software Version	V1.3
Antenna Designation	FPC Antenna
Antenna Gain	3.01dBi
Power Supply	DC 7.2V by battery or DC 5V by adapter

#### 2.2 Test Frequency List

Frequency Band	Channel Number	Test Frequency		
	0	2402 MHz		
	1	2403 MHz		
	:	:		
2400~2483.5MHz	39	2441MHz		
	:	:		
	77	2479 MHz		
	78	2480 MHz		
Note: f = 2402 + 1k MHz, k = 0,, 78 ; "f "is the operating frequency (MHz); "k" is the operating channel.				



#### 2.3 Related Submittal(S) / Grant (S)

This submittal(s) (test report) is intended for FCC ID: **2AOKB-A3116L**, filing to comply with Part 2, Part 15 of the Federal Communication Commission rules.

#### 2.4 Test Methodology

The tests were performed according to following standards:

No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 15	Radio Frequency Devices
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
4	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on Digital Transmission Systems, Frequency Hopping Spread Spectrum system, and Hybrid system devices operating under Section 15.247 of the FCC rules

#### 2.5 Receiver Input Bandwidth

The input bandwidth of the receiver is 1.3MHz, in every connection one Bluetooth device is the master and the other one is slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master. Additionally, the type of connection (e.g. single of multi slot packet) is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also, the slave of the connection will use these settings. Repeating of a packet has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means, a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.

#### 2.6 Equally Average Use of Frequencies and Behaviour.

The generation of the hopping sequence in connection mode depends essentially on two input values:

1. LAP/UAP of the master of the connection.

2. Internal master clock.

The LAP (lower address part) are the 24 LSB's of the 48 BD\_ADDRESS. The BD\_ADDRESS is an unambiguous number of every Bluetooth unit. The UAP (upper address part) are the 24MSB's of the 48BD\_ADDRESS

The internal clock of a Bluetooth unit is derived from a free running clock which is never adjusted and is never turned off. For behavior action with other units only offset is used. It has no relation to the time of the day. Its resolution is at least half the RX/TX slot length of 312.5us. The clock has a cycle of about one day(23h30).

In most case it is implemented as 28 bits counter. For the deriving of the hopping sequence the entire. LAP (24 bits),4LSB's(4bits) (Input 1) and the 27MSB's of the clock (Input 2) are used. With this input values different mathematical procedures (permutations, additions, XOR-operations) are performed to generate the Sequence. This will be done at the beginning of every new transmission.

Regarding short transmissions the Bluetooth system has the following behavior:


The first connection between the two devices is established, a hopping sequence was generated. For Transmitting the wanted data the complete hopping sequence was not used. The connection ended. The second connection will be established. A new hopping sequence is generated. Due to the fact the Bluetooth clock has a different value, because the period between the two transmission is longer (and it Cannot be shorter) than the minimum resolution of the clock(312.5us). The hopping sequence will always differ from the first one.



#### 2.7 Pseudorandom Frequency Hopping Sequence

The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: 29 1 = 511 bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of The PRBS Sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:

44	35	78	03	20	76	02	19		21	64 75
								1		
			li							
				1					i i	
				i		<u>-</u>		1	i	

Each frequency used equally on the average by each transmitter.

The system receivers have input bandwidths that match the hopping channel bandwidths of their Corresponding transmitters and shift frequencies in synchronization with the transmitted signals.



#### 2.8 Special Accessories

Not available for this EUT intended for grant.

#### 2.9 Equipment Modifications

Not available for this EUT intended for grant.

#### 2.10 Antenna Requirement

#### Standard Requirement

#### 15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

#### 15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi

#### EUT Antenna:

The non-detachable antenna inside the device cannot be replaced by the user at will. The gain of the antenna is 3.01 dBi.



#### 3. Test Environment

#### 3.1 Address of The Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

#### 3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to follow CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories.)

#### A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to follow ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

#### FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

#### IC-Registration No.: 24842(CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



#### **3.3 Environmental Conditions**

	Normal Conditions
Temperature range (°C)	15 - 35
Relative humidity range	20 % - 75 %
Pressure range (kPa)	86 - 106
Power supply	DC 7.2V by battery or DC 5V by adapter

#### 3.4 Measurement Uncertainty

The reported uncertainty of measurement y  $\pm$ U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 2.9 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.9 \text{ dB}$
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.9 \text{ dB}$
Uncertainty of total RF Power, Conducted	$U_c = \pm 0.8 \text{ dB}$
Uncertainty of RF Power Density, Conducted	$U_c = \pm 2.6 \text{ dB}$
Uncertainty of Spurious Emissions, Conducted	$U_c = \pm 2 \%$
Uncertainty of Occupied Channel Bandwidth	$U_c = \pm 2 \%$
Uncertainty of Dwell Time	$U_c = \pm 2 \%$



#### 3.5 List of Equipment Used

● F	Radiated Spurious Emission							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)	
$\boxtimes$	AGC-EM-E046	EMI Test Receiver	R&S	ESCI	10096	2025-01-14	2026-01-13	
	AGC-EM-E116	EMI Test Receiver	R&S	ESCI	100034	2024-05-24	2025-05-23	
$\boxtimes$	AGC-EM-E061	Spectrum Analyzer	Agilent	N9010A	MY53470504	2024-05-28	2025-05-27	
$\boxtimes$	AGC-EM-E086	Loop Antenna	ZHINAN	ZN30900C	18051	2024-03-05	2026-03-04	
$\boxtimes$	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023-05-11	2025-05-10	
$\boxtimes$	AGC-EM-E029	Broadband Ridged Horn Antenna	ETS	3117	00034609	2024-03-31	2025-03-30	
$\boxtimes$	AGC-EM-E082	Horn Antenna	SCHWARZBECK	BBHA 9170	#768	2023-09-24	2025-09-23	
$\boxtimes$	AGC-EM-E146	Pre-amplifier	ETS	3117-PA	00246148	2024-07-24	2026-07-23	
$\boxtimes$	AGC-EM-A119	2.4GHz Filter	SongYi	N/A	N/A	2024-05-23	2025-05-22	
$\boxtimes$	AGC-EM-A138	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2025-06-08	
	AGC-EM-A139	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2025-06-08	

• Tes	st Software				
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Version Information
	AGC-EM-S003	RE Test System	FARA	EZ-EMC	V.RA-03A
$\square$	AGC-EM-S011	RSE Test System	Tonscend	TS+-Ver2.1(JS36-RSE)	4.0.0.0



## **4.System Test Configuration**

#### 4.1 EUT Configuration


The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

#### 4.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

#### 4.3 Configuration of Tested System

Radiated Emission Configure:



#### 4.4 Equipment Used in Tested System

The following peripheral devices and interface cables were connected during the measurement:

☐ Test Accessories Come From The Laboratory

No.	Equipment	Manufacturer	Model No.	Specification Information	Cable
1	Android Phone	LOGICOM	LUNAR		
2	Adapter	HUAWEI	HW-200440C00		

Test Accessories Come From The Manufacturer

No.	Equipment	Manufacturer	Model No.	Specification Information	Cable
1				-	



#### 4.5 Summary of Test Results

ltem	FCC Rules	Description of Test	Result
5	§15.209	Radiated Spurious Emission	Pass



## 5. Description of Test Modes

	Summary table of Test Cases
	Data Rate / Modulation
Test Item	Bluetooth – BR_EDR (GFSK/π /4-DQPSK/8DPSK)
Radiated & Conducted Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps (Battery powered or AC/DC adapter) Mode 2: Bluetooth Tx CH39_2441 MHz_1Mbps (Battery powered or AC/DC adapter) Mode 3: Bluetooth Tx CH78_2480 MHz_1Mbps (Battery powered or AC/DC adapter) Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps (Battery powered or AC/DC adapter) Mode 5: Bluetooth Tx CH39_2441 MHz_2Mbps (Battery powered or AC/DC adapter) Mode 6: Bluetooth Tx CH39_2441 MHz_2Mbps (Battery powered or AC/DC adapter) Mode 6: Bluetooth Tx CH78_2480 MHz_2Mbps (Battery powered or AC/DC adapter) Mode 7: Bluetooth Tx CH78_2480 MHz_3Mbps (Battery powered or AC/DC adapter) Mode 8: Bluetooth Tx CH39_2441 MHz_3Mbps (Battery powered or AC/DC adapter) Mode 8: Bluetooth Tx CH39_2441 MHz_3Mbps (Battery powered or AC/DC adapter) Mode 9: Bluetooth Tx CH78_2480 MHz_3Mbps (Battery powered or AC/DC adapter) Mode 9: Bluetooth Tx CH78_2480 MHz_3Mbps (Battery powered or AC/DC adapter) Mode 10: Bluetooth Tx Hopping-1Mbps (Battery powered or AC/DC adapter) Mode11: Bluetooth Tx Hopping-3Mbps (Battery powered or AC/DC adapter) Mode12: Bluetooth Tx Hopping-3Mbps (Battery powered or AC/DC adapter)
AC Conducted Emission	Mode 1: Bluetooth Link + Battery + USB Cable (Charging from AC Adapter)
<ol> <li>The battery is full-cha</li> <li>For Radiated Emission</li> <li>For Conducted Test r</li> <li>For Conducted Test r</li> </ol>	on, 3axis were chosen for testing for each applicable mode. method, a temporary antenna connector is provided by the manufacture. Software Setting Diagram etrest3 - LE Tester Interface Mode Commands FREQ MS Power target 4 Close



## 6. Radiated Spurious Emission

#### 6.1 Measurement Limit

#### 15.209 Limit in the below table has to be followed

Frequencies	Field Strength	Measurement Distance
(MHz)	(microvolts/meter)	(meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

#### 6.2 Measurement Procedure

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.



- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.

Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz 1MHz/3MHz for Peak, 1MHz/3MHz for Average

The following table is the setting of spectrum analyzer and receiver.

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP



#### Quasi-Peak Measurements below 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. Span was set greater than 1MHz
- 3. RBW = as shown in the table above
- 4. Detector = CISPR quasi-peak
- 5. Sweep time = auto couple
- 6. Trace was allowed to stabilize

#### Peak Measurements above 1GHz


- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW = 3MHz
- 4. Detector = peak
- 5. Sweep time = auto couple
- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize

#### • Average Measurements above 1GHz


- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW  $\geq$  [3 × RBW]
- 4. Detector = Power averaging (rms)
- 5. Averaging type = power (i.e., rms)
- 6. Sweep time = auto
- 7. Perform a trace average of at least 100 traces.
- 8. The applicable correction factor is [10\*log (1 / D)], where D is the duty cycle. The factor had been edited in the "Input Correction" of the Spectrum Analyzer.




#### 6.3 Measurement Setup (Block Diagram of Configuration)



Radiated Emission Test Setup 30MHz-1000MHz



#### Radiated Emission Test Setup Above 1000MHz





#### 6.4 Measurement Result

#### Radiated Emission Below 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.

			Radia	ated Emiss	ion Test Res	ults at 30MHz	z-1GHz		
EUT Na	me	Sou	ndcore Motior	ı +		Model Na	me	A3116	
Tempera	ature	19.8	BC			Relative I	Humidity	47.2%	
Pressur	е	960	hPa			Test Volta	age	DC 5V by	adapter
Test Mo	de	Мос	le 8			Antenna	Polarity	Horizontal	
	72.0	dBu∀/m	I						
								Limit: — Margin: —	
								f	
						J		<b>_</b>	
							_		
	32			1	2 X	MM .	Mr. Marrier	are of product	
			wenter bei eine	in Maker	Marker Alligher	in the second	** ·		
	aller	www.www	ernentertertertertertertertertertertertertert	NWUNAP	"NHT				
	-8 30.00	)0 4	0 50 60 70	80	(MHz)	300	400 500 60	0 700 1000.0	00
Final Da							1	1	
NO.	Freq. [MHz]		Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	110.95	71	30.02	16.31	43.50	13.48	100	170	Horizontal
2	180.01	65	28.70	12.20	43.50	14.8	100	180	Horizontal
3	261.05	83	31.39	14.81	46.00	14.61	100	90	Horizontal
4	304.60	99	34.67	16.50	46.00	11.33	100	230	Horizontal
5	449.55	58	31.20	24.77	46.00	14.8	100	100	Horizontal
6	903.30	94	37.73	31.34	46.00	8.27	100	120	Horizontal



		Radia	ted Emiss	ion Test Res	ults at 30MH	z-1GHz		
EUT Name	Soundco	re Motion	+		Model Na	ame	A3116	
Temperature	<b>19.8</b> ℃				Relative	Humidity	47.2%	
Pressure	960hPa				Test Volt	age	DC 5V by	adapter
Test Mode	Mode 8				Antenna	Polarity	Vertical	
72.0	dBu∀/m							
							Limit: — Margin: —	
32 -8 30.0 Final Data List		2 ////////////////////////////////////	80	(MHz)	300	400 500 60		00
NO Freq		Level	Factor	Limit	Margin	Height	Angle	Polarity
1 42.45		3µV/m] 28.92	[dB]	[dBµV/m] 40.00	[dB] 11.08	[cm]	[°] 160	Vertical
		28.92 27.37	16.92 17.04	40.00	12.63	100		Vertical
						100	170	
3 107.88		34.08	15.58	43.50	9.42	100	90	Vertical
4 183.20		33.93	18.40	43.50	9.57	100	220	Vertical
5 296.18		32.30	18.80	46.00	13.7	100	160	Vertical
6 938.83	326 3	36.73	30.84	46.00	9.27	100	140	Vertical

#### **RESULT: Pass**

**Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. All test modes had been pre-tested. The mode 8 is the worst case and recorded in the report.



EUT Name		Soundcore	Motion +		Mode	I Name	A3116	
Temperature		<b>19.8</b> ℃			Relat	ive Humidity	47.2%	
Pressure		960hPa			Test \	Voltage	DC 5V by	adapter
Test Mode		Mode 7			Anter	nna Polarity	Horizonta	
							·	
Frequency	Met	ter Reading	Factor	Emissio	n Level	Limits	Margin	Value Type
(MHz)		(dBµV)	(dB)	(dBµ\	//m)	(dBµV/m)	(dB)	value Type
4804.000		46.41	0.08	46.4	49	74	-27.51	peak
4804.000		37.01	0.08	37.0	)9	54	-16.91	AVG
7206.000		41.76	2.21	43.9	97	74	-30.03	peak
7206.000		32.49	2.21	34.7	70	54	-19.30	AVG
Remark:								
Factor = Anter	nna Fa	actor + Cabl	e Loss – Pre-	amplifier.				
EUT Name		Soundcore	Motion +		Mode	I Name	A3116	
Temperature		<b>19.8</b> ℃			Relat	ive Humidity	47.2%	
Pressure		960hPa			Test \	Voltage	DC 5V by	adapter
Test Mode		Mode 7			Anter	nna Polarity	Vertical	
Frequency	Met	er Reading	Factor	Emissio		Limits	Margin	Value Type
(MHz)		(dBµV)	(dB)	(dBµ\	,	(dBµV/m)	(dB)	
4804.000		46.27	0.08	46.3		74	-27.65	peak
4804.000		38.00	0.08	38.0		54	-15.92	AVG
7206.000		41.49	2.21	43.7		74	-30.30	peak
7206.000		33.00	2.21	35.2	21	54	-18.79	AVG
	<u> </u>							
Develo								ļ
Remark:								
Factor = Anter	ina Fa	actor + Cabl	e Loss – Pre-	amplitier.				

#### **Radiated Emissions Test Results Above 1GHz**

#### **RESULT: Pass**



#### **Radiated Emissions Test Results for Above 1GHz**

EUT Name	Soun	dcore Motior	า +		Mode	IName	A3116		
<b>Temperature</b>	19.8°	С			Relati	ive Humidity	47.2%	47.2%	
Pressure	960h	Pa			Test \	/oltage	DC 5V by adapter		
Test Mode	Mode	8	Antenna Polarity		Horizonta	Horizontal			
Frequency	Meter Read	ling Fa	actor	Emissio	n Level	Limits	Margin	Value Type	
(MHz)	(dBµV)	(	dB)	(dBµ\	//m)	(dBµV/m)	(dB)	value Type	
4882.000	46.56	0	.08	46.6	64	74	-27.36	peak	
4882.000	37.25	0	.08	37.3	33	54	-16.67	AVG	
7323.000	41.17	2	2.21	43.3	38	74	-30.62	peak	
7323.000	32.73	2	2.21	34.9	94	54	-19.06	AVG	
Remark:									
	nna Factor +	Cable Loss	– Pre-a	molifier					
Factor = Anter	nna Factor +	Cable Loss	– Pre-a	amplifier.					
		Cable Loss		amplifier.	Mode	I Name	A3116		
Factor = Anter		dcore Motior		amplifier.		I Name ive Humidity	A3116 47.2%		
Factor = Anter	Soun	dcore Motior		amplifier.	Relati			adapter	
Factor = Anter EUT Name Femperature	Soun 19.8°	dcore Motior C Pa		amplifier.	Relati	ive Humidity	47.2%	adapter	
Factor = Anter EUT Name Temperature Pressure Fest Mode	Soun 19.8° 960h Mode	dcore Motior C Pa 98	ו +		Relati Test \ Anter	ive Humidity /oltage nna Polarity	47.2% DC 5V by Vertical	adapter	
Factor = Anter EUT Name Femperature Pressure Fest Mode	Soun 19.8° 960h Mode Meter Read	dcore Motior C Pa 98 ing Fa	n +	Emission	Relati Test V Anter	ive Humidity /oltage nna Polarity Limits	47.2% DC 5V by Vertical Margin	adapter Value Type	
Factor = Anter EUT Name Femperature Pressure Fest Mode Frequency (MHz)	Soun 19.8° 960h Mode Meter Reac (dBµV)	dcore Motior C Pa e 8 ing Fa	n + Ictor dB)	Emissior (dBµV	Relati Test V Anter	ive Humidity /oltage nna Polarity Limits (dBµV/m)	47.2% DC 5V by Vertical Margin (dB)	- Value Type	
Factor = Anter EUT Name Femperature Pressure Fest Mode Frequency (MHz) 4882.000	Soun 19.8 <sup>°</sup> 960h Mode Meter Reac (dBμV) 46.85	dcore Motior C Pa e 8 ing Fa (( 0	n + Inctor dB) .08	Emissior (dBµV 46.9	Relati Test V Anter	Limits (dBµV/m) 74	47.2% DC 5V by Vertical Margin (dB) -27.07	Value Type	
Factor = Anter	Sourt           19.8°           960h           Mode           Meter Read           (dBμV)           46.85           37.49	dcore Motior C Pa e 8 ing Fa (( 0 0 0	n + actor dB) .08	Emissior (dBµV 46.9 37.5	Relati Test V Anter	Limits (dBµV/m) 74 54	47.2% DC 5V by Vertical Margin (dB) -27.07 -16.43	- Value Type peak AVG	
Factor = Anter EUT Name Femperature Pressure Fest Mode Frequency (MHz) 4882.000 4882.000 7323.000	Soun           19.8°           960h           Mode           (dBμV)           46.85           37.49           41.85	dcore Motior C Pa e 8 ing Fa (( 0 0 0 2	n + actor dB) .08 .08 .21	Emissior (dBµV 46.9 37.5 44.0	Relati Test V Anter	Limits (dBµV/m) 74 54 74	47.2% DC 5V by Vertical Margin (dB) -27.07 -16.43 -29.94	Value Type peak AVG peak	
Factor = Anter	Sourt           19.8°           960h           Mode           Meter Read           (dBμV)           46.85           37.49	dcore Motior C Pa e 8 ing Fa (( 0 0 0 2	n + actor dB) .08	Emissior (dBµV 46.9 37.5	Relati Test V Anter	Limits (dBµV/m) 74 54	47.2% DC 5V by Vertical Margin (dB) -27.07 -16.43	- Value Type peak AVG	
Factor = Anter EUT Name Femperature Pressure Fest Mode Frequency (MHz) 4882.000 4882.000 7323.000	Soun           19.8°           960h           Mode           (dBμV)           46.85           37.49           41.85	dcore Motior C Pa e 8 ing Fa (( 0 0 0 2	n + actor dB) .08 .08 .21	Emissior (dBµV 46.9 37.5 44.0	Relati Test V Anter	Limits (dBµV/m) 74 54 74	47.2% DC 5V by Vertical Margin (dB) -27.07 -16.43 -29.94	Value Type peak AVG peak	
Factor = Anter EUT Name Femperature Pressure Fest Mode Frequency (MHz) 4882.000 4882.000 7323.000	Soun           19.8°           960h           Mode           (dBμV)           46.85           37.49           41.85	dcore Motior C Pa e 8 ing Fa (( 0 0 0 2	n + actor dB) .08 .08 .21	Emissior (dBµV 46.9 37.5 44.0	Relati Test V Anter	Limits (dBµV/m) 74 54 74	47.2% DC 5V by Vertical Margin (dB) -27.07 -16.43 -29.94	Value Type peak AVG peak	

#### **RESULT: Pass**



#### **Radiated Emissions Test Results for Above 1GHz**

UT Name		Soundcore	Motion +		Model	Name	A3116										
Temperature Pressure Test Mode		19.8℃ 960hPa Mode 9			Relative Humidity Test Voltage Antenna Polarity		47.2% DC 5V by adapter Horizontal										
									Frequency	Me	ter Reading	Factor	Emissio	on Level	Limits	Margin	Value Type
(MHz)		(dBµV)	(dB)	(dBµ	ıV/m)	(dBµV/m)	(dB)										
4960.000		46.40	0.08	46.48		74	-27.52	peak									
4960.000		37.45	0.08	37.	.53	54	-16.47	AVG									
7440.000		41.28	2.21	43.	.49	74	-30.51	peak									
7440.000		32.84	2.21	35.05		54	-18.95	AVG									
Remark:																	
Factor = Anter	nna Fa			amplifier.													
	nna Fa	actor + Cable Soundcore		amplifier.	Model	Name	A3116										
Factor = Anter	nna Fa			amplifier.		Name /e Humidity	A3116 47.2%										
Factor = Anter	nna Fa	Soundcore		amplifier.		ve Humidity		adapter									
Factor = Anter UT Name emperature	nna Fa	Soundcore 19.8℃		amplifier.	Relativ Test Ve	ve Humidity	47.2%	adapter									
Factor = Anter UT Name emperature Pressure est Mode		Soundcore 19.8℃ 960hPa Mode 9	Motion +		Relativ Test Vo Anteni	ve Humidity oltage na Polarity	47.2% DC 5V by a Vertical										
Factor = Anter		Soundcore 19.8℃ 960hPa Mode 9 ter Reading	Motion + Factor	Emissio	Relativ Test Ve Anteni	ve Humidity oltage na Polarity Limits	47.2% DC 5V by a Vertical	adapter Value Type									
Factor = Anter UT Name emperature Pressure fest Mode Frequency (MHz)		Soundcore 19.8℃ 960hPa Mode 9	Motion +	Emissic (dBµ	Relativ Test Vo Anteni	ve Humidity oltage na Polarity	47.2% DC 5V by a Vertical Margin (dB)										
Factor = Anter UT Name emperature Pressure fest Mode Frequency (MHz) 4960.000		Soundcore 19.8℃ 960hPa Mode 9 ter Reading (dBµV) 46.62	Motion + Factor (dB) 0.08	Emissic (dBµ	Relativ Test Vo Anteni on Level	ve Humidity oltage na Polarity Limits (dBµV/m)	47.2% DC 5V by a Vertical Margin (dB) -27.30	Value Type									
Factor = Anter UT Name emperature ressure est Mode Frequency (MHz) 4960.000 4960.000		Soundcore 19.8℃ 960hPa Mode 9 ter Reading (dBµV) 46.62 37.99	Motion + Factor (dB) 0.08 0.08	Emissic (dBµ 46. 38.	Relativ Test Vo Anteni Dn Level IV/m) .70 .07	ve Humidity oltage na Polarity Limits (dBμV/m) 74	47.2% DC 5V by a Vertical Margin (dB) -27.30 -15.93	Value Type peak AVG									
Factor = Anter UT Name emperature Pressure fest Mode Frequency (MHz) 4960.000		Soundcore 19.8℃ 960hPa Mode 9 ter Reading (dBµV) 46.62	Motion + Factor (dB) 0.08	Emissic (dBµ 46 38 43	Relativ Test Vo Anteni Dn Level IV/m) .70 .07	/e Humidity oltage na Polarity Limits (dBµV/m) 74 54	47.2% DC 5V by a Vertical Margin (dB) -27.30	- Value Type peak									
Factor = Anter UT Name emperature Pressure est Mode Frequency (MHz) 4960.000 4960.000 7440.000		Soundcore 19.8℃ 960hPa Mode 9 ter Reading (dBµV) 46.62 37.99 41.59	Motion + Factor (dB) 0.08 0.08 2.21	Emissic (dBµ 46 38 43	Relativ Test Vo Anteni Dn Level V/m) .70 .07 .80	ve Humidity oltage na Polarity Limits (dBµV/m) 74 54 74	47.2% DC 5V by a Vertical Margin (dB) -27.30 -15.93 -30.20	- Value Type peak AVG peak									
Factor = Anter UT Name emperature Pressure est Mode Frequency (MHz) 4960.000 4960.000 7440.000		Soundcore 19.8℃ 960hPa Mode 9 ter Reading (dBµV) 46.62 37.99 41.59	Motion + Factor (dB) 0.08 0.08 2.21	Emissic (dBµ 46 38 43	Relativ Test Vo Anteni Dn Level V/m) .70 .07 .80	ve Humidity oltage na Polarity Limits (dBµV/m) 74 54 74	47.2% DC 5V by a Vertical Margin (dB) -27.30 -15.93 -30.20	- Value Type peak AVG peak									

#### RESULT: Pass

Note:

- 1. The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.
- 2. Factor = Antenna Factor + Cable loss Pre-amplifier gain, Margin = Emission Level-Limit.
- 3. The "Factor" value can be calculated automatically by software of measurement system.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com



Report No.: AGC01110211010FE03A Page 24 of 25

## Appendix I: Photographs of Test Setup

Refer to the Report No.: AGC01110211010AP02A

## Appendix II: Photographs of Test EUT

Refer to the Report No.: AGC01110211010AP03A



## Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").

2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.

3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.

4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.

5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.

 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
 7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.

8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.

9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.

-----End of Report-----