



RF Exposure Evaluation Declaration

FCC ID: 2ABLK-8X4G-1V2

APPLICANT: Calix Inc.

Application Type: Certification

Product: WIFI dual band 4 GE LAN GPON HGU, BROADBAND CPE

Model No.: 844G-1, 854G-1, 844GE-1, C844G

Trademark: Calix

FCC Classification: Digital Transmission System (DTS)
Unlicensed National Information Infrastructure (UNII)

Reviewed By : Robin Wu

(Robin Wu)

Approved By : Marlin Chen

(Marlin Chen)



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date
1502RSU00404	Rev. 01	Initial report	04-01-2015
1502RSU00404	Rev. 02	Added the model number "844GE-1"	11-24-2015
1502RSU00404	Rev. 03	Add the UK adapter	03-29-2016
1502RSU00404	Rev. 04	Add the product name and model number	04-24-2016

1. PRODUCT INFORMATION

1.1. Equipment Description

Product Name	WIFI dual band 4 GE LAN GPON HGU, BROADBAND CPE
Model No.	844G-1, 854G-1, 844GE-1, C844G
Frequency Range	<u>For 2.4GHz Band:</u> 802.11b/g/n-HT20: 2412 ~ 2462MHz 802.11n-HT40: 2422 ~ 2452MHz <u>For 5GHz Band:</u> For 802.11a/n-HT20: 5180~5320MHz, 5500~5700MHz, 5745~5825MHz For 802.11ac-VHT20: 5180~5320MHz, 5500~5720MHz, 5745~5825MHz For 802.11n-HT40: 5190~5310MHz, 5510~5670MHz, 5755~5795MHz For 802.11ac-VHT40: 5190~5310MHz, 5510~5710MHz, 5755~5795MHz For 802.11ac-VHT80: 5210MHz, 5290MHz, 5530MHz, 5610MHz, 5690MHz, 5775MHz
Type of Modulation	802.11b: DSSS 802.11g/a/n/ac: OFDM
Maximum Average Output Power	<u>For 2.4GHz Band:</u> 802.11b: 24.02dBm 802.11g: 23.74dBm 802.11n-HT20: 26.30dBm 802.11n-HT40: 23.46dBm <u>For 5GHz Band:</u> 802.11a: 27.19dBm 802.11n-HT20: 27.10dBm 802.11n-HT40: 27.15dBm 802.11ac-VHT20: 27.26dBm 802.11ac-VHT40: 27.20dBm 802.11ac-VHT80: 25.19dBm

Components	
UPS #1	M/N: D13CU12V-NA3-G Input: 100-240V ~ 50/60Hz, 1.0A OUTPUT: 12Vdc, 30W
UPS #2	M/N: D13CU12V-NA3-G Input: 100-240V ~ 50/60Hz, 1.0A OUTPUT: 12Vdc, 36W
Adapter #1	M/N: AMS157-1202500FU Input: 100-240V ~ 50/60Hz, 1.0A OUTPUT: 12Vdc, 2.5A
Adapter #2	M/N: AMS157-1202500FB Input: 100-120V ~ 50/60Hz, 1.0A OUTPUT: 12Vdc, 2.5A

Note 1: There is different laser module between models “844G-1” & “844GE-1”.

Note 2: For this model “844GE-1” has been assessed the worst case mode in this report, and showed in the Annex 1 of “DTS Report & NII Report”.

Note 3: There is different DDR between models “844G-1” & “C844G”, for this model “C844G” has been assessed the worst case mode in this report, and showed in the Annex 2 of “DTS Report & NII Report”.

1.2. Antenna Description

Antenna Type	Frequency Band (GHz)	T _x Paths	Directional Gain (dBi)
PCB Antenna	2.4	2	1.90

Antenna Type	Frequency Band (GHz)	T _x Paths	Directional Gain (dBi)	
			Beam Forming	CDD
PCB Antenna	5.2	4	8.04	8.04
	5.3	4	7.78	7.78
	5.6	4	8.38	8.38
	5.8	4	8.70	8.70

Note:

- Transmit at 2.4GHz support two antennas, and support four antennas at 5GHz transmit. There are different antenna gains between each antenna.
- The EUT working on Beam Forming mode, and the Beam Forming support 802.11n/ac, not include 802.11a, and 802.11a working on CDD mode.
- Correlated signals include, but are not limited to, signals transmitted in any of the following modes:
 - Any transmit Beam Forming mode, whether fixed or adaptive (e.g., phased array modes, closed loop MIMO modes, Transmitter Adaptive Antenna modes, Maximum Ratio Transmission (MRT) modes, and Statistical Eigen Beam Forming (EBF) modes).
- Unequal antenna gains, with equal transmit powers. For antenna gains given by $G_1, G_2, \dots, G_N$ dBi
 - transmit signals are correlated, then
 - Directional gain = $10 \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N_{ANT}]$ dBi [Note the “20”s in the denominator of each exponent and the square of the sum of terms; the object is to combine the signal levels coherently.]

2. RF Exposure Evaluation

2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	f/1500	6
1500-100,000	--	--	1	30

f= Frequency in MHz

Calculation Formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.2. Test Result of RF Exposure Evaluation

Product	WIFI dual band 4 GE LAN GPON HGU, BROADBAND CPE
Test Item	RF Exposure Evaluation

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.90dBi for 2.4GHz, 8.04dBi for 5.2GHz, 7.78dBi for 5.3GHz, 8.38dBi for 5.6GHz and 8.70dBi for 5.80GHz in logarithm scale.

For 2.4GHz ISM Band:

Test Mode	Frequency Band (MHz)	Maximum Average Output Power (dBm)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)
802.11b	2412 ~ 2462	24.02	0.0778	1
802.11g	2412 ~ 2462	23.74	0.0729	1
802.11n-HT20	2412 ~ 2462	26.30	0.1314	1
802.11n-HT40	2422 ~ 2452	23.46	0.0683	1

For 5GHz UNII Band:

Test Mode	Frequency Band (MHz)	Maximum Average Output Power (dBm)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)
802.11a	5180 ~ 5240	24.27	0.3386	1
	5260 ~ 5320	20.65	0.1386	1
	5500 ~ 5700	20.01	0.1373	1
	5725 ~ 5825	27.19	0.7722	1
802.11n-HT20	5180 ~ 5240	24.33	0.3433	1
	5260 ~ 5320	20.50	0.1339	1
	5500 ~ 5700	20.47	0.1527	1
	5725 ~ 5825	27.10	0.7564	1
802.11n-HT40	5190 ~ 5230	24.67	0.3713	1
	5270 ~ 5310	21.16	0.1559	1
	5510 ~ 5670	21.10	0.1765	1
	5755 ~ 5795	27.15	0.7651	1

802.11ac-VHT20	5180 ~ 5240	24.31	0.3418	1
	5260 ~ 5320	20.79	0.1431	1
	5500 ~ 5720	21.10	0.1765	1
	5725 ~ 5825	27.26	0.7847	1
802.11ac-VHT40	5190 ~ 5230	24.58	0.3637	1
	5270 ~ 5310	20.72	0.1408	1
	5510 ~ 5710	21.26	0.1831	1
	5755 ~ 5795	27.20	0.7740	1
802.11ac-VHT80	5210	16.77	0.0602	1
	5290	18.12	0.0774	1
	5530 ~ 5690	20.92	0.1693	1
	5775	25.19	0.4872	1

CONCULISON:

Both of the WLAN 2.4GHz Band and WLAN 5GHz Band can transmit simultaneously. Therefore, the Max Power Density at R (20 cm) = $0.1314\text{mW}/\text{cm}^2 + 0.7847\text{mW}/\text{cm}^2 = 0.9161\text{mW}/\text{cm}^2 < 1\text{mW}/\text{cm}^2$.

So the EUT complies with the requirement.

The End
