



**In accordance with the requirements of  
FCC 47 CFR Part 2(2.1093), ANSI/IEEE C95.1-1992 and  
IEEE Std 1528-2013**

## **FCC SAR EVALUATION REPORT**

**Product Name :** Fingerprint smart terminal

**Trademark :** The Aratek logo, which consists of a stylized 'A' inside a circle followed by the word 'Aratek' in a bold, sans-serif font.

**Model Name :** BM5510

**Serial Model :** BM5500, BM5520, BM5530,  
VIU500-ATK100

**Report No. :** NTEK-2015NT1126170HF-01

**FCC ID :** 2AGUJBM5510

**Prepared for**

ShenZhen Aratek Biometrics Technology Co.,Ltd  
2F,T2-A Building,ShenZhen Software Park,South Area,Hi-Tech Park,  
ShenZhen,Guangdong,China

**Prepared by**

Shenzhen NTEK Testing Technology Co., Ltd.  
1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street  
Bao'an District, Shenzhen P.R. China  
Tel.: +86-0755-61156588 Fax.: +86-0755-61156599  
Website: [www.ntek.org.cn](http://www.ntek.org.cn)


## TEST RESULT CERTIFICATION

**Applicant's name**..... ShenZhen Aratek Biometrics Technology Co.,Ltd  
**Address** ..... 2F,T2-A Building,ShenZhen Software Park,South Area,Hi-Tech  
 Park,ShenZhen,Guangdong,China

**Manufacture's Name** .... ShenZhen Aratek Biometrics Technology Co.,Ltd  
**Address** ..... 2F,T2-A Building,ShenZhen Software Park,South Area,Hi-Tech  
 Park,ShenZhen,Guangdong,China

### Product description

**Product name**..... Fingerprint smart terminal

**Trademark** ..... 

**Model and/or type** ..... BM5510  
**reference** .....

**Serial Model** ..... BM5500, BM5520, BM5530, VIU500-ATK100

..... FCC 47 CFR Part 2(2.1093)  
 ANSI/IEEE C95.1-1992  
**Standards**..... IEEE Std 1528-2013  
 Published RF exposure KDB procedures

This device described above has been tested by Shenzhen NTEK. In accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 and KDB 865664 D01. Testing has shown that this device is capable of compliance with localized specific absorption rate (SAR) specified in FCC 47 CFR Part 2(2.1093) and ANSI/IEEE C95.1-1992. The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.


This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK, this document may be altered or revised by Shenzhen NTEK, personal only, and shall be noted in the revision of the document.


### Date of Test

**Date (s) of performance of tests**..... Nov. 30, 2015 ~ Jun. 06, 2016

**Date of Issue** ..... Jun. 15, 2016

**Test Result** ..... **Pass**

**Prepared By** :   
**(Test Engineer)** : \_\_\_\_\_  
 (Jerry)

**Approved By** :   
**(Lab Manager)** : \_\_\_\_\_  
 (Sam Chen)

### ※ ※ Revision History ※ ※

REV.	DESCRIPTION	ISSUED DATE	REMARK
Rev.1.0	Initial Test Report Release	Dec. 03, 2015	Cheng Jiawen
Rev.1.1	Added 3G test data	Jun. 15, 2016	Jerry

## TABLE OF CONTENTS

1. General Information .....	6
1.1. RF exposure limits.....	6
1.2. Statement of Compliance .....	7
1.3. EUT Description .....	8
1.4. Test specification(s) .....	9
1.5. Ambient Condition.....	9
2. SAR Measurement System .....	10
2.1. SATIMO SAR Measurement Set-up Diagram .....	10
2.2. Robot .....	11
2.3. E-Field Probe.....	12
2.3.1. E-Field Probe Calibration .....	12
2.4. SAM phantoms .....	13
2.4.1. Technical Data .....	13
2.5. Device Holder .....	15
2.6. Test Equipment List .....	16
3. SAR Measurement Procedures .....	18
3.1. Power Reference .....	18
3.2. Area scan & Zoom scan.....	18
3.3. Description of interpolation/extrapolation scheme .....	20
3.4. Volumetric Scan .....	20
3.5. Power Drift .....	20
4. System Verification Procedure .....	21
4.1. Tissue Verification .....	21
4.1.1. Tissue Dielectric Parameter Check Results .....	21
4.2. System Verification Procedure .....	23
4.2.1. System Verification Results.....	24
5. SAR Measurement variability and uncertainty .....	25
5.1. SAR measurement variability.....	25
5.2. SAR measurement uncertainty .....	25
6. RF Exposure Positions.....	26
6.1. Ear and handset reference point .....	26
6.2. Definition of the cheek position .....	26
6.3. Definition of the tilt position .....	28
6.4. Body Worn Accessory .....	28
6.5. Wireless Router Devices .....	29
7. RF Output Power .....	30
7.1. Maximum Tune-up Limit.....	30
7.2. GSM Conducted Power .....	31
7.3. UMTS Conducted Power .....	32

7.4. WiFi & BT Output Power.....	35
7.4.1. Output Power Results Of WiFi .....	35
7.4.2. Output Power Results Of BT.....	35
8. Antenna Location.....	36
9. Stand-alone SAR test exclusion.....	37
10. SAR Measurement Results.....	38
10.1. SAR measurement results .....	38
10.1.1. SAR measurement Result of GSM850.....	39
10.1.2. SAR measurement Result of GSM1900.....	40
10.1.3. SAR measurement Result of UMTS Band V.....	41
10.1.4. SAR measurement Result of UMTS Band II.....	42
10.1.5. SAR measurement Result of WiFi 2.4G.....	43
10.2. Simultaneous Transmission Possibilities .....	44
10.3. SAR Summation Scenario.....	45
11. Appendix A. Photo documentation .....	49
12. Appendix B. System Check Plots.....	55
13. Appendix C. SAR Measurement Plots .....	66
14. Appendix D. Calibration Certificate .....	77

## 1. General Information

### 1.1. RF exposure limits

(A).Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

(B).Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

NOTE: **Whole-Body SAR** is averaged over the entire body, **partial-body SAR** is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. **SAR for hands, wrists, feet and ankles** is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

#### Occupational/Controlled Environments:

Are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

#### General Population/Uncontrolled Environments:

Are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

NOTE  
HEAD AND TRUNK LIMIT  
1.6 W/kg  
APPLIED TO THIS EUT


## 1.2. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for BM5510 are as follows.

Band	Max Reported SAR(W/kg)		
	1-g Head	1-g Body (Separation distance of 0mm)	Max. SAR Summation
GSM 850	0.737	1.197	1.517
GSM 1900	1.079	1.190	
UMTS Band V	0.359	0.996	
UMTS Band II	0.748	0.930	
WiFi 2.4G	0.338	0.327	

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR Part 2(2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 & KDB 865664 D01.

### 1.3. EUT Description

Device Information			
Product Name	Fingerprint smart terminal		
Trade Name			
Model Name	BM5510		
Serial Model	BM5500, BM5520, BM5530, VIU500-ATK100		
FCC ID	2AGUJ-BM5510		
Device Phase	Identical Prototype		
Exposure Category	General population / Uncontrolled environment		
Device Operating Configurations			
Supporting Mode(s)	GSM 850/1900, UMTS Band V/II, WiFi 2.4G, BT		
Test Modulation	GSM(GMSK/8PSK), UMTS(QPSK), WiFi(DSSS/OFDM)		
Device Class	B		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	GSM 850	824-849	869-894
	GSM 1900	1850-1910	1930-1990
	UMTS Band V	824-849	869-894
	UMTS Band II	1850-1910	1930-1990
	WiFi 2.4G	2412-2462	
	BT	2402-2480	
GPRS Multislot Class(12)	Max Number of Timeslots in Uplink		4
	Max Number of Timeslots in Downlink		4
	Max Total Timeslot		5
EDGE Multislot Class(12)	Max Number of Timeslots in Uplink		4
	Max Number of Timeslots in Downlink		4
	Max Total Timeslot		5
HSDPA UE Category	14		
HSUPA UE Category	6		
Power Class	4, tested with power level 5(GSM 850)		
	1, tested with power level 0(GSM 1900)		
	3, tested with power control “all 1”(UMTS Band V)		
	3, tested with power control “all 1”(UMTS Band II)		
Test Channels (low-mid-high)	128-189-251(GSM 850)		
	512-661-810(GSM 1900)		
	4132-4182-4233(UMTS Band V)		
	9262-9400-9538(UMTS Band II)		
	802.11 b/g/n:1-3-6-9-11(WiFi 2.4G)		



#### 1.4. Test specification(s)

FCC 47 CFR Part 2(2.1093)
ANSI/IEEE C95.1-1992
IEEE Std 1528-2013
KDB 865664 D01 SAR measurement 100 MHz to 6 GHz
KDB 865664 D02 RF Exposure Reporting
KDB 447498 D01 General RF Exposure Guidance
KDB 248227 D01 802.11 Wi-Fi SAR
KDB 941225 D01 3G SAR Procedures
KDB 941225 D06 Hotspot Mode
KDB 648474 D04 Handset SAR

#### 1.5. Ambient Condition

Ambient temperature	20°C – 24°C
Relative Humidity	30% – 70%

The Keithley multimeter reads the voltage of each sensor and send these three values to the PC. The corresponding E field value is calculated using the probe calibration factors, which are stored in the working directory. This evaluation includes linearization of the diode characteristics. The field calculation is done separately for each sensor. Each component of the E field is displayed on the "Dipole Area Scan Interface" and the total E field is displayed on the "3D Interface"

## 2.2. Robot

The SATIMO SAR system uses the high precision robots from KUKA. For the 6-axis controller system, the robot controller version (KUKA) from KUKA is used. The KUKA robot series have many features that are important for our application:



- High precision (repeatability  $\pm 0.03$  mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)

### 2.3. E-Field Probe

This E-field detection probe is composed of three orthogonal dipoles linked to special Schottky diodes with low detection thresholds. The probe allows the measurement of electric fields in liquids such as the one defined in the IEEE and CENELEC standards.

For the measurements the Specific Dosimetric E-Field Probe SN 34/15 EPGO 267 with following specifications is used



- Dynamic range: 0.01-100 W/kg
  - Tip Diameter : 2.5 mm
  - Distance between probe tip and sensor center: 1 mm
  - Distance between sensor center and the inner phantom surface: 4 mm (repeatability better than  $\pm 1$  mm).
  - Probe linearity:  $\pm 0.06$  dB
  - Axial isotropy:  $< 0.25$  dB
  - Hemispherical Isotropy:  $< 0.50$  dB
  - Calibration range: 450MHz to 6000MHz for head & body simulating liquid.
  - Lower detection limit: 9mW/kg
- Angle between probe axis (evaluation axis) and surface normal line: less than  $30^\circ$ .

#### 2.3.1. E-Field Probe Calibration

Each probe needs to be calibrated according to a dosimetric assessment procedure with accuracy better than  $\pm 10\%$ . The spherical isotropy shall be evaluated and within  $\pm 0.25$ dB. The sensitivity parameters (Norm X, Norm Y, and Norm Z), the diode compression parameter (DCP) and the conversion factor (Conv F) of the probe are tested. The calibration data can be referred to appendix D of this report.

## 2.4. SAM phantoms


Photo of SAM phantom SN 16/15 SAM119



The SAM phantom is used to measure the SAR relative to people exposed to electro-magnetic field radiated by mobile phones.

### 2.4.1. Technical Data

Serial Number	Shell thickness	Filling volume	Dimensions	Positionner Material	Permittivity	Loss Tangent
SN 16/15 SAM119	2 mm $\pm$ 0.2 mm	27 liters	Length:1000 mm Width:500 mm Height:200 mm	Gelcoat with fiberglass	3.4	0.02




Serial Number	Left Head		Right Head		Flat Part	
SN 16/15 SAM119	2	2.02	2	2.08	1	2.09
	3	2.05	3	2.06	2	2.06
	4	2.07	4	2.07	3	2.08
	5	2.08	5	2.08	4	2.10
	6	2.05	6	2.07	5	2.10
	7	2.05	7	2.05	6	2.07
	8	2.07	8	2.06	7	2.07
	9	2.08	9	2.06	-	-

The test, based on ultrasonic system, allows measuring the thickness with an accuracy of 10 µm.

## 2.5. Device Holder

The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1 degree.



Serial Number	Holder Material	Permittivity	Loss Tangent
SN 16/15 MSH100	Delrin	3.7	0.005

## 2.6. Test Equipment List

This table gives a complete overview of the SAR measurement equipment.

Devices used during the test described are marked ☒

	Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
					Last Cal.	Due Date
<input checked="" type="checkbox"/>	MVG	E FIELD PROBE	SSE2	SN 34/15 EPGO267	Aug. 24, 2015	Aug. 23, 2016
<input type="checkbox"/>	MVG	450 MHz Dipole	SID450	SN 03/15 DIP 0G450-345	Apr. 06, 2015	Apr. 05, 2018
<input type="checkbox"/>	MVG	750 MHz Dipole	SID750	SN 03/15 DIP 0G750-355	Apr. 06, 2015	Apr. 05, 2018
<input checked="" type="checkbox"/>	MVG	835 MHz Dipole	SID835	SN 03/15 DIP 0G835-347	Apr. 06, 2015	Apr. 05, 2018
<input type="checkbox"/>	MVG	900 MHz Dipole	SID900	SN 03/15 DIP 0G900-348	Apr. 06, 2015	Apr. 05, 2018
<input type="checkbox"/>	MVG	1800 MHz Dipole	SID1800	SN 03/15 DIP 1G800-349	Apr. 06, 2015	Apr. 05, 2018
<input checked="" type="checkbox"/>	MVG	1900 MHz Dipole	SID1900	SN 03/15 DIP 1G900-350	Apr. 06, 2015	Apr. 05, 2018
<input type="checkbox"/>	MVG	2000 MHz Dipole	SID2000	SN 03/15 DIP 2G000-351	Apr. 06, 2015	Apr. 05, 2018
<input checked="" type="checkbox"/>	MVG	2450 MHz Dipole	SID2450	SN 03/15 DIP 2G450-352	Apr. 06, 2015	Apr. 05, 2018
<input type="checkbox"/>	MVG	2600 MHz Dipole	SID2600	SN 03/15 DIP 2G600-356	Apr. 06, 2015	Apr. 05, 2018
<input type="checkbox"/>	MVG	5000 MHz Dipole	SWG5500	SN 13/14 WGA 33	Apr. 06, 2015	Apr. 05, 2018
<input checked="" type="checkbox"/>	MVG	Liquid measurement Kit	SCLMP	SN 21/15 OCPG 72	NCR	NCR
<input checked="" type="checkbox"/>	MVG	Power Amplifier	N.A	AMPLISAR_28/14_003	NCR	NCR
<input checked="" type="checkbox"/>	KEITHLEY	Millivoltmeter	2000	4072790	NCR	NCR
<input checked="" type="checkbox"/>	R&S	Universal radio communication tester	CMU200	117858	Aug. 08, 2015	Aug. 07, 2016
<input checked="" type="checkbox"/>	Agilent	Network Analyzer	8753D	3410J01136	Aug. 08, 2015	Aug. 07, 2016
<input checked="" type="checkbox"/>	Agilent	PSG Analog Signal Generator	E8257D	MY51110112	Aug. 08, 2015	Aug. 07, 2016



<input checked="" type="checkbox"/>	Agilent	Power meter	E4419B	MY45102538	Jul. 31, 2015	Jul. 30, 2016
<input checked="" type="checkbox"/>	Agilent	Power sensor	E9301A	MY41495644	Jul. 31, 2015	Jul. 30, 2016
<input checked="" type="checkbox"/>	Agilent	Power sensor	E9301A	US39212148	Jul. 31, 2015	Jul. 30, 2016
<input checked="" type="checkbox"/>	MCLI/USA	Directional Coupler	CB11-20	0D2L51502	Aug. 13, 2015	Aug. 12, 2016

### 3. SAR Measurement Procedures

The measurement procedures are as follows:

#### <Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WiFi/BT power measurement, use engineering software to configure EUT WiFi/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band.
- (d) Connect EUT RF port through RF cable to the power meter, and measure WiFi/BT output power.

#### <SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WiFi/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix A demonstrates.
- (c) Set scan area, grid size and other setting on the OPENSAR software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band.
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg.

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

#### 3.1. Power Reference

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

#### 3.2. Area scan & Zoom scan

The area scan is a 2D scan to find the hot spot location on the DUT. The zoom scan is a 3D scan above the hot spot to calculate the 1g and 10g SAR value.

Measurement of the SAR distribution with a grid of 8 to 16 mm \* 8 to 16 mm and a constant distance to

the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme. Around this point, a cube of 30 \* 30 \* 30 mm or 32 \* 32 \* 32 mm is assessed by measuring 5 or 8 \* 5 or 8 \* 4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

From the scanned SAR distribution, identify the position of the maximum SAR value, in addition identify the positions of any local maxima with SAR values within 2 dB of the maximum value that will not be within the zoom scan of other peaks; additional peaks shall be measured only when the primary peak is within 2 dB of the SAR compliance limit (e.g., 1 W/kg for 1,6 W/kg 1 g limit, or 1,26 W/kg for 2 W/kg, 10 g limit).

Area scan & Zoom scan scan parameters extracted from FCC KDB 865664 D01 SAR measurement 100 MHz to 6 GHz.

			$\leq 3$ GHz	$> 3$ GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			$5 \pm 1$ mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$			$\leq 2$ GHz: $\leq 15$ mm 2 – 3 GHz: $\leq 12$ mm	3 – 4 GHz: $\leq 12$ mm 4 – 6 GHz: $\leq 10$ mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			$\leq 2$ GHz: $\leq 8$ mm 2 – 3 GHz: $\leq 5$ mm *	3 – 4 GHz: $\leq 5$ mm * 4 – 6 GHz: $\leq 4$ mm *
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		$\leq 5$ mm	3 – 4 GHz: $\leq 4$ mm 4 – 5 GHz: $\leq 3$ mm 5 – 6 GHz: $\leq 2$ mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$ : between 1 <sup>st</sup> two points closest to phantom surface	$\leq 4$ mm	3 – 4 GHz: $\leq 3$ mm 4 – 5 GHz: $\leq 2.5$ mm 5 – 6 GHz: $\leq 2$ mm
		$\Delta z_{\text{Zoom}}(n>1)$ : between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		$\geq 30$ mm	3 – 4 GHz: $\geq 28$ mm 4 – 5 GHz: $\geq 25$ mm 5 – 6 GHz: $\geq 22$ mm

Note:  $\delta$  is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.

\* When zoom scan is required and the *reported* SAR from the *area scan based 1-g SAR estimation* procedures of KDB 447498 is  $\leq 1.4$  W/kg,  $\leq 8$  mm,  $\leq 7$  mm and  $\leq 5$  mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

### **3.3. Description of interpolation/extrapolation scheme**

The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimise measurements errors, but the highest local SAR will occur at the surface of the phantom.

An extrapolation is used to determine this highest local SAR values. The extrapolation is based on a fourth-order least-square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1 mm step.

The measurements have to be performed over a limited time (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8 mm. To obtain an accurate assessment of the maximum SAR averaged over 10 grams and 1 gram requires a very fine resolution in the three dimensional scanned data array.

### **3.4. Volumetric Scan**

The volumetric scan consists to a full 3D scan over a specific area. This 3D scan is useful for multi Tx SAR measurement. Indeed, it is possible with OpenSAR to add, point by point, several volumetric scan to calculate the SAR value of the combined measurement as it is defined in the standard IEEE1528 and IEC62209.

### **3.5. Power Drift**

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In OpenSAR measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in V/m. If the power drifts more than  $\pm 5\%$ , the SAR will be retested.

## 4. System Verification Procedure

### 4.1. Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Ingredients (% of weight)	Head Tissue							
Frequency Band (MHz)	750	835	900	1800	1900	2000	2450	2600
Water	34.40	34.40	34.40	55.36	55.36	57.87	57.87	57.87
NaCl	0.79	0.79	0.79	0.35	0.35	0.16	0.16	0.16
1,2-Propanediol	64.81	64.81	64.81	0.00	0.00	0.00	0.00	0.00
Triton X-100	0.00	0.00	0.00	30.45	30.45	19.97	19.97	19.97
DGBE	0.00	0.00	0.00	13.84	13.84	22.00	22.00	22.00
Ingredients (% of weight)	Body Tissue							
Frequency Band (MHz)	750	835	900	1800	1900	2000	2450	2600
Water	50.30	50.30	50.30	69.91	69.91	71.88	71.88	71.88
NaCl	0.60	0.60	0.60	0.13	0.13	0.16	0.16	0.16
1,2-Propanediol	49.10	49.10	49.10	0.00	0.00	0.00	0.00	0.00
Triton X-100	0.00	0.00	0.00	9.99	9.99	19.97	19.97	19.97
DGBE	0.00	0.00	0.00	19.97	19.97	7.99	7.99	7.99

#### 4.1.1. Tissue Dielectric Parameter Check Results

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values. The measured conductivity and relative permittivity should be within  $\pm 5\%$  of the target values.

Tissue Type	Measured Frequency (MHz)	Target Tissue		Measured Tissue		Liquid Temp.	Test Date
		$\epsilon_r$ ( $\pm 5\%$ )	$\sigma$ (S/m) ( $\pm 5\%$ )	$\epsilon_r$	$\sigma$ (S/m)		
Head 850	835	41.50 (39.43~43.57)	0.90 (0.86~0.94)	42.07	0.89	21.3 °C	Dec 01, 2015
Body 850	835	55.20 (52.44~57.96)	0.97 (0.92~1.01)	55.27	0.98	21.5 °C	Dec 01, 2015
Head 1900	1900	40.00 (38.00~42.00)	1.40 (1.33~1.47)	39.27	1.46	21.4 °C	Nov 30, 2015
Body 1900	1900	53.30 (50.64~55.96)	1.52 (1.44~1.59)	53.62	1.55	21.4 °C	Nov 30, 2015
Head 2450	2450	39.20 (37.24~41.16)	1.80 (1.71~1.89)	39.35	1.76	21.6 °C	Dec 03, 2015


Body 2450	2450	52.70 (50.07~55.33)	1.95 (1.85~2.04)	52.23	1.89	21.5 °C	Dec 03, 2015
Head 850	835	41.50 (39.43~43.57)	0.90 (0.86~0.94)	40.98	0.93	21.4 °C	Jun. 06, 2016
Body 850	835	55.20 (52.44~57.96)	0.97 (0.92~1.01)	55.18	0.99	21.3 °C	Jun. 06, 2016
Head 1900	1900	40.00 (38.00~42.00)	1.40 (1.33~1.47)	39.11	1.45	21.4 °C	Jun. 03, 2016
Body 1900	1900	53.30 (50.64~55.96)	1.52 (1.44~1.59)	52.93	1.51	21.6 °C	Jun. 03, 2016

NOTE: The dielectric parameters of the tissue-equivalent liquid should be measured under similar ambient conditions and within 2 °C of the conditions expected during the SAR evaluation to satisfy protocol requirements.

## 4.2. System Verification Procedure

The system verification is performed for verifying the accuracy of the complete measurement system and performance of the software. The dipole is connected to the signal source consisting of signal generator and amplifier via a directional coupler, N-connector cable and adaption to SMA. It is fed with a power of 100mW (below 5GHz) or 100mW (above 5GHz). To adjust this power a power meter is used. The power sensor is connected to the cable before the system verification to measure the power at this point and do adjustments at the signal generator. At the outputs of the directional coupler both return loss as well as forward power are controlled during the system verification to make sure that emitted power at the dipole is kept constant. This can also be checked by the power drift measurement after the test (result on plot).

The system verification is shown as below picture:



#### 4.2.1. System Verification Results

Comparing to the original SAR value provided by SATIMO, the verification data should be within its specification of  $\pm 10\%$ . Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance verification can meet the variation criterion and the plots can be referred to Appendix B of this report.

System Verification	Target SAR (1W) ( $\pm 10\%$ )		Measured SAR (Normalized to 1W)		Liquid Temp.	Test Date
	1-g (W/Kg)	10-g (W/Kg)	1-g (W/Kg)	10-g (W/Kg)		
835MHz Head	9.56 (8.60~10.51)	6.22 (5.60~6.84)	9.39	6.08	21.3 °C	Dec 01, 2015
835MHz Body	9.48 (8.53~10.42)	6.29 (5.66~6.91)	8.95	6.37	21.5 °C	Dec 01, 2015
1900MHz Head	39.70 (35.73~43.67)	20.50 (18.45~22.55)	38.16	19.86	21.4 °C	Nov 30, 2015
1900MHz Body	38.43 (34.59~42.27)	20.34 (18.31~22.37)	38.01	20.21	21.4 °C	Nov 30, 2015
2450MHz Head	52.40 (47.16~57.64)	24.00 (21.60~26.40)	50.87	22.85	21.6 °C	Dec 03, 2015
2450MHz Body	49.32 (44.39~54.25)	22.89 (20.60~25.17)	53.82	24.36	21.5 °C	Dec 03, 2015
835MHz Head	9.56 (8.60~10.51)	6.22 (5.60~6.84)	8.93	5.96	21.4 °C	Jun. 06, 2016
835MHz Body	9.48 (8.53~10.42)	6.29 (5.66~6.91)	9.55	6.22	21.3 °C	Jun. 06, 2016
1900MHz Head	39.70 (35.73~43.67)	20.50 (18.45~22.55)	41.05	19.17	21.4 °C	Jun. 03, 2016
1900MHz Body	38.43 (34.59~42.27)	20.34 (18.31~22.37)	41.28	21.06	21.6 °C	Jun. 03, 2016



## **5. SAR Measurement variability and uncertainty**

### **5.1. SAR measurement variability**

Per KDB865664 D01 SAR measurement 100 MHz to 6 GHz, SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. The additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is  $< 0.80$  W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is  $\geq 0.80$  W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is  $> 1.20$  or when the original or repeated measurement is  $\geq 1.45$  W/kg ( $\sim 10\%$  from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is  $\geq 1.5$  W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is  $> 1.20$ .

### **5.2. SAR measurement uncertainty**

Per KDB865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is  $< 1.5$  W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.

## 6. RF Exposure Positions

### 6.1. Ear and handset reference point

Figure 6.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled “M”, the left ear reference point (ERP) is marked “LE”, and the right ERP is marked “RE”.



Fig 6.1.1 Front, back, and side views of SAM phantom

### 6.2. Definition of the cheek position

1. Define two imaginary lines on the handset, the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset: the midpoint of the width  $w_t$  of the handset at the level of the acoustic output (point A in Figure 6.2.1 and Figure 6.2.2), and the midpoint of the width  $w_b$  of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 6.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 6.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
2. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
3. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP
4. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
5. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.

6. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 6.2.3. The actual rotation angles should be documented in the test report.




Fig 6.2.1 Handset vertical and horizontal reference lines—"fixed case"




Fig 6.2.2 Handset vertical and horizontal reference lines—"clam-shell case"




Fig 6.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

### 6.3. Definition of the tilt position

1. While maintaining the orientation of the handset, retract the handset parallel to the reference plane far enough away from the phantom to enable a rotation of the device by 15 degree.
2. Rotate the Handset around the horizontal line by 15 degree (see Figure 6.3.1).
3. While maintaining the orientation of the handset, move the handset towards the phantom on a line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact is on the pinna. If the contact is at any location other than the pinna, e.g., the antenna with the back of the phantom head, the angle of the handset shall be reduced. In this case, the tilt position is obtained if any part of the handset is in contact with the pinna as well as a second part of the handset is in contact with the phantom, e.g., the antenna with the back of the head.




Figure 6.3.1 – Tilt position of the wireless device on the left side of SAM

### 6.4. Body Worn Accessory

1. Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6.4.1). Per KDB 648474 D04, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is  $< 1.2 \text{ W/kg}$ , the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.
2. Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are test with the

device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Figure 6.4.1 – Test positions for body-worn devices

### 6.5. Wireless Router Devices

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 where SAR test considerations for handsets ( $L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$ ) are based on a composite test separation distance of 0mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01 publication procedures. The “Portable Hotspot” feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

## 7. RF Output Power

### 7.1. Maximum Tune-up Limit

Band	Mode	The Tune-up Maximum Power (Customer Declared)(dBm)	Range	Measured Maximum Output Power(dBm)
GSM 850	GSM (GMSK)	32±1	31~33	32.17
	GPRS(GMSK, 1 Tx slot)	32±1	31~33	32.17
	GPRS(GMSK, 2 Tx slot)	31±1	30~32	31.54
	GPRS(GMSK, 3 Tx slot)	30±1	29~31	30.04
	GPRS(GMSK, 4 Tx slot)	29±1	28~30	29.05
	EDGE(8PSK, 1 Tx slot)	27±1	26~28	27.07
	EDGE(8PSK, 2 Tx slot)	25±1	24~26	25.76
	EDGE(8PSK, 3 Tx slot)	23±1	22~24	23.49
	EDGE(8PSK, 4 Tx slot)	22±1	21~23	22.25
GSM 1900	GSM (GMSK)	29±1	28~30	29.36
	GPRS(GMSK, 1 Tx slot)	29±1	28~30	29.43
	GPRS(GMSK, 2 Tx slot)	28±1	27~29	28.64
	GPRS(GMSK, 3 Tx slot)	26±1	25~27	26.86
	GPRS(GMSK, 4 Tx slot)	25±1	24~26	25.87
	EDGE(8PSK, 1 Tx slot)	25±1	24~26	25.49
	EDGE(8PSK, 2 Tx slot)	24±1	23~25	24.20
	EDGE(8PSK, 3 Tx slot)	21±1	20~22	21.83
	EDGE(8PSK, 4 Tx slot)	20±1	20~21	20.49
UMTS Band V	RMC 12.2Kbps	23±1	22~24	22.98
	HSDPA Subtest-1	22±1	21~23	21.69
	HSDPA Subtest-2	22±1	21~23	21.74
	HSDPA Subtest-3	22±1	21~23	21.35
	HSDPA Subtest-4	22±1	21~23	21.29
	HSUPA Subtest-1	22±1	21~23	22.01
	HSUPA Subtest-2	22±1	21~23	21.98
	HSUPA Subtest-3	22±1	21~23	22.04
	HSUPA Subtest-4	22±1	21~23	21.96
	HSUPA Subtest-5	22±1	21~23	21.35
UMTS Band II	RMC 12.2Kbps	22±1	21~23	22.56
	HSDPA Subtest-1	21±1	20~22	21.43
	HSDPA Subtest-2	21±1	20~22	21.41
	HSDPA Subtest-3	21±1	20~22	21.24
	HSDPA Subtest-4	21±1	20~22	21.18



	HSUPA Subtest-1		21±1	20~22	21.30
	HSUPA Subtest-2		21±1	20~22	21.29
	HSUPA Subtest-3		21±1	20~22	21.35
	HSUPA Subtest-4		21±1	20~22	21.42
	HSUPA Subtest-5		21±1	20~22	21.56
WiFi 2.4G	802.11b		14±1	13~15	14.27
	802.11g		10±1	9~11	10.69
	802.11n-HT20		9±1	8~10	9.67
	802.11n-HT40		5±1	4~6	5.67
Band	Channel	Mode	The Tune-up Maximum Power (Customer Declared)(dBm)	Range	Measured Maximum Output Power(dBm)
BT	0	DH5	2±1	2~4	2.67
		2DH5			
		3DH5			
	39	DH5	2±1	2~4	2.79
		2DH5			
		3DH5			
	78	DH5	2±1	2~4	2.94
		2DH5			
		3DH5			
	0	4.0	-6±1	-7~-5	-6.54
	19				-6.11
	39				-6.28

## 7.2. GSM Conducted Power

- 1) Per KDB 447498 D01, the maximum output power channel is used for SAR testing and for further SAR test reduction.
- 2) Per KDB 941225 D01, considering the possibility of e.g. 3rd party VoIP operation for Head and body-worn SAR test reduction for GSM and GPRS modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the EUT was set in GPRS (4Tx slots) for GSM850/GSM1900.
- 3) Per KDB 941225 D01, for Hotspot SAR test reduction for GPRS modes is determined by the source-based time-averaged output power including tune-up tolerance, for modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested, therefore, the EUT was set in GPRS (4Tx slots) for GSM850/GSM1900.

Band GSM850	Burst-Averaged output Power (dBm)				Frame-Averaged output Power (dBm)			
Tx Channel	Tune-up	128	189	251	Tune-up	128	189	251
Frequency (MHz)	(dBm)	824.2	836.4	848.8	(dBm)	824.2	836.4	848.8
GSM (GMSK)	33.00	32.11	32.16	32.17	23.97	23.08	23.13	23.14
GPRS(GMSK, 1 TS)	33.00	32.10	32.15	32.17	23.97	23.07	23.12	23.14
GPRS(GMSK, 2 TS)	32.00	31.53	31.52	31.54	25.98	25.51	25.50	25.52
GPRS(GMSK, 3 TS)	31.00	29.97	30.02	30.04	26.74	25.71	25.76	25.78
GPRS(GMSK, 4 TS)	30.00	29.05	29.01	29.05	26.99	26.04	26.00	26.04
EDGE(8PSK, 1 TS)	28.00	27.07	26.99	26.92	18.97	18.04	17.96	17.89
EDGE(8PSK, 2 TS)	26.00	25.74	25.76	25.69	19.98	19.72	19.74	19.67
EDGE(8PSK, 3 TS)	24.00	23.49	23.44	23.37	19.74	19.23	19.18	19.11
EDGE(8PSK, 4 TS)	23.00	22.25	22.23	22.15	19.99	19.24	19.22	19.14
Band GSM1900	Burst-Averaged output Power (dBm)				Frame-Averaged output Power (dBm)			
Tx Channel	Tune-up	512	661	810	Tune-up	512	661	810
Frequency (MHz)	(dBm)	1850.2	1880.0	1909.8	(dBm)	1850.2	1880.0	1909.8
GSM (GMSK)	30.00	29.24	29.22	29.36	20.97	20.21	20.19	20.33
GPRS(GMSK, 1 TS)	30.00	29.37	29.43	29.39	20.97	20.34	20.40	20.36
GPRS(GMSK, 2 TS)	29.00	28.59	28.64	28.63	22.98	22.57	22.62	22.61
GPRS(GMSK, 3 TS)	27.00	26.78	26.85	26.86	22.74	22.52	22.59	22.60
GPRS(GMSK, 4 TS)	26.00	25.76	25.86	25.87	22.99	22.75	22.85	22.86
EDGE(8PSK, 1 TS)	26.00	25.40	25.49	25.48	16.97	16.37	16.46	16.45
EDGE(8PSK, 2 TS)	25.00	24.19	24.20	24.17	18.98	18.17	18.18	18.15
EDGE(8PSK, 3 TS)	22.00	21.83	21.81	21.74	17.74	17.57	17.55	17.48
EDGE(8PSK, 4 TS)	21.00	20.45	20.49	20.37	17.99	17.44	17.48	17.36

Note: The frame-averaged power is linearly scaled the maximum burst averaged power over 8 time slots.

The calculated method are shown as below:

Frame-averaged power = Maximum burst averaged power (1 TS) – 9.03 dB

Frame-averaged power = Maximum burst averaged power (2 TS) – 6.02 dB

Frame-averaged power = Maximum burst averaged power (3 TS) - 4.26 dB

Frame-averaged power = Maximum burst averaged power (4 TS) – 3.01 dB

### 7.3. UMTS Conducted Power

The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification. A summary of these settings are illustrated below:

#### 1. Release99 Setup Configuration

Mode	Subtest	Rel99
UMTS General Settings	Loopback Mode	Test Mode 1
	Rel99 RMC	12.2kbps RMC
	Power Control Algorithm	Algorithm2
	$\beta_c/\beta_d$	8/15



## 2. HSDPA Setup Configuration

	Mode	HSDPA	HSDPA	HSDPA	HSDPA
	Subtest	1	2	3	4
UMTS General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set1			
	Power Control Algorithm	Algorithm 2			
	$\beta_c$	2/15	12/15	15/15	15/15
	$\beta_d$	15/15	15/15	8/15	4/15
	Bd (SF)	64			
	$\beta_c/\beta_d$	2/15	12/15	15/8	15/4
	$\beta_{hs}$	4/15	24/15	30/15	30/15
HSDPA Specific Settings	D <sub>ACK</sub>	8			
	D <sub>NAK</sub>	8			
	DCQI	8			
	Ack-Nack repetition factor	3			
	CQI Feedback (Table 5.2B.4)	4ms			
	CQI Repetition Factor (Table 5.2B.4)	2			
	A <sub>hs</sub> = $\beta_{hs}/\beta_c$	30/15			

## 3. HSUPA Setup Configuration

	Mode	HSUPA	HSUPA	HSUPA	HSUPA	HSUPA
	Subtest	1	2	3	4	5
UMTS General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2kbps RMC				
	HSDPA FRC	H-Set1				
	HSUPA Test	HSUPA Loopback				
	Power Control Algorithm	Algorithm2				
	$\beta_c$	11/15	6/15	15/15	2/15	15/15
	$\beta_d$	15/15	15/15	9/15	15/15	15/15
	$\beta_{ec}$	209/225	12/15	30/15	2/15	24/15
	$\beta_c/\beta_d$	11/15	6/15	15/9	2/15	15/15
	$\beta_{hs}$	22/15	12/15	30/15	4/15	30/15
	$\beta_{ed}$	1309/225	94/75	47/15 47/15	56/75	134/15
HSDPA Specific Settings	CM (dB)	1.0	3.0	2.0	3.0	1.0
	D <sub>ACK</sub>	8				
	D <sub>NAK</sub>	8				
	DCQI	8				
	Ack-Nack repetition factor	3				
	CQI Feedback (Table 5.2B.4)	4ms				
	CQI Repetition Factor (Table 5.2B.4)	2				
HSUPA Specific Settings	A <sub>hs</sub> = $\beta_{hs}/\beta_c$	30/15				
	D E-DPCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
	AG Index	20	12	15	17	21
	ETFCI (from 34.121 Table C.11.1.3)	75	67	92	71	81
	Associated Max UL Data Rate kbps	242.1	174.9	482.8	205.8	308.9

## 4. UMTS Conducted Power Results

- 1) Per KDB 941225 D01, SAR for Head / Hotspot / Body-worn exposure is measured using a 12.2

kbps RMC with TPC bits configured to all "1's".

2) Per KDB 941225 D01, RMC 12.2kbps setting is used to evaluate SAR. If the maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA is  $\leq \frac{1}{4}$  dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA to RMC12.2Kbps and the adjusted SAR is  $\leq 1.2$  W/kg, SAR measurement is not required for HSDPA / HSUPA.

Band	UMTS Band V			
Tx Channel	Tune-up	4132	4182	4233
Frequency (MHz)		826.4	836.4	846.6
RMC 12.2Kbps	23.00	22.69	22.78	22.98
HSDPA Subtest-1	23.00	21.27	21.69	21.51
HSDPA Subtest-2	23.00	21.25	21.74	21.46
HSDPA Subtest-3	23.00	21.16	21.35	21.14
HSDPA Subtest-4	23.00	21.09	21.29	21.11
HSUPA Subtest-1	23.00	21.58	22.01	21.86
HSUPA Subtest-2	23.00	21.55	21.98	21.81
HSUPA Subtest-3	23.00	21.53	22.04	21.93
HSUPA Subtest-4	23.00	21.49	21.96	21.74
HSUPA Subtest-5	23.00	21.13	21.35	21.16
Band	UMTS Band II			
Tx Channel	Tune-up	9262	9400	9538
Frequency (MHz)		1852.4	1880	1907.6
RMC 12.2Kbps	23.00	21.69	22.56	21.99
HSDPA Subtest-1	22.00	20.31	21.43	20.88
HSDPA Subtest-2	22.00	20.29	21.41	20.93
HSDPA Subtest-3	22.00	20.12	21.24	20.35
HSDPA Subtest-4	22.00	20.09	21.18	20.36
HSUPA Subtest-1	22.00	20.43	21.30	20.82
HSUPA Subtest-2	22.00	20.41	21.29	20.88
HSUPA Subtest-3	22.00	20.40	21.35	20.83
HSUPA Subtest-4	22.00	20.39	21.42	20.78
HSUPA Subtest-5	22.00	21.01	21.56	21.26

## 7.4. WiFi & BT Output Power

### 7.4.1. Output Power Results Of WiFi

The output power of WiFi is as following:

WiFi 2450MHz	Channel	Output Power (dBm) for Data Rates (Mbps)								
		Tune-up	1	2	5.5	11	/	/	/	/
802.11b	1	15.00	14.03	13.89	13.83	13.60	/	/	/	/
	6	15.00	14.15	14.15	13.91	13.81	/	/	/	/
	11	15.00	14.27	14.15	13.99	13.92	/	/	/	/
802.11g	Channel	Tune-up	6	9	12	18	24	36	48	54
	1	11.00	10.62	10.53	10.31	10.32	10.18	9.95	9.66	9.61
	6	11.00	10.57	10.45	10.25	10.21	10.01	9.82	9.56	9.40
	11	11.00	10.69	10.58	10.39	10.28	10.29	10.01	9.81	9.49
802.11n (HT20)	Channel	Tune-up	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
	1	10.00	9.67	9.49	9.49	9.41	9.25	8.92	8.80	8.54
	6	10.00	9.55	9.41	9.37	9.16	9.14	8.85	8.51	8.40
	11	10.00	9.61	9.63	9.30	9.16	9.22	9.04	8.59	8.62
802.11n (HT40)	Channel	Tune-up	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
	3	6.00	5.49	5.40	5.28	5.06	5.01	4.77	4.51	4.41
	6	6.00	5.55	5.37	5.25	5.18	4.94	4.85	4.63	4.45
	9	6.00	5.67	5.63	5.35	5.33	5.24	5.04	4.73	4.48


### 7.4.2. Output Power Results Of BT

The output power of BT is as following:

BT	Output Power (dBm)			
	Tune-up	1M	2M	3M
0CH	3.00	2.55	2.71	2.82
39CH	3.00	2.67	2.79	2.94
78CH	3.00	2.59	2.69	2.73

BT(4.0)	Output Power (dBm)			
	Tune-up	0CH	19CH	39CH
	-5.00	-6.54	-6.11	-6.28

## 8. Antenna Location



Distance of the Antenna to the EUT surface/edge						
Antennas	Front Side	Back Side	Left Side	Right Side	Top Side	Bottom Side
WWAN Main	≤ 25mm	≤ 25mm	> 25mm	≤ 25mm	>25mm	> 25mm
WLAN & BT	≤ 25mm	≤ 25mm	≤ 25mm	>25mm	>25mm	> 25mm

Positions for SAR tests; Hotspot mode						
Antennas	Front Side	Back Side	Left Side	Right Side	Top Side	Bottom Side
WWAN Main	Yes	Yes	NO	Yes	NO	NO
WLAN & BT	Yes	Yes	Yes	NO	NO	NO

NOTE: Referring to KDB 941225 D06, when the overall device length and width are  $\geq 9\text{cm} \times 5\text{cm}$ , the test distance is 10mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge.

## 9. Stand-alone SAR test exclusion

Per FCC KDB 447498D01, the 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

- $f_{\text{(GHz)}}$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	$P_{\text{max}}$ (dBm)	$P_{\text{max}}$ (mW)	Distance (mm)	f (GHz)	Calculation Result	SAR Exclusion threshold	SAR test exclusion
BT	3.00	2.00	<5	2.480	0.6	3.0	Yes

NOTE: Standalone SAR test exclusion for BT

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}/x] \text{ W/kg}$  for test separation distances  $\leq 50\text{mm}$ , where  $x = 7.5$  for 1-g SAR and  $x = 18.75$  for 10-g SAR.

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	Position	$P_{\text{max}}$ (dBm)	$P_{\text{max}}$ (mW)	Distance (mm)	f (GHz)	x	Estimated SAR (W/Kg)
BT	Head	3.00	2.00	<5	2.480	7.5	0.083
BT	Body-worn	3.00	2.00	<5	2.480	7.5	0.083
BT	Hotspot	3.00	2.00	<5	2.480	7.5	0.083

NOTE: Estimated SAR calculation for BT

## 10. SAR Measurement Results

### 10.1. SAR measurement results

General Notes:

- 1) Per KDB447498 D01, all measurement SAR results are scaled to the maximum tune-up tolerance limit to demonstrate compliant.
- 2) Per KDB447498 D01, testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is:  $\leq 0.8$  W/kg or  $2.0$  W/kg, for 1-g or 10-g respectively, when the transmission band is  $\leq 100$  MHz. When the maximum output power variation across the required test channels is  $> \frac{1}{2}$  dB, instead of the middle channel, the highest output power channel must be used.
- 3) Per KDB865664 D01, for each frequency band, repeated SAR measurement is required only when the measured SAR is  $\geq 0.8$  W/Kg; if the deviation among the repeated measurement is  $\leq 20\%$ , and the measured SAR  $< 1.45$  W/Kg, only one repeated measurement is required.
- 4) Per KDB941225 D06, the DUT Dimension is bigger than  $9\text{ cm} \times 5\text{ cm}$ , so 10mm is chosen as the test separation distance for Hotspot mode. When the antenna-to-edge distance is greater than 2.5cm, such position does not need to be tested.
- 5) Per KDB648474 D04, SAR is evaluated without a headset connected to the device. When the standalone reported Body-Worn SAR is  $\leq 1.2$  W/kg, no additional SAR evaluations using a headset are required.
- 6) Per KDB648474D04, the device is considered a "Phablet" since the diagonal dimension is greater than 160mm and less than 200mm. 10-g Extremity SAR tests are required when hotspot mode does not apply or if hotspot 1-g reported SAR  $> 1.2$  W/kg when scaled to the maximum allowed output power tolerance. When hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR  $> 1.2$  W/kg. When power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for Phablet modes to compare with the 1.2 W/kg SAR test reduction threshold. Simultaneous transmission SAR consideration for 10-g extremity SAR requires consideration only when standalone 10-g SAR is required.
- 7) Per KDB865664 D02, SAR plot is only required for the highest measured SAR in each exposure configuration, wireless mode and frequency band combination; Plots are also required when the measured SAR is  $> 1.5$  W/kg, or  $> 7.0$  W/kg for occupational exposure. The published RF exposure KDB procedures may require additional plots; for example, to support SAR to peak location separation ratio test exclusion and/or volume scan post-processing(Refer to appendix C for details).

### 10.1.1. SAR measurement Result of GSM850

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	251/848.8	GPRS(GMSK 4TS)	0.592	0.376	0.85	29.05	30.00	<b>0.737</b>
Left Tilt 15 Degree	251/848.8	GPRS(GMSK 4TS)	0.313	0.205	0.60	29.05	30.00	0.390
Right Cheek	251/848.8	GPRS(GMSK 4TS)	0.481	0.331	-1.48	29.05	30.00	0.599
Right Tilt 15 Degree	251/848.8	GPRS(GMSK 4TS)	0.232	0.167	-1.55	29.05	30.00	0.289

NOTE: Head SAR test results of GSM850.

Test Position of Body-Worn with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	251/848.8	GPRS(GMSK 4TS)	0.714	0.438	2.10	29.05	30.00	0.889
Back Side	251/848.8	GPRS(GMSK 4TS)	0.962	0.838	0.58	29.05	30.00	<b>1.197</b>
Back Side-Repeated	251/848.8	GPRS(GMSK 4TS)	0.942	0.824	0.85	29.05	30.00	1.172
Front Side	128/824.2	GPRS(GMSK 4TS)	0.503	0.321	1.16	29.05	30.00	0.626
Front Side	189/836.4	GPRS(GMSK 4TS)	0.628	0.395	-1.69	29.01	30.00	0.789
Back Side	128/824.2	GPRS(GMSK 4TS)	0.897	0.780	-2.06	29.05	30.00	1.116
Back Side	189/836.4	GPRS(GMSK 4TS)	0.924	0.819	1.25	29.01	30.00	1.161

NOTE: Body-Worn SAR test results of GSM850

Test Position of Hotspot with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	251/848.8	GPRS(GMSK 4TS)	0.714	0.438	2.10	29.05	30.00	0.889
Back Side	251/848.8	GPRS(GMSK 4TS)	0.962	0.838	0.58	29.05	30.00	<b>1.197</b>
Back Side-Repeated	251/848.8	GPRS(GMSK 4TS)	0.942	0.824	0.85	29.05	30.00	1.172
Right Side	251/848.8	GPRS(GMSK 4TS)	0.653	0.363	-0.25	29.05	30.00	0.813
Front Side	128/824.2	GPRS(GMSK 4TS)	0.503	0.321	1.16	29.05	30.00	0.626
Front Side	189/836.4	GPRS(GMSK 4TS)	0.628	0.395	-1.69	29.01	30.00	0.789
Back Side	128/824.2	GPRS(GMSK 4TS)	0.897	0.780	-2.06	29.05	30.00	1.116
Back Side	189/836.4	GPRS(GMSK 4TS)	0.924	0.819	1.25	29.01	30.00	1.161



Right Side	128/824.2	GPRS(GMSK 4TS)	0.521	0.373	1.67	29.05	30.00	0.648
Right Side	189/836.4	GPRS(GMSK 4TS)	0.559	0.321	-1.64	29.01	30.00	0.702

NOTE: Hotspot SAR test results of GSM850

#### 10.1.2. SAR measurement Result of GSM1900

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	810/1909.8	GPRS(GMSK 4TS)	0.912	0.542	0.13	25.87	26.00	0.940
Left Tilt 15 Degree	810/1909.8	GPRS(GMSK 4TS)	0.498	0.305	-2.05	25.87	26.00	0.513
Right Cheek	810/1909.8	GPRS(GMSK 4TS)	0.771	0.453	-3.24	25.87	26.00	0.794
Right Tilt 15 Degree	810/1909.8	GPRS(GMSK 4TS)	0.504	0.306	-1.49	25.87	26.00	0.519
Left Cheek	512/1850.2	GPRS(GMSK 4TS)	1.021	0.603	-0.05	25.76	26.00	<b>1.079</b>
Left Cheek-Repeated	512/1850.2	GPRS(GMSK 4TS)	1.017	0.587	1.02	25.76	26.00	1.075
Left Cheek	661/1880	GPRS(GMSK 4TS)	0.959	0.570	-0.07	25.86	26.00	0.990

NOTE: Head SAR test results of GSM1900

Test Position of Body-Worn with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	810/1909.8	GPRS(GMSK 4TS)	1.127	0.636	-2.69	25.87	26.00	1.161
Back Side	810/1909.8	GPRS(GMSK 4TS)	0.468	0.278	-2.83	25.87	26.00	0.482
Front Side	512/1850.2	GPRS(GMSK 4TS)	1.126	0.665	-1.77	25.76	26.00	<b>1.190</b>
Front Side	661/1880	GPRS(GMSK 4TS)	1.132	0.641	-2.63	25.86	26.00	1.169
Front Side-Repeated	661/1880	GPRS(GMSK 4TS)	1.082	0.674	0.84	25.76	26.00	1.143

NOTE: Body-Worn SAR test results of GSM1900

Test Position of Hotspot with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	810/1909.8	GPRS(GMSK 4TS)	1.127	0.636	-2.69	25.87	26.00	1.161
Back Side	810/1909.8	GPRS(GMSK 4TS)	0.468	0.278	-2.83	25.87	26.00	0.482
Right Side	810/1909.8	GPRS(GMSK 4TS)	0.863	0.493	1.45	25.87	26.00	0.889
Front Side	512/1850.2	GPRS(GMSK 4TS)	1.126	0.665	-1.77	25.76	26.00	<b>1.190</b>



		4TS)						
Front Side	661/1880	GPRS(GMSK 4TS)	1.132	0.641	-2.63	25.86	26.00	1.169
Front Side-Repeated	661/1880	GPRS(GMSK 4TS)	1.082	0.674	0.84	25.76	26.00	1.143
Right Side	512/1850.2	GPRS(GMSK 4TS)	0.932	0.534	-1.68	25.76	26.00	0.985
Right Side	661/1880	GPRS(GMSK 4TS)	0.885	0.510	-0.91	25.86	26.00	0.914

NOTE: Hotspot SAR test results of GSM1900

### 10.1.3. SAR measurement Result of UMTS Band V

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	4233/846.6	RMC12.2K	0.284	0.179	-3.98	22.98	24.00	<b>0.359</b>
Left Tilt 15 Degree	4233/846.6	RMC12.2K	0.154	0.100	0.11	22.98	24.00	0.195
Right Cheek	4233/846.6	RMC12.2K	0.173	0.114	0.22	22.98	24.00	0.219
Right Tilt 15 Degree	4233/846.6	RMC12.2K	0.102	0.067	2.03	22.98	24.00	0.129

NOTE: Head SAR test results of UMTS Band V

Test Position of Body-Worn with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	4233/846.6	RMC12.2K	0.412	0.271	-4.47	22.98	24.00	0.521
Back Side	4233/846.6	RMC12.2K	0.554	0.415	0.21	22.98	24.00	<b>0.701</b>

NOTE: Body-Worn SAR test results of UMTS Band V

Test Position of Hotspot with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	4233/846.6	RMC12.2K	0.412	0.271	-4.47	22.98	24.00	0.521
Back Side	4233/846.6	RMC12.2K	0.554	0.415	0.21	22.98	24.00	<b>0.701</b>
Right Side	4233/846.6	RMC12.2K	0.755	0.402	-0.31	22.98	24.00	0.955
Right Side	4132/826.4	RMC12.2K	0.590	0.310	-0.60	22.69	24.00	0.798
Right Side	4182/836.4	RMC12.2K	0.752	0.399	0.10	22.78	24.00	0.996

NOTE: Hotspot SAR test results of UMTS Band V

#### 10.1.4. SAR measurement Result of UMTS Band II

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	9400/1880	RMC12.2K	0.621	0.466	0.24	22.56	23.00	0.687
Left Tilt 15 Degree	9400/1880	RMC12.2K	0.445	0.277	0.02	22.56	23.00	0.492
Right Cheek	9400/1880	RMC12.2K	0.676	0.545	-0.27	22.56	23.00	<b>0.748</b>
Right Tilt 15 Degree	9400/1880	RMC12.2K	0.573	0.324	-0.45	22.56	23.00	0.634

NOTE: Head SAR test results of UMTS Band II

Test Position of Body-Worn with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	9400/1880	RMC12.2K	0.665	0.334	-0.09	22.56	23.00	<b>0.736</b>
Back Side	9400/1880	RMC12.2K	0.363	0.193	-0.39	22.56	23.00	0.402

NOTE: Body-Worn SAR test results of UMTS Band II

Test Position of Hotspot with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	9400/1880	RMC12.2K	0.665	0.334	-0.09	22.56	23.00	0.736
Back Side	9400/1880	RMC12.2K	0.363	0.193	-0.39	22.56	23.00	0.402
Right Side	9400/1880	RMC12.2K	0.773	0.447	-0.10	22.56	23.00	0.855
Right Side	9262/1852.4	RMC12.2K	0.688	0.371	0.07	21.69	23.00	<b>0.930</b>
Right Side	9538/1907.6	RMC12.2K	0.643	0.361	-0.05	21.99	23.00	0.811

NOTE: Hotspot SAR test results of UMTS Band II

### 10.1.5. SAR measurement Result of WiFi 2.4G

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	11/2462	802.11 b 1M	0.135	0.091	-0.97	14.27	15.00	0.160
Left Tilt 15 Degree	11/2462	802.11 b 1M	0.086	0.064	-3.54	14.27	15.00	0.102
Right Cheek	11/2462	802.11 b 1M	0.286	0.163	-3.06	14.27	15.00	<b>0.338</b>
Right Tilt 15 Degree	11/2462	802.11 b 1M	0.133	0.090	-4.53	14.27	15.00	0.157

NOTE: Head SAR test results of WiFi 2.4G

Test Position of Body-Worn with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	11/2462	802.11 b 1M	0.276	0.156	-0.99	14.27	15.00	<b>0.327</b>
Back Side	11/2462	802.11 b 1M	0.199	0.114	-1.73	14.27	15.00	0.235

NOTE: Body-Worn SAR test results of WiFi 2.4G

Test Position of Hotspot with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	11/2462	802.11 b 1M	0.276	0.156	-0.99	14.27	15.00	0.327
Back Side	11/2462	802.11 b 1M	0.199	0.114	-1.73	14.27	15.00	0.235
Left Side	11/2462	802.11 b 1M	0.559	0.280	-0.60	14.27	15.00	<b>0.661</b>

NOTE: Hotspot SAR test results of WiFi 2.4G

## 10.2. Simultaneous Transmission Possibilities

The Simultaneous Transmission Possibilities of this device are as below:

No.	Configuration	Head	Body	Hotspot	Note
1	GSM(Voice) + WiFi 2.4GHz(data)	Yes	Yes	N/A	VOIP
2	UMTS(Voice) + WiFi 2.4GHz(data)	Yes	Yes	N/A	VOIP
3	GSM(Voice) + BT(data)	Yes	Yes	N/A	VOIP
4	UMTS(Voice) + BT(data)	Yes	Yes	N/A	VOIP
5	GPRS/EDGE(data) + WiFi 2.4GHz(data)	Yes	Yes	Yes	2.4GHz Hotspot
6	UMTS(data) + WiFi 2.4GHz(data)	Yes	Yes	Yes	2.4GHz Hotspot
7	GPRS/EDGE(data) + BT(data)	Yes	Yes	Yes	BT Tethering
8	UMTS(data) + BT(data)	Yes	Yes	Yes	BT Tethering

NOTE:

- 1) This device supported VoIP in GPRS/EDGE and UMTS(e.g. 2rd party VoIP).
- 2) This device WiFi 2.4GHz supports Hotspot operation.
- 3) WiFi 2.4GHz and BT share the same antenna, and cannot transmit simultaneously.
- 4) EUT will choose each GSM, and UMTS according to the network signal condition; therefore, they will not operate simultaneously at any moment.
- 5) The Scaled SAR summation is calculated based on the same configuration and test position.

### 10.3. SAR Summation Scenario

Per KDB 447498 D01, simultaneous transmission SAR is compliant if,

- 1) Scalar SAR summation  $< 1.6\text{W/kg}$ .
- 2)  $\text{SPLSR} = (\text{SAR}_1 + \text{SAR}_2)^{1.5} / (\text{min. separation distance, mm})$ , and the peak separation distance is determined from the square root of  $[(x_1 - x_2)^2 + (y_1 - y_2)^2 + (z_1 - z_2)^2]$ , where  $(x_1, y_1, z_1)$  and  $(x_2, y_2, z_2)$  are the coordinates of the extrapolated peak SAR locations in the zoom scan. If  $\text{SPLSR} \leq 0.04$ , simultaneously transmission SAR measurement is not necessary.

Test Position		Scaled SAR <sub>MAX</sub>		$\Sigma$ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 850	WiFi 2.4G			
Head	Left Cheek	0.737	0.160	0.896	N/A	N/A
	Left Tilt 15 Degree	0.390	0.102	0.491	N/A	N/A
	Right Cheek	0.599	0.338	0.937	N/A	N/A
	Right Tilt 15 Degree	0.289	0.157	0.446	N/A	N/A
Body-worn	Front Side	0.889	0.327	1.216	N/A	N/A
	Back Side	1.197	0.235	1.432	N/A	N/A
Hotspot	Front Side	0.889	0.327	1.216	N/A	N/A
	Back Side	1.197	0.235	1.432	N/A	N/A
	Left Side	N/A	0.661	0.661	N/A	N/A
	Right Side	0.813	N/A	0.813	N/A	N/A

NOTE: 1-g SAR Simultaneous TX Combination of GSM850 and WiFi 2.4G.

Test Position		Scaled SAR <sub>MAX</sub>		$\Sigma$ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 1900	WiFi 2.4G			
Head	Left Cheek	1.079	0.160	1.239	N/A	N/A
	Left Tilt 15 Degree	0.513	0.102	0.615	N/A	N/A
	Right Cheek	0.794	0.338	1.133	N/A	N/A
	Right Tilt 15 Degree	0.519	0.157	0.677	N/A	N/A
Body-worn	Front Side	1.190	0.327	1.517	N/A	N/A
	Back Side	0.482	0.235	0.717	N/A	N/A
Hotspot	Front Side	1.190	0.327	<b>1.517</b>	N/A	N/A
	Back Side	0.482	0.235	0.717	N/A	N/A
	Left Side	N/A	0.661	0.661	N/A	N/A
	Right Side	0.985	N/A	0.985	N/A	N/A

NOTE: 1-g SAR Simultaneous TX Combination of GSM1900 and WiFi 2.4G.

Test Position		Scaled SAR <sub>MAX</sub>		$\Sigma$ 1-g SAR (W/Kg)	SPLSR	Remark
		UMTS Band V	WiFi 2.4G			
Head	Left Cheek	0.359	0.160	0.519	N/A	N/A
	Left Tilt 15 Degree	0.195	0.102	0.297	N/A	N/A
	Right Cheek	0.219	0.338	0.557	N/A	N/A
	Right Tilt 15 Degree	0.129	0.157	0.286	N/A	N/A
Body-worn	Front Side	0.521	0.327	0.848	N/A	N/A
	Back Side	0.701	0.235	0.936	N/A	N/A
Hotspot	Front Side	0.521	0.327	0.848	N/A	N/A
	Back Side	0.701	0.235	0.936	N/A	N/A
	Left Side	N/A	0.661	0.661	N/A	N/A
	Right Side	0.996	N/A	0.996	N/A	N/A

NOTE: 1-g SAR Simultaneous TX Combination of UMTS Band V and WiFi 2.4G.

Test Position		Scaled SAR <sub>MAX</sub>		$\Sigma$ 1-g SAR (W/Kg)	SPLSR	Remark
		UMTS Band II	WiFi 2.4G			
Head	Left Cheek	0.687	0.160	0.847	N/A	N/A
	Left Tilt 15 Degree	0.492	0.102	0.594	N/A	N/A
	Right Cheek	0.748	0.338	1.086	N/A	N/A
	Right Tilt 15 Degree	0.634	0.157	0.791	N/A	N/A
Body-worn	Front Side	0.736	0.327	1.062	N/A	N/A
	Back Side	0.402	0.235	0.637	N/A	N/A
Hotspot	Front Side	0.736	0.327	1.062	N/A	N/A
	Back Side	0.402	0.235	0.637	N/A	N/A
	Left Side	N/A	0.661	0.661	N/A	N/A
	Right Side	0.930	N/A	0.930	N/A	N/A

NOTE: 1-g SAR Simultaneous TX Combination of UMTS Band II and WiFi 2.4G.

Test Position		Scaled SAR <sub>MAX</sub>		$\Sigma$ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 850	BT			
Head	Left Cheek	0.737	0.083	0.820	N/A	N/A
	Left Tilt 15 Degree	0.390	0.083	0.473	N/A	N/A
	Right Cheek	0.599	0.083	0.682	N/A	N/A
	Right Tilt 15 Degree	0.289	0.083	0.372	N/A	N/A
Body-worn	Front Side	0.889	0.083	0.972	N/A	N/A
	Back Side	1.197	0.083	1.280	N/A	N/A
Hotspot	Front Side	0.889	0.083	0.972	N/A	N/A
	Back Side	1.197	0.083	1.280	N/A	N/A
	Left Side	N/A	0.083	0.083	N/A	N/A
	Right Side	0.813	N/A	0.813	N/A	N/A

NOTE: 1-g SAR Simultaneous TX Combination of GSM850 and BT.

Test Position		Scaled SAR <sub>MAX</sub>		$\Sigma$ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 1900	BT			
Head	Left Cheek	1.079	0.083	1.162	N/A	N/A
	Left Tilt 15 Degree	0.513	0.083	0.596	N/A	N/A
	Right Cheek	0.794	0.083	0.877	N/A	N/A
	Right Tilt 15 Degree	0.519	0.083	0.602	N/A	N/A
Body-worn	Front Side	1.190	0.083	1.273	N/A	N/A
	Back Side	0.482	0.083	0.565	N/A	N/A
Hotspot	Front Side	1.190	0.083	1.273	N/A	N/A
	Back Side	0.482	0.083	0.565	N/A	N/A
	Left Side	N/A	0.083	0.083	N/A	N/A
	Right Side	0.985	N/A	0.985	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM1900 and BT.

Test Position		Scaled SAR <sub>MAX</sub>		$\Sigma$ 1-g SAR (W/Kg)	SPLSR	Remark
		UMTS Band V	BT			
Head	Left Cheek	0.359	0.083	0.442	N/A	N/A
	Left Tilt 15 Degree	0.195	0.083	0.278	N/A	N/A
	Right Cheek	0.219	0.083	0.302	N/A	N/A
	Right Tilt 15 Degree	0.129	0.083	0.212	N/A	N/A
Body-worn	Front Side	0.521	0.083	0.604	N/A	N/A
	Back Side	0.701	0.083	0.784	N/A	N/A
Hotspot	Front Side	0.521	0.083	0.604	N/A	N/A
	Back Side	0.701	0.083	0.784	N/A	N/A
	Left Side	N/A	0.083	0.083	N/A	N/A
	Right Side	0.996	N/A	0.996	N/A	N/A

NOTE: 1-g SAR Simultaneous TX Combination of UMTS Band V and BT.

Test Position		Scaled SAR <sub>MAX</sub>		$\Sigma$ 1-g SAR (W/Kg)	SPLSR	Remark
		UMTS Band II	BT			
Head	Left Cheek	0.687	0.083	0.770	N/A	N/A
	Left Tilt 15 Degree	0.492	0.083	0.575	N/A	N/A
	Right Cheek	0.748	0.083	0.831	N/A	N/A
	Right Tilt 15 Degree	0.634	0.083	0.717	N/A	N/A
Body-worn	Front Side	0.736	0.083	0.819	N/A	N/A
	Back Side	0.402	0.083	0.485	N/A	N/A
Hotspot	Front Side	0.736	0.083	0.819	N/A	N/A
	Back Side	0.402	0.083	0.485	N/A	N/A
	Left Side	N/A	0.083	0.083	N/A	N/A
	Right Side	0.930	N/A	0.930	N/A	N/A

NOTE: 1-g SAR Simultaneous TX Combination of UMTS Band II and BT.



## 11. Appendix A. Photo documentation

Table of contents
Test Facility
Product Photo
Test Positions
Liquid depth

**Test Facility****Measurement System SATIMO**

Product Photo

Front View



Back View



Reference Line




Battery



# Test Positions

Left Cheek



Left Tilt 15 Degree



Right Cheek




Right Tilt 15 Degree



Front Side  
(Separation distance of 0mm)




Back Side  
(Separation distance of 0mm)



Left Side  
(Separation distance of 0mm)

Right Side  
(Separation distance of 0mm)



**Liquid depth**

Head 850MHz depth (15.2cm)



Body 850MHz depth (15.1cm)



Head 1900MHz depth (15.3cm)



Body 1900MHz depth (15.2cm)



Head 2450MHz depth (15.2cm)



Body 2450MHz depth (15.1cm)






## 12. Appendix B. System Check Plots


Table of contents
System Performance Check - SID835 - Head
System Performance Check - SID835 - Body
System Performance Check - SID1900 - Head
System Performance Check - SID1900 - Body
System Performance Check - SID2450 - Head
System Performance Check - SID2450 - Body

Date of measurement:	Dec 01, 2015
Signal:	Communication System: CW; Frequency: 835.00MHz; Duty Cycle: 1:1.00
ConvF:	1.89
Liquid Parameters:	Relative permittivity (real part): 42.07; Conductivity (S/m): 0.89;
Device Position:	Dipole
Area Scan:	dx=15mm dy=15mm, h=5.00mm
Zoom Scan:	5x5x7, dx=8mm dy=8mm dz=5mm, h=5.00mm

### 3D screen shot




### Volume SAR



Maximum location: X=3.00, Y=2.00

SAR Peak: 1.16 W/kg

SAR 1g (W/Kg)				0.939			
SAR 10g (W/Kg)				0.608			
Power Drift (±5%):				-0.16			
Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.1543	0.9854	0.7914	0.6351	0.5166	0.4380	0.3877









### System Performance Check - SID1900-Head

Date of measurement:	Nov 30, 2015
Signal:	Communication System: CW; Frequency: 1900.00MHz; Duty Cycle: 1:1.00
ConvF:	2.16
Liquid Parameters:	Relative permittivity (real part): 39.27; Conductivity (S/m): 1.46;
Device Position:	Dipole
Area Scan:	dx=15mm dy=15mm, h=5.00mm
Zoom Scan:	5x5x7, dx=8mm dy=8mm dz=5mm, h=5.00mm




### System Performance Check - SID1900-Body

Date of measurement:	Nov 30, 2015
Signal:	Communication System: CW; Frequency: 1900.00MHz; Duty Cycle: 1:1.00
ConvF:	2.24
Liquid Parameters:	Relative permittivity (real part): 53.62; Conductivity (S/m): 1.55;
Device Position:	Dipole
Area Scan:	dx=15mm dy=15mm, h=5.00mm
Zoom Scan:	5x5x7, dx=8mm dy=8mm dz=5mm, h=5.00mm



## System Performance Check - SID2450-Head


Date of measurement:	Dec 03, 2015
Signal:	Communication System: CW; Frequency: 2450.00MHz; Duty Cycle: 1:1.00
ConvF:	2.11
Liquid Parameters:	Relative permittivity (real part): 39.35; Conductivity (S/m): 1.76;
Device Position:	Dipole
Area Scan:	dx=12mm dy=12mm, h=5.00mm
Zoom Scan:	7x7x7, dx=5mm dy=5mm dz=5mm, h=5.00mm





### System Performance Check - SID835-Head


Date of measurement:	Jun. 06, 2016
Signal:	Communication System: CW; Frequency: 835.00MHz; Duty Cycle: 1:1.00
ConvF:	1.89
Liquid Parameters:	Relative permittivity (real part): 40.98; Conductivity (S/m):0.93;
Device Position:	Dipole
Area Scan:	dx=15mm dy=15mm, h=5.00mm
Zoom Scan:	5x5x7, dx=8mm dy=8mm dz=5mm, h=5.00mm




## System Performance Check - SID835-Body

Date of measurement:	Jun. 06, 2016
Signal:	Communication System: CW; Frequency: 835.00MHz; Duty Cycle: 1:1.00
ConvF:	1.94
Liquid Parameters:	Relative permittivity (real part): 55.18; Conductivity (S/m): 0.99;
Device Position:	Dipole
Area Scan:	dx=15mm dy=15mm, h=5.00mm
Zoom Scan:	5x5x7, dx=8mm dy=8mm dz=5mm, h=5.00mm

### 3D screen shot




### Volume SAR



Maximum location: X=3.00, Y=2.00

SAR Peak: 1.36 W/kg


SAR 1g (W/Kg)				0.955			
SAR 10g (W/Kg)				0.622			
Power Drift (±5%):				-0.05			
Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.3540	0.9940	0.6808	0.4797	0.3423	0.2503	0.1849




## System Performance Check - SID1900-Head

Date of measurement:	Jun. 03, 2016
Signal:	Communication System: CW; Frequency: 1900.00MHz; Duty Cycle: 1:1.00
ConvF:	2.16
Liquid Parameters:	Relative permittivity (real part): 39.11; Conductivity (S/m): 1.45;
Device Position:	Dipole
Area Scan:	dx=15mm dy=15mm, h=5.00mm
Zoom Scan:	5x5x7, dx=8mm dy=8mm dz=5mm, h=5.00mm

### 3D screen shot




### Volume SAR



Maximum location: X=5.00, Y=2.00  
SAR Peak: 7.62 W/kg


SAR 1g (W/Kg)				4.105			
SAR 10g (W/Kg)				1.917			
Power Drift (±5%):				-0.10			
Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	7.2337	4.0225	1.7695	0.8147	0.3833	0.1919	0.1029





### System Performance Check - SID1900-Body

Date of measurement:	Jun. 03, 2016
Signal:	Communication System: CW; Frequency: 1900.00MHz; Duty Cycle: 1:1.00
ConvF:	2.24
Liquid Parameters:	Relative permittivity (real part): 52.93; Conductivity (S/m): 1.51;
Device Position:	Dipole
Area Scan:	dx=15mm dy=15mm, h=5.00mm
Zoom Scan:	5x5x7, dx=8mm dy=8mm dz=5mm, h=5.00mm





### 13. Appendix C. SAR Measurement Plots

Table of contents
GSM 850 Head
GSM 850 Body
GSM 1900 Head
GSM 1900 Body
UMTS Band V Head
UMTS Band V Body
UMTS Band II Head
UMTS Band II Body
WiFi 2.4G Head
WiFi 2.4G Body

### GSM850\_GPRS(GMSK 4TS)\_Ch251\_Left Cheek


Date of measurement:	Dec. 01, 2015
Signal:	Communication System: GPRS(GMSK 4TS); Frequency: 848.80MHz; Duty Cycle: 1:2.08
ConvF:	1.89
Liquid Parameters:	Relative permittivity (real part): 41.86; Conductivity (S/m): 0.90;
Device Position:	Cheek
Area Scan:	dx=15mm dy=15mm, h=5.00mm
Zoom Scan:	5x5x7, dx=8mm dy=8mm dz=5mm, h=5.00mm






### GSM1900\_GPRS(GMSK 4TS)\_Ch512\_Left Cheek

Date of measurement:	Nov. 30, 2015
Signal:	Communication System: GPRS(GMSK 4TS); Frequency: 1850.20MHz; Duty Cycle: 1:2.08
ConvF:	2.16
Liquid Parameters:	Relative permittivity (real part): 39.51; Conductivity (S/m):1.43;
Device Position:	Cheek
Area Scan:	dx=15mm dy=15mm, h=5.00mm
Zoom Scan:	5x5x7, dx=8mm dy=8mm dz=5mm, h=5.00mm




**GSM1900\_GPRS(GMSK 4TS)\_Ch661\_Front Side\_0mm**


Date of measurement:	Nov. 30, 2015
Signal:	Communication System: GPRS(GMSK 4TS); Frequency: 1880.00MHz; Duty Cycle: 1:2.08
ConvF:	2.24
Liquid Parameters:	Relative permittivity (real part): 53.69; Conductivity (S/m): 1.54;
Device Position:	Body
Area Scan:	dx=15mm dy=15mm, h=5.00mm
Zoom Scan:	5x5x7, dx=8mm dy=8mm dz=5mm, h=5.00mm



### UMTS Band V\_RMC 12.2Kbps\_Ch4233\_Left Cheek

Date of measurement:	Jun. 06, 2016
Signal:	Communication System: UMTS-FDD(WCDMA); Frequency: 846.6MHz; Duty Cycle: 1:1.00
ConvF:	1.89
Liquid Parameters:	Relative permittivity (real part): 40.80; Conductivity (S/m): 0.95;
Device Position:	Cheek
Area Scan:	dx=15mm dy=15mm, h=5.00mm
Zoom Scan:	5x5x7, dx=8mm dy=8mm dz=5mm, h=5.00mm










### UMTS Band II\_RMC 12.2Kbps\_Ch9400\_Right Check

Date of measurement:	Jun. 03, 2016
Signal:	Communication System: UMTS-FDD(WCDMA); Frequency: 1880.00MHz; Duty Cycle: 1:1.00
ConvF:	2.16
Liquid Parameters:	Relative permittivity (real part): 39.16; Conductivity (S/m): 1.44;
Device Position:	Cheek
Area Scan:	dx=15mm dy=15mm, h=5.00mm
Zoom Scan:	5x5x7, dx=8mm dy=8mm dz=5mm, h=5.00mm









## 14. Appendix D. Calibration Certificate

Table of contents
E Field Probe - SN 34/15 EPGO267
835 MHz Dipole - SN 03/15 DIP 0G835-347
1900 MHz Dipole - SN 03/15 DIP 1G900-350
2450 MHz Dipole - SN 03/15 DIP 2G450-352
Extended Calibration Certificate



## COMOSAR E-Field Probe Calibration Report

Ref : ACR.261.1.15.SATU.A

**NTEK TESTING TECHNOLOGY CO., LTD.**  
**BUILDING E, FENDA SCIENCE PARK, SANWEI**  
**COMMUNITY, XIXIANG STREET,**  
**BAO'AN DISTRICT, SHENZHEN GUANGDONG, CHINA**  
**MVG COMOSAR DOSIMETRIC E-FIELD PROBE**  
**SERIAL NO.: SN 34/15 EPGO267**

**Calibrated at MVG US**  
**2105 Barrett Park Dr. - Kennesaw, GA 30144**



**Calibration Date: 08/24/2015**

### *Summary:*

This document presents the method and results from an accredited COMOSAR Dosimetric E-Field Probe calibration performed in MVG USA using the CALISAR / CALIBAIR test bench, for use with a COMOSAR system only. All calibration results are traceable to national metrology institutions.



# COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.261.1.15.SATU.A

	<i>Name</i>	<i>Function</i>	<i>Date</i>	<i>Signature</i>
<i>Prepared by :</i>	Jérôme LUC	Product Manager	9/18/2015	<i>JS</i>
<i>Checked by :</i>	Jérôme LUC	Product Manager	9/18/2015	<i>JS</i>
<i>Approved by :</i>	Kim RUTKOWSKI	Quality Manager	9/18/2015	<i>Kim Rutkowski</i>

	<i>Customer Name</i>
<i>Distribution :</i>	NTEK TESTING TECHNOLOGY CO., LTD.

<i>Issue</i>	<i>Date</i>	<i>Modifications</i>
A	9/18/2015	Initial release



## COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.261.1.15.SATU.A

### TABLE OF CONTENTS

1	Device Under Test .....	4
2	Product Description .....	4
2.1	General Information .....	4
3	Measurement Method .....	4
3.1	Linearity .....	4
3.2	Sensitivity .....	5
3.3	Lower Detection Limit .....	5
3.4	Isotropy .....	5
3.5	Boundary Effect .....	5
4	Measurement Uncertainty .....	5
5	Calibration Measurement Results .....	6
5.1	Sensitivity in air .....	6
5.2	Linearity .....	7
5.3	Sensitivity in liquid .....	7
5.4	Isotropy .....	8
6	List of Equipment .....	10





## COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.261.1.15.SATU.A

### 1 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR DOSIMETRIC E FIELD PROBE
Manufacturer	MVG
Model	SSE2
Serial Number	SN 34/15 EPGO267
Product Condition (new / used)	New
Frequency Range of Probe	0.45 GHz-6GHz
Resistance of Three Dipoles at Connector	Dipole 1: R1=0.234 MΩ Dipole 2: R2=0.236 MΩ Dipole 3: R3=0.233 MΩ

A yearly calibration interval is recommended.

### 2 PRODUCT DESCRIPTION

#### 2.1 GENERAL INFORMATION

MVG's COMOSAR E field Probes are built in accordance to the IEEE 1528, OET 65 Bulletin C and CEI/IEC 62209 standards.



Figure 1 – MVG COMOSAR Dosimetric E field Dipole

Probe Length	330 mm
Length of Individual Dipoles	2 mm
Maximum external diameter	8 mm
Probe Tip External Diameter	2.5 mm
Distance between dipoles / probe extremity	1 mm

### 3 MEASUREMENT METHOD

The IEEE 1528, OET 65 Bulletin C, CENELEC EN50361 and CEI/IEC 62209 standards provide recommended practices for the probe calibrations, including the performance characteristics of interest and methods by which to assess their affect. All calibrations / measurements performed meet the fore mentioned standards.

#### 3.1 LINEARITY

The evaluation of the linearity was done in free space using the waveguide, performing a power sweep to cover the SAR range 0.01W/kg to 100W/kg.



## COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.261.1.15.SATU.A

### 3.2 SENSITIVITY

The sensitivity factors of the three dipoles were determined using a two step calibration method (air and tissue simulating liquid) using waveguides as outlined in the standards.

### 3.3 LOWER DETECTION LIMIT

The lower detection limit was assessed using the same measurement set up as used for the linearity measurement. The required lower detection limit is 10 mW/kg.

### 3.4 ISOTROPY

The axial isotropy was evaluated by exposing the probe to a reference wave from a standard dipole with the dipole mounted under the flat phantom in the test configuration suggested for system validations and checks. The probe was rotated along its main axis from 0 - 360 degrees in 15 degree steps. The hemispherical isotropy is determined by inserting the probe in a thin plastic box filled with tissue-equivalent liquid, with the plastic box illuminated with the fields from a half wave dipole. The dipole is rotated about its axis (0°–180°) in 15° increments. At each step the probe is rotated about its axis (0°–360°).

### 3.5 BOUNDARY EFFECT

The boundary effect is defined as the deviation between the SAR measured data and the expected exponential decay in the liquid when the probe is oriented normal to the interface. To evaluate this effect, the liquid filled flat phantom is exposed to fields from either a reference dipole or waveguide. With the probe normal to the phantom surface, the peak spatial average SAR is measured and compared to the analytical value at the surface.

## 4 MEASUREMENT UNCERTAINTY

The guidelines outlined in the IEEE 1528, OET 65 Bulletin C, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty associated with an E-field probe calibration using the waveguide technique. All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

Uncertainty analysis of the probe calibration in waveguide					
ERROR SOURCES	Uncertainty value (%)	Probability Distribution	Divisor	ci	Standard Uncertainty (%)
Incident or forward power	3.00%	Rectangular	$\sqrt{3}$	1	1.732%
Reflected power	3.00%	Rectangular	$\sqrt{3}$	1	1.732%
Liquid conductivity	5.00%	Rectangular	$\sqrt{3}$	1	2.887%
Liquid permittivity	4.00%	Rectangular	$\sqrt{3}$	1	2.309%
Field homogeneity	3.00%	Rectangular	$\sqrt{3}$	1	1.732%
Field probe positioning	5.00%	Rectangular	$\sqrt{3}$	1	2.887%



## COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.261.1.15.SATU.A

Field probe linearity	3.00%	Rectangular	$\sqrt{3}$	1	1.732%
<b>Combined standard uncertainty</b>					5.831%
<b>Expanded uncertainty</b> 95 % confidence level k = 2					12.0%

## 5 CALIBRATION MEASUREMENT RESULTS

Calibration Parameters	
Liquid Temperature	21 °C
Lab Temperature	21 °C
Lab Humidity	45 %


### 5.1 SENSITIVITY IN AIR

Normx dipole 1 ( $\mu\text{V}/(\text{V}/\text{m})^2$ )	Normy dipole 2 ( $\mu\text{V}/(\text{V}/\text{m})^2$ )	Normz dipole 3 ( $\mu\text{V}/(\text{V}/\text{m})^2$ )
0.80	0.84	0.81

DCP dipole 1 (mV)	DCP dipole 2 (mV)	DCP dipole 3 (mV)
91	93	90

Calibration curves  $e_i=f(V)$  ( $i=1,2,3$ ) allow to obtain H-field value using the formula:

$$E = \sqrt{E_1^2 + E_2^2 + E_3^2}$$






**COMOSAR E-FIELD PROBE CALIBRATION REPORT**

Ref: ACR.261.1.15.SATU.A

**5.2 LINEARITY**



Linearity:  $\pm 1.31\%$  ( $\pm 0.06\text{dB}$ )

**5.3 SENSITIVITY IN LIQUID**

Liquid	Frequency (MHz $\pm$ 100MHz)	Permittivity	Epsilon (S/m)	ConvF
HL450	450	43.68	0.87	1.87
BL450	450	58.34	0.99	1.92
HL750	750	41.82	0.90	1.69
BL750	750	56.28	0.98	1.75
HL850	835	42.59	0.90	1.89
BL850	835	53.19	0.97	1.94
HL900	900	42.05	0.98	1.74
BL900	900	56.41	1.08	1.81
HL1800	1800	41.82	1.38	1.91
BL1800	1800	53.00	1.52	1.95
HL1900	1900	40.38	1.41	2.16
BL1900	1900	53.93	1.55	2.24
HL2000	2000	40.12	1.43	2.02
BL2000	2000	53.65	1.54	2.09
HL2450	2450	38.34	1.80	2.11
BL2450	2450	52.70	1.94	2.17
HL2600	2600	38.16	1.93	2.16
BL2600	2600	51.55	2.21	2.21
HL5200	5200	36.44	4.79	1.97
BL5200	5200	50.70	5.11	2.03
HL5400	5400	35.99	4.91	2.20
BL5400	5400	50.01	5.64	2.29
HL5600	5600	35.22	5.18	2.24
BL5600	5600	49.34	5.85	2.29
HL5800	5800	34.95	5.42	2.02
BL5800	5800	48.54	6.22	2.09

LOWER DETECTION LIMIT: 9mW/kg

Page: 7/10

*This document shall not be reproduced, except in full or in part, without the written approval of MVG.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.*






**COMOSAR E-FIELD PROBE CALIBRATION REPORT**

Ref: ACR.261.1.15.SATU.A

**5.4 ISOTROPY**


**HL900 MHz**

- Axial isotropy: 0.04 dB
- Hemispherical isotropy: 0.05 dB



**HL1800 MHz**

- Axial isotropy: 0.06 dB
- Hemispherical isotropy: 0.07 dB






**COMOSAR E-FIELD PROBE CALIBRATION REPORT**

Ref: ACR.261.1.15.SATU.A

**HL5600 MHz**

- Axial isotropy: 0.06 dB
- Hemispherical isotropy: 0.08 dB





## COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.261.1.15.SATU.A

### 6 LIST OF EQUIPMENT

Equipment Summary Sheet				
Equipment Description	Manufacturer / Model	Identification No.	Current Calibration Date	Next Calibration Date
Flat Phantom	MVG	SN-20/09-SAM71	Validated. No cal required.	Validated. No cal required.
COMOSAR Test Bench	Version 3	NA	Validated. No cal required.	Validated. No cal required.
Network Analyzer	Rhode & Schwarz ZVA	SN100132	02/2013	02/2016
Reference Probe	MVG	EP 94 SN 37/08	10/2014	10/2015
Multimeter	Keithley 2000	1188656	12/2013	12/2016
Signal Generator	Agilent E4438C	MY49070581	12/2013	12/2016
Amplifier	Aethercomm	SN 046	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Power Meter	HP E4418A	US38261498	12/2013	12/2016
Power Sensor	HP ECP-E26A	US37181460	12/2013	12/2016
Directional Coupler	Narda 4216-20	01386	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Waveguide	Mega Industries	069Y7-158-13-712	Validated. No cal required.	Validated. No cal required.
Waveguide Transition	Mega Industries	069Y7-158-13-701	Validated. No cal required.	Validated. No cal required.
Waveguide Termination	Mega Industries	069Y7-158-13-701	Validated. No cal required.	Validated. No cal required.
Temperature / Humidity Sensor	Control Company	11-661-9	8/2012	8/2015



## SAR Reference Dipole Calibration Report

Ref : ACR.139.4.15.SATU.A

**NTEK TESTING TECHNOLOGY CO., LTD.**  
**BUILDING E, FENDA SCIENCE PARK, SANWEI**  
**COMMUNITY, XIXIANG STREET,**  
**BAO'AN DISTRICT, SHENZHEN GUANGDONG, CHINA**  
**MVG COMOSAR REFERENCE DIPOLE**  
**FREQUENCY: 835 MHZ**  
**SERIAL NO.: SN 03/15 DIP 0G835-347**

**Calibrated at MVG US**  
**2105 Barrett Park Dr. - Kennesaw, GA 30144**



**04/06/2015**

### *Summary:*

This document presents the method and results from an accredited SAR reference dipole calibration performed in MVG USA using the COMOSAR test bench. All calibration results are traceable to national metrology institutions.





## SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.139.4.15.SATU.A

	<i>Name</i>	<i>Function</i>	<i>Date</i>	<i>Signature</i>
<i>Prepared by :</i>	Jérôme LUC	Product Manager	5/19/2015	<i>JS</i>
<i>Checked by :</i>	Jérôme LUC	Product Manager	5/19/2015	<i>JS</i>
<i>Approved by :</i>	Kim RUTKOWSKI	Quality Manager	5/19/2015	<i>Kim Rutkowski</i>

	<i>Customer Name</i>
<i>Distribution :</i>	NTEK TESTING TECHNOLOGY CO., LTD.

<i>Issue</i>	<i>Date</i>	<i>Modifications</i>
A	5/19/2015	Initial release



## SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.139.4.15.SATUA

## TABLE OF CONTENTS

1	Introduction.....	4
2	Device Under Test .....	4
3	Product Description .....	4
3.1	General Information .....	4
4	Measurement Method .....	5
4.1	Return Loss Requirements .....	5
4.2	Mechanical Requirements .....	5
5	Measurement Uncertainty .....	5
5.1	Return Loss .....	5
5.2	Dimension Measurement .....	5
5.3	Validation Measurement .....	5
6	Calibration Measurement Results .....	6
6.1	Return Loss and Impedance In Head Liquid .....	6
6.2	Return Loss and Impedance In Body Liquid .....	6
6.3	Mechanical Dimensions .....	6
7	Validation measurement .....	7
7.1	Head Liquid Measurement .....	7
7.2	SAR Measurement Result With Head Liquid .....	8
7.3	Body Liquid Measurement .....	9
7.4	SAR Measurement Result With Body Liquid .....	10
8	List of Equipment .....	12