

MPE TEST REPORT

Applicant	Deer Management Systems LLC
FCC ID	2BBNQ-DFDCAM1
Product	Defend Cam
Brand	Tactacam
Model	Defend Cam Gen 1
Report No.	R2404A0397-M1
Issue Date	May 28, 2024

Eurofins TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC 47 CFR Part 1 1.1310**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Prepared by: Wei Fangying

Approved by: Fan Guangchang

Eurofins TA Technology (Shanghai) Co., Ltd.

Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000

Table of Contents

1	Test Laboratory	3
1.1	Notes of the Test Report.....	3
1.2	Test Facility.....	3
1.3	Testing Location.....	3
1.4	Laboratory Environment	3
2	Description of Equipment Under Test	4
3	Maximum Tune up and Antenna Gain	5
4	MPE Limit.....	6
5	RF Exposure Evaluation Result.....	8
	ANNEX A: The EUT Appearance	9

1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **Eurofins TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2 Test Facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

1.3 Testing Location

Company: Eurofins TA Technology (Shanghai) Co., Ltd.
 Address: Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China
 City: Shanghai
 Post code: 201201
 Country: P. R. China
 Contact: Fan Guangchang
 Telephone: +86-021-50791141/2/3
 Fax: +86-021-50791141/2/3-8000
 Website: <https://www.eurofins.com/electrical-and-electronics>
 E-mail: Jack.Fan@cpt.eurofinscn.com

1.4 Laboratory Environment

Temperature	Min. = 18°C, Max. = 25°C
Relative humidity	Min. = 20%, Max. = 80%
Ground system resistance	< 0.5 Ω
Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards.	

2 Description of Equipment Under Test

Client Information

Applicant	Deer Management Systems LLC
Applicant address	1668 Jordan West Road Decorah Iowa United States
Manufacturer	Deer Management Systems LLC
Manufacturer address	1668 Jordan West Road Decorah Iowa United States

General Technologies

EUT Description			
Model	Defend Cam Gen 1		
Lab internal SN	R2404A0397/S01		
Hardware Version	P3		
Software Version	1.0		
Frequency	Band	TX (MHz)	RX (MHz)
	WCDMA Band II	1850 ~ 1910	1930 ~ 1990
	WCDMA Band IV	1710 ~ 1755	2110 ~ 2155
	WCDMA Band V	824 ~ 849	869 ~ 894
	LTE Band 2	1850 ~ 1910	1930 ~ 1990
	LTE Band 4	1710 ~ 1755	2110 ~ 2155
	LTE Band 5	824 ~ 849	869 ~ 894
	LTE Band 12	699 ~ 716	729 ~ 746
	LTE Band 13	777 ~ 787	746 ~ 756
	LTE Band 25	1850 ~ 1915	1930 ~ 1995
	LTE Band 26	814 ~ 849	859 ~ 894
	Bluetooth LE	2400 ~ 2483.5	2400 ~ 2483.5
	Wi-Fi 2.4G	2400 ~ 2483.5	2400 ~ 2483.5
Date of Testing	April 16, 2024 ~ May 7, 2024		
Date of Sample Received	April 15, 2024		
<p>Note:</p> <ol style="list-style-type: none"> The EUT is sent from the applicant to Eurofins TA and the information of the EUT is declared by the applicant. All indications of Pass/Fail in this report are opinions expressed by Eurofins TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. 			

3 Maximum Tune up and Antenna Gain

The numeric gain (G) of the antenna with a gain specified in dB is determined by

Numeric gain (G)=10^(antenna gain/10)

Band	Maximum Tune up Power		Antenna Gain (dBi)	Numeric Gain
	(dBm)	(mW)		
WCDMA Band II	24.00	251.189	4.59	2.877
WCDMA Band IV	24.00	251.189	3.01	2.000
WCDMA Band V	24.00	251.189	3.68	2.333
LTE Band 2	24.00	251.189	4.59	2.877
LTE Band 4	24.00	251.189	3.01	2.000
LTE Band 5	24.00	251.189	3.68	2.333
LTE Band 12	24.00	251.189	0.71	1.178
LTE Band 13	24.00	251.189	3.58	2.280
LTE Band 25	24.00	251.189	4.59	2.877
LTE Band26	24.00	251.189	4.44	2.780
Wi-Fi 2.4G	16.00	39.811	1.64	1.459
Bluetooth LE	5.00	3.162	2.98	1.986

4 MPE Limit

According to section 1.1310 of FCC 47 CFR Part 1, limits for maximum permissible exposure (MPE) are as following.

TABLE 1 – LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	f/300	6
1500-100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Note1. Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational / controlled limits apply provided he or she is made aware of the potential for exposure.

Note2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

The maximum permissible exposure for 300~1500 MHz is $f/1500$, for 1500~100,000MHz is 1.0. So

Band	The Maximum Permissible Exposure (mW/cm ²)
WCDMA Band II	1.000
WCDMA Band IV	1.000
WCDMA Band V	0.549
LTE Band 2	1.000
LTE Band 4	1.000
LTE Band 5	0.549
LTE Band 12	0.466
LTE Band 13	0.518
LTE Band 25	1.000
LTE Band 26	0.543
Wi-Fi 2.4GHz	1.000
Bluetooth LE	1.000

5 RF Exposure Evaluation Result

RF exposure evaluation method is based on KDB 447498 D01, this calculation is based on the conducted power, maximum power and antenna gain with provides the minimum separation distance. The formula shown below is from OET Bulletin 65 Edition 97-01 Per KDB 447498 D01:

$$S = PG / 4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm²)

P = Time-average maximum tune up procedure (in appropriate units, e.g., mW)

G = the numeric gain of the antenna

R = distance to the center of radiation of the antenna (20 cm = limit for MPE)

Band	Maximum Tune up (dBm)	Antenna Gain (dBi)	Maximum EIRP (dBm)	PG (mW)	Result (mW/cm ²)	Limit Value (mW/cm ²)	The MPE Ratio
WCDMA Band II	24.00	4.59	28.590	722.770	0.1438	1.000	0.144
WCDMA Band IV	24.00	3.01	27.010	502.343	0.100	1.000	0.100
WCDMA Band V	24.00	3.68	27.680	586.138	0.117	0.549	0.212
LTE Band 2	24.00	4.59	28.590	722.770	0.144	1.000	0.144
LTE Band 4	24.00	3.01	27.010	502.343	0.100	1.000	0.100
LTE Band 5	24.00	3.68	27.680	586.138	0.117	0.549	0.212
LTE Band 12	24.00	0.71	24.710	295.801	0.059	0.466	0.126
LTE Band 13	24.00	3.58	27.580	572.796	0.114	0.518	0.220
LTE Band 25	24.00	4.59	28.590	722.770	0.144	1.000	0.144
LTE Band 26	24.00	4.44	28.440	698.232	0.139	0.543	0.256
Wi-Fi 2.4GHz	16.00	1.64	17.640	58.076	0.012	1.000	0.012
Bluetooth LE	5.00	2.98	7.980	6.281	0.001	1.000	0.001
Note: R = 20cm $\pi = 3.1416$ The MPE Ratio = Mac Result ÷ Limit Value							

So the simultaneous transmitting antenna pairs as below:

∑ of MPE ratios = Main Antenna + Wi-Fi Antenna + Bluetooth LE Antenna = 0.256 + 0.012 + 0.001 = 0.269 < 1

Note: For transmitters, minimum separation distance is 20cm, even if calculations indicate MPE distance is less.

IMPORTANT NOTE: To comply with the FCC RF exposure compliance requirements, the antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter. No change to the antenna or the device is permitted. Any change to the antenna or the device could result in the device exceeding the RF exposure requirements and void user's authority to operate the device.

ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.

*******END OF REPORT *******