

## **FCC ID : 2AYMH-CT10-W0C3**

### **RF EXPOSURE EVALUATION**

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
<b>300-1500</b>	--	--	<b>F/300</b>	<b>6</b>
<b>1500-100000</b>	--	--	<b>5</b>	<b>6</b>
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
<b>300-1500</b>	--	--	<b>F/1500</b>	<b>6</b>
<b>1500-100000</b>	--	--	<b>1</b>	<b>30</b>

#### **11.1 Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$**

Where

$P_d$ = Power density in mW/cm<sup>2</sup>

$P_{out}$ =output power to antenna in mW

$G$ = Numeric gain of the antenna relative to isotropic antenna

$\pi$ =3.1416

$R$ = distance between observation point and center of the radiator in cm

$P_d$  the limit of MPE, 1mW/cm<sup>2</sup>, If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

RF Exposure Information: The radiated output power of this device meets the limits of FCC/IC radio frequency exposure limits. This device should be operated with a minimum separation distance of 20cm (8 inches) between the equipment and a person's body.

## 11.2 Measurement Result

Mode	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain (dBi)	Antenna Gain Numeric	Evaluation result (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
BT	4.45	4 to 5	5	1	1.26	0.0008	1
BLE	-0.99	-1 to 0	0	1	1.26	0.0003	1
2.4G WiFi	14.20	14 to 15	15	1.8	1.51	0.0095	1
5G WiFi	15.71	15 to 16	16	1.4	1.38	0.0109	1

SRD 2.4G, Antenna Gain:1.5dBi

Operation Mode	Emission Level(dBuV/m)	EIRP (dBm)	Max power (mW)	Max tune-up power (dBm)	Antenna Gain Numeric
SRD	98.11	2.88	0.28	2.88	1
Evaluation result (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )				
0.00039	1				
* EIRP[dBm] = E[dBuV/m] + 20 log(d[meters]) - 104.77					

RFID 13.56MHz, Antenna Gain: 0dBi

Operation Mode	Channel Number	Channel Frequency (MHz)	Emission Level(dBuV/m)	EIRP (dBm)	Max power (mW)
RFID	1	13.56	49.52	-45.71	0
Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )		
0	1	0.0002	1		
* EIRP[dBm] = E[dBuV/m] + 20 log(d[meters]) - 104.77					

## MAX RF EXPOSURE EVALUATION

Wifi 5G	RFID	BT	SRD	Summation of Evaluation result (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
0.0109	0.0002	0.0008	0.00039	0.01229	<1

