

TEST REPORT

Reference No...... : WTF24D10230966W002 V1
FCC ID : 2A6UA-BM04-A
Applicant..... : Hong Kong Lute Technology Co., Limited
Address..... : Room 02, 21/F, Hip Kwan Commercial, Building,38 Pitt Street, Yau Ma Tei, Kowloon, Hong Kong
Manufacturer : Hong Kong Lute Technology Co., Limited
Address..... : Room 02, 21/F, Hip Kwan Commercial, Building,38 Pitt Street, Yau Ma Tei, Kowloon, Hong Kong
Product..... : Video Baby Monitor (Camera)
Model(s) : BM04
Standards..... : FCC 47CFR Part 15.247
Date of Receipt sample : 2024-10-16
Date of Test : 2024-10-16 to 2024-11-26
Date of Issue..... : 2024-12-10
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Testing Group Co., Ltd.

Address: No. 77, Houjie Section, Guantai Road, Houjie Town, Dongguan City, Guangdong, China

Tel: +86-769-2267 6998

Fax: +86-769-2267 6828

Compiled by:

James Cheng

James Cheng / Project Engineer

Approved by:



Devalgin / Designated Reviewer

2 Contents

	Page
1 COVER PAGE	1
2 CONTENTS	2
3 REVISION HISTORY	4
4 GENERAL INFORMATION	5
4.1 General Description of E.U.T.	5
4.2 Details of E.U.T.	5
4.3 Channel List	5
4.4 Test Facility	6
4.5 Subcontracted	6
4.6 Abnormalities from Standard Conditions	6
4.7 Test Mode	7
5 TEST SUMMARY	8
6 EQUIPMENT USED DURING TEST	9
6.1 Equipments List	9
6.2 Description of Support Units	10
6.3 Measurement Uncertainty	10
6.4 Test Equipment Calibration	10
7 DUTY CYCLE	11
8 CONDUCTED EMISSION	14
8.1 E.U.T. Operation	14
8.2 EUT Setup	14
8.3 Measurement Description	15
8.4 Conducted Emission Test Result	15
9 RADIATED EMISSIONS	17
9.1 EUT Operation	17
9.2 Test Setup	18
9.3 Spectrum Analyzer Setup	19
9.4 Test Procedure	20
9.5 Corrected Amplitude & Margin Calculation	20
9.6 Summary of Test Results	21
10 CONDUCTED SPURIOUS EMISSIONS	24
10.1 Test Procedure	24
10.2 Test Result	25
11 BAND EDGE MEASUREMENT	49
11.1 Test Produce	49
11.2 Test Result	50
12 6 DB BANDWIDTH AND 99% BANDWIDTH MEASUREMENT	54
12.1 Test Procedure	54
12.2 Test Result	54
13 MAXIMUM CONDUCTED OUTPUT POWER	68
13.1 Test Procedure	68
13.2 Test Result	68
14 POWER SPECTRAL DENSITY	78

14.1 Test Procedure78

14.2 Test Result.....78

15 ANTENNA REQUIREMENT88

16 RF EXPOSURE88

17 PHOTOGRAPHS OF TEST SETUP AND EUT.....88

3 Revision History

Test Report No.	Date of Receipt Sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTF24D10230966W002	2024-10-16	2024-10-16 to 2024-11-26	2024-11-26	Original	-	Replaced
WTF24D10230966W002 V1	2024-10-16	2024-10-16 to 2024-11-26	2024-12-10	Version 1	Updated	Valid

4 General Information

4.1 General Description of E.U.T.

Product:	Video Baby Monitor (Camera)
Model(s):	BM04
Model Description:	N/A
Wi-Fi Specification:	2.4G-802.11b/g/n HT20/n HT40
Hardware Version:	BM04-TX-MAIN-01B-1
Software Version:	v1.1.1-2411221351

4.2 Details of E.U.T.

Operation Frequency:	802.11b/g/n (HT20), 2412-2462MHz 11CH 802.11n (HT40), 2422-2452MHz 7CH
Max. RF output power:	Ant.0: 19.87dBm, Ant.1: 19.49dBm, Total: 21.45dBm Max.
Type of Modulation:	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11n: OFDM (BPSK, QPSK, 16QAM, 64QAM)
Antenna installation:	ANT 0: Steel Plate Antenna ANT 1: Copper Tube Antenna
Antenna Gain:	ANT 0: 2.12dBi ANT 1: 2.75dBi
Ratings:	Input: DC 5V 2A MODEL: XSC-0502000SU
Adapter:	INPUT: 100-240V, 50/60Hz 0.4A OUTPUT: 5V, 2A

4.3 Channel List

Wi-Fi

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2412	2	2417	3	2422	4	2427
5	2432	6	2437	7	2442	8	2447
9	2452	10	2457	11	2462	-	-

4.4 Test Facility

The test facility has a test site registered with the following organizations:

ISED CAB identifier: CN0013. Test Firm Registration No.: 7760A.

Waltek Testing Group Co., Ltd. Has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files.

Registration number 7760A, October 15, 2016.

FCC Designation No.: CN1201. Test Firm Registration No.: 523476.

Waltek Testing Group Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration number 523476, September 10, 2019.

4.5 Subcontracted

Whether parts of tests for the product have been subcontracted to other labs:

☐ Yes ☒ No

If Yes, list the related test items and lab information:

Test Lab: N/A

Lab address: N/A

Test items: N/A

4.6 Abnormalities from Standard Conditions

None.

4.7 Test Mode

Tests Carried Out Under FCC part 15.247

Test Items	Mode	Data Rate	Channel	TX/RX
Maximum Conducted Output Power	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX
Power Spectral Density	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX
6 dB Bandwidth and 99% Bandwidth	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX
Band Edge	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX
Transmitter Spurious Emissions	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX

Note: Parameters set by test software during channel & power tests, the software provided by the applicant was used to set the operating channels as well as the maximum output power level. The RF output power set is the power expected by the manufacturer and is going to be fixed on the firmware of the final product.

5 Test Summary

Test Items	Test Requirement	Result
Radiated Emissions	15.247(d) 15.205(a) 15.209(a)	PASS
Conducted Spurious Emissions	15.247(d)	PASS
Conducted Emissions	15.207(a)	PASS
6 dB Bandwidth and 99% Bandwidth	15.247(a)(2)	PASS
Maximum Output Power	15.247(b)(3), (4)	PASS
Power Spectral Density	15.247(e)	PASS
Band Edge	15.247(d)	PASS
Antenna Requirement	15.203	PASS
RF Exposure	1.1307(b)(1)	PASS
Note: Pass=Compliance; NC=Not Compliance; NT=Not Tested; N/A=Not Applicable.		

6 Equipment Used during Test

6.1 Equipments List

Conducted Emissions Test Site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	EMI Test Receiver	R&S	ESCI	101155	2024-07-18	2025-07-17
2	LISN	SCHWARZBECK	NSLK 8128	8128-259	2024-10-10	2025-10-09
3	Limiter	CYBERTEK	EM5010	261115-001-0024	2024-07-18	2025-07-17
4	Cable	Laplace	RF300	-	2024-07-18	2025-07-17
3m Semi-anechoic Chamber for Radiation Emissions Test site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	Spectrum Analyzer	R&S	FSP30	100091	2024-04-22	2025-04-21
2	Amplifier	Agilent	8447D	2944A10178	2024-07-18	2025-07-17
3	Trilog Broadband Antenna	SCHWARZBECK	VULB9163	336	2024-07-21	2025-07-20
4	Coaxial Cable (below 1GHz)	Top	TYPE16(13M)	-	2024-04-22	2025-04-21
5	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	667	2024-01-23	2025-01-22
6	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9170	335	2024-07-18	2025-07-17
7	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	2024-07-18	2025-07-17
8	Coaxial Cable (above 1GHz)	ZT26-NJ-NJ-8M/FA	1GHz-18GHz	NA	2024-04-22	2025-04-21
3m Semi-anechoic Chamber for Radiation Emissions Test site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	Test Receiver	R&S	ESCI	101296	2024-04-22	2025-04-21
2	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	2024-07-18	2025-07-17
3	Active Loop Antenna	Com-Power Corp.	AL-130R	10160007	2024-04-27	2025-04-26
4	Amplifier	ANRITSU	MH648A	M43381	2024-04-22	2025-04-21
5	Cable	HUBER+SUHNER	CBL2	525178	2024-04-22	2025-04-21
RF Conducted Testing						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	Spectrum Analyzer	R&S	FSP40	100501	2024-07-18	2025-07-17
2.	EXA Signal Analyzer	Malaysia Keysight	N9010A	MY50520207	2024-04-22	2025-04-21

6.2 Description of Support Units

Equipment	Manufacturer	Model No.	Series No.
/	/	/	/

6.3 Measurement Uncertainty

Parameter	Uncertainty
Conducted Emission	$\pm 3.64\text{dB}$ (AC mains 150KHz~30MHz)
Radiated Spurious Emissions	$\pm 5.08\text{dB}$ (Bilog antenna 30M~1000MHz)
	$\pm 5.47\text{ dB}$ (Horn antenna 1000M~25000MHz)
Radio Frequency	$\pm 1 \times 10^{-7}\text{Hz}$
RF Power	$\pm 0.42\text{ dB}$
RF Power Density	$\pm 0.7\text{dB}$
Conducted Spurious Emissions	$\pm 2.76\text{ dB}$ (9kHz~26500MHz)
Confidence interval: 95%. Confidence factor: k=2	

6.4 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R. China.

7 Duty Cycle

ANT 0:

Type of Modulation	On time ms	Period ms	Duty Cycle linear	Duty Cycle %	Duty Cycle Factor(dB)	Average Factor(dB)
802.11b	4.300	4.420	0.97	97.29	0.12	-0.24
802.11g	0.708	0.750	0.94	94.40	0.25	-0.50
802.11n-HT20	0.666	0.714	0.93	93.28	0.30	-0.60
802.11n-HT40	0.340	0.384	0.89	88.54	0.53	-1.06

ANT 1:

Type of Modulation	On time ms	Period ms	Duty Cycle linear	Duty Cycle %	Duty Cycle Factor(dB)	Average Factor(dB)
802.11b	4.285	4.410	0.97	97.17	0.12	-0.25
802.11g	0.705	0.750	0.94	94.00	0.27	-0.54
802.11n-HT20	0.670	0.710	0.94	94.37	0.25	-0.50
802.11n-HT40	0.340	0.385	0.88	88.31	0.54	-1.08

Remark:


Duty cycle=On Time/period;

Duty cycle factor= $10 \cdot \log(1/\text{Duty cycle})$;

Average factor= $20 \log_{10} \text{Duty cycle}$


ANT 0:

Wi-Fi 802.11b




Date: 24.OCT.2024 14:28:00

Wi-Fi 802.11g




Date: 24.OCT.2024 12:10:28

Wi-Fi 802.11n-HT20



Date: 24.OCT.2024 12:11:11


Wi-Fi 802.11n-HT40



Date: 24.OCT.2024 12:12:03


ANT 1:

Wi-Fi 802.11b




Date: 24.OCT.2024 16:30:18

Wi-Fi 802.11g




Date: 24.OCT.2024 16:29:19

Wi-Fi 802.11n-HT20



Date: 24.OCT.2024 16:30:36

Wi-Fi 802.11n-HT40



Date: 24.OCT.2024 16:25:44

8 Conducted Emission

Test Requirement: 47CFR FCC Part15 Subpart C §15.207

Test Method: ANSI C63.10:2013

Test Result: PASS

Frequency Range: 150kHz to 30MHz

Limit:

Frequency (MHz)	Conducted Limit (dB μ V)	
	Quasi peak	Average
0.15 to 0.5	6 to 56*	56 to 46*
0.5 to 5.0	56	46
.0 to 30	60	50

*Decreases with the logarithm of the frequency.

8.1 E.U.T. Operation

Operating Environment:

Temperature: 22.3 °C

Humidity: 38.5 % RH


Atmospheric Pressure: 101.2kPa

EUT Operation:

The test was performed in Transmitting mode, the worst test data were shown in the report.

8.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10:2013.




8.3 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

8.4 Conducted Emission Test Result


Remark: only the worst data (Ant. 0+ Ant. 1 TX 11b mode High channel mode) were reported

Live line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1499	33.84	9.52	43.36	66.00	-22.64	QP	
2	0.1499	18.63	9.52	28.15	56.00	-27.85	AVG	
3	0.6060	28.65	9.60	38.25	56.00	-17.75	QP	
4	0.6060	25.68	9.60	35.28	46.00	-10.72	AVG	
5	0.6340	32.03	9.60	41.63	56.00	-14.37	QP	
6	0.6340	26.67	9.60	36.27	46.00	-9.73	AVG	
7	15.5859	34.53	10.12	44.65	60.00	-15.35	QP	
8	15.5859	25.55	10.12	35.67	50.00	-14.33	AVG	
9	17.0739	33.25	10.13	43.38	60.00	-16.62	QP	
10	17.0739	25.03	10.13	35.16	50.00	-14.84	AVG	
11	18.5579	34.43	10.14	44.57	60.00	-15.43	QP	
12	18.5579	25.38	10.14	35.52	50.00	-14.48	AVG	

Neutral line:



9 Radiated Emissions

Test Requirement: 47CFR FCC Part15 Subpart C §15.209&15.247
KDB 662911 D01 Multiple Transmitter Output v02r01, October 31, 2013

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02, April 2, 2019;
ANSI C63.10:2013

Test Result: PASS

Measurement Distance: 3m

Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	$20\log^{(2400/F(kHz))} + 80$
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	$20\log^{(24000/F(kHz))} + 40$
1.705 ~ 30	30	30	100 * 30	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

9.1 EUT Operation

Operating Environment:

Temperature: 23.5 °C

Humidity: 52.1 % RH

Atmospheric Pressure: 101.2kPa


EUT Operation:

The test was performed in Transmitting mode, the worst test data were shown in the report.


9.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



9.3 Spectrum Analyzer Setup

Below 30MHz

Sweep Speed Auto
IF Bandwidth..... 10kHz
Video Bandwidth..... 10kHz
Resolution Bandwidth..... 10kHz

30MHz ~ 1GHz

Sweep Speed Auto
Detector PK
Resolution Bandwidth..... 100kHz
Video Bandwidth..... 300kHz

Above 1GHz

Sweep Speed Auto
Detector PK
Resolution Bandwidth..... 1MHz
Video Bandwidth..... 3MHz
Detector Ave.
Resolution Bandwidth..... 1MHz
Video Bandwidth..... 10Hz

9.4 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane for below 1GHz and 1.5m for above 1GHz.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are performed in X, Y and Z axis positioning (X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), the worst condition was tested putting the EUT in Z axis, so the worst data were shown as follow.
8. A 2.4GHz high –pass filter is used during radiated emissions above 1GHz measurement.

9.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

9.6 Summary of Test Results

Note:

Only the worst-case 802.11n HT20 mode were record in the report.

Test Mode: TX (Ant. 0+ Ant. 1)

Test Frequency: 9kHz ~ 30MHz

The measurements were more than 20 dB below the limit and not reported.

Test Frequency: 30MHz ~ 8GHz

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11n HT20: Low Channel 2412MHz									
241.85	38.72	QP	252	1.8	H	-13.21	25.51	46.00	-20.49
241.85	45.66	QP	161	1.3	V	-13.21	32.45	46.00	-13.55
4824.00	60.66	PK	280	1.8	V	-1.06	59.60	74.00	-14.40
4824.00	45.93	Ave	280	1.8	V	-1.06	44.87	54.00	-9.13
7236.00	52.13	PK	349	1.7	H	1.33	53.46	74.00	-20.54
7236.00	34.71	Ave	349	1.7	H	1.33	36.04	54.00	-17.96
2327.11	45.98	PK	72	2.0	V	-13.19	32.79	74.00	-41.21
2327.11	38.94	Ave	72	2.0	V	-13.19	25.75	54.00	-28.25
2388.03	43.56	PK	62	1.3	H	-13.14	30.42	74.00	-43.58
2388.03	38.13	Ave	62	1.3	H	-13.14	24.99	54.00	-29.01
2495.81	43.27	PK	227	1.7	V	-13.08	30.19	74.00	-43.81
2495.81	37.57	Ave	227	1.7	V	-13.08	24.49	54.00	-29.51

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11n HT20: Middle Channel 2437MHz									
241.85	40.22	QP	353	1.9	H	-13.21	27.01	46.00	-18.99
241.85	44.21	QP	228	2.0	V	-13.21	31.00	46.00	-15.00
4874.00	61.01	PK	224	1.6	V	-0.62	60.39	74.00	-13.61
4874.00	46.18	Ave	224	1.6	V	-0.62	45.56	54.00	-8.44
7311.00	53.32	PK	292	1.8	H	2.21	55.53	74.00	-18.47
7311.00	34.96	Ave	292	1.8	H	2.21	37.17	54.00	-16.83
2317.01	46.31	PK	102	1.0	V	-13.19	33.12	74.00	-40.88
2317.01	38.62	Ave	102	1.0	V	-13.19	25.43	54.00	-28.57
2372.52	44.36	PK	78	1.4	H	-13.14	31.22	74.00	-42.78
2372.52	37.73	Ave	78	1.4	H	-13.14	24.59	54.00	-29.41
2492.07	42.45	PK	343	1.0	V	-13.08	29.37	74.00	-44.63
2492.07	38.34	Ave	343	1.0	V	-13.08	25.26	54.00	-28.74

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11n HT20: High Channel 2462MHz									
241.85	41.53	QP	185	1.8	H	-13.21	28.32	46.00	-17.68
241.85	43.47	QP	274	1.9	V	-13.21	30.26	46.00	-15.74
4924.00	61.84	PK	269	1.7	V	-0.24	61.60	74.00	-12.40
4924.00	44.72	Ave	269	1.7	V	-0.24	44.48	54.00	-9.52
7386.00	53.35	PK	19	2.0	H	2.84	56.19	74.00	-17.81
7386.00	33.99	Ave	19	2.0	H	2.84	36.83	54.00	-17.17
2346.17	46.36	PK	317	1.9	V	-13.19	33.17	74.00	-40.83
2346.17	39.18	Ave	317	1.9	V	-13.19	25.99	54.00	-28.01
2363.83	44.25	PK	97	1.9	H	-13.14	31.11	74.00	-42.89
2363.83	38.61	Ave	97	1.9	H	-13.14	25.47	54.00	-28.53
2486.22	43.60	PK	335	1.9	V	-13.08	30.52	74.00	-43.48
2486.22	37.27	Ave	335	1.9	V	-13.08	24.19	54.00	-29.81

Test Frequency: 8GHz~25GHz

The measurements were more than 20 dB below the limit and not reported.

10 Conducted Spurious Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.247
KDB 662911 D01 Multiple Transmitter Output v02r01, October 31, 2013
Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019;
ANSI C63.10:2013
Test Result: PASS

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

10.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;

2. Set the spectrum analyzer:

Below 30MHz:

RBW = 100kHz, VBW = 300kHz, Sweep = auto

Detector function = peak, Trace = max hold

Above 30MHz:

RBW = 100kHz, VBW = 300kHz, Sweep = auto

Detector function = peak, Trace = max hold


10.2 Test Result

ANT 0


9kHz – 150kHz

Mode: TX 11b channel 1

Mode: TX 11b channel 6




Date: 24.OCT.2024 15:11:35




Date: 24.OCT.2024 15:12:15

Mode: TX 11b channel 11




Date: 24.OCT.2024 15:12:36

Mode: TX 11g channel 1




Date: 24.OCT.2024 15:11:05

Mode: TX 11g channel 6




Date: 24.OCT.2024 15:10:34

Mode: TX 11g channel 11




Date: 24.OCT.2024 15:10:09

Mode: TX 11n HT20 channel 1




Date: 24.OCT.2024 15:08:50

Mode: TX 11 n HT20 channel 6




Date: 24.OCT.2024 15:09:12

Mode: TX 11 n HT20 channel 11




Date: 24.OCT.2024 15:09:30

Mode: TX 11n HT40 channel 3




Date: 24.OCT.2024 15:07:57

Mode: TX 11 n HT40 channel 6



Date: 24.OCT.2024 15:07:35


Mode: TX 11 n HT40 channel 9



Date: 24.OCT.2024 15:07:11


150kHz – 30MHz

Mode: TX 11b channel 1




Date: 24.OCT.2024 15:01:53

Mode: TX 11b channel 6




Date: 24.OCT.2024 15:01:31

Mode: TX 11b channel 11




Date: 24.OCT.2024 15:01:12

Mode: TX 11g channel 1




Date: 24.OCT.2024 15:02:19

Mode: TX 11g channel 6




Date: 24.OCT.2024 15:03:52

Mode: TX 11g channel 11




Date: 24.OCT.2024 15:04:13

Mode: TX 11n HT20 channel 1




Date: 24.OCT.2024 15:05:18

Mode: TX 11 n HT20 channel 6




Date: 24.OCT.2024 15:04:58

Mode: TX 11 n HT20 channel 11




Date: 24.OCT.2024 15:04:29

Mode: TX 11n HT40 channel 3




Date: 24.OCT.2024 15:05:43

Mode: TX 11 n HT40 channel 6



Date: 24.OCT.2024 15:06:04

Mode: TX 11 n HT40 channel 9




Date: 24.OCT.2024 15:06:29

Above 30MHz


Mode: TX 11b channel 1

Fundamental




Mode: TX 11b channel 6

Fundamental




Mode: TX 11b channel 11

Fundamental




Mode: TX 11g channel 1




Date: 24.OCT.2024 14:21:17

Mode: TX 11g channel 6




Date: 24.OCT.2024 14:18:31

Mode: TX 11g channel 11




Date: 24.OCT.2024 14:17:41

Mode: TX 11n HT20 channel 1




Date: 24.OCT.2024 14:15:05

Mode: TX 11 n HT20 channel 6




Date: 24.OCT.2024 14:15:05

Mode: TX 11 n HT20 channel 11




Date: 24.OCT.2024 14:16:34


Mode: TX 11n HT40 channel 3



Mode: TX 11 n HT40 channel 6




Mode: TX 11 n HT40 channel 9



ANT 1


9kHz – 150kHz

Mode: TX 11b channel 1




Date: 24.OCT.2024 17:05:00

Mode: TX 11b channel 6




Date: 24.OCT.2024 17:05:16

Mode: TX 11b channel 11




Date: 24.OCT.2024 17:05:30

Mode: TX 11g channel 1




Date: 24.OCT.2024 17:04:44

Mode: TX 11g channel 6




Date: 24.OCT.2024 17:04:27

Mode: TX 11g channel 11




Date: 24.OCT.2024 17:04:09

Mode: TX 11n HT20 channel 1




Date: 24.OCT.2024 17:03:25

Mode: TX 11 n HT20 channel 6




Date: 24.OCT.2024 17:03:39

Mode: TX 11 n HT20 channel 11




Date: 24.OCT.2024 17:03:53

Mode: TX 11n HT40 channel 3




Date: 24.OCT.2024 17:02:56

Mode: TX 11 n HT40 channel 6



Date: 24.OCT.2024 17:02:43


Mode: TX 11 n HT40 channel 9



Date: 24.OCT.2024 17:02:17


150kHz – 30MHz

Mode: TX 11b channel 1




Date: 24.OCT.2024 16:58:04

Mode: TX 11b channel 6




Date: 24.OCT.2024 16:57:49

Mode: TX 11b channel 11




Date: 24.OCT.2024 16:57:31

Mode: TX 11g channel 1




Date: 24.OCT.2024 16:58:24

Mode: TX 11g channel 6




Date: 24.OCT.2024 16:58:52

Mode: TX 11g channel 11




Date: 24.OCT.2024 16:59:16

Mode: TX 11n HT20 channel 1




Date: 24.OCT.2024 17:00:36

Mode: TX 11 n HT20 channel 6




Date: 24.OCT.2024 17:00:11

Mode: TX 11 n HT20 channel 11




Date: 24.OCT.2024 16:59:55

Mode: TX 11n HT40 channel 3




Date: 24.OCT.2024 17:00:56

Mode: TX 11 n HT40 channel 6



Date: 24.OCT.2024 17:01:17

Mode: TX 11 n HT40 channel 9




Date: 24.OCT.2024 17:01:42

Above 30MHz

Mode: TX 11b channel 1


Fundamental



Date: 24.OCT.2024 16:41:02

Mode: TX 11b channel 6


Fundamental



Date: 24.OCT.2024 16:51:02


Mode: TX 11b channel 11

Fundamental




Date: 24.OCT.2024 16:53:10

Mode: TX 11g channel 1




Date: 24.OCT.2024 16:33:27

Mode: TX 11g channel 6




Date: 24.OCT.2024 16:34:03

Mode: TX 11g channel 11




Date: 24.OCT.2024 16:34:55

Mode: TX 11n HT20 channel 1




Date: 24.OCT.2024 16:37:26

Mode: TX 11 n HT20 channel 6




Date: 24.OCT.2024 16:36:25

Mode: TX 11 n HT20 channel 11




Date: 24.OCT.2024 16:35:41

Mode: TX 11n HT40 channel 3




Date: 24.OCT.2024 16:38:16

Mode: TX 11 n HT40 channel 6



Date: 24.OCT.2024 16:38:53

Mode: TX 11 n HT40 channel 9



Date: 24.OCT.2024 16:39:47

11 Band Edge Measurement

Test Requirement:	47CFR FCC Part15 Subpart C §15.247 KDB 662911 D01 Multiple Transmitter Output v02r01, October 31, 2013
Test Method:	KDB 558074 D01 15.247 Meas Guidance v05r02, April 2, 2019 Regulation 15.247 (d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
Test Limit:	
Test Mode:	Transmitting


11.1 Test Produce

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

11.2 Test Result


Ant. 0

TX 11b: Band edge-left side




Date: 24.OCT.2024 14:23:25

TX 11b: Band edge-right side




Date: 24.OCT.2024 14:42:20

TX 11g: Band edge-left side




Date: 24.OCT.2024 12:19:53

TX 11g: Band edge-right side




Date: 24.OCT.2024 12:20:53

TX 11n HT20: Band edge-left side




Date: 24.OCT.2024 12:19:09

TX 11n HT20: Band edge-right side




Date: 24.OCT.2024 12:21:46

TX 11n HT40: Band edge-left side



Date: 24.OCT.2024 12:12:54


TX 11n HT40: Band edge-right side



Date: 24.OCT.2024 12:22:35


Ant. 1

TX 11b: Band edge-left side




Date: 24.OCT.2024 16:41:40

TX 11b: Band edge-right side




Date: 24.OCT.2024 16:54:13

TX 11g: Band edge-left side




Date: 24.OCT.2024 16:22:02

TX 11g: Band edge-right side




Date: 24.OCT.2024 16:21:05

TX 11n HT20: Band edge-left side




Date: 24.OCT.2024 16:24:02

TX 11n HT20: Band edge-right side




Date: 24.OCT.2024 16:20:31

TX 11n HT40: Band edge-left side



Date: 24.OCT.2024 16:24:46

TX 11n HT40: Band edge-right side



Date: 24.OCT.2024 16:18:17

12 6 dB Bandwidth and 99% Bandwidth Measurement

Test Requirement:	47CFR FCC Part15 Subpart C §15.247 KDB 662911 D01 Multiple Transmitter Output v02r01, October 31, 2013
Test Method:	ANSI C63.10:2013 KDB 558074 D01 15.247 Meas Guidance v05r02, April 2, 2019
Test Limit:	§15.247(a)(2) Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.
Test Mode:	Transmitting

12.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. 6dB Bandwidth Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz
99% Bandwidth Set the spectrum analyzer: 1~5% of the OBW, VBW = 3 times the RBW

12.2 Test Result

Ant. 0

Operation mode	Test Channel	6dB Bandwidth (MHz)	99% Bandwidth (MHz)
TX 11b	Channel 1	10.080	12.900
	Channel 6	10.080	12.900
	Channel 11	10.080	12.960
TX 11g	Channel 1	16.380	16.800
	Channel 6	16.380	16.800
	Channel 11	16.380	16.920
TX 11n HT20	Channel 1	17.160	17.700
	Channel 6	17.460	17.640
	Channel 11	17.240	17.760
TX 11n HT40	Channel 3	35.520	36.240
	Channel 6	35.640	36.240
	Channel 9	35.520	36.240

Ant. 1


Operation mode	Test Channel	6dB Bandwidth (MHz)	99% Bandwidth (MHz)
TX 11b	Channel 1	10.140	13.200
	Channel 6	10.140	13.200
	Channel 11	10.140	13.200
TX 11g	Channel 1	16.440	16.860
	Channel 6	16.440	16.860
	Channel 11	16.440	16.860
TX 11n HT20	Channel 1	17.520	17.760
	Channel 6	17.520	17.760
	Channel 11	17.460	17.760
TX 11n HT40	Channel 3	35.720	36.480
	Channel 6	35.720	36.360
	Channel 9	35.880	36.360

Test result plot:
Ant. 0


6 dB Bandwidth

99% Bandwidth

Mode: TX 11b channel 1




Date: 24.OCT.2024 14:24:44




Date: 24.OCT.2024 14:25:06

Mode: TX 11b channel 6



Date: 24.OCT.2024 14:34:33





Date: 24.OCT.2024 14:35:00

6 dB Bandwidth

99% Bandwidth



Mode: TX 11b channel 11



Date: 24.OCT.2024 14:47:20

Date: 24.OCT.2024 14:47:51

Mode: TX 11g channel 1




Date: 24.OCT.2024 11:28:49

Date: 24.OCT.2024 11:38:37


6 dB Bandwidth

99% Bandwidth

Mode: TX 11g channel 6




Date: 24.OCT.2024 11:31:17




Date: 24.OCT.2024 11:45:01

Mode: TX 11g channel 11



Date: 24.OCT.2024 11:32:24





Date: 24.OCT.2024 11:33:46

6 dB Bandwidth

99% Bandwidth



Mode: TX 11n HT20 channel 1



Date: 24.OCT.2024 11:27:32

Date: 24.OCT.2024 11:45:42

Mode: TX 11n HT20 channel 6





Date: 24.OCT.2024 11:26:27

Date: 24.OCT.2024 11:50:50

6 dB Bandwidth

99% Bandwidth



Mode: TX 11n HT20 channel 11



Date: 24.OCT.2024 11:25:05

Date: 24.OCT.2024 11:50:16

Mode: TX 11n HT40 channel 3





Date: 24.OCT.2024 11:21:12

Date: 24.OCT.2024 11:51:54

6 dB Bandwidth

99% Bandwidth



Mode: TX 11n HT40 channel 6



Date: 24.OCT.2024 11:22:09

Date: 24.OCT.2024 11:52:27

Mode: TX 11n HT40 channel 9



Date: 24.OCT.2024 11:23:03


Date: 24.OCT.2024 11:53:36

Ant. 1


6 dB Bandwidth

99% Bandwidth

Mode: TX 11b channel 1




Date: 24.OCT.2024 16:43:13




Date: 24.OCT.2024 16:43:38

Mode: TX 11b channel 6



Date: 24.OCT.2024 16:49:11




Date: 24.OCT.2024 16:47:35


6 dB Bandwidth

99% Bandwidth

Mode: TX 11b channel 11




Date: 24.OCT.2024 16:56:46




Date: 24.OCT.2024 16:56:00

Mode: TX 11g channel 1



Date: 24.OCT.2024 15:46:16





Date: 24.OCT.2024 16:10:49

6 dB Bandwidth

99% Bandwidth



Mode: TX 11g channel 6



Date: 24.OCT.2024 15:47:31

Date: 24.OCT.2024 16:10:13

Mode: TX 11g channel 11





Date: 24.OCT.2024 15:48:52

Date: 24.OCT.2024 16:09:37

6 dB Bandwidth

99% Bandwidth



Mode: TX 11n HT20 channel 1



Date: 24.OCT.2024 15:59:25

Date: 24.OCT.2024 16:06:25

Mode: TX 11n HT20 channel 6





Date: 24.OCT.2024 15:58:17

Date: 24.OCT.2024 16:08:23

6 dB Bandwidth

99% Bandwidth



Mode: TX 11n HT20 channel 11



Date: 24.OCT.2024 15:51:27

Date: 24.OCT.2024 16:09:00

Mode: TX 11n HT40 channel 3




Date: 24.OCT.2024 16:00:55

Date: 24.OCT.2024 16:05:15


6 dB Bandwidth

99% Bandwidth

Mode: TX 11n HT40 channel 6




Date: 24.OCT.2024 16:01:48




Date: 24.OCT.2024 16:04:01

Mode: TX 11n HT40 channel 9



Date: 24.OCT.2024 16:02:33



Date: 24.OCT.2024 16:03:07

13 Maximum Conducted Output Power

Test Requirement:	47CFR FCC Part15 Subpart C §15.247 KDB 662911 D01 Multiple Transmitter Output v02r01, October 31, 2013
Test Method:	ANSI C63.10:2013 KDB 558074 D01 15.247 Meas Guidance v05r02, April 2, 2019
Test Limit:	§15.247(b) The maximum peak conducted output power of the intentional radiator shall not exceed 1W.
Test Mode:	Transmitting

13.1 Test Procedure

According to KDB 558074 D01 15.247 Meas Guidance v05r02, April 2, 2019

Section 8.3.1.1 RBW $\geq$ DTS bandwidth

Subclause 11.9.1.1 of ANSI C63.10 is applicable.

Section 8.3.1.2 Integrated band power method

For measuring the output power of a device transmitting a wide-band noise-like signal where the peak power amplitude is a statistical parameter, the preferred methodology is to use an integrated average power measurement, as described in 8.3.2. The peak integrated band power method of 11.9.1 in ANSI C63.10 is not applicable.

Subclause 11.9.2 of ANSI C63.10 is applicable.

13.2 Test Result

ANT 0:

Operation mode	Channel Frequency (MHz)	Measurements (dBm)	Duty Cycle Factor (dB)	Conducted Output Power (dBm)
TX 11b	Low-2412	18.77	0.12	18.89
	Middle-2437	18.94		19.06
	High-2462	19.75		19.87
TX 11g	Low-2412	17.71	0.25	17.96
	Middle-2437	17.79		18.04
	High-2462	18.99		19.24
TX 11n HT20	Low-2412	17.7	0.30	18.00
	Middle-2437	17.8		18.10
	High-2462	18.53		18.83
TX 11n HT40	Low-2422	16.51	0.53	17.04
	Middle-2437	16.3		16.83
	High-2452	16.59		17.12

ANT 1:

Operation mode	Channel Frequency (MHz)	Measurements (dBm)	Duty Cycle Factor (dB)	Conducted Output Power (dBm)
TX 11b	Low-2412	19.07	0.12	19.19
	Middle-2437	19.37		19.49
	High-2462	19.35		19.47
TX 11g	Low-2412	17.8	0.27	18.07
	Middle-2437	17.79		18.06
	High-2462	17.96		18.23
TX 11n HT20	Low-2412	17.42	0.25	17.67
	Middle-2437	17.68		17.93
	High-2462	17.77		18.02
TX 11n HT40	Low-2422	16.57	0.54	17.11
	Middle-2437	16.5		17.04
	High-2452	16.53		17.07

Operation mode	Channel Frequency (MHz)	Maximum Conducted Output Power (dBm)			Limit ¹
		ANT0	ANT1	SUM	
TX 11n HT20	Low-2412	18.00	17.67	20.85	30dBm
	Middle-2437	18.10	17.93	21.03	
	High-2462	18.83	18.02	21.45	
TX 11n HT40	Low-2422	17.04	17.11	20.09	
	Middle-2437	16.83	17.04	19.95	
	High-2452	17.12	17.07	20.11	

Note:

Antenna 0 gain:2.12dBi

Antenna 1 gain:2.75dBi

For power measurements on IEEE 802.11 devices, Array gain=0 dB for Nant≤4

Directional gain= Gant + Array gain=2.75+0=2.75dBi



The max Directional gain is 2.75dBi that not greater than 6dBi, Limit of power (SUM) is **30.00dBm**.

Test Plot:

ANT 0:

Mode: TX 11b channel 1


Mode: TX 11b channel 6



Date: 24.OCT.2024 14:25:42


Date: 24.OCT.2024 14:35:47

Mode: TX 11b channel 11




Date: 24.OCT.2024 14:50:44

Mode: TX 11g channel 1




Date: 24.OCT.2024 15:26:13

Mode: TX 11g channel 6




Date: 24.OCT.2024 15:25:50

Mode: TX 11g channel 11




Date: 24.OCT.2024 15:25:24

Mode: TX 11n HT20 channel 1




Date: 24.OCT.2024 15:26:53

Mode: TX 11n HT20 channel 6




Date: 24.OCT.2024 15:27:48

Mode: TX 11n HT20 channel 11




Date: 24.OCT.2024 15:28:21

Mode: TX 11n HT40 channel 3




Date: 24.OCT.2024 15:30:21

Mode: TX 11n HT40 channel 6



Date: 24.OCT.2024 15:29:41


Mode: TX 11n HT40 channel 9



Date: 24.OCT.2024 15:29:12


ANT 1:

Mode: TX 11b channel 1




Date: 24.OCT.2024 17:13:30

Mode: TX 11b channel 6




Date: 24.OCT.2024 17:14:59

Mode: TX 11b channel 11




Date: 24.OCT.2024 16:55:24

Mode: TX 11g channel 1




Date: 24.OCT.2024 17:08:11

Mode: TX 11g channel 6




Date: 24.OCT.2024 17:08:37

Mode: TX 11g channel 11




Date: 24.OCT.2024 17:10:05

Mode: TX 11n HT20 channel 1




Date: 24.OCT.2024 17:11:23

Mode: TX 11n HT20 channel 6




Date: 24.OCT.2024 17:11:00

Mode: TX 11n HT20 channel 11




Date: 24.OCT.2024 17:10:38

Mode: TX 11n HT40 channel 3




Date: 24.OCT.2024 17:11:53

Mode: TX 11n HT40 channel 6



Date: 24.OCT.2024 17:12:14

Mode: TX 11n HT40 channel 9



Date: 24.OCT.2024 17:12:36

14 Power Spectral density

Test Requirement:	47CFR FCC Part15 Subpart C §15.247
Test Method:	ANSI C63.10:2013 KDB 558074 D01 15.247 Meas Guidance v05r02, April 2, 2019 KDB 662911 D01 Multiple Transmitter Output v02r01, October 31, 2013
Test Limit:	§15.247(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.
Test Mode:	Transmitting

14.1 Test Procedure

According to KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019 section 8.4

Subclause 11.10 of ANSI C63.10 is applicable.

Choose the test procedure according to the product type

Peak PSD

Subclause 11.10.2 of ANSI C63.10 is applicable.

AVG PSD

Subclause 11.10.3/4/5/6/7/8 of ANSI C63.10 is applicable.

14.2 Test Result

ANT 0:

Operation mode	Channel Frequency (MHz)	Measurements (dBm per 3kHz)	Duty Cycle Factor (dB)	Power Spectral density (dBm per 3kHz)
TX 11b	Low-2412	-12.35	0.12	-12.23
	Middle-2437	-13.04		-12.92
	High-2462	-11.96		-11.84
TX 11g	Low-2412	-17.53	0.25	-17.28
	Middle-2437	-17.26		-17.01
	High-2462	-16.33		-16.08
TX 11n HT20	Low-2412	-18.17	0.30	-17.87
	Middle-2437	-17.61		-17.31
	High-2462	-17.24		-16.94
TX 11n HT40	Low-2422	-23.07	0.53	-22.54
	Middle-2437	-23.29		-22.76
	High-2452	-23.04		-22.51

ANT 1:

Operation mode	Channel Frequency (MHz)	Measurements (dBm per 3kHz)	Duty Cycle Factor (dB)	Power Spectral density (dBm per 3kHz)
TX 11b	Low-2412	-12.83	0.12	-12.71
	Middle-2437	-12.93		-12.81
	High-2462	-12.79		-12.67
TX 11g	Low-2412	-17.89	0.27	-17.62
	Middle-2437	-18.05		-17.78
	High-2462	-17.56		-17.29
TX 11n HT20	Low-2412	-17.98	0.25	-17.73
	Middle-2437	-18.4		-18.15
	High-2462	-18.09		-17.84
TX 11n HT40	Low-2422	-22.79	0.54	-22.25
	Middle-2437	-22.7		-22.16
	High-2452	-22.32		-21.78

Operation mode	Channel Frequency (MHz)	Power Spectral density (dBm)			Limit ¹
		ANT0	ANT1	SUM	
TX 11n HT20	Low-2412	-17.87	-17.73	-14.79	8.00dBm per 3kHz
	Middle-2437	-17.31	-18.15	-14.70	
	High-2462	-16.94	-17.84	-14.36	
TX 11n HT40	Low-2422	-22.54	-22.25	-19.38	
	Middle-2437	-22.76	-22.16	-19.44	
	High-2452	-22.51	-21.78	-19.12	

Note:

Antenna 0 gain:2.12dBi

Antenna 1 gain:2.75dBi

Directional gain= $2.75+10\log(2/1)=5.76\text{dBi}$


The max Directional gain is 5.76dBi that not greater than 6dBi, Limit of Power Spectral density (SUM) is 8.00dBm per 3kHz

Test Plot:


ANT 0:

Mode: TX 11b channel 1

Mode: TX 11b channel 6




Date: 24.OCT.2024 14:23:58




Date: 24.OCT.2024 14:36:36

Mode: TX 11b channel 11




Date: 24.OCT.2024 14:51:15

Mode: TX 11g channel 1




Date: 24.OCT.2024 12:05:42

Mode: TX 11g channel 6




Date: 24.OCT.2024 12:04:53

Mode: TX 11g channel 11




Date: 24.OCT.2024 12:02:49

Mode: TX 11n HT20 channel 1




Date: 24.OCT.2024 12:00:15

Mode: TX 11n HT20 channel 6




Date: 24.OCT.2024 12:00:52

Mode: TX 11n HT20 channel 11




Date: 24.OCT.2024 12:01:42

Mode: TX 11n HT40 channel 3




Date: 24.OCT.2024 11:59:42

Mode: TX 11n HT40 channel 6



Date: 24.OCT.2024 11:59:11


Mode: TX 11n HT40 channel 9



Date: 24.OCT.2024 11:58:36


ANT 1:

Mode: TX 11b channel 1




Date: 24.OCT.2024 16:42:16

Mode: TX 11b channel 6




Date: 24.OCT.2024 16:49:48

Mode: TX 11b channel 11




Date: 24.OCT.2024 16:55:00

Mode: TX 11g channel 1




Date: 24.OCT.2024 16:11:42

Mode: TX 11g channel 6




Date: 24.OCT.2024 16:12:24

Mode: TX 11g channel 11




Date: 24.OCT.2024 16:13:09

Mode: TX 11n HT20 channel 1




Date: 24.OCT.2024 16:14:56

Mode: TX 11n HT20 channel 6




Date: 24.OCT.2024 16:14:16

Mode: TX 11n HT20 channel 11




Date: 24.OCT.2024 16:13:42

Mode: TX 11n HT40 channel 3




Date: 24.OCT.2024 16:15:37

Mode: TX 11n HT40 channel 6



Date: 24.OCT.2024 16:16:13

Mode: TX 11n HT40 channel 9



Date: 24.OCT.2024 16:16:58

15 Antenna Requirement

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. This product have two antennas, ANT 0: Steel Plate Antenna, ANT 1: Copper Tube Antenna fulfil the requirement of this section.

Note: Please refer to EUT photos for more details.

16 RF Exposure

Note: Please refer to RF Exposure Report: WTF24D10230966W003.

17 Photographs of test setup and EUT.

Note: Please refer to appendix: Appendix- Appendix-BM04-Photos.

=====End of Report=====