

Test Report

Product: 3-in-1 Wireless Charging Station

Trade Mark: N/A

Model Number: T26

FCC ID: 2BGF3-T26

Prepared for

Shenzhen Tengsay Technology Co., Ltd
Room 203, Building A, No. 12, 1st Road, Xiawei Industrial Zone, Zhangxi
Community, Guanhu Street, Longhua District, Shenzhen Province

Prepared by

Shenzhen HongBiao Certification& Testing Co., Ltd
Room 102, 201, Building 2, Yuanwanggu RFID Industrial Park, Tongguan
Road, Tianliao Community, Yutang Street, Guangming District, Shenzhen,
China
Tel.: +86-755-2998 9321 Fax.: +86-755-2998 5110
Website: <http://www.sz-hongbiao.com>

Table of Contents

1 GENERAL DESCRIPTION 5

1.1 DESCRIPTION OF EUT 5

1.2 TEST MODE..... 5

1.3 TEST SETUP 6

1.4 ANCILLARY EQUIPMENT 6

2 SUMMARY OF TEST RESULT 7

3 TEST FACILITIES AND ACCREDITATIONS 8

3.1 TEST LABORATORY 8

3.2 ENVIRONMENTAL CONDITIONS 8

3.3 MEASUREMENT UNCERTAINTY 8

3.4 TEST SOFTWARE 8

4 LIST OF TEST EQUIPMENT 9

5 TEST ITEM AND RESULTS.....11

5.1 ANTENNA REQUIREMENT 11

5.2 CONDUCTED EMISSION..... 12

5.3 RADIATED EMISSION 16

5.4 OCCUPIED BANDWIDTH 21

6 PHOTOGRAPHS OF THE TEST SETUP.....23

7 PHOTOGRAPHS OF THE EUT.....25

TEST RESULT CERTIFICATION

Applicant's Name..... : Shenzhen Tengsay Technology Co., Ltd
Room 203, Building A, No. 12, 1st Road, Xiawei Industrial Zone,
Address : Zhangxi Community, Guanhu Street, Longhua District,
Shenzhen Province
Manufacturer's Name : Shenzhen Tengsay Technology Co., Ltd
Room 203, Building A, No. 12, 1st Road, Xiawei Industrial Zone,
Address : Zhangxi Community, Guanhu Street, Longhua District,
Shenzhen Province

Product description

Product name : 3-in-1 Wireless Charging Station
Model Number : T26
Standards : FCC Part 15C
Test procedure..... : IEEE/ANSI C63.10-2020

This device described above has been tested by Shenzhen HongBiao Certification& Testing Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the EMC requirements. And it is applicable only to the tested sample identified in the report.

Date of Test..... :

Date (s) of performance of tests..... : May 22, 2024~ May 28, 2024

Test Result..... : **Pass**

Testing Engineer :

Zoe Su

(Z o e S u)

Technical Manager :

Mark Chen

(Mark Chen)

Authorized Signatory :

Leo Su

(L e o S u)

[illegible]

1 General Description

1.1 Description of EUT

Product name:	3-in-1 Wireless Charging Station
Model name:	T26
Series Model:	G22, G23, G24
Different of series model:	Except for the model and housing color, all models have the same circuit and module.
Operation frequency:	Watch: 325kHz Phone: 115kHz~205kHz TWS: 115kHz~205kHz
Operational mode:	Wireless charging
Modulation type:	ASK
Antenna type:	Coil Antenna
Hardware version:	V1.0
Software version:	V1.0
Battery:	N/A
Power supply:	Input: DC 9V/2A Wireless Output: For Phone 15W Max Wireless Output: For iPhone 7.5W Max Wireless Output: For TWS 5W Max Wireless Output: For Watch 3W Max
Adapter information:	N/A

1.2 Test Mode

Pretest Test Mode	Description of Mode
1	Wireless Output (Phone: 5W+TWS: 5W+Watch: 3W)
2	Wireless Output (Phone: 7.5W+TWS: 5W+Watch: 3W)
3	Wireless Output (Phone: 10W+TWS: 5W+Watch: 3W)
4	Wireless Output (Phone: 15W+TWS: 5W+Watch: 3W)

Test Item	Final Test Mode
Conducted Emissions	4
Radiated Emissions	4
20dB bandwidth	4

Note: All modes have been tested, and the report only reflects the test results of the worst mode (Final Test Mode).

1.3 Test Setup

See photographs of the test setup in the report for the actual setup and connections between EUT and support equipment.

1.4 Ancillary Equipment

Equipment	Model	S/N	Manufacturer
Adapter	TA65B	2S36003438 PL97T09582	Nanjing Bolande Electronic Technology Co., Ltd
Load	YBZ1.1	86631yp378- 220519	YBZ
Air Pods	A2031	H04F3NS0L X2Y	Apple Inc.
Watch	NYYK2CH/A	H4HFR0ZHQ 1N2	Apple Inc.

2 Summary of Test Result

Test procedures according to the technical standards:

FCC Part 15C				
No.	Standard Section	Test Item	Result	Remark
1	FCC Part 15.203	Antenna Requirement	Pass	
2	FCC Part 15.207	Conducted Emission	Pass	
3	FCC Part 15.209	Radiated Emission	Pass	
4	FCC Part 15.215	20dB Bandwidth	Pass	
Note: 1. "N/A" means the test case does not apply to the test object.				

3 Test Facilities and Accreditations

3.1 Test Laboratory

Test Site	Shenzhen HongBiao Certification& Testing Co., Ltd
Test Site Location	Room 102, 201, Building 2, Yuanwanggu RFID Industrial Park, Tongguan Road, Tianliao Community, Yutang Street, Guangming District, Shenzhen, China
Telephone:	(86-755) 2998 9321
Fax:	(86-755) 2998 5110
FCC Registration No.:	CN1341
A2LA Certificate No.:	6765.01

3.2 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15°C~35°C
Relative Humidity:	20%~75%
Air Pressure:	98kPa~101kPa

3.3 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

Measurement Frequency Range	U, (dB)	Note
RF frequency	2×10^{-5}	
RF power, conducted	± 0.57 dB	
Conducted emission(150kHz~30MHz)	± 2.5 dB	
Radiated emission(9kHz-30MHz)	± 2.5 dB	
Radiated emission(30MHz~1GHz)	± 4.2 dB	
Radiated emission (above 1GHz)	± 4.7 dB	
Occupied Bandwidth	$\pm 3\%$	
Temperature	± 1 degree	
Humidity	$\pm 5 \%$	

3.4 Test Software

Software name	Manufacturer	Model	Version
EMI Measurement	Farad	EZ-EMC	V1.1.4.2
Conducted test system	MWRF-test	MTS 8310	V2.0.0

4 List of Test Equipment

Radiation emission							
Item	Equipment No.	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	HB-E001	Horn Antenna	Schwarzbeck	BBHA 9120D	02592	2024-05-18	2026-05-17
2	HB-E002	Biconical log-periodic composite antenna	Schwarzbeck	VULB 9168	01340	2024-05-18	2026-05-17
3	HB-E003	SHF-EHF Horn	Schwarzbeck	BBHA 91270	01193	2024-05-18	2026-05-17
4	HB-E005	Preamplifier	Noyetec	LAN-01 18	NYCM1420 102	2024-05-17	2025-05-16
5	HB-E006	Preamplifier	Noyetec	LAN-18 40	NYCM1420 103	2024-05-17	2025-05-16
6	HB-E007	EMI TEST RECEIVER	R&S	ESR7	102520	2024-05-17	2025-05-16
7	HB-E009	POSITINAL COTROLLE R	Noyetec	N/A	N/A	/	/
8	HB-E013	RF switch	Noyetec	NY-RF4	NY0CM142 0204	/	/
9	HB-E066	Illuminance Tester	TASI	TA8121	N/A	2024-05-21	2025-05-20
10	HB-E075	Active loop antenna	Schwarzbeck	FMZB 1519B	1519B-245	2024-05-18	2026-05-17
11	HB-E076	Preamplifier	Hewlett Packard	8447D	1937A0227 8	2024-05-17	2025-05-16
Conduction emission							
Item	Equipment No.	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	HB-E014	4 Path V-LISN	Schwarzbeck	NNLK 8121	00770	2024-05-17	2025-05-16
2	HB-E015	Pulse Limiter	Schwarzbeck	VTSD 9561-F	00949	2024-05-17	2025-05-16
3	HB-E016	ZN23201	Noyetec	ZN23201	N/A	2024-05-21	2025-05-20
4	HB-E059	Attenuator	Xianghua	TS2-6-1	220215166	2024-05-17	2025-05-16
5	HB-E069	EMI TEST RECEIVER	R&S	ESCI	N/A	2024-05-17	2025-05-16
RF							
Item	Equipment No.	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	HB-E041	MXG Anaio Signal Generator	Agilent	N5181A	MY47070421	2024-05-17	2025-05-16
2	HB-E042	WIDEBAND RADIO COMMUNICA	R&S	CMW500	132108	2024-05-17	2025-05-16

		TION TESTER					
3	HB-E043	MXG Anaio Signal Generator	Agilent	N5182A	US46240335	2024-05-17	2025-05-16
4	HB-E044	Signal& spectrum Analyzer	R&S	FSV3044	101264	2024-05-17	2025-05-16
5	HB-E045	RF Control Box	Noyetec	NY100-R FCB	N/A	/	/
6	HB-E058	Thermometer Clock Humidity Monitor	N/A	HTC-1	N/A	/	/

Note: the calibration interval of the above test instruments is 12&24 months and the calibrations are traceable to international system unit (SI).

5 Test Item And Results

5.1 Antenna Requirement

5.1.1 Standard Requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device

5.1.2 Test Result

The EUT antenna is Coil Antenna. It comply with the standard requirement. In case of replacement of broken antenna the same antenna type must be used.

5.2 Conducted Emission


5.2.1 Limits

Limits – Class A		
Frequency (MHz)	Limit (dBμV)	
	Quasi-Peak	Average
0.15 to 0.5	79	66
0.5 to 30	73	60
Limits – Class B		
Frequency (MHz)	Limit (dBμV)	
	Quasi-Peak	Average
0.15 to 0.5	66 to 56*	56 to 46*
0.5 to 5	56	46
5 to 30	60	50
Note: 1. the tighter limit applies at the band edges. 2. the limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.		

5.2.2 Test Procedures


- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN is at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item – photographs of the test setup.

5.2.3 Test setup




5.2.4 Test Result

EUT:	3-in-1 Wireless Charging Station	Model Name:	T26
Test Mode:	Mode 4	Phase:	L
Test Voltage:	DC 9V from adapter AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.159000	41.50	10.13	51.63	65.52	-13.89	QP
2	0.159000	31.71	10.13	41.84	55.52	-13.68	AVG
3	3.070500	31.92	9.93	41.85	56.00	-14.15	QP
4 *	3.070500	28.95	9.93	38.88	46.00	-7.12	AVG
5	3.363000	31.84	9.91	41.75	56.00	-14.25	QP
6	3.363000	27.55	9.91	37.46	46.00	-8.54	AVG
7	9.356900	34.87	9.60	44.47	60.00	-15.53	QP
8	9.356900	30.98	9.60	40.58	50.00	-9.42	AVG
9	12.322500	35.66	9.51	45.17	60.00	-14.83	QP
10	12.322500	32.29	9.51	41.80	50.00	-8.20	AVG
11	13.204500	36.02	9.50	45.52	60.00	-14.48	QP
12	13.204500	31.98	9.50	41.48	50.00	-8.52	AVG



5.3 Radiated Emission

5.3.1 Limits

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

5.3.2 Test Procedures


- The radiated emission tests were performed in the 3 meters.
- The EUT was placed on the top of a rotating table 0.8 meters above the ground. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the test antenna shall vary between 1m to 4m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- If the peak mode measured value compliance with and lower than quasi peak mode limit, the EUT shall be deemed to meet QP limits and then no additional QP mode measurement performed.
- If the peak mode measured value compliance with and lower than average mode limit, the EUT shall be deemed to meet average limits and then no additional average mode measurement performed.
- For the actual test configuration, please refer to the related item – EUT test photos.

5.3.3 Test Setup

Radiated Emission Test-Up Frequency Below 30MHz




Radiated Emission Test-Up Frequency 30MHz~1GHz




5.3.4 Test Result


Frequency range (9kHz – 30MHz)



Frequency range (30MHz – 1GHz)



EUT:	3-in-1 Wireless Charging Station	Model Name:	T26
Test Mode:	Mode 4	Phase:	Horizontal
Test Voltage:	DC 9V from adapter AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 !	75.4462	54.65	-17.67	36.98	40.00	-3.02	QP
2 !	183.2005	56.11	-15.45	40.66	43.50	-2.84	QP
3 !	259.2336	57.67	-14.43	43.24	46.00	-2.76	QP
4 *	269.4282	57.74	-14.02	43.72	46.00	-2.28	QP
5 !	295.1467	56.88	-13.19	43.69	46.00	-2.31	QP
6 !	341.9786	52.91	-11.87	41.04	46.00	-4.96	QP

5.4 Occupied Bandwidth

5.4.1 Test method


Use the following spectrum analyzer settings:
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel
RBW $\geq 1\%$ of the 20 dB bandwidth
VBW $\geq$ RBW
Sweep = auto
Detector function = peak
Trace = max hold

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth and 99% occupied bandwidth of the emission.

5.4.2 Test result


Frequency (kHz)	20dB emission bandwidth (Hz)
149.65	769.20

Phone: Test plots as below:




Frequency (kHz)	20dB emission bandwidth (Hz)
325.65	804.20

Watch: Test plots as below:



Frequency (kHz)	20dB emission bandwidth (Hz)
150.25	764.20

TWS: Test plots as below:




6 Photographs of the Test Setup


Radiated Emission Below 30MHz



Radiated Emission Above 30MHz



Conducted Emission



7 Photographs of the EUT

Photo 1



Photo 2



Photo 3



Photo 4



Photo 5



Photo 6



Photo 7



Photo 8



Photo 9




Photo 10




Photo 11




Photo 12




Photo 13




Photo 14




Photo 15





Photo 16



***** END OF REPORT *****