


FCC PART 15.247 TEST REPORT

For

Shenzhen Huafurui Technology Co., Ltd

Unit 1401 14/F, Jin qi zhi gu mansion Liu xian street, Xili, Nan shan district, Shenzhen, China

FCC ID: 2AHZ5SW10

Report Type: Original Report	Product Type: Projector
Report Number: <u>SZ1210918-48944E-00A</u>	
Report Date: <u>2021-11-02</u>	
Candy Li 	
Reviewed By: <u>RF Engineer</u>	
Prepared By: Shenzhen Accurate Technology Co., Ltd. 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China Tel: (0755) 26503290 Fax: (0755) 26503396 Http://www.atc-lab.com	

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
SPECIAL ACCESSORIES	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL I/O CABLE	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	9
TEST EQUIPMENT LIST	10
FCC §1.1310 & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)	11
FCC §15.203 – ANTENNA REQUIREMENT	12
APPLICABLE STANDARD	12
ANTENNA CONNECTOR CONSTRUCTION	12
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	13
APPLICABLE STANDARD	13
EUT SETUP	13
EMI TEST RECEIVER SETUP	13
TEST PROCEDURE	13
TRANSD FACTOR & MARGIN CALCULATION	14
TEST DATA	14
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS	17
APPLICABLE STANDARD	17
EUT SETUP	17
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	18
TEST PROCEDURE	18
FACTOR & MARGIN CALCULATION	18
TEST DATA	18
FCC §15.247(a) (1)-CHANNEL SEPARATION TEST	23
APPLICABLE STANDARD	23
TEST PROCEDURE	23
TEST DATA	23
FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH & 99% OCCUPIED BANDWIDTH	26
APPLICABLE STANDARD	26
TEST PROCEDURE	26
TEST DATA	27
FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST	38
APPLICABLE STANDARD	38
TEST PROCEDURE	38
TEST DATA	38

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)	41
APPLICABLE STANDARD	41
TEST PROCEDURE	41
TEST DATA	41
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	51
APPLICABLE STANDARD	51
TEST PROCEDURE	51
TEST DATA	51
FCC §15.247(d) - BAND EDGES TESTING	57
APPLICABLE STANDARD	57
TEST PROCEDURE	57
TEST DATA	57

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	Projector
Tested Model	SW10
Frequency Range	Bluetooth: 2402~2480MHz
Maximum conducted Peak output power	Bluetooth: 8.98dBm
Modulation Technique	Bluetooth: GFSK, $\pi/4$ -DQPSK, 8DPSK
Antenna Specification*	Internal Antenna: -0.76dBi(provided by the applicant)
Voltage Range	AC 100-240V, 50-60Hz
Date of Test	2021-10-12 to 2021-10-31
Sample number	SZ1210918-48944E-RF-S1 (Assigned by ATC)
Received date	2021-09-18
Sample/EUT Status	Good condition

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		5%
RF output power, conducted		0.73dB
Unwanted Emission, conducted		1.6dB
AC Power Lines Conducted Emissions		2.72dB
Emissions, Radiated	30MHz - 1GHz	4.28dB
	1GHz - 18GHz	4.98dB
	18GHz - 26.5GHz	5.06dB
Temperature		1°C
Humidity		6%
Supply voltages		0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode.

EUT Exercise Software

“RTLBTAPP”* software was used during testing, the power level is 36*.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
GIEC	DVD	BDP-G4308	Unknown
HUAWEI	Earphone	Unknown	Unknown
Unknown	USB flash disk*2	Unknown	Unknown

External I/O Cable


Cable Description	Length (m)	From/Port	To
Un-Shielding Detachable AC power Cable	1.5	EUT	LISN
Un-Shielding Detachable AUX IN Cable 1	0.2	EUT	AUX IN Cable 2
Un-Shielding Detachable AUX IN Cable 2	1.0	AUX IN Cable 1	DVD
Un-Shielding Detachable Earphone Cable	0.75	EUT	Earphone
Un-Shielding Detachable HDMI Cable*2	1.45	EUT	DVD


Block Diagram of Test Setup

For conducted emission:



For radiated emission:
Below 1GHz:



Above 1GHz:

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (I), §1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207(a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209 & §15.247(d)	Radiated Emissions	Compliant
§15.247(a)(1)	20 dB Emission Bandwidth & 99% Occupied Bandwidth	Compliant
§15.247(a)(1)	Channel Separation Test	Compliant
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliant
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliant
§15.247(b)(1)	Peak Output Power Measurement	Compliant
§15.247(d)	Band edges	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde& Schwarz	Test Receiver	ESPI3	100396	2020/12/24	2021/12/23
R & S	L.I.S.N.	ENV216	101314	2020/12/25	2021/12/24
Anritsu Corp	50Ω Coaxial Switch	MP59B	6200506474	2020/12/25	2021/12/24
Unknown	RF Coaxial Cable	N-2m	No.2	2020/12/25	2021/12/24
Conducted Emission Test Software: e3 19821b(V9)					
Radiated Emissions Test					
Rohde&Schwarz	Test Receiver	ESR	101817	2020/12/24	2021/12/23
Rohde & Schwarz	Spectrum Analyzer	FSV-40	101495	2020/12/24	2021/12/23
A.H. Systems, inc.	Preamplifier	PAM-0118P	531	2021/07/08	2022/07/07
SONOMA INSTRUMENT	Amplifier	310 N	186131	2020/12/25	2021/12/24
Quinstar	Amplifier	QLW-184055 36-J0	15964001002	2020/11/28	2021/11/27
Anritsu Corp	50 Coaxial Switch	MP59B	6100237248	2020/12/25	2021/12/24
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2020/01/05	2023/01/04
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-1067	2020/01/05	2023/01/04
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2020/01/05	2023/01/04
Unknown	RF Coaxial Cable	N-5m	No.3	2020/12/25	2021/12/24
Unknown	RF Coaxial Cable	N-5m	No.4	2020/12/25	2021/12/24
Unknown	RF Coaxial Cable	N-1m	No.5	2020/12/25	2021/12/24
Unknown	RF Coaxial Cable	N-1m	No.6	2020/12/25	2021/12/24
Radiated Emission Test Software: EZ EMC V 1.1.4.2 & e3 19821b(V9)					
RF Conducted Test					
Rohde&Schwarz	Spectrum Analyzer	FSV40	101495	2020/12/24	2021/12/23
Rohde & Schwarz	Open Switch and Control Unit	OSP120 +OSP -B157	101244 + 100866	2020/12/24	2021/12/23
OREGON SCIENTIFIC	Temperature & Humidity Meter	JB913R	GZ-WS004	2020/01/02	2023/01/01

*** Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1310 & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart §2.1091 and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

For worst case:

Mode	Frequency Range (MHz)	Antenna Gain		Tune-up Output Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
BT	2402-2480	-0.76	0.84	9.0	7.94	20	0.0013	1.0

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant.

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one internal antenna arrangement for Bluetooth, which was permanently attached and the antenna gain is -0.76dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the device was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Transd Factor & Margin Calculation

The Transd factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correct Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Result} - \text{Limit} \\ \text{Result} &= \text{Reading} + \text{Correct Factor}\end{aligned}$$


Test Data

Environmental Conditions


Temperature:	23 °C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa

The testing was performed by Fan Yang on 2021-10-29.

EUT operation mode: BT Transmitting (the worst case is GFSK Mode, Middle channel)

AC 120V/60 Hz, Line

No.	Frequency	Reading	Correct	Result	Limit	Over Limit	Remark	Phase
	(MHz)	(dBuV)	Factor(dB)	(dBuV)	(dBuV)	(dB)		
1	0.193	19.5	9.81	29.31	53.92	-24.61	Average	Line
2	0.193	27.35	9.81	37.16	63.92	-26.76	QP	Line
3	0.259	18.34	9.8	28.14	51.48	-23.34	Average	Line
4	0.259	25.24	9.8	35.04	61.48	-26.44	QP	Line
5	0.313	12.25	9.8	22.05	49.89	-27.84	Average	Line
6	0.313	18.4	9.8	28.2	59.89	-31.69	QP	Line
7	1.951	5.72	9.92	15.64	46	-30.36	Average	Line
8	1.951	15.02	9.92	24.94	56	-31.06	QP	Line
9	4.952	16.86	9.99	26.85	46	-19.15	Average	Line
10	4.952	21.83	9.99	31.82	56	-24.18	QP	Line
11	14.996	19.11	10.05	29.16	50	-20.84	Average	Line
12	14.996	24.41	10.05	34.46	60	-25.54	QP	Line

AC 120V/60 Hz, Neutral

No.	Frequency	Reading	Correct	Result	Limit	Over Limit	Remark	Phase
	(MHz)	(dBuV)	Factor(dB)	(dBuV)	(dBuV)	(dB)		
1	0.159	12.66	9.92	22.58	55.53	-32.95	Average	Neutral
2	0.159	26.72	9.92	36.64	65.53	-28.89	QP	Neutral
3	0.247	22.8	9.98	32.78	51.86	-19.08	Average	Neutral
4	0.247	28.79	9.98	38.77	61.86	-23.09	QP	Neutral
5	0.309	15.01	9.96	24.97	49.99	-25.02	Average	Neutral
6	0.309	22.29	9.96	32.25	59.99	-27.74	QP	Neutral
7	0.553	7.85	9.91	17.76	46	-28.24	Average	Neutral
8	0.553	15.74	9.91	25.65	56	-30.35	QP	Neutral
9	4.952	12.91	10.05	22.96	46	-23.04	Average	Neutral
10	4.952	17.74	10.05	27.79	56	-28.21	QP	Neutral
11	15.635	23.21	10.07	33.28	50	-16.72	Average	Neutral
12	15.635	27.3	10.07	37.37	60	-22.63	QP	Neutral


FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS

Applicable Standard


FCC §15.205; §15.209; §15.247(d)

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	PK
	1 MHz	10 Hz	/	Average

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Factor & Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\begin{aligned} \text{Margin} &= \text{Result} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Result} / \text{Corrected Amplitude} &= \text{Reading} + \text{Factor} \end{aligned}$$

Test Data


Environmental Conditions

Temperature:	23-25 °C
Relative Humidity:	48-52 %
ATM Pressure:	101.0 kPa


The testing was performed by Fan Yang on 2021-10-31 for below 1GHz and 2021-10-13 for above 1GHz.

EUT operation mode: Transmitting

(Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK mode, the worst case is GFSK Mode)

30MHz-1GHz:**Horizontal:**

No.	Frequency	Reading	Correct	Result	Limit	Over	Detector	Phase
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)		
1	30.000	42.32	-20.55	21.77	40.00	-18.23	QP	HORIZONTAL
2	97.798	53.76	-19.62	34.14	43.50	-9.36	QP	HORIZONTAL
3	147.404	58.34	-21.68	36.66	43.50	-6.84	QP	HORIZONTAL
4	297.224	53.81	-16.75	37.06	46.00	-8.94	QP	HORIZONTAL
5	537.589	53.40	-13.15	40.25	46.00	-5.75	QP	HORIZONTAL
6	1000.000	40.14	-7.34	32.80	54.00	-21.20	QP	HORIZONTAL

Vertical

No.	Frequency	Reading	Correct	Result	Limit	Over	Detector	Phase
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)		
1	33.799	52.02	-19.71	32.31	40.00	-7.69	QP	VERTICAL
2	54.452	55.49	-18.25	37.24	40.00	-2.76	QP	VERTICAL
3	101.644	54.65	-19.17	35.48	43.50	-8.02	QP	VERTICAL
4	297.224	47.00	-16.75	30.25	46.00	-15.75	QP	VERTICAL
5	537.589	50.12	-13.15	36.97	46.00	-9.03	QP	VERTICAL
6	1000.000	40.70	-7.34	33.36	54.00	-20.64	QP	VERTICAL

Above 1GHz:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2402 MHz)									
2310	45.98	PK	214	1.6	H	-6.84	39.14	74	-34.86
2310	44.27	PK	266	1.4	V	-6.84	37.43	74	-36.57
2390	46.92	PK	167	1.3	H	-6.44	40.48	74	-33.52
2390	46.17	PK	86	1.2	V	-6.44	39.73	74	-34.27
4804	38.65	PK	210	1.4	H	2.81	41.46	74	-32.54
4804	39.91	PK	234	1.7	V	2.81	42.72	74	-31.28
Middle Channel (2441 MHz)									
4882	38.07	PK	232	2.1	H	3.04	41.11	74	-32.89
4882	39.26	PK	285	1.6	V	3.04	42.3	74	-31.7
High Channel (2480 MHz)									
2483.5	44.32	PK	164	2.2	H	-5.96	38.36	74	-35.64
2483.5	42.9	PK	321	1.5	V	-5.96	36.94	74	-37.06
2500	46	PK	289	1	H	-5.88	40.12	74	-33.88
2500	45.51	PK	292	1.2	V	-5.88	39.63	74	-34.37
4960	37.77	PK	134	1.6	H	3.29	41.06	74	-32.94
4960	39.18	PK	171	1.1	V	3.29	42.47	74	-31.53

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading

Margin = Corrected Amplitude – Limit

The other spurious emission which is in the noise floor level was not recorded.


The test result of peak was less than the limit of average, so just peak value were recorded.

1-18GHz


Pre-scan for Peak

Low Channel

Horizontal:



Vertical:




18-25GHz


Pre-scan for Peak

Low Channel

Horizontal:



Vertical:



FCC §15.247(a) (1)-CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Test Procedure

1. Set the EUT in transmitting mode, maxhold the channel.
2. Set the adjacent channel of the EUT and maxhold another trace.
3. Measure the channel separation.

Test Data

Environmental Conditions

Temperature:	24 °C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa

The testing was performed by Fan Yang on 2021-10-12.


EUT operation mode: Transmitting

Test Result: Compliant.

Test Mode	Antenna	Channel	Result[MHz]	Limit[MHz]	Verdict
DH1	Ant1	Hop	1	≥ 0.640	PASS
2DH1	Ant1	Hop	1.0014	≥ 0.910	PASS
3DH1	Ant1	Hop	1	≥ 0.900	PASS


Please refer to the below plots:

DH1_Ant1_Hop




Date: 12.OCT.2021 10:38:25

2DH1_Ant1_Hop



Date: 12.OCT.2021 10:45:02

3DH1_Ant1_Hop



Date: 12.OCT.2021 10:21:57

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH & 99% OCCUPIED BANDWIDTH

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.


Test Procedure

The following conditions shall be observed for measuring the occupied bandwidth and 20 dB bandwidth:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- The detector of the spectrum analyzer shall be set to “Sample”. However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or “Max Hold”) may be necessary to determine the occupied / 20 dB bandwidth if the device is not transmitting continuously.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / 20 dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).



Test Data**Environmental Conditions**

Temperature:	24 °C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa

The testing was performed by Fan Yang on 2021-10-12.

EUT operation mode: Transmitting

Test Result: Compliant.


Test Mode	Antenna	Channel[MHz]	20db EBW[MHz]	Limit[MHz]	Verdict
DH1	Ant1	2402	0.960	---	PASS
		2441	0.960	---	PASS
		2480	0.960	---	PASS
2DH1	Ant1	2402	1.365	---	PASS
		2441	1.365	---	PASS
		2480	1.365	---	PASS
3DH1	Ant1	2402	1.347	---	PASS
		2441	1.347	---	PASS
		2480	1.350	---	PASS

Test Mode	Antenna	Channel[MHz]	99% Occupied Bandwidth [MHz]	Limit[MHz]	Verdict
DH1	Ant1	2402	0.893	---	PASS
		2441	0.893	---	PASS
		2480	0.899	---	PASS
2DH1	Ant1	2402	1.193	---	PASS
		2441	1.193	---	PASS
		2480	1.193	---	PASS
3DH1	Ant1	2402	1.196	---	PASS
		2441	1.196	---	PASS
		2480	1.199	---	PASS

Please refer to the below plots:


20 dB EMISSION BANDWIDTH

DH1_Ant1_2402MHz




Date: 12.OCT.2021 17:42:29

DH1_Ant1_2441MHz




Date: 12.OCT.2021 17:43:47

DH1_Ant1_2480MHz




Date: 12.OCT.2021 10:54:55

2DH1_Ant1_2402MHz




Date: 12.OCT.2021 17:46:05

2DH1_Ant1_2441MHz




Date: 12.OCT.2021 17:49:40

2DH1_Ant1_2480MHz




Date: 12.OCT.2021 17:50:49

3DH1_Ant1_2402MHz




Date: 12.OCT.2021 17:52:38

3DH1_Ant1_2441MHz




Date: 12.OCT.2021 17:54:08


3DH1_Ant1_2480MHz



Date: 12.OCT.2021 17:54:08


99% OCCUPIED BANDWIDTH**DH1_Ant1_2402MHz**

Date: 12.OCT.2021 17:42:50

DH1_Ant1_2441MHz


Date: 12.OCT.2021 17:44:04

DH1_Ant1_2480MHz




Date: 12.OCT.2021 18:37:23

2DH1_Ant1_2402MHz




Date: 12.OCT.2021 17:46:31

2DH1_Ant1_2441MHz




Date: 12.OCT.2021 17:50:04

2DH1_Ant1_2480MHz




Date: 12.OCT.2021 17:51:09

3DH1_Ant1_2402MHz




Date: 12.OCT.2021 17:53:02

3DH1_Ant1_2441MHz



Date: 12.OCT.2021 17:54:31

3DH1_Ant1_2480MHz



Date: 12.OCT.2021 17:56:28

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST**Applicable Standard**

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the max-hold function record the quantity of the channel.

Test Data**Environmental Conditions**

Temperature:	24 °C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa


The testing was performed by Fan Yang on 2021-10-12.

EUT operation mode: Transmitting


Test Result: Compliant.

TestMode	Antenna	Channel	Result[Num]	Limit[Num]	Verdict
DH1	Ant1	Hop	79	≥ 15	PASS
2DH1	Ant1	Hop	79	≥ 15	PASS
3DH1	Ant1	Hop	79	≥ 15	PASS


DH1_Ant1_Hop



2DH1_Ant1_Hop



3DH1_Ant1_Hop



Date: 12.OCT.2021 18:41:22

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWEELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. The EUT was worked in channel hopping.
2. Set the RBW to: 1MHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Set the span to 0Hz.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Recorded the time of single pulses

Test Data

Environmental Conditions

Temperature:	24 °C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa


The testing was performed by Fan Yang on 2021-10-12.

EUT operation mode: Transmitting


Test Result: Compliant.

Test Mode	Antenna	Channel	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Ant1	Hop	0.38	330	0.125	≤ 0.4	PASS
DH3	Ant1	Hop	1.63	140	0.228	≤ 0.4	PASS
DH5	Ant1	Hop	2.87	100	0.287	≤ 0.4	PASS
2DH1	Ant1	Hop	0.39	330	0.128	≤ 0.4	PASS
2DH3	Ant1	Hop	1.64	160	0.262	≤ 0.4	PASS
2DH5	Ant1	Hop	2.87	110	0.316	≤ 0.4	PASS
3DH1	Ant1	Hop	0.39	330	0.127	≤ 0.4	PASS
3DH3	Ant1	Hop	1.63	170	0.277	≤ 0.4	PASS
3DH5	Ant1	Hop	2.88	90	0.259	≤ 0.4	PASS

DH1_Ant1_Hop




Date: 12.OCT.2021 18:55:23




Date: 12.OCT.2021 18:55:28

DH3_Ant1_Hop




Date: 12.OCT.2021 18:08:48




Date: 12.OCT.2021 18:08:54

DH5_Ant1_Hop




Date: 12.OCT.2021 18:09:30




Date: 12.OCT.2021 18:09:36

2DH1_Ant1_Hop





Date: 12.OCT.2021 19:00:37




Date: 12.OCT.2021 19:00:42


2DH3_Ant1_Hop



2DH5_Ant1_Hop




Date: 12.OCT.2021 18:14:44




Date: 12.OCT.2021 18:14:50

3DH1_Ant1_Hop




Date: 12.OCT.2021 18:23:34




Date: 12.OCT.2021 18:23:39

3DH3_Ant1_Hop




Date: 12.OCT.2021 18:56:29




Date: 12.OCT.2021 18:56:34

3DH5_Ant1_Hop



Date: 12.OCT.2021 18:41:55



Date: 12.OCT.2021 18:42:00

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

Test Data

Environmental Conditions

Temperature:	24 °C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa


The testing was performed by Fan Yang on 2021-10-12

EUT operation mode: Transmitting

Test Result: Compliant.


TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
DH1	Ant1	2402	8.98	<=20.97	PASS
		2441	8.15	<=20.97	PASS
		2480	8.67	<=20.97	PASS
2DH1	Ant1	2402	7.43	<=20.97	PASS
		2441	6.88	<=20.97	PASS
		2480	6.85	<=20.97	PASS
3DH1	Ant1	2402	8.02	<=20.97	PASS
		2441	7.48	<=20.97	PASS
		2480	7.95	<=20.97	PASS

DH1_Ant1_2402




Date: 12.OCT.2021 17:36:50

DH1_Ant1_2441




Date: 12.OCT.2021 17:37:24

DH1_Ant1_2480




Date: 12.OCT.2021 17:37:47

2DH1_Ant1_2402




Date: 12.OCT.2021 17:38:14

2DH1_Ant1_2441




Date: 12.OCT.2021 17:38:48

2DH1_Ant1_2480




Date: 12.OCT.2021 17:39:06

3DH1_Ant1_2402




Date: 12.OCT.2021 17:39:31

3DH1_Ant1_2441



Date: 12.OCT.2021 17:39:53

3DH1_Ant1_2480



Date: 12.OCT.2021 17:40:15

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data


Environmental Conditions

Temperature:	24°C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa


The testing was performed by Fan Yang on 2021-10-12.

EUT operation mode: Transmitting

Test Result: Compliant.


Conducted Band Edge Result:**DH1_Ant1_Low_2402MHz**

Date: 12.OCT.2021 17:43:05

DH1_Ant1_High_2480MHz


Date: 12.OCT.2021 18:37:39

DH1_Ant1_Low_Hop_2402MHz




Date: 12.OCT.2021 18:05:55

DH1_Ant1_High_Hop_2480MHz




Date: 12.OCT.2021 18:10:03


2DH1_Ant1_Low_2402MHz



2DH1_Ant1_High_2480MHz




2DH1_Ant1_Low_Hop_2402MHz




Date: 12.OCT.2021 18:10:34

2DH1_Ant1_High_Hop_2480MHz




Date: 12.OCT.2021 18:17:14

3DH1_Ant1_Low_2402MHz




Date: 12.OCT.2021 17:53:17

3DH1_Ant1_High_2480MHz




Date: 12.OCT.2021 17:56:43

3DH1_Ant1_Low_Hop_2402MHz



Date: 12.OCT.2021 18:16:33

3DH1_Ant1_High_Hop_2480MHz



Date: 12.OCT.2021 18:25:47

***** END OF REPORT *****